

79-#318-#7427
REPORT ON DIAMOND DRILLING SUBMITTED
FOR ASSESSMENT WORK ON THE
COVE GROUP
OF MINERAL CLAIMS

Nanaimo M.D. Aug. 1979
Utah Mines Ltd. J. Lamb P. Eng.



UTAH MINES LTD.
ISLAND COPPER MINE
P.O. BOX 370
PORT HARDY, B.C. V0N 2P0
TELEPHONE (604) 949-6326

August 31, 1979

Ministry of Energy, Mines &
Petroleum Resources
Douglas Building
Victoria, B.C.
V8V 1X4

Sirs:

Assessment Report - Cove Group of Mineral Claims

The above report, in duplicate, is being submitted in compliance with regulations governing assessment work under the Mineral Act, revised to January 1, 1978.

Credit is requested for diamond drilling performed between July 4th and 23rd, 1979, on the Cove No. 17 M.C. (#18120).


Yours truly,



John Lamb, P. Eng.
Project Geologist

JL/ns

enc.



UTAH MINES LTD.

ISLAND COPPER MINE

P.O. BOX 370

PORT HARDY, B.C. V0N 2P0

TELEPHONE (604) 949-6326

Work Performed

1. Two holes were diamond drilled between July 4th and 23rd, 1979. The holes are on local logging roads approximately 1500 feet northwest of Frances Lake, about one mile north of Rupert Inlet. They lie close to and east of Utah's paved access road to the mine and are just west of the boundary of L. 2145, which demises Mineral Lease M-34. Both holes were drilled on Cove No. 17 mineral claim (#18120).

2. Particulars of the holes are:

Number	Inclination (degrees)	Length (ft)	Collar Elevation	Co-ordinates
E-41	-90	755	198	N 11116.12 E 17757.76
E-42	-90	698	295	N 12164.0 E 17868.6

The co-ordinate positions of the hole collars belong to the co-ordinate grid used over the whole Island Copper property.

3. All drill core is in storage at the Island Copper mine. Logs of the holes are included in the report.
4. Core logging was performed by:
John Lamb, P. Eng.
BASc, MASc - University of British Columbia
This person is on the geological staff at the Island Copper mine.
5. An itemized cost statement is included in the report.
6. A copy of the diamond drilling proposal is included. This proposal is from Thirty Two Albert Crescent Ltd., a member company of the Tonto Drilling Ltd. organization. Together with my letter of acceptance, it forms the agreement under which the work was done.
7. Both an index map and a detailed claim map are attached to this report, showing the drill hole locations and the extent of the Cove group of claims.


John Lamb, P. Eng.
Project Geologist

JL/ns

enc.

Statement of Costs
For the
Cove Group of Mineral Claims

A. Contractor's Charges:

Overburden

E-41 - 19 ft. @ \$14.25	\$ 270.75
E-42 - 90 ft. @ \$14.25	1,282.50

Rock

E-41 - 736 ft. @ \$14.25	10,488.20
E-42 - 608 ft. @ \$14.25	8,664.00

Field Costs (reaming, setting casing,
conditioning, etc.)

E-41 -	2,043.50
E-42 -	1,745.75

Extra Charges (materials consumed)

E-41	3,851.32
E-42	1,829.29
Mud circulation products at 9.5% of total mud costs	1,894.68
Mobilization costs at 9.5% of total mobilization	364.80
Hard ground charge at 20% of total footage drilled	1,740.00

B. Utah Costs:

- Sampling and assaying 114 at \$3.07 per assay	349.98
- Core house labor	1,500.00
- Geological supervision	1,600.00
- Company overhead cost	775.00
- Core boxes 54 at \$3.95 each	213.20
- Room and board 4 men for 19 days at 15.72/day	1,194.72
- Tractor for towing drills and preparing drill sites - 16 hours at \$50/hour	800.00
- Preparation of report	400.00
- Survey of holes	200.00
- Vehicle operation - @ 30¢/mi. for 100 miles	<u>30.00</u>
TOTAL COST:	\$41,237.69

Footage Drilled = 1453 ∴ cost per foot = \$28.38

J. Lamb
J. Lamb

JL/ns

April 30th, 1979.

Mr. C. Croft,
Tonto Drilling Limited,
1215 W. 7th Avenue,
Vancouver, B.C.
V6H 1B7.

Dear Chuck,

This is to advise you that your bid for this summer's diamond drilling at Island Copper has been accepted with the following proviso's which you and I and John Fleming just discussed on the telephone:

- 1) That your quote will include a non-running foreman which will add approximately 75^c/foot to the drilling footage rates.
- 2) That your crews will deliver the boxes of core to our shed in camp, when they come off shift.
- 3) That overburden drilling rates beyond 50 feet will increase \$1.00 per ft. to 100 feet of depth and \$2.00 per foot to 150 feet of depth.
- 4) That your definition of hard ground will be "when rate of penetration is less than 4 feet per hour and bit life is less than 60 feet".
- 5) That you will rent us a bombardier carrier for difficult access problems at a rate of approximately \$2,500/month.


You should try to meet a commencement date of May 22nd, just after the long Victoria day holiday weekend.

Wishing you the best and looking forward to working with you this summer, I remain,

yours truly,


John Lamb,
Project Geologist.

JL:ebh



thirty-two albert crescent limited

A MEMBER OF THE TONTO GROUP OF COMPANIES

UTAH MINES LTD.


PROPOSAL FOR ISLAND COPPER MINE PROJECT

APRIL 30, 1979

2nd proposal

revised from that
dated 25 April 79.

G.S.



thirty-two albert crescent Limited

A MEMBER OF THE TONTO GROUP OF COMPANIES

April 30, 1979

Utah Mines Ltd.
Island Copper Mine
Port Hardy, B.C.

Attn: Mr. John Lamb

Dear Sir:

We are pleased to submit the following quotation on your project at the Island Copper Mine.

A. Scope of the Program

1. The program contemplates a minimum of 15,000 feet of NQ and BQ drilling.
2. The drilling will commence in mid May 1979.
3. The program contemplates holes ranging in depth from 500' to 1,000' with a capability of going to 1,600'. Holes will be inclined from minus 70 degrees to minus 90 degrees.

B. Union Certification

Our employees will be members of the Tunnel and Rock Workers Union, Local 168.

C. UTAH's Responsibilities

1. Drill roads and drill sites are to be constructed and maintained accessible to skid mounted drill rigs, supply trucks and pickups

...2

free of cost to Thirty-Two Albert. Any environmental responsibility relating to the construction, use or reclamation of same shall be the responsibility of Utah. Thirty-Two Albert will, however, remove all trash and loose materials, leaving drill sites in a clean and orderly condition.

2. All licences, land and water use permits, environmental reports, reports relating to hole plugging, etc. shall be the responsibility of Utah. Thirty-Two Albert shall cooperate with and give technical assistance if requested for compliance with these regulations.
3. Utah will hold Thirty-Two Albert harmless for any liability claims which may arise from normal activity related to this contract including pollution of ground water or surrounding land from discharge of drill water and wastes save if Thirty-Two Albert's employees act in an irresponsible manner.
4. Utah will provide locked storage space for Thirty-Two Albert's parts and supplies.
5. Utah will provide equipment to assist in moving Thirty-Two Albert's rigs from site to site.
6. Utah will either provide or be responsible for the following items at Thirty-Two Albert's list price plus 10%:
 - a) cement, drilling mud and additives and soluble oils
 - b) core boxes
 - c) any other special tools or drilling accessories which may be required for testing purposes or requested left in the hole.
7. Utah will provide room and board for Thirty-Two Albert's crews at no cost to Thirty-Two Albert. It is understood crews will be accommodated in Utah's camp at the mine site.

D. THIRTY-TWO ALBERT's Responsibilities

1. Thirty-Two Albert will provide drill crews, drills and all other necessary equipment and materials to complete the program as outlined above.
 - a) The following equipment will be supplied:
 - 1 skid mounted Longyear Super 38 rig and 1 skid mounted Longyear 34 rig
 - all ancillary pumps, drill strings and other equipment
 - 2 3/4 ton trucks
 - mobile parts trailer and all spares
 - a Bombardier personnel carrier at industry rental rates of approximately \$2,500.00 per month

- b) All drill operators employed on this job will have a minimum of five years drilling experience.
- 2. Thirty-Two Albert will provide transportation for its personnel to and from the drill sites.
- 3. Thirty-Two Albert will provide a full time foreman to supervise the drilling operations. The foreman will have a minimum of ten years experience in running and being responsible for diamond drill jobs.
- 4. Thirty-Two Albert will transport the core from the drill site to Utah's core shed.
- 5. Thirty-Two Albert will provide water to the drill site at no cost providing the horizontal distance does not exceed 1,500' and the lift 250'. Installation and maintenance are to Utah's account at quoted labour rates.

E. General

- 1. In the event that drill pipe and other equipment become broken or lost in the hole, Utah will be responsible for time and materials consumed to recover the materials. If they should end up being left in the hole, then they will be charged at their replacement value.
- 2. In the event that cavities or loose and caving materials are encountered of a nature as to prevent the completion of any hole, then Thirty-Two Albert does not, under these conditions, guarantee to drill to a predetermined depth and in the event that it becomes necessary to abandon the said hole, Thirty-Two Albert shall charge Utah for those holes abandoned, at the depth at which they were abandoned, at the footage rates specified. If required to continue on in the hole then Thirty-Two Albert has the option to revert to standby rate plus all materials, supplies and equipment needed at delivered cost, subsequent to Utah's approval.
- 3. It is agreed that hourly rates shall be interpreted here to mean the labour of a two-man crew, machine and equipment rental, plus pipe and casing lost or left in holes, diamond loss and setting charges, materials and supplies consumed in the work at Thirty-Two Albert's list price.

In the event extra labour over and above the regular two-man crew is required, Thirty-Two Albert agrees to supply such

additional labour at the rate of sixteen dollars and fifty cents (\$16.50) per man per hour.

F. Bid Prices

1. Moving time

a) Move in charge including all equipment, supplies and personnel to the transport discharge point for each rig	\$ 1900.00
b) Move from site to site and to and from the transport loading or discharge point including all equipment, supplies and personnel for the rigs. Four hours free time will be allowed for each move.	16.50/man hr. 10.00/drill hr.
c) Move out charge including all equipment, supplies and personnel for each rig	1900.00

2. Drilling Rates

	<u>BWL</u>	<u>NWL</u>
a) Overburden or Wastedumps		
0 - 50'	14.25	15.25
50 - 100'*	15.25	16.25
100 - 150'*	17.25	18.25
*or hourly rate plus material whichever is greater.		
Casing shoes charged at cost plus 10%.		
b) Core Drilling	<u>BQ</u>	<u>NQ</u>
0 - 1000'	14.25	15.25
1000 - 1500'	15.25	16.25
1500 - 2000'	17.25	18.25

Note: If siliceous magnetite breccia or similar hard material is encountered, an additional \$6.00 per foot will be charged for BQ drilling and \$7.00 per foot for NQ drilling. The hard material surcharge will apply anytime the penetration rate drops below four feet per hour and the footage drops below 60 feet per bit.

3. The following services will be performed at the designated hourly cost:
 - a) Testing
 - b) Standby at Utah's request or any other delays not caused by Thirty-Two Albert
 - c) Setting and pulling casing
 - d) Regaining lost circulation and cementing including setting and drilling time
 - e) Reaming, hole conditioning, drilling cave

	16.50/man hr. 10.00/drill hr.
--	----------------------------------

5.

4. Travel time in excess of one hour per man shift 16.50/man hr.

Thank you for permitting us to tender on your project. We look forward to working for you in the near future.

Yours very truly,

THIRTY-TWO ALBERT CRESCENT
LIMITED



Charles E. Croft

CEC:cm

HOLE NO. E-41
 CASING COLLAR ELEV.: 1190.35' GROUND ELEV.: 17757.76
 COORDINATES: N. 11716.47' E. 11116.72' BEARING: 11116.72'

PROJECT:
 DATE STARTED: 5 Jul '79
 DATE FINISHED: 16 Jul '79
 TOTAL DEPTH: 755 FT.

PAGE NO: 1 OF 13

REF. TO CLAIM CORNER:

SCALE:

LOGGED BY: J. Lamb

SECTION	ALTERATION	FRACTURING	MINERAL	GEOLOGY	COMMENTS: Casing to 19' Rubbly to 28' w. some surface gravel. On old mainline road 500' E of Wobble City	AVE CORE REC'Y/HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP. INT.	ESTI- MATED
	Silica	Chlor	Mica										
20	/	/	/		No real bedrock in first 28'								
30	/	/	/		28 - 80 - Dark gray to black and. rock w. fine scatt'd rock to 50' 50 - 70 - gray-buff. lap. tuff w. occ patches of hem. A few narrow gtz. vns. Minor amts calc in vlts.							BQ	
40	/	/	/		70 - 80 - Dark green gray tuff. Some fine disseminated py.								
50	/	/	/										
60	/	/	/										
70	/	/	/										
80	/	/	/										

7427

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT :

PAGE NO: 2 OF 13

COORDINATES:

DATE STARTED:

REF. TO CLAIM CORNER:

DATE FINISHED:

SCALE

INCLINATION:

TOTAL DEPTH:

LOGGED BY:

MOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT 2

PAGE NO: 3 OF 13

COORDINATES:

DATE STARTED

REF. TO CLAIM CORNER:

INCLINATION.

DATE FINISHED

SCALE

BEARING:

TOTAL DEPTH

LOGGED BY

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

COORDINATES:

N. E.

INCLINATION:

BEARING:

PROJECT:

DATE STARTED:

DATE FINISHED:

TOTAL DEPTH:

PAGE NO: 4 OF 13

REF. TO CLAIM CORNER:

SCALE:

LOGGED BY:

SECTION	ALTERATION				FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	SULPHIDES %	DRILLING INTERVAL 200	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP. INT.	ESTI- MATED
	Silicic	Chlor	Mag													
200	/	/	/													
210	/	/	/													
220	/	/	/													
230	/	/	/													
240	/	/	/													
250	/	/	/													
260																

200 - 260 - Much shaff'd core
Med gray andesite
A few gtz vns. Num. irreg vns
& blobs pinkish cak-lauw
Almost no mag.
Some short runs definitely fgtl
tuff
Very fine bright dissempy but no vis
cpx

clay slip

$\frac{1}{2}$ " narrow gouge seam

much shearing & fractg

strongly fractd pebbly core.

7427

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 5 OF 13

COORDINATES:

N.

E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION				COMMENTS:	DESCRIPTIVE	GEOLOGY	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP. INT.	ESTI-MATED	
	FRACTURING	MINERAL	GEOLOGY													
260	Silica Chl. 1 1/2 Ag				rubby core	260 - 303 - Much broken, core w. strong shatting in last 10'. Some scatt'd mag throughout. Minor qtz vns. Many calc-lauv sms. Minor streaks epid. Chlorite development. Spse disseminated py.			260		BQ					
270	/													79		
280	/															
290	/															
300	/				- green grey gouge	303			303							
303 - 350	rubble. Some core missing. low rec.				Broken rubby core. Light mag throughout. Partly flooded w. silica. Num irreg wh. calc-lauv sms. Short runs brownish biot. aft'n. Fine fract w. cpy & py. Partly disseminated											
320	/	/	/	/		7427								75		

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 6 OF 13

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION	FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP INT.	ESTI-MATED
320	Siliceous Chlor. Mica.	/	/	/	- shearing w. vns calc-lam.	303 - 350 See P5		320		50			
330	/	/	/	/	cpy on fracs.				75				
340	/	/	/	/									
350	/	/	/	/	gtz vns.	350		350					
350	/	/	/	/	350 - 421 Broken core. B'xtd gray to dark lap. tuff v tuff breccia.								
360	/	/	/	/	Fair no. of narrow gtz vns. Many irreg vns. calc-lam.								
370	/	/	/	/	Some fine dissemin py. Cpy showing in some tiny hairline fracs Fine scatt'd mag through darker vungs.								
380	/	/	/	/	gtz vns + calc.	7427		380					

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.

PROJECT 2

DATE STARTED:

PAGE NO: 7 OF 13

REF. TO CLAIM CORNERS

COORDINATES:

1. E.

DATE FINISHED

INCLINATION:

BEARING;

TOTAL DEPTH

LOGGED BY

SECTION	ALTERATION	FRACTURING	MINERAL	GEOLOGY	COMMENTS:	Ave Core Rec'y / Hole	Descriptive Geology				% Sulphides	Drilling Interval	% Core Recovered	Core Size	Sample Interval	% Rec'y Samp. Int.	Estimated
380	Silica Chlor. Mafic	/	/	/	{ sheared w. much calc gashes	380	350 - 421	See Pg.				380	BQ				
390		/	/	/	½" chl. gouge												
400		/	/	/	1" calc-taum												
410		/	/	/	shearing w. calc.												
420		/	/	/	9½' vein & incl. calc vn.												
430		/	/	/	3" f/t gouge → 1' chlor. gouge		421 - 460	Dark andesite w. some scatt'd mag. Siliceous runs & small vns. also many gashes calc-taum. Several rubble zones & lost core where noted.			421						
440		/	/	/	2' rubbly & gougy			Fine dusting cpy on some fracs			20						

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 8 OF 13

COORDINATES:

N.

E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP INT.	ESTI-MATED	
	SILICIC	CALC.													
440	Silicic Chlorite Calc.	Calcareous							440						
450	/	/				{ Chlorite to gray w. much streaky calc				80					
460	/	/				{ 2½' core missing	460		460						
470	/	/				460 - 530 - As above dark mag. andesite w. both narrow gtz stringers & wide vns Numerous calc-lam stringers @ low angles to core. Some brownish affn. looks like bio. A few gashes w cpy & fine dustings cpy on fracs.									
480	=	=				gray gtz vn.				85					
490	=	=				gtz vn									
500	/	/							500						

7427

HOLE NO.

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT :

PAGE NO: 9 OF 13

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER

INCLINATION:

BEARING:

DATE 11/18/2003

SCALE:

LOGGED BY

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 10 OF 13

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP INT.	ESTI-MATED
	SILICIC	CH/TOC												
560	Silicic Ch/TOC Magg.													
570														
580						1/2' gouge & calc in fault @ 40°								
590														
600														
610														
620														

7427

530 - 600 See Pg.

600 - 644 - Weakly mag'tc andesite
w. some weak brown biot alt'n.
Good firm core. Tiny vlt's cpy & py.
Vlt's calc-taum.

560

81

600

90

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 11 OF 13

COORDINATES:

N.

E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION				FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP INT.	ESTI-MATED			
	Silica	Chlor	Magnetite	Pyrite															
620	/	/	/	/	/	/	/	- bleaching irreg. blotch calc-lauv	600 - 644 See P10	620									
630	/	/	/	/									91						
640	/	/	/	/				1/2 calc @ 40°											
								1" calc @ 35°											
650	/	/						644 - 693 - Greenish to dk gray weakly mag'te andesite. A few calc lauv vns. but little silica of any kind. Brown biot. alt'n.. Quite a few hairline opy vlt's. Core is smooth & firm w. a brownish tinge.											
660	/	/																	
670	/	/																	
680	/	/						calc.											

1427

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 12 OF 13

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP INT.	ESTI-MATED
	Silica	Chlorite												
680	/	/	/	/					680					
685	/	/	/	/										
690	/	/							693					
693														
700	/	/												
705	/	/												
710	/	/												
715	/	/												
720	/	/												
725	/	/												
730	/	/												
735	/	/												
740	/	/												

1427

PROJECT:

DATE STARTED:

REF. TO CLAIM CORNER:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

BEARING:

LOGGED BY:

ALTERATION:

BEARING:

LOGGED BY:

FRACTURING:

BEARING:

LOGGED BY:

MINERAL:

BEARING:

LOGGED BY:

GEOLOGY:

HOLE NO. E-41

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 13 OF 13

DATE STARTED:

REF. TO CLAIM CORNER

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY

COORDINATES:

N. E.

Co-ords - 11746.5N 17467.8E

Collar El. - 1194.4 FT.

Inclination - 90°

Bearing. —

Length. 55 FT.

HOLE E-41

P. 1

Sample Footage	Bench.	ASSAY		Bench % Cu	Grade % Mo
		% Cu	% Mo		
1 40 - 50		.15		.007	
2 50 - 60		.12		.008	
3 60 - 70		.20		.010	
4 70 - 80		.0.12		.012	
5 80 - 90		.0.14		.007	
6					
7 90 - 100		.16		.008	
8 100 - 110		.14		.012	
9 110 - 120		.68		.007	
10 120 - 130		.12			
11 130 - 140		.05		.004	
12 140 - 150		.13		.009	
13 150 - 160		.08		.007	
14 160 - 170		.09		.012	
15 170 - 180		.12		.005	
16 180 - 190		.17		.005	
17 190 - 200		.12		.007	
18 200 - 210		.21		.013	
19 210 - 220		.12		.011	
20 220 - 230		.22		.006	
21 230 - 240		.14		.010	
22 240 - 250		.22		.016	
23 250 - 260		.07		.001	
24 260 - 270		.20		.011	
25 270 - 280		.20		.007	
26 280 - 290		.18		.007	
27 290 - 300		.11		.005	
28 300 - 310		.14		.009	
29 310 - 320		.23		.004	
30 320 - 330		.27		.010	
31 330 - 340		.43		.012	
32 340 - 350		.39		.013	
33 350 - 360		.37		.010	
34 360 - 370		.35		.011	
35 370 - 380		.24		.010	
36 380 - 390		.19		.011	
37 390 - 400		.41		.014	
38 400 - 410		.48		.014	
39 410 - 420		.15		.009	
40 420 - 430		.25		.007	
41 430 - 440		.13		.006	
42 440 - 450		.14		.013	
43 450 - 460		.14		.010	
44 460 - 470		.24		.005	
45 470 - 480		.12		.013	

7427

	Sample Footage	Bench	ASSAY	Bench Grade
			% Cu	% Mo
			% Mo	% Cu
1	480 - 490		.15	.019
2	490 - 500		.32	.038
3	500 - 510		.09	.006
4	510 - 520		.11	.004
5	520 - 530		.09	.007
6	530 - 540		.42	.008
7	540 - 550		.22	.009
8	550 - 560		.13	.008
9	560 - 570		.14	.014
10	570 - 580		.16	.006
11	580 - 590		.10	.004
12	590 - 600		.26	.009
13	600 - 610		.20	.020
14	610 - 620		.30	.005
15	620 - 630		.22	.006
16	630 - 640		.12	.006
17	640 - 650		.18	.005
18	650 - 660		.31	.017
19	660 - 670		.23	.008
20	670 - 680		.18	.007
21	680 - 690		.29	.009
22	690 - 700		.09	.007
23	700 - 710		.12	.009
24	710 - 720		.11	.007
25	720 - 730		.07	.005
26	730 - 740		.07	.007
27	740 - 750		.04	.006
28	750 - 755		.07	.008
29		—		
30				
31		#		
32		71 sample	3.07 = 217.97	
33		77		
34		78		
35		79		
36		80		
37		81		
38		82		
39		83		
40		84		
41		85		
42		86		
43		87		

1427

HOLE NO. E-42

CASING COLLAR ELEV.: 1295.1 GROUND ELEV.:

COORDINATES:

INCLINATION: -90°

PROJECT:

PAGE NO: 1 OF 11

DATE STARTED: 16 Jul '79

REF. TO CLAIM CORNER:

DATE FINISHED: 23 Jul '79

SCALE:

TOTAL DEPTH: 698 FT

LOGGED BY: J. Lamb

N. 12164.0 E. 17868.65

BEARING:

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS: 0 - 80' or to 94' overburden. No core. On hill above paved road N of Wobble City	AVE CORE REC'Y / HOLE	SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP.	ESTI-MATED
	Si/Silica	Chlor												
90	/	/				DESCRIPTIVE GEOLOGY								
94	/	/				94 - 118 - Much broken core Grayish lap. tuff w. a few short runs brownish att'n. Finely disseminated py & minor cpx. Weakly mag'te in short runs Numerous irreg. white calc gashes & vns. w. streaks gils.	94				BQ			
100	/	/										80		
110	/	/												
118	/	/				118 - 132 - Weakly mag'te broken core Gray, spotted lap. tuff Network white calc vns w. minor streaks gils Sparse sulphide								
132	/	/										85		
132	/	/				132 - 159.5 - Mostly soft gouge, gray, w. spare cpx & py. Some patches & streaks of calc Looks like a strong fault zone								
140														
150														

1427

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT :

PAGE NO: 2 OF 11

DATE STARTED:

REF. TO CLAIM CORNER

DATE FINISHED:

SCALE

TOTAL DEPTH:

LOGGED BY

COORDINATES:

N. E.

INCLINATION: **BEARING:**

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 3 OF 11

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY: J.L.

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP. INT.	ESTI-MATED
	Silica	Chlor												
210	/	/	/	/	/	- 2" milky gouge @ 45°	210 - 239 - Mod'ly mag'tc andesite w. fine lacing calc. fracs. in lighter runs Some tiny seams py & spsc cpy.		210	BQ				
220	/	/	/	/	/	- 1/2' fit @ 45°				91				
230	/	/	/	/	/	- 1/4" milky gray cherty vn. cutting calc vns.								
240	/	/	/	/	/		239 - 295 - Blackish-green andesite w tuff core, fairly firm. Mod mag'tc A few narrow gtz vns. Irreg vns. & streaky white to pnk calc-taum. Fine hairline vns py & minor cpy. Also dissempy.		239					
250	/	/	/	/	/									
260	/	/	/	/	/	- calc in slip at 20°								
270	/	/	/	/	/									

7427

MOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 4 OF 11

DATE STARTED:

REF. TO CLAIM CORNER:

COORDINATES:

DATE FINISHED:

SCALE:

INCLINATION:

BEARING:

TOTAL DEPTH:

LOGGED BY

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 5 OF 11

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION	FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	DESCRIPTIVE GEOLOGY			% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP. INT.	ESTI-MATED
330	Silic Chlor 1/16g	/	/	/						330		80				
330					- 1' calc @ 25°	330 - 390	Dark brown-green andesite, smooth w. weak mag'tsm throughout									
340					{ shearing @ 10°		Very little gtz but freq. vns. of calc-lauv.									
350					- gtz vn w. py & cpy.		Hairline cracks of py & spse cpy. Some Mo on a frac.					93				
360					ser gougy slip											
370					clay att'n on slip											
380					{ 2' green ser, pyr clay gouge											
390					1' sheared.											
					- 1/2' clay att'l gougy @ 35°		7427									
										390						

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT :

PAGE NO: 6 OF 11

COORDINATES:

200

DATE STARTED

REF. TO CLAIM CORNER

INCLINATION;

BEARING:

SCALE:

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 7 OF 11

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP INT.	ESTI-MATED
	Silica	Chlor												
450	Si/ice	Chlor												
460														
470														
480														
490														
500														
510														

435.5 - 510 See Pg.← 1' sheared
4' greenish

1' sheared w. py & mo.

6" green gouge slip

80" sheared & 6' t.d.
w. calc
lacingchlor. gouge on vn.
at 380

1" shearing

7427

510

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 8 OF 11

DATE STARTED:

REF. TO CLAIM CORNER:

COORDINATES:

N. E.

DATE FINISHED:

SCALE:

INCLINATION:

BEARING:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION	FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y SAMP INT.	ESTI-MATED
510	S. 1/2 N. Chlor N/2 S.	/	/	/	sheared	510 - 570 - Greenish to dark gray smooth andesitic tuff. Weakly mag'tc.	510	BQ					
520	/	/	/	/	6" gtz, calc chay gouge @ 35° } gouge w. calc & py.	Laced w. many calc-taum. seams. but sparse gtz. Quite a bit py. lacings & dissems. Spse cpy.							
530	/	/	/	/	2" slip w. green shearing w. moly. in gouge } 2' shearing w. gouge.		85						
540	/	/	/	/	1" fault @ 35°								
550	/	/	/	/	1" fault @ 50° w. green gouge								
560	/	/	/	/									
570	/	/	/	/									

7427

570

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 9 OF 11

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION		FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	SULPHIDES %	DRILLING INTERVAL 570	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC.Y. SAMP. INT.	ESTI- MATED
	Silica	Chlor.												
570	/	/	/	/	/							BQ		
580	/	/	/	/	/									
590	/	/	/	/	/	- $\frac{1}{4}$ " slip @ 45°							83	
600	/	/	/	/	/	- $\frac{1}{8}$ " slip.								
610	/	/	/	/	/									
620	/	/	/	/	/	- 6' fault								
630	/	/	/	/	/	= shearing								

7427

630

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: 10 OF 11

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION					COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP. INT.	ESTI-MATED
	ALTERATION	FRACTURING	MINERAL	GEOLOGY									
630	Silic Chlor Mg.2	/ / / / / / / / / / / / / /											
640		/ / / / / / / / / / / / / /											
650		/ / / / / / / / / / / / / /			- good dissemin cpy								
660		/ / / / / / / / / / / / / /											
670		/ / / / / / / / / / / / / /											
680		/ / / / / / / / / / / / / /			- shearing w gtz, calc + py + cpy								
690	/ / /	/ / /			- 1' gougy								

7427

HOLE NO. E-42

CASING COLLAR ELEV.:

GROUND ELEV.:

PROJECT:

PAGE NO: // OF //

COORDINATES:

N. E.

DATE STARTED:

REF. TO CLAIM CORNER:

INCLINATION:

BEARING:

DATE FINISHED:

SCALE:

TOTAL DEPTH:

LOGGED BY:

SECTION	ALTERATION	FRACTURING	MINERAL	GEOLOGY	COMMENTS:	AVE CORE REC'Y / HOLE	% SULPHIDES	DRILLING INTERVAL	% CORE RECOVERED	CORE SIZE	SAMPLE INTERVAL	% REC'Y. SAMP. INT.	ESTI-MATED
690	Si/V/C Ca/S Na/S	/	/	/	630 - 698 - See P10 6" gougy fault @ 45°								
700					698 END OF HOLE								

7427

Co-ords -

Collar Elev -

Inclination - -90°

Bearing - —

Length 1695 feet.

HOLE E-42

P. 1

Sample Footage	Bench	ASSAY		Bench	Grade
		% Cu	% Mo	% Cu	% Mo
1 100 - 110		.13		.008	
2					
3 120 - 130		.17		.014	
4					
5 160 - 170		.08		.006	
6 170 - 180		.08		.011	
7					
8 190 - 200		.05		.020	
9					
10 210 - 220		.06		.026	
11					
12 240 - 250		.06		.005	
13					
14 270 - 280		.04		.005	
15					
16 320 - 330		.06		.008	
17					
18 340 - 350		.09		.013	
19					
20 360 - 370		.04		.012	
21					
22 380 - 390		.06		.017	
23 390 - 400		.10		.005	
24 400 - 410		.04		.008	
25 410 - 420		.09		.007	
26 420 - 430		.11		.007	
27 430 - 440		.49		.022)
28 440 - 450		.14		.009	
29 450 - 460		.11		.010	
30 460 - 470		.19		.018	
31 470 - 480		.14		.018	
32 480 - 490		.28		.020	120
33 490 - 500		.29		.026	.22
34 500 - 510		.17		.016	
35 510 - 520		.22		.030	
36 520 - 530		.19		.005	
37 530 - 540		.25		.010	
38 540 - 550		.20		.015	
39 550 - 560		.07		.005	
40 560 - 570		.04		.009	
41 570 - 580		.12		.020	
42 580 - 590		.08		.009	
43 590 - 600		.15		.028	
600 - 610		.18		.014	

7427

HOLE E-42
P2.

	Sample Footage	Bench	ASSAY	Bench	Grade	
			% Cu	% Mo	% Cu	% Mo
1	610 - 620		.16	.009		
2	620 - 630		.17	.014		
3	630 - 640		.12	.012		
4	640 - 650		.13	.018		
5	650 - 660		.29	.036	.128	.020
6	660 - 670		.10	.066	.24	
7	670 - 680		.17	.012		
8	680 - 690		.26	.013		
9	690 - 698		.15	.009		
10						
11						
12						
13						
14						
15						
16						
17						
18						
20						
21						
22						
23						
24						
25						
26						
27						
28						
29						
30						
31						
32						
33						
34						
35						
36						
37						
38						
39						
41						
42						
43						

1421

