

Part of Appendix D  
of Assessment Report on  
GEOPHYSICAL, GEOCHEMICAL AND  
DIAMOND DRILLING ON EXPO GROUPS  
A, B, C and D

NANAIMO MINING DIVISION  
NTS 92 L/12

UTAH MINES LTD.

October 1982

5 YEAR CONFIDENTIALITY!



PAGE NO.: 1 OF 11

CASING COLLAR ELEV.: ..

GROUND ELEV.: 1650'

COORDINATES: 2586+90' N. 2057+80' E.

INCLINATION: -51° BEARING: 357°

PRO.: RED DOG

DATE STARTED: June 2, 1982

DATE FINISHED: June 6, 1982

TOTAL DEPTH: 620'

HOLE NO.: EC-131

REF. TO CLAIM CORNER: Red Dog 7

SCALE: 1"=100' (1:120)

LOGGED BY: H. Muntanion

DEPTH INTERVAL		CORE								DEPTH INTERVAL		SLUDGE			
FROM	TO	SAMPLE NO.	INCHES REC.	% REC.	ASSAY				FROM	TO	SAMPLE NO.	LBS. REC.	% REC.	ASSAY	
					Cu %	Mo %	As oz/t.	Ag oz/t.							
0	10'														
10	20'	36451	106	88	.07	.002	.003	.02							
20	24'	36452	32	66	.02	<.001	.003	.02							
24	30'	36453	71	99	.21	.009	.015	.02							
30	40'	36454	110	92	.35	.007	.012	.03							
40	50'	36455	114	95	.38	.004	.020	.03							
50	60'	36456	120	100	.25	.009	.015	.03							

GEOLOGICAL BRANCH  
ASSESSMENT REPORT

10,982  
part 2 of 2













































































































































