

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
133	4.27	4.88	0.61	0.17	28	0.00	0	6	3	3	4	5	3	
133	4.88	6.55	1.67	1.45	87	0.45	27	6	3	3	30	5	3	
133	6.55	7.47	0.92	1.32	143	0.67	73	7	3	3	25	3	3	
133	7.47	9.14	1.67	1.53	92	0.33	20	5	3	5	30	3	3	
133	9.14	10.97	1.83	1.85	101	1.50	82	10	3	5	15	5	3	
133	10.97	12.80	1.83	1.77	97	0.58	32	7	3	5	25	5	3	
133	12.80	14.02	1.22	1.26	103	0.89	73	11	3	5	8	1	2	
133	14.02	15.54	1.52	1.47	97	0.52	34	6	3	5	30	1	2	
133	15.54	16.61	1.07	1.23	115	0.49	46	7	3	5	23	5	3	
133	16.61	19.66	3.05	3.07	101	1.12	37	10	2	3	25	4	3	
133	19.66	21.18	1.52	2.16	142	0.50	33	8	2	3	30	4	3	
133	21.18	23.16	1.98	2.07	105	0.37	19	6	2	3	50	4	3	
133	23.16	25.30	2.14	2.08	97	1.00	47	8	3	5	28	1	2	
133	25.30	27.74	2.44	2.12	87	1.43	59	8	3	5	30	4	2	
133	27.74	28.35	0.61	0.74	121	0.34	56	9	3	5	10	1	3	
133	28.35	31.55	3.20	3.03	95	2.15	67	14	3	5	9	1	2	
133	31.55	34.44	2.89	2.77	96	1.30	45	9	3	5	33	1	2	
133	34.44	37.49	3.05	2.93	96	1.17	38	9	3	5	30	3	3	
133	37.49	38.40	0.91	0.92	101	0.53	58	6	3	5	20	4	3	
133	38.40	41.45	3.05	3.08	101	2.24	73	13	3	5	13	4	3	2 39.35 m.-slickenside 50 to c.a.,45 rake
133	41.45	44.50	3.05	2.94	96	2.26	74	13	3	5	11	1	3	2 42.5 m. - slick at 70 to c.a., wk rake
133	44.50	47.55	3.05	2.83	93	2.72	89	13	3	5	10	1	3	
133	47.55	50.44	2.89	2.65	92	2.17	75	14	3	5	8	1	2	
133	50.44	53.04	2.60	2.57	99	2.29	88	14	1	3	8	1	3	3 fault zone
133	53.04	56.08	3.04	2.87	94	2.33	77	14	1	3	6	1	3	3 fault zone
133	56.08	59.13	3.05	2.93	96	0.81	27	15	2	4	4	1	3	
133	59.13	61.87	2.74	2.64	96	1.38	50	9	3	4	29	1	3	
133	61.87	64.77	2.90	2.75	95	2.28	79	13	3	4	13	4	3	
133	64.77	65.84	1.07	1.10	103	1.00	93	10	3	4	8	5	3	
133	65.84	68.88	3.04	3.03	100	2.56	84	13	3	5	11	4	2	
133	68.88	71.93	3.05	2.96	97	2.81	92	14	2	4	9	4	3	
133	71.93	74.98	3.05	2.50	82	1.20	39	9	2	4	25	1	3	
133	74.98	76.50	1.52	0.74	49	0.32	21	4	0	3	25	5	3	3 fault zone
133	76.50	78.03	1.53	0.90	59	0.41	27	5	1	3	30	5	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
133	78.03	81.08	3.05	2.81	92	2.13	70	10	1	3	28	3	3	
133	81.08	82.30	1.22	1.13	93	0.63	52	4	2	4	30	4	4	
133	82.30	84.12	1.82	1.66	91	1.04	57	12	3	5	11	1	3	
133	84.12	86.56	2.44	2.22	91	1.06	43	9	2	4	28	5	3	
133	86.56	87.48	0.92	0.72	78	0.19	21	4	1	3	35	5	3	
133	87.48	90.22	2.74	2.41	88	1.75	64	9	2	4	27	5	3	
133	90.22	93.27	3.05	2.93	96	2.62	86	10	2	4	21	1	2	brecciated (healed), slick 65 at 94.8 m.
133	93.27	96.32	3.05	2.81	92	2.17	71	12	2	4	18	1	3	
133	96.32	99.36	3.04	2.89	95	2.37	78	12	1	3	15	5	4	fault
133	99.36	102.11	2.75	2.60	95	1.72	63	10	2	4	25	1	3	fault at first 0.5 m.
133	102.11	105.16	3.05	2.47	81	1.80	59	10	3	5	17	1	3	
133	105.16	108.20	3.04	3.08	101	2.05	67	10	3	5	30	1	4	
133	108.20	111.25	3.05	2.85	93	2.45	80	12	3	5	17	5	3	
133	111.25	114.30	3.05	2.87	94	2.36	77	12	3	5	15	1	3	111.14 m. - gouge on fracture
133	114.30	117.35	3.05	3.05	100	2.60	85	12	2	4	18	1	3	
133	117.35	120.40	3.05	3.00	98	2.17	71	10	2	4	25	1	3	
133	120.40	123.44	3.04	2.81	92	2.56	84	10	3	5	20	1	2	
133	123.44	126.80	3.36	2.78	83	2.35	70	10	2	5	25	4	3	
133	126.80	129.85	3.05	2.94	96	2.61	86	12	3	5	15	1	2	
133	129.85	132.89	3.04	2.88	95	2.06	68	10	1	3	26	5	3	
133	132.89	135.94	3.05	2.90	95	2.05	67	12	2	4	16	1	3	
133	135.94	138.99	3.05	2.77	91	1.75	57	9	2	4	30	5	3	
133	138.99	142.04	3.05	2.90	95	1.95	64	10	3	5	20	5	3	
133	142.04	145.08	3.04	3.03	100	2.05	67	10	2	4	22	1	2	142.2 m. slick at 70 to c.a.; weak rake
133	145.08	148.13	3.05	2.93	96	2.31	76	12	2	4	16	1	3	
133	148.13	151.18	3.05	2.86	94	0.76	25	7	2	5	40	5	3	
133	151.18	154.23	3.05	2.99	98	1.21	40	7	2	4	40	1	3	
133	154.23	157.28	3.05	2.87	94	1.00	33	7	2	4	40	5	3	
133	157.28	160.17	2.89	2.50	87	1.13	39	7	2	4	40	1	2	
133	160.17	163.22	3.05	3.00	98	1.67	55	10	2	4	25	1	2	gouge mat'l in fractures at 161.0 m.
133	163.22	166.12	2.90	2.86	99	1.24	43	7	2	4	40	1	2	gouge mat'l in fractures at 164.82 m.
133	166.12	169.47	3.35	3.08	92	1.18	35	9	2	4	40	1	2	gouge on fractures
133	169.47	172.52	3.05	2.90	95	1.59	52	10	2	4	24	1	2	healed fault gouge
133	172.52	175.56	3.04	2.85	94	2.40	79	14	2	4	6	1	2	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
133	175.56	177.09	1.53	1.76	115	1.76	115	10	2	5	13	1	2	
133	177.09	179.83	2.74	2.49	91	1.74	64	13	2	5	12	1	2	
133	179.83	181.97	2.14	2.09	98	0.50	23	9	2	5	22	1	2	
133	181.97	183.49	1.52	1.37	90	0.00	0	6	1	3	40	1		2 30 cm. section of gouge
133	183.49	184.71	1.22	1.14	93	0.77	63	12	2	5	6	1	3	
133	184.71	187.76	3.05	3.08	101	2.18	71	12	2	4	13	1	3	
133	187.76	190.80	3.04	2.95	97	2.58	85	14	2	4	8	1	2	
133	190.80	193.85	3.05	3.06	100	1.70	56	13	2	4	13	1		1 polished surfaces
133	193.85	196.90	3.05	3.05	100	2.20	72	15	2	4	7	1	2	
133	196.90	198.73	1.83	0.45	25	0.17	9	7	2	4	7	1		2 10 cm. healed gouge
133	198.73	199.34	0.61	0.39	64	0.00	0	5	2	4	13	2	2	
133	199.34	200.56	1.22	0.70	57	0.00	0	7	2	4	11	1		2 gouge - mismatch
133	200.56	203.00	2.44	0.44	18	0.00	0	5	1	3	12	1		3 mismatch - missing core
133	203.00	204.22	1.22	1.15	94	0.60	49	6	1	4	25	1		3 fault zone
133	204.22	206.65	2.43	2.55	105	0.65	27	7	1	3	40	5		4 fault zone
133	206.65	209.09	2.44	2.27	93	0.55	23	5	1	3	30	5		4 fault zone
133	209.09	212.14	3.05	2.90	95	0.47	15	2	0	2	80	5		4 fault zone
133	212.14	215.19	3.05	2.90	95	0.93	30	3	0	4	40	5		4 fault zone
133	215.19	218.24	3.05	2.97	97	1.07	35	10	1	4	19	1		3 fault zone
133	218.24	221.28	3.04	3.02	99	2.93	96	15	2	5	2	1		2 minor gouge on fractures
133	221.28	224.33	3.05	3.08	101	2.86	94	15	3	5	3	1	2	
133	224.33	227.38	3.05	3.05	100	2.72	89	15	3	5	3	1	2	
133	227.38	230.43	3.05	3.02	99	2.82	92	15	3	5	4	1	2	
133	230.43	233.48	3.05	3.05	100	2.59	85	14	2	5	8	1	3	
133	233.48	233.78	0.30	0.25	83	0.25	83	13	3	5	1	1	2	
133	233.78	236.52	2.74	2.85	104	2.55	93	14	2	5	6	2		2 clay on fractures
133	236.52	239.57	3.05	3.02	99	3.02	99	15	2	5	4	1	2	
133	239.57	242.62	3.05	2.78	91	2.32	76	13	2	5	9	1	2	
133	242.62	244.45	1.83	2.13	116	1.52	83	13	2	5	7	1	2	
133	244.45	247.50	3.05	2.90	95	2.00	66	13	2	5	11	1		2 gouge on fractures
133	247.50	248.72	1.22	1.20	98	1.04	85	14	2	5	4	1		2 gouge on fractures
133	248.72	251.76	3.04	3.15	104	2.08	68	13	2	4	12	1	3	
133	251.76	253.21	1.45	1.20	83	0.85	59	10	3	4	10	1		2 minor gouge on fractures
133	253.21	254.20	0.99	0.75	76	0.25	25	6	3	4	17	1		2 minor gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
133	254.20	255.12	0.92	0.92	100	0.60	65	12	3	5	5	1	3	
133	255.12	257.86	2.74	2.65	97	2.65	97	14	3	5	6	1	2	
133	257.86	260.91	3.05	3.05	100	2.68	88	14	3	5	8	1	2	
133	260.91	263.96	3.05	2.70	89	1.14	37	9	2	3	30	1	2	263.0 m. - fault gouge
133	263.96	266.09	2.13	2.15	101	0.23	11	6	1	3	40	1	1	1 fault zone
133	266.09	268.53	2.44	2.06	84	1.02	42	10	2	3	13	1	1	1 weak slicks with gouge, 50 to c.a.
133	268.53	270.05	1.52	1.06	70	0.95	62	14	3	4	2	1	2	
133	270.05	272.19	2.14	2.40	112	2.24	105	14	3	5	5	2	2	
133	272.19	273.10	0.91	1.03	113	0.94	103	10	3	5	8	2	3	3 cave
133	273.10	276.15	3.05	3.00	98	2.95	97	14	3	5	6	2	2	
133	276.15	279.20	3.05	3.00	98	2.46	81	13	3	4	12	1	1	1 mineralized fracture
133	279.20	282.24	3.04	2.98	98	2.14	70	13	2	4	14	1	1	1 slick with gouge and clay
133	282.24	285.29	3.05	3.02	99	1.87	61	12	3	4	17	1	2	
133	285.29	288.34	3.05	3.02	99	2.18	71	13	2	4	13	2	1	
133	288.34	291.39	3.05	2.97	97	2.61	86	14	3	5	7	1	2	
133	291.39	294.44	3.05	2.97	97	2.87	94	15	3	5	4	1	1	1 mineralized slick, 20 to c.a.
133	294.44	297.48	3.04	3.04	100	3.00	99	15	3	5	5	1	2	
133	297.48	300.53	3.05	3.08	101	3.05	100	15	3	5	4	1	1	1 slick mineralized, 15 to c.a.
133	300.53	303.58	3.05	2.92	96	2.92	96	15	3	6	1	1	2	
133	303.58	306.63	3.05	3.05	100	2.90	95	15	3	5	3	1	2	
133	306.63	309.68	3.05	3.10	102	1.42	47	10	2	3	25	1	1	1 308.0 to 311.5 m. fault zone
133	309.68	312.72	3.04	2.83	93	1.50	49	10	2	4	19	1	1	1 slick joints, no rake
133	312.72	315.77	3.05	2.85	93	2.35	77	13	2	4	11	1	1	1 slick joints, no rake
133	315.77	318.82	3.05	3.04	100	3.04	100	15	3	6	2	1	3	
133	318.82	321.56	2.74	2.94	107	2.74	100	15	3	6	1	1	2	
133	321.56	324.61	3.05	3.05	100	3.05	100	15	3	6	2	1	2	
133	324.61	327.96	3.35	3.20	96	3.20	96	14	3	5	7	1	3	
133	327.96	331.01	3.05	3.02	99	2.85	93	10	3	5	30	4	3	
133	331.01	334.06	3.05	3.01	99	2.67	88	13	3	5	15	3	4	4 section contains vugs/broken core
133	334.06	336.80	2.74	2.65	97	2.29	84	12	3	4	14	1	3	
133	336.80	340.16	3.36	3.36	100	2.51	75	13	3	5	12	5	4	4 337.95m-slip plane w/ gouge 65 to c.a.
133	340.16	343.20	3.04	3.04	100	3.04	100	15	3	5	5	1	3	
133	343.20	346.25	3.05	3.05	100	1.45	48	10	2	4	30	5	3	3 broken core with gouge in last metres
133	346.25	349.30	3.05	3.05	100	3.05	100	14	3	5	8	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
133	349.30	352.35	3.05	3.05	100	3.05	100	15	3	5	5	1	3	
133	352.35	355.40	3.05	3.05	100	3.05	100	14	3	5	10	5	3	
133	355.40	358.44	3.04	3.04	100	3.04	100	14	3	5	7	4	3	
133	358.44	361.49	3.05	3.05	100	3.05	100	14	3	5	7	5	3	
133	361.49	364.54	3.05	3.05	100	3.05	100	14	3	5	6	5	3	
133	364.54	367.59	3.05	3.05	100	3.00	98	14	3	4	7	5	3	367.45 m.-slip plane w/ gouge 85 to c.a.
133	367.59	370.64	3.05	3.05	100	1.87	61	12	3	5	20	4	4	
133	370.64	373.68	3.04	3.04	100	1.97	65	10	2	4	30	1	3	broken core w/ gouge
133	373.68	376.73	3.05	3.05	100	3.05	100	14	3	5	8	4	3	
133	376.73	379.78	3.05	3.05	100	3.05	100	14	3	5	7	1	2	
133	379.78	382.83	3.05	3.05	100	3.02	99	14	2	4	9	4	3	380.7 m.-23 cm. fault gouge 38 to c.a.
133	382.83	385.88	3.05	3.05	100	2.78	91	14	2	4	10	1	3	384.74 m. - fault gouge at 28 to c.a.
133	385.88	388.92	3.04	2.89	95	2.35	77	13	3	5	14	1	3	
133	388.92	391.97	3.05	3.05	100	3.05	100	14	3	5	7	4	3	
133	391.97	395.02	3.05	3.05	100	3.05	100	14	3	5	9	1	3	
133	395.02	398.07	3.05	3.05	100	2.45	80	10	3	5	25	1	3	
133	398.07	401.12	3.05	3.05	100	3.03	99	15	3	5	5	1	3	
133	401.12	404.16	3.04	3.04	100	2.25	74	14	2	4	8	1	2	401.75 m. - fault gouge at 28 to c.a.
133	404.16	407.21	3.05	3.05	100	2.41	79	13	3	5	14	4	3	
133	407.21	410.26	3.05	3.05	100	2.20	72	13	3	5	13	1	3	
133	410.26	413.31	3.05	3.05	100	3.05	100	15	3	5	2	1	3	12 to c.a. fracture ± py gouge
133	413.31	416.36	3.05	3.05	100	2.75	90	15	3	5	4	1	2	
133	416.36	419.40	3.04	3.04	100	3.00	99	15	3	5	5	1	2	2 fracture parallel to c.a.
133	419.40	422.45	3.05	3.05	100	2.80	92	15	3	5	3	3	3	3 fracture 10 to c.a.
133	422.45	425.50	3.05	3.05	100	2.90	95	14	3	4	6	1	1	1 minor clay alteration
133	425.50	428.55	3.05	3.05	100	2.70	89	14	3	5	7	2	2	2 minor polishing on fractures
133	428.55	431.60	3.05	3.05	100	3.00	98	14	4	4	6	1	1	1 40 cm. soft to hard shear zone
133	431.60	434.64	3.04	3.04	100	2.95	97	15	3	5	5	2	3	
133	434.64	437.69	3.05	3.05	100	2.98	98	14	3	5	8	2	3	3 435.1 m. - slip plane at 60 to c.a.
133	437.69	440.74	3.05	3.05	100	2.95	97	13	3	5	15	1	3	
133	440.74	443.79	3.05	3.05	100	2.25	74	13	2	4	15	1	2	2 1 cm. gouge 20 to c.a. in 70 cm. zone
133	443.79	446.84	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
133	446.84	449.88	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
134	3.65	5.18	1.53	1.10	72	0.47	31	12	4	0	8	3	3	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
134	5.18	8.23	3.05	3.00	98	2.38	78	12	4	0	18	1	3	
134	8.23	9.57	1.34	1.60	119	0.93	69	7	4	4	17	1	2	
134	9.57	11.28	1.71	1.52	89	1.20	70	13	4	4	6	1	2	
134	11.28	12.80	1.52	1.52	100	1.00	66	7	4	2	25	2	2	
134	12.80	15.85	3.05	3.05	100	2.35	77	10	4	1	20	3	2	2 minor fault gouge 10 and 30 to c.a.
134	15.85	18.90	3.05	3.10	102	2.88	94	14	3	5	9	1	4	
134	18.90	21.95	3.05	2.47	81	0.55	18	13	3	3	13	1	2	
134	21.95	23.16	1.21	1.22	101	0.00	0	4	0	0	50	1	1	1 fault gouge slip planes 40 to c.a.
134	23.16	25.30	2.14	2.20	103	0.18	8	4	0	0	50	1	1	1 fault gouge slip planes 10 to c.a.
134	25.30	26.82	1.52	1.05	69	0.53	35	4	0	0	50	1	1	1 fault gouge slip planes 10 & 45 to c.a.
134	26.82	28.34	1.52	1.43	94	0.00	0	4	0	0	50	1	1	1 fault gouge & well-altered rock
134	28.34	31.39	3.05	3.10	102	1.27	42	12	2	3	18	3	1	
134	31.39	34.44	3.05	3.05	100	1.90	62	13	2	2	15	1	1	1 slip planes at 10 and 40 to c.a.
134	34.44	37.49	3.05	3.05	100	1.87	61	10	2	2	25	2	2	
134	37.49	40.54	3.05	3.10	102	1.07	35	14	0	0	5	3	3	1 fault gouge 5 cm. 70 to c.a.
134	40.54	43.59	3.05	3.10	102	1.20	39	13	3	4	12	3	2	
134	43.59	46.33	2.74	2.25	82	1.20	44	10	0	0	20	3	3	1 fault gouge
134	46.33	49.38	3.05	3.05	100	2.45	80	13	1	1	12	2	2	2 fault gouge slip planes at 10, 30 & 45
134	49.38	52.73	3.35	3.07	92	1.45	43	13	0	3	15	3	3	1 fault gouge 1 cm. 30 to c.a.
134	52.73	55.17	2.44	2.53	104	0.95	39	13	0	0	9	1	1	2 ground core fault gouge 60 to c.a. 2 cm.
134	55.17	58.22	3.05	3.00	98	2.15	70	13	5	2	13	1	1	3 ground core
134	58.22	61.26	3.04	3.07	101	2.00	66	14	4	2	9	4	3	
134	61.26	64.31	3.05	3.10	102	1.70	56	11	4	3	20	1	1	2 broken rock
134	64.31	67.36	3.05	3.10	102	2.70	89	14	4	3	8	3	1	
134	67.36	70.41	3.05	3.10	102	2.72	89	14	4	5	9	1	2	
134	70.41	73.46	3.05	3.05	100	2.75	90	14	4	5	8	3	2	
134	73.46	75.29	1.83	1.77	97	1.77	97	14	4	5	4	5	3	
134	75.29	78.33	3.04	3.00	99	2.52	83	13	3	3	11	3	3	1 slip plane at 45 to c.a.
134	78.33	81.38	3.05	3.05	100	2.96	97	14	4	5	5	3	3	
134	81.38	84.43	3.05	3.05	100	2.94	96	14	0	3	6	3	3	3 slip plane w/ gouge at 45 to c.a.
134	84.43	87.48	3.05	2.95	97	2.54	83	14	4	5	10	3	2	
134	87.48	90.53	3.05	3.20	105	2.78	91	14	4	5	8	3	2	
134	90.53	93.57	3.04	3.04	100	2.04	67	12	0	2	16	3	3	1 fault gouge 15 cm.
134	93.57	96.62	3.05	3.04	100	2.90	95	14	4	4	9	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
134	96.62	99.67	3.05	3.07	101	3.03	99	15	4	4	5	1	2	some grinding of core
134	99.67	102.72	3.05	3.00	98	2.80	92	13	4	3	11	3	1	minor shears
134	102.72	105.77	3.05	3.04	100	2.55	84	14	4	4	7	2	2	
134	105.77	108.81	3.04	2.85	94	1.60	53	12	4	4	20	1	2	
134	108.81	111.86	3.05	3.20	105	2.78	91	13	4	4	11	2	1	
134	111.86	114.91	3.05	3.30	108	2.90	95	14	4	5	5	4	1	
134	114.91	117.96	3.05	3.05	100	3.05	100	15	4	5	4	4	1	
134	117.96	121.01	3.05	3.02	99	2.20	72	14	4	5	7	3	1	
134	121.01	124.05	3.04	3.05	100	2.87	94	14	4	4	6	3	1	
134	124.05	127.10	3.05	3.05	100	2.70	89	15	4	5	4	3	2	
134	127.10	130.15	3.05	3.05	100	2.65	87	14	4	4	7	4	2	
134	130.15	133.20	3.05	3.10	102	3.00	98	14	4	5	6	1	3	
134	133.20	136.25	3.05	3.15	103	2.80	92	15	4	5	4	1	3	
134	136.25	139.29	3.04	3.10	102	2.95	97	15	4	5	4	3	2	
134	139.29	142.34	3.05	3.10	102	3.10	102	15	4	5	3	3	3	
134	142.34	145.39	3.05	3.05	100	3.05	100	14	4	5	5	3	3	
134	145.39	148.44	3.05	3.00	98	2.90	95	14	4	5	5	1	3	
134	148.44	151.49	3.05	3.05	100	3.05	100	14	4	5	5	3	2	
134	151.49	154.53	3.04	3.04	100	2.40	79	14	4	3	5	3	3	
134	154.53	157.58	3.05	3.10	102	2.97	97	15	4	4	4	3	2	
134	157.58	160.63	3.05	3.05	100	2.95	97	14	2	1	5	1	2	
134	160.63	163.68	3.05	3.00	98	3.00	98	15	4	5	3	3	4	
134	163.68	166.73	3.05	3.10	102	3.10	102	15	4	5	3	3	2	
134	166.73	169.77	3.04	3.04	100	3.04	100	15	4	5	2	4	2	
134	169.77	172.82	3.05	3.05	100	3.05	100	15	4	5	3	3	3	
134	172.82	175.87	3.05	3.05	100	3.05	100	15	4	5	3	3	1	slip plane 30 to c.a.
134	175.87	178.92	3.05	3.05	100	3.05	100	15	4	5	2	3	4	
134	178.92	181.97	3.05	3.05	100	3.05	100	15	4	5	3	3	2	
134	181.97	185.01	3.04	3.04	100	3.04	100	15	4	5	3	3	2	
134	185.01	188.06	3.05	3.05	100	3.05	100	15	4	5	3	3	3	
134	188.06	191.11	3.05	3.05	100	3.05	100	15	4	5	1	3	4	
134	191.11	194.16	3.05	2.45	80	2.45	80	15	4	5	3	3	3	
134	194.16	197.21	3.05	3.09	101	3.09	101	15	4	5	10	4	3	
134	197.21	200.25	3.04	3.01	99	3.01	99	14	4	5	7	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
134	200.25	203.30	3.05	2.93	96	2.93	96	14	4	5	5	1	2	201.15 m - slip plane w/ talc 70 to c.a.
134	203.30	206.35	3.05	2.95	97	2.95	97	15	4	5	3	1	2	
134	206.35	209.40	3.05	3.03	99	3.03	99	15	4	5	4	3	3	
134	209.40	212.44	3.04	3.01	99	3.01	99	15	4	5	2	3	2	
134	212.44	215.44	3.00	3.03	101	3.03	101	14	4	5	7	3	2	
134	215.44	218.54	3.10	3.04	98	2.64	85	14	4	5	5	3	3	
134	218.54	221.59	3.05	2.93	96	2.93	96	14	4	5	7	1	3	
134	221.59	224.64	3.05	3.05	100	2.91	95	15	4	5	4	4	3	
134	224.64	227.69	3.05	3.01	99	2.82	92	14	4	5	6	3	3	
134	227.69	230.73	3.04	3.07	101	3.07	101	15	4	5	5	1	4	
134	230.73	233.78	3.05	2.94	96	2.94	96	13	4	5	11	1	2	
134	233.78	236.83	3.05	2.93	96	2.80	92	14	4	5	7	3	3	
134	236.83	239.88	3.05	3.01	99	2.97	97	14	4	5	6	4	3	
134	239.88	242.93	3.05	3.05	100	3.03	99	13	4	5	9	4	3	
134	242.93	245.97	3.04	3.04	100	3.04	100	14	4	5	7	1	3	
134	245.97	249.02	3.05	2.88	94	2.65	87	15	4	5	4	3	2	
134	249.02	252.07	3.05	2.90	95	2.88	94	14	4	5	8	1	3	
134	252.07	255.12	3.05	2.91	95	2.91	95	14	4	5	7	1	3	
134	255.12	258.17	3.05	3.03	99	3.03	99	15	4	5	6	3	3	
134	258.17	261.21	3.04	3.03	100	3.03	100	15	4	5	4	1	3	
134	261.21	264.26	3.05	3.02	99	2.93	96	15	4	5	6	3	3	
134	264.26	267.31	3.05	3.04	100	2.84	93	14	4	5	8	2	3	
134	267.31	270.36	3.05	3.00	98	2.98	98	14	4	5	6	1	3	
134	270.36	273.41	3.05	2.88	94	2.50	82	13	4	5	11	1	2	
134	273.41	276.45	3.04	3.04	100	3.04	100	13	2	4	15	5	3	275.04 m. - soft gouge for 0.5 m.
134	276.45	279.50	3.05	3.04	100	3.03	99	14	4	5	6	2	3	
134	279.50	282.55	3.05	2.92	96	2.92	96	13	4	5	10	2	3	
134	282.55	285.60	3.05	3.01	99	3.01	99	14	4	5	6	1	3	
134	285.60	288.65	3.05	2.97	97	2.97	97	15	4	5	4	2	2	
134	288.65	291.69	3.04	3.04	100	3.04	100	15	4	5	4	5	3	
134	291.69	294.74	3.05	3.01	99	3.01	99	15	4	5	2	5	3	
134	294.74	297.79	3.05	3.01	99	3.01	99	15	4	5	5	4	3	
134	297.79	300.84	3.05	2.97	97	2.97	97	15	4	5	4	1	2	
134	300.84	303.89	3.05	3.02	99	3.02	99	15	4	5	5	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
134	303.89	306.93	3.04	3.05	100	3.05	100	14	4	5	8	4	3	
134	306.93	309.98	3.05	3.03	99	3.03	99	15	4	5	4	4	3	
134	309.98	313.03	3.05	3.02	99	3.02	99	14	4	5	8	1	3	
134	313.03	316.07	3.04	2.98	98	2.92	96	14	4	5	6	2	3	
134	316.07	319.13	3.06	3.00	98	3.00	98	14	4	5	7	2	3	
134	319.13	322.17	3.04	3.01	99	3.01	99	14	4	5	8	2	3	
134	322.17	325.22	3.05	2.98	98	2.98	98	14	4	5	5	1	2	
134	325.22	328.27	3.05	3.05	100	3.05	100	15	4	5	4	2	3	
134	328.27	331.32	3.05	3.00	98	3.00	98	14	4	5	5	5	3	
134	331.32	334.37	3.05	3.00	98	3.00	98	15	4	5	4	5	3	
134	334.37	337.41	3.04	3.06	101	3.06	101	14	4	5	6	1	3	
134	337.41	340.46	3.05	3.01	99	2.51	82	14	4	5	8	1	2	
134	340.46	343.51	3.05	2.98	98	2.65	87	14	4	5	7	1	3	
134	343.51	346.56	3.05	3.00	98	2.96	97	14	4	5	8	2	3	
134	346.56	349.61	3.05	2.99	98	2.81	92	13	3	5	10	4	3	347.3 m. - 3 cm. wide gouge at 55 to c.a.
134	349.61	352.65	3.04	3.04	100	2.84	93	14	4	5	6	1	3	
134	352.65	355.70	3.05	3.01	99	2.73	90	14	4	5	7	1	3	
134	355.70	358.75	3.05	3.04	100	2.80	92	14	4	5	7	1	3	
134	358.75	361.80	3.05	3.02	99	3.00	98	14	4	5	9	2	3	358.5 m. - slip plane, little gouge, 75 c.a.
134	361.80	364.85	3.05	2.95	97	2.95	97	15	4	5	3	1	3	
134	364.85	367.89	3.04	3.04	100	2.76	91	14	4	5	10	4	3	366.90 m.- slip plane, 65 to c.a.
134	367.89	370.94	3.05	3.02	99	3.00	98	14	4	5	8	4	3	
134	370.94	373.99	3.05	3.00	98	2.74	90	6	3	5	50	5	3	gouge, clay & broken rock
134	373.99	377.04	3.05	2.88	94	2.65	87	13	4	5	12	3	3	
134	377.04	380.09	3.05	3.05	100	3.05	100	14	4	5	7	1	2	
134	380.09	383.13	3.04	3.03	100	3.03	100	14	4	5	8	1	2	
134	383.13	386.18	3.05	3.02	99	3.02	99	14	4	5	9	5	3	
134	386.18	389.23	3.05	3.01	99	3.01	99	14	4	5	6	4	3	
134	389.23	392.28	3.05	3.02	99	3.02	99	14	4	5	6	5	3	
134	392.28	395.33	3.05	2.89	95	2.65	87	14	4	5	5	1	2	
134	395.33	398.37	3.04	2.90	95	2.87	94	10	4	5	25	2	2	
134	398.37	401.42	3.05	3.10	102	2.95	97	14	4	5	7	2	3	
134	401.42	404.47	3.05	3.05	100	3.05	100	15	4	5	3	3	2	
134	404.47	407.52	3.05	2.75	90	2.75	90	14	4	5	6	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
134	407.52	410.57	3.05	3.05	100	3.05	100	14	4	5	5	3	3	
134	410.57	413.61	3.04	3.10	102	3.10	102	13	4	5	10	1	1	
134	413.61	416.66	3.05	3.05	100	3.05	100	14	4	5	7	3	3	
134	416.66	419.71	3.05	3.05	100	2.90	95	14	4	5	7	1	2	
134	419.71	422.76	3.05	3.05	100	3.05	100	14	4	5	7	1	3	
134	422.76	425.81	3.05	3.05	100	3.00	98	14	4	5	7	3	2	
134	425.81	428.85	3.04	3.04	100	3.04	100	13	4	3	10	1	3	
134	428.85	431.90	3.05	3.05	100	3.05	100	14	4	5	9	3	1	dykes with gypsum
134	431.90	434.95	3.05	3.05	100	3.02	99	14	4	5	7	2	1	dyke
134	434.95	438.00	3.05	3.05	100	3.05	100	14	4	5	5	1	3	
134	438.00	441.05	3.05	3.05	100	3.05	100	14	4	5	6	3	2	Py fracture fillings
134	441.05	444.10	3.05	3.05	100	3.00	98	14	4	5	4	3	3	
134	444.10	447.14	3.04	3.04	100	3.00	99	14	4	5	4	3	3	
134	447.14	450.19	3.05	3.10	102	3.05	100	14	4	5	6	3	2	
134	450.19	453.24	3.05	3.05	100	3.03	99	14	4	2	7	1	1	slip planes - graphite?
134	453.24	456.29	3.05	3.05	100	3.05	100	14	4	4	9	3	2	
134	456.29	459.33	3.04	3.04	100	3.04	100	14	4	3	9	3	1	gypsum slip plane
134	459.33	462.38	3.05	3.05	100	3.05	100	14	4	3	8	3	1	mud slip plane
134	462.38	465.43	3.05	3.05	100	3.05	100	14	0	0	8	3	1	mud seam <1 cm. wide
134	465.43	468.48	3.05	3.05	100	2.95	97	13	0	0	10	1	2	minor gouge
134	468.48	471.53	3.05	3.05	100	3.00	98	14	4	5	7	1	2	
134	471.53	474.57	3.04	3.04	100	3.04	100	14	4	5	5	1	2	
134	474.57	477.62	3.05	3.10	102	3.10	102	14	0	2	9	1	2	small 3 cm. fault zone
134	477.62	480.67	3.05	3.05	100	3.03	99	14	4	4	8	3	2	
134	480.67	483.72	3.05	3.05	100	3.05	100	14	4	4	8	3	2	minor mud seam <1 mm.
134	483.72	486.77	3.05	3.05	100	3.05	100	14	4	4	6	3	2	minor mud seam <1 mm.
134	486.77	489.81	3.04	3.00	99	3.00	99	15	4	4	4	1	2	
134	489.81	492.86	3.05	3.05	100	3.05	100	15	4	4	3	3	2	minor mud seam <1 mm.
134	492.86	495.91	3.05	3.05	100	3.05	100	15	4	4	3	3	2	
134	495.91	498.96	3.05	3.05	100	3.05	100	14	4	4	6	3	2	
134	498.96	502.01	3.05	3.05	100	3.03	99	14	4	3	7	3	1	healed fault gouge & minor mud seam
134	502.01	505.05	3.04	3.04	100	3.04	100	14	4	3	7	3	2	ground core due to re-drilling
134	505.05	508.10	3.05	3.05	100	3.02	99	14	4	3	7	3	1	
135	4.27	7.32	3.05	1.84	60	0.00	0	7	1	2	30	5	4	gouge and clay

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
135	7.32	10.36	3.04	2.87	94	0.83	27	9	2	3	30	1	2 gouge on fractures at 4.27 to 18.9 m.	
135	10.36	12.50	2.14	1.90	89	0.38	18	6	2	3	40	1	2	
135	12.50	14.02	1.52	1.57	103	0.78	51	9	2	3	16	1	1 weak slickensides	
135	14.02	17.06	3.04	3.08	101	1.73	57	12	3	4	18	2	1 weak slickensides	
135	17.06	18.90	1.84	1.70	92	0.40	22	10	2	3	16	1	2	
135	18.90	21.95	3.05	3.02	99	1.68	55	13	3	4	14	1	2	
135	21.95	24.38	2.43	2.33	96	2.20	91	14	3	5	5	1	2	
135	24.38	26.21	1.83	1.94	106	1.74	95	13	3	5	7	3	2 minor gouge	
135	26.21	29.26	3.05	3.00	98	2.95	97	15	3	5	4	1	2	
135	29.26	32.31	3.05	3.00	98	2.38	78	14	2	4	6	1	2 30.80 m. - 10 cm. fault gouge	
135	32.31	35.36	3.05	3.05	100	2.90	95	15	1	3	4	1	2 50% fault material, healed	
135	35.36	38.40	3.04	3.00	99	2.23	73	14	2	4	7	2	1 gouge on fractures	
135	38.40	41.45	3.05	2.90	95	2.46	81	13	2	4	10	1	2 gouge on fractures	
135	41.45	44.50	3.05	2.94	96	1.46	48	13	2	4	14	1	2 gouge on fractures	
135	44.50	47.55	3.05	2.93	96	1.77	58	12	1	3	16	1	2 50% fault gouge, brecciated	
135	47.55	50.60	3.05	3.02	99	2.34	77	14	3	5	9	1	2 slip planes	
135	50.60	53.64	3.04	3.05	100	2.88	95	15	3	5	5	1	2	
135	53.64	56.69	3.05	2.93	96	2.93	96	15	3	5	3	1	2	
135	56.69	59.74	3.05	2.97	97	2.97	97	15	3	5	2	1	3	
135	59.74	62.79	3.05	2.99	98	1.80	59	13	2	4	10	1	3 60.00 m. - 3 cm. of clay,	
135	62.79	65.53	2.74	2.60	95	1.58	58	11	2	4	18	1	2 minor gouge on fractures	
135	65.53	68.58	3.05	3.00	98	2.43	80	11	2	4	20	1	2 gouge on fractures	
135	68.58	71.63	3.05	3.05	100	1.50	49	10	2	3	30	1	2 30% gouge material	
135	71.63	74.68	3.05	3.05	100	2.60	85	11	3	5	16	3	3	
135	74.68	78.03	3.35	3.35	100	3.25	97	13	2	3	15	1	2 minor gouge on fractures	
135	78.03	81.08	3.05	3.05	100	2.55	84	13	2	3	12	5	4 brecciated unit w/ gouge on fractures	
135	81.08	84.12	3.04	3.04	100	2.45	81	10	2	3	30	5	4 1st half of interval same as above	
135	84.12	87.17	3.05	3.05	100	2.17	71	10	3	4	30	3	3 1st m. is broken core	
135	87.17	89.00	1.83	1.71	93	1.71	93	10	3	5	16	1	2 89.45-89.75 m. softer, brecciated rx	
135	89.00	92.05	3.05	3.15	103	3.15	103	14	3	5	7	1	3 90.23 m. - 1 cm. gouge at 35 to c.a.	
135	92.05	93.27	1.22	1.16	95	0.76	62	13	3	5	5	1	3	
135	93.27	96.32	3.05	3.02	99	3.00	98	14	3	5	7	3	3	
135	96.32	99.36	3.04	3.04	100	3.04	100	14	3	5	8	1	2 98.32 m. - 4 cm. gouge at 30 to c.a.	
135	99.36	102.41	3.05	3.05	100	3.05	100	15	4	5	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
135	102.41	105.46	3.05	3.02	99	3.02	99	14	4	4	10	2	3	
135	105.46	108.51	3.05	3.05	100	2.52	83	13	4	5	11	4	3	
135	108.51	111.56	3.05	3.05	100	2.43	80	10	4	5	30	1	3	
135	111.56	112.47	0.91	0.82	90	0.23	25	4	3	4	50	5		2 35% of interval is broken w/ gouge
135	112.47	115.52	3.05	3.05	100	1.53	50	10	3	4	30	5		3 first 0.5 m. is broken w/ gouge
135	115.52	117.65	2.13	2.10	99	1.95	92	14	2	4	7	1	2	
135	117.65	120.40	2.75	2.62	95	0.97	35	13	2	3	13	2		1 weak slick, 45 to c.a.
135	120.40	123.44	3.04	2.96	97	2.90	95	15	3	5	3	1	2	
135	123.44	126.80	3.36	3.33	99	3.33	99	15	4	6	1	1	3	
135	126.80	129.85	3.05	3.05	100	3.05	100	15	3	5	1	1	3	
135	129.85	132.90	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
135	132.90	135.95	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
135	135.95	137.77	1.82	1.63	90	1.49	82	14	3	5	4	1		4 137.60 m. - 50 cm. fault zone
135	137.77	139.29	1.52	1.73	114	0.98	64	7	3	5	26	1		4 blocky core
135	139.29	142.04	2.75	2.69	98	2.13	77	13	3	5	9	1	3	
135	142.04	145.08	3.04	3.05	100	2.84	93	15	3	5	5	1		1 slickenside, 45 to c.a.
135	145.08	146.91	1.83	1.97	108	0.57	31	9	2	4	22	1		3 minor gouge on fractures
135	146.91	149.96	3.05	2.87	94	2.49	82	12	2	5	15	1		2 minor gouge on fractures
135	149.96	151.18	1.22	1.12	92	1.00	82	13	3	5	4	1		3 vuggy material
135	151.18	154.23	3.05	2.94	96	2.54	83	14	3	5	7	1	4	
135	154.23	157.28	3.05	3.00	98	2.35	77	13	3	5	12	1	4	
135	157.28	158.34	1.06	1.05	99	0.67	63	7	1	3	17	1		4 gouge on weak slicks
135	158.34	159.11	0.77	0.34	44	0.00	0	4	1	3	20	1		3 blocky ground - mismatch
135	159.11	161.54	2.43	2.37	98	1.74	72	12	2	4	12	1	2	
135	161.54	163.37	1.83	1.74	95	0.88	48	7	2	4	25	1		3 20% fault gouge
135	163.37	166.42	3.05	2.94	96	2.80	92	14	3	4	6	1	3	
135	166.42	169.47	3.05	2.98	98	2.38	78	11	3	4	19	1		2 20% fault gouge
135	169.47	172.52	3.05	3.08	101	3.08	101	15	3	5	4	1		1 20 cm. of healed gouge, slicks
135	172.52	175.56	3.04	2.97	98	2.75	90	14	3	5	7	1		3 50 to c.a. slicks w/ +5 rake
135	175.56	178.61	3.05	3.03	99	2.70	89	13	3	4	12	1	2	
135	178.61	181.66	3.05	3.15	103	1.16	38	10	1	3	30	2		2 gouge on fractures, 30%
135	181.66	184.10	2.44	2.32	95	1.48	61	9	2	4	24	2		1 gouge on fractures, 30%
135	184.10	186.54	2.44	2.15	88	1.25	51	10	2	4	16	1		2 gouge on fractures, 30%
135	186.54	187.76	1.22	1.32	108	1.10	90	12	2	4	8	1		3 healed fault gouge, 10 cm.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
135	187.76	190.80	3.04	3.00	99	2.90	95	14	3	5	7	1	2	
135	190.80	193.85	3.05	3.05	100	3.05	100	15	4	5	3	1	2	
135	193.85	196.90	3.05	3.05	100	3.01	99	14	4	5	6	1	3	3 small section of gouge
135	196.90	199.95	3.05	3.00	98	2.93	96	15	4	5	5	1	3	
135	199.95	202.39	2.44	2.28	93	2.02	83	13	3	5	8	1	1	1 weak slicks
135	202.39	205.44	3.05	3.03	99	2.56	84	15	4	6	5	1	2	
135	205.44	207.26	1.82	1.88	103	1.88	103	14	4	6	2	1	2	
135	207.26	209.09	1.83	1.82	99	1.82	99	14	3	6	4	1	3	
135	209.09	212.14	3.05	3.05	100	3.05	100	15	3	6	4	1	4	
135	212.14	215.19	3.05	2.88	94	2.73	90	15	3	5	4	1	2	2 gouge on fractures
135	215.19	218.24	3.05	2.92	96	2.86	94	14	3	5	6	1	2	
135	218.24	221.28	3.04	2.90	95	1.28	42	10	3	5	25	1	3	3 10% of interval healed fault gouge
135	221.28	224.33	3.05	3.05	100	2.27	74	14	3	5	9	1	3	
135	224.33	227.38	3.05	3.05	100	2.51	82	14	3	5	6	1	3	
135	227.38	230.43	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
135	230.43	233.48	3.05	3.05	100	3.05	100	14	3	5	6	1	3	
135	233.48	236.52	3.04	3.04	100	3.05	100	14	3	5	7	1	3	
135	236.52	239.57	3.05	2.96	97	2.53	83	14	2	4	8	5	3	3 healed fault gouge 30 to 35c.a.last m.
135	239.57	242.62	3.05	3.05	100	3.05	100	15	2	4	5	5	3	3 fault gouge
135	242.62	245.67	3.05	3.05	100	3.05	100	14	2	4	9	5	3	3 fault gouge
135	245.67	248.72	3.05	3.05	100	3.05	100	14	2	4	8	5	3	3 fault gouge
135	248.72	251.76	3.04	3.04	100	2.57	85	14	2	4	10	5	3	3 fault gouge
135	251.76	254.81	3.05	3.05	100	2.65	87	14	2	4	10	5	3	3 252 m.-slip plane at 15 c.a. fault
135	254.81	257.86	3.05	3.05	100	2.51	82	13	2	4	12	5	3	3 fault gouge
135	257.86	260.91	3.05	3.05	100	3.05	100	14	2	4	9	5	3	3 fault gouge
135	260.91	263.96	3.05	3.03	99	3.00	98	14	2	4	10	5	3	3 fault gouge
135	263.96	267.00	3.04	3.04	100	2.25	74	13	2	4	12	5	3	3 fault gouge
135	267.00	270.05	3.05	3.00	98	1.36	45	8	2	4	40	5	3	3 fault gouge
135	270.05	273.10	3.05	2.98	98	1.73	57	10	2	4	20	5	3	3 intermittent shearing & fault gouge
135	273.10	276.15	3.05	2.45	80	0.40	13	6	2	4	50	5	3	3 50% rubble
135	276.15	279.20	3.05	2.85	93	2.01	66	7	2	4	50	5	3	
135	279.20	282.24	3.04	3.04	100	3.04	100	14	2	4	10	5	3	3 intermittent shearing & fault gouge
135	282.24	285.29	3.05	3.05	100	2.79	91	14	2	4	9	1	3	3 intermittent shearing & fault gouge
135	285.29	288.34	3.05	3.05	100	3.03	99	14	2	4	7	1	3	3 intermittent shearing & fault gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
135	288.34	291.39	3.05	2.82	92	1.91	63	9	2	4	30	5	3 intermittent shearing & fault gouge	
135	291.39	294.44	3.05	3.05	100	3.00	98	14	2	4	9	5	3 intermittent shearing & fault gouge	
135	294.44	297.48	3.04	2.85	94	0.90	30	7	2	4	50	5	3 intermittent shearing & fault gouge	
135	297.48	300.53	3.05	2.93	96	0.25	8	7	2	4	50	5	3 intermittent shearing & fault gouge	
135	300.53	303.58	3.05	2.75	90	1.33	44	7	2	4	50	5	3 intermittent shearing & fault gouge	
135	303.58	306.63	3.05	3.05	100	1.34	44	12	2	4	20	5	3 intermittent shearing & fault gouge	
135	306.63	309.68	3.05	3.05	100	2.05	67	13	2	4	13	5	3 intermittent shearing & fault gouge	
135	309.68	312.72	3.04	3.10	102	1.52	50	7	0	1	50	2	2 fault gouge, healed, rubble	
135	312.72	315.77	3.05	3.02	99	1.53	50	7	0	1	50	1	2 fault gouge, healed, rubble	
135	315.77	318.82	3.05	3.05	100	2.91	95	13	2	2	14	1	1 mud slip plane	
135	318.82	321.87	3.05	3.18	104	2.75	90	12	2	2	18	2	2 rubble rock	
135	321.87	324.92	3.05	3.05	100	2.73	90	14	0	1	8	1	2 healed fault	
135	324.92	327.96	3.04	3.10	102	1.67	55	12	1	1	18	1	3 healed fault gouge	
135	327.96	330.40	2.44	2.50	102	1.78	73	10	0	1	30	1	2	
135	330.40	333.45	3.05	3.10	102	2.20	72	13	2	1	10	3	1 gypsum surface fracture, healed gouge	
135	333.45	336.80	3.35	3.35	100	2.25	67	12	0	1	17	3	2 healed gouge & gouge	
135	336.80	339.85	3.05	3.05	100	1.90	62	10	0	1	25	1	2 gouge, broken rock	
135	339.85	342.90	3.05	3.05	100	1.20	39	10	0	1	25	1	2 gouge, broken rock	
135	342.90	345.95	3.05	3.25	107	1.66	54	10	0	1	25	1	2 broken rock	
135	345.95	349.30	3.35	3.45	103	2.74	82	11	0	1	20	1	2	
135	349.30	352.35	3.05	3.00	98	2.50	82	13	0	1	13	1	1 gouge	
135	352.35	355.40	3.05	3.10	102	2.20	72	11	3	3	20	1	1 gouge. minor graphite on slip	
135	355.40	356.92	1.52	1.60	105	1.12	74	11	3	4	10	1	3	
135	356.92	359.97	3.05	2.93	96	2.75	90	14	3	4	8	1	3	
135	359.97	362.41	2.44	2.30	94	1.27	52	12	3	4	11	3	2	
135	362.41	364.54	2.13	2.35	110	2.03	95	14	3	4	8	3	2	
135	364.54	368.20	3.66	2.85	78	2.65	72	14	3	4	11	1	2 graphitic slip plane	
135	368.20	370.64	2.44	3.15	129	2.09	86	10	2	2	25	3	2 graphitic slip plane	
136	4.27	6.10	1.83	0.95	52	0.95	52	14	0	1	3	2	1 fault gouge	
136	6.10	8.23	2.13	2.25	106	1.45	68	10	0	1	16	2	2 fault gouge	
136	8.23	10.97	2.74	2.90	106	0.95	35	7	0	2	50	1	2 broken rock & fault gouge	
136	10.97	13.11	2.14	1.75	82	0.20	9	8	0	1	25	1	2 fault gouge up to 1 cm.	
136	13.11	15.54	2.43	2.41	99	1.50	62	5	0	1	15	1	3 fault gouge up to 10 cm.	
136	15.54	16.15	0.61	0.16	26	0.00	0	2	0	1	15	1	1 fault gouge & broken rock	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
136	16.15	19.20	3.05	2.95	97	2.50	82	12	2	3	17	1	2	2 healed gouge & mud surfaces
136	19.20	22.25	3.05	3.10	102	1.87	61	10	2	3	24	1	2	2 healed gouge & slip planes
136	22.25	25.30	3.05	3.05	100	1.98	65	10	0	1	25	1	2	2 fault gouge & healed gouge
136	25.30	27.13	1.83	1.80	98	0.74	40	10	0	1	17	1	2	2 fault gouge
136	27.13	29.57	2.44	2.40	98	2.40	98	14	4	5	7	1	2	2
136	29.57	32.61	3.04	3.03	100	2.15	71	11	4	5	18	1	2	2 some broken rock
136	32.61	35.66	3.05	3.12	102	2.62	86	13	4	5	14	1	2	2
136	35.66	37.49	1.83	1.68	92	1.06	58	12	0	1	10	3	2	2 fault gouge
136	37.49	40.54	3.05	3.05	100	2.63	86	13	4	5	13	1	2	2
136	40.54	41.76	1.22	1.22	100	0.95	78	13	4	5	6	3	2	2
136	41.76	44.81	3.05	3.15	103	2.20	72	10	2	3	26	1	2	2 healed fault gouge
136	44.81	46.63	1.82	1.50	82	0.42	23	8	0	1	19	1	2	2 fault gouge
136	46.63	49.07	2.44	2.24	92	1.80	74	13	3	5	9	1	2	2
136	49.07	50.90	1.83	1.69	92	1.05	57	11	3	5	12	1	2	2
136	50.90	53.95	3.05	3.05	100	2.77	91	14	3	4	6	1	2	2
136	53.95	57.00	3.05	3.00	98	1.74	57	13	1	3	11	2	2	2
136	57.00	60.05	3.05	2.95	97	2.78	91	14	2	3	7	2	2	1 slip plane, healed gouge
136	60.05	63.09	3.04	2.95	97	2.10	69	14	3	5	6	2	2	1 slip plane, healed gouge
136	63.09	66.14	3.05	3.00	98	0.80	26	9	2	4	30	3	2	2 healed fault gouge
136	66.14	69.19	3.05	3.10	102	2.20	72	11	2	4	19	1	2	1 slip plane, rake + 45 to c.a.
136	69.19	72.24	3.05	2.90	95	1.50	49	12	2	4	16	1	2	2 gouge on fractures
136	72.24	75.29	3.05	2.82	92	1.58	52	12	2	4	15	1	2	2 gouge on fractures
136	75.29	78.33	3.04	2.84	93	1.57	52	12	2	4	17	1	2	2 gouge on fractures
136	78.33	81.38	3.05	2.97	97	2.76	90	13	3	5	12	1	2	2 gouge on fractures
136	81.38	84.43	3.05	2.90	95	2.60	85	13	2	4	13	1	2	2 gouge on fractures
136	84.43	87.48	3.05	2.94	96	0.86	28	13	2	4	14	3	2	2
136	87.48	90.53	3.05	2.95	97	2.20	72	11	3	4	19	1	2	2
136	90.53	93.57	3.04	2.98	98	2.10	69	14	2	4	9	1	2	1 slip plane, minor gouge
136	93.57	96.62	3.05	2.94	96	2.10	69	13	2	4	12	2	2	1 slip plane, minor gouge
136	96.62	99.67	3.05	3.02	99	2.28	75	13	2	4	13	1	2	2 healed fault gouge
136	99.67	102.72	3.05	3.00	98	2.80	92	13	3	5	11	1	2	2
136	102.72	105.77	3.05	3.00	98	2.68	88	14	2	4	6	1	2	2
136	105.77	108.81	3.04	3.05	100	2.26	74	12	2	4	18	1	2	2 20 cm. fault gouge
136	108.81	111.86	3.05	2.82	92	2.46	81	13	2	4	12	1	2	1 weak slicks

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
136	111.86	114.91	3.05	3.05	100	2.89	95	14	2	4	10	1	2	
136	114.91	117.96	3.05	3.05	100	1.26	41	10	2	4	23	1	2	2 dyke; 5 cm fault gouge at 115.37 m.
136	117.96	121.01	3.05	2.68	88	2.01	66	10	3	4	18	4	3	
136	121.01	124.05	3.04	3.04	100	1.71	56	10	2	4	30	1	2	
136	124.05	127.10	3.05	2.42	79	1.82	60	9	2	4	30	5	3	20% broken core; brecciated
136	127.10	130.15	3.05	2.92	96	2.06	68	12	2	4	15	5	3	40% healed gouge
136	130.15	133.20	3.05	3.05	100	3.05	100	14	2	4	8	4	3	50% healed gouge
136	133.20	136.25	3.05	2.82	92	1.45	48	9	2	4	30	5	3	
136	136.25	139.29	3.04	2.58	85	1.81	60	9	2	4	30	5	3	30% healed gouge
136	139.29	142.34	3.05	3.01	99	1.86	61	10	2	4	30	5	3	30% healed gouge
136	142.34	145.39	3.05	3.05	100	1.95	64	13	2	4	11	1	3	144.28 m. - slick15 to ca; 50% gouge
136	145.39	148.44	3.05	3.05	100	2.37	78	13	3	4	12	1	3	10% healed gouge
136	148.44	151.49	3.05	3.00	98	1.43	47	10	2	4	25	3	3	10% broken core, minor gouge
136	151.49	154.53	3.04	2.99	98	2.38	78	12	3	4	15	1	2	154 m.-minor gouge 80 to c.a.
136	154.53	157.58	3.05	3.05	100	1.35	44	10	2	4	30	5	3	50% healed gouge
136	157.58	160.63	3.05	3.05	100	2.21	72	13	2	4	8	1	2	158.75 m.&159.02 m. 45c.a. slip
136	160.63	163.68	3.05	3.03	99	3.03	99	15	3	5	5	1	3	170.0m.-slip plane, minor gouge 45ca
136	163.68	166.73	3.05	2.83	93	1.80	59	10	3	5	20	1	3	
136	166.73	169.78	3.05	3.05	100	2.61	86	15	3	5	4	1	3	
136	169.78	172.82	3.04	3.00	99	3.00	99	15	3	5	3	1	3	
136	172.82	175.87	3.05	3.05	100	2.36	77	14	3	5	7	1	3	172.9m.- slip plane at 20 to c.a.
136	175.87	178.92	3.05	3.05	100	3.05	100	15	3	5	4	1	3	
136	178.92	181.97	3.05	3.05	100	3.00	98	15	3	5	3	1	3	
136	181.97	185.01	3.04	3.04	100	3.04	100	15	3	5	4	1	3	
136	185.01	188.06	3.05	3.05	100	2.55	84	14	3	5	10	1	3	
136	188.06	191.11	3.05	3.05	100	2.45	80	14	4	5	9	5	3	
136	191.11	194.16	3.05	3.05	100	2.48	81	14	3	4	8	1	2	191.4-191.6m.- 10 cm. irregular gouge
136	194.16	197.21	3.05	3.05	100	2.29	75	13	4	5	14	4	3	
136	197.21	200.25	3.04	3.04	100	1.91	63	10	3	5	25	2	3	
136	200.25	203.30	3.05	2.02	66	0.64	21	4	2	3	50	5	2	85% broken core, 20% healed gouge
136	203.30	206.35	3.05	2.85	93	2.00	66	10	3	3	25	2	2	first 0.25 m. is rubble
136	206.35	209.40	3.05	3.05	100	2.61	86	14	3	5	6	1	3	
136	209.40	212.45	3.05	3.05	100	3.05	100	14	2	4	7	5	3	30% healed gouge
136	212.45	215.49	3.04	3.01	99	2.14	70	13	3	5	12	5	3	10% healed gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
136	215.49	218.54	3.05	2.09	69	1.83	60	12	4	5	13	1	3	3 minor gouge on fractures
136	218.54	221.59	3.05	3.03	99	3.02	99	13	3	5	11	1	2	
136	221.59	224.64	3.05	3.05	100	2.19	72	13	3	5	15	1	3	3 225 m.-10 cm. healed gouge
136	224.64	227.69	3.05	3.05	100	2.21	72	14	3	5	8	1	3	
136	227.69	230.73	3.04	3.01	99	1.97	65	14	3	5	6	1	3	3 minor gouge in fractures
136	230.73	233.78	3.05	3.05	100	2.50	82	13	3	5	12	1	3	
136	233.78	236.83	3.05	3.05	100	2.11	69	13	3	5	15	1	3	
136	236.83	239.88	3.05	3.05	100	2.29	75	14	3	5	10	1	2	
136	239.88	242.93	3.05	3.05	100	1.22	40	10	3	4	30	5	3	3 10% broken rock; minor gouge
136	242.93	245.97	3.04	2.92	96	2.00	66	13	3	4	10	1	3	
136	245.97	249.02	3.05	3.05	100	1.83	60	14	4	5	10	1	3	
136	249.02	252.07	3.05	3.05	100	3.05	100	14	4	5	7	1	3	2 minor gouge on some fractures
136	252.07	255.12	3.05	3.03	99	2.06	68	10	4	5	30	5	3	3 10% broken core
136	255.12	258.17	3.05	2.75	90	1.05	34	7	3	4	50	5	3	3 40% broken core; 257.5 m. - gouge
136	258.17	261.27	3.10	3.02	97	1.65	53	10	3	4	30	5	3	
136	261.27	264.26	2.99	2.99	100	1.02	34	7	3	4	50	5	3	3 30% broken core w/ some gouge
136	264.26	267.31	3.05	3.02	99	1.20	39	10	4	5	30	5	3	
136	267.31	270.36	3.05	2.90	95	2.35	77	12	4	5	15	2	3	
136	270.36	273.41	3.05	2.85	93	1.83	60	9	3	4	30	5	3	
136	273.41	275.84	2.43	2.38	98	1.44	59	6	3	4	50	5	3	3 last 0.5 m. is rubble w/ gouge
136	275.84	278.59	2.75	2.30	84	1.00	36	6	4	5	50	4	3	3 last 0.25 m. is rubble w/ gouge
136	278.59	281.64	3.05	3.05	100	2.12	70	10	4	5	30	1	3	
136	281.64	284.68	3.04	3.04	100	2.25	74	14	2	3	6	5	3	3 50% healed fault gouge
136	284.68	286.51	1.83	1.35	74	1.12	61	10	3	4	10	5	3	
136	286.51	288.65	2.14	1.65	77	1.15	54	9	1	3	20	5	3	3 healed fault gouge
136	288.65	291.69	3.04	3.04	100	3.00	99	14	1	3	6	5	3	3 healed fault gouge
136	291.69	294.74	3.05	2.95	97	2.57	84	14	1	3	6	4	4	4 healed fault gouge
136	294.74	297.79	3.05	3.05	100	2.20	72	11	1	3	20	4	4	4 healed fault gouge
136	297.79	300.84	3.05	3.05	100	1.88	62	14	1	3	10	4	4	4 healed fault gouge
136	300.84	303.89	3.05	2.75	90	1.54	50	10	1	3	25	4	4	4 healed fault gouge
136	303.89	306.93	3.04	2.82	93	2.01	66	2	1	3	50	4	4	4 healed fault gouge
136	306.93	309.68	2.75	2.05	75	0.34	12	2	1	3	50	4	4	4 healed fault gouge
136	309.68	312.72	3.04	3.02	99	2.30	76	13	1	3	15	4	4	4 healed fault gouge
136	312.72	316.08	3.36	3.20	95	1.42	42	2	1	3	50	4	4	4 healed fault gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
136	316.08	319.13	3.05	2.94	96	2.38	78	14	1	3	8	4	4	4 healed fault gouge
136	319.13	322.17	3.04	3.04	100	2.68	88	14	1	3	7	4	4	4 healed fault gouge
136	322.17	325.22	3.05	3.05	100	2.78	91	13	1	3	13	4	4	4 healed fault gouge
136	325.22	328.27	3.05	3.05	100	2.49	82	14	1	3	6	4	4	4 healed fault gouge
136	328.27	331.32	3.05	3.03	99	2.82	92	15	1	3	5	4	4	4 healed fault gouge
136	331.32	334.37	3.05	3.06	100	3.02	99	14	1	3	8	4	4	4 healed fault gouge
136	334.37	337.41	3.04	3.04	100	2.36	78	13	1	3	12	4	4	4 healed fault gouge
136	337.41	340.46	3.05	2.97	97	2.97	97	14	1	3	6	4	4	4 healed fault gouge
136	340.46	343.51	3.05	2.94	96	2.94	96	15	1	3	4	4	4	4 healed fault gouge
136	343.51	346.56	3.05	3.05	100	3.05	100	14	1	3	7	4	3	3 healed fault gouge
136	346.56	349.61	3.05	3.05	100	3.05	100	15	1	3	4	4	3	3 healed fault gouge
136	349.61	352.65	3.04	3.04	100	3.02	99	15	1	3	5	4	3	3 healed fault gouge
136	352.65	355.70	3.05	3.01	99	2.94	96	14	1	3	9	4	4	4 healed fault gouge
136	355.70	358.75	3.05	3.02	99	2.96	97	15	1	3	4	4	3	3 healed fault gouge
136	358.75	361.80	3.05	2.93	96	2.93	96	14	1	3	7	4	3	3 healed fault gouge
136	361.80	364.85	3.05	3.05	100	2.72	89	9	1	3	30	4	3	3 healed fault gouge
136	364.85	367.89	3.04	3.01	99	2.42	80	12	1	3	17	4	3	3 healed fault gouge
136	367.89	370.94	3.05	3.05	100	2.97	97	15	1	3	6	2	3	3 healed fault gouge
136	370.94	373.99	3.05	3.05	100	3.05	100	13	1	3	11	1	3	3 healed fault gouge
136	373.99	377.04	3.05	3.05	100	2.90	95	14	1	3	6	4	3	3 healed fault gouge
136	377.04	380.09	3.05	3.02	99	2.81	92	14	1	3	7	5	3	3 healed fault gouge
136	380.09	383.13	3.04	3.04	100	2.62	86	13	1	3	11	5	3	3 healed fault gouge
137	5.49	8.23	2.74	1.30	47	0.00	0	5	3	4	50	5	3	3 broken core
137	8.23	11.28	3.05	2.98	98	0.00	0	7	3	4	50	5	3	3 broken core
137	11.28	14.23	2.95	2.95	100	1.94	66	9	3	5	30	5	3	3 some broken core
137	14.23	17.37	3.14	3.07	98	1.81	58	10	3	5	22	1	3	3
137	17.37	20.42	3.05	2.95	97	1.45	48	10	3	5	30	1	3	3 18.45 m.-slip plane at 45 to c.a.
137	20.42	23.47	3.05	3.05	100	2.61	86	13	3	5	15	2	3	3 21.0 m.- gouge material
137	23.47	26.52	3.05	3.05	100	2.48	81	14	3	5	10	1	3	3
137	26.52	29.57	3.05	3.05	100	2.02	66	12	3	5	19	1	2	2
137	29.57	32.61	3.04	3.04	100	1.82	60	13	3	5	12	1	2	2
137	32.61	35.66	3.05	3.05	100	2.39	78	13	3	5	13	1	3	3
137	35.66	38.71	3.05	3.03	99	2.48	81	13	4	5	14	1	3	3
137	38.71	41.76	3.05	3.05	100	2.62	86	14	4	5	8	1	3	3

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
137	41.76	44.81	3.05	2.95	97	2.95	97	14	4	5	6	5	3	
137	44.81	47.85	3.04	3.04	100	2.33	77	14	4	5	9	1	2	
137	47.85	50.90	3.05	3.04	100	2.60	85	14	4	5	7	1	2	2 49.35 m.-4 cm. wide gouge
137	50.90	53.95	3.05	3.05	100	2.57	84	14	4	5	6	1	2	
137	53.95	57.00	3.05	3.05	100	3.05	100	14	4	5	5	1	3	
137	57.00	60.05	3.05	3.05	100	2.19	72	13	4	5	12	1	3	
137	60.05	63.09	3.04	2.95	97	2.95	97	14	4	5	6	1	2	
137	63.09	66.14	3.05	3.05	100	3.05	100	14	4	5	7	1	2	
137	66.14	69.19	3.05	2.97	97	2.78	91	14	4	5	9	1	2	
137	69.19	72.24	3.05	3.05	100	2.54	83	14	4	5	7	1	2	2 15-20% gouge throughout interval
137	72.24	75.29	3.05	2.85	93	2.46	81	13	4	5	12	1	3	3 73.72 m.-slip plane at 60 to c.a.
137	75.29	78.33	3.04	3.04	100	2.87	94	14	4	5	9	5	2	
137	78.33	81.38	3.05	3.05	100	3.02	99	14	4	5	6	1	2	
137	81.38	84.43	3.05	2.99	98	2.58	85	14	4	5	5	1	2	
137	84.43	87.48	3.05	3.01	99	2.48	81	14	4	5	8	1	2	
137	87.48	90.53	3.05	3.05	100	2.37	78	13	4	5	11	1	3	
137	90.53	93.57	3.04	3.04	100	2.49	82	13	4	5	13	1	3	
137	93.57	96.62	3.05	3.08	101	2.52	83	14	5	5	10	1	2	2 dyke
137	96.62	99.67	3.05	2.97	97	1.94	64	12	4	5	15	1	2	
137	99.67	102.72	3.05	3.05	100	2.73	90	14	4	5	10	1	3	
137	102.72	105.77	3.05	3.05	100	2.45	80	12	4	5	17	5	2	
137	105.77	108.81	3.04	3.04	100	2.41	79	14	4	5	9	5	3	3 106.5 m.-2-3 cm. fault gouge 20 c.a.
137	108.81	111.86	3.05	3.05	100	2.54	83	13	4	5	12	1	3	
137	111.86	114.91	3.05	3.05	100	2.32	76	14	4	5	9	1	2	
137	114.91	117.96	3.05	3.05	100	2.05	67	13	4	5	13	1	3	3 115.0 m.-2 cm. fault gouge 40 to c.a.
137	117.96	121.01	3.05	3.05	100	2.78	91	10	4	5	25	5	3	
137	121.01	124.05	3.04	2.65	87	1.33	44	7	4	5	50	1	2	2 25% broken core
137	124.05	127.10	3.05	3.05	100	2.73	90	13	4	5	12	1	3	
137	127.10	130.15	3.05	3.05	100	2.27	74	12	4	5	20	1	2	
137	130.15	133.20	3.05	3.00	98	1.99	65	12	4	5	18	1	2	
137	133.20	136.25	3.05	3.05	100	1.96	64	13	4	5	11	1	3	
137	136.25	139.29	3.04	3.04	100	2.48	82	14	4	5	10	1	2	
137	139.29	142.34	3.05	3.05	100	2.03	67	14	4	5	10	5	3	3 140.0 m.-slip plane at 40 c.a.,rake-5
137	142.34	145.39	3.05	3.05	100	3.00	98	14	4	5	7	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
137	145.39	148.44	3.05	3.05	100	3.05	100	14	4	5	10	2	3	
137	148.44	151.49	3.05	3.05	100	2.62	86	13	4	5	12	1	2	
137	151.49	154.53	3.04	3.04	100	2.50	82	13	4	5	11	1	2	
137	154.53	157.58	3.05	3.15	103	2.93	96	14	4	5	10	1	2	
137	157.58	160.63	3.05	3.00	98	2.33	76	13	3	5	15	1	3	158.6 m.- 5-6 cm. fault gouge at 40c.a.
137	160.63	163.68	3.05	2.98	98	1.13	37	8	3	5	40	5	3	
137	163.68	166.73	3.05	3.05	100	2.02	66	12	4	5	16	1	3	
137	166.73	169.77	3.04	3.04	100	1.56	51	10	4	5	22	1	2	
137	169.77	172.82	3.05	3.05	100	3.05	100	13	4	5	12	1	3	
137	172.82	175.87	3.05	3.05	100	3.05	100	13	4	5	11	1	3	
137	175.87	178.92	3.05	3.02	99	2.78	91	12	4	5	20	1	3	
137	178.92	181.97	3.05	3.05	100	1.55	51	14	4	5	8	1	2	
137	181.97	185.01	3.04	3.05	100	2.21	73	10	3	5	30	1	2	
137	185.01	188.06	3.05	3.05	100	1.81	59	10	2	4	30	5	3	3 fault gouge ± brecciated
137	188.06	191.11	3.05	3.00	98	3.00	98	13	2	4	11	5	3	3 fault gouge ± brecciated
137	191.11	194.16	3.05	3.05	100	2.32	76	14	2	4	10	5	3	3 fault gouge ± brecciated
137	194.16	197.21	3.05	3.05	100	2.52	83	15	2	4	5	5	3	3 fault gouge ± brecciated
137	197.21	200.25	3.04	2.97	98	2.45	81	14	2	4	6	5	3	3 fault gouge ± brecciated
138	5.49	7.92	2.43	1.12	46	0.00	0	7	0	3	40	1	3	3 overburden
138	7.92	9.75	1.83	0.08	4	0.00	0	2	0	3	8	2	3	3 casing ends
138	9.75	12.19	2.44	0.79	32	0.00	0	5	0	2	30	1	3	3 50% fault gouge
138	12.19	12.50	0.31	0.04	13	0.00	0	5	0	2	10	1	2	2 100% fault gouge
138	12.50	14.93	2.43	1.74	72	0.00	0	9	2	4	24	1	2	2 gouge on fractures
138	14.93	17.07	2.14	1.46	68	0.00	0	7	1	3	40	1	2	2 20% fault gouge
138	17.07	17.68	0.61	0.62	102	0.00	0	5	2	3	18	1	3	3
138	17.68	19.20	1.52	0.90	59	0.40	26	7	1	3	15	1	1	1 30% fault gouge, weak slick
138	19.20	21.34	2.14	1.17	55	0.20	9	7	1	2	18	1	2	2 30% fault gouge, weak slick
138	21.34	22.56	1.22	0.84	69	0.00	0	6	1	3	20	1	2	2 30% fault gouge, weak slick
138	22.56	23.77	1.21	1.04	86	0.48	40	10	2	4	8	1	2	2 minor gouge
138	23.77	26.21	2.44	2.44	100	1.32	54	10	2	4	18	2	2	2 minor gouge
138	26.21	29.26	3.05	3.02	99	1.75	57	13	3	4	13	1	1	1
138	29.26	32.31	3.05	2.92	96	1.55	51	13	3	4	14	1	2	2
138	32.31	34.75	2.44	2.06	84	0.40	16	7	1	3	40	1	1	1 healed breccia, no gouge
138	34.75	35.66	0.91	0.85	93	0.27	30	9	3	4	10	1	2	2 minor gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
138	35.66	38.40	2.74	2.70	99	1.07	39	12	2	4	15	1	1	30% gouge, weak slicks
138	38.40	38.86	0.46	0.33	72	0.00	0	6	2	4	7	1	2	20% gouge
138	38.86	41.45	2.59	2.36	91	1.74	67	12	3	5	13	3	1	
138	41.45	44.50	3.05	2.90	95	1.86	61	12	2	4	15	3	1	
138	44.50	47.55	3.05	2.70	89	1.92	63	13	2	4	13	1	3	
138	47.55	50.60	3.05	2.91	95	2.13	70	11	2	3	18	1	2	healed gouge
138	50.60	52.73	2.13	2.10	99	0.65	31	7	2	3	30	1	2	rubble, minor fault gouge
138	52.73	53.95	1.22	1.08	89	0.16	13	5	2	3	34	1	2	rubble, minor fault gouge
138	53.95	57.00	3.05	2.64	87	0.80	26	10	2	4	26	1	2	
138	57.00	58.83	1.83	1.73	95	0.97	53	12	3	5	9	1	3	
138	58.83	61.87	3.04	2.84	93	1.49	49	13	2	4	14	1	2	minor gouge on fractures
138	61.87	64.92	3.05	2.97	97	2.46	81	14	2	4	9	1	2	minor gouge on fractures
138	64.92	68.28	3.36	3.15	94	1.75	52	13	2	4	14	1	2	minor gouge on fractures
138	68.28	69.49	1.21	0.97	80	0.18	15	7	2	3	15	1	2	20% healed gouge
138	69.49	71.93	2.44	2.18	89	1.29	53	12	2	4	12	1	3	minor gouge on fractures
138	71.93	74.07	2.14	2.28	107	1.55	72	13	2	4	9	1	3	minor gouge on fractures
138	74.07	77.11	3.04	2.70	89	2.50	82	15	3	4	4	1	3	minor gouge on fractures
138	77.11	80.16	3.05	3.00	98	2.67	88	14	2	4	10	1	3	minor gouge on fractures
138	80.16	83.21	3.05	2.86	94	2.32	76	13	2	4	13	1	2	minor gouge on fractures
138	83.21	86.26	3.05	2.90	95	2.05	67	12	2	4	16	1	1	20% healed gouge. weak slicks
138	86.26	89.31	3.05	2.76	90	1.87	61	11	3	4	19	1	1	weak slickensides
138	89.31	92.66	3.35	3.05	91	1.61	48	10	2	3	25	1	2	
138	92.66	94.79	2.13	1.94	91	0.40	19	10	2	3	18	1	2	
138	94.79	97.84	3.05	2.80	92	1.38	45	11	2	4	21	1	2	
138	97.84	100.89	3.05	2.78	91	1.63	53	10	2	4	24	2	2	
138	100.89	102.41	1.52	1.47	97	0.83	55	10	2	4	13	1	2	
138	102.41	105.46	3.05	2.93	96	1.68	55	11	2	4	18	1	2	
138	105.46	107.29	1.83	1.85	101	0.96	52	10	2	4	19	1	2	
138	107.29	110.34	3.05	2.34	77	1.08	35	10	2	4	24	1	2	
138	110.34	112.78	2.44	2.20	90	1.28	52	10	2	4	18	1	2	
138	112.78	114.60	1.82	1.76	97	1.10	60	10	2	4	13	1	2	
138	114.60	117.65	3.05	2.72	89	1.58	52	10	2	4	20	1	2	
138	117.65	120.70	3.05	2.96	97	2.20	72	10	1	3	24	5	4	healed fault gouge
138	120.70	123.75	3.05	3.08	101	3.08	101	15	1	3	5	5	4	healed fault gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
138	123.75	126.80	3.05	2.98	98	2.98	98	14	2	3	6	5	4	4 healed fault gouge
138	126.80	129.84	3.04	3.04	100	3.03	100	15	2	3	5	5	4	4 healed fault gouge
138	129.84	132.89	3.05	3.04	100	3.02	99	14	2	3	6	1	2	2 healed fault gouge
138	132.89	135.94	3.05	3.04	100	3.04	100	14	2	3	7	1	1	1 healed fault gouge, 45 c.a. slicks
138	135.94	138.99	3.05	3.04	100	2.56	84	14	1	4	6	1	1	1 healed fault gouge, 50 c.a. slicks
138	138.99	142.04	3.05	3.04	100	3.04	100	15	2	4	5	1	1	1 50% competent, weak slicks
138	142.04	145.08	3.04	3.00	99	2.82	93	14	2	3	6	1	1	1 healed gouge, weak slicks
138	145.08	148.13	3.05	3.05	100	3.05	100	15	2	3	4	1	2	2 healed gouge, weak slicks
138	148.13	151.18	3.05	3.05	100	3.05	100	15	2	4	3	1	3	3 50% competent
138	151.18	154.23	3.05	3.05	100	3.05	100	15	2	3	4	5	4	4 healed gouge with solid rock
138	154.23	157.28	3.05	3.05	100	3.05	100	15	2	3	4	1	1	1 healed gouge, slick gouge
138	157.28	160.32	3.04	3.04	100	2.98	98	14	2	4	5	1	2	2 healed gouge, slick gouge
138	160.32	163.37	3.05	3.05	100	3.05	100	15	2	4	5	1	2	2 healed gouge, slick gouge
138	163.37	166.42	3.05	3.05	100	3.05	100	15	2	4	4	1	2	2 healed gouge, slick gouge
138	166.42	169.47	3.05	3.05	100	2.90	95	15	2	4	5	1	1	1 gouge on weak slicks
138	169.47	172.52	3.05	3.05	100	2.61	86	13	2	4	12	1	2	2
138	172.52	174.96	2.44	2.47	101	1.64	67	13	2	4	13	1	2	2
138	174.96	177.99	3.03	2.93	97	2.12	70	13	2	4	12	1	1	1 45 to c.a. slicks, no rake
138	177.99	180.04	2.05	2.92	142	2.92	142	14	2	4	7	1	1	1 gouge on slick
138	180.04	184.40	4.36	3.28	75	3.17	73	14	2	4	8	1	1	1 gouge on slick
138	184.40	187.45	3.05	3.05	100	2.94	96	14	2	4	7	1	1	1 gouge, no rake
138	187.45	190.50	3.05	3.02	99	3.02	99	15	2	4	4	3	1	1 20 to c.a. gouge contact, no rake
138	190.50	193.55	3.05	2.93	96	2.71	89	15	3	5	4	1	2	2
138	193.55	196.90	3.35	3.34	100	3.04	91	15	3	5	6	1	2	2
138	196.90	199.03	2.13	2.20	103	1.88	88	14	3	5	6	1	2	2 gouge on fractures
138	199.03	202.08	3.05	3.05	100	3.05	100	15	3	5	4	1	2	2
138	202.08	205.13	3.05	3.05	100	3.05	100	15	3	5	5	1	2	2
138	205.13	208.18	3.05	3.05	100	3.05	100	15	3	5	3	1	2	2
138	208.18	209.09	0.91	0.91	100	0.91	100	14	3	5	2	1	2	2
138	209.09	212.14	3.05	3.05	100	3.05	100	15	3	5	3	1	2	2
138	212.14	215.19	3.05	3.05	100	3.05	100	15	3	5	3	1	2	2
138	215.19	216.71	1.52	1.52	100	1.41	93	14	3	5	5	1	2	2
139	2.74	5.18	2.44	1.30	53	0.20	8	7	2	4	23	1	3	3 broken core
139	5.18	8.23	3.05	3.01	99	1.70	56	13	2	4	15	2	3	3 30% broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
139	8.23	11.28	3.05	3.00	98	1.30	43	13	2	4	10	1	2	gouge on fractures
139	11.28	14.33	3.05	2.95	97	1.53	50	10	2	4	25	5	3	45% gouge (H=1); gouge on fractures
139	14.33	17.37	3.04	3.04	100	1.80	59	10	1	3	23	1	3	90% healed gouge
139	17.37	20.42	3.05	2.95	97	1.85	61	13	2	3	14	1	3	20% healed gouge; broken
139	20.42	23.47	3.05	3.05	100	1.95	64	13	2	4	12	1	2	
139	23.47	26.51	3.04	2.85	94	0.30	10	7	2	4	40	1	4	broken; 30% gouge
139	26.51	29.56	3.05	3.05	100	1.80	59	10	3	5	21	1	2	
139	29.56	32.61	3.05	3.05	100	1.95	64	13	3	5	11	1	3	
139	32.61	35.66	3.05	3.01	99	1.85	61	11	3	5	20	1	3	broken; 10% gouge
139	35.66	38.71	3.05	3.00	98	2.30	75	14	3	5	9	1	3	
139	38.71	41.76	3.05	3.05	100	2.55	84	14	3	5	10	1	3	
139	41.76	44.81	3.05	3.00	98	1.85	61	14	3	4	6	1	2	30% broken and gouge on fractures
139	44.81	47.85	3.04	3.04	100	0.90	30	9	3	4	35	1	3	broken
139	47.85	50.90	3.05	3.05	100	1.50	49	13	3	4	14	1	1	10% healed gouge (H=2); slicks 50 rake
139	50.90	53.95	3.05	3.01	99	1.50	49	11	3	4	20	1	2	10% gouge; gouge on fractures
139	53.95	57.00	3.05	3.05	100	1.60	52	12	3	4	20	1	3	broken core
139	57.00	60.05	3.05	3.05	100	1.70	56	12	3	4	16	1	3	gouge on fractures; py on fractures
139	60.05	63.09	3.04	3.04	100	1.85	61	12	3	4	18	1	2	gouge on fractures
139	63.09	66.14	3.05	3.00	98	2.25	74	13	4	4	14	1	3	
139	66.14	69.19	3.05	3.05	100	2.35	77	14	4	4	8	1	2	65.15 m. - 5 cm. gouge
139	69.19	72.24	3.05	3.04	100	2.10	69	14	4	4	9	1	3	
139	72.24	75.29	3.05	3.02	99	2.45	80	14	4	4	6	2	3	
139	75.29	78.33	3.04	3.03	100	2.15	71	12	2	4	18	1	1	20% gouge (H=1); weak slicks
139	78.33	81.38	3.05	3.05	100	2.55	84	13	2	4	14	1	3	pyrite on fractures
139	81.38	84.43	3.05	3.03	99	2.30	75	13	2	3	15	1	2	40% healed gouge/gouge; H=1
139	84.43	87.48	3.05	3.05	100	2.50	82	14	1	3	10	1	2	gouge on fractures - no slicks
139	87.48	90.53	3.05	3.00	98	2.05	67	12	2	4	17	1	2	pyrite on fractures
139	90.53	93.57	3.04	3.00	99	1.90	63	11	2	4	20	1	2	pyrite on fractures
139	93.57	96.62	3.05	3.03	99	1.83	60	12	2	3	20	1	2	pyrite on fractures
139	96.62	99.67	3.05	3.05	100	2.53	83	13	3	4	13	1	2	pyrite on fractures
139	99.67	102.72	3.05	3.05	100	2.25	74	13	4	4	13	1	2	pyrite on fractures
139	102.72	105.77	3.05	3.00	98	2.30	75	13	2	4	12	1	3	104.3 m.-30 cm. gouge, pyrite on fract
139	105.77	108.81	3.04	2.97	98	2.45	81	14	2	4	7	1	2	gouge on fractures
139	108.81	111.86	3.05	3.00	98	2.11	69	13	2	4	13	1	2	pyrite on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
139	111.86	114.91	3.05	2.95	97	2.40	79	14	3	4	8	1	1 py and gouge on frags; weak slicks	
139	114.91	117.96	3.05	3.00	98	2.20	72	13	2	4	13	1	3 gouge on fractures	
139	117.96	121.01	3.05	2.95	97	2.20	72	12	2	4	18	1	3 20% healed gouge	
139	121.01	123.44	2.43	2.34	96	0.76	31	11	2	4	26	1	2	
139	123.44	124.05	0.61	0.43	70	0.00	0	7	2	4	8	1	3	
139	124.05	127.10	3.05	2.85	93	0.92	30	12	3	4	13	1	1 weak slicks	
139	127.10	130.15	3.05	2.76	90	0.98	32	12	3	4	14	1	2	
139	130.15	133.20	3.05	2.94	96	2.12	70	14	3	4	8	1	2	
139	133.20	136.25	3.05	3.05	100	2.72	89	14	2	4	7	1	2 gouge on fractures	
139	136.25	139.29	3.04	3.05	100	2.76	91	14	2	4	7	1	2 gouge on fractures	
139	139.29	142.34	3.05	3.05	100	2.56	84	14	3	5	6	1	2	
139	142.34	145.39	3.05	2.98	98	2.87	94	14	3	5	5	1	1 weak slicks	
139	145.39	148.44	3.05	3.02	99	3.02	99	15	3	5	5	1	2	
139	148.44	151.49	3.05	3.02	99	3.02	99	15	3	5	5	1	2	
139	151.49	154.53	3.04	3.04	100	2.95	97	14	3	5	7	2	1	
139	154.53	157.58	3.05	3.05	100	2.76	90	13	2	4	12	1	2 minor gouge	
139	157.58	160.63	3.05	3.00	98	2.51	82	14	3	4	8	1	2	
139	160.63	163.68	3.05	3.01	99	1.58	52	13	2	4	15	1	2 fault begins	
139	163.68	166.73	3.05	2.85	93	1.82	60	5	1	3	40	2	1 50% gouge	
139	166.73	169.77	3.04	2.90	95	1.68	55	7	2	3	30	1	1 weak slicks; gouge (healed ?)	
139	169.77	172.82	3.05	3.00	98	1.89	62	5	1	3	40	1	1 very slick on contact; no rake	
139	172.82	175.87	3.05	2.93	96	2.00	66	10	2	4	24	1	1 173.5 m. - end of fault; weak slick	
139	175.87	178.92	3.05	2.83	93	1.90	62	12	3	5	17	2	1 slicks with gouge	
139	178.92	181.97	3.05	2.86	94	2.70	89	14	3	4	9	2	1 slicks with gouge	
139	181.97	185.01	3.04	2.95	97	2.20	72	12	2	3	15	1	2 healed gouge	
139	185.01	188.06	3.05	2.98	98	2.65	87	14	2	4	8	1	2 gouge on fractures	
139	188.06	191.11	3.05	2.70	89	2.40	79	14	3	5	8	1	2	
139	191.11	194.16	3.05	2.90	95	1.98	65	11	2	4	17	1	2	
139	194.16	197.21	3.05	2.97	97	1.82	60	12	2	4	16	1	2	
139	197.21	200.25	3.04	2.72	89	1.52	50	10	2	4	22	1	2 minor gouge	
139	200.25	203.30	3.05	3.05	100	2.30	75	14	3	4	9	1	2	
139	203.30	206.35	3.05	2.95	97	1.75	57	13	2	4	14	1	2	
139	206.35	209.40	3.05	2.72	89	1.20	39	7	1	3	40	1	2 well healed fault; soft gouge	
139	209.40	212.45	3.05	2.85	93	2.50	82	13	2	4	11	1	2 clay on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
139	212.45	215.49	3.04	2.78	91	2.78	91	14	3	5	6	2	1	
139	215.49	218.54	3.05	2.95	97	2.09	69	12	3	5	16	1	2	pyrite on fractures
139	218.54	221.59	3.05	2.87	94	2.20	72	13	3	5	12	1	1	weak slicks
139	221.59	224.64	3.05	2.93	96	2.93	96	15	3	5	4	1	2	
139	224.64	227.69	3.05	3.00	98	3.00	98	14	3	5	6	1	3	
139	227.69	230.73	3.04	2.85	94	2.77	91	14	3	5	5	1	2	
139	230.73	233.78	3.05	2.00	66	1.53	50	13	2	4	11	1	2	weathered slightly
139	233.78	236.83	3.05	3.05	100	2.42	79	13	3	5	13	1	2	clay on fractures
139	236.83	239.88	3.05	3.00	98	2.00	66	13	2	3	13	1	3	last 50% healed gouge
139	239.88	242.93	3.05	2.90	95	2.23	73	13	2	3	11	1	2	sheared and gouge rx; clay on fracts
139	242.93	245.97	3.04	3.05	100	2.80	92	15	2	4	4	1	3	py and clay on fractures
139	245.97	249.02	3.05	3.00	98	2.78	91	14	3	5	5	1	3	pyrite on fractures
139	249.02	252.07	3.05	3.10	102	3.10	102	15	3	5	3	1	3	pyrite on fractures
139	252.07	255.12	3.05	2.90	95	2.70	89	15	3	5	4	1	3	
139	255.12	258.17	3.05	2.90	95	2.30	75	14	3	5	7	1	3	
139	258.17	261.21	3.04	3.10	102	2.30	76	14	2	4	9	1	3	gouge on fractures
139	261.21	264.26	3.05	3.00	98	1.30	43	10	2	4	30	1	2	clay on fractures
139	264.26	267.31	3.05	2.90	95	2.23	73	14	2	4	6	1	3	
139	267.31	270.36	3.05	3.02	99	2.20	72	13	2	4	13	1	3	
139	270.36	273.41	3.05	3.07	101	2.70	89	14	2	4	6	1	3	
139	273.41	276.45	3.04	2.98	98	2.45	81	13	2	4	10	1	2	gouge/clay on fracts; 10 cm. healed gouge
139	276.45	279.50	3.05	3.03	99	2.10	69	13	2	4	12	1	3	gouge on fractures
139	279.50	282.55	3.05	3.05	100	2.10	69	12	2	4	16	1	2	
139	282.55	285.60	3.05	3.05	100	1.90	62	10	2	4	25	1	2	clay on fractures
139	285.60	288.65	3.05	3.05	100	1.60	52	9	2	4	40	1	2	
139	288.65	291.69	3.04	2.95	97	1.80	59	9	2	4	30	1	3	broken core
139	291.69	294.74	3.05	3.10	102	1.55	51	9	2	4	35	1	3	50% broken core
139	294.74	297.79	3.05	3.05	100	1.42	47	9	2	4	40	1	3	295.2 m. - 3 cm gouge, 50 to c.a.
139	297.79	300.84	3.05	3.00	98	1.85	61	10	1	3	27	1	2	intermittent gouge zones
139	300.84	303.89	3.05	2.95	97	2.15	70	10	2	3	25	1	3	301.3-302.10 m. - gouge 50 to c.a.
139	303.89	306.93	3.04	3.04	100	1.55	51	10	2	3	25	1	3	304.75 m. - 5 cm gouge 55 to c.a.
139	306.93	309.98	3.05	3.05	100	1.70	56	10	2	4	28	1	3	
139	309.98	313.03	3.05	3.05	100	2.00	66	12	2	3	16	5	3	310.9 m. - healed gouge 20 to c.a. (60cm)
139	313.03	316.08	3.05	3.05	100	2.40	79	13	3	4	13	1	3	last 1.5 m. sheared and gouge mat'l

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
139	316.08	319.13	3.05	3.05	100	2.25	74	13	3	5	15	1	3	316.08-316.31 m.-healed gouge
139	319.13	322.17	3.04	3.04	100	2.22	73	13	3	5	12	1	3	319.53 m.- fracture w/ gouge, 55 to c.a.
139	322.17	325.22	3.05	2.98	98	2.81	92	13	3	5	10	2	3	
139	325.22	328.27	3.05	3.05	100	2.02	66	13	3	5	11	5	3	325.67-325.97 m.-healed gouge, 35 c.a.
139	328.27	331.32	3.05	3.05	100	3.05	100	13	3	5	13	5	3	first 0.5 m. fault gouge (healed)
139	331.32	334.37	3.05	2.97	97	2.15	70	12	3	5	18	5	3	
139	334.37	337.41	3.04	3.00	99	2.19	72	12	3	5	16	1	3	Two < 1 cm. gouge sections
139	337.41	340.46	3.05	3.05	100	1.92	63	13	3	5	13	5	3	338.65 m.- 10 cm. fault gouge 45 to c.a.
139	340.46	343.51	3.05	3.05	100	1.74	57	13	3	5	15	1	3	
139	343.51	346.56	3.05	3.05	100	2.23	73	13	3	5	13	1	2	
139	346.56	349.61	3.05	3.05	100	2.60	85	14	3	5	9	5	3	
140	3.65	4.88	1.23	1.21	98	0.43	35	7	3	3	17	1	2	
140	4.88	7.01	2.13	2.13	100	0.83	39	6	0	1	30	1	2	oxidized to 7.01 m.; gouge zone
140	7.01	8.23	1.22	1.05	86	0.19	16	6	0	1	30	3	2	gouge zone
140	8.23	10.06	1.83	1.83	100	0.62	34	9	0	1	20	3	2	gouge zone
140	10.06	12.80	2.74	2.74	100	1.60	58	5	0	1	50	1	2	gouge zone; ground core
140	12.80	14.33	1.53	1.70	111	1.39	91	12	5	6	8	1	3	
140	14.33	16.76	2.43	2.20	91	1.94	80	15	3	6	4	3	2	
140	16.76	19.81	3.05	3.15	103	2.60	85	13	5	4	12	1	3	
140	19.81	23.16	3.35	3.05	91	3.05	91	15	5	6	4	1	3	
140	23.16	26.52	3.36	3.35	100	2.95	88	13	4	3	14	3	3	
140	26.52	29.57	3.05	3.05	100	2.92	96	14	5	6	7	1	3	
140	29.57	32.61	3.04	3.04	100	2.75	90	14	3	6	6	1	3	
140	32.61	35.66	3.05	3.00	98	2.60	85	14	4	3	9	3	2	
140	35.66	38.71	3.05	3.13	103	2.95	97	14	3	6	9	3	2	
140	38.71	41.76	3.05	3.03	99	2.90	95	14	4	6	4	3	3	
140	41.76	44.81	3.05	3.02	99	2.95	97	14	3	4	8	3	2	
140	44.81	47.85	3.04	3.18	105	2.80	92	13	4	4	12	3	2	
140	47.85	50.90	3.05	3.10	102	2.88	94	14	4	4	8	3	3	
140	50.90	53.95	3.05	3.04	100	2.84	93	14	4	5	9	1	2	
140	53.95	57.00	3.05	3.00	98	3.00	98	15	4	6	2	3	3	
140	57.00	60.05	3.05	3.05	100	3.05	100	15	4	5	3	3	3	
140	60.05	63.09	3.04	3.04	100	3.04	100	15	4	6	3	3	2	
140	63.09	66.14	3.05	2.96	97	2.93	96	14	5	5	6	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	66.14	69.19	3.05	3.12	102	3.12	102	14	4	6	6	3	3	
140	69.19	72.24	3.05	2.93	96	2.93	96	14	4	6	2	3	2	
140	72.24	75.29	3.05	3.08	101	3.08	101	15	4	6	3	3	3	
140	75.29	78.33	3.04	3.10	102	3.10	102	14	4	5	6	3	2	
140	78.33	81.38	3.05	3.10	102	2.50	82	14	4	4	8	3	3	3 start of broken rock section
140	81.38	84.43	3.05	3.10	102	0.92	30	7	3	2	50	1	3	3 natural breaks; acid leached fract's
140	84.43	86.56	2.13	2.30	108	0.97	46	7	3	2	30	3	2	2 natural breaks; acid leached fract's
140	86.56	88.39	1.83	1.40	77	0.30	16	6	3	2	35	1	2	2 natural breaks; acid leached fract's
140	88.39	91.44	3.05	3.02	99	1.32	43	12	3	2	17	1	2	2 end of broken rock section
140	91.44	93.57	2.13	2.24	105	2.20	103	14	4	5	4	3	2	
140	93.57	96.62	3.05	3.05	100	3.05	100	15	3	6	3	3	2	
140	96.62	99.67	3.05	3.05	100	3.05	100	15	5	6	2	3	2	
140	99.67	102.72	3.05	3.07	101	2.94	96	15	4	5	3	3	1	
140	102.72	105.77	3.05	3.05	100	3.05	100	15	3	5	4	3	1	
140	105.77	108.81	3.04	2.95	97	2.95	97	15	4	6	3	3	4	
140	108.81	111.86	3.05	3.13	103	3.13	103	15	3	6	3	3	2	
140	111.86	114.91	3.05	2.87	94	2.64	87	15	5	6	5	3	2	
140	114.91	117.96	3.05	3.25	107	2.90	95	14	4	6	8	3	2	
140	117.96	119.79	1.83	1.70	93	1.70	93	14	4	6	4	3	2	
140	119.79	121.01	1.22	1.45	119	1.15	94	14	4	6	2	3	2	2 ground core
140	121.01	124.05	3.04	2.95	97	2.95	97	15	4	6	4	3	3	
140	124.05	127.10	3.05	3.30	108	2.40	79	13	5	5	10	1	2	
140	127.10	130.15	3.05	3.17	104	2.72	89	15	4	5	4	3	3	
140	130.15	133.20	3.05	3.02	99	3.02	99	14	5	6	5	3	3	
140	133.20	136.25	3.05	3.02	99	2.55	84	14	4	5	9	3	3	
140	136.25	139.29	3.04	3.15	104	2.90	95	14	4	5	7	3	3	
140	139.29	142.34	3.05	3.00	98	2.63	86	14	4	5	5	3	3	
140	142.34	145.39	3.05	2.92	96	2.08	68	14	4	4	10	1	2	2 ground core; gypsum
140	145.39	148.44	3.05	3.10	102	3.00	98	14	4	4	6	3	3	
140	148.44	151.49	3.05	3.05	100	3.02	99	15	4	4	3	3	2	
140	151.49	154.53	3.04	3.00	99	3.00	99	15	5	4	1			ground surface
140	154.53	157.58	3.05	3.15	103	3.15	103	15	5	5	3	4	3	
140	157.58	160.63	3.05	3.05	100	3.05	100	15	5	5	4	3	3	
140	160.63	163.68	3.05	2.87	94	2.68	88	14	4	5	5	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	163.68	166.73	3.05	3.05	100	2.63	86	14	3	5	5	3	3	
140	166.73	169.77	3.04	3.04	100	2.95	97	15	4	5	4	3	2	gypsum fracture
140	169.77	172.82	3.05	3.10	102	2.25	74	14	3	4	9	3	2	
140	172.82	175.87	3.05	3.10	102	2.89	95	14	3	4	5	3	2	
140	175.87	178.92	3.05	3.05	100	2.18	71	10	0	2	25	3	2	broken rock; gouge
140	178.92	181.97	3.05	3.05	100	1.68	55	10	2	2	25	3	2	broken rock; gouge
140	181.97	185.01	3.04	3.04	100	2.45	81	14	3	3	8	3	2	minor mud seams
140	185.01	188.06	3.05	3.15	103	2.60	85	14	0	2	7	3	1	mud/gouge seam 3 cm. wide
140	188.06	191.11	3.05	3.10	102	3.02	99	14	3	3	5	3	2	
140	191.11	194.16	3.05	3.10	102	2.50	82	14	3	3	5	3	2	
140	194.16	197.21	3.05	3.05	100	2.97	97	15	4	4	3	3	2	
140	197.21	200.25	3.04	3.04	100	2.65	87	15	3	4	3	1	2	
140	200.25	203.30	3.05	3.15	103	1.80	59	13	3	2	10	3	2	gouge seams
140	203.30	206.35	3.05	3.13	103	3.13	103	15	3	4	3	3	2	
140	206.35	209.40	3.05	3.05	100	2.99	98	15	4	5	3	3	2	
140	209.40	212.45	3.05	3.00	98	3.00	98	14	3	5	5	3	2	
140	212.45	215.49	3.04	3.00	99	3.00	99	15	3	5	2	3	2	
140	215.49	218.54	3.05	3.05	100	2.41	79	15	4	5	4	3	2	
140	218.54	221.59	3.05	3.07	101	2.85	93	14	4	5	5	3	2	
140	221.59	224.64	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
140	224.64	227.69	3.05	3.05	100	2.55	84	12	0	2	16	1	2	gouge & broken rock
140	227.69	230.73	3.04	3.17	104	2.90	95	14	1	2	6	2	2	
140	230.73	233.17	2.44	2.45	100	1.90	78	14	4	4	5	3	3	
140	233.17	236.22	3.05	3.10	102	2.75	90	14	3	4	6	3	2	
140	236.22	239.27	3.05	2.95	97	2.78	91	14	3	2	8	3	2	gouge seams
140	239.27	242.62	3.35	3.25	97	3.08	92	14	3	3	8	3	2	
140	242.62	245.67	3.05	3.10	102	2.40	79	13	3	3	11	3	2	broken rock
140	245.67	248.72	3.05	3.20	105	0.62	20	9	0	2	25	1	1	gouge & broken rock
140	248.72	251.76	3.04	3.04	100	2.95	97	14	4	4	5	3	2	
140	251.76	254.81	3.05	3.10	102	2.98	98	14	4	4	5	3	2	re-drilled portion of core
140	254.81	257.56	2.75	2.73	99	2.73	99	15	4	5	3	3	2	
140	257.56	260.60	3.04	2.93	96	2.93	96	15	4	5	3	3	2	
140	260.60	263.65	3.05	3.15	103	3.05	100	15	4	5	2	4	2	
140	263.65	267.31	3.66	2.75	75	2.75	75	15	4	5	1	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
140	267.31	268.83	1.52	1.35	89	0.46	30	11	4	3	10	1	3	3 broken rock over short section
140	268.83	270.36	1.53	1.66	108	1.05	69	13	4	5	6	1	4	
140	270.36	273.41	3.05	3.05	100	3.00	98	15	4	3	3	1	2	2 minor gouge zone
140	273.41	274.93	1.52	1.33	88	0.75	49	13	3	3	7	2	2	2 minor broken rock sections
140	274.93	277.67	2.74	3.05	111	2.55	93	14	2	3	5	3	2	
140	277.67	279.50	1.83	1.83	100	1.57	86	14	3	3	5	1	2	2 graphite-chlorite fracture
140	279.50	282.55	3.05	3.00	98	2.94	96	15	3	3	3	1	2	
140	282.55	285.60	3.05	2.70	89	2.54	83	15	4	3	4	2	2	2 cave
140	285.60	288.65	3.05	3.05	100	2.49	82	13	0	2	14	3	3	1 gypsum fracture & gouge
140	288.65	290.47	1.82	2.25	124	1.19	65	9	0	2	17	1	1	1 gypsum powder on fractures
140	290.47	293.50	3.03	3.03	100	2.34	77	14	4	3	5	3	3	
140	293.50	296.27	2.77	2.74	99	2.25	81	15	4	4	4	3	2	
140	296.27	299.31	3.04	3.04	100	2.13	70	7	0	2	50	3	3	2 gouge & broken rock
140	299.31	302.67	3.36	2.97	88	2.83	84	15	4	3	3	3	3	2 start of dyke
140	302.67	305.71	3.04	2.96	97	2.44	80	15	4	4	4	1	4	4 dyke
140	305.71	306.93	1.22	1.18	97	0.22	18	6	0	2	25	1	2	2 gouge & broken rock
140	306.93	309.37	2.44	2.55	105	0.53	22	12	3	3	15	3	3	
140	309.37	312.42	3.05	3.12	102	2.88	94	15	5	5	2	3	3	
140	312.42	315.47	3.05	3.05	100	3.05	100	15	3	5	2	3	3	
140	315.47	318.82	3.35	3.33	99	3.03	90	14	3	5	5	3	2	
140	318.82	321.87	3.05	3.03	99	2.82	92	15	3	4	4	3	3	
140	321.87	324.92	3.05	3.05	100	2.95	97	15	0	2	4	3	3	2 1 cm. gouge zone
140	324.92	327.96	3.04	2.97	98	2.93	96	15	4	5	2	3	3	
140	327.96	331.01	3.05	3.08	101	3.03	99	15	4	5	2	3	3	
140	331.01	334.37	3.36	3.05	91	2.71	81	14	4	3	5	3	2	
140	334.37	337.41	3.04	3.20	105	2.94	97	15	3	5	4	3	3	1 gypsum powder
140	337.41	340.46	3.05	3.20	105	3.04	100	15	4	5	4	3	3	
140	340.46	342.90	2.44	2.41	99	2.41	99	15	4	5	4	5	3	
140	342.90	345.03	2.13	2.06	97	2.06	97	15	4	5	1			re-drill of top; 40 cm. ground core
140	345.03	346.56	1.53	1.62	106	1.62	106	15	4	6	0	0	0	
140	346.56	349.61	3.05	2.95	97	2.20	72	14	4	4	9	1	2	2 mud seam
140	349.61	352.65	3.04	3.06	101	3.06	101	15	3	6	2	3	2	
140	352.65	355.70	3.05	2.85	93	2.24	73	15	3	4	20	3	3	2 twice re-drilled core; broken core
140	355.70	358.75	3.05	3.00	98	3.00	98	15	3	6	2	4	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	358.75	361.80	3.05	2.95	97	2.95	97	15	5	6	3	3	3	
140	361.80	364.85	3.05	3.13	103	2.94	96	14	4	6	5	3	2	
140	364.85	367.89	3.04	3.03	100	2.90	95	15	4	6	3	3	2	
140	367.89	370.94	3.05	3.06	100	2.95	97	15	4	6	3	3	2	
140	370.94	373.99	3.05	3.05	100	2.68	88	15	4	6	3	3	3	
140	373.99	377.04	3.05	3.15	103	2.27	74	13	3	5	11	1	3	
140	377.04	380.09	3.05	3.05	100	2.77	91	13	1	3	10	3	1	1 slick surface
140	380.09	383.13	3.04	3.00	99	2.70	89	14	3	3	6	3	1	1 mud seam
140	383.13	386.18	3.05	3.05	100	2.85	93	14	3	5	5	1	2	
140	386.18	389.23	3.05	3.00	98	2.93	96	14	3	4	8	3	1	
140	389.23	392.28	3.05	3.15	103	2.72	89	14	3	4	8	1	1	1 slick surface
140	392.28	395.33	3.05	3.00	98	2.20	72	12	0	2	15	1	1	1 slick gouge
140	395.33	397.15	1.82	1.90	104	0.60	33	10	3	2	15	4	1	1 broken rock
140	397.15	400.20	3.05	2.97	97	2.97	97	14	3	4	7	3	1	1 slick surface
140	400.20	402.64	2.44	2.44	100	2.09	86	14	3	4	5	3	2	
140	402.64	404.47	1.83	1.97	108	0.92	50	10	0	2	15	3	1	1 gouge zone
140	404.47	407.52	3.05	2.97	97	1.04	34	7	0	2	50	3	1	1 gouge zones; broken rock
140	407.52	410.57	3.05	3.02	99	1.86	61	10	0	2	25	3	1	1 gouge zones; broken rock
140	410.57	413.61	3.04	3.00	99	2.44	80	14	3	3	8	1	1	1 slick surface
140	413.61	416.66	3.05	3.03	99	1.85	61	14	0	2	8	1	1	1 slick surface; gouge
140	416.66	419.71	3.05	3.10	102	2.70	89	13	3	2	12	2	1	1 slick surface; mud seams
140	419.71	422.76	3.05	3.08	101	2.94	96	15	3	5	4	1	2	
140	422.76	424.28	1.52	1.56	103	1.19	78	10	3	4	4	1	2	
140	424.28	425.81	1.53	1.12	73	0.60	39	13	3	4	5	1	1	1 gouge on weak slicks
140	425.81	428.85	3.04	2.81	92	2.32	76	14	2	3	8	1	1	1 reduce to NQ; mud seams
140	428.85	431.90	3.05	3.00	98	2.86	94	14	2	3	8	1	1	1 slip plane at contacts
140	431.90	434.95	3.05	3.00	98	2.69	88	13	1	3	12	1	1	1 healed gouge
140	434.95	438.00	3.05	2.69	88	2.27	74	14	2	4	7	3	1	1 mud seam
140	438.00	441.05	3.05	2.91	95	2.21	72	10	2	3	22	3	1	1 gouge on fractures
140	441.05	444.09	3.04	3.00	99	2.94	97	14	3	4	9	1	1	1 slick contact
140	444.09	447.14	3.05	3.20	105	3.16	104	14	2	4	7	1	1	1 slicks with gouge
140	447.14	450.19	3.05	3.08	101	2.80	92	13	2	4	13	1	1	1 re-drilled rubble
140	450.19	453.24	3.05	2.90	95	2.32	76	12	2	3	17	1	1	1 fault gouge on fractures
140	453.24	456.29	3.05	2.97	97	2.83	93	15	3	5	4	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	456.29	459.33	3.04	3.11	102	2.14	70	13	3	4	14	1	3 broken rock by drillers	
140	459.33	462.38	3.05	3.05	100	2.64	87	14	3	5	9	1	3	
140	462.38	465.43	3.05	3.05	100	2.70	89	14	3	5	6	1	1 lick contacts; weak rake	
140	465.43	468.48	3.05	2.72	89	2.00	66	13	3	5	11	1	1 slick, rake at +5 to c.a.	
140	468.48	471.53	3.05	3.10	102	2.05	67	13	3	5	13	1	2 gouge on fractures	
140	471.53	474.57	3.04	3.08	101	2.80	92	14	2	4	9	1	1 weak slicks	
140	474.57	476.40	1.83	2.00	109	1.55	85	14	2	4	6	1	1 weak slicks	
140	476.40	479.45	3.05	3.02	99	2.76	90	14	2	4	8	1	1 weak slicks; gouge on joints	
140	479.45	482.50	3.05	2.89	95	2.47	81	13	2	4	12	1	1 weak slicks; gouge on joints	
140	482.50	485.55	3.05	3.00	98	2.55	84	14	2	4	10	1	1 weak slicks	
140	485.55	488.90	3.35	3.05	91	2.87	86	14	2	4	9	1	1 weak slicks; gouge on joints	
140	488.90	491.95	3.05	2.87	94	2.46	81	13	2	4	13	1	1 weak slicks	
140	491.95	495.00	3.05	2.93	96	2.51	82	13	2	4	11	1	1 gouge on fractures	
140	495.00	498.04	3.04	2.92	96	2.78	91	14	2	3	8	1	1 gouge on fractures	
140	498.04	501.09	3.05	3.02	99	2.42	79	13	2	4	13	1	1 weak slicks	
140	501.09	504.14	3.05	2.97	97	2.35	77	14	2	4	9	1	1	
140	504.14	506.58	2.44	2.37	97	1.63	67	13	2	4	8	1	1 strong slicks, 40 to c.a., 20 to c.a.	
140	506.58	508.10	1.52	1.51	99	1.32	87	14	3	4	5	1	2	
140	508.10	511.15	3.05	2.97	97	2.83	93	15	3	5	4	1	2	
140	511.15	514.20	3.05	3.05	100	3.05	100	14	3	5	6	1	2	
140	514.20	517.25	3.05	3.05	100	2.75	90	14	2	4	8	1	1 weak slicks	
140	517.25	520.29	3.04	3.04	100	2.60	86	13	2	4	13	1	1 weak slicks	
140	520.29	523.34	3.05	3.03	99	2.67	88	14	2	4	9	1	1 weak slicks	
140	523.34	526.39	3.05	3.05	100	2.65	87	14	2	4	9	1	1 weak slicks, 20 to c.a.; gouge	
140	526.39	529.44	3.05	3.02	99	2.95	97	14	3	5	8	2	1 weak slicks, 45 to c.a.	
140	529.44	532.49	3.05	3.05	100	2.72	89	15	3	5	4	2	2 clay on fractures	
140	532.49	535.53	3.04	3.04	100	3.04	100	15	3	5	5	3	1 weak slicks	
140	535.53	538.58	3.05	2.89	95	2.89	95	15	3	5	4	1	2	
140	538.58	541.63	3.05	3.05	100	3.05	100	14	3	5	6	1	3 3 cm. dyke, 28 to c.a.	
140	541.63	544.68	3.05	3.05	100	3.05	100	14	3	4	10	1	2 gouge on fractures	
140	544.68	546.20	1.52	1.52	100	1.52	100	15	3	5	2	1	3	
140	546.20	547.73	1.53	1.58	103	1.58	103	15	3	5	2	1	2	
140	547.73	550.77	3.04	3.04	100	2.89	95	15	3	5	5	3	3 15 cm. healed shearing	
140	550.77	553.82	3.05	3.00	98	2.90	95	15	3	5	3	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	553.82	556.87	3.05	3.05	100	2.91	95	15	3	5	3	1	3	3 minor cemented gouge
140	556.87	559.92	3.05	3.05	100	3.05	100	15	3	5	2	2	2	
140	559.92	562.96	3.04	3.04	100	2.85	94	14	3	5	6	1	2	
140	562.96	566.01	3.05	3.05	100	2.95	97	15	3	5	4	1	1	2 mm. wet gouge
140	566.01	569.06	3.05	3.10	102	3.10	102	15	3	4	2	1	2	2 minor gouge
140	569.06	572.11	3.05	3.05	100	2.90	95	15	3	5	4	2	2	2 two 5 to 10 cm. rubble zones
140	572.11	575.16	3.05	3.05	100	3.05	100	15	3	5	4	1	3	
140	575.16	578.21	3.05	3.05	100	3.05	100	15	3	5	3	1	3	3 1.5 cm. cemented gouge
140	578.21	581.25	3.04	3.04	100	3.05	100	15	3	5	3	1	3	
140	581.25	584.30	3.05	3.05	100	3.05	100	15	3	5	2	4	3	
140	584.30	587.35	3.05	2.94	96	2.85	93	14	3	5	5	2	2	
140	587.35	590.40	3.05	3.05	100	3.05	100	15	3	5	3	3	2	
140	590.40	593.44	3.04	3.04	100	3.00	99	15	3	5	5	2	2	2 minor gouge on fractures
140	593.44	596.49	3.05	3.05	100	2.95	97	15	3	5	5	2	2	2 minor gouge w/ f.g. pyrite
140	596.49	599.54	3.05	3.00	98	1.85	61	13	3	4	14	2	1	1 rubble zones w/ gouge
140	599.54	602.59	3.05	3.05	100	1.80	59	12	3	4	20	2	1	1 rubble zones w/ gouge
140	602.59	605.64	3.05	3.05	100	1.98	65	14	3	4	9	2	1	1 1-2 cm. gouge & rubble 10-15 to c.a.
140	605.64	608.69	3.05	3.05	100	2.95	97	15	3	5	4	1	1	1 1-2 mm. gouge
140	608.69	611.73	3.04	3.04	100	3.00	99	15	3	5	4	1	1	1 1-2 mm. gouge
140	611.73	612.95	1.22	1.22	100	1.10	90	15	3	4	2	1	3	3 trace gouge
140	612.95	616.00	3.05	3.05	100	3.05	100	15	4	5	3	2	2	
140	616.00	618.43	2.43	2.43	100	2.43	100	15	4	5	3	2	3	
140	618.43	620.88	2.45	2.45	100	2.45	100	15	4	5	4	2	2	
140	620.88	623.93	3.05	3.05	100	3.05	100	15	4	5	2	2	2	
140	623.93	626.97	3.04	3.04	100	2.95	97	15	4	5	1	3	3	
140	626.97	630.02	3.05	3.05	100	3.00	98	15	4	5	3	1	1	1 gouge w/ possible slicks
140	630.02	633.07	3.05	3.05	100	3.05	100	15	4	5	2	2	2	
140	633.07	636.12	3.05	3.05	100	2.95	97	14	4	5	7	1	1	1 trace gouge on rubble
140	636.12	639.17	3.05	3.05	100	3.05	100	14	4	5	9	2	2	
140	639.17	642.21	3.04	3.04	100	3.04	100	15	4	5	3	1	1	1 fracture 50 to c.a., rake 70 to c.a.
140	642.21	643.74	1.53	1.53	100	1.06	69	13	4	5	6	3	2	2 gouge on rubble
140	643.74	646.79	3.05	3.05	100	2.34	77	13	4	5	14	3	2	2 cemented gouge
140	646.79	649.53	2.74	2.50	91	2.20	80	14	4	5	5	2	2	2 trace gouge
140	649.53	651.36	1.83	1.93	105	1.93	105	14	4	5	4	1	2	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	651.36	654.41	3.05	3.05	100	3.05	100	14	4	5	5	2	2	
140	654.41	657.45	3.04	3.04	100	3.00	99	14	4	5	9	1	2	
140	657.45	660.50	3.05	2.95	97	2.85	93	15	4	5	7	2	2	
140	660.50	662.33	1.83	1.73	95	1.73	95	14	4	5	4	1	1	1 2 mm. gouge
140	662.33	665.38	3.05	3.00	98	3.00	98	15	4	5	2	2	1	1 trace gouge
140	665.38	668.12	2.74	2.74	100	2.40	88	14	4	5	7	1	1	1 3 mm cemented gouge; cave @ EOR
140	668.12	669.65	1.53	1.70	111	1.70	111	14	4	5	4	1	1	
140	669.65	672.69	3.04	3.04	100	2.95	97	14	4	5	10	2	1	
140	672.69	675.74	3.05	3.05	100	3.00	98	14	4	5	6	1	1	1 two 3-4 mm. cemented gouge
140	675.74	678.79	3.05	3.05	100	3.00	98	15	4	5	3	2	2	
140	678.79	681.84	3.05	3.05	100	3.05	100	15	4	5	4	2	2	
140	681.84	684.89	3.05	3.05	100	2.85	93	14	4	5	10	2	1	
140	684.89	687.93	3.04	3.05	100	2.95	97	14	4	5	10	1	2	
140	687.93	690.98	3.05	3.05	100	2.95	97	14	4	5	7	1	1	1 gouge w/ trace slicks
140	690.98	694.03	3.05	3.05	100	3.05	100	15	4	5	4	2	2	
140	694.03	697.08	3.05	3.05	100	3.05	100	14	4	5	5	2	2	
140	697.08	700.13	3.05	3.05	100	3.00	98	14	4	5	7	2	2	
140	700.13	703.17	3.04	3.05	100	3.00	99	14	4	5	7	2	3	
140	703.17	706.22	3.05	3.05	100	3.05	100	14	4	5	5	2	2	
140	706.22	709.27	3.05	3.05	100	3.00	98	14	4	5	8	3	2	
140	709.27	712.32	3.05	3.05	100	2.95	97	14	4	5	11	1	1	1 trace gouge
140	712.32	715.36	3.04	3.05	100	2.85	94	13	4	5	13	1	1	1 trace gouge w/ slicks
140	715.36	718.41	3.05	3.05	100	2.95	97	13	4	5	11	1	2	
140	718.41	721.46	3.05	3.05	100	2.90	95	14	4	5	8	1	2	
140	721.46	724.51	3.05	3.05	100	3.05	100	14	4	5	6	3	2	2 trace gouge
140	724.51	727.56	3.05	3.05	100	2.85	93	13	3	5	12	1	2	2 two 1-2 cm. cemented gouge
140	727.56	730.61	3.05	3.05	100	2.90	95	13	4	5	13	1	1	1 1 mm. dark gouge w/ trace slicks
140	730.61	733.65	3.04	3.05	100	2.85	94	14	4	5	9	3	1	1 trace gouge
140	733.65	736.70	3.05	3.05	100	2.65	87	13	4	5	12	1	1	1 four fractures have 2 mm. gouge
140	736.70	738.23	1.53	1.53	100	0.39	25	10	4	5	13	1	1	1 gouge w/ < 2 mm. gouge
140	738.23	741.27	3.04	3.04	100	2.75	90	13	4	5	13	2	2	
140	741.27	744.32	3.05	3.05	100	2.95	97	14	4	5	9	2	2	
140	744.32	746.76	2.44	2.10	86	2.00	82	14	4	5	6	1	2	2 10 cm. subangular 1-2 cm. rubble
140	746.76	748.89	2.13	2.13	100	2.00	94	13	4	5	9	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
140	748.89	751.94	3.05	3.05	100	2.90	95	13	4	5	13	1	1	
140	751.94	754.99	3.05	3.05	100	2.70	89	12	4	5	16	1	1	2 cm. cemented gouge at 40 to c.a.
140	754.99	758.04	3.05	3.05	100	2.70	89	14	4	5	10	1	3	50% of breaks in qz vein
140	758.04	761.09	3.05	2.95	97	2.95	97	14	4	5	9	2	2	mineralized fractures
140	761.09	764.13	3.04	2.95	97	2.80	92	14	4	5	9	1	1	cemented gouge at 40 to c.a.
140	764.13	767.18	3.05	3.05	100	2.95	97	14	4	5	8	3	1	weak slicks w/ 30 to c.a. rake
140	767.18	770.23	3.05	2.95	97	2.95	97	14	4	5	7	1	2	
140	770.23	773.28	3.05	3.05	100	2.95	97	13	4	5	13	1	2	
140	773.28	776.32	3.04	3.04	100	2.90	95	14	4	5	8	2	2	
140	776.32	779.37	3.05	3.10	102	2.74	90	14	3	3	8	1	2	
140	779.37	782.42	3.05	3.10	102	3.05	100	15	3	5	5	4	2	
140	782.42	785.47	3.05	2.97	97	2.57	84	14	3	4	7	1	1	
140	785.47	788.52	3.05	3.05	100	2.94	96	14	3	4	9	3	2	
140	788.52	791.57	3.05	3.04	100	3.04	100	15	3	4	5	3	2	
140	791.57	794.61	3.04	3.13	103	3.00	99	14	3	4	8	3	2	
140	794.61	797.66	3.05	3.09	101	1.74	57	9	0	2	35	3	2	fault gouge/broken rx at 50 to c.a.
140	797.66	800.71	3.05	3.10	102	3.04	100	14	2	3	6	1	2	
140	800.71	803.76	3.05	3.00	98	3.00	98	15	3	4	3	1	2	
140	803.76	806.81	3.05	2.72	89	2.65	87	14	3	4	6	3	1	
140	806.81	809.85	3.04	3.10	102	3.05	100	15	3	4	5	1	2	
140	809.85	812.90	3.05	3.08	101	3.08	101	14	3	4	6	1	2	
141	4.88	7.62	2.74	1.75	64	0.00	0	4	0	2	100	1	2	blocky material w/ gouge
141	7.62	9.14	1.52	1.40	92	0.00	0	5	1	2	60	1	2	blocky material w/ gouge, clay
141	9.14	10.36	1.22	1.41	116	0.00	0	8	1	2	19	1	2	blocky material w/ gouge
141	10.36	10.97	0.61	0.60	98	0.00	0	5	2	3	18	1	2	blocky material w/ gouge
141	10.97	11.89	0.92	0.80	87	0.00	0	6	2	3	20	1	2	blocky material w/ gouge
141	11.89	14.34	2.45	2.16	88	0.87	36	10	2	3	17	1	2	blocky material w/ gouge
141	14.34	17.39	3.05	2.46	81	0.15	5	6	1	3	50	1	2	blocky material w/ gouge
141	17.39	19.51	2.12	1.64	77	0.00	0	7	2	3	24	1	2	blocky material w/ gouge; broken
141	19.51	22.25	2.74	1.50	55	0.16	6	7	2	3	26	1	2	blocky material w/ gouge
141	22.25	24.38	2.13	2.10	99	0.63	30	7	2	3	40	1	2	blocky material w/ gouge
141	24.38	26.52	2.14	2.07	97	0.54	25	7	2	3	32	1	2	blocky material w/ gouge
141	26.52	29.57	3.05	3.05	100	2.21	72	12	2	3	16	1	1	25% healed gouge
141	29.57	32.62	3.05	2.90	95	1.48	49	10	2	3	28	1	1	50 cm. of gouge; H=0

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
141	32.62	35.66	3.04	3.06	101	1.93	63	11	2	4	21	1	2	
141	35.66	37.80	2.14	1.95	91	0.97	45	10	2	4	19	1	2	
141	37.80	40.84	3.04	2.90	95	1.85	61	13	2	3	14	1	1	30 cm. of gouge; H=0
141	40.84	44.20	3.36	3.05	91	2.62	78	14	2	4	7	1	2	gouge on fractures (extra footage)
141	44.20	47.24	3.04	3.04	100	3.05	100	14	2	4	8	1	2	gouge on fractures
141	47.24	50.29	3.05	3.05	100	2.48	81	14	2	4	10	1	2	gouge on fractures
141	50.29	53.34	3.05	2.98	98	2.52	83	14	2	4	8	1	1	weak slicks; gouge sect'n 4 cm.
141	53.34	56.69	3.35	3.15	94	3.15	94	14	2	4	9	1	2	extra footage
141	56.69	59.74	3.05	3.05	100	1.49	49	10	1	3	29	1	1	50% gouge, weak slicks
141	59.74	62.79	3.05	2.84	93	1.82	60	10	2	3	23	1	2	30% gouge in sections
141	62.79	65.84	3.05	2.58	85	1.44	47	9	1	3	30	2	1	40 cm. of very weak material
141	65.84	69.19	3.35	3.08	92	1.68	50	10	1	3	23	3	1	70% gouge; extra footage
141	69.19	71.63	2.44	2.44	100	1.48	61	10	2	4	21	1	2	
141	71.63	74.68	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
141	74.68	77.72	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
141	77.72	80.77	3.05	3.05	100	2.72	89	14	2	4	7	1	3	
141	80.77	83.82	3.05	3.03	99	3.03	99	14	3	5	6	1	3	
141	83.82	86.87	3.05	3.05	100	3.05	100	15	3	5	4	1	3	
141	86.87	90.22	3.35	3.15	94	3.15	94	15	3	5	3	1	2	extra footage
141	90.22	93.27	3.05	3.05	100	3.05	100	15	3	5	4	1	3	
141	93.27	96.32	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
141	96.32	99.36	3.04	3.04	100	3.04	100	14	3	5	6	1	2	
141	99.36	102.72	3.36	3.01	90	2.36	70	13	3	4	13	1	1	weak slicks, no rake, minor gouge
141	102.72	105.77	3.05	3.05	100	1.53	50	8	3	4	40	1	2	blocky ground; mineralized fract's
141	105.77	108.81	3.04	2.00	66	0.00	0	5	2	4	60	1	2	blocky ground; mineralized fract's
141	108.81	111.86	3.05	2.95	97	1.12	37	6	2	4	30	1	2	blocky ground; mineralized fract's
141	111.86	114.91	3.05	2.85	93	0.48	16	5	2	4	60	1	2	blocky ground; mineralized fract's
141	114.91	117.96	3.05	2.94	96	1.15	38	8	2	4	40	1	2	blocky ground; mineralized fract's
141	117.96	121.01	3.05	2.96	97	0.65	21	6	2	4	60	1	2	blocky ground; mineralized fract's
141	121.01	124.06	3.05	3.02	99	3.02	99	14	2	5	7	1	2	
141	124.06	127.10	3.04	3.15	104	2.95	97	14	2	5	8	1	3	
141	127.10	130.15	3.05	2.79	91	1.37	45	10	2	4	23	1	2	gouge on fractures
141	130.15	133.20	3.05	3.02	99	3.02	99	5	3	5	5	1	2	
141	133.20	136.25	3.05	2.68	88	0.67	22	11	2	4	18	1	3	blocky ground

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
141	136.25	139.29	3.04	2.89	95	1.32	43	11	2	4	17	1	3	blocky ground
141	139.29	142.34	3.05	3.12	102	2.99	98	15	3	5	4	1	3	
141	142.34	145.39	3.05	3.05	100	3.05	100	14	2	4	6	1	1	dyke; weak slick contact
141	145.39	148.44	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
141	148.44	151.49	3.05	3.05	100	3.05	100	15	3	5	2	1	3	
141	151.49	154.53	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
141	154.53	157.58	3.05	2.89	95	2.76	90	14	3	5	7	1	2	
141	157.58	160.63	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
141	160.63	163.68	3.05	3.02	99	2.82	92	14	2	4	7	1	1	mineralized slick, 90 to c.a. rake
141	163.68	166.73	3.05	2.87	94	2.78	91	14	2	4	8	1	2	
141	166.73	169.77	3.04	3.04	100	3.04	100	15	3	5	3	1	2	
141	169.77	172.82	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
141	172.82	175.87	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
141	175.87	178.92	3.05	2.93	96	2.72	89	14	2	4	8	1	1	weak slicks; rake ± 50 to c.a.
141	178.92	181.97	3.05	2.87	94	2.52	83	13	2	4	12	1	3	
141	181.97	185.01	3.04	3.03	100	2.92	96	13	2	4	10	1	2	
141	185.01	188.06	3.05	3.05	100	2.85	93	14	2	4	8	1	1	weak slicks; no rake
141	188.06	191.11	3.05	2.96	97	2.73	90	14	2	4	8	1	2	
141	191.11	194.16	3.05	3.05	100	2.80	92	13	2	4	13	1	2	
141	194.16	197.21	3.05	3.05	100	2.83	93	13	2	4	11	1	2	
141	197.21	200.25	3.04	2.98	98	2.68	88	13	3	5	10	1	2	
141	200.25	203.30	3.05	3.02	99	2.86	94	14	3	5	9	1	2	
141	203.30	206.35	3.05	2.97	97	2.57	84	14	3	5	7	1	1	powder on fractures
141	206.35	209.40	3.05	3.02	99	3.02	99	15	3	5	5	1	2	
141	209.40	212.45	3.05	2.91	95	2.53	83	14	3	5	7	1	2	
141	212.45	215.49	3.04	2.98	98	2.66	87	14	3	5	8	1	2	
141	215.49	218.54	3.05	2.95	97	2.35	77	13	3	5	10	1	1	weak slicks
141	218.54	221.59	3.05	2.99	98	2.79	91	14	3	5	7	1	3	
141	221.59	224.64	3.05	3.05	100	3.05	100	14	2	4	6	1	3	
141	224.64	227.69	3.05	3.05	100	3.05	100	15	3	5	5	1	3	
141	227.69	230.73	3.04	3.07	101	2.94	97	14	2	4	9	1	2	
141	230.73	233.78	3.05	3.05	100	2.72	89	14	2	4	7	1	2	
141	233.78	236.83	3.05	3.05	100	2.60	85	14	2	4	8	1	2	
141	236.83	239.88	3.05	3.05	100	3.02	99	14	2	4	10	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
141	239.88	242.93	3.05	3.05	100	2.24	73	14	3	5	8	1	3	
141	242.93	245.97	3.04	3.04	100	2.14	70	14	3	5	7	1	2	
141	245.97	249.02	3.05	2.95	97	2.52	83	14	3	5	5	1	2	
141	249.02	252.06	3.04	2.98	98	2.36	78	14	3	5	7	1	2	
141	252.06	255.12	3.06	3.06	100	2.08	68	14	3	5	9	1	2	
141	255.12	258.17	3.05	3.05	100	2.01	66	14	3	5	8	1	2	
141	258.17	261.21	3.04	3.04	100	2.41	79	14	3	5	7	5	3	
141	261.21	264.26	3.05	3.05	100	2.52	83	14	3	5	6	1	3	
141	264.26	267.31	3.05	3.03	99	2.33	76	13	3	5	15	1	2	
141	267.31	270.36	3.05	3.02	99	3.02	99	14	3	5	10	1	2	2 10% broken core
141	270.36	273.41	3.05	3.05	100	2.55	84	13	3	5	12	1	2	
141	273.41	276.45	3.04	3.04	100	2.31	76	13	3	5	14	1	2	
141	276.45	279.50	3.05	3.05	100	2.02	66	13	3	5	12	1	2	
141	279.50	282.55	3.05	3.05	100	2.47	81	14	3	5	7	1	2	
141	282.55	285.60	3.05	3.05	100	1.61	53	10	3	5	25	5	2	2 283.1 to 283.3 m. - broken core
141	285.60	288.65	3.05	3.05	100	2.12	70	13	3	5	13	1	2	
141	288.65	291.69	3.04	3.04	100	2.50	82	14	3	5	10	1	2	
141	291.69	294.74	3.05	3.05	100	2.47	81	13	3	5	11	1	2	
141	294.74	297.79	3.05	3.05	100	3.05	100	14	3	5	7	1	2	
141	297.79	300.84	3.05	3.05	100	3.05	100	14	3	5	7	1	2	
141	300.84	303.58	2.74	2.74	100	1.97	72	12	3	5	15	1	2	
142	8.53	10.67	2.14	1.58	74	1.05	49	10	2	3	14	1	1	1 gouge on fractures
142	10.67	12.19	1.52	1.50	99	0.71	47	9	2	3	17	1	1	
142	12.19	14.33	2.14	2.97	139	1.47	69	12	2	3	16	1	1	1 blocks in wrong place
142	14.33	17.37	3.04	2.85	94	2.34	77	11	2	3	17	1	1	
142	17.37	20.42	3.05	2.97	97	2.15	70	13	2	4	12	1	2	
142	20.42	23.47	3.05	3.05	100	1.70	56	13	2	4	14	1	2	
142	23.47	26.52	3.05	2.89	95	2.12	70	14	2	4	9	1	2	
142	26.52	29.57	3.05	2.88	94	2.40	79	13	2	4	11	1	1	1 gouge on slick fractures 45 to c.a.
142	29.57	32.61	3.04	2.90	95	2.34	77	13	2	4	10	1	1	1 gouge on slick fractures 45 to c.a.
142	32.61	34.75	2.14	2.05	96	1.65	77	13	2	4	9	1	1	1 gouge on slick fractures 45 to c.a.
142	34.75	35.66	0.91	0.96	105	0.40	44	10	2	4	8	1	1	1 gouge on slick fractures 45 to c.a.
142	35.66	38.71	3.05	2.93	96	2.78	91	14	3	4	6	1	1	1 gouge on slick fractures 45 to c.a.
142	38.71	41.76	3.05	3.00	98	2.18	71	14	3	4	9	1	1	1 gouge on slick fractures 45 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
142	41.76	44.81	3.05	2.97	97	2.55	84	13	3	4	10	1	1 slip plane, 4 cm. clay	
142	44.81	47.85	3.04	3.02	99	2.76	91	14	3	5	7	1	1 gouge on fractures; mineralization	
142	47.85	50.90	3.05	3.05	100	3.05	100	15	4	5	5	1	2 mineralization on fractures	
142	50.90	53.95	3.05	3.05	100	3.05	100	15	4	5	5	1	2 mineralization on fractures	
142	53.95	57.00	3.05	3.05	100	2.88	94	14	3	4	8	1	1 healed gouge; min'l on fractures	
142	57.00	60.05	3.05	3.05	100	3.05	100	15	3	4	5	1	1 healed gouge; clay on fractures	
142	60.05	63.09	3.04	3.04	100	2.74	90	14	3	4	9	1	1 62.7 m.- gouge on contact 20 to c.a.	
142	63.09	66.14	3.05	3.05	100	3.05	100	15	4	5	4	1	3	
142	66.14	69.19	3.05	3.05	100	3.02	99	14	3	5	9	1	4	
142	69.19	72.24	3.05	3.05	100	3.05	100	14	4	5	7	1	2 gouge on fractures	
142	72.24	75.29	3.05	3.05	100	2.60	85	15	2	4	10	1	2 gouge on fractures	
142	75.29	78.33	3.04	3.04	100	2.52	83	13	2	4	13	1	2 gouge on fractures	
142	78.33	81.38	3.05	3.05	100	2.95	97	14	3	4	8	2	1	
142	81.38	84.43	3.05	2.78	91	2.51	82	13	3	5	12	1	2 gouge on fractures	
142	84.43	87.48	3.05	3.05	100	2.80	92	14	3	5	7	1	2	
142	87.48	90.53	3.05	2.86	94	2.50	82	13	2	4	12	1	1 slick at 45 to c.a.	
142	90.53	93.57	3.04	2.98	98	2.58	85	13	2	4	13	1	1 slick at 40 to c.a.	
142	93.57	96.62	3.05	3.05	100	2.85	93	14	3	4	8	3	1	
142	96.62	99.67	3.05	3.05	100	3.02	99	14	3	4	8	3	1	
142	99.67	102.72	3.05	3.05	100	3.11	102	14	3	4	6	3	1	
142	102.72	105.77	3.05	2.92	96	2.68	88	14	2	4	7	3	1	
142	105.77	108.81	3.04	3.04	100	2.94	97	15	3	5	5	1	1 slicks at 50 to c.a.	
142	108.81	111.86	3.05	3.05	100	3.01	99	15	3	5	5	3	1 slick contact at 20 to c.a.	
142	111.86	114.91	3.05	3.05	100	3.02	99	14	3	5	7	1	1 slicks	
142	114.91	117.96	3.05	3.05	100	2.95	97	14	3	5	7	1	1 slicks	
142	117.96	121.01	3.05	3.05	100	2.78	91	14	2	4	10	1	1 extreme slicks at 40 to c.a.	
142	121.01	124.05	3.04	3.00	99	3.00	99	14	2	4	8	1	1 extreme slicks at 40 to c.a.	
142	124.05	127.10	3.05	3.05	100	2.95	97	15	2	4	5	1	2	
142	127.10	130.15	3.05	3.05	100	3.02	99	14	3	5	6	1	2	
142	130.15	133.20	3.05	2.89	95	2.84	93	14	3	5	8	1	1 slick contact at 45 to c.a.	
142	133.20	136.24	3.04	2.84	93	2.84	93	15	3	5	3	1	2	
142	136.24	139.29	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
142	139.29	142.34	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
142	142.34	145.39	3.05	3.05	100	3.01	99	15	3	5	4	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
142	145.39	148.44	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
142	148.44	151.49	3.05	2.96	97	2.96	97	15	3	5	4	1	2	
142	151.49	154.53	3.04	3.00	99	2.85	94	14	3	5	5	2	1	1 weak slicks
142	154.53	157.58	3.05	3.02	99	2.90	95	15	3	5	5	3	1	1 weak slicks; gouge on fractures
142	157.58	160.63	3.05	3.00	98	3.00	98	15	3	5	5	1	1	1 weak slicks; gouge on fractures
142	160.63	163.68	3.05	3.10	102	3.10	102	15	3	5	3	1	1	1 weak slicks; gouge on fractures
142	163.68	166.73	3.05	3.05	100	3.05	100	15	3	5	2	1	1	1 weak slicks; gouge on fractures
142	166.73	169.78	3.05	3.05	100	3.05	100	15	3	5	4	3	2	
142	169.78	172.83	3.05	3.05	100	3.05	100	15	3	5	4	3	2	
142	172.83	175.87	3.04	3.04	100	2.93	96	15	3	5	4	1	1	1 slick joint
142	175.87	178.92	3.05	3.05	100	3.05	100	15	3	5	5	1	2	
142	178.92	181.97	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
142	181.97	185.01	3.04	3.04	100	3.05	100	15	3	5	5	1	2	
142	185.01	188.06	3.05	3.05	100	3.05	100	15	3	5	4	3	2	
142	188.06	191.11	3.05	3.05	100	3.04	100	15	4	5	3	1	3	
142	191.11	194.16	3.05	3.05	100	2.90	95	14	3	5	6	1	1	1 weak slick; several contacts
142	194.16	197.21	3.05	3.05	100	3.05	100	15	3	4	5	1	2	
142	197.21	200.25	3.04	3.05	100	3.05	100	15	3	5	2	1	2	
142	200.25	203.30	3.05	3.05	100	3.05	100	14	3	4	8	1	1	1 wk to mod. slicks 40 to c.a.; 80 rake
142	203.30	206.35	3.05	2.92	96	2.82	92	14	3	5	6	1	1	1 wk to mod. slicks 40 to c.a.; 80 rake
142	206.35	209.40	3.05	3.18	104	2.72	89	13	3	4	11	1	1	1 wk to mod. slicks 40 to c.a.; 80 rake
142	209.40	212.45	3.05	3.05	100	2.95	97	14	3	5	6	1	1	1 wk to mod. slicks 40 to c.a.; 80 rake
142	212.45	215.49	3.04	3.04	100	3.04	100	15	2	4	4	1	1	1 wk to mod. slicks 40 to c.a.; 80 rake
142	215.49	218.54	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
142	218.54	221.59	3.05	3.05	100	3.05	100	15	3	5	3	1	2	2 minor gouge
142	221.59	224.64	3.05	3.05	100	2.92	96	14	3	5	6	1	2	
142	224.64	227.69	3.05	3.05	100	2.99	98	15	3	5	4	1	2	
142	227.69	230.73	3.04	3.04	100	2.97	98	15	3	5	5	1	2	
142	230.73	233.78	3.05	3.05	100	3.05	100	14	3	5	7	1	2	
142	233.78	236.83	3.05	3.05	100	3.05	100	14	3	5	6	1	1	1 weak slicks
142	236.83	239.88	3.05	3.02	99	2.96	97	14	3	5	9	1	1	1 weak slicks
142	239.88	242.93	3.05	3.02	99	2.94	96	14	3	5	8	1	1	1 weak slicks
142	242.93	245.97	3.04	3.07	101	3.02	99	15	2	5	4	2	1	
142	245.97	249.02	3.05	3.02	99	2.65	87	15	2	5	5	1	1	1 strong slicks; gypsum

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
142	249.02	252.07	3.05	2.92	96	2.62	86	14	2	5	9	1	1	1 polished joint; very slick 45 to c.a.
142	252.07	255.12	3.05	3.04	100	2.51	82	14	2	5	8	1	1	1 weathering on joints; very slick
142	255.12	258.17	3.05	3.00	98	2.97	97	14	2	4	7	1	1	1 polished joints; very slick
142	258.17	261.21	3.04	3.20	105	3.20	105	15	2	4	4	1	2	
142	261.21	264.26	3.05	3.05	100	3.05	100	14	2	4	6	1	1	
142	264.26	267.31	3.05	3.05	100	2.75	90	14	2	5	7	2	1	1 gouge on slicks; moderate; no rake
142	267.31	270.36	3.05	2.90	95	2.57	84	13	2	4	14	1	2	
142	270.36	273.41	3.05	3.00	98	2.80	92	14	2	4	8	1	3	
142	273.41	276.45	3.04	2.98	98	2.88	95	14	3	5	9	1	3	
142	276.45	279.50	3.05	3.05	100	3.05	100	15	3	6	4	1	2	
142	279.50	282.55	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
142	282.55	285.60	3.05	3.02	99	3.02	99	15	3	6	1	1	3	3 pyrite on fractures
142	285.60	288.65	3.05	3.00	98	3.00	98	15	3	6	2	1	3	3 pyrite on fractures
142	288.65	291.69	3.04	3.04	100	3.04	100	15	3	5	3	1	3	
142	291.69	294.74	3.05	3.05	100	3.05	100	15	3	6	1	1	2	
142	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
142	297.79	300.84	3.05	2.98	98	2.98	98	15	3	6	1	1	3	
142	300.84	303.89	3.05	3.05	100	3.05	100	15	3	5	4	1	3	
142	303.89	306.93	3.04	3.04	100	2.99	98	14	3	5	6	1	3	3 gouge on fractures
142	306.93	309.98	3.05	3.02	99	2.92	96	15	3	4	4	1	3	
142	309.98	313.03	3.05	3.05	100	3.02	99	14	3	4	6	1	2	
142	313.03	316.08	3.05	3.05	100	2.85	93	14	3	4	7	1	2	
142	316.08	319.13	3.05	3.05	100	3.02	99	15	3	5	4	1	2	
142	319.13	322.17	3.04	3.05	100	3.05	100	15	3	5	3	1	2	
142	322.17	325.22	3.05	3.05	100	2.92	96	14	3	4	7	1	1	1 slick; no rake; weathering
142	325.22	328.27	3.05	3.05	100	2.90	95	15	3	5	4	1	2	
142	328.27	331.32	3.05	3.14	103	3.14	103	15	3	5	4	1	2	
142	331.32	334.36	3.04	2.98	98	2.86	94	14	3	5	5	1	2	
142	334.36	337.41	3.05	3.02	99	3.02	99	14	3	5	6	1	2	
142	337.41	340.46	3.05	3.00	98	2.86	94	14	3	4	8	1	1	1 gouge on slick fractures at 60 to c.a.
142	340.46	343.51	3.05	3.05	100	2.85	93	14	2	4	9	1	1	1 healed gouge 10 to 15 cm.
142	343.51	346.56	3.05	3.11	102	3.11	102	15	3	5	4	1	1	1 weak slicks 40 to c.a.
142	346.56	349.61	3.05	2.92	96	2.65	87	14	3	4	7	1	1	1 weak slicks 40 to c.a.
142	349.61	352.65	3.04	3.09	102	2.69	88	14	2	4	10	1	1	1 mineralized slick; rake + 10 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
142	352.65	355.70	3.05	3.05	100	2.81	92	14	2	4	8	3	3	
142	355.70	358.75	3.05	2.98	98	2.98	98	15	4	5	4	1	2	
142	358.75	361.80	3.05	3.05	100	3.05	100	15	3	5	3	1	1	1 weak slicks; mineralized
142	361.80	364.85	3.05	3.05	100	2.95	97	15	3	5	5	1	1	1 slick with gouge; rake -45, 50 to c.a.
142	364.85	367.90	3.05	2.97	97	2.97	97	14	3	5	8	1	2	
142	367.90	370.94	3.04	3.09	102	3.09	102	15	3	5	3	1	2	
142	370.94	373.99	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
142	373.99	377.04	3.05	3.02	99	3.02	99	15	3	5	3	1	1	1 very well polished; 45 to c.a.; no rake
142	377.04	380.09	3.05	3.00	98	3.00	98	15	3	5	5	1	3	
142	380.09	383.13	3.04	3.05	100	3.05	100	15	3	5	4	1	2	
142	383.13	386.18	3.05	3.02	99	3.02	99	15	3	5	4	1	2	
142	386.18	389.23	3.05	3.05	100	3.01	99	15	3	5	4	1	1	2 4 cm. of healed gouge
142	389.23	392.28	3.05	3.04	100	3.04	100	15	3	5	4	1	2	
142	392.28	395.33	3.05	3.05	100	3.05	100	15	3	5	4	1	1	1 weak slicks
142	395.33	398.37	3.04	2.94	97	2.82	93	14	3	5	6	1	1	
142	398.37	401.42	3.05	3.10	102	2.54	83	15	2	4	4	1	1	1 weak slicks 55 to c.a.
142	401.42	404.47	3.05	3.05	100	2.87	94	14	2	5	8	1	1	1 weak slicks 55 to c.a.
142	404.47	407.52	3.05	3.05	100	3.05	100	15	2	5	4	1	2	
142	407.52	410.57	3.05	3.10	102	3.10	102	15	3	5	3	1	2	
142	410.57	413.61	3.04	3.05	100	3.05	100	15	3	5	4	1	1	1 gouge on weak slicks
142	413.61	416.66	3.05	2.94	96	2.78	91	14	2	5	5	1	1	2 gouge on fracture; H=0
142	416.66	419.71	3.05	3.05	100	3.05	100	14	3	5	6	1	2	
142	419.71	422.76	3.05	3.06	100	3.05	100	15	3	5	4	1	2	
142	422.76	425.81	3.05	3.00	98	2.90	95	15	3	5	3	1	2	
142	425.81	428.85	3.04	2.98	98	2.68	88	14	2	5	7	1	1	1 gouge on slicks
142	428.85	431.90	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
142	431.90	434.95	3.05	3.02	99	3.02	99	15	3	5	4	1	1	1 slick fractures to 50 to c.a.
142	434.95	438.00	3.05	3.05	100	3.05	100	15	3	5	4	1	1	1 contact at 25 to c.a.
142	438.00	441.05	3.05	3.10	102	3.00	98	15	2	4	4	1	2	2 10 cm. of healed gouge
142	441.05	444.09	3.04	3.09	102	3.09	102	15	3	5	3	1	2	
142	444.09	447.14	3.05	3.05	100	2.85	93	15	3	5	5	1	2	
142	447.14	450.19	3.05	2.75	90	2.64	87	15	3	5	3	1	2	
142	450.19	453.24	3.05	2.79	91	2.79	91	15	3	5	3	1	3	
142	453.24	456.29	3.05	3.05	100	3.05	100	15	3	5	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
142	456.29	459.33	3.04	3.04	100	3.04	100	15	3	5	3	1	1	1 weak slicks
142	459.33	462.38	3.05	3.05	100	3.00	98	15	3	5	3	1	2	
142	462.38	465.43	3.05	3.05	100	3.00	98	15	2	5	5	1	1	1 slick contact
142	465.43	468.48	3.05	3.05	100	2.73	90	14	2	4	8	1	1	1 30% healed gouge on fractures
142	468.48	471.53	3.05	2.96	97	2.60	85	13	2	4	12	1	1	1 10% healed gouge; slicks
142	471.53	474.57	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
142	474.57	477.62	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
142	477.62	480.67	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
142	480.67	483.72	3.05	3.05	100	3.05	100	14	2	5	7	1	2	2 mineralized fractures
142	483.72	485.55	1.83	1.83	100	1.71	93	13	2	5	6	1	2	2 mineralized fractures; blocky ground
142	485.55	488.59	3.04	3.03	100	3.03	100	14	2	5	4	1	2	2 mineralized fractures
142	488.59	491.03	2.44	2.45	100	2.45	100	15	2	5	3	1	2	2 mineralized fractures
142	491.03	494.08	3.05	3.11	102	3.05	100	14	2	4	7	1	1	1 gouge on fractures; slicks
142	494.08	497.13	3.05	2.98	98	2.70	89	14	2	5	8	1	1	1 gouge on fractures; slicks
142	497.13	500.18	3.05	3.14	103	3.00	98	14	2	5	7	1	1	1 gouge on fractures; slicks
142	500.18	503.22	3.04	3.08	101	2.68	88	13	2	5	11	1	1	1 gouge on fractures; slicks
142	503.22	506.27	3.05	3.10	102	2.88	94	14	2	5	6	1	1	1 weak slicks; 30 cm. healed gouge
142	506.27	509.32	3.05	3.07	101	2.64	87	14	2	4	9	1	1	1 weak slicks
142	509.32	512.37	3.05	2.90	95	2.70	89	14	2	4	7	1	1	1 weak slicks
142	512.37	514.20	1.83	1.49	81	1.49	81	15	3	5	3	1	1	1 weak slicks; slip plane 25 to c.a.
142	514.20	517.25	3.05	3.05	100	3.01	99	15	3	5	3	1	1	1 weak slicks
142	517.25	520.29	3.04	3.01	99	2.91	96	15	3	5	3	1	1	1 weak slicks
142	520.29	523.34	3.05	3.05	100	1.17	38	10	1	3	30	1	1	1 weak slicks; 50% gouge; part healed
142	523.34	526.39	3.05	3.02	99	2.75	90	14	2	3	9	1	2	
142	526.39	529.44	3.05	3.05	100	2.91	95	14	2	4	8	1	2	
143	6.10	7.32	1.22	0.80	66	0.00	0	13	2	3	13	1	1	1 weathered joints, gouge, slicks
143	7.32	10.06	2.74	2.95	108	1.57	57	12	2	4	16	1	1	1 weathered joints, gouge, slicks
143	10.06	13.11	3.05	3.02	99	2.72	89	14	2	4	9	1	1	1 weathered joints, gouge, slicks
143	13.11	16.46	3.35	2.70	81	0.98	29	8	2	3	35	1	1	1 40 cm. of gouge
143	16.46	19.51	3.05	3.20	105	2.92	96	12	2	4	17	1	1	1 weak slicks
143	19.51	22.56	3.05	2.97	97	1.84	60	12	2	4	15	1	1	1 weak slicks
143	22.56	25.60	3.04	2.62	86	1.72	57	9	2	4	28	1	1	1 40% gouge
143	25.60	28.65	3.05	2.95	97	2.50	82	14	3	5	8	1	2	
143	28.65	31.70	3.05	3.08	101	2.90	95	14	3	5	7	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
143	31.70	34.75	3.05	3.08	101	2.81	92	14	3	5	8	1	1 weak slicks
143	34.75	37.80	3.05	3.07	101	2.99	98	15	2	5	5	1	2
143	37.80	38.71	0.91	0.79	87	0.79	87	15	2	5	1	1	2
143	38.71	41.76	3.05	2.96	97	2.86	94	14	2	5	5	1	3
143	41.76	44.81	3.05	2.90	95	2.55	84	13	2	5	13	1	3 gouge on fractures
143	44.81	47.85	3.04	3.12	103	3.07	101	14	2	5	6	1	1 gouge on fractures
143	47.85	50.90	3.05	3.05	100	2.85	93	14	2	5	9	1	3
143	50.90	53.95	3.05	2.92	96	2.54	83	13	2	5	10	1	2
143	53.95	57.00	3.05	3.02	99	2.78	91	14	2	5	8	1	1 slick joints
143	57.00	60.05	3.05	3.02	99	2.97	97	15	2	5	4	1	2
143	60.05	63.09	3.04	3.04	100	3.04	100	15	2	5	4	1	2
143	63.09	66.14	3.05	3.15	103	3.01	99	14	2	4	7	2	3 dyke
143	66.14	69.19	3.05	3.05	100	2.60	85	13	3	5	10	1	2
143	69.19	72.24	3.05	3.05	100	3.05	100	14	3	5	6	2	2
143	72.24	75.29	3.05	2.76	90	2.62	86	14	2	5	8	1	2
143	75.29	78.33	3.04	3.05	100	2.81	92	14	2	5	8	1	1 gypsum on fractures
143	78.33	81.38	3.05	3.05	100	3.05	100	15	2	5	5	2	2 minor gouge on fractures
143	81.38	84.43	3.05	3.00	98	3.00	98	15	2	5	5	1	2
143	84.43	87.48	3.05	3.12	102	2.95	97	15	2	5	5	1	2
143	87.48	90.53	3.05	3.00	98	2.83	93	15	2	5	5	1	2
143	90.53	92.96	2.43	2.65	109	1.63	67	12	2	4	16	1	1 weak slicks
143	92.96	94.18	1.22	1.05	86	0.00	0	7	1	3	19	1	1 50% gouge; not healed
143	94.18	96.62	2.44	2.41	99	0.64	26	9	1	3	30	1	1 50% gouge; not healed
143	96.62	99.67	3.05	2.88	94	2.46	81	13	2	4	12	1	1 gouge on fractures; slick
143	99.67	102.72	3.05	2.95	97	2.17	71	11	2	4	20	1	1 gouge on fractures; slick
143	102.72	104.55	1.83	1.87	102	0.90	49	11	2	4	12	1	1 gouge on fractures; slick
143	104.55	107.59	3.04	3.00	99	2.26	74	13	2	4	13	1	1 gouge on fractures; slick
143	107.59	109.55	1.96	1.04	53	1.04	53	14	2	4	3	1	1 weak slicks
143	109.55	110.64	1.09	1.90	174	1.90	174	15	2	4	3	1	3 misplaced block
143	110.64	113.69	3.05	3.10	102	2.52	83	13	2	4	13	1	1 mineralized slicks
143	113.69	116.74	3.05	3.00	98	2.93	96	14	2	4	6	3	1 shearing 15 to c.a., -45 rake
143	116.74	119.79	3.05	3.00	98	2.92	96	15	3	5	5	1	2
143	119.79	122.83	3.04	2.93	96	2.86	94	14	3	5	5	1	1 clay on slicks
143	122.83	125.88	3.05	3.05	100	3.02	99	15	2	5	4	1	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
143	125.88	127.10	1.22	1.32	108	1.22	100	14	2	5	3	1	3	
143	127.10	130.15	3.05	3.04	100	3.04	100	14	2	4	7	1	1	1 healed gouge on slicks 15 to c.a.
143	130.15	133.20	3.05	3.00	98	2.85	93	14	2	4	8	1	1	
143	133.20	136.25	3.05	3.04	100	2.97	97	15	4	5	5	3	2	
143	136.25	139.29	3.04	3.07	101	3.07	101	15	4	5	5	3	1	
143	139.29	142.34	3.05	3.00	98	2.80	92	15	3	3	8	3	1	
143	142.34	145.39	3.05	3.15	103	2.48	81	15	3	3	16	1	2	
143	145.39	148.44	3.05	3.00	98	3.00	98	14	3	4	6	1	1	
143	148.44	151.49	3.05	3.05	100	3.05	100	14	3	4	7	3	3	
143	151.49	154.53	3.04	3.04	100	2.88	95	15	3	5	4	2	2	
143	154.53	157.58	3.05	3.02	99	2.87	94	15	3	5	3	3	1	
143	157.58	160.63	3.05	3.05	100	2.95	97	14	3	4	6	3	1	
143	160.63	163.68	3.05	3.04	100	3.04	100	15	3	4	5	3	1	
143	163.68	166.73	3.05	3.04	100	2.75	90	14	3	4	6	3	1	
143	166.73	169.77	3.04	3.00	99	2.91	96	14	3	4	8	3	1	
143	169.77	172.82	3.05	3.11	102	3.11	102	14	3	4	8	3	1	
143	172.82	175.87	3.05	3.12	102	3.12	102	15	3	4	5	1	1	
143	175.87	178.92	3.05	3.06	100	3.00	98	15	3	4	5	3	1	
143	178.92	181.97	3.05	3.05	100	2.88	94	15	3	4	5	3	1	
143	181.97	185.01	3.04	3.04	100	2.85	94	14	3	4	9	1	2	
143	185.01	188.06	3.05	3.05	100	2.97	97	15	3	4	4	3	1	
143	188.06	191.11	3.05	3.05	100	3.05	100	14	3	4	6	3	2	
143	191.11	194.16	3.05	3.05	100	3.05	100	15	3	4	3	3	1	
143	194.16	197.21	3.05	3.03	99	3.03	99	15	3	4	3	3	1	
143	197.21	200.25	3.04	3.04	100	2.94	97	15	3	4	5	3	2	
143	200.25	203.30	3.05	3.00	98	2.99	98	15	3	4	3	3	2	
143	203.30	206.35	3.05	3.08	101	2.70	89	14	3	3	8	1	2	
143	206.35	209.40	3.05	3.05	100	3.05	100	15	3	4	3	3	3	
143	209.40	212.45	3.05	3.15	103	3.15	103	15	3	4	4	3	3	
143	212.45	215.49	3.04	3.03	100	3.03	100	15	3	4	4	3	3	
143	215.49	218.54	3.05	3.04	100	3.03	99	15	3	4	4	1	1	
143	218.54	221.59	3.05	3.02	99	2.98	98	15	3	4	4	3	2	
143	221.59	224.64	3.05	3.10	102	3.06	100	15	3	5	3	3	3	
143	224.64	227.69	3.05	3.02	99	2.79	91	15	3	4	4	1	1	1 gypsum fracture; minor gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
143	227.69	230.73	3.04	3.10	102	3.10	102	15	3	4	3	4	2	
143	230.73	233.78	3.05	3.04	100	3.04	100	15	3	4	3	3	3	
143	233.78	236.83	3.05	3.10	102	3.10	102	15	3	4	3	3	3	
143	236.83	239.88	3.05	3.05	100	3.05	100	15	3	4	4	3	2	
143	239.88	242.93	3.05	3.03	99	2.88	94	15	3	4	5	3	2	
143	242.93	245.97	3.04	3.06	101	2.94	97	15	3	4	4	3	2	
143	245.97	249.02	3.05	3.00	98	3.00	98	15	3	4	3	3	3	
143	249.02	252.07	3.05	3.10	102	3.10	102	15	3	4	4	3	2	
143	252.07	255.12	3.05	3.00	98	3.00	98	15	3	4	5	1	2	
143	255.12	258.17	3.05	3.04	100	2.94	96	15	3	4	3	3	2	
143	258.17	261.21	3.04	3.05	100	3.05	100	15	3	4	3	3	3	
143	261.21	264.26	3.05	3.10	102	2.53	83	14	2	4	6	3	2	3 gouge zone at 30 to c.a.
143	264.26	267.31	3.05	2.95	97	2.95	97	14	0	2	6	3	2	2 gouge zone at 30 to c.a.
143	267.31	270.36	3.05	3.10	102	3.10	102	15	3	4	4	3	2	
143	270.36	273.41	3.05	3.05	100	3.05	100	15	3	4	5	3	2	
143	273.41	276.45	3.04	3.08	101	3.04	100	14	2	3	7	3	2	2 stressed rx
143	276.45	279.50	3.05	3.10	102	2.85	93	14	2	3	7	3	1	1 stressed rx
143	279.50	282.55	3.05	3.05	100	2.70	89	14	3	3	6	3	3	3 qz veining; minor 0.5 cm. gouge
143	282.55	285.60	3.05	3.03	99	2.80	92	14	2	4	8	3	1	1 1 cm. wide gouge zone 40 to c.a.
143	285.60	288.65	3.05	2.90	95	2.19	72	13	2	4	12	3	1	1 minor gouge; 5 cm. clay present
143	288.65	291.69	3.04	2.93	96	2.72	89	14	2	4	5	3	1	
143	291.69	294.74	3.05	3.10	102	2.98	98	14	3	5	7	1	1	1 gouge on weak slicks, 50 to c.a.
143	294.74	297.79	3.05	3.08	101	3.08	101	15	3	5	4	1	3	
143	297.79	300.84	3.05	3.07	101	3.07	101	15	3	5	2	1	2	
143	300.84	303.89	3.05	3.02	99	2.95	97	15	3	5	3	3	1	1 slick joints, no rake
143	303.89	306.94	3.05	3.05	100	3.00	98	14	2	5	8	2	3	
143	306.94	309.98	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
143	309.98	313.03	3.05	3.05	100	3.05	100	15	3	5	5	2	1	1 powder on fracture
143	313.03	316.08	3.05	3.05	100	3.05	100	15	3	5	5	1	2	
143	316.08	319.13	3.05	3.05	100	3.01	99	13	2	4	12	3	1	1 4 cm. gouge, H=0 to 1
143	319.13	322.17	3.04	3.04	100	2.94	97	14	3	5	6	1	1	1 slicks with gouge, 1 cm. wide
143	322.17	325.22	3.05	2.96	97	2.88	94	14	3	5	5	1	2	
143	325.22	328.27	3.05	3.05	100	2.92	96	15	3	5	5	1	2	
143	328.27	331.32	3.05	3.11	102	3.11	102	15	3	5	3	1	2	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
143	331.32	334.37	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
143	334.37	337.41	3.04	3.04	100	3.04	100	15	3	5	3	1	2	
143	337.41	340.46	3.05	3.05	100	3.05	100	15	2	5	3	1	2	
143	340.46	343.51	3.05	3.02	99	2.90	95	15	2	5	5	3	1	2 gouge on fractures; slick
143	343.51	346.56	3.05	3.10	102	3.10	102	15	3	5	3	1	3	
143	346.56	349.61	3.05	3.05	100	2.74	90	14	3	5	6	3	1	1 very slick, rake -45 to c.a.
143	349.61	352.65	3.04	3.02	99	2.70	89	14	3	5	7	3	1	1 very slick
143	352.65	355.70	3.05	3.11	102	2.96	97	15	3	5	5	1	1	1 gouge on weak slicks
143	355.70	358.75	3.05	3.02	99	3.02	99	15	3	5	4	1	1	1 weak slick, 90 rake
143	358.75	361.80	3.05	2.97	97	2.97	97	15	3	5	4	1	2	
143	361.80	364.85	3.05	3.10	102	2.78	91	13	2	4	11	1	1	1 gouge, very slick, 10 cm. of H=1
143	364.85	367.89	3.04	3.00	99	3.00	99	15	3	5	2	1	1	1 gouge, very slick
143	367.89	370.94	3.05	3.05	100	3.05	100	15	3	5	2	1	1	1 gouge, very slick
143	370.94	373.99	3.05	3.05	100	2.92	96	15	3	5	5	1	3	
143	373.99	377.04	3.05	2.90	95	2.81	92	15	3	5	4	3	3	
143	377.04	380.09	3.05	3.05	100	2.60	85	13	2	4	12	1	1	1 2 cm. of gouge, H=0; strong slick
143	380.09	383.13	3.04	2.93	96	2.83	93	14	3	4	7	3	1	
143	383.13	386.18	3.05	3.05	100	3.05	100	15	3	5	5	1	2	2 mineralized fractures
143	386.18	389.23	3.05	3.05	100	2.86	94	14	3	5	8	1	1	1 mineralized fractures; slick at 45 to c.a.
143	389.23	392.28	3.05	3.09	101	3.01	99	15	2	4	5	1	1	1 weak slicks
143	392.28	395.33	3.05	3.07	101	3.05	100	15	2	4	4	1	1	1 2 cm. of gouge; slick
143	395.33	398.37	3.04	3.10	102	3.10	102	15	3	5	3	1	3	
143	398.37	401.42	3.05	2.98	98	2.76	90	14	3	5	8	3	2	
143	401.42	404.47	3.05	2.94	96	2.77	91	13	3	4	11	3	1	
143	404.47	407.52	3.05	3.10	102	3.10	102	14	3	4	10	3	2	
143	407.52	410.57	3.05	3.08	101	1.61	53	13	3	4	11	3	1	1 carbonate shears
143	410.57	413.61	3.04	3.10	102	2.69	88	13	2	2	12	3	2	2 healed gouge
143	413.61	415.14	1.53	1.45	95	1.19	78	9	0	1	15	3	1	1 20 cm. gouge, 80-90 to c.a., 1-3 cm.
144	9.14	11.28	2.14	1.28	60	0.00	0	4	2	3	40	1	1	1 Slicks due to bedding laminae, no rake
144	11.28	14.33	3.05	2.47	81	0.00	0	7	2	3	40	1	1	1 Slicks due to bedding laminae, no rake
144	14.33	15.85	1.52	1.18	78	0.00	0	4	2	3	60	1	1	1 Slicks due to bedding laminae, no rake
144	15.85	16.46	0.61	0.70	115	0.00	0	3	2	3	50	1	1	1 Slicks due to bedding laminae, no rake
144	16.46	17.68	1.22	1.40	115	0.00	0	5	2	3	50	1	1	1 Slicks due to bedding laminae, no rake
144	17.68	18.29	0.61	1.29	211	0.00	0	5	2	3	50	1	1	1 Slicks due to bedding laminae, no rake

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
144	18.29	20.12	1.83	1.67	91	0.00	0	5	2	3	50	1	1	1 Slicks due to bedding laminae, no rake
144	20.12	21.34	1.22	1.20	98	0.00	0	4	2	3	50	1	1	1 Slicks due to bedding laminae, no rake
144	21.34	22.86	1.52	1.32	87	0.00	0	4	2	3	50	1	1	1 Slicks due to bedding laminae, no rake
144	22.86	24.08	1.22	0.81	66	0.00	0	2	2	3	80	1	1	1 Slicks due to bedding laminae, no rake
144	24.08	26.52	2.44	0.21	9	0.00	0	2	2	3	30	1	1	1 Slicks due to bedding laminae, no rake
144	26.52	29.57	3.05	0.47	15	0.00	0	3	2	3	40	1	1	1 Slicks due to bedding laminae, no rake
145	3.66	5.18	1.52	1.16	76	0.37	24	10	2	4	9	1	3	
145	5.18	7.32	2.14	2.28	107	1.77	83	13	3	4	8	1	3	
145	7.32	10.36	3.04	2.77	91	2.40	79	14	3	4	8	1	2	
145	10.36	13.41	3.05	3.17	104	3.17	104	15	3	4	4	1	2	
145	13.41	14.33	0.92	0.96	104	0.96	104	14	3	4	3	1	3	
145	14.33	17.37	3.04	3.00	99	2.70	89	14	4	5	7	1	2	
145	17.37	20.42	3.05	3.10	102	2.86	94	14	4	5	8	3	2	
145	20.42	22.86	2.44	2.63	108	1.52	62	11	4	5	17	1	2	
145	22.86	26.21	3.35	3.05	91	1.83	55	13	4	4	13	3	2	
145	26.21	27.43	1.22	1.42	116	0.63	52	11	4	4	9	3	2	
145	27.43	29.57	2.14	2.85	133	1.32	62	13	4	4	12	3	1	
145	29.57	32.61	3.04	2.92	96	2.17	71	14	2	5	9	3	1	
145	32.61	35.66	3.05	2.82	92	2.20	72	13	2	5	10	3	1	
145	35.66	38.71	3.05	3.05	100	2.30	75	13	2	5	11	1	1	1 minor gouge, slicks
145	38.71	41.76	3.05	3.11	102	2.22	73	13	2	4	12	1	3	
145	41.76	44.81	3.05	3.05	100	2.00	66	12	2	4	17	1	3	
145	44.81	47.85	3.04	3.00	99	1.93	63	13	2	4	14	2	2	
145	47.85	50.29	2.44	2.56	105	2.44	100	13	2	4	13	1	2	
145	50.29	53.34	3.05	3.05	100	2.35	77	13	2	4	11	1	2	
145	53.34	56.39	3.05	2.94	96	1.56	51	12	2	4	18	1	1	1 minor gouge
145	56.39	59.44	3.05	2.96	97	2.48	81	14	4	4	9	1	2	
145	59.44	60.96	1.52	1.73	114	1.45	95	15	4	5	4	1	2	
145	60.96	63.09	2.13	1.71	80	1.60	75	15	4	5	3	1	2	
145	63.09	66.14	3.05	2.92	96	2.05	67	15	4	5	5	1	2	
145	66.14	69.19	3.05	3.05	100	3.05	100	15	4	5	4	1	2	
145	69.19	72.24	3.05	3.05	100	2.80	92	15	2	4	5	1	1	
145	72.24	75.29	3.05	3.10	102	2.71	89	14	2	4	7	1	1	
145	75.29	78.33	3.04	3.02	99	2.76	91	15	2	4	5	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
145	78.33	81.38	3.05	2.90	95	2.57	84	14	2	4	7	1	1	1 slick contact at 10 to c.a.
145	81.38	84.43	3.05	3.12	102	3.00	98	14	2	4	6	1	1	
145	84.43	87.48	3.05	2.79	91	2.79	91	15	3	5	4	1	1	
145	87.48	90.53	3.05	2.92	96	2.92	96	14	3	5	7	1	1	1 weak slicks at 15 to c.a.
145	90.53	93.57	3.04	3.01	99	3.01	99	14	3	5	6	1	1	
145	93.57	96.62	3.05	3.10	102	3.10	102	15	3	5	3	1	1	1 gypsum on fractures
145	96.62	99.67	3.05	2.99	98	2.99	98	15	3	5	2	1	1	1 slick powder
145	99.67	102.72	3.05	3.05	100	3.05	100	15	3	5	3	1	1	
145	102.72	105.77	3.05	3.05	100	3.05	100	15	3	5	3	1	1	
145	105.77	108.81	3.04	3.00	99	3.00	99	15	3	5	4	1	2	
145	108.81	111.86	3.05	3.01	99	3.01	99	15	3	5	3	1	2	
145	111.86	114.91	3.05	3.05	100	2.51	82	13	3	5	11	1	1	1 15 to c.a.
145	114.91	117.96	3.05	3.00	98	3.00	98	14	3	5	8	1	1	1 weak slicks, 40 to c.a.
145	117.96	121.01	3.05	3.08	101	3.08	101	14	3	5	6	1	1	1 polished surface
145	121.01	124.05	3.04	2.95	97	2.95	97	14	3	5	5	1	3	
145	124.05	127.10	3.05	2.92	96	2.86	94	14	3	5	6	1	3	
145	127.10	130.15	3.05	3.10	102	2.98	98	14	2	5	7	1	2	
145	130.15	133.20	3.05	2.98	98	2.88	94	14	4	5	7	2	1	1 gouge on fracture, 0 to 5 to c.a.
145	133.20	136.25	3.05	3.08	101	2.32	76	14	2	4	9	1	2	
145	136.25	139.29	3.04	2.83	93	2.13	70	13	2	4	14	1	2	
145	139.29	142.34	3.05	3.02	99	2.79	91	14	2	5	8	1	2	
145	142.34	145.39	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
145	145.39	148.44	3.05	3.05	100	3.05	100	15	3	5	4	1	2	
145	148.44	151.49	3.05	3.05	100	2.96	97	14	3	5	6	1	2	
145	151.49	154.53	3.04	3.05	100	2.95	97	14	3	5	7	1	2	
145	154.53	157.58	3.05	3.05	100	3.05	100	14	3	5	7	1	2	
145	157.58	160.63	3.05	3.05	100	2.88	94	14	3	5	8	1	1	1 powder on fractures
145	160.63	163.68	3.05	3.05	100	2.77	91	14	3	5	6	1	1	1 powder on fractures
145	163.68	166.73	3.05	3.05	100	3.05	100	15	3	5	3	1	2	2 fractures at 35 to c.a.
145	166.73	169.77	3.04	3.16	104	3.06	101	14	3	5	7	1	2	
145	169.77	172.82	3.05	3.05	100	3.05	100	15	4	5	2	1	3	
145	172.82	175.87	3.05	3.05	100	3.05	100	15	3	5	2	3	3	
145	175.87	178.92	3.05	3.05	100	2.91	95	15	2	5	4	1	1	1 slick joint, no rake, at 15 to c.a.
145	178.92	181.97	3.05	3.05	100	3.05	100	15	3	5	5	1	1	1 weak slicks, 15 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
145	181.97	185.01	3.04	2.98	98	2.50	82	13	2	5	10	1	1	
145	185.01	188.06	3.05	3.00	98	2.85	93	13	2	5	10	1	1	1 minor gouge with slicks, gypsum
145	188.06	191.11	3.05	3.00	98	2.91	95	15	3	5	4	1	1	
145	191.11	194.16	3.05	2.90	95	2.90	95	15	3	5	4	1	1	1 gypsum slicks, 5 to c.a.
145	194.16	197.21	3.05	3.08	101	3.02	99	14	3	5	7	1	1	1 gypsum slicks, 25 to c.a.
145	197.21	200.25	3.04	3.05	100	2.92	96	15	3	5	4	1	1	1 gypsum slicks, 45 to c.a.
145	200.25	203.30	3.05	2.90	95	2.76	90	14	3	5	6	1	1	1 gypsum slicks, 45 to c.a.
145	203.30	206.35	3.05	3.00	98	2.86	94	15	3	5	3	1	1	1 slicks at 45 to c.a., 45 rake
145	206.35	209.40	3.05	3.00	98	2.81	92	14	3	5	6	1	1	1 strong slicks at 35 to c.a., 45 to c.a. rake
145	209.40	212.45	3.05	3.03	99	3.03	99	15	3	5	4	1	1	1 weak slicks at 35 to 40 to c.a.
145	212.45	215.49	3.04	2.98	98	2.87	94	15	3	5	5	1	1	1 very slick at 50 to c.a., -70 rake
145	215.49	218.54	3.05	2.97	97	2.23	73	12	2	4	15	1	1	
145	218.54	221.59	3.05	3.02	99	2.70	89	13	2	4	12	1	1	
145	221.59	224.64	3.05	3.05	100	3.05	100	15	2	5	3	2	1	1 gouge on slicks
145	224.64	227.69	3.05	3.05	100	3.05	100	15	2	5	2	3	1	
145	227.69	230.73	3.04	3.05	100	3.05	100	15	3	5	4	1	3	
145	230.73	233.78	3.05	3.05	100	3.05	100	15	3	5	3	3	1	1 fractures at 20 to c.a.
145	233.78	236.83	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
145	236.83	239.88	3.05	2.97	97	2.90	95	15	3	5	4	1	1	1 slick w/ gouge at 28 to c.a.
145	239.88	241.71	1.83	1.85	101	1.14	62	7	2	4	30	1	1	1 40% gouge, H=1
145	241.71	244.75	3.04	2.45	81	1.35	44	8	2	4	30	1	1	1 20 cm. of H=0
145	244.75	247.80	3.05	3.05	100	3.05	100	15	4	6	2	1	2	2 mineralized fractures
145	247.80	249.02	1.22	1.45	119	1.45	119	15	3	5	1	1	2	
145	249.02	252.07	3.05	3.05	100	3.05	100	15	3	5	3	1	2	2 powder on joints
145	252.07	255.12	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
145	255.12	258.17	3.05	3.05	100	3.05	100	15	3	6	3	1	3	
145	258.17	261.21	3.04	3.05	100	3.05	100	15	3	6	2	1	3	
145	261.21	264.26	3.05	3.05	100	3.05	100	15	3	6	1	1	3	
145	264.26	267.31	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
145	267.31	270.36	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
145	270.36	273.41	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
145	273.41	276.45	3.04	3.02	99	3.02	99	15	3	5	3	1	2	
145	276.45	279.50	3.05	3.11	102	3.00	98	14	3	5	6	1	1	1 gypsum & pyrite slick, 60 to c.a., 0 rake
145	279.50	281.64	2.14	1.90	89	1.13	53	12	2	4	11	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
145	281.64	283.77	2.13	2.12	100	1.88	88	13	3	5	8	1	1	1 slick contact 25 to c.a.
145	283.77	285.60	1.83	1.89	103	1.56	85	12	2	5	10	1	1	
145	285.60	288.65	3.05	3.05	100	2.65	87	14	2	4	8	1	1	1 slick contact 12 to c.a.
145	288.65	291.69	3.04	3.04	100	2.70	89	13	2	4	14	1	1	1 weak slicks, minor gouge
145	291.69	294.74	3.05	2.95	97	2.95	97	15	3	5	4	3	2	
145	294.74	297.79	3.05	3.00	98	3.00	98	15	3	5	3	1	2	
145	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
145	300.84	303.89	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
145	303.89	306.93	3.04	3.04	100	3.04	100	15	3	5	4	1	2	
145	306.93	309.98	3.05	3.05	100	3.05	100	14	2	5	8	3	2	
145	309.98	313.03	3.05	3.05	100	2.74	90	14	2	5	6	3	1	1 slick at 55 to c.a.
145	313.03	316.08	3.05	3.05	100	2.02	66	13	2	4	13	3	1	1 gypsum on fractures at 40 to c.a.
145	316.08	319.13	3.05	3.05	100	2.94	96	15	3	5	5	1	3	
145	319.13	322.17	3.04	3.04	100	3.04	100	15	3	5	2	3	2	2 gouge on fractures
145	322.17	325.22	3.05	3.05	100	3.05	100	15	3	5	3	1	1	1 weak slicks, gouge
145	325.22	328.27	3.05	3.05	100	3.05	100	15	3	5	2	1	1	1 weak slicks, gouge
145	328.27	331.32	3.05	3.05	100	3.00	98	15	3	5	4	1	1	1 weak slicks, gouge, 45 to c.a.
145	331.32	334.37	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
145	334.37	337.41	3.04	3.04	100	3.04	100	15	4	6	2	1	2	
145	337.41	340.46	3.05	2.80	92	2.80	92	15	3	5	2	1	1	
145	340.46	343.51	3.05	3.15	103	3.15	103	15	3	5	2	1	1	1 slick fracture, 10 to c.a.
145	343.51	346.56	3.05	3.10	102	3.10	102	15	3	5	4	1	1	
145	346.56	349.61	3.05	3.10	102	3.10	102	15	3	5	3	1	1	
145	349.61	352.65	3.04	2.93	96	2.93	96	15	3	5	3	1	1	1 weak slicks, minor gouge
145	352.65	355.70	3.05	3.05	100	2.97	97	15	3	5	3	1	2	
145	355.70	358.75	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
145	358.75	361.80	3.05	3.00	98	3.00	98	15	4	6	1	1	2	
145	361.80	364.85	3.05	3.05	100	2.85	93	14	2	5	6	3	1	1 slick at approx. 15 to c.a.
145	364.85	367.89	3.04	3.05	100	2.81	92	14	2	5	6	3	1	1 major gouge on slicks
145	367.89	370.94	3.05	3.05	100	2.92	96	14	2	5	6	1	1	1 polished joint, very slick
145	370.94	373.99	3.05	2.85	93	2.68	88	14	2	5	6	3	2	
145	373.99	377.04	3.05	3.08	101	2.82	92	15	2	5	5	3	2	2 gouge on some fractures
145	377.04	380.09	3.05	2.95	97	2.08	68	10	2	4	22	3	1	1 slick contact, gouge
145	380.09	383.13	3.04	3.05	100	2.72	89	12	4	4	17	2	1	1 20% broken core w/ gouge

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
145	383.13	384.35	1.22	1.04	85	0.61	50	10	4	4	8	1	1 mod. gouge on broken core	
145	384.35	386.18	1.83	1.83	100	1.36	74	12	5	4	12	2	2	
145	386.18	389.23	3.05	2.80	92	1.06	35	9	4	4	30	2	2 100% is broken core	
145	389.23	392.28	3.05	2.90	95	1.44	47	10	4	4	20	2	1 30 cm. of <2 cm. broken core w/ gouge	
145	392.28	395.33	3.05	2.89	95	2.65	87	13	5	5	11	1	1 1 cm. Cb shear at 25 to c.a.	
145	395.33	398.37	3.04	3.04	100	2.41	79	13	5	4	13	3	2	
145	398.37	399.57	1.20	0.87	73	0.18	15	9	4	3	11	2	2 30 cm. of broken 1-3 cm. core w/ gouge	
145	399.57	400.20	0.63	0.58	92	0.16	25	5	4	3	20	2	2 100% broken core , 2 cm. w/ gouge	
145	400.20	403.25	3.05	2.88	94	2.20	72	13	4	3	14	3	2	
145	403.25	404.47	1.22	1.25	102	0.88	72	13	3	3	6	2	2 40 cm. cemented gouge- reduced to NQ	
145	404.47	407.52	3.05	2.03	67	1.13	37	10	3	3	14	2	1 NQ core; two 2 cm. cemented gouge	
145	407.52	409.35	1.83	1.36	74	0.39	21	9	4	3	16	2	1 gouge on fractures	
145	409.35	411.78	2.43	2.41	99	1.35	56	10	4	4	18	2	2 gouge w/ broken core	
145	411.78	414.83	3.05	3.28	108	2.19	72	13	5	4	12	2	1	
145	414.83	417.88	3.05	2.84	93	2.13	70	13	5	4	14	1	1 1 cm. gougy fault zone at 60 to c.a.	
145	417.88	419.10	1.22	1.22	100	0.15	12	10	5	4	10	1	1 slip plane at 50 to c.a.	
145	419.10	420.32	1.22	1.16	95	0.28	23	9	5	4	13	2	2 3 cm. broken core 1-2 cm. w/ gouge	
145	420.32	423.37	3.05	3.05	100	2.60	85	13	5	4	12	2	2 3 cm. broken core 1-2 cm. w/ gouge	
145	423.37	425.81	2.44	2.44	100	2.32	95	14	5	4	8	2	2	
145	425.81	428.85	3.04	3.05	100	2.87	94	14	5	4	9	2	2	
145	428.85	431.90	3.05	3.05	100	2.17	71	13	5	4	14	2	2 weakly broken 2-3 cm. subang core	
145	431.90	434.95	3.05	3.08	101	2.84	93	14	5	4	9	2	2	
145	434.95	438.00	3.05	3.05	100	2.95	97	14	5	4	9	2	2 breaks in brecciated rx	
145	438.00	441.05	3.05	3.00	98	2.89	95	14	4	4	10	2	2	
145	441.05	444.09	3.04	3.04	100	2.67	88	13	4	4	12	2	2 3 cm. cemented gouge at 35 to c.a.	
145	444.09	447.14	3.05	2.75	90	2.07	68	12	4	4	18	2	2 trace gouge on fractures	
145	447.14	450.19	3.05	3.11	102	2.89	95	14	4	4	8	2	1 joints at 40 to c.a.	
145	450.19	453.24	3.05	3.05	100	3.05	100	14	4	4	8	2	2	
145	453.24	456.29	3.05	3.05	100	2.69	88	13	4	4	14	1	1 1-2 mm. gouge	
145	456.29	459.33	3.04	3.04	100	2.32	76	13	4	4	11	2	2 2-3 cm. of mod. broken core w/ gouge	
145	459.33	462.38	3.05	3.05	100	2.15	70	14	4	4	10	2	2 all fractures have trace gouge	
145	462.38	465.43	3.05	3.05	100	2.86	94	14	4	4	8	2	2	
145	465.43	468.17	2.74	2.66	97	2.35	86	14	4	4	8	2	2	
145	468.17	471.22	3.05	3.22	106	2.92	96	14	4	4	10	2	1 two 1 cm. gouge zones at 80 & 60 to ca	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
145	471.22	474.27	3.05	2.95	97	2.31	76	13	4	4	13	1	1	1 trace gouge at 10-15 to c.a. (no slicks)
145	474.27	477.32	3.05	3.00	98	2.89	95	14	4	4	10	3	2	2 fractures at low angles to c.a.
145	477.32	480.36	3.04	3.04	100	2.58	85	13	4	4	12	2	1	1 203 cm. broken core w/ gouge
145	480.36	483.41	3.05	3.05	100	2.01	66	13	4	4	13	2	1	1 15 cm. strongly broken ang core w/ gouge
145	483.41	486.46	3.05	3.05	100	2.48	81	14	5	4	9	2	2	2 start of mod-strong qz stockwork
145	486.46	489.51	3.05	3.05	100	2.73	90	14	5	4	8	2	2	2
145	489.51	492.56	3.05	3.04	100	2.89	95	14	5	4	9	2	2	2
145	492.56	495.60	3.04	3.05	100	2.49	82	14	5	4	7	2	2	2
145	495.60	498.96	3.36	3.22	96	3.05	91	13	5	4	12	2	2	2
145	498.96	501.70	2.74	2.56	93	2.38	87	14	5	4	7	2	2	2 3 cm. broken core w/ trace gouge
145	501.70	504.75	3.05	3.00	98	2.85	93	14	5	4	8	2	2	2
145	504.75	507.80	3.05	2.95	97	2.65	87	13	5	4	10	2	2	2 >50 % of joints on qz veins
145	507.80	510.85	3.05	3.15	103	2.68	88	13	5	4	11	1	2	2
145	510.85	513.89	3.04	3.00	99	2.76	91	14	5	4	8	1	2	2
145	513.89	516.94	3.05	3.10	102	3.05	100	14	5	4	7	2	2	2
145	516.94	519.99	3.05	3.05	100	2.75	90	14	5	4	8	2	2	2 trace gouge at end of breccia zone
145	519.99	523.04	3.05	2.90	95	2.75	90	13	5	4	10	2	2	2 three 2 cm. mod. broken subang core
145	523.04	523.34	0.30	0.42	140	0.42	140	14	5	4	1	2	2	2
145	523.34	526.39	3.05	3.15	103	2.95	97	13	5	4	11	2	2	2 trace gouge at 20 to 30 to c.a.
145	526.39	529.44	3.05	3.05	100	2.71	89	13	5	4	11	2	2	2 trace gouge at 40 to c.a.
145	529.44	532.49	3.05	3.05	100	2.86	94	15	5	4	5	2	1	1 no slicks on slip
145	532.49	535.53	3.04	3.00	99	3.00	99	14	5	4	9	1	2	2 gouge on slip at 30 to c.a.
145	535.53	538.58	3.05	3.05	100	2.71	89	13	5	4	12	2	2	2 gouge on slip at 30 to c.a.
145	538.58	541.63	3.05	3.09	101	2.85	93	14	5	4	9	1	2	2 gouge on slip at 40 to c.a.
145	541.63	544.68	3.05	3.00	98	2.58	85	14	5	4	10	2	2	2 trace gouge in broken core
145	544.68	547.73	3.05	3.10	102	2.60	85	13	4	4	13	1	3	3 gouge on fractures
145	547.73	550.77	3.04	3.01	99	2.48	82	10	4	4	22	1	2	2 5 cm. gouge at 15 to c.a. 549.95-550.0
145	550.77	553.82	3.05	3.05	100	2.92	96	14	4	4	9	1	3	3
145	553.82	556.87	3.05	3.05	100	2.95	97	14	4	4	10	1	3	3 Cb-qz breccia (55 to ca) 554.35-554.67
145	556.87	559.92	3.05	3.05	100	3.00	98	14	4	4	10	1	2	2
145	559.92	562.97	3.05	3.07	101	2.73	90	12	4	4	20	1	3	3
145	562.97	566.01	3.04	3.04	100	2.53	83	10	4	4	23	1	2	2 brecciated-healed w/ qz-Cb
145	566.01	568.45	2.44	2.39	98	1.96	80	7	2	3	40	1	1	1 slicks on fract 70 rake; gouge 567.65
145	568.45	570.28	1.83	1.90	104	0.20	11	6	2	3	50	1	2	2 gouge and broken rx

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
145	570.28	572.41	2.13	2.13	100	1.45	68	7	4	4	33	1	3	broken rock
145	572.41	575.16	2.75	2.80	102	1.58	57	7	4	4	50	1	3	broken rock
145	575.16	577.29	2.13	2.05	96	1.45	68	7	4	3	35	1	3	gouge 0-30 to c.a. 575.55-576.7 m.
145	577.29	580.34	3.05	3.02	99	2.32	76	10	5	4	25	1	3	
145	580.34	582.47	2.13	2.27	107	1.74	82	10	5	4	18	1	2	
145	582.47	584.30	1.83	1.60	87	1.09	60	7	5	4	25	1	3	
145	584.30	587.35	3.05	3.01	99	2.23	73	9	4	4	35	1	2	veined and brecciated w/ qz-Cb
145	587.35	589.79	2.44	2.35	96	1.43	59	6	4	4	45	1	3	veined and brecciated w/ qz-Cb
145	589.79	592.84	3.05	2.97	97	1.75	57	6	2	3	60	1	2	591.65-592.84 healed gouge 25 to c.a.
145	592.84	594.30	1.46	1.13	77	0.56	38	4	3	4	30	1	3	
145	594.30	595.88	1.58	1.45	92	0.70	44	4	2	3	50	1	3	594.5-594.7 gouge; broken rx
145	595.88	597.71	1.83	0.80	44	0.24	13	4	2	3	30	1	3	gouge-healed gouge, 35 to c.a.
145	597.71	599.50	1.79	1.05	59	0.23	13	6	2	3	35	1	3	gouge-healed gouge, 40 to c.a.
146	6.10	8.23	2.13	0.74	35	0.00	0	9	1	3	23	1	1	> 50% friable material
146	8.23	11.28	3.05	2.97	97	0.00	0	4	1	3	100	1	1	> 50% friable material
146	11.28	14.33	3.05	1.55	51	0.00	0	3	0	2	80	5	4	> 50% friable material
146	14.33	16.15	1.82	1.08	59	0.00	0	3	1	2	30	1	2	
146	16.15	17.98	1.83	1.02	56	0.00	0	3	1	3	30	1	1	
146	17.98	20.42	2.44	2.55	105	0.58	24	6	1	3	40	3	2	
146	20.42	23.47	3.05	3.04	100	0.50	16	4	0	2	100	3	1	
146	23.47	26.52	3.05	3.04	100	0.64	21	4	0	2	80	5	4	
146	26.52	28.35	1.83	1.64	90	1.15	63	12	2	4	9	1	2	
146	28.35	30.48	2.13	1.94	91	0.80	38	9	1	3	23	1	1	slicks on fractures
146	30.48	33.53	3.05	3.05	100	2.67	88	7	0	2	50	1	1	> 50% of interval H=1
146	33.53	35.66	2.13	1.98	93	0.50	23	4	0	2	70	1	2	> 50% of interval H=1
146	35.66	38.71	3.05	3.10	102	2.45	80	4	0	2	50	1	1	> 50% of interval H=1
146	38.71	41.15	2.44	2.17	89	0.94	39	4	0	2	40	1	1	> 50% of interval H=1
146	41.15	44.20	3.05	2.93	96	0.33	11	4	0	2	80	3	1	polished joints
146	44.20	47.24	3.04	3.05	100	0.37	12	4	0	3	40	2	1	
146	47.24	50.29	3.05	2.82	92	0.31	10	5	2	3	40	1	2	gouge on fractures
146	50.29	53.34	3.05	1.48	49	0.83	27	7	2	3	25	1	2	gouge on fractures
146	53.34	53.95	0.61	0.46	75	0.32	52	9	2	3	5	3	3	
146	53.95	57.00	3.05	3.05	100	1.94	64	11	2	3	19	3	3	
146	57.00	60.05	3.05	3.05	100	2.15	70	13	2	4	14	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
146	60.05	63.09	3.04	3.05	100	2.37	78	14	2	4	10	3	2	
146	63.09	66.14	3.05	3.00	98	1.44	47	10	2	4	26	3	1	chalky slicks
146	66.14	69.19	3.05	2.92	96	1.43	47	11	2	4	18	1	1	
146	69.19	72.24	3.05	3.06	100	1.67	55	13	2	4	14	1	1	
146	72.24	75.29	3.05	3.00	98	2.02	66	13	2	4	12	1	1	
146	75.29	78.33	3.04	3.02	99	1.98	65	13	2	4	10	1	1	
146	78.33	81.38	3.05	3.08	101	1.50	49	12	2	4	17	1	1	very slick, rake -10
146	81.38	84.43	3.05	3.05	100	2.11	69	13	2	4	12	1	2	
146	84.43	87.48	3.05	2.96	97	2.07	68	12	2	4	16	1	1	
146	87.48	90.53	3.05	3.05	100	2.34	77	13	2	5	11	1	2	
146	90.53	93.57	3.04	2.62	86	1.85	61	13	2	4	13	3	1	
146	93.57	96.32	2.75	2.60	95	1.39	51	10	2	4	25	1	1	
146	96.32	99.36	3.04	3.06	101	1.35	44	10	2	4	27	1	1	
146	99.36	102.41	3.05	2.87	94	2.10	69	13	3	5	10	1	1	gouge on fractures, slicks at 55 to c.a.
146	102.41	105.46	3.05	2.97	97	1.99	65	12	2	4	15	1	1	gouge on fractures, slicks at 55 to c.a.
146	105.46	108.51	3.05	2.92	96	2.50	82	13	2	4	10	3	1	gouge on fractures, slicks at 55 to c.a.
146	108.51	111.56	3.05	2.94	96	1.57	51	12	2	4	11	1	1	
146	111.56	114.60	3.04	3.10	102	2.02	66	13	2	4	15	1	1	
146	114.60	114.91	0.31	0.21	68	0.00	0	7	2	4	4	1	1	
146	114.91	117.96	3.05	2.92	96	2.28	75	13	2	4	12	3	1	
146	117.96	121.01	3.05	3.02	99	2.07	68	12	2	4	17	3	1	
146	121.01	124.05	3.04	3.05	100	2.33	77	14	2	4	7	3	1	
146	124.05	127.10	3.05	3.05	100	3.05	100	14	3	5	6	1	2	
146	127.10	130.15	3.05	3.05	100	2.71	89	14	3	5	9	1	2	
146	130.15	133.20	3.05	3.05	100	2.38	78	12	3	5	17	1	2	
146	133.20	136.25	3.05	3.03	99	1.70	56	12	3	5	19	1	2	
146	136.25	139.29	3.04	3.04	100	2.37	78	13	3	5	13	5	2	
146	139.29	142.34	3.05	3.05	100	2.41	79	14	3	5	10	1	2	
146	142.34	145.39	3.05	3.05	100	1.29	42	12	2	5	17	5	3	142.65 m.-3-5 cm. fault gouge 60 to c.a.
146	145.39	148.44	3.05	2.95	97	1.78	58	13	3	5	12	1	3	
146	148.44	151.49	3.05	3.05	100	2.99	98	13	3	5	14	1	3	
146	151.49	154.53	3.04	3.04	100	1.52	50	10	3	5	21	1	3	some gouge on fractures
146	154.53	157.58	3.05	2.79	91	0.67	22	13	3	5	12	1	3	30% broken core
146	157.58	160.63	3.05	2.86	94	1.91	63	9	2	4	30	5	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
146	160.63	163.68	3.05	3.05	100	2.48	81	13	3	5	11	1	3	gouge on fracture at 163.19 m.
146	163.68	166.73	3.05	3.05	100	2.29	75	12	3	5	19	5	3	
146	166.73	169.77	3.04	3.05	100	1.72	57	10	3	5	22	1	2	
146	169.77	172.82	3.05	3.05	100	2.82	92	13	3	5	11	1	13	
146	172.82	175.87	3.05	3.05	100	3.05	100	14	2	5	8	1	3	
146	175.87	178.92	3.05	3.05	100	3.05	100	14	2	5	9	5	3	
146	178.92	181.97	3.05	3.05	100	2.95	97	14	3	5	8	1	3	
146	181.97	185.01	3.04	3.04	100	3.04	100	14	3	5	7	1	3	
146	185.01	188.06	3.05	3.02	99	3.02	99	14	3	5	10	5	3	
146	188.06	191.11	3.05	3.05	100	3.00	98	14	3	5	7	5	3	188.35 m. - 3-5 cm. gouge zone
146	191.11	194.16	3.05	3.05	100	2.01	66	13	2	4	12	1	3	
146	194.16	197.21	3.05	3.05	100	2.44	80	13	2	4	14	5	3	gouge on fractures
146	197.21	200.25	3.04	3.04	100	1.85	61	10	2	4	25	5	3	10% broken core
146	200.25	203.30	3.05	3.05	100	2.00	66	12	3	5	18	1	2	
146	203.30	206.35	3.05	3.05	100	3.01	99	13	2	5	13	1	3	dyke
146	206.35	209.40	3.05	3.05	100	3.05	100	15	2	4	3	1	3	fault - mixed dykes/fault at 30 to c.a.
146	209.40	212.45	3.05	3.05	100	3.05	100	15	2	4	5	1	3	fault - mixed dykes/fault at 30 to c.a.
146	212.45	215.49	3.04	3.04	100	3.05	100	15	2	4	4	5	3	fault - mixed dykes/fault at 30 to c.a.
146	215.49	218.54	3.05	3.05	100	2.95	97	14	2	4	7	5	3	fault - mixed dykes/fault at 30 to c.a.
146	218.54	221.59	3.05	3.05	100	2.97	97	14	2	4	10	5	3	fault - mixed dykes/fault at 30 to c.a.
146	221.59	224.64	3.05	3.02	99	2.95	97	13	2	4	11	5	3	fault - mixed dykes/fault at 30 to c.a.
146	224.64	227.69	3.05	3.05	100	2.52	83	13	2	4	14	5	3	fault - mixed dykes/fault at 30 to c.a.
146	227.69	230.73	3.04	3.04	100	2.40	79	13	2	4	13	5	3	fault - mixed dykes/fault at 30 to c.a.
146	230.73	233.78	3.05	3.05	100	2.00	66	13	2	4	13	5	3	fault - mixed dykes/fault at 30 to c.a.
146	233.78	236.83	3.05	3.05	100	2.96	97	14	2	4	7	5	3	fault - mixed dykes/fault at 30 to c.a.
146	236.83	239.88	3.05	3.05	100	2.32	76	13	3	5	15	1	3	
146	239.88	242.93	3.05	3.05	100	1.92	63	12	3	5	18	1	2	
146	242.93	245.97	3.04	3.04	100	2.87	94	13	3	5	11	5	3	
146	245.97	249.02	3.05	3.04	100	2.72	89	13	3	5	15	5	3	5 cm. gouge at 246.2 m. at 40 to c.a.
146	249.02	252.07	3.05	3.05	100	2.17	71	12	2	4	17	5	3	fault gouge at 250.45 to 260.25 m.
146	252.07	255.12	3.05	3.05	100	1.39	46	12	3	5	19	1	2	
146	255.12	258.17	3.05	3.05	100	1.43	47	10	3	5	30	1	2	
146	258.17	261.21	3.04	3.00	99	2.21	73	10	3	5	22	1	2	
146	261.21	264.26	3.05	3.05	100	1.13	37	10	2	5	25	2	3	15% broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
146	264.26	267.31	3.05	3.05	100	1.24	41	10	3	5	28	1	3	
146	267.31	270.36	3.05	3.05	100	1.31	43	10	2	4	25	1	2	
146	270.36	273.41	3.05	3.05	100	2.28	75	13	3	5	15	5	3	
146	273.41	276.45	3.04	3.04	100	2.52	83	14	2	4	10	1	2	2 shear at 274.0 to 274.65 m.
146	276.45	279.50	3.05	3.05	100	2.14	70	13	3	5	12	5	5	2 first 0.5 m. is faulted, brecciated
146	279.50	282.55	3.05	3.05	100	2.18	71	13	3	5	14	1	2	
146	282.55	285.60	3.05	3.05	100	3.05	100	13	3	5	11	1	2	
146	285.60	288.65	3.05	3.05	100	1.56	51	13	3	5	12	5	2	
146	288.65	291.69	3.04	3.04	100	2.18	72	10	2	5	25	5	3	
146	291.69	294.74	3.05	3.05	100	2.56	84	14	3	5	7	5	2	2 10 cm. black fault gouge at 292.0 m.
146	294.74	297.79	3.05	3.05	100	3.05	100	14	3	5	6	5	3	
146	297.79	300.84	3.05	3.05	100	2.13	70	13	2	4	12	5	2	
146	300.84	303.89	3.05	3.05	100	2.00	66	13	2	4	15	5	3	3 15% fault and brecciated in interval
146	303.89	306.93	3.04	3.04	100	1.88	62	14	3	5	10	1	2	
146	306.93	309.98	3.05	3.05	100	2.61	86	14	3	5	9	1	2	
147	9.14	11.28	2.14	1.60	75	0.94	44	9	3	4	18	1	2	
147	11.28	14.33	3.05	2.69	88	1.53	50	10	3	4	22	1	2	
147	14.33	17.07	2.74	2.74	100	0.94	34	7	3	5	50	1	2	2 30% broken core w/ minor gouge
147	17.07	20.12	3.05	2.61	86	0.00	0	6	2	3	100	5	3	3 85% broken core w/ minor gouge
147	20.12	22.25	2.13	1.52	71	0.00	0	4	2	3	100	5	3	3 100% broken core w/ minor gouge
147	22.25	24.99	2.74	1.60	58	0.00	0	6	2	2	100	5	3	3 100% broken core
147	24.99	25.91	0.92	0.70	76	0.00	0	1	2	2	100	5	3	3 100% broken core
147	25.91	26.52	0.61	0.45	74	0.00	0	1	2	2	100	5	3	3 100% broken core
147	26.52	29.57	3.05	2.81	92	0.52	17	7	2	2	50	2	3	3 65% broken core w/ minor gouge
147	29.57	31.39	1.82	1.75	96	0.20	11	5	2	2	65	5	3	3 80% broken core
147	31.39	32.61	1.22	1.22	100	0.24	20	7	3	3	22	1	3	3 10% broken core w/ minor gouge
147	32.61	34.14	1.53	1.47	96	0.43	28	5	3	3	40	5	2	2 20% broken core w/ minor gouge
147	34.14	35.05	0.91	0.91	100	0.00	0	1	2	2	100	5	3	3 90% broken core w/ minor gouge
147	35.05	35.47	0.42	0.42	100	0.10	24	1	2	2	100	2	3	3 90% broken core w/ minor gouge
147	35.47	37.49	2.02	1.25	62	0.00	0	5	3	2	50	2	2	2 100% broken angular core w/ gouge
147	37.49	40.84	3.35	2.25	67	0.00	0	5	3	2	75	2	2	2 100% broken angular core w/ gouge
147	40.84	42.98	2.14	1.80	84	0.00	0	4	3	2	75	2	2	2 100% broken angular core w/ gouge
147	42.98	44.81	1.83	1.35	74	0.11	6	4	3	2	75	2	2	2 100% broken angular core w/ gouge
147	44.81	47.85	3.04	2.25	74	0.00	0	5	3	2	75	2	2	2 100% broken angular core w/ gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
147	47.85	50.90	3.05	1.90	62	0.00	0	5	3	2	75	2	2	2 100% broken angular core w/ gouge
147	50.90	53.95	3.05	2.55	84	0.00	0	6	3	2	75	2	2	2 100% broken angular core w/ gouge
147	53.95	57.00	3.05	1.95	64	0.00	0	5	3	2	75	2	2	2 100% broken angular core w/ gouge
147	57.00	60.05	3.05	2.45	80	2.40	79	14	4	3	8	2	2	2 out of fault (no angle)
147	60.05	63.09	3.04	3.04	100	2.88	95	13	4	3	11	2	2	1 slip w/ gouge at 50 to c.a.
147	63.09	66.14	3.05	3.00	98	3.00	98	15	4	3	8	2	2	1 slip plane at 60 to c.a.
147	66.14	69.19	3.05	2.93	96	2.93	96	14	4	3	8	2	2	2
147	69.19	72.24	3.05	3.05	100	2.83	93	14	4	3	10	2	2	2 fracturing on Cb and Gy veins
147	72.24	75.29	3.05	3.05	100	2.95	97	14	4	3	9	2	2	2
147	75.29	78.33	3.04	3.04	100	2.95	97	14	4	3	8	2	2	1 slip on Cb veins at 60 to c.a.
147	78.33	81.38	3.05	3.05	100	3.05	100	15	4	3	4	2	2	2 fracturing on Cb and Gy veins
147	81.38	84.43	3.05	3.05	100	3.00	98	15	4	3	6	2	2	2 fracturing on Cb and Gy veins
147	84.43	87.48	3.05	3.05	100	3.01	99	15	4	3	6	3	2	2
147	87.48	90.53	3.05	3.05	100	3.00	98	14	4	3	9	2	2	2
147	90.53	93.57	3.04	3.04	100	2.98	98	15	4	4	4	1	3	3
147	93.57	96.62	3.05	3.05	100	2.95	97	14	4	3	10	3	2	2
147	96.62	99.67	3.05	3.05	100	2.76	90	14	4	3	10	2	2	1 50% fracturing on Cb veins
147	99.67	102.72	3.05	3.05	100	3.05	100	15	4	3	4	2	2	2 strong Cb stockwork
147	102.72	105.77	3.05	3.05	100	3.00	98	14	4	3	6	1	2	2 sharp fracture on Cb vein at 70 to c.a.
147	105.77	108.81	3.04	3.04	100	2.99	98	14	4	3	8	1	2	2
147	108.81	111.86	3.05	3.05	100	2.84	93	15	4	3	5	3	2	2 undulating Cb-Gy veins at 35 to c.a.
147	111.86	114.91	3.05	3.05	100	3.05	100	14	4	3	8	2	2	2
147	114.91	117.96	3.05	3.05	100	2.98	98	14	4	3	9	2	2	2
147	117.96	121.01	3.05	3.05	100	3.05	100	14	4	3	6	2	2	2
147	121.01	124.05	3.04	3.04	100	3.01	99	14	4	3	6	2	2	2 Cb/Gy vein w/ trace gouge at 55 to c.a.
147	124.05	127.10	3.05	3.05	100	2.98	98	15	4	3	5	2	2	2
147	127.10	130.15	3.05	3.05	100	2.96	97	14	4	3	7	2	2	2
147	130.15	133.20	3.05	3.05	100	2.87	94	15	4	3	5	2	2	2 5 cm. broken 1-2 cm. subangular core
147	133.20	136.25	3.05	3.05	100	2.66	87	14	4	3	8	2	2	2
147	136.25	139.29	3.04	3.04	100	2.88	95	14	4	3	7	2	2	2
147	139.29	142.34	3.05	3.05	100	2.10	69	14	4	3	6	2	2	2
147	142.34	145.39	3.05	3.05	100	2.96	97	13	3	5	13	1	3	3
147	145.39	148.44	3.05	3.05	100	3.05	100	14	3	5	9	1	2	2
147	148.44	151.49	3.05	3.05	100	2.94	96	14	3	5	10	1	3	3

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
147	151.49	154.53	3.04	3.04	100	3.00	99	14	3	5	8	4	3	
147	154.53	157.58	3.05	3.00	98	3.00	98	15	3	5	4	4	3	
147	157.58	160.63	3.05	3.05	100	3.05	100	14	3	5	10	1	3	
147	160.63	163.68	3.05	3.05	100	3.05	100	14	3	5	8	1	3	
147	163.68	166.72	3.04	3.04	100	3.01	99	13	3	5	11	1	3	
147	166.72	169.77	3.05	3.05	100	3.01	99	13	3	5	12	1	3	
147	169.77	172.82	3.05	3.05	100	2.98	98	13	3	5	11	1	3	
147	172.82	175.87	3.05	3.05	100	2.98	98	14	3	5	6	1	3	
147	175.87	178.92	3.05	3.08	101	3.08	101	13	3	5	12	1	3	
147	178.92	181.97	3.05	3.05	100	3.05	100	13	3	5	14	1	2	2 dyke for first 0.5 m.
147	181.97	185.01	3.04	3.04	100	3.04	100	14	3	5	10	1	2	
147	185.01	188.06	3.05	3.05	100	3.05	100	13	3	5	12	1	3	
147	188.06	191.11	3.05	3.05	100	3.05	100	14	3	5	9	1	3	
147	191.11	194.16	3.05	3.05	100	2.97	97	12	3	5	18	1	2	
147	194.16	196.60	2.44	2.44	100	2.44	100	14	3	5	6	1	2	
147	196.60	199.64	3.04	3.04	100	2.98	98	13	3	5	14	1	2	
147	199.64	202.67	3.03	3.03	100	3.03	100	14	3	5	8	1	3	
147	202.67	204.52	1.85	1.77	96	1.77	96	12	3	5	9	1	2	
147	204.52	206.35	1.83	1.78	97	1.78	97	14	3	5	5	1	2	
147	206.35	209.40	3.05	3.05	100	3.05	100	13	3	5	14	1	2	
147	209.40	212.45	3.05	3.05	100	2.98	98	13	3	5	13	1	3	
147	212.45	215.49	3.04	3.04	100	3.04	100	14	3	5	9	1	2	
147	215.49	218.54	3.05	3.05	100	3.05	100	14	3	5	7	1	2	
147	218.54	221.59	3.05	3.05	100	2.30	75	9	4	5	40	1	2	2 mostly dyke material, 20% broken core
147	221.59	224.64	3.05	3.05	100	1.73	57	10	4	5	22	1	2	
147	224.64	227.69	3.05	3.03	99	2.01	66	10	4	5	30	1	2	2 10% broken core; 50% dyke
147	227.69	230.73	3.04	3.04	100	2.47	81	13	3	5	14	4	2	
147	230.73	233.78	3.05	3.05	100	2.20	72	10	2	4	25	5	3	3 some gouge on fractures
147	233.78	236.83	3.05	3.00	98	2.95	97	13	2	4	15	1	3	3 first 0.5 m. is soft gouge rx to 234.67 m.
147	236.83	239.88	3.05	3.05	100	2.98	98	13	3	5	14	1	2	2 gouge at 237.5 m. (15 to 20 cm. wide)
147	239.88	242.93	3.05	3.05	100	2.30	75	10	3	5	25	1	2	
147	242.93	245.97	3.04	3.04	100	3.04	100	13	4	5	11	1	2	2 1 m. dyke
147	245.97	249.02	3.05	3.05	100	2.55	84	12	3	5	20	1	3	
147	249.02	252.07	3.05	3.05	100	2.87	94	12	3	5	16	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
147	252.07	255.12	3.05	3.05	100	3.05	100	13	3	5	11	1	2	
147	255.12	258.17	3.05	3.05	100	3.05	100	13	3	5	12	1	2	
147	258.17	261.21	3.04	3.04	100	2.93	96	14	3	5	10	1	2	
147	261.21	264.26	3.05	3.05	100	3.05	100	14	3	5	6	1	2	
147	264.26	267.31	3.05	3.05	100	2.92	96	13	2	4	13	5	3	3 gouge on some fractures
147	267.31	270.36	3.05	3.05	100	2.44	80	13	2	4	11	5	3	
147	270.36	273.41	3.05	3.05	100	3.05	100	14	3	5	8	1	2	
147	273.41	276.45	3.04	3.04	100	2.89	95	14	3	5	6	1	2	
147	276.45	279.50	3.05	3.05	100	3.05	100	13	3	5	11	1	2	
147	279.50	282.55	3.05	2.93	96	2.93	96	14	3	5	7	1	2	
147	282.55	285.60	3.05	3.05	100	3.05	100	14	3	5	9	1	2	
147	285.60	288.65	3.05	3.05	100	2.57	84	13	4	5	12	1	2	
147	288.65	291.69	3.04	3.04	100	2.51	83	13	4	5	15	5	3	
147	291.69	294.74	3.05	3.05	100	2.41	79	12	4	5	16	5	3	3 15% broken core
147	294.74	297.79	3.05	2.79	91	1.51	50	9	3	5	30	5	2	
147	297.79	300.84	3.05	3.05	100	2.55	84	13	4	5	14	1	3	
147	300.84	303.89	3.05	3.00	98	2.57	84	9	4	5	25	1	3	3 some gouge on fractures
147	303.89	306.93	3.04	3.04	100	3.04	100	13	4	5	11	1	2	
147	306.93	309.98	3.05	3.05	100	3.05	100	14	4	5	6	1	2	
147	309.98	313.03	3.05	3.05	100	3.05	100	14	4	5	8	1	2	
147	313.03	316.08	3.05	3.05	100	3.05	100	14	4	5	7	1	2	
147	316.08	319.13	3.05	3.05	100	3.05	100	14	4	5	6	1	2	
147	319.13	322.17	3.04	3.04	100	3.04	100	14	4	5	7	1	2	
147	322.17	325.22	3.05	3.05	100	3.05	100	14	4	5	9	1	2	
147	325.22	328.27	3.05	3.05	100	3.05	100	13	4	5	11	1	2	
147	328.27	331.32	3.05	3.05	100	2.36	77	14	4	5	40	1	2	2 15% broken core, 80% dyke
147	331.32	334.37	3.05	3.05	100	2.11	69	9	4	5	32	5	3	3 10% broken core
147	334.37	337.41	3.04	3.04	100	2.83	93	13	4	5	12	5	3	
147	337.41	340.46	3.05	3.05	100	2.95	97	14	4	5	7	1	2	
147	340.46	343.51	3.05	3.05	100	3.05	100	14	4	5	6	1	3	
147	343.51	346.56	3.05	3.05	100	3.05	100	14	4	5	10	5	2	
147	346.56	349.61	3.05	3.05	100	1.92	63	7	3	5	45	5	3	3 20% broken core w/ some gouge
147	349.61	352.65	3.04	3.04	100	3.04	100	13	3	5	11	1	2	
147	352.65	355.70	3.05	3.05	100	3.05	100	13	3	5	15	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
147	355.70	358.75	3.05	3.05	100	3.05	100	14	3	5	10	1	2	
147	358.75	361.80	3.05	3.05	100	3.00	98	14	3	5	9	1	2	
147	361.80	364.85	3.05	3.05	100	2.98	98	13	3	5	12	1	2	
147	364.85	367.89	3.04	3.04	100	2.59	85	13	4	5	15	1	2	
147	367.89	370.94	3.05	3.05	100	2.42	79	12	4	5	20	1	2	
147	370.94	373.99	3.05	3.05	100	2.57	84	10	4	5	28	1	2	
147	373.99	377.04	3.05	3.05	100	2.49	82	13	4	5	14	1	2	
148	9.14	11.28	2.14	0.25	12	0.00	0	1	2	3	100	5	3	100% broken core
148	11.28	14.33	3.05	0.79	26	0.00	0	1	2	3	100	5	3	100% broken core
148	14.33	17.37	3.04	1.61	53	0.00	0	2	2	3	100	5	3	100% broken core
148	17.37	20.42	3.05	1.56	51	0.00	0	2	2	3	100	5	3	100% broken core
148	20.42	23.47	3.05	1.67	55	0.00	0	4	2	3	100	5	3	100% broken core
148	23.47	26.52	3.05	0.67	22	0.00	0	1	2	3	100	5	3	100% broken core
148	26.52	29.57	3.05	1.49	49	0.00	0	1	2	3	100	5	3	100% broken core
148	29.57	32.61	3.04	1.78	59	0.56	18	4	2	3	75	5	3	100% broken core
148	32.61	35.66	3.05	1.44	47	0.35	11	1	2	3	100	5	3	100% broken core
148	35.66	38.71	3.05	0.25	8	0.00	0	1	2	3	100	5	3	100% broken core
148	38.71	41.76	3.05	0.05	2	0.00	0	1	2	3	20	5	3	100% broken core
148	41.76	43.28	1.52	0.60	39	0.00	0	1	2	3	75	5	3	100% broken core
148	43.28	44.81	1.53	0.15	10	0.00	0	1	2	3	20	5	3	gouge section; broken core
148	44.81	47.85	3.04	1.74	57	1.10	36	4	3	5	50	5	2	50% broken core
148	47.85	50.90	3.05	3.05	100	2.95	97	13	3	5	11	1	3	10 cm. fault gouge at 48.2 m. at 40 to ca
148	50.90	53.95	3.05	3.05	100	3.05	100	13	3	5	14	1	3	some gouge in fractures
148	53.95	57.00	3.05	3.05	100	2.90	95	14	3	5	9	1	3	
148	57.00	60.05	3.05	3.05	100	3.05	100	13	3	5	12	1	2	
148	60.05	63.09	3.04	2.98	98	2.98	98	13	3	5	11	1	2	
148	63.09	66.14	3.05	3.05	100	3.01	99	14	3	5	10	1	2	
148	66.14	69.19	3.05	3.05	100	1.91	63	12	4	5	18	1	2	
148	69.19	72.24	3.05	3.05	100	2.94	96	12	3	5	19	2	2	fault gouge at 71.65-71.96 m. at 50 to ca
148	72.24	75.29	3.05	3.05	100	2.86	94	13	3	5	12	1	2	
148	75.29	78.33	3.04	3.04	100	2.97	98	12	4	5	20	1	2	
148	78.33	81.38	3.05	3.05	100	3.05	100	13	3	5	12	1	2	
148	81.38	84.43	3.05	3.05	100	3.05	100	14	2	5	10	1	3	50% is cemented fault gouge
148	84.43	87.48	3.05	3.05	100	2.46	81	13	3	5	13	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
156	242.93	245.98	3.05	2.96	97	2.96	97	15	3	5	2	1	3	
156	245.98	249.02	3.04	3.04	100	3.04	100	15	3	5	4	1	3	3 minor gouge on fractures
156	249.02	252.07	3.05	3.05	100	2.85	93	13	3	5	11	5	3	
156	252.07	255.12	3.05	3.11	102	3.00	98	15	3	5	3	1	3	3 gypsum on fractures
156	255.12	258.17	3.05	3.05	100	2.72	89	14	3	5	7	1	3	
156	258.17	261.21	3.04	3.04	100	2.25	74	13	3	5	15	5	3	3 5% broken core
156	261.21	264.26	3.05	3.05	100	2.51	82	14	3	5	9	5	3	
156	264.26	267.31	3.05	3.00	98	3.00	98	15	3	5	1	1	3	
156	267.31	270.36	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
156	270.36	273.41	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
156	273.41	276.45	3.04	2.85	94	2.85	94	15	3	5	2	1	2	
156	276.45	279.50	3.05	3.10	102	2.45	80	12	3	5	20	5	3	3 gouge on fractures; 10% broken core
156	279.50	282.55	3.05	3.12	102	2.96	97	15	3	5	3	1	3	
156	282.55	285.60	3.05	2.92	96	2.67	88	15	3	5	4	1	3	3 gypsum on fractures
156	285.60	288.65	3.05	3.05	100	2.91	95	15	3	5	1	1	3	
156	288.65	291.69	3.04	3.02	99	3.02	99	15	3	5	3	1	3	
156	291.69	294.74	3.05	3.05	100	3.05	100	15	3	5	2	1	3	3 gypsum on fractures
156	294.74	297.79	3.05	3.05	100	3.05	100	15	3	5	3	1	3	3 gypsum on fractures
156	297.79	300.84	3.05	2.96	97	2.96	97	15	3	5	2	1	3	3 gypsum on fractures
156	300.84	303.89	3.05	2.97	97	2.97	97	15	3	5	3	1	3	3 gypsum on fractures
156	303.89	306.93	3.04	3.00	99	3.00	99	15	3	5	4	1	3	3 gypsum on fractures
156	306.93	309.98	3.05	3.02	99	3.02	99	15	3	5	3	1	3	3 gypsum on fractures
156	309.98	313.03	3.05	3.05	100	2.86	94	14	3	5	10	1	3	
156	313.03	316.08	3.05	3.00	98	3.00	98	15	4	5	3	1	3	
156	316.08	319.13	3.05	3.05	100	3.05	100	15	4	5	2	1	3	
156	319.13	322.17	3.04	2.93	96	2.05	67	15	4	5	5	1	3	
156	322.17	325.22	3.05	3.20	105	3.20	105	15	4	5	2	1	3	
156	325.22	328.27	3.05	3.05	100	3.05	100	15	4	5	1	1	3	
156	328.27	331.32	3.05	2.95	97	2.95	97	15	4	5	1	1	3	
156	331.32	334.37	3.05	3.08	101	3.08	101	15	4	5	2	1	3	
156	334.37	337.41	3.04	3.10	102	3.10	102	15	4	5	3	1	3	
156	337.41	340.46	3.05	3.05	100	3.05	100	15	4	5	2	1	3	
156	340.46	343.51	3.05	3.05	100	3.05	100	15	4	5	2	1	3	
156	343.51	346.56	3.05	2.92	96	2.41	79	13	4	5	12	5	3	3 gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
156	346.56	349.61	3.05	3.05	100	2.85	93	14	4	5	9	5	3 gouge on fractures	
156	349.61	352.65	3.04	3.09	102	2.83	93	14	4	5	6	5	3 gouge on fractures	
156	352.65	355.70	3.05	3.05	100	3.05	100	15	4	5	2	1	3	
156	355.70	358.75	3.05	3.00	98	3.00	98	15	4	5	1	1	3 minor gouge on fractures	
156	358.75	361.80	3.05	3.10	102	2.95	97	13	4	5	11	1	3	
156	361.80	364.85	3.05	3.05	100	3.05	100	15	4	5	2	1	3	
156	364.85	367.89	3.04	3.04	100	3.04	100	15	4	5	2	1	3 minor gouge on fractures	
156	367.89	370.94	3.05	2.97	97	2.86	94	15	4	5	3	1	3 minor gouge on fractures	
156	370.94	372.77	1.83	1.83	100	1.83	100	15	4	5	1	1	3	
157	6.10	8.23	2.13	1.28	60	0.00	0	7	1	3	24	1	2 rubble, trace of overburden	
157	8.23	11.28	3.05	2.84	93	1.12	37	11	2	4	17	1	1 minor gouge	
157	11.28	14.33	3.05	3.11	102	2.00	66	14	2	4	8	1	1 very slick	
157	14.33	17.37	3.04	2.87	94	2.42	80	14	2	4	9	1	1 very slick	
157	17.37	20.42	3.05	2.90	95	2.32	76	14	3	5	7	1	2	
157	20.42	23.47	3.05	3.05	100	1.85	61	13	2	5	13	1	2	
157	23.47	26.06	2.59	2.18	84	1.06	41	13	2	4	11	1	2	
157	26.06	28.65	2.59	2.36	91	0.76	29	14	2	4	8	2	1 no rake	
157	28.65	29.57	0.92	1.06	115	1.06	115	15	2	4	3	1	1 minor gouge	
157	29.57	32.61	3.04	2.90	95	1.39	46	13	2	4	14	1	1	
157	32.61	35.66	3.05	2.52	83	1.18	39	10	2	3	23	3	2	
157	35.66	38.71	3.05	2.39	78	1.50	49	9	2	3	25	1	1 fault begins at 37.20 m.	
157	38.71	40.23	1.52	1.16	76	0.00	0	5	1	3	30	1	1 20% of material is H=0	
157	40.23	41.76	1.53	1.59	104	0.35	23	7	1	3	25	1	1 20% of material is H=0	
157	41.76	42.98	1.22	1.21	99	0.20	16	8	1	3	14	1	1 20% of material is H=0	
157	42.98	44.81	1.83	1.20	66	0.33	18	10	1	3	9	1	1 20% of material is H=0	
157	44.81	46.33	1.52	1.80	118	0.56	37	13	1	3	7	1	2 20% of material is H=0	
157	46.33	48.16	1.83	1.08	59	0.37	20	10	1	3	9	1	2 20% of material is H=0	
157	48.16	50.90	2.74	2.10	77	0.00	0	9	1	3	25	1	1 fault ends at 50.90 m.	
157	50.90	53.45	2.55	2.96	116	2.17	85	13	2	4	11	1	2	
157	53.45	57.00	3.55	2.95	83	2.46	69	12	2	4	15	1	2	
157	57.00	58.83	1.83	1.72	94	0.52	28	10	2	4	13	1	2 blocky	
157	58.83	61.87	3.04	2.85	94	2.85	94	15	3	5	2	1	2	
157	61.87	64.62	2.75	2.60	95	2.60	95	15	3	5	2	1	1 gypsum on fractures	
157	64.62	66.14	1.52	2.68	176	2.68	176	15	3	5	2	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
157	66.14	69.19	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
157	69.19	72.24	3.05	3.05	100	2.48	81	14	3	5	10	1	2	mineralized fractures
157	72.24	75.29	3.05	3.12	102	2.84	93	14	2	5	9	1	1	3 cm. of mineralized slick gouge
157	75.29	78.33	3.04	3.05	100	2.72	89	14	3	5	7	1	1	gouged slicks
157	78.33	81.38	3.05	3.05	100	3.05	100	14	3	5	7	1	2	gouge on fractures
157	81.38	84.43	3.05	3.00	98	2.87	94	14	3	5	6	3	2	
157	84.43	87.48	3.05	3.05	100	3.02	99	14	3	5	6	3	2	
157	87.48	90.53	3.05	3.05	100	3.05	100	15	4	5	3	3	2	
157	90.53	93.57	3.04	3.16	104	3.16	104	15	4	6	3	3	1	
157	93.57	94.95	1.38	1.16	84	1.16	84	14	3	5	2	3	1	
157	94.95	96.62	1.67	1.70	102	1.70	102	14	3	5	4	1	2	
157	96.62	99.67	3.05	3.02	99	2.85	93	14	3	5	6	1	1	very slick
157	99.67	102.72	3.05	3.02	99	2.90	95	14	3	5	8	1	1	very slick w/ gouge at 30 to c.a.
157	102.72	105.77	3.05	3.08	101	3.08	101	14	3	5	4	1	1	
157	105.77	108.81	3.04	3.05	100	3.05	100	14	3	5	6	1	1	
157	108.81	111.86	3.05	3.05	100	2.85	93	14	3	5	8	1	1	
157	111.86	114.91	3.05	3.05	100	2.98	98	14	3	5	7	1	1	slicks at 35 to c.a., rake -70
157	114.91	117.96	3.05	3.05	100	2.90	95	14	2	5	8	1	1	
157	117.96	121.01	3.05	3.05	100	2.81	92	13	2	5	11	1	1	slick with gouge
157	121.01	124.05	3.04	3.05	100	2.76	91	14	3	5	7	1	1	slick with gouge
157	124.05	125.88	1.83	1.65	90	0.85	46	11	2	5	12	1	1	slick with gouge
157	125.88	128.47	2.59	2.40	93	1.75	68	13	2	5	11	1	1	slick with gouge
157	128.47	131.67	3.20	3.05	95	2.91	91	14	2	5	7	1	2	
157	131.67	133.20	1.53	1.83	120	1.75	114	15	2	5	4	1	2	
157	133.20	136.25	3.05	3.05	100	3.05	100	14	2	5	6	1	2	
157	136.25	139.29	3.04	3.07	101	3.07	101	15	2	5	4	2	1	minor gouge
157	139.29	142.34	3.05	3.10	102	2.91	95	14	2	5	8	2	1	
157	142.34	145.39	3.05	3.04	100	2.89	95	14	2	5	9	1	1	
157	145.39	146.61	1.22	1.09	89	0.82	67	10	2	4	10	1	1	slick at 15 to c.a.
157	146.61	147.83	1.22	0.92	75	0.62	51	8	2	4	12	1	1	
157	147.83	148.44	0.61	0.84	138	0.69	113	13	2	4	4	1	1	cave; healed gouge
157	148.44	151.49	3.05	3.05	100	2.90	95	14	2	5	7	1	1	
157	151.49	154.53	3.04	3.05	100	3.00	99	14	2	5	6	1	1	
157	154.53	157.58	3.05	3.05	100	2.92	96	14	2	5	8	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
157	157.58	160.63	3.05	3.05	100	2.84	93	14	2	5	8	3	1	possible slick, weak rake
157	160.63	163.68	3.05	3.12	102	3.01	99	14	2	5	7	1	1	
157	163.68	166.73	3.05	3.08	101	3.05	100	14	2	5	6	1	1	clay filled slick fractures
157	166.73	169.77	3.04	3.04	100	2.85	94	14	2	5	8	1	1	slick contact at 20 to c.a., no rake
157	169.77	172.82	3.05	2.99	98	2.68	88	13	2	5	12	1	1	weak slicks
157	172.82	175.87	3.05	3.05	100	3.05	100	14	3	5	6	1	1	weak slicks
157	175.87	178.92	3.05	3.05	100	2.90	95	14	3	5	9	1	1	weak slicks
157	178.92	181.97	3.05	3.10	102	3.10	102	15	3	5	3	1	1	178.80 m. - slick contact
157	181.97	185.01	3.04	2.89	95	2.67	88	14	3	5	7	2	2	
157	185.01	188.06	3.05	3.12	102	3.00	98	14	3	5	10	1	1	healed gouge
157	188.06	191.11	3.05	2.97	97	2.68	88	13	2	4	13	1	2	healed gouge
157	191.11	194.16	3.05	3.09	101	3.09	101	14	3	5	7	3	2	
157	194.16	197.21	3.05	2.94	96	2.80	92	14	3	5	8	1	2	
157	197.21	200.25	3.04	3.04	100	3.04	100	15	3	5	5	1	1	
157	200.25	203.30	3.05	2.99	98	2.82	92	14	2	5	9	1	1	15 to c.a.
157	203.30	206.35	3.05	3.07	101	2.70	89	13	2	5	14	2	1	weak slick
157	206.35	209.40	3.05	3.09	101	3.09	101	15	3	5	5	1	2	mineralized fractures
157	209.40	212.45	3.05	3.05	100	3.05	100	14	3	5	7	1	1	
157	212.45	214.88	2.43	2.66	109	2.60	107	15	2	5	4	1	1	
157	214.88	218.08	3.20	3.05	95	2.88	90	15	2	5	5	1	1	gouge on fractures, extra footage
157	218.08	221.28	3.20	3.05	95	2.79	87	14	2	5	9	3	1	striations on joints, extra footage
157	221.28	224.33	3.05	3.05	100	2.99	98	14	2	5	7	1	1	very slick, no rake
157	224.33	227.53	3.20	3.05	95	2.90	91	15	2	5	5	2	1	extra footage
157	227.53	230.73	3.20	3.05	95	3.05	95	15	3	5	5	2	2	extra footage
157	230.73	233.78	3.05	3.05	100	2.85	93	14	3	5	7	2	1	
157	233.78	236.83	3.05	3.05	100	2.88	94	14	3	5	8	1	1	very slick at 50 to c.a.
157	236.83	239.88	3.05	3.05	100	2.84	93	13	2	4	15	1	1	10 cm. of gouge, healed gouge
157	239.88	242.93	3.05	3.15	103	2.91	95	13	2	4	12	3	1	healed gouge
157	242.93	245.97	3.04	2.79	92	2.54	84	14	2	5	9	1	2	
157	245.97	249.02	3.05	3.18	104	2.90	95	14	2	5	6	1	2	
157	249.02	252.07	3.05	3.05	100	2.68	88	13	2	5	12	1	2	
157	252.07	255.12	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
157	255.12	258.17	3.05	3.05	100	3.05	100	15	3	5	4	1	1	
157	258.17	261.21	3.04	3.04	100	3.01	99	15	3	5	5	1	1	very slick, no rake

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
157	261.21	264.26	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
157	264.26	267.31	3.05	3.05	100	3.05	100	15	3	5	2	1	3	
157	267.31	270.36	3.05	2.81	92	1.90	62	10	3	5	25	1	1	50% fault material
157	270.36	273.41	3.05	3.09	101	2.82	92	14	3	5	7	3	1	
157	273.41	276.45	3.04	3.05	100	3.04	100	14	3	5	8	1	1	
157	276.45	279.50	3.05	3.17	104	2.60	85	14	2	4	8	1	1	
157	279.50	282.55	3.05	3.05	100	2.51	82	14	2	4	6	1	1	
157	282.55	285.60	3.05	2.99	98	2.90	95	14	3	5	7	1	1	
157	285.60	288.65	3.05	3.08	101	3.00	98	14	4	6	6	1	2	
157	288.65	291.69	3.04	3.05	100	3.05	100	15	3	6	5	1	2	
157	291.69	294.74	3.05	2.62	86	2.62	86	15	3	5	5	1	2	
157	294.74	297.79	3.05	3.08	101	2.81	92	14	4	5	7	1	1	
157	297.79	300.84	3.05	3.25	107	2.42	79	10	3	5	30	1	1	1 weak slicks, 85 cm. of H=1
157	300.84	303.89	3.05	2.98	98	2.59	85	13	3	5	14	1	2	20 cm. of healed gouge
157	303.89	306.93	3.04	3.05	100	3.05	100	14	3	5	7	2	2	
157	306.93	309.98	3.05	3.08	101	3.05	100	15	3	5	5	1	2	
157	309.98	313.03	3.05	3.23	106	3.22	106	14	3	5	8	1	2	
157	313.03	316.08	3.05	2.80	92	2.69	88	14	3	5	7	1	2	
157	316.08	319.13	3.05	2.99	98	2.51	82	13	3	5	10	1	1	1 weak slicks at 40 to c.a.
157	319.13	322.17	3.04	3.05	100	3.05	100	15	3	5	5	2	3	
157	322.17	325.22	3.05	3.10	102	3.10	102	15	3	5	4	1	2	
157	325.22	328.27	3.05	2.97	97	2.77	91	14	3	5	6	1	2	
157	328.27	331.32	3.05	3.10	102	3.00	98	15	3	5	4	3	1	1 minor gouge
157	331.32	334.37	3.05	3.02	99	2.89	95	14	3	5	6	3	1	1 very slick, gouge
157	334.37	337.41	3.04	3.10	102	2.93	96	15	3	5	5	3	1	1 very slick, gouge
157	337.41	340.46	3.05	2.98	98	2.90	95	15	3	5	4	3	1	
157	340.46	343.51	3.05	3.08	101	3.08	101	15	3	5	5	1	1	
157	343.51	346.56	3.05	2.98	98	2.81	92	14	3	5	6	1	1	1 gouge filled slick
157	346.56	349.61	3.05	2.99	98	2.99	98	15	3	5	3	1	1	1 gouge filled slick
157	349.61	352.65	3.04	2.85	94	2.41	79	13	2	5	12	1	1	1 minor gouge, minor slicks
157	352.65	355.70	3.05	2.85	93	2.73	90	14	2	5	9	1	1	1 minor gouge, minor slicks
157	355.70	358.75	3.05	3.11	102	2.71	89	14	3	5	9	1	1	1 minor gouge & slicks, 40 cm. of H=1
157	358.75	361.80	3.05	2.81	92	2.59	85	14	3	5	7	1	1	1 minor gouge, minor slicks
157	361.80	364.85	3.05	3.05	100	2.78	91	14	3	5	8	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
157	364.85	367.89	3.04	3.05	100	2.98	98	15	4	5	3	3	3	
157	367.89	370.94	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
157	370.94	373.99	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
157	373.99	377.04	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
157	377.04	380.09	3.05	2.95	97	2.41	79	15	2	4	22	1		1 15 cm. of healed gouge, H=1
157	380.09	383.13	3.04	2.96	97	2.84	93	14	3	5	10	1		2 10 cm. of healed gouge, H=1
157	383.13	386.18	3.05	3.05	100	2.62	86	13	2	5	13	1		1 weak slicks
157	386.18	389.23	3.05	3.00	98	2.85	93	14	2	5	8	1		1 weak slicks
157	389.23	392.28	3.05	3.02	99	3.02	99	15	3	5	4	1		2
157	392.28	395.33	3.05	3.08	101	3.08	101	15	3	5	5	1		1 weak slicks
157	395.33	398.37	3.04	3.04	100	1.19	39	10	1	3	25	1		1 contacts at 395.93(30); 398.00 (55)
157	398.37	401.42	3.05	3.05	100	3.05	100	15	3	5	4	1		3
157	401.42	404.47	3.05	3.02	99	2.92	96	15	3	5	5	1		1
157	404.47	407.52	3.05	2.90	95	2.90	95	15	3	5	4	1		1
157	407.52	410.57	3.05	2.98	98	2.71	89	14	2	5	9	1		1 very slick, no rake; cave
157	410.57	413.61	3.04	3.24	107	2.76	91	13	2	5	12	1		1 gouge on fractures, slicks
157	413.61	416.66	3.05	2.70	89	2.27	74	11	2	4	18	1		1 very slick
157	416.66	419.71	3.05	2.94	96	2.50	82	13	2	4	13	1		1 very slick
157	419.71	422.76	3.05	3.02	99	3.02	99	15	3	5	5	1		3
157	422.76	425.81	3.05	2.98	98	2.98	98	15	3	5	4	1		2
157	425.81	428.85	3.04	3.05	100	3.05	100	15	3	5	5	1		2
157	428.85	431.90	3.05	2.95	97	2.95	97	15	3	5	4	1		2
157	431.90	434.95	3.05	3.05	100	3.05	100	15	4	5	2	1		2
157	434.95	438.00	3.05	3.05	100	3.05	100	15	3	5	4	1		1
157	438.00	441.05	3.05	3.05	100	3.05	100	15	4	6	2	1		2
157	441.05	444.09	3.04	3.18	105	3.18	105	15	4	5	2	1		2
157	444.09	447.14	3.05	3.05	100	3.05	100	15	4	5	3	1		2
157	447.14	450.19	3.05	3.02	99	2.35	77	7	3	5	60	1		1 52 cm. of fault gouge; H=0,1
157	450.19	453.24	3.05	3.01	99	2.18	71	4	3	5	80	1		1 451.50 m. - very slick at 45 to c.a.
157	453.24	455.98	2.74	2.71	99	2.71	99	15	2	5	4	1		1 minor gouge on slicks
157	455.98	459.03	3.05	3.02	99	2.90	95	15	2	4	5	3		1 redrilled core, gouge on slicks
157	459.03	462.38	3.35	3.30	99	3.30	99	15	3	5	3	1		2
157	462.38	465.43	3.05	2.93	96	2.93	96	15	3	5	3	1		2
157	465.43	468.48	3.05	3.00	98	3.00	98	15	3	5	2	1		3

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
157	468.48	471.53	3.05	3.10	102	3.10	102	15	3	5	5	1	1	1 weak slick with gouge
157	471.53	474.57	3.04	3.09	102	3.09	102	14	3	5	7	1	1	
157	474.57	477.62	3.05	3.05	100	3.02	99	14	3	5	7	1	1	1 no rake, strong slicks with gouge
157	477.62	480.06	2.44	2.47	101	2.31	95	10	3	4	20	1	1	1 no rake, slicks with gouge, H=0
157	480.06	483.26	3.20	2.72	85	2.62	82	14	3	4	8	1	1	1 no rake, strong slicks with gouge
157	483.26	486.77	3.51	3.80	108	3.80	108	15	3	5	5	1	2	2 redrilled core
157	486.77	489.81	3.04	3.02	99	3.02	99	15	3	5	3	1	2	
157	489.81	492.86	3.05	2.96	97	2.83	93	15	3	5	5	1	1	1 slick fractures, minor gouge
157	492.86	495.91	3.05	3.01	99	3.01	99	15	4	6	3	1	2	
157	495.91	498.96	3.05	3.15	103	3.15	103	15	3	5	4	3	1	1 slight gouge
157	498.96	502.01	3.05	3.08	101	2.88	94	14	2	5	6	3	1	
157	502.01	505.05	3.04	3.04	100	2.94	97	15	2	5	5	1	1	
157	505.05	508.10	3.05	3.02	99	2.90	95	15	2	5	5	1	1	
157	508.10	511.15	3.05	3.05	100	3.05	100	15	4	5	4	1	1	1 gouge, start of mineralization, slicks
157	511.15	514.20	3.05	3.05	100	2.92	96	14	4	5	6	1	1	1 heavily mineralized
157	514.20	517.25	3.05	2.95	97	2.95	97	14	3	5	6	2	1	1 redrilled core, very slick
157	517.25	520.29	3.04	3.01	99	3.01	99	15	4	6	2	1	2	
157	520.29	523.34	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
157	523.34	526.39	3.05	2.98	98	2.98	98	15	4	6	3	1	2	2 redrilled bit of core
157	526.39	529.44	3.05	3.05	100	3.05	100	14	3	6	6	1	1	1 polished slick/fracture
157	529.44	532.49	3.05	3.05	100	3.05	100	15	4	5	4	1	1	1 possible slick, very weak
157	532.49	535.53	3.04	3.04	100	3.04	100	15	4	6	4	1	2	
157	535.53	538.58	3.05	3.05	100	3.05	100	15	4	6	4	1	2	
158	5.18	8.84	3.66	2.05	56	0.29	8	7	2	3	30	5	3	3 broken weathered core
158	8.84	11.28	2.44	2.25	92	1.31	54	7	2	3	30	5	3	3 broken weathered core
158	11.28	14.33	3.05	2.67	88	0.47	15	7	2	3	30	5	3	3 broken weathered core
158	14.33	17.38	3.05	2.74	90	0.57	19	7	2	3	30	5	3	3 broken weathered core
158	17.38	20.42	3.04	2.95	97	0.46	15	10	3	4	25	1	3	3 15% broken core with gouge
158	20.42	23.47	3.05	2.82	92	1.14	37	12	3	4	17	1	3	3 20% broken core with gouge
158	23.47	26.52	3.05	2.76	90	0.89	29	9	3	5	30	5	3	3 25% broken core
158	26.52	29.57	3.05	2.95	97	2.16	71	13	3	5	13	1	3	
158	29.57	32.61	3.04	2.64	87	0.00	0	9	2	4	30	5	3	3 75% broken core with gouge
158	32.61	35.66	3.05	1.92	63	1.60	52	7	2	4	30	5	3	3 first 0.5 m. broken core with gouge
158	35.66	38.71	3.05	2.69	88	1.73	57	10	3	5	18	5	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
158	38.71	41.76	3.05	3.01	99	2.51	82	13	2	4	14	5	3	fractures contain gouge material
158	41.76	44.81	3.05	3.00	98	2.78	91	14	3	4	10	5	3	minor gouge on fractures
158	44.81	47.85	3.04	3.04	100	2.92	96	14	3	5	8	1	3	
158	47.85	50.90	3.05	3.05	100	2.93	96	15	3	5	5	1	3	
158	50.90	53.95	3.05	3.00	98	2.61	86	15	3	5	4	1	3	gouge on fractures
158	53.95	57.00	3.05	3.05	100	2.49	82	14	3	5	7	1	3	
158	57.00	60.05	3.05	3.00	98	3.00	98	15	3	5	2	1	3	
158	60.05	63.09	3.04	2.88	95	2.88	95	15	3	5	1	1	3	
158	63.09	66.14	3.05	3.05	100	3.05	100	15	3	5	2	1	3	
158	66.14	69.19	3.05	3.05	100	2.84	93	14	3	5	7	1	3	
158	69.19	72.24	3.05	3.05	100	3.05	100	15	3	5	5	1	3	
158	72.24	75.29	3.05	3.05	100	3.05	100	15	3	5	2	1	3	minor gouge on fractures
158	75.29	78.33	3.04	3.00	99	3.00	99	15	3	5	3	1	3	gouge on fractures
158	78.33	81.38	3.05	2.92	96	2.44	80	15	3	5	1	1	3	minor gouge on fractures
158	81.38	84.43	3.05	3.05	100	2.94	96	15	3	5	2	1	3	
158	84.43	87.48	3.05	3.09	101	2.87	94	15	3	5	4	1	3	minor gouge on fractures
158	87.48	90.53	3.05	3.05	100	3.05	100	15	3	5	1	1	3	
158	90.53	93.57	3.04	2.99	98	2.99	98	15	3	5	3	1	3	
158	93.57	96.62	3.05	3.05	100	3.05	100	15	3	5	2	1	3	
158	96.62	99.67	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
158	99.67	102.72	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
158	102.72	105.77	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
158	105.77	108.81	3.04	3.04	100	3.04	100	15	3	5	2	1	2	
158	108.81	111.86	3.05	3.05	100	2.64	87	14	3	5	7	5	3	gouge on fractures
158	111.86	114.91	3.05	2.77	91	2.25	74	13	3	5	12	5	3	5% broken core with gouge
158	114.91	117.96	3.05	3.05	100	2.72	89	14	3	5	8	1	3	5% broken core with gouge
158	117.96	121.01	3.05	3.05	100	2.70	89	13	3	5	14	5	3	gouge on fractures
158	121.01	124.05	3.04	2.95	97	2.68	88	12	3	5	17	5	3	129.60 m. - 0.5 m. healed gouge at 30
158	124.05	127.10	3.05	3.05	100	2.49	82	10	3	5	22	5	3	gouge on fractures
158	127.10	130.15	3.05	3.09	101	2.79	91	12	3	5	19	5	3	gouge on fractures
158	130.15	133.20	3.05	3.08	101	2.45	80	10	2	5	25	5	3	10% broken core with gouge
158	133.20	136.25	3.05	2.80	92	2.12	70	10	2	5	25	5	3	15% broken core with gouge
158	136.25	139.29	3.04	3.00	99	2.65	87	10	2	5	25	5	3	last 0.25 m. of interval is gouge
158	139.29	142.34	3.05	3.05	100	2.95	97	14	2	5	6	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
158	142.34	145.39	3.05	2.91	95	2.69	88	14	2	5	9	1	3	144.40 m. - 145.39 healed fault gouge
158	145.39	148.44	3.05	3.00	98	2.57	84	14	2	5	8	1	3	145.39 m. - 146.72 healed fault gouge
158	148.44	151.49	3.05	2.72	89	2.49	82	15	3	5	3	1	3	
158	151.49	154.53	3.04	3.12	103	2.76	91	15	3	5	4	1	3	
158	154.53	157.58	3.05	2.70	89	2.24	73	12	3	5	15	5	3	20% broken core
158	157.58	160.63	3.05	2.53	83	1.60	52	10	4	4	25	5	3	broken core (dyke)
158	160.63	163.68	3.05	3.00	98	1.76	58	10	4	4	25	5	3	broken core (dyke)
158	163.68	166.73	3.05	2.60	85	1.04	34	10	4	4	25	5	3	broken core (dyke)
158	166.73	169.77	3.04	2.72	89	2.14	70	10	4	5	25	5	3	broken core (dyke)
158	169.77	172.82	3.05	3.08	101	2.94	96	14	4	5	7	1	3	
158	172.82	175.87	3.05	3.07	101	2.13	70	12	4	5	20	5	3	20% broken core
158	175.87	178.92	3.05	2.95	97	2.68	88	10	3	5	20	5	3	40% broken core, healed gouge @
158	178.92	181.97	3.05	3.09	101	3.08	101	15	3	5	3	1	3	177.93 to 178.32 m. at 30 to c.a.
158	181.97	185.01	3.04	2.96	97	2.96	97	15	3	5	1	1	2	
158	185.01	188.06	3.05	2.84	93	2.84	93	15	3	5	3	1	3	
158	188.06	191.11	3.05	3.10	102	3.10	102	15	3	5	2	1	3	
158	191.11	194.16	3.05	2.92	96	2.75	90	14	3	5	5	1	3	
158	194.16	197.21	3.05	2.89	95	2.77	91	13	3	5	10	1	3	194.16-194.3 m. healed fault gouge
158	197.21	200.25	3.04	2.96	97	2.96	97	15	3	5	2	1	3	
158	200.25	203.30	3.05	2.93	96	2.80	92	15	3	5	4	1	3	200.79-200.86 m. - healed gouge at 60
158	203.30	206.35	3.05	3.10	102	2.59	85	14	3	5	10	1	3	
158	206.35	209.40	3.05	2.91	95	1.50	49	10	4	5	25	5	3	40% broken core
158	209.40	212.45	3.05	3.09	101	2.94	96	15	4	5	3	1	3	
158	212.45	215.49	3.04	2.97	98	2.61	86	14	4	5	8	1	3	
158	215.49	218.54	3.05	3.05	100	2.68	88	15	3	5	11	1	3	
158	218.54	221.59	3.05	3.08	101	2.93	96	15	3	5	3	1	3	minor gouge on fractures
158	221.59	224.64	3.05	3.00	98	2.51	82	15	3	5	18	5	3	10% broken core with gouge
158	224.64	227.69	3.05	3.05	100	2.90	95	15	3	5	6	1	3	
158	227.69	230.73	3.04	2.98	98	2.72	89	14	3	5	4	1	3	
158	230.73	233.78	3.05	3.10	102	3.10	102	15	3	5	2	1	3	
158	233.78	236.83	3.05	3.05	100	3.05	100	15	3	5	1	1	3	
158	236.83	239.88	3.05	3.12	102	2.67	88	14	3	5	6	1	3	gouge on fractures
158	239.88	242.93	3.05	2.97	97	2.10	69	10	2	5	25	5	3	15% broken core with gouge
158	242.93	245.97	3.04	3.04	100	2.72	89	14	2	5	7	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
158	245.97	249.02	3.05	3.05	100	3.05	100	15	3	5	3	1	3	3 minor gouge on fractures
158	249.02	252.07	3.05	2.98	98	2.88	94	14	2	5	8	1	1	1 gouge on fractures
158	252.07	255.12	3.05	3.10	102	3.02	99	15	3	5	4	1	1	1 gypsum and gouge, weak slick
158	255.12	258.17	3.05	3.10	102	3.10	102	15	2	5	3	3	2	2 gouge on fractures
158	258.17	261.21	3.04	3.02	99	3.02	99	15	3	4	4	1	1	1 30cm. of healed gouge
158	261.21	264.26	3.05	3.04	100	3.01	99	15	3	5	3	1	2	2
158	264.26	267.31	3.05	3.15	103	3.10	102	15	3	5	5	1	1	1 gypsum on fractures
158	267.31	270.36	3.05	3.13	103	3.13	103	15	3	5	4	1	1	1 gypsum on fractures
158	270.36	273.41	3.05	2.84	93	2.80	92	15	3	5	3	1	2	2
158	273.41	276.45	3.04	2.44	80	2.10	69	13	2	4	12	3	1	1 20 cm. of redrilled core
158	276.45	279.50	3.05	2.98	98	2.42	79	13	2	4	12	3	2	2 redrilled core
158	279.50	282.55	3.05	3.05	100	2.69	88	13	2	4	14	1	1	1 soft sections of rock
158	282.55	285.60	3.05	3.12	102	2.22	73	14	2	4	9	1	1	1 very slick contact at 10 to c.a.
158	285.60	288.65	3.05	2.80	92	2.52	83	14	3	5	7	1	1	1 slicks at 283.8 - 284.65 m., healed gouge
158	288.65	291.69	3.04	2.93	96	2.84	93	14	3	5	5	1	1	1 powdered joints - fairly slick
158	291.69	294.74	3.05	3.08	101	2.93	96	14	3	5	8	1	1	1 gouge on slick
158	294.74	297.79	3.05	3.08	101	2.84	93	14	3	5	9	1	2	2 15 to c.a. contact, not slick
158	297.79	300.83	3.04	3.00	99	2.78	91	15	3	5	5	1	3	3
158	300.83	303.88	3.05	3.11	102	3.11	102	15	3	6	4	1	3	3
158	303.88	306.93	3.05	2.94	96	2.94	96	15	3	6	3	1	3	3 10 to c.a. contact - not slick
158	306.93	309.98	3.05	3.20	105	2.51	82	14	3	5	10	1	1	1 slicks at 45 to c.a., weak rake
158	309.98	313.03	3.05	3.05	100	2.75	90	13	3	4	13	1	2	2 30 cm. of rubble & gouge, H=1
158	313.03	316.08	3.05	3.05	100	2.91	95	15	3	5	5	2	2	2
158	316.08	319.13	3.05	3.09	101	2.88	94	14	3	5	6	1	2	2
158	319.13	322.17	3.04	3.02	99	3.02	99	15	3	5	4	1	1	1 weak slick, gouge on fracture
158	322.17	325.22	3.05	3.06	100	3.06	100	14	3	5	7	1	1	1 minor gouge
158	325.22	328.27	3.05	3.00	98	3.00	98	15	3	5	4	1	1	1 slick axis at 25 to c.a.
158	328.27	331.32	3.05	2.85	93	0.84	28	10	2	3	23	1	1	1
158	331.32	334.37	3.05	2.90	95	0.62	20	10	2	3	26	1	1	1 10 cm. of gouge, H=0
158	334.37	337.41	3.04	3.05	100	2.73	90	14	2	4	8	1	1	1
158	337.41	340.46	3.05	3.15	103	3.15	103	15	3	5	3	1	2	2
158	340.46	343.51	3.05	2.99	98	2.99	98	14	3	5	6	2	1	1
158	343.51	346.56	3.05	2.97	97	2.78	91	14	3	5	6	3	1	1 weak slick, minor gouge
158	346.56	349.61	3.05	3.10	102	3.10	102	15	2	5	5	1	2	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
158	349.61	352.65	3.04	3.04	100	3.02	99	15	3	5	3	1	2	
158	352.65	355.70	3.05	3.08	101	3.00	98	15	2	5	5	1	1	very slick, no rake
158	355.70	358.75	3.05	3.00	98	3.00	98	15	2	5	4	1	2	
158	358.75	361.80	3.05	3.13	103	3.13	103	14	2	5	6	1	2	
158	361.80	364.85	3.05	2.98	98	2.70	89	14	2	5	9	1	2	
158	364.85	367.89	3.04	3.08	101	2.68	88	14	2	5	8	1	1	gypsum
158	367.89	370.94	3.05	3.02	99	3.02	99	15	2	5	5	1	2	
158	370.94	373.99	3.05	3.05	100	1.63	53	13	2	4	15	1	1	gypsum fracture fillings
158	373.99	377.04	3.05	3.16	104	3.16	104	14	3	5	7	1	1	gypsum fracture fillings
158	377.04	380.09	3.05	3.05	100	3.05	100	15	3	5	4	1	1	gypsum fracture fillings
158	380.09	383.13	3.04	3.05	100	3.05	100	15	3	5	5	1	3	
158	383.13	386.18	3.05	3.05	100	3.05	100	14	3	5	6	2	2	
159	9.75	11.28	1.53	0.45	29	0.00	0	2	1	2	60	5	4	
159	11.28	11.89	0.61	0.42	69	0.00	0	2	0	1	50	5	4	
159	11.89	14.33	2.44	0.25	10	0.00	0	4	2	3	13	1	3	poor recovery
159	14.33	17.37	3.04	1.13	37	0.00	0	4	1	2	90	1	1	
159	17.37	20.42	3.05	1.97	65	0.00	0	5	1	3	40	1	2	
159	20.42	23.47	3.05	2.38	78	0.23	8	6	2	3	50	2	1	20 cm of H=0
159	23.47	26.52	3.05	2.53	83	0.35	11	7	2	3	40	2	1	30 cm of H=0
159	26.52	29.57	3.05	2.55	84	0.93	30	8	2	3	35	2	2	10 cm of H=0
159	29.57	32.61	3.04	1.78	59	0.34	11	4	0	2	70	1	1	50 % H=2,0
159	32.61	35.66	3.05	0.95	31	0.00	0	2	0	2	80	5	4	
159	35.66	38.71	3.05	0.47	15	0.00	0	2	0	2	40	5	4	
159	38.71	41.76	3.05	1.60	52	0.47	15	7	0	2	30	1	1	50% H=2,0
159	41.76	44.81	3.05	3.00	98	2.25	74	13	2	4	15	1	3	gouge on fracture
159	44.81	47.24	2.43	2.10	86	1.31	54	9	2	4	25	5	3	15% broken core with gouge
159	47.24	49.07	1.83	1.74	95	1.32	72	7	2	4	25	5	3	15% broken core with gouge
159	49.07	52.12	3.05	3.00	98	2.08	68	11	3	5	20	5	3	5% broken core with gouge
159	52.12	55.47	3.35	2.88	86	2.88	86	15	3	5	2	1	3	
159	55.47	57.00	1.53	1.82	119	1.43	93	15	3	5	3	1	3	
159	57.00	60.05	3.05	3.05	100	2.86	94	15	3	5	2	1	3	
159	60.05	63.09	3.04	3.00	99	3.00	99	15	3	5	1	1	3	
159	63.09	66.14	3.05	3.05	100	3.05	100	15	3	5	2	1	3	
159	66.14	69.19	3.05	3.10	102	3.00	98	15	3	5	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To	Lgth	m.	%	m.								%
159	69.19	72.24	3.05	3.05	100	2.58	85	15	3	5	4	1	3	
159	72.24	75.29	3.05	2.95	97	2.95	97	15	3	5	2	1	3	
159	75.29	78.33	3.04	3.06	101	2.90	95	15	3	5	3	1	3	
159	78.33	81.38	3.05	3.05	100	2.22	73	12	3	5	20	1	3	3 15% broken core with gouge
159	81.38	84.43	3.05	3.00	98	2.13	70	14	3	5	6	1	3	3 minor gouge on fracture
159	84.43	87.48	3.05	2.98	98	2.79	91	15	3	5	3	1	3	3 minor gouge on fracture
159	87.48	90.53	3.05	3.01	99	2.69	88	15	3	5	4	1	3	
159	90.53	93.57	3.04	3.04	100	2.86	94	15	2	4	5	1	3	3 healed fault gouge at 50 to c.a.
159	93.57	96.62	3.05	3.00	98	3.00	98	15	3	5	2	1	3	3 minor gouge on fractures
159	96.62	99.67	3.05	3.05	100	2.57	84	15	3	5	4	1	3	3 minor gouge on fractures
159	99.67	102.72	3.05	3.05	100	2.50	82	15	3	5	2	5	3	3 minor gouge on fractures
159	102.72	105.77	3.05	2.98	98	2.98	98	15	3	5	2	1	3	
159	105.77	108.81	3.04	3.09	102	3.00	99	15	3	5	3	1	3	
159	108.81	111.86	3.05	3.05	100	2.97	97	15	4	5	2	1	3	
159	111.86	114.91	3.05	3.05	100	3.05	100	15	4	5	1	1	3	
159	114.91	117.96	3.05	3.01	99	3.01	99	15	4	5	2	1	3	
159	117.96	121.01	3.05	3.05	100	3.05	100	15	3	5	1	1	3	
159	121.01	124.05	3.04	2.98	98	2.06	68	12	3	5	15	5	3	3 5% broken core
159	124.05	127.10	3.05	3.08	101	3.08	101	15	3	5	2	1	3	3 minor gouge on fracture
159	127.10	130.15	3.05	2.97	97	2.97	97	15	3	5	3	1	3	
159	130.15	133.20	3.05	3.05	100	3.05	100	15	4	5	1	1	3	
159	133.20	136.25	3.05	3.05	100	3.05	100	15	4	5	0			
159	136.25	139.29	3.04	3.04	100	3.04	100	15	3	5	1	1	3	
159	139.29	142.34	3.05	3.00	98	2.90	95	15	3	5	3	1	3	3 minor gouge on fracture
159	142.34	145.39	3.05	2.96	97	2.96	97	15	4	5	1	1	2	
159	145.39	148.44	3.05	3.05	100	3.05	100	15	4	5	2	1	2	
159	148.44	151.49	3.05	3.00	98	3.00	98	15	3	5	3	1	3	
159	151.49	154.53	3.04	3.09	102	3.09	102	15	4	5	2	1	3	
159	154.53	157.58	3.05	3.05	100	2.91	95	15	4	5	1	1	3	
159	157.58	160.63	3.05	2.96	97	2.96	97	15	4	5	2	1	3	
159	160.63	163.68	3.05	2.92	96	2.92	96	15	4	5	1	1	3	
159	163.68	166.73	3.05	3.00	98	3.00	98	15	3	5	3	1	3	
159	166.73	169.77	3.04	3.01	99	3.01	99	15	3	5	2	1	3	
159	169.77	172.82	3.05	3.05	100	2.87	94	15	3	5	2	1	3	3 minor gouge on fracture

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
159	172.82	175.87	3.05	2.99	98	2.99	98	15	3	5	3	1	3	3 minor gouge on fracture
159	175.87	178.92	3.05	3.05	100	2.67	88	15	2	4	4	1	3	3 healed fault gouge at 45 to c.a.
159	178.92	181.97	3.05	3.05	100	2.94	96	15	3	5	3	1	3	3 gouge on fractures
159	181.97	185.01	3.04	3.04	100	2.80	92	15	3	5	4	5	3	3 gouge on fractures
159	185.01	188.06	3.05	2.97	97	2.56	84	15	3	5	4	1	3	3
159	188.06	191.11	3.05	3.05	100	2.84	93	15	3	5	2	1	3	3
159	191.11	194.16	3.05	3.05	100	2.90	95	15	3	5	5	1	3	3
159	194.16	197.21	3.05	3.05	100	3.05	100	15	3	5	2	1	3	3
159	197.21	200.25	3.04	3.04	100	3.04	100	15	3	5	3	1	3	3 gouge on fractures
159	200.25	203.30	3.05	3.08	101	3.08	101	15	3	5	2	1	3	3
159	203.30	206.35	3.05	3.05	100	2.96	97	15	3	5	4	5	3	3
159	206.35	209.40	3.05	3.05	100	2.84	93	15	3	5	3	1	2	2
159	209.40	212.45	3.05	3.05	100	3.05	100	15	3	5	2	1	2	2
159	212.45	215.49	3.04	3.00	99	3.00	99	15	3	5	4	1	3	3 gouge on fractures
159	215.49	218.54	3.05	3.09	101	3.09	101	15	3	5	2	1	3	3
159	218.54	221.59	3.05	3.00	98	3.00	98	15	3	5	1	5	3	3
159	221.59	224.64	3.05	2.92	96	2.80	92	14	3	5	7	1	3	3 gouge on fractures
159	224.64	227.69	3.05	3.05	100	3.05	100	15	4	5	3	1	3	3
159	227.69	230.73	3.04	3.00	99	2.87	94	15	3	5	4	1	3	3
159	230.73	233.78	3.05	3.05	100	2.87	94	15	3	4	4	1	3	3
159	233.78	236.83	3.05	3.05	100	2.86	94	14	3	4	6	1	3	3
159	236.83	239.88	3.05	3.03	99	2.85	93	15	3	4	5	1	3	3
159	239.88	242.93	3.05	2.94	96	2.72	89	14	2	4	8	1	3	3 shear w/gouge 5 to c.a.240.95-242.0m
159	242.93	245.97	3.04	2.97	98	2.57	85	14	2	4	5	1	3	3 shear gouge 242.93-243.50 m
159	245.97	249.02	3.05	3.05	100	2.90	95	14	3	5	6	1	3	3 gouge on fracture 247.30m 40.to c.a.
159	249.02	252.07	3.05	3.05	100	2.90	95	14	3	5	6	1	1	1 weak slicks on fracture= pyrite/mud
159	252.07	255.12	3.05	3.05	100	2.65	87	14	3	5	10	1	3	3 gouge on fracture
159	255.12	258.17	3.05	2.90	95	2.75	90	15	3	5	4	1	3	3
159	258.17	261.21	3.04	3.04	100	2.65	87	13	3	5	13	1	2	2 gouge on fracture
159	261.21	264.26	3.05	2.95	97	2.80	92	14	3	5	7	1	3	3 calcite on fracture 45 to c.a.
159	264.26	267.31	3.05	3.05	100	3.05	100	15	3	5	5	1	2	2
159	267.31	270.36	3.05	3.01	99	2.81	92	15	3	5	4	1	2	2
159	270.36	273.41	3.05	3.00	98	2.71	89	14	3	5	7	1	2	2 pyrite on fracture
159	273.41	276.45	3.04	3.04	100	2.95	97	15	3	5	4	1	2	2 pyrite on fracture

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
159	276.45	279.50	3.05	3.03	99	2.95	97	15	3	5	4	1	3	
159	279.50	282.55	3.05	2.98	98	2.75	90	15	3	5	4	1	2	
159	282.55	285.60	3.05	3.10	102	2.80	92	15	3	5	5	1	2	
159	285.60	288.65	3.05	3.01	99	3.01	99	15	3	5	1	1	2	
159	288.65	291.69	3.04	2.88	95	2.62	86	14	3	5	5	1	2	pyrite on fracture
159	291.69	294.74	3.05	3.10	102	2.86	94	15	3	5	3	1	3	
159	294.74	297.79	3.05	3.00	98	2.88	94	15	3	5	2	1	3	minor gouge on fracture 15 to c.a.
159	297.79	300.84	3.05	3.00	98	2.47	81	15	3	5	4	1	2	pyrite on fracture
159	300.84	303.89	3.05	3.02	99	2.82	92	15	3	5	5	1	3	minor gouge at 301.60 m. 50 to c.a.
159	303.89	306.93	3.04	3.01	99	2.73	90	15	2	4	4	1	3	shear 304.8m 0-35 to c.a.; gouge
159	306.93	309.98	3.05	2.99	98	2.99	98	15	3	5	1	3	3	
159	309.98	313.03	3.05	3.06	100	2.94	96	15	3	5	3	1	2	
159	313.03	316.08	3.05	3.07	101	3.07	101	15	3	5	1	1	2	
159	316.08	319.13	3.05	3.02	99	2.90	95	15	3	5	2	1	3	
159	319.13	322.17	3.04	3.00	99	2.90	95	15	3	5	2	1	3	
159	322.17	325.22	3.05	3.05	100	2.90	95	15	3	5	3	1	3	minor gouge on fracture
159	325.22	328.27	3.05	2.99	98	2.66	87	14	3	5	5	1	3	
159	328.27	331.32	3.05	3.02	99	2.63	86	15	3	5	4	1	3	
159	331.32	334.37	3.05	3.01	99	3.01	99	15	3	5	1	1	3	
159	334.37	337.41	3.04	3.02	99	2.68	88	14	3	5	6	1	3	
159	337.41	340.46	3.05	3.00	98	3.00	98	15	3	5	2	1	3	
159	340.46	343.51	3.05	3.02	99	2.97	97	14	3	5	6	1	2	
159	343.51	346.56	3.05	3.05	100	2.46	81	14	3	5	7	1	3	
159	346.56	349.61	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
159	349.61	352.65	3.04	3.04	100	2.94	97	15	3	5	2	3	3	
159	352.65	355.70	3.05	3.05	100	3.05	100	15	3	5	2	3	2	
159	355.70	358.75	3.05	3.05	100	3.05	100	15	3	5	3	3	2	
159	358.75	361.80	3.05	3.05	100	3.05	100	15	3	5	0			
159	361.80	364.85	3.05	3.05	100	3.05	100	15	3	5	1	3	3	
159	364.85	367.89	3.04	3.04	100	3.04	100	15	3	5	3	3	2	
159	367.89	370.94	3.05	3.05	100	3.00	98	15	3	5	4	2	3	
159	370.94	373.99	3.05	3.05	100	2.75	90	14	3	5	7	3	2	
159	373.99	377.04	3.05	3.05	100	3.05	100	15	3	5	2	1	3	
159	377.04	380.09	3.05	3.05	100	2.95	97	15	2	4	3	1	2	cave @ 378m 15. 1cm shear

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
159	380.09	383.13	3.04	3.04	100	2.90	95	14	2	4	6	3	2 multiple shears/clay areas	
159	383.13	386.18	3.05	3.05	100	2.90	95	15	3	5	4	1	2 fault/shear @ 20. over 30 cm	
159	386.18	389.23	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
159	389.23	392.28	3.05	3.05	100	2.90	95	15	3	5	3	3	3	
159	392.28	395.33	3.05	3.05	100	3.00	98	15	3	5	3	1	2	
159	395.33	398.37	3.04	3.04	100	2.84	93	15	3	5	3	3	1	
159	398.37	401.42	3.05	3.05	100	2.65	87	14	3	4	6	3	3 40 cm highly fractured	
159	401.42	404.47	3.05	3.05	100	3.05	100	15	3	5	2	2	3	
159	404.47	407.52	3.05	3.05	100	3.05	100	15	3	5	1	1	2	
159	407.52	410.57	3.05	3.05	100	2.90	95	15	3	5	5	1	2	
159	410.57	413.61	3.04	3.04	100	3.04	100	15	3	5	1	1	3	
159	413.61	416.66	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
159	416.66	419.71	3.05	3.05	100	2.90	95	14	3	5	7	1	2	
159	419.71	422.76	3.05	3.05	100	2.50	82	13	3	4	11	3	1 clay altered fracture	
159	422.76	425.81	3.05	3.05	100	2.25	74	13	2	3	11	3	1 clay	
159	425.81	428.85	3.04	3.04	100	3.04	100	15	2	4	4	3	1	
159	428.85	431.90	3.05	3.05	100	3.05	100	15	3	5	2	1	2	
159	431.90	434.95	3.05	3.00	98	2.90	95	14	3	5	6	1	2	
159	434.95	438.00	3.05	2.96	97	2.96	97	14	3	5	6	1	2	
159	438.00	441.05	3.05	3.01	99	2.65	87	14	3	5	9	1	3	
159	441.05	444.09	3.04	3.09	102	3.09	102	15	3	5	4	1	2	
159	444.09	447.14	3.05	2.90	95	2.13	70	13	3	5	10	1	2	
159	447.14	450.19	3.05	3.00	98	3.00	98	15	3	5	4	1	2	
159	450.19	452.17	1.98	1.98	100	1.78	90	15	3	5	3	3	3	
159	452.17	453.24	1.07	1.00	93	0.65	61	14	3	5	3	1	3	
159	453.24	454.46	1.22	1.39	114	1.27	104	14	3	5	3	1	3	
159	454.46	456.29	1.83	1.70	93	1.37	75	14	3	5	3	1	3 calcite on fractures	
159	456.29	459.33	3.04	3.02	99	3.02	99	15	3	5	2	1	2	
159	459.33	462.38	3.05	3.05	100	2.78	91	14	3	5	6	1	2 mud on fractures	
159	462.38	465.43	3.05	2.85	93	2.35	77	14	2	4	9	1	2 mu/gouge on fractures	
159	465.43	468.48	3.05	2.90	95	2.21	72	13	2	4	10	1	3	
159	468.48	471.53	3.05	2.95	97	2.00	66	12	3	5	16	1	2 gypsum on fractures	
159	471.53	474.57	3.04	3.03	100	2.54	84	13	3	5	13	1	3	
159	474.57	477.62	3.05	3.03	99	2.85	93	14	3	5	6	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
159	477.62	480.67	3.05	3.09	101	2.98	98	14	3	5	7	1	1	1 weak slicks(80 rake) frags 20 to c.a.
159	480.67	483.72	3.05	3.05	100	2.92	96	15	3	5	5	1	3	
159	483.72	486.77	3.05	2.98	98	2.98	98	14	3	5	6	3	3	3 gypsum on fractures
159	486.77	489.81	3.04	3.01	99	2.50	82	14	2	4	8	1	1	1 weak slicks 30 to c.a.(80 rake)
159	489.81	492.86	3.05	3.02	99	2.90	95	15	3	5	4	1	3	
159	492.86	495.91	3.05	3.05	100	2.96	97	15	3	5	4	1	3	
159	495.91	498.96	3.05	3.05	100	2.70	89	14	3	5	8	1	3	
159	498.96	502.00	3.04	2.96	97	2.59	85	14	3	5	6	1	3	3 gypsum on fractures
160	24.92	26.52	1.60	1.54	96	1.11	69	13	2	4	8	1	2	
160	26.52	29.57	3.05	3.05	100	2.28	75	11	2	4	18	1	1	
160	29.57	32.61	3.04	2.85	94	2.52	83	13	2	5	12	1	2	
160	32.61	35.66	3.05	3.02	99	2.55	84	13	2	5	13	1	2	
160	35.66	38.71	3.05	3.05	100	3.05	100	15	3	6	3	1	2	
160	38.71	41.76	3.05	2.95	97	2.95	97	14	3	5	6	1	1	
160	41.76	44.81	3.05	3.00	98	2.84	93	14	3	5	8	2	1	1 gypsum on joints
160	44.81	47.85	3.04	3.00	99	2.72	89	14	3	5	10	2	2	2 gypsum on joints
160	47.85	50.90	3.05	3.00	98	2.50	82	13	3	5	14	1	1	1 gypsum on joints
160	50.90	53.95	3.05	3.05	100	2.78	91	13	3	5	13	1	1	1 gypsum on joints
160	53.95	57.00	3.05	3.02	99	2.36	77	13	3	5	15	1	1	1 gypsum on joints
160	57.00	60.05	3.05	3.00	98	2.85	93	14	3	5	9	1	1	1 gypsum on joints
160	60.05	63.09	3.04	3.05	100	2.81	92	13	2	5	14	1	1	1 13 cm of H=0, slicks
160	63.09	66.14	3.05	2.85	93	2.40	79	13	2	4	12	1	1	
160	66.14	69.19	3.05	3.05	100	2.28	75	11	2	4	18	1	1	
160	69.19	72.24	3.05	2.95	97	2.65	87	14	2	5	9	1	1	
160	72.24	75.29	3.05	2.99	98	2.48	81	13	2	4	12	1	1	1 gouge on fractures
160	75.29	78.33	3.04	2.97	98	2.87	94	13	2	4	13	1	1	1 gouge on fractures
160	78.33	81.38	3.05	3.05	100	2.70	89	14	2	4	9	1	1	1 gouge on fractures
160	81.38	84.43	3.05	3.05	100	2.87	94	14	2	4	8	1	1	1 gouge on fractures
160	84.43	87.48	3.05	3.00	98	2.60	85	13	2	4	12	1	1	1 gouge on fractures
160	87.48	90.53	3.05	2.65	87	2.10	69	12	2	4	16	1	1	1 gouge on fractures
160	90.53	93.57	3.04	3.07	101	2.60	86	12	2	5	17	3	1	
160	93.57	96.62	3.05	2.98	98	2.28	75	13	2	5	14	1	1	
160	96.62	99.67	3.05	3.36	110	3.08	101	12	2	5	16	1	2	
160	99.67	102.72	3.05	3.08	101	2.91	95	14	3	5	7	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
160	102.72	105.77	3.05	2.90	95	2.66	87	14	2	5	8	1	2	
160	105.77	108.81	3.04	3.04	100	2.40	79	11	2	4	19	1	2	
160	108.81	111.86	3.05	2.95	97	2.95	97	14	3	5	6	1	2	
160	111.86	114.91	3.05	3.07	101	2.95	97	14	2	5	8	1	1	
160	114.91	117.96	3.05	3.05	100	3.05	100	15	3	5	5	1	1	
160	117.96	121.01	3.05	3.05	100	2.81	92	14	2	4	7	1	1	1 very slick
160	121.01	124.05	3.04	3.11	102	2.84	93	14	2	4	7	1	1	
160	124.05	127.10	3.05	2.75	90	2.05	67	12	2	4	16	1	1	
160	127.10	130.15	3.05	3.20	105	2.82	92	13	2	4	11	1	1	
160	130.15	133.20	3.05	3.00	98	2.72	89	13	2	5	12	1	1	1 slick contact
160	133.20	136.25	3.05	3.00	98	2.90	95	14	3	5	8	1	1	1 gypsum
160	136.25	139.29	3.04	2.66	88	2.46	81	14	3	5	7	1	1	
160	139.29	142.34	3.05	3.02	99	3.02	99	15	3	5	3	1	1	
160	142.34	145.39	3.05	3.05	100	3.00	98	15	3	5	3	1	1	1 145.30 m. - gouge H = 0
160	145.39	148.44	3.05	2.97	97	2.90	95	15	3	5	4	1	2	
160	148.44	151.49	3.05	3.05	100	3.05	100	15	3	5	5	1	2	
160	151.49	154.53	3.04	3.04	100	3.04	100	15	3	5	3	1	1	1 weak slicks
160	154.53	157.58	3.05	3.05	100	3.00	98	14	2	5	6	1	1	1 weak slicks, some healed material
160	157.58	160.63	3.05	2.99	98	2.99	98	14	3	5	6	1	1	1 weak slicks, fractures 40 to c.a.
160	160.63	163.68	3.05	3.15	103	3.15	103	15	3	5	5	1	2	
160	163.68	166.73	3.05	3.10	102	3.10	102	15	3	5	4	1	2	
160	166.73	169.77	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
160	169.77	172.82	3.05	3.05	100	3.05	100	15	3	5	5	1	2	
160	172.82	175.87	3.05	3.05	100	3.05	100	15	3	5	5	1	2	
160	175.87	178.92	3.05	2.93	96	2.93	96	14	3	5	7	1	2	
160	178.92	181.97	3.05	2.98	98	2.93	96	14	3	5	7	1	1	
160	181.97	185.01	3.04	2.95	97	2.95	97	14	4	5	6	1	2	
160	185.01	188.06	3.05	3.00	98	3.00	98	14	3	5	6	1	2	
160	188.06	191.11	3.05	3.00	98	2.90	95	13	3	5	10	1	2	
160	191.11	194.16	3.05	3.08	101	3.08	101	15	3	5	4	1	2	
160	194.16	197.21	3.05	3.12	102	3.06	100	14	3	5	6	1	2	
160	197.21	200.25	3.04	2.84	93	2.72	89	14	3	5	8	1	2	
160	200.25	203.30	3.05	2.83	93	2.69	88	14	3	5	8	1	2	
160	203.30	206.35	3.05	3.05	100	3.05	100	15	3	5	4	1	2	2 re-drilled core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
160	206.35	209.40	3.05	3.05	100	2.92	96	14	3	5	8	1	1	very slick; contact at 30 to c.a.
160	209.40	212.45	3.05	3.09	101	2.56	84	13	3	5	15	1	1	
160	212.45	215.49	3.04	3.04	100	3.04	100	14	2	5	9	1	1	
160	215.49	218.54	3.05	3.30	108	3.08	101	14	2	5	9	1	1	
160	218.54	221.59	3.05	3.05	100	3.01	99	14	2	5	7	1	1	
160	221.59	224.64	3.05	2.83	93	2.83	93	14	3	5	6	2	2	
160	224.64	227.69	3.05	3.08	101	3.08	101	15	3	5	4	1	2	
160	227.69	230.73	3.04	3.02	99	3.02	99	15	3	5	5	1	1	weak slicks, 45 to c.a.
160	230.73	233.78	3.05	3.05	100	3.05	100	14	3	5	6	1	1	weak slicks
160	233.78	236.83	3.05	3.05	100	3.05	100	15	3	5	5	1	1	weak slicks
160	236.83	239.88	3.05	3.05	100	3.05	100	14	3	5	6	1	2	
160	239.88	242.93	3.05	3.12	102	3.02	99	14	3	5	8	1	1	very slick contact
160	242.93	245.97	3.04	3.01	99	3.01	99	14	3	5	6	1	2	
160	245.97	249.02	3.05	2.94	96	2.94	96	15	3	5	5	1	2	
160	249.02	252.07	3.05	2.93	96	2.88	94	14	3	5	5	1	2	
160	252.07	255.12	3.05	3.10	102	3.10	102	14	3	5	7	1	2	
160	255.12	258.17	3.05	3.07	101	2.93	96	14	2	5	8	1	2	
160	258.17	261.21	3.04	3.04	100	3.04	100	15	3	5	5	1	2	
160	261.21	264.26	3.05	3.05	100	2.76	90	14	2	5	9	3	1	20 cm of clay H=1,2
160	264.26	267.31	3.05	3.00	98	3.00	98	15	3	5	4	1	2	
160	267.31	270.36	3.05	3.08	101	2.88	94	14	2	5	8	1	2	
160	270.36	273.41	3.05	2.95	97	2.95	97	15	3	5	3	1	2	re-drilled core
160	273.41	276.45	3.04	3.00	99	2.32	76	13	3	5	14	1	2	many gypsum fractures
160	276.45	279.50	3.05	2.97	97	2.77	91	13	3	5	11	1	2	many gypsum fractures
160	279.50	282.55	3.05	3.05	100	2.96	97	14	3	5	6	1	1	gypsum on fracture
160	282.55	285.60	3.05	3.05	100	3.00	98	15	3	5	4	1	1	slick 80 to c.a. with gouge
160	285.60	288.65	3.05	3.05	100	3.05	100	14	3	5	7	1	1	gypsum fractures
160	288.65	291.69	3.04	3.04	100	3.04	100	15	3	5	4	1	1	gypsum fractures
160	291.69	294.74	3.05	3.05	100	3.05	100	15	3	5	5	1	1	gypsum fractures
160	294.74	297.79	3.05	2.98	98	2.98	98	14	3	5	5	1	1	gypsum fractures
160	297.79	300.84	3.05	3.14	103	3.07	101	14	3	5	8	1	1	gypsum fractures
160	300.84	303.89	3.05	3.02	99	2.95	97	13	3	5	12	1	2	
160	303.89	306.93	3.04	3.13	103	2.93	96	13	3	5	15	1	1	
160	306.93	309.98	3.05	3.11	102	2.76	90	13	2	4	12	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
160	309.98	313.03	3.05	3.05	100	2.75	90	14	2	4	10	1	1	
160	313.03	316.08	3.05	2.80	92	2.15	70	12	2	4	18	1	1	
160	316.08	319.13	3.05	3.19	105	2.19	72	11	2	4	19	1	1	
160	319.13	322.17	3.04	3.00	99	2.05	67	11	2	4	20	1	1	
160	322.17	325.22	3.05	2.42	79	1.73	57	10	2	4	18	1	1	1 many slick contacts
160	325.22	328.27	3.05	3.02	99	2.59	85	13	2	4	15	1	1	1 gouge on fracture
160	328.27	331.32	3.05	3.05	100	2.90	95	14	3	4	9	1	2	
160	331.32	334.37	3.05	3.00	98	2.94	96	14	3	5	6	1	1	
160	334.37	337.41	3.04	2.53	83	0.85	28	11	2	4	17	3	1	
160	337.41	340.46	3.05	3.02	99	2.62	86	13	2	4	13	1	1	1 4 cm of H=0
160	340.46	343.51	3.05	3.04	100	2.96	97	14	2	5	9	1	1	1 slicks 45 to c.a.; rake at 10 to c.a.
160	343.51	346.56	3.05	2.95	97	2.50	82	10	3	5	14	1	1	1 very slick polished joints
160	346.56	349.61	3.05	3.02	99	2.99	98	15	3	5	5	1	1	
160	349.61	352.65	3.04	3.08	101	3.08	101	14	2	5	7	3	1	
160	352.65	355.70	3.05	3.12	102	3.12	102	15	3	5	5	3	1	
160	355.70	358.75	3.05	3.08	101	3.07	101	15	3	5	4	1	1	
160	358.75	361.80	3.05	2.91	95	2.88	94	14	3	5	8	1	1	1 gouge filled fracture
160	361.80	364.85	3.05	3.00	98	3.00	98	14	3	5	7	1	1	1 re-drilled, gypsum on fracture
160	364.85	367.89	3.04	3.07	101	3.07	101	15	3	5	5	1	1	1 re-drilled, gypsum on fracture
160	367.89	370.94	3.05	2.95	97	2.95	97	15	3	5	3	3	1	
160	370.94	373.99	3.05	2.95	97	2.95	97	15	3	5	3	1	2	
160	373.99	377.04	3.05	3.10	102	3.10	102	15	4	5	1	3	2	
160	377.04	380.09	3.05	3.14	103	3.14	103	15	4	5	3	1	1	
160	380.09	383.13	3.04	2.96	97	2.96	97	15	4	6	4	1	2	
160	383.13	386.18	3.05	3.10	102	2.80	92	15	3	5	5	1	1	1 gouge on slick, 30 to c.a.
160	386.18	389.23	3.05	3.05	100	2.91	95	14	2	5	7	1	1	
160	389.23	392.28	3.05	3.09	101	2.61	86	12	2	4	17	1	1	1 gouge on fractures
160	392.28	395.33	3.05	3.00	98	2.01	66	7	2	3	50	1	1	1 88 cm of H=0
160	395.33	398.37	3.04	3.19	105	2.74	90	12	2	4	16	1	1	
161	5.18	6.40	1.22	1.14	93	0.00	0	6	3	4	25	2	2	2 limonite stained broken core
161	6.40	7.62	1.22	1.18	97	0.71	58	9	3	4	12	2	2	2 limonite stained fractures
161	7.62	11.28	3.66	3.41	93	2.51	69	13	3	4	14	2	2	2 mod. broken angular core w/ gouge
161	11.28	14.33	3.05	2.42	79	1.48	49	10	3	4	19	2	2	2 gouge in broken core
161	14.33	17.37	3.04	2.87	94	1.32	43	12	3	4	16	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
161	17.37	20.42	3.05	2.59	85	2.38	78	13	3	4	10	2	2	2 gouge in fault zone at 50 to c.a.
161	20.42	23.47	3.05	2.94	96	1.76	58	13	3	4	11	2	2	
161	23.47	26.52	3.05	2.97	97	1.73	57	13	3	4	12	2	2	2 8 cm. gouge at 50 to c.a.
161	26.52	29.57	3.05	3.05	100	2.23	73	13	3	4	13	2	2	2 rubble cemented by gouge
161	29.57	32.61	3.04	3.04	100	2.64	87	14	3	4	7	2	2	2 broken core cemented by wet gouge
161	32.61	35.66	3.05	2.95	97	2.85	93	15	3	4	4	2	2	
161	35.66	38.71	3.05	2.94	96	2.06	68	14	3	4	9	2	2	2 wet clayish gouge
161	38.71	41.76	3.05	2.97	97	1.31	43	12	3	4	19	2	2	2 60% mod. broken core w/ 8 cm. gouge
161	41.76	44.81	3.05	3.05	100	2.42	79	12	3	4	18	2	2	2 5 cm. cemented wet gouge
161	44.81	47.85	3.04	3.04	100	2.40	79	14	3	4	8	2	2	2 gouge at end of fault zone at 50 to c.a.
161	47.85	50.90	3.05	3.05	100	2.04	67	13	3	4	12	2	2	2 strongly broken core w/ gouge
161	50.90	53.95	3.05	3.05	100	1.45	48	14	3	4	10	2	2	
161	53.95	57.00	3.05	2.98	98	0.51	17	13	3	4	14	2	2	2 strongly broken core w/ 10% gouge
161	57.00	60.05	3.05	3.01	99	0.96	31	10	3	4	30	2	2	2 70% strongly broken core w/ gouge
161	60.05	63.09	3.04	3.04	100	1.38	45	13	3	4	14	2	2	2 100% weakly broken core w/ gouge
161	63.09	66.14	3.05	2.83	93	0.00	0	7	3	4	50	2	2	2 100% weakly broken core w/ gouge
161	66.14	69.19	3.05	3.05	100	2.03	67	14	3	4	8	2	2	
161	69.19	72.24	3.05	2.81	92	2.25	74	14	3	4	6	2	2	2 gouge in mod. broken core
161	72.24	75.29	3.05	2.66	87	2.44	80	14	3	4	8	2	2	
161	75.29	78.34	3.05	3.05	100	1.71	56	12	3	3	19	2	2	2 two 1 cm. cemented gouge
161	78.34	81.38	3.04	2.92	96	2.19	72	14	3	4	8	2	2	2 gouge w/ 2-3 cm. sectn's of brkn core
161	81.38	84.43	3.05	3.05	100	1.14	37	11	3	4	19	2	2	
161	84.43	87.48	3.05	2.97	97	2.54	83	14	3	4	8	2	2	2 mod. broken core w/ gouge
161	87.48	90.53	3.05	3.18	104	1.94	64	12	3	4	16	2	2	2 mod. to strongly brkn core w/ gouge
161	90.53	93.57	3.04	2.94	97	2.88	95	14	3	4	6	2	2	2 fracturing parallel to c.a.
161	93.57	96.62	3.05	3.00	98	2.79	91	14	3	4	7	2	2	
161	96.62	99.67	3.05	3.05	100	2.89	95	14	3	4	7	2	1	
161	99.67	102.72	3.05	2.74	90	2.17	71	13	3	4	13	2	1	
161	102.72	105.77	3.05	2.81	92	1.51	50	13	3	4	13	1	1	1 slicks on edge of gypsum vein
161	105.77	108.81	3.04	3.19	105	2.59	85	13	2	3	13	1	1	1 fractures on gypsum veins
161	108.81	111.86	3.05	3.20	105	1.53	50	10	2	3	25	1	1	
161	111.86	114.91	3.05	3.30	108	0.80	26	6	2	2	50	1	1	
161	114.91	117.96	3.05	3.20	105	0.98	32	6	0	2	50	1	1	1 broken core w/ minor gouge
161	117.96	121.01	3.05	2.88	94	1.63	53	9	0	2	30	1	1	1 gouge & broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
161	121.01	124.05	3.04	3.00	99	0.83	27	6	0	2	50	1	1 gouge & broken core	
161	124.05	127.10	3.05	3.40	111	2.60	85	10	0	2	21	3	1 gypsum fractures	
161	127.10	130.15	3.05	3.15	103	1.94	64	9	0	2	30	2	2 broken and crumbly rock	
161	130.15	133.20	3.05	2.95	97	2.31	76	13	2	3	11	2	1	
161	133.20	136.25	3.05	3.15	103	2.31	76	12	2	3	15	2	1 polished surface	
161	136.25	139.29	3.04	3.15	104	2.72	89	14	2	3	8	4	1	
161	139.29	142.34	3.05	3.10	102	2.93	96	14	2	4	10	1	2 minor gouge fractures	
161	142.34	145.39	3.05	2.80	92	2.80	92	14	2	4	7	3	1 gypsum fractures	
161	145.39	148.44	3.05	2.97	97	2.12	70	11	0	2	20	1	2 gouge & broken core; gypsum	
161	148.44	151.49	3.05	3.10	102	2.61	86	11	0	2	20	1	1 gypsum fractures; gouge	
161	151.49	154.53	3.04	3.10	102	2.52	83	13	0	2	12	1	1 gypsum fractures	
161	154.53	157.58	3.05	3.13	103	2.98	98	15	3	3	5	2	2	
161	157.58	160.63	3.05	3.13	103	3.13	103	15	3	3	3	2	2	
161	160.63	163.68	3.05	3.20	105	2.84	93	14	3	3	6	2	1 gouge fracture at 30 to c.a.	
161	163.68	166.73	3.05	3.13	103	2.93	96	15	3	3	5	2	1 gouge fracture at 60 to c.a.	
161	166.73	169.77	3.04	3.10	102	2.95	97	15	3	3	4	2	1 gouge fracture at 55 to c.a.	
161	169.77	172.82	3.05	3.12	102	3.03	99	15	3	3	3	2	1 fractures on gypsum veins	
161	172.82	175.87	3.05	3.22	106	3.00	98	15	3	3	3	2	2	
161	175.87	178.92	3.05	3.18	104	3.18	104	15	3	3	3	2	2	
161	178.92	181.97	3.05	3.03	99	3.03	99	15	3	3	2	2	1 gouge along veins at 25 to c.a.	
161	181.97	185.01	3.04	3.08	101	3.08	101	15	3	3	5	1	1 trace gouge on slip at 30 to c.a.	
161	185.01	188.06	3.05	3.03	99	3.03	99	15	3	3	3	2	2 fractures on gypsum veins	
161	188.06	191.11	3.05	3.00	98	3.00	98	15	4	3	2	2	2	
161	191.11	194.16	3.05	3.13	103	3.12	102	15	4	3	3	2	1 gouge on 30 to c.a. slip; rake at 50 to c.a.	
161	194.16	197.21	3.05	3.10	102	3.05	100	15	4	3	3	2	2	
161	197.21	200.25	3.04	3.02	99	2.95	97	15	4	3	3	2	1 trace gouge on slip at 30 to c.a.	
161	200.25	203.30	3.05	3.08	101	3.08	101	15	4	3	3	2	2	
161	203.30	206.35	3.05	3.10	102	3.10	102	15	4	3	2	2	2	
161	206.35	209.40	3.05	2.97	97	2.97	97	15	4	3	1	2	2	
161	209.40	212.45	3.05	3.07	101	3.05	100	15	4	3	3	2	2	
161	212.45	215.49	3.04	3.05	100	2.92	96	15	4	3	3	2	1 1-2 mm. gouge on fracture at 35 to c.a.	
161	215.49	218.54	3.05	3.02	99	3.02	99	15	4	3	2	2	2	
161	218.54	221.59	3.05	3.04	100	2.94	96	15	4	3	2	2	1 trace gouge on slip at 45 to c.a.	
161	221.59	224.64	3.05	3.10	102	3.10	102	15	4	3	3	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
161	224.64	227.69	3.05	2.83	93	2.81	92	15	4	3	2	2	2	2 trace to weakly broken core
161	227.69	230.73	3.04	3.07	101	3.07	101	15	4	3	2	2	2	
161	230.73	233.78	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
161	233.78	236.83	3.05	3.15	103	3.11	102	15	2	4	5	1	3	3 shears at 30-35 to c.a.
161	236.83	239.88	3.05	3.05	100	2.67	88	14	2	4	10	3	3	3 gouge on fractures
161	239.88	242.93	3.05	2.79	91	1.94	64	12	2	4	17	1	3	
161	242.93	245.97	3.04	3.12	103	3.12	103	15	3	5	4	1	1	1 weak slicks/polished surfaces
161	245.97	249.02	3.05	3.06	100	3.06	100	14	3	5	10	1	2	2 polished slip planes
161	249.02	252.07	3.05	3.14	103	3.14	103	14	3	5	6	1	3	
161	252.07	255.12	3.05	2.97	97	2.97	97	15	3	5	4	1	2	
161	255.12	258.17	3.05	3.08	101	3.08	101	14	3	5	7	1	3	
161	258.17	261.21	3.04	3.05	100	3.05	100	14	3	5	9	1	2	2 gypsum along fractures
161	261.21	264.26	3.05	3.02	99	3.02	99	14	3	5	6	1	3	
161	264.26	267.31	3.05	3.07	101	3.07	101	15	3	5	5	1	3	3 gypsum along fractures
161	267.31	270.36	3.05	3.00	98	2.93	96	15	3	5	3	1	3	
161	270.36	273.41	3.05	3.10	102	3.07	101	14	3	5	6	1	3	3 gypsum along fractures
161	273.41	276.45	3.04	3.12	103	3.04	100	14	3	5	9	1	2	2 polished slip planes w/ pyrite
161	276.45	279.50	3.05	3.00	98	2.93	96	15	3	5	3	1	3	
161	279.50	282.55	3.05	3.10	102	3.10	102	15	3	5	5	1	3	3 gypsum & pyrite on fractures
161	282.55	285.60	3.05	3.08	101	3.01	99	15	3	5	4	4	3	
161	285.60	288.65	3.05	3.04	100	3.00	98	15	3	5	3	1	2	2 very weak slicks
161	288.65	291.69	3.04	3.04	100	3.04	100	14	3	5	6	1	2	2 gypsum on fractures
161	291.69	294.74	3.05	2.95	97	2.88	94	15	3	5	3	5	3	
161	294.74	297.79	3.05	3.15	103	3.10	102	15	3	5	5	1	2	2 gypsum on fractures
161	297.79	300.84	3.05	3.12	102	3.08	101	14	3	5	6	3	3	3 gypsum on fractures
161	300.84	303.89	3.05	3.05	100	2.38	78	12	3	5	20	1	2	
161	303.89	306.93	3.04	2.91	96	2.91	96	14	3	5	9	1	2	
161	306.93	309.98	3.05	3.03	99	3.00	98	15	4	4	4	2	2	
161	309.98	313.03	3.05	3.10	102	3.10	102	15	4	4	1	2	2	2 gouge on gypsum veins
161	313.03	316.08	3.05	2.96	97	2.94	96	15	4	4	4	2	2	1 slip w/ no gouge but slicks at 60 to c.a.
161	316.08	319.13	3.05	3.10	102	3.00	98	15	4	4	2	2	2	
161	319.13	322.17	3.04	3.01	99	3.01	99	15	4	4	3	2	2	
161	322.17	325.22	3.05	3.05	100	3.05	100	15	4	4	3	2	2	1 trace gouge at 20 to c.a.
161	325.22	328.27	3.05	3.10	102	3.10	102	15	4	4	3	1	1	1 trace gouge at 40 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
161	328.27	331.32	3.05	3.02	99	2.90	95	15	4	4	2	2	2	
161	331.32	334.37	3.05	3.02	99	2.98	98	15	4	4	3	2	2	2 2 cm. gypsum vein at 35 to c.a.
161	334.37	337.41	3.04	3.10	102	3.06	101	15	4	4	3	2	2	
161	337.41	340.46	3.05	2.90	95	2.90	95	15	4	4	3	2	2	
161	340.46	343.51	3.05	2.90	95	2.90	95	15	4	4	3	2	2	
161	343.51	346.56	3.05	3.03	99	3.03	99	15	4	4	4	2	2	1 gouge at 20 to c.a.
161	346.56	349.61	3.05	3.17	104	3.03	99	15	4	4	2	2	2	2 trace gouge at 20 to c.a.
161	349.61	352.65	3.04	3.15	104	3.09	102	15	4	4	5	1	1	1 slip w/ gouge in shear zone at 50 to c.a.
161	352.65	355.70	3.05	3.10	102	3.03	99	15	4	4	3	2	2	
161	355.70	358.75	3.05	3.08	101	3.08	101	15	4	4	2	2	2	
161	358.75	361.80	3.05	2.85	93	2.85	93	15	4	4	2	2	2	
161	361.80	364.85	3.05	3.20	105	3.05	100	15	4	4	4	2	2	2 trace gouge at 55 to c.a.
161	364.85	367.89	3.04	3.25	107	3.16	104	14	4	4	6	2	2	2 broken core in shear zone at 40 to c.a.
161	367.89	370.94	3.05	3.17	104	2.73	90	15	4	4	4	2	2	2 trace gouge in broken core
161	370.94	373.99	3.05	3.20	105	3.06	100	15	4	4	1	2	2	
161	373.99	377.04	3.05	3.10	102	2.97	97	15	4	4	1	2	2	
161	377.04	380.09	3.05	3.07	101	3.07	101	15	4	4	2	2	2	
161	380.09	383.13	3.04	3.04	100	1.40	46	10	3	4	10	2	2	2 50% weakly broken 1-10 cm. ang. core
161	383.13	386.18	3.05	3.17	104	2.97	97	12	3	4	15	1	1	1 gypsum on fractures
161	386.18	389.23	3.05	3.03	99	2.92	96	14	3	4	8	1	4	4 gypsum on fractures
161	389.23	392.28	3.05	3.14	103	3.14	103	14	3	4	9	1	1	1 gypsum on fractures
161	392.28	395.33	3.05	3.03	99	3.03	99	14	3	4	6	3	2	2 gypsum on fractures
162	6.10	8.23	2.13	0.20	9	0.00	0	6	2	3	6	1	3	3 weathered & iron stained; broken
162	8.23	11.28	3.05	1.50	49	0.48	16	6	2	3	30	5	3	3 weathered, 30% gouge; broken
162	11.28	14.33	3.05	1.35	44	0.00	0	6	2	4	30	5	3	3 end of iron staining; 11.40 m.-20% gouge
162	14.33	17.37	3.04	2.22	73	1.00	33	7	2	4	30	1	2	2 broken; 30% gouge
162	17.37	20.42	3.05	1.52	50	0.36	12	6	3	4	30	1	3	3 broken; minor gouge
162	20.42	23.47	3.05	2.70	89	1.32	43	7	3	4	40	1	2	2 gouge on fractures
162	23.47	26.52	3.05	2.62	86	0.92	30	7	3	4	35	5	3	3 5% gouge
162	26.52	29.57	3.05	2.93	96	2.15	70	10	3	3	25	1	3	3 gouge on fractures
162	29.57	32.61	3.04	3.08	101	1.85	61	12	3	4	20	5	3	3 gouge on fractures
162	32.61	35.66	3.05	3.05	100	2.13	70	10	3	4	22	1	3	3 5 cm. gouge sections throughout
162	35.66	38.71	3.05	2.97	97	1.82	60	9	3	4	35	3	3	3 10% gouge
162	38.71	41.76	3.05	2.80	92	2.20	72	10	3	4	20	1	2	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
162	41.76	44.81	3.05	2.98	98	1.94	64	10	3	4	20	5	3 gouge on fractures	
162	44.81	47.85	3.04	3.01	99	2.26	74	12	4	4	17	5	3 minor gouge on fractures	
162	47.85	50.90	3.05	2.80	92	1.20	39	9	4	4	35	5	3	
162	50.90	53.95	3.05	3.05	100	2.10	69	10	3	4	25	5	3 shears and gouge at 0 to c.a.	
162	53.95	57.00	3.05	3.05	100	2.27	74	10	3	3	21	5	3 5-10% gouge	
162	57.00	60.05	3.05	3.10	102	2.70	89	14	3	4	10	1	3 gouge; 57.35-57.75 m.-healed shear	
162	60.05	63.09	3.04	3.00	99	2.73	90	14	4	4	9	1	2 calcite on fractures	
162	63.09	66.14	3.05	3.03	99	2.85	93	14	3	4	10	1	3	
162	66.14	69.19	3.05	3.00	98	2.75	90	14	3	4	7	3	3 gouge on fractures	
162	69.19	72.24	3.05	2.70	89	1.65	54	9	3	4	30	3	3	
162	72.24	75.29	3.05	3.05	100	2.24	73	12	3	4	20	1	2 calcite on fracture surfaces	
162	75.29	78.33	3.04	3.04	100	2.65	87	14	3	4	10	1	3 gouge on fractures	
162	78.33	81.38	3.05	3.05	100	2.40	79	12	3	4	16	1	2	
162	81.38	84.43	3.05	3.05	100	2.85	93	14	4	5	6	1	2 trace gouge in broken core	
162	84.43	87.48	3.05	3.05	100	2.85	93	14	4	5	6	2	2	
162	87.48	90.53	3.05	2.95	97	2.63	86	14	4	5	7	1	1 three parallel breaks at 35 to c.a.	
162	90.53	93.57	3.04	3.14	103	3.01	99	14	4	5	7	1	2 breaks are in weakly broken core	
162	93.57	96.62	3.05	3.07	101	3.02	99	15	4	5	3	2	2	
162	96.62	99.67	3.05	2.90	95	2.74	90	15	4	5	4	1	2 trace gouge	
162	99.67	102.72	3.05	3.07	101	3.07	101	15	4	5	2	1	2	
162	102.72	105.77	3.05	2.97	97	2.90	95	15	4	5	4	1	2	
162	105.77	108.81	3.04	3.00	99	1.83	60	15	4	5	4	1	1 trace gouge on slip at 60 to c.a.	
162	108.81	111.86	3.05	2.86	94	2.69	88	14	4	4	9	1	2 15 cm. mod. broken core w/ trace gouge	
162	111.86	114.91	3.05	2.95	97	1.23	40	12	4	4	18	1	2 50% weakly broken core	
162	114.91	117.96	3.05	2.85	93	1.67	55	12	4	4	16	1	2 80% weakly broken core	
162	117.96	121.00	3.04	3.00	99	1.99	65	13	4	4	14	1	1 slip at 50 to c.a.	
162	121.00	124.05	3.05	3.00	98	2.57	84	15	4	5	4	1	2	
162	124.05	127.10	3.05	2.96	97	2.89	95	15	4	5	4	1	1 slip at 40 to ca.	
162	127.10	130.15	3.05	2.88	94	2.26	74	15	4	5	5	1	1 slip at 30 to c.a. with gouge	
162	130.15	133.20	3.05	3.05	100	2.80	92	15	4	5	5	1	2 trace gouge in fault zone at 50 to c.a.	
162	133.20	136.25	3.05	3.05	100	3.05	100	15	4	5	5	1	1 slip w/ gouge at 60 to c.a.	
162	136.25	139.29	3.04	2.95	97	2.95	97	15	4	5	1	1	2	
162	139.29	142.34	3.05	3.09	101	3.09	101	15	4	5	0			
162	142.34	145.39	3.05	3.08	101	3.08	101	15	4	5	0			

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
162	145.39	148.44	3.05	3.06	100	3.06	100	15	4	5	3	1	1 slip w/ gouge at 40 to c.a.	
162	148.44	151.49	3.05	3.02	99	3.02	99	15	4	5	4	1	1 trace gouge	
162	151.49	154.53	3.04	3.05	100	3.05	100	15	4	5	3	1	2	
162	154.53	157.58	3.05	3.09	101	3.09	101	15	4	5	1	1	2	
162	157.58	160.63	3.05	3.05	100	3.05	100	15	4	5	1	1	1 breaks on carbonate veins	
162	160.63	163.68	3.05	3.05	100	2.66	87	13	4	4	10	1	1 3 mm. wet gouge on slip at 65 to c.a.	
162	163.68	166.73	3.05	3.13	103	3.13	103	15	4	5	1	1	2	
162	166.73	169.77	3.04	3.06	101	2.92	96	15	4	5	5	1	2 breaks in broken core	
162	169.77	172.82	3.05	3.11	102	3.08	101	15	4	4	3	1	1 gouge on slip in fault zone at 30 to c.a.	
162	172.82	175.87	3.05	3.08	101	3.05	100	15	4	5	5	1	1 gouge on slip at 35 to c.a.	
162	175.87	178.92	3.05	3.05	100	2.94	96	15	4	5	2	1	2	
162	178.92	181.97	3.05	3.09	101	3.06	100	15	4	5	3	1	1 gouge on slip on qz vein at 60 to c.a.	
162	181.97	185.01	3.04	3.12	103	3.12	103	15	4	5	2	1	1 gouge on slip at 35 to c.a.	
162	185.01	188.06	3.05	2.97	97	2.97	97	15	4	5	2	2	2	
162	188.06	191.11	3.05	3.11	102	3.11	102	15	4	5	3	1	2	
162	191.11	194.16	3.05	3.03	99	2.88	94	14	4	4	7	1	1 gouge on slip at 40 to c.a.	
162	194.16	197.21	3.05	3.09	101	3.00	98	14	4	5	8	1	1 gouge on slips at 30, 40 and 60 to c.a.	
162	197.21	200.25	3.04	3.08	101	3.08	101	15	4	5	2	1	2	
162	200.25	203.30	3.05	3.04	100	2.93	96	15	4	5	2	1	1 gouge on slip in 2 cm. fault at 65 to c.a.	
162	203.30	206.35	3.05	3.07	101	2.82	92	14	4	4	8	1	1 gouge on slip in 3 cm. fault at 35 to c.a.	
162	206.35	209.40	3.05	2.91	95	2.91	95	15	4	5	4	1	1 gouge on gypsum vein at 40 to c.a.	
162	209.40	212.45	3.05	3.07	101	2.86	94	14	4	5	8	1	1 gouge on slips at 60 to c.a.	
162	212.45	215.49	3.04	3.07	101	3.07	101	15	4	5	4	1	2	
162	215.49	218.54	3.05	3.03	99	3.03	99	15	4	5	3	1	2 breaks on gypsum veins	
162	218.54	221.59	3.05	3.02	99	2.98	98	15	4	5	3	1	2 breaks on gypsum veins	
162	221.59	224.64	3.05	3.08	101	3.00	98	15	4	5	4	1	2 breaks on gypsum veins	
162	224.64	227.69	3.05	3.09	101	3.09	101	15	4	5	3	1	2 breaks on gypsum veins	
162	227.69	230.73	3.04	2.98	98	2.98	98	15	4	5	3	1	2	
162	230.73	233.78	3.05	3.00	98	3.00	98	15	4	5	3	1	2	
162	233.78	236.83	3.05	3.05	100	3.05	100	15	3	5	3	1	2	
162	236.83	239.88	3.05	3.05	100	3.05	100	15	3	5	5	1	2	
162	239.88	242.93	3.05	3.05	100	2.99	98	15	3	5	5	1	1 gypsum fractures at 60 to c.a.	
162	242.93	245.97	3.04	3.04	100	2.78	91	13	3	5	12	1	1 gypsum fractures; 35 cm. gouge	
162	245.97	249.02	3.05	3.05	100	3.05	100	14	3	5	6	1	1 slick contact at 30 to c.a.	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
162	249.02	252.07	3.05	3.02	99	3.02	99	14	3	5	6	1	1	75 to c.a.; very slick
162	252.07	255.12	3.05	3.00	98	3.00	98	15	3	5	4	3	1	very slick, minor gouge
162	255.12	258.17	3.05	3.05	100	3.02	99	15	3	5	5	1	1	weak slick
162	258.17	261.21	3.04	3.05	100	3.05	100	15	2	5	4	1	1	30% healed gouge
162	261.21	264.26	3.05	3.02	99	2.42	79	13	2	5	12	1	1	slick contact at 60 to c.a.
162	264.26	267.31	3.05	3.13	103	3.13	103	14	3	5	6	1	2	
162	267.31	270.36	3.05	3.05	100	3.05	100	14	3	5	6	1	1	gypsum
162	270.36	273.41	3.05	3.05	100	3.05	100	15	3	5	5	3	1	gypsum
162	273.41	276.45	3.04	3.00	99	2.80	92	14	3	5	8	1	1	slicks at 30 to 15 to c.a.
162	276.45	279.50	3.05	3.00	98	2.88	94	14	3	5	8	1	1	slicks at 25 to c.a.; gouge on fractures
162	279.50	282.55	3.05	3.07	101	3.00	98	14	3	5	7	1	1	60 to c.a.
162	282.55	285.60	3.05	3.10	102	2.86	94	15	4	5	4	2	1	gypsum; very slick at 15 to c.a.
162	285.60	288.65	3.05	3.05	100	2.88	94	15	3	5	4	2	1	gypsum; very slick at 15 to c.a.
162	288.65	291.69	3.04	3.02	99	2.96	97	14	3	5	6	1	1	minor gouge
162	291.69	294.74	3.05	3.10	102	3.08	101	14	3	5	7	1	1	minor gouge
162	294.74	297.79	3.05	2.90	95	2.80	92	14	3	5	6	1	1	
162	297.79	300.84	3.05	2.80	92	2.79	91	14	3	5	8	1	1	
162	300.84	303.89	3.05	3.10	102	3.05	100	14	3	5	8	1	1	
162	303.89	306.93	3.04	3.02	99	3.02	99	14	3	5	7	1	1	slick at 40 to c.a.; rake at 10
162	306.93	309.98	3.05	3.05	100	2.86	94	14	2	5	10	1	1	slick at 45 to c.a.; rake at 45
162	309.98	313.03	3.05	3.05	100	2.82	92	15	4	5	3	1	3	
162	313.03	316.08	3.05	3.07	101	3.07	101	15	4	5	4	1	3	minor gouge on fractures
162	316.08	319.13	3.05	3.01	99	3.01	99	15	3	5	2	1	3	minor gouge on fractures
162	319.13	322.17	3.04	2.88	95	2.88	95	15	3	5	1	1	3	
162	322.17	325.22	3.05	3.18	104	2.85	93	15	3	5	4	1	3	minor gouge on fractures
162	325.22	328.27	3.05	3.00	98	2.88	94	15	4	5	3	1	3	minor gouge on fractures
162	328.27	331.32	3.05	2.95	97	2.83	93	15	4	5	2	1	3	minor gouge on fractures
162	331.32	334.37	3.05	3.05	100	3.05	100	15	3	5	2	1	3	minor gouge on fractures
162	334.37	337.41	3.04	2.95	97	2.95	97	15	3	5	3	1	3	
162	337.41	340.46	3.05	3.05	100	2.98	98	15	3	5	2	1	3	
162	340.46	343.51	3.05	3.05	100	3.05	100	15	3	5	1	1	3	gouge on fractures
162	343.51	346.56	3.05	3.04	100	3.04	100	15	3	5	1	1	3	gouge on fractures
162	346.56	349.61	3.05	2.97	97	2.97	97	15	3	5	2	1	3	
163	6.71	7.92	1.21	0.20	17	0.00	0	6	3	3	10	1	3	broken rock

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
163	7.92	9.14	1.22	0.65	53	0.00	0	6	3	3	35	1	3 broken rock	
163	9.14	9.75	0.61	0.33	54	0.00	0	3	4	4	30	2	3 broken rock and minor gouge	
163	9.75	10.36	0.61	0.32	52	0.00	0	3	4	4	30	2	3 broken and minor gouge on fractures	
163	10.36	10.97	0.61	0.39	64	0.00	0	6	4	4	25	1	3 broken rock and minor gouge	
163	10.97	13.11	2.14	1.88	88	0.15	7	6	4	3	50	5	3 broken rock and minor gouge	
163	13.11	14.33	1.22	1.05	86	0.00	0	6	4	4	35	1	2 broken rock and minor gouge	
163	14.33	16.46	2.13	1.55	73	0.15	7	6	4	4	50	5	3 broken and minor gouge on fractures	
163	16.46	17.37	0.91	1.10	121	0.21	23	6	4	4	45	1	3	
163	17.37	20.42	3.05	2.93	96	1.92	63	12	3	3	17	5	3	
163	20.42	22.86	2.44	2.25	92	1.45	59	10	3	4	18	5	3	
163	22.86	25.91	3.05	2.93	96	1.97	65	12	3	4	17	1	3 pyrite and gouge on fractures 50 to c.a.	
163	25.91	28.96	3.05	2.80	92	1.03	34	10	3	4	22	2	3 pyrite and chalcopyrite on fractures	
163	28.96	29.26	0.30	0.44	147	0.44	147	14	4	4	1	1	3	
163	29.26	32.31	3.05	2.88	94	2.66	87	13	4	4	11	1	3	
163	32.31	35.36	3.05	2.87	94	2.19	72	13	4	4	13	1	3 pyrite on fractures	
163	35.36	35.66	0.30	0.30	100	0.17	57	7	4	4	5	5	3	
163	35.66	38.71	3.05	2.88	94	2.88	94	15	4	4	3	1	3	
163	38.71	41.76	3.05	3.02	99	2.93	96	15	4	4	5	5	3	
163	41.76	44.81	3.05	2.98	98	2.67	88	14	4	4	8	5	3	
163	44.81	47.85	3.04	3.04	100	3.04	100	15	4	4	2	5	3	
163	47.85	50.90	3.05	2.96	97	2.96	97	15	4	4	4	5	3	
163	50.90	53.95	3.05	2.98	98	2.92	96	14	4	5	5	1	2 calcite on fractures	
163	53.95	57.00	3.05	3.05	100	2.30	75	13	4	5	13	5	3	
163	57.00	60.05	3.05	2.98	98	2.52	83	13	4	5	13	1	2 gouge/mud on fragments	
163	60.05	63.09	3.04	2.99	98	2.53	83	14	4	5	7	1	3 calcite on fractures	
163	63.09	66.14	3.05	2.96	97	2.18	71	13	4	5	13	1	2 calcite on fractures	
163	66.14	69.19	3.05	3.05	100	2.41	79	13	4	5	13	1	3	
163	69.19	72.24	3.05	2.92	96	2.92	96	14	4	5	5	1	3 pyrite on fractures	
163	72.24	75.29	3.05	3.01	99	2.95	97	14	4	5	7	1	3	
163	75.29	78.33	3.04	3.10	102	3.10	102	15	3	5	5	1	1 gouge at 25 to c.a.; no rake	
163	78.33	81.38	3.05	3.10	102	2.99	98	14	3	5	7	1	2	
163	81.38	84.43	3.05	3.10	102	3.01	99	15	3	5	4	1	2	
163	84.43	87.48	3.05	3.05	100	2.99	98	14	3	5	6	1	1 very slick; 5 to c.a. with gouge	
163	87.48	90.53	3.05	2.98	98	2.88	94	14	3	5	8	3	1 very slick; 5 to c.a. with gouge	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
163	90.53	93.57	3.04	3.04	100	3.04	100	15	4	5	3	1	1	1 very slick; 5 to c.a. with gouge
163	93.57	96.62	3.05	3.05	100	2.98	98	14	3	5	8	1	1	1 weak slicks at 45 to c.a.
163	96.62	99.67	3.05	2.93	96	2.57	84	14	3	5	9	2	2	
163	99.67	102.72	3.05	3.05	100	2.88	94	14	4	5	6	2	2	1 35 to c.a.
163	102.72	105.77	3.05	3.02	99	3.02	99	15	3	5	5	1	2	
163	105.77	108.81	3.04	2.99	98	2.99	98	15	3	5	3	1	2	
163	108.81	111.86	3.05	3.19	105	3.19	105	15	4	5	4	3	2	2 gouge on fractures
163	111.86	114.91	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
163	114.91	117.96	3.05	3.05	100	3.00	98	15	4	5	5	1	3	
163	117.96	121.01	3.05	3.02	99	3.02	99	15	4	5	3	3	1	1 minor gouge
163	121.01	124.05	3.04	2.97	98	2.97	98	15	4	5	3	1	2	2 fractures at 15 to c.a.
163	124.05	127.10	3.05	3.02	99	3.02	99	15	3	5	3	3	2	
163	127.10	130.15	3.05	3.08	101	3.00	98	14	3	5	6	1	1	1 slicks at 45 to c.a.
163	130.15	133.20	3.05	3.10	102	3.10	102	15	3	5	3	1	1	1 weak slicks at 65 to c.a.
163	133.20	136.25	3.05	2.97	97	2.80	92	14	3	5	6	1	1	1 weak slicks at 65 to c.a.
163	136.25	139.29	3.04	3.00	99	2.75	90	14	2	5	6	1	1	1 slicks at 60 to c.a.
163	139.29	142.34	3.05	3.08	101	3.08	101	15	3	5	4	1	2	
163	142.34	145.39	3.05	2.98	98	2.98	98	15	3	5	3	1	2	
163	145.39	148.44	3.05	3.09	101	3.09	101	15	3	5	3	3	1	
163	148.44	151.49	3.05	3.02	99	2.97	97	15	3	5	4	3	1	
163	151.49	154.53	3.04	2.92	96	2.92	96	15	4	5	2	3	1	
163	154.53	157.58	3.05	3.02	99	2.90	95	14	3	4	7	1	1	1 slick contact at 55 to c.a.
163	157.58	158.80	1.22	1.09	89	0.37	30	10	3	5	8	1	3	
163	158.80	160.63	1.83	1.88	103	1.88	103	15	3	5	2	1	2	
163	160.63	163.68	3.05	2.95	97	1.42	47	13	3	5	13	1	2	
163	163.68	166.73	3.05	2.88	94	2.86	94	10	3	4	25	1	1	1 slick at 10 to c.a.; 20 cm. of H=0
163	166.73	169.77	3.04	2.85	94	2.85	94	15	3	5	4	1	1	1 slicks at 60 to c.a.
163	169.77	172.82	3.05	3.08	101	3.08	101	15	3	5	5	1	3	3 healed fractures
163	172.82	175.87	3.05	3.08	101	3.08	101	15	4	5	3	2	3	3 healed fractures
163	175.87	178.92	3.05	2.95	97	2.95	97	15	4	5	2	3	2	2 gouge on joint at 50 to c.a.; slick ?
163	178.92	181.97	3.05	2.96	97	2.96	97	15	3	5	4	1	1	1 90 cm. of healed gouge; H=2
163	181.97	185.01	3.04	2.95	97	2.95	97	15	4	5	2	3	2	2 healed fractures
163	185.01	188.06	3.05	2.90	95	2.90	95	15	4	5	3	3	4	
163	188.06	191.11	3.05	2.98	98	2.98	98	15	4	6	1	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
163	191.11	192.94	1.83	1.73	95	1.68	92	14	4	5	4	1	2 fracture filled with minor gouge
163	192.94	194.16	1.22	1.31	107	1.31	107	15	4	5	1	5	3 192.72-193.01 m. - redrilled core
163	194.16	197.21	3.05	3.00	98	3.00	98	15	4	6	2	1	3
163	197.21	200.25	3.04	3.02	99	3.02	99	15	4	6	3	1	3
163	200.25	203.30	3.05	3.15	103	3.15	103	15	4	6	2	1	3 healed fractures
163	203.30	206.35	3.05	3.01	99	3.01	99	15	4	6	2	1	4
163	206.35	209.40	3.05	3.10	102	3.10	102	15	4	6	2	3	3
163	209.40	212.45	3.05	3.00	98	3.00	98	15	4	6	3	3	2
163	212.45	215.49	3.04	3.08	101	3.08	101	15	4	6	2	1	1 slick joints, no rake
163	215.49	218.54	3.05	3.02	99	3.02	99	15	4	6	2	1	3
163	218.54	221.59	3.05	3.05	100	3.05	100	15	4	6	2	1	3
163	221.59	224.64	3.05	3.02	99	3.02	99	15	3	5	2	1	2 healed fractures, minor gouge
163	224.64	227.69	3.05	3.01	99	2.87	94	15	4	6	3	1	2 fractures close together
163	227.69	230.73	3.04	3.02	99	2.84	93	15	4	6	4	1	1 18 cm. of H=2, slick
163	230.73	233.78	3.05	2.94	96	2.94	96	15	3	5	3	3	2
163	233.78	236.83	3.05	3.10	102	3.02	99	15	3	5	4	1	1 8 cm. of H=2, weak slicks
163	236.83	239.88	3.05	3.05	100	3.04	100	15	4	6	4	1	1 slip plane, 1 cm. of H=2
163	239.88	242.93	3.05	2.89	95	2.89	95	15	4	6	3	1	3
163	242.93	245.97	3.04	3.02	99	2.57	85	15	3	5	12	1	1 45 cm. healed gouge, H=0,2
163	245.97	249.02	3.05	3.15	103	3.15	103	15	3	5	4	1	4 slick contact at 20 to c.a.
163	249.02	252.07	3.05	2.95	97	2.95	97	15	3	5	3	1	2 minor gouge on fractures; healed brxx
163	252.07	255.12	3.05	3.05	100	2.98	98	15	4	6	5	1	4 healed fractures; 7 cm. broken material
163	255.12	258.17	3.05	3.08	101	3.08	101	15	4	6	1	3	3
163	258.17	261.21	3.04	3.06	101	3.06	101	15	4	6	3	2	2 weak slicks
163	261.21	264.26	3.05	3.05	100	3.05	100	15	4	6	1	1	3
163	264.26	267.31	3.05	3.05	100	3.05	100	15	3	5	2	1	4
163	267.31	270.36	3.05	2.95	97	2.85	93	15	2	2	10	1	1 healed gouge, not many X-joints
163	270.36	273.41	3.05	3.08	101	2.98	98	15	2	2	8	1	1 healed gouge; few X-joints 45 to c.a.
163	273.41	276.45	3.04	2.95	97	2.95	97	15	3	5	2	3	2 gouge on fractures
163	276.45	279.50	3.05	3.05	100	3.05	100	15	3	5	3	1	3
163	279.50	282.55	3.05	3.05	100	3.05	100	15	3	6	2	1	3 slicks at 35 to c.a.
163	282.55	285.60	3.05	3.00	98	2.54	83	15	3	5	8	1	1 50% partially healed shearing
163	285.60	288.65	3.05	2.96	97	2.42	79	15	4	5	7	1	1 banded slick joints 25 to 55 to c.a.
163	288.65	291.69	3.04	2.82	93	2.82	93	15	3	6	2	3	1 very slick 30 to c.a.; 60 cm. H=3,2;redrill

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
163	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	4	2	2	10 cm. of H=3; healed fractures
163	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	1	3	3	
163	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	4	2	2	2 healed fractures; slick?
163	300.84	303.89	3.05	3.05	100	3.05	100	15	3	5	4	2	2	2 50% dyke, H=3; joints at 30-40 to c.a.
163	303.89	306.93	3.04	3.00	99	3.00	99	15	4	6	1	1	4	4 gypsum, not slick
163	306.93	309.98	3.05	3.04	100	3.04	100	15	4	6	1	3	4	4 gypsum, not slick
163	309.98	313.03	3.05	3.05	100	3.05	100	15	4	6	1	3	4	4 gypsum, not slick
163	313.03	316.08	3.05	3.00	98	3.00	98	15	3	5	4	2	1	1 healed fractures, some gouge at 25 to c.a.
163	316.08	319.13	3.05	3.08	101	2.83	93	15	4	6	6	1	2	2 60 cm. of H=2,3
163	319.13	322.17	3.04	2.96	97	2.89	95	15	4	5	4	3	2	2 gouge on fractures at 25 to c.a.
163	322.17	325.22	3.05	3.05	100	3.05	100	15	3	5	4	2	1	1 slick joints
163	325.22	328.27	3.05	2.92	96	2.84	93	15	3	5	4	3	2	2 40 to c.a. healed fractures; H=1
163	328.27	331.32	3.05	3.02	99	2.49	82	15	3	5	12	3	2	2 53 cm. of H=2,1; partially healed
163	331.32	334.37	3.05	3.08	101	2.76	90	15	3	5	8	3	3	3 17 cm. of H=1; weak fractures
163	334.37	337.41	3.04	2.92	96	2.88	95	15	4	5	3	1	2	
163	337.41	340.46	3.05	3.12	102	2.90	95	15	2	4	7	1	2	2 partially healed fault; H=0,1 15 to c.a.
163	340.46	343.51	3.05	3.00	98	2.87	94	14	2	4	10	1	1	1 69 cm. of H=1
163	343.51	345.95	2.44	0.99	41	0.82	34	13	3	5	16	1	2	2 tube mismatch; rubble and gouge, H=0,1
163	345.95	349.00	3.05	3.00	98	2.59	85	13	3	5	11	1	1	1 minor fault gouge
163	349.00	352.05	3.05	3.05	100	2.67	88	12	3	4	14	1	1	1 50% of H=4, slicks at 40 to c.a.
163	352.05	355.09	3.04	3.08	101	3.08	101	15	4	6	2	3	2	2 gouge on fractures
163	355.09	355.40	0.31	0.33	106	0.33	106	15	4	6	1	1	1	1 healed fractures, not very strong
163	355.40	358.44	3.04	2.98	98	2.98	98	15	4	6	2	1	1	1 healed fractures, not very strong
163	358.44	361.49	3.05	2.92	96	2.92	96	15	3	5	3	1	1	1 weak slicks
163	361.49	364.54	3.05	2.90	95	2.90	95	15	4	6	4	2	3	3 gouge filled fractures at 20 to c.a.
163	364.54	367.89	3.35	3.20	96	3.20	96	15	4	6	2	3	2	2 19 cm. gouge on fractures; slick?
163	367.89	370.94	3.05	3.28	108	3.28	108	15	4	6	1	3	3	
163	370.94	373.99	3.05	3.05	100	3.05	100	15	4	6	2	1	1	1 weak mineralized slick
163	373.99	377.04	3.05	3.05	100	3.05	100	15	4	6	2	1	2	2 possible slick
163	377.04	380.09	3.05	3.05	100	2.95	97	15	3	6	5	3	3	3 gouge on fractures at 15 to c.a.; not healed
163	380.09	383.13	3.04	2.97	98	2.97	98	15	4	6	2	3	3	
163	383.13	386.18	3.05	2.90	95	2.90	95	15	4	6	2	3	3	
163	386.18	389.23	3.05	3.10	102	3.10	102	15	4	6	3	3	4	
163	389.23	392.28	3.05	3.08	101	3.08	101	15	4	6	1	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
163	392.28	395.33	3.05	3.05	100	2.98	98	15	3	5	4	1	1	7 cm. of H=2,3; slick contact
163	395.33	398.37	3.04	3.12	103	3.12	103	15	3	6	3	1	3	well healed breccia
163	398.37	401.42	3.05	3.05	100	3.05	100	15	3	6	4	2	2	gypsum on fractures
163	401.42	404.47	3.05	3.05	100	3.05	100	15	4	6	1	1	3	mineralized fractures
163	404.47	407.52	3.05	2.97	97	3.05	100	15	4	6	4	2	1	weak slicks
163	407.52	410.57	3.05	3.05	100	3.05	100	15	4	6	4	1	1	gouge on fractures; slicks at 40 to c.a.
163	410.57	413.61	3.04	3.02	99	2.98	98	15	3	5	6	2	1	partially healed; 10 cm. of H=1
163	413.61	416.66	3.05	3.02	99	3.02	99	15	4	6	1	3	3	
163	416.66	419.71	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
163	419.71	422.76	3.05	3.05	100	3.05	100	15	4	6	3	2	1	1 slick joint at approx. 45 to c.a.
163	422.76	425.81	3.05	3.02	99	3.02	99	15	4	6	2	2	2	some healed breccia
163	425.81	428.85	3.04	3.12	103	3.12	103	15	4	6	2	1	3	gouge filled fractures
163	428.85	431.90	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gouge filled fractures
163	431.90	434.95	3.05	3.05	100	3.05	100	15	4	6	2	1	1	gypsum; slick
163	434.95	438.00	3.05	3.05	100	3.05	100	15	4	6	3	1	2	slightly slick
163	438.00	441.05	3.05	3.05	100	3.05	100	15	3	5	4	1	1	50 to c.a.
163	441.05	444.09	3.04	3.04	100	3.04	100	15	3	5	4	1	1	30 to c.a.
163	444.09	447.14	3.05	3.05	100	2.88	94	15	3	5	9	1	1	50 cm. of H=2; partially healed
163	447.14	450.19	3.05	3.20	105	3.20	105	15	4	6	2	1	2	slightly slick
163	450.19	453.24	3.05	3.05	100	3.05	100	15	3	6	3	1	1	weak slick
163	453.24	456.29	3.05	3.05	100	3.05	100	15	3	6	2	3	3	
163	456.29	459.33	3.04	3.04	100	3.04	100	15	4	6	2	1	3	
163	459.33	462.38	3.05	3.05	100	3.05	100	15	4	6	2	3	3	
163	462.38	465.43	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
163	465.43	468.48	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
163	468.48	471.53	3.05	3.05	100	3.05	100	15	4	6	2	3	2	2 slick undulated joints at ± 40 to c.a.
163	471.53	474.57	3.04	3.00	99	3.00	99	15	4	6	3	1	3	3 healed gouge with 50 to c.a. contact
163	474.57	477.62	3.05	3.05	100	2.65	87	15	3	6	9	1	1	40 cm. of H=2; healed gouge w/ 70 to
163	477.62	480.67	3.05	3.05	100	3.05	100	15	4	6	2	3	3	c.a. slicks
163	480.67	483.72	3.05	3.09	101	3.09	101	15	4	6	2	1	3	
163	483.72	486.77	3.05	3.08	101	3.08	101	15	4	6	3	1	3	
163	486.77	489.81	3.04	2.97	98	2.97	98	15	4	6	1	1	3	
163	489.81	492.86	3.05	3.02	99	3.02	99	15	4	6	2	1	3	
163	492.86	495.91	3.05	2.92	96	2.76	90	15	4	6	6	1	3	3 minor gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
164	6.10	8.23	2.13	1.40	66	0.22	10	5	3	4	37	1	3 15 cm. OVB; 7 cm. of H=0; redrill core	
164	8.23	11.28	3.05	2.29	75	0.44	14	5	3	4	35	1	3 broken core w/ minor gouge&mod. wthr	
164	11.28	14.33	3.05	2.15	70	0.26	9	5	3	4	50	1	3 broken core w/ minor gouge&mod. wthr	
164	14.33	17.37	3.04	1.46	48	0.00	0	5	3	4	50	1	3 broken core with minor gouge	
164	17.37	20.42	3.05	1.05	34	0.00	0	5	3	4	50	1	3 broken core with minor gouge	
164	20.42	23.47	3.05	1.87	61	0.17	6	5	3	4	50	1	3 broken core with minor gouge	
164	23.47	26.52	3.05	2.44	80	0.12	4	5	4	4	50	1	3 broken core	
164	26.52	27.74	1.22	1.05	86	0.00	0	5	3	5	50	1	3 broken core	
164	27.74	30.48	2.74	2.50	91	0.30	11	5	3	5	50	1	3 broken core	
164	30.48	32.61	2.13	0.36	17	0.00	0	5	3	5	25	1	3 broken core	
164	32.61	35.66	3.05	0.49	16	0.00	0	5	3	5	25	1	3 broken core	
164	35.66	38.71	3.05	2.97	97	0.44	14	5	3	5	25	1	3 broken core	
164	38.71	41.76	3.05	2.72	89	2.25	74	5	3	5	10	1	3 10% broken core	
164	41.76	44.81	3.05	3.05	100	3.05	100	15	3	5	2	1	3 gypsum on fractures	
164	44.81	47.86	3.05	2.99	98	2.71	89	15	3	5	3	1	3 gypsum on fractures	
164	47.86	50.90	3.04	2.97	98	2.62	86	15	3	5	3	1	3 gypsum on fractures	
164	50.90	53.95	3.05	3.05	100	2.96	97	15	3	5	2	1	3 gypsum on fractures; minor gouge	
164	53.95	57.00	3.05	3.05	100	2.88	94	15	3	5	4	1	3 gypsum on fractures; minor gouge	
164	57.00	60.05	3.05	3.11	102	2.76	90	15	3	5	5	1	3 gypsum on fractures	
164	60.05	63.10	3.05	3.00	98	3.00	98	15	3	5	3	1	3 gypsum on fractures	
164	63.10	66.14	3.04	3.04	100	2.86	94	15	3	5	4	1	3 gypsum on fractures	
164	66.14	69.19	3.05	3.00	98	2.15	70	14	3	5	7	1	3 minor gouge on fractures	
164	69.19	72.24	3.05	2.96	97	1.84	60	13	3	4	10	1	3 some broken core w/ gouge	
164	72.24	75.29	3.05	3.05	100	2.90	95	15	3	5	4	2	3	
164	75.29	78.33	3.04	2.96	97	2.96	97	15	3	5	3	1	3	
164	78.33	81.38	3.05	3.02	99	3.02	99	15	3	6	1	1	3	
164	81.38	84.43	3.05	3.01	99	1.48	49	13	2	6	11	1	3 fault zone	
164	84.43	87.48	3.05	3.05	100	1.45	48	13	2	6	14	1	3 fault zone up to 86.90 m.	
164	87.48	90.53	3.05	2.91	95	2.21	72	14	2	6	6	1	3 gouge on joints (dyke)	
164	90.53	93.57	3.04	3.07	101	3.00	99	15	3	6	2	1	3 gouge on joints	
164	93.57	96.62	3.05	2.95	97	1.74	57	9	3	6	20	1	3 15% broken core ± gouge on fractures	
164	96.62	99.67	3.05	2.87	94	2.21	72	12	3	6	16	1	3 minor gypsum on fractures	
164	99.67	102.72	3.05	3.05	100	3.05	100	15	3	6	2	1	3 minor gypsum on fractures/minor gouge	
164	102.72	105.77	3.05	2.92	96	2.92	96	15	3	6	3	2	3 minor gypsum on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
164	105.77	108.81	3.04	2.98	98	2.98	98	15	3	6	2	1	3 gypsum on fractures; 10 cm. broken core	
164	108.81	111.86	3.05	2.84	93	1.45	48	10	3	6	25	1	3 25% broken core w/ gouge on fractures	
164	111.86	114.91	3.05	3.11	102	3.11	102	15	3	6	4	1	3 gypsum on fractures	
164	114.91	117.96	3.05	3.05	100	3.05	100	15	3	6	4	1	3 gypsum on fractures	
164	117.96	121.01	3.05	3.00	98	2.68	88	15	3	6	3	1	3 gypsum on fractures	
164	121.01	124.06	3.05	3.09	101	2.98	98	15	3	6	4	1	3 gypsum on fractures	
164	124.06	127.10	3.04	2.99	98	2.99	98	15	3	6	4	1	3 gypsum on fractures	
164	127.10	130.15	3.05	3.08	101	3.00	98	15	3	6	3	1	3 gypsum on fractures	
164	130.15	133.20	3.05	3.09	101	3.09	101	15	3	6	2	1	3 gypsum on fractures	
164	133.20	136.25	3.05	2.96	97	2.96	97	15	3	6	2	1	3 gypsum on fractures	
164	136.25	139.29	3.04	3.07	101	2.81	92	15	3	6	4	1	3 gypsum on fractures	
164	139.29	142.34	3.05	3.11	102	2.88	94	15	3	6	3	1	3 gypsum on fractures	
164	142.34	145.39	3.05	2.78	91	2.78	91	15	3	6	1	1	3 gypsum on fractures	
164	145.39	148.44	3.05	3.07	101	3.07	101	15	3	6	2	1	3 gypsum on fractures	
164	148.44	151.49	3.05	3.05	100	3.05	100	15	3	6	1	1	3 gypsum on fractures	
164	151.49	154.53	3.04	3.34	110	3.30	109	15	3	6	5	1	3 gypsum on fractures	
164	154.53	157.58	3.05	2.99	98	2.99	98	15	3	6	4	1	3 gypsum on fractures	
164	157.58	160.63	3.05	3.00	98	2.87	94	15	3	6	3	1	3 gypsum on fractures	
164	160.63	163.68	3.05	2.89	95	2.45	80	15	3	6	8	1	3 gouge and gypsum on fractures	
164	163.68	166.73	3.05	2.95	97	2.51	82	15	3	6	4	1	3 gypsum on fractures; 50% dyke (H=4)	
164	166.73	169.77	3.04	3.05	100	3.05	100	15	3	6	2	1	3	
164	169.77	172.82	3.05	3.05	100	2.97	97	15	3	6	2	1	3	
164	172.82	175.87	3.05	2.86	94	2.67	88	15	3	6	4	1	3 minor gouge on fractures	
164	175.87	178.92	3.05	3.01	99	2.89	95	15	2	6	5	1	3	
164	178.92	181.97	3.05	3.08	101	3.08	101	15	3	6	1	1	3 gypsum on fractures	
164	181.97	185.01	3.04	3.04	100	3.04	100	15	3	6	2	1	3 gypsum on fractures	
164	185.01	188.06	3.05	3.05	100	3.05	100	15	3	6	1	1	3 gypsum on fractures	
164	188.06	191.11	3.05	3.07	101	3.07	101	15	3	6	1	1	3 gypsum on fractures	
164	191.11	194.16	3.05	2.97	97	2.74	90	14	3	6	5	1	3 gypsum on fractures	
164	194.16	197.21	3.05	3.09	101	2.89	95	15	3	6	6	1	3 three 2-4 cm. gouge zones at 45 to c.a.	
164	197.21	200.25	3.04	3.00	99	3.00	99	15	3	6	3	1	3 gypsum on fractures	
164	200.25	203.30	3.05	2.99	98	2.99	98	15	3	6	2	1	3 gypsum on fractures	
164	203.30	206.35	3.05	2.95	97	2.86	94	15	3	6	4	1	3 gypsum on fractures; 3 cm. fault zone	
164	206.35	209.40	3.05	3.06	100	3.06	100	15	3	6	2	1	3 gypsum on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
164	209.40	212.45	3.05	3.08	101	3.08	101	15	3	6	2	1	3 gypsum on fractures
164	212.45	215.49	3.04	3.06	101	3.06	101	15	3	6	1	1	3 gypsum on fractures
164	215.49	218.54	3.05	2.99	98	2.99	98	15	3	6	1	1	3 gypsum on fractures
164	218.54	221.59	3.05	3.09	101	3.09	101	15	3	6	2	1	3 gypsum on fractures
164	221.59	224.64	3.05	3.03	99	3.03	99	15	3	6	2	1	3 gypsum on fractures
164	224.64	227.69	3.05	3.08	101	3.08	101	15	3	6	4	1	3 gypsum on fractures
164	227.69	230.74	3.05	2.97	97	2.97	97	15	3	6	3	1	3 gypsum and minor gouge on fractures
164	230.74	233.78	3.04	3.09	102	3.09	102	15	3	6	3	1	3 gypsum and minor gouge on fractures
164	233.78	236.83	3.05	3.09	101	3.00	98	15	3	6	2	1	3 gypsum on fractures
164	236.83	239.88	3.05	2.94	96	3.03	99	15	3	6	4	1	3 gouge on fractures
164	239.88	242.93	3.05	3.09	101	3.09	101	15	3	6	4	3	3 gypsum on fractures
164	242.93	245.97	3.04	3.04	100	2.87	94	14	3	6	6	1	3 gypsum and minor gouge on fractures
164	245.97	249.02	3.05	2.96	97	2.88	94	15	3	6	3	1	3 gypsum on fractures
164	249.02	252.07	3.05	3.05	100	3.05	100	15	3	6	2	1	3 gypsum on fractures
164	252.07	255.12	3.05	2.99	98	2.96	97	15	3	6	2	1	3 gypsum on fractures
164	255.12	258.17	3.05	3.08	101	3.00	98	15	3	6	5	1	3 gypsum on fractures
164	258.17	261.21	3.04	2.86	94	2.86	94	15	3	6	1	1	3 gypsum on fractures
164	261.21	264.26	3.05	3.17	104	3.17	104	15	3	6	3	1	3 gypsum on fractures
164	264.26	267.31	3.05	3.05	100	3.05	100	15	3	6	2	1	3 gypsum on fractures
164	267.31	270.36	3.05	3.05	100	3.05	100	15	3	6	2	1	3 gypsum on fractures
164	270.36	273.41	3.05	2.97	97	2.97	97	15	3	6	1	1	3 gypsum on fractures
164	273.41	276.45	3.04	2.95	97	2.95	97	15	3	6	2	1	3 gypsum on fractures
164	276.45	279.50	3.05	3.11	102	3.11	102	15	3	6	1	1	3 gypsum on fractures (dyke)
164	279.50	282.55	3.05	3.02	99	3.02	99	15	3	6	3	1	3 gypsum on fractures
164	282.55	285.60	3.05	2.88	94	2.88	94	15	3	6	3	1	2 gypsum on fractures
164	285.60	288.65	3.05	2.97	97	2.97	97	15	3	6	3	1	3 gypsum on fractures
164	288.65	291.69	3.04	3.04	100	3.04	100	15	3	6	4	1	3 gypsum and minor gouge on fractures
164	291.69	294.74	3.05	2.90	95	2.90	95	15	3	6	1	1	3 gypsum on fractures
164	294.74	297.79	3.05	3.05	100	3.05	100	15	3	6	2	1	2 gypsum on fractures
164	297.79	300.84	3.05	3.30	108	3.05	100	15	3	6	3	1	2 gypsum on fractures
164	300.84	303.89	3.05	3.05	100	2.63	86	15	3	6	6	1	3 gypsum on fractures
164	303.89	306.93	3.04	3.04	100	3.04	100	15	3	6	3	1	3 gypsum on fractures
164	306.93	309.98	3.05	2.99	98	2.99	98	15	3	6	1	1	3 gypsum on fractures
164	309.98	313.03	3.05	2.91	95	2.91	95	15	3	6	2	1	3 gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
164	313.03	316.08	3.05	3.01	99	3.01	99	15	3	6	1	1	3	gypsum on fractures
164	316.08	319.13	3.05	3.05	100	3.05	100	15	3	6				gypsum on fractures
164	319.13	322.17	3.04	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
164	322.17	325.22	3.05	2.96	97	2.90	95	15	3	6	4	1	3	gypsum and minor gouge on fractures
164	325.22	328.27	3.05	3.00	98	2.56	84	14	3	6	7	1	3	gypsum/gouge on fractures; 10% broken
164	328.27	329.79	1.52	1.21	80	1.21	80	15	3	6	3	1	3	
165	12.19	14.33	2.14	0.31	14	0.00	0	2	4	4	20	5	3	broken core with gouge
165	14.33	17.37	3.04	1.74	57	0.15	5	2	4	4	50	5	3	broken core with gouge
165	17.37	20.42	3.05	2.85	93	1.93	63	11	4	5	20	1	3	broken core with gouge
165	20.42	23.47	3.05	2.63	86	1.54	50	10	3	6	25	1	3	broken core with gouge
165	23.47	26.52	3.05	0.48	16	0.00	0	10	3	6	25	1	3	broken core with gouge
165	26.52	29.57	3.05	2.43	80	1.02	33	10	4	6	25	1	3	broken core with gouge
165	29.57	32.61	3.04	3.18	105	1.88	62	12	4	6	17	1	3	broken core with gouge
165	32.61	35.66	3.05	2.45	80	1.31	43	10	4	6	25	1	3	broken core with gouge
165	35.66	38.71	3.05	2.25	74	0.55	18	10	4	6	25	1	3	broken core with gouge
165	38.71	41.76	3.05	3.02	99	1.33	44	13	4	6	14	1	3	broken core with gouge
165	41.76	44.81	3.05	2.94	96	2.87	94	15	4	6	4	1	3	
165	44.81	47.85	3.04	3.35	110	1.44	47	12	4	6	20	1	3	broken core with gouge
165	47.85	50.90	3.05	2.85	93	2.23	73	14	4	6	5	1	3	10% broken core; gouge on fractures
165	50.90	53.95	3.05	3.05	100	2.57	84	14	4	6	6	1	3	gouge on fractures
165	53.95	57.00	3.05	3.03	99	2.32	76	14	4	6	8	1	3	
165	57.00	60.05	3.05	3.10	102	2.87	94	15	4	6	4	1	3	minor gouge on fractures
165	60.05	63.09	3.04	2.99	98	2.99	98	15	4	6	2	1	3	
165	63.09	66.14	3.05	3.05	100	3.11	102	15	4	6	4	1	3	
165	66.14	69.19	3.05	3.13	103	3.00	98	15	4	6	2	1	3	
165	69.19	72.24	3.05	2.85	93	2.67	88	15	4	6	4	1	3	minor gouge on fractures
165	72.24	75.29	3.05	3.05	100	3.05	100	15	3	6	3	1	3	minor gouge on fractures
165	75.29	78.33	3.04	2.75	90	2.58	85	15	3	6	4	1	3	minor gouge on fractures
165	78.33	81.38	3.05	3.15	103	2.78	91	15	4	6	5	1	3	
165	81.38	84.43	3.05	3.01	99	2.89	95	15	4	6	3	1	3	
165	84.43	87.48	3.05	3.03	99	2.96	97	14	3	6	6	1	3	
165	87.48	90.53	3.05	3.05	100	2.67	88	15	4	6	3	1	3	gouge on fractures
165	90.53	92.66	2.13	2.13	100	2.00	94	15	4	6	5	1	3	
165	92.66	92.96	0.30	0.15	50	0.00	0	1	4	6	25	5	3	broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
165	92.96	95.71	2.75	2.75	100	2.60	95	10	4	6	25	1	2	10% broken core
165	95.71	96.62	0.91	0.81	89	0.59	65	9	4	6	9	1	3	
165	96.62	99.67	3.05	3.05	100	2.03	67	15	3	6	4	1	3	
165	99.67	102.72	3.05	3.07	101	3.00	98	15	4	6	1	1	3	
165	102.72	105.77	3.05	3.12	102	1.99	65	12	4	6	20	1	3	15% broken core
165	105.77	108.81	3.04	3.04	100	1.18	39	10	4	6	30	1	3	70% broken core
165	108.81	111.86	3.05	3.01	99	2.11	69	12	4	6	20	1	3	10% broken core w/ minor gouge
165	111.86	114.91	3.05	3.05	100	2.93	96	15	4	6	3	1	3	
165	114.91	117.96	3.05	2.91	95	2.91	95	15	4	6	4	1	3	
165	117.96	121.01	3.05	3.05	100	2.51	82	14	4	6	6	1	3	
165	121.01	124.05	3.04	3.04	100	2.39	79	13	4	6	12	1	3	5% broken core
165	124.05	127.10	3.05	3.07	101	2.87	94	15	4	6	4	1	3	
165	127.10	130.15	3.05	3.05	100	2.55	84	15	4	6	3	1	3	
165	130.15	133.20	3.05	2.92	96	2.97	97	15	4	6	2	1	3	
165	133.20	136.25	3.05	3.10	102	2.77	91	13	4	6	11	1	3	
165	136.25	139.29	3.04	3.02	99	2.99	98	15	4	6	3	1	3	
165	139.29	142.34	3.05	3.02	99	3.02	99	15	4	6	2	1	3	
165	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
165	145.39	148.44	3.05	3.05	100	2.90	95	15	4	6	3	1	3	4 cm. fault gouge at 147.6 m. at 55 to c.a.
165	148.44	151.49	3.05	3.04	100	3.04	100	15	4	6	3	1	3	
165	151.49	154.53	3.04	3.05	100	3.05	100	15	4	6	2	1	3	
165	154.53	157.58	3.05	3.05	100	3.00	98	15	4	6	4	1	3	gypsum on fractures
165	157.58	160.63	3.05	3.05	100	2.89	95	15	4	6	4	1	3	gypsum on fractures
165	160.63	163.68	3.05	3.05	100	3.00	98	15	4	6	5	1	3	gypsum on fractures
165	163.68	166.73	3.05	3.12	102	2.69	88	15	4	6	4	1	3	gypsum on fractures
165	166.73	169.77	3.04	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
165	169.77	172.82	3.05	3.05	100	3.00	98	15	3	6	3	1	3	gypsum on fractures
165	172.82	175.87	3.05	2.99	98	2.99	98	15	4	6	2	1	3	gypsum on fractures
165	175.87	178.92	3.05	3.05	100	2.79	91	15	4	6	4	1	3	gypsum on fractures; healed gouge
165	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	2	1	3	gypsum on fractures
165	181.97	185.01	3.04	3.04	100	2.94	97	15	4	6	2	1	3	gypsum on fractures
165	185.01	188.06	3.05	3.05	100	3.05	100	15	4	6	1	1	3	gypsum on fractures
165	188.06	191.11	3.05	3.05	100	3.00	98	15	4	6	3	1	3	gypsum on fractures
165	191.11	194.16	3.05	3.00	98	3.00	98	15	4	6	3	1	3	gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
165	194.16	197.21	3.05	3.01	99	3.01	99	15	4	6	2	1	3 gypsum on fractures	
165	197.21	200.25	3.04	3.07	101	3.07	101	15	4	6	2	1	3 gypsum on fractures	
165	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	1	1	3 gypsum on fractures	
165	203.30	206.35	3.05	3.03	99	2.92	96	15	4	6	5	1	3 gypsum on fractures	
165	206.35	209.40	3.05	3.05	100	2.67	88	15	4	6	4	1	3 gypsum on fractures	
165	209.40	212.45	3.05	3.05	100	2.90	95	15	4	6	2	1	3 15 cm. zone of gouge H=1/2	
165	212.45	215.49	3.04	3.04	100	2.93	96	15	4	6	2	1	3 gypsum on fractures	
165	215.49	218.54	3.05	3.05	100	2.27	74	13	4	6	12	1	3 gypsum on fractures; 5% broken core	
165	218.54	221.59	3.05	3.05	100	2.95	97	15	4	6	3	1	3 gypsum on fractures	
165	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6	4	1	3 gypsum on fractures	
165	224.64	227.69	3.05	3.03	99	3.03	99	15	4	6	1	1	3 gypsum on fractures	
165	227.69	230.73	3.04	3.00	99	3.00	99	15	4	6	1	1	3 gypsum on fractures	
165	230.73	233.78	3.05	3.05	100	3.05	100	15	4	6	1	1	3 gypsum on fractures	
165	233.78	236.83	3.05	3.05	100	3.05	100	15	4	6	2	1	3 gypsum on fractures	
165	236.83	239.88	3.05	3.05	100	2.92	96	15	4	6	3	1	3 gypsum on fractures	
165	239.88	242.93	3.05	3.12	102	2.99	98	15	4	6	5	1	3 gypsum on fractures	
165	242.93	245.97	3.04	3.00	99	2.60	86	13	4	6	15	5	3 gypsum on fractures	
165	245.97	249.02	3.05	3.07	101	3.07	101	15	4	6	3	1	2	
165	249.02	252.07	3.05	3.05	100	2.94	96	15	4	6	4	1	3 249.58 m. - 3-4 cm. gouge section	
165	252.07	255.12	3.05	2.92	96	2.73	90	14	4	6	6	1	3 gypsum on fractures & minor gouge	
165	255.12	258.17	3.05	3.11	102	2.99	98	15	4	6	3	1	3 gypsum on fractures & minor gouge	
165	258.17	261.21	3.04	2.98	98	2.76	91	15	4	6	3	1	3 gypsum on fractures & minor gouge	
165	261.21	264.26	3.05	3.28	108	3.28	108	15	4	6	4	1	3 gypsum on fractures & minor gouge	
165	264.26	267.31	3.05	2.94	96	2.94	96	15	4	6	3	1	3 gypsum on fractures & minor gouge	
165	267.31	270.36	3.05	3.05	100	2.86	94	15	4	6	4	1	3 gypsum on fractures & minor gouge	
165	270.36	273.41	3.05	3.00	98	2.77	91	15	4	6	2	1	3 gypsum on fractures & minor gouge	
165	273.41	276.45	3.04	3.08	101	2.64	87	14	4	6	7	1	3 30 cm. fault gouge at 276.0 m.; gypsum	
165	276.45	279.50	3.05	3.02	99	2.20	72	14	4	6	8	1	3 1.28 m. of H=1/2 (healed shear zone)	
165	279.50	282.55	3.05	3.14	103	2.13	70	13	4	6	14	1	3 0.8 m. of H=1/2 (healed shear zone)	
165	282.55	285.60	3.05	2.96	97	2.60	85	14	4	6	8	1	3 0.2 m. of H=1/2 (healed shear zone)	
165	285.60	288.65	3.05	3.05	100	2.51	82	15	4	6	5	1	3 gouge on fractures	
165	288.65	291.69	3.04	3.11	102	3.00	99	15	4	6	3	1	3 gouge on fractures	
165	291.69	294.74	3.05	3.08	101	2.67	88	15	4	6	4	1	3 0.35 m. of H=1/2 (healed shear zone)	
165	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
165	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
165	300.84	303.89	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
165	303.89	306.93	3.04	3.07	101	3.00	99	15	4	6	3	1	3	
165	306.93	309.98	3.05	2.99	98	2.99	98	15	4	6	2	1	3	
165	309.98	313.02	3.04	2.96	97	2.96	97	15	4	6	1	1	3	
165	313.02	316.08	3.06	3.08	101	3.08	101	15	4	6	2	1	3	
165	316.08	319.13	3.05	3.05	100	3.00	98	15	4	6	2	1	3	3 minor gouge on fractures
165	319.13	322.17	3.04	3.05	100	2.94	97	15	4	6	3	1	3	3 dyke
165	322.17	325.22	3.05	3.02	99	3.02	99	15	4	6	2	1	3	3 dyke
165	325.22	328.27	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3 gypsum on fractures
165	328.27	331.32	3.05	3.05	100	3.08	101	15	4	6	1	1	3	3 gypsum on fractures
165	331.32	334.37	3.05	3.08	101	2.79	91	15	4	6	3	1	3	3 minor gouge on fractures
165	334.37	337.41	3.04	3.09	102	3.09	102	15	4	6	2	1	3	3 minor gouge on fractures
165	337.41	340.46	3.05	2.72	89	2.17	71	15	4	6	4	1	3	3 minor gouge on fractures
165	340.46	343.51	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3 minor gouge on fractures
166	1.22	4.87	3.65	1.94	53	0.17	5	12	3	4	22	1	3	3 casing at 8 ft, manual breaks
166	4.87	7.62	2.75	1.19	43	0.93	34	15	3	4	3	1	3	
166	7.62	9.60	1.98	1.82	92	1.53	77	15	3	4	6	1	4	
166	9.60	11.28	1.68	1.43	85	0.78	46	13	3	4	14	1	4	
166	11.28	12.80	1.52	1.47	97	0.00	0	4	3	3	50	1	4	4 broken core, moderately weathered
166	12.80	13.72	0.92	0.35	38	0.00	0	4	3	3	50	1	4	4 broken core
166	13.72	14.63	0.91	0.86	95	0.00	0	7	3	3	50	1	4	4 broken core
166	14.63	16.76	2.13	1.47	69	0.44	21	5	3	3	30	2	4	4 broken core
166	16.76	17.68	0.92	0.86	93	0.00	0	2	3	3	30	2	4	4 broken core
166	17.68	19.51	1.83	1.62	89	1.11	61	14	3	3	20	1	3	3 broken core
166	19.51	22.71	3.20	3.09	97	2.18	68	13	3	3	16	3	4	4 gouge on fractures
166	22.71	25.00	2.29	2.35	103	1.24	54	13	3	4	13	3	4	
166	25.00	26.52	1.52	1.27	84	0.58	38	11	3	4	15	3	4	
166	26.52	28.65	2.13	2.10	99	1.63	77	14	3	4	10	3	4	4 5cm zone of H=2 at 29.75m
166	28.65	30.48	1.83	1.53	84	0.62	34	10	3	4	20	1	4	4 broken core
166	30.48	31.70	1.22	1.17	96	0.35	29	11	2	3	20	1	4	4 broken core
166	31.70	34.29	2.59	2.22	86	1.02	39	13	3	3	20	1	3	3 broken core
166	34.29	35.66	1.37	1.30	95	0.38	28	9	2	3	20	1	3	3 broken core
166	35.66	36.89	1.23	0.93	76	0.74	60	14	3	4	11	1	3	3 broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
166	36.89	37.49	0.60	0.47	78	0.00	0	11	3	4	15	1	3	3 broken core
166	37.49	38.71	1.22	1.17	96	0.85	70	13	3	4	18	1	4	4 broken core
166	38.71	39.93	1.22	1.01	83	0.72	59	13	3	4	12	1	4	4
166	39.93	41.45	1.52	1.49	98	0.83	55	12	4	5	7	1	4	4
166	41.45	44.50	3.05	2.81	92	2.50	82	15	4	5	5	1	4	4 minor gouge on fractures
166	44.50	47.55	3.05	2.85	93	2.80	92	15	3	5	4	1	4	4 rough fractures, tourmaline
166	47.55	49.99	2.44	2.13	87	0.62	25	14	3	3	20	5	3	3 rough fractures
166	49.99	52.73	2.74	2.45	89	1.15	42	14	4	3	20	5	3	3 65% broken core
166	52.73	53.95	1.22	1.16	95	0.48	39	15	4	5	9	1	3	3
166	53.95	57.00	3.05	3.05	100	2.03	67	15	4	4	5	1	3	3 15cm of H=2 (fault gouge)
166	57.00	60.05	3.05	2.93	96	2.04	67	14	4	4	10	1	3	3
166	60.05	63.09	3.04	3.08	101	2.49	82	14	4	5	12	1	3	3
166	63.09	66.14	3.05	2.86	94	2.51	82	15	4	5	6	1	3	3 minor gouge on fractures
166	66.14	69.19	3.05	2.91	95	2.05	67	15	4	5	7	1	3	3 minor gouge & gypsum on fractures
166	69.19	72.24	3.05	2.97	97	2.97	97	15	4	5	4	1	3	3 minor gouge on fractures
166	72.24	75.29	3.05	3.08	101	2.97	97	15	4	5	5	1	3	3 10cm healed gouge at 73.67m
166	75.29	78.33	3.04	2.98	98	2.98	98	15	4	5	2	1	3	3
166	78.33	81.38	3.05	2.95	97	2.95	97	15	4	5	2	1	2	2
166	81.38	84.43	3.05	2.99	98	2.65	87	15	4	5	4	1	2	2 8cm fault gouge H=2 at 83.8m
166	84.43	87.48	3.05	3.08	101	3.08	101	15	4	5	2	1	2	2
166	87.48	90.53	3.05	3.05	100	3.05	100	15	4	5	4	1	3	3 gypsum on fractures
166	90.53	93.57	3.04	3.02	99	2.55	84	15	4	5	4	5	3	3 0.93m healed gouge(H=2) at 92.62m
166	93.57	96.62	3.05	2.84	93	2.22	73	15	4	5	3	1	3	3 0.29m healed gouge H=2 at 93.57m
166	96.62	99.67	3.05	3.05	100	3.05	100	15	4	5	6	1	3	3
166	99.67	102.72	3.05	3.07	101	3.07	101	15	4	5	2	1	2	2
166	102.72	105.77	3.05	3.05	100	3.05	100	15	4	5	4	1	2	2
166	105.77	108.81	3.04	3.07	101	3.07	101	15	4	5	1	1	3	3
166	108.81	111.86	3.05	2.96	97	2.87	94	15	4	5	3	1	3	3 5cm fault gouge at 110.33m
166	111.86	114.91	3.05	2.93	96	2.67	88	15	4	5	5	1	3	3
166	114.91	117.96	3.05	2.97	97	2.97	97	15	4	5	3	1	3	3 gypsum on fractures
166	117.96	121.01	3.05	2.99	98	2.37	78	15	4	5	9	1	3	3 5% broken core
166	121.01	124.05	3.04	2.95	97	2.90	95	15	4	5	3	3	2	2 at 122.78m 2cm fault gouge at 60 to c.a.
166	124.05	127.10	3.05	2.70	89	2.70	89	15	4	6	2	3	4	4
166	127.10	130.15	3.05	3.12	102	3.12	102	15	4	6	2	1	2	2 gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
166	130.15	133.20	3.05	3.10	102	3.10	102	15	4	6	1	3	3	
166	133.20	136.25	3.05	3.04	100	3.04	100	15	4	6	1	1	1	1 weak slick at 40 to c.a.
166	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6	1	3	3	
166	139.29	142.34	3.05	2.92	96	2.72	89	13	3	6	8	3	3	2 60cm healed breccia gouge on fracture
166	142.34	145.39	3.05	2.95	97	2.95	97	15	3	5	1	1	3	
166	145.39	148.44	3.05	3.10	102	3.10	102	15	3	5	3	1	1	2 minor gouge on slicks
166	148.44	151.49	3.05	2.60	85	2.10	69	8	3	5	27	1	1	1 50cm H=1 weak slicks
166	151.49	154.53	3.04	3.12	103	2.42	80	7	3	5	40	1	1	1 70cm H=1 weak slicks
166	154.53	157.58	3.05	3.10	102	2.83	93	15	3	5	4	1	3	3 27cm H=2
166	157.58	160.63	3.05	3.00	98	3.00	98	15	3	5	3	1	1	
166	160.63	163.68	3.05	3.00	98	2.90	95	15	3	5	3	1	2	
166	163.68	166.73	3.05	3.05	100	3.05	100	15	3	5	3	1	1	1 slick at 20 to c.a.
166	166.73	169.77	3.04	3.05	100	3.05	100	15	3	5	4	1	1	1 minor gouge on slick joints
166	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	4	2	1	
166	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6	2	3	3	
166	175.87	178.92	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
166	178.92	181.97	3.05	3.01	99	3.01	99	15	4	6	4	1	1	1 powdered & polished, no rake
166	181.97	185.01	3.04	3.05	100	3.05	100	15	4	6	2	1	3	
166	185.01	188.06	3.05	3.08	101	3.08	101	15	3	5	5	3	3	3 healed fault ?
166	188.06	191.11	3.05	2.94	96	2.74	90	13	3	5	8	1	1	2 healed fault ?
166	191.11	194.16	3.05	2.92	96	2.68	88	13	3	5	10	2	1	1 healed fault ?
166	194.16	197.21	3.05	3.05	100	3.05	100	14	2	5	7	1	1	1 partially healed fault
166	197.21	200.25	3.04	3.00	99	3.00	99	15	4	6	3	1	3	
166	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
166	203.30	206.35	3.05	3.05	100	3.00	98	15	4	6	4	3	2	2 start of partially healed mat'l 10 to c.a.
166	206.35	209.40	3.05	2.98	98	2.90	95	15	2	5	9	1	1	
166	209.40	211.23	1.83	1.87	102	1.80	98	15	3	5	4	1	2	2 gouge on fractures
166	211.23	212.95	1.72	1.04	60	1.04	60	15	3	5	2	1	3	
166	212.95	215.49	2.54	3.00	118	2.92	115	15	3	5	6	1	2	2 slightly slick joints
166	215.49	218.54	3.05	3.10	102	2.85	93	15	4	6	6	3	4	
166	218.54	221.59	3.05	2.75	90	2.48	81	13	3	5	12	3	4	4 minor gouge, partially healed fault
166	221.59	224.03	2.44	2.38	98	1.63	67	14	3	5	7	3	4	4 minor gouge, partially healed fault
166	224.03	227.08	3.05	2.97	97	2.74	90	15	3	5	8	3	3	
166	227.08	230.12	3.04	2.76	91	2.53	83	15	4	6	4	1	4	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
166	230.12	230.73	0.61	0.61	100	0.61	100	15	4	6	1	1	2	3cm gouge, H=1
166	230.73	233.78	3.05	3.05	100	3.05	100	15	4	6	4	1	2	
166	233.78	236.83	3.05	3.00	98	2.86	94	15	3	5	6	1	2	
166	236.83	239.88	3.05	3.00	98	3.00	98	15	4	6	4	1	1	
166	239.88	242.93	3.05	3.05	100	3.05	100	15	4	6	4	1	2	gouge filled fractures
166	242.93	245.97	3.04	3.05	100	3.02	99	13	3	5	8	1	2	50% partially healed mat'l
166	245.97	249.02	3.05	3.10	102	3.10	102	15	3	5	3	1	3	dike
166	249.02	252.07	3.05	3.08	101	3.08	101	15	3	5	6	3	2	20% healed fault
166	252.07	255.12	3.05	3.02	99	3.02	99	15	4	6	4	1	3	
166	255.12	258.17	3.05	3.00	98	2.70	89	14	3	5	7	1	1	10% partially healed mat'l H=2
166	258.17	261.21	3.04	3.02	99	2.94	97	15	3	5	4	1	1	core tube pulled
166	261.21	264.26	3.05	3.05	100	2.96	97	15	3	5	3	1	2	5% partially healed mat'l H=2
166	264.26	267.31	3.05	3.05	100	3.05	100	15	4	6	1	1	4	
166	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	3	3	2	minor gouge
166	270.36	273.41	3.05	2.90	95	2.86	94	15	3	5	5	3	2	4cm H=1, brecciated & partially healed
166	273.41	276.45	3.04	3.02	99	3.02	99	15	4	6	2	3	2	
166	276.45	279.50	3.05	3.04	100	3.04	100	15	4	6	1	3	4	
166	279.50	282.55	3.05	3.05	100	3.05	100	15	4	6	3	1	4	
166	282.55	285.60	3.05	2.99	98	2.99	98	15	4	6	2	1	4	
166	285.60	288.65	3.05	3.08	101	3.08	101	15	4	6	1	3	4	
166	288.65	291.69	3.04	3.00	99	3.00	99	15	4	6	1	1	4	
166	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	1	3	4	
166	294.74	297.79	3.05	2.90	95	2.90	95	15	4	6	1	3	3	
166	297.79	300.84	3.05	2.92	96	2.92	96	15	4	6	2	1	3	redrilled core
166	300.84	303.89	3.05	3.15	103	3.15	103	15	4	6	2	3	3	
166	303.89	306.93	3.04	3.13	103	3.13	103	15	4	6	1	3	3	
166	306.93	309.98	3.05	3.00	98	2.93	96	15	3	6	3	1	1	1.50m healed fault H=2/3, slick cts
166	309.98	313.03	3.05	3.10	102	3.10	102	15	4	6	1	1	4	
166	313.03	316.08	3.05	3.03	99	3.03	99	15	4	6	1	1	4	
166	316.08	319.13	3.05	3.05	100	3.05	100	15	3	5	5	3	2	healed fault mat'l
166	319.13	322.17	3.04	2.90	95	2.90	95	15	4	6	1	2	3	
166	322.17	325.22	3.05	2.95	97	2.95	97	15	4	6	3	3	3	
166	325.22	328.27	3.05	2.95	97	2.95	97	15	4	6	2	1	1	gouge on fractures, slick 20 to c.a.
166	328.27	331.32	3.05	3.00	98	3.00	98	15	4	6	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
166	331.32	334.37	3.05	3.10	102	3.10	102	15	4	6	3	1	4	
166	334.37	337.41	3.04	3.07	101	3.07	101	15	4	6	3	1	1	1 minor slicks
166	337.41	340.46	3.05	3.00	98	3.00	98	15	3	6	3	1	4	
166	340.46	343.51	3.05	3.10	102	3.10	102	15	4	6	3	3	3	
166	343.51	346.56	3.05	2.98	98	2.98	98	15	4	6	5	3	3	3 gypsum, 60cm H=3
166	346.56	349.61	3.05	3.05	100	2.65	87	15	3	5	8	3	2	2 gypsum on slick fractures/healed gouge
166	349.61	352.65	3.04	3.00	99	3.00	99	15	4	6	5	1	1	1 weak slicks, gouge present
166	352.65	355.70	3.05	2.75	90	1.58	52	11	3	5	18	1	2	2 weak slicks, 40% gouge
166	355.70	358.75	3.05	3.00	98	3.00	98	15	4	5	3	1	4	
166	358.75	361.80	3.05	2.82	92	2.82	92	15	4	6	2	1	2	
166	361.80	364.85	3.05	3.02	99	3.02	99	15	4	6	3	1	4	
166	364.85	367.89	3.04	2.60	86	2.40	79	15	3	5	8	1	1	1 20cm H=0, slick 40 to c.a.
166	367.89	370.94	3.05	3.02	99	2.62	86	13	3	5	12	1	1	1 slick 30 to c.a. (40cm H=2)
166	370.94	373.99	3.05	3.08	101	3.08	101	15	3	6	5	1	1	1 very slick joint, no rake 15 to c.a.
166	373.99	377.04	3.05	3.10	102	2.83	93	15	3	6	5	1	1	1 slick 45 to c.a.,no rake,27cm clay H=0
166	377.04	380.09	3.05	3.02	99	3.02	99	15	4	6	3	1	3	
166	380.09	383.13	3.04	3.01	99	3.01	99	15	4	6	3	1	3	
166	383.13	386.18	3.05	3.07	101	2.25	74	12	3	5	9	1	1	1 30% partially healed H=0,2
166	386.18	389.23	3.05	3.01	99	3.00	98	15	4	6	4	1	2	2 1cm gouge H=0
166	389.23	392.28	3.05	2.93	96	2.93	96	15	4	6	1	1	4	
166	392.28	395.33	3.05	3.10	102	3.10	102	15	4	6	1	1	4	4 5cm redrilled core
166	395.33	398.37	3.04	3.05	100	3.05	100	15	4	6	0			
166	398.37	401.42	3.05	3.00	98	3.00	98	15	4	6	0			
166	401.42	404.47	3.05	2.98	98	2.98	98	15	4	6	0			
166	404.47	407.52	3.05	2.86	94	2.64	87	15	3	5	6	3	3	3 22cm gouge H=2
166	407.52	410.57	3.05	3.08	101	3.08	101	15	4	6	1	1	3	
166	410.57	413.61	3.04	3.06	101	3.06	101	15	4	6	0			
166	413.61	416.66	3.05	3.10	102	3.10	102	15	4	6	3	1	3	
166	416.66	419.71	3.05	2.93	96	2.93	96	15	4	6	1	3	3	
166	419.71	422.76	3.05	3.05	100	3.05	100	15	4	6	1	1	4	
166	422.76	425.81	3.05	3.05	100	3.05	100	15	4	6	0			
166	425.81	428.85	3.04	3.05	100	3.05	100	15	4	6	0			
166	428.85	431.90	3.05	3.03	99	3.03	99	15	4	6	2	1	4	4 at 428.85m 6cm redrilled core
166	431.90	434.95	3.05	3.03	99	3.03	99	15	4	6	0			

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
166	434.95	438.00	3.05	2.98	98	2.98	98	15	4	6	1	1	3	at 437.68m 6cm broken mat'l
166	438.00	440.44	2.44	2.00	82	1.35	55	7	4	5	30	1	4	15% broken core with gouge
166	440.44	442.87	2.43	2.36	97	1.14	47	8	4	6	30	1	3	15% broken core with gouge
166	442.87	445.62	2.75	2.58	94	1.33	48	9	4	6	30	1	3	50% broken core with gouge
166	445.62	447.14	1.52	1.57	103	1.23	81	15	4	6	2	1	4	
166	447.14	450.19	3.05	2.97	97	2.84	93	15	4	6	5	1	1	slick 30 to c.a.
166	450.19	453.24	3.05	3.02	99	3.02	99	15	4	6	1	1	3	
166	453.24	456.29	3.05	3.03	99	2.84	93	15	4	6	3	1	4	
166	456.29	459.33	3.04	3.01	99	3.01	99	15	4	6	3	3	4	cross joint undulating at 5% slope
166	459.33	462.38	3.05	3.00	98	3.00	98	15	4	6	1	1	4	
166	462.38	465.43	3.05	3.03	99	3.03	99	15	4	6	3	1	4	
166	465.43	468.48	3.05	2.97	97	2.97	97	15	4	6	1	1	3	
166	468.48	471.53	3.05	2.75	90	2.66	87	15	4	6	3	1	3	
166	471.53	474.57	3.04	3.05	100	3.05	100	15	4	6	1	1	3	
166	474.57	477.62	3.05	2.92	96	2.40	79	15	4	6	2	1	4	
166	477.62	480.67	3.05	2.90	95	2.49	82	15	4	6	4	1	4	
166	480.67	483.72	3.05	3.00	98	3.00	98	15	4	6	0			
166	483.72	486.77	3.05	2.88	94	2.88	94	15	4	6	2	1	3	
166	486.77	489.81	3.04	2.99	98	2.90	95	15	4	6	4	1	3	1m fracture perpendicular to c.a.
166	489.81	492.86	3.05	3.07	101	3.07	101	15	4	6	0			
166	492.86	495.91	3.05	2.88	94	2.88	94	15	4	6	2	1	3	
166	495.91	498.96	3.05	3.30	108	3.30	108	15	4	6	0			first 10cm redrilled core
166	498.96	502.01	3.05	2.52	83	2.52	83	15	4	6	0			
166	502.01	505.05	3.04	2.98	98	2.98	98	15	4	6	1	1	3	
166	505.05	508.10	3.05	3.00	98	3.00	98	15	4	6	0			
166	508.10	511.15	3.05	3.01	99	3.01	99	15	5	6	0			
166	511.15	514.20	3.05	3.04	100	3.04	100	15	5	6	0			
167	3.05	5.18	2.13	1.79	84	1.30	61	12	3	3	10	1	3	Gouge and mod. weathered on joints
167	5.18	8.23	3.05	2.44	80	1.15	38	9	3	3	30	5	3	40% broken core with gouge
167	8.23	11.28	3.05	2.86	94	0.92	30	9	3	3	20	5	3	15% broken core with gouge
167	11.28	14.33	3.05	2.94	96	2.52	83	11	3	5	15	5	3	15% broken core with gouge
167	14.33	17.37	3.04	2.89	95	2.25	74	10	3	5	25	5	3	0.65 m. broken core w/ gouge at 16.55 m.
167	17.37	20.42	3.05	2.93	96	1.10	36	10	3	5	25	5	3	10% broken core with gouge
167	20.42	23.47	3.05	2.92	96	2.29	75	12	3	5	17	5	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
167	23.47	26.52	3.05	2.19	72	1.32	43	10	3	5	20	5	3	3 first 0.5 m. broken core with gouge
167	26.52	29.57	3.05	3.32	109	2.27	74	10	3	5	22	1	3	3 1.23 m. of H=2; gouge on fractures
167	29.57	32.61	3.04	3.02	99	2.64	87	15	3	5	5	1	3	3 gouge on fractures
167	32.61	35.66	3.05	2.91	95	2.23	73	14	3	5	6	1	3	3 gouge on fractures
167	35.66	38.71	3.05	2.28	75	2.07	68	13	3	5	10	1	3	3 10cm section of gouge at 38.04m
167	38.71	41.76	3.05	2.99	98	2.17	71	12	3	5	16	1	3	3 0.40m of H=2 (gouge) at 40.90m
167	41.76	44.81	3.05	2.95	97	2.35	77	14	3	5	7	1	3	3 minor gouge on fractures
167	44.81	47.85	3.04	2.97	98	2.59	85	14	3	5	5	1	3	3 minor gouge on fractures
167	47.85	50.90	3.05	2.93	96	2.87	94	15	3	5	4	1	3	3
167	50.90	53.95	3.05	3.09	101	2.54	83	14	3	5	6	1	3	3 2cm gouge at 52.50m at 40 to c.a.
167	53.95	57.00	3.05	2.88	94	2.12	70	14	3	5	9	1	3	3 gouge on fractures
167	57.00	60.05	3.05	3.03	99	2.66	87	15	3	5	4	1	3	3 gouge on fractures
167	60.05	63.09	3.04	3.04	100	2.94	97	15	3	5	6	1	3	3 gouge on fractures
167	63.09	66.14	3.05	3.00	98	2.48	81	13	3	5	15	1	3	3 last .25m broken core with gouge
167	66.14	69.19	3.05	3.08	101	2.41	79	14	3	5	7	1	3	3 0.17m section of H=2 at 66.47m
167	69.19	72.24	3.05	3.04	100	2.86	94	14	3	5	6	1	3	3 gouge on fractures, .1/2 unit H=4 (dike)
167	72.24	75.29	3.05	3.03	99	2.23	73	14	3	5	11	1	3	3 gouge on fractures
167	75.29	78.33	3.04	3.10	102	2.87	94	14	3	5	7	1	3	3
167	78.33	81.38	3.05	3.05	100	3.05	100	15	3	6	3	1	3	3
167	81.38	84.43	3.05	2.95	97	2.07	68	15	3	6	4	1	3	3
167	84.43	87.48	3.05	2.87	94	2.22	73	12	3	6	17	1	3	3 gouge on fractures, 5% broken core
167	87.48	90.53	3.05	3.05	100	2.82	92	15	3	6	4	1	3	3 0.14m gouge of H=2 at 89.42m at 45 to c.a.
167	90.53	93.57	3.04	3.05	100	3.05	100	15	3	6	2	1	3	3 gouge & minor gypsum on fractures
167	93.57	96.62	3.05	3.05	100	2.96	97	15	3	6	4	1	3	3
167	96.62	99.67	3.05	3.05	100	3.05	100	15	3	6	1	1	3	3 gouge on fractures
167	99.67	102.72	3.05	3.05	100	3.05	100	15	3	6	1	1	3	3 gouge on fractures
167	102.72	105.77	3.05	2.94	96	2.78	91	15	3	6	3	1	3	3 0.55m of H=2 (fault gouge)
167	105.77	108.81	3.04	3.11	102	2.00	66	14	3	6	9	1	3	3
167	108.81	111.86	3.05	2.94	96	2.76	90	14	3	6	5	1	3	3 gouge on fractures
167	111.86	114.91	3.05	3.05	100	2.83	93	14	3	6	7	1	3	3 gouge on fractures
167	114.91	117.96	3.05	2.91	95	1.68	55	14	3	6	8	1	3	3 slip plane at 118.63m at 8 to c.a.
167	117.96	121.01	3.05	3.07	101	2.37	78	14	3	6	9	1	3	3 gouge on fractures
167	121.01	124.05	3.04	3.04	100	2.96	97	15	3	6	2	1	3	3 gouge on fractures
167	124.05	127.10	3.05	2.96	97	2.59	85	15	3	6	4	1	3	3 5-10% broken core with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
167	127.10	130.15	3.05	2.85	93	1.63	53	13	3	6	12	1	3	gouge on fractures
167	130.15	133.20	3.05	3.08	101	2.57	84	15	3	6	7	1	3	last .65m H=2(fault gouge 20-25 to c.a.)
167	133.20	136.25	3.05	3.10	102	2.33	76	14	3	6	9	1	3	gouge on fractures, slightly sheared
167	136.25	139.29	3.04	2.96	97	2.31	76	13	3	6	11	1	3	gouge on fractures
167	139.29	142.34	3.05	3.00	98	2.36	77	15	3	6	5	5	3	gouge on fractures
167	142.34	145.39	3.05	2.99	98	2.48	81	14	3	6	9	5	3	gouge on fractures
167	145.39	148.44	3.05	2.95	97	2.95	97	15	3	6	3	1	2	2cm gouge at 144.50m at 40 to c.a.
167	148.44	151.49	3.05	3.07	101	2.39	78	13	3	6	12	1	3	0.30m shear H=2/3
167	151.49	154.53	3.04	3.04	100	2.16	71	14	3	6	10	1	3	at 152.20m 15cm shear H=2/3at 55 to c.a.
167	154.53	157.58	3.05	2.75	90	1.72	56	10	3	6	15	5	3	5% broken core with gouge
167	157.58	160.63	3.05	2.94	96	2.77	91	15	3	6	4	1	3	
167	160.63	163.68	3.05	2.33	76	0.87	29	10	3	6	25	5	3	70 % broken core with gouge
167	163.68	166.73	3.05	3.00	98	2.14	70	13	3	6	15	5	3	15 % broken core with gouge
167	166.73	169.77	3.04	3.10	102	2.40	79	14	3	6	8	1	3	0.55m H=2/3 at 166.73m at 50 to c.a.
167	169.77	172.82	3.05	3.05	100	2.93	96	15	3	6	4	1	3	slip plane at 171.84m at 20 to c.a.
167	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gouge on fractures
167	175.87	178.92	3.05	3.05	100	3.05	100	15	4	6	2	1	3	gouge on fractures
167	178.92	181.97	3.05	2.90	95	2.90	95	14	4	6	4	1	3	gouge on fractures
167	181.97	185.01	3.04	3.19	105	2.97	98	15	3	6	5	1	3	
167	185.01	188.06	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gouge on fractures
167	188.06	191.11	3.05	3.05	100	2.79	91	15	3	6	4	1	3	gouge on fractures
167	191.11	194.16	3.05	3.08	101	3.08	101	15	3	6	3	1	3	gouge on fractures
167	194.16	197.21	3.05	2.91	95	2.91	95	15	3	6	4	1	3	gouge on fractures
167	197.21	200.25	3.04	3.04	100	2.89	95	15	3	6	3	5	3	gouge on fractures
167	200.25	203.30	3.05	3.05	100	3.05	100	15	3	6	4	1	3	gouge on fractures
167	203.30	206.35	3.05	3.09	101	2.88	94	14	3	6	8	1	3	0.25m of H=2, gouge on fractures
167	206.35	209.40	3.05	2.90	95	2.69	88	14	4	6	6	1	3	
167	209.40	212.45	3.05	3.00	98	2.91	95	15	4	6	5	1	3	
167	212.45	215.49	3.04	3.30	109	3.05	100	15	4	6	3	1	3	
167	215.49	218.54	3.05	3.12	102	2.93	96	15	4	6	7	1	3	weak slicks
167	218.54	221.59	3.05	3.00	98	2.81	92	15	3	6	4	1	3	gouge on fractures
167	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
167	224.64	227.69	3.05	3.15	103	2.97	97	15	4	6	3	1	2	
167	227.69	230.73	3.04	3.04	100	2.69	88	15	4	6	6	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
167	230.73	233.78	3.05	2.99	98	2.72	89	15	4	6	3	1	2	brecciated rock
167	233.78	236.83	3.05	3.10	102	2.46	81	14	4	6	7	1	3	brecciated rock
167	236.83	239.88	3.05	3.02	99	2.84	93	15	4	6	4	1	3	brecciated rock
167	239.88	242.92	3.04	3.00	99	2.44	80	13	4	6	11	1	3	0.35m healed fault at 35-45 to c.a.
167	242.92	245.97	3.05	2.96	97	2.96	97	15	4	6	3	1	3	minor gouge on fractures
167	245.97	249.02	3.05	3.10	102	2.98	98	15	4	6	2	2	3	brecciated rock
167	249.02	252.07	3.05	3.04	100	2.87	94	15	4	6	4	1	3	brecciated rock, minor gouge fractures
167	252.07	255.12	3.05	3.05	100	3.05	100	15	5	6	2	1	2	
167	255.12	258.17	3.05	3.09	101	3.00	98	15	5	6	2	1	2	
167	258.17	261.21	3.04	3.10	102	3.10	102	15	5	6	3	1	2	
167	261.21	264.26	3.05	3.00	98	2.96	97	15	5	6	4	1	2	
167	264.26	267.31	3.05	3.05	100	2.84	93	15	5	6	5	1	3	0.37m shear/fault (healed) at 40-45 to c.a.
167	267.31	270.36	3.05	2.99	98	2.59	85	14	4	6	6	1	3	0.50m shear zone at 267.68m
167	270.36	273.41	3.05	2.98	98	1.48	49	10	3	6	20	5	3	0.42m fault H=2 at 30-40 to c.a.
167	273.41	276.45	3.04	3.07	101	2.89	95	15	5	6	3	1	3	
167	276.45	279.50	3.05	3.10	102	2.62	86	15	5	6	5	1	2	
167	279.50	282.55	3.05	3.10	102	2.92	96	15	4	6	6	1	3	minor gouge on fractures
167	282.55	285.60	3.05	2.97	97	2.97	97	15	4	6	2	1	2	
167	285.60	288.65	3.05	3.07	101	2.49	82	13	4	6	14	1	3	0.25m broken core with gouge
167	288.65	291.69	3.04	3.10	102	3.10	102	15	4	6	2	1	2	
167	291.69	294.74	3.05	2.95	97	2.95	97	15	4	6	4	1	3	gouge on fractures
167	294.74	297.79	3.05	3.14	103	3.10	102	15	4	6	3	1	2	
167	297.79	300.84	3.05	3.05	100	2.96	97	15	4	6	3	1	2	
167	300.84	303.89	3.05	2.88	94	2.88	94	15	5	6	2	1	2	
167	303.89	306.93	3.04	3.10	102	3.02	99	15	5	6	3	1	3	gouge on fractures
167	306.93	309.98	3.05	3.05	100	2.93	96	15	5	6	3	2	2	
167	309.98	313.03	3.05	2.91	95	2.33	76	13	5	6	7	1	3	
167	313.03	316.08	3.05	3.05	100	2.69	88	15	5	6	4	1	3	
167	316.08	319.13	3.05	3.07	101	2.90	95	15	5	6	5	1	2	
167	319.13	322.17	3.04	3.03	100	2.87	94	15	5	6	3	1	3	0.15m fault gouge H=2 at 319.13m
167	322.17	325.22	3.05	3.05	100	3.05	100	15	5	6	3	1	2	
167	325.22	328.27	3.05	2.86	94	1.59	52	13	5	6	5	1	3	
167	328.27	331.32	3.05	3.14	103	2.72	89	14	5	6	7	1	2	minor gypsum on fractures
167	331.32	334.37	3.05	3.05	100	2.67	88	14	5	6	5	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
167	334.37	337.41	3.04	2.89	95	2.58	85	14	5	6	6	1	2	brecciated & slightly sheared
167	337.41	340.46	3.05	3.00	98	3.00	98	15	5	6	3	1	2	brecciated & slightly sheared
167	340.46	343.51	3.05	2.86	94	2.47	81	15	5	6	4	1	2	1.25m fracture perpendicular to c.a.
167	343.51	346.56	3.05	3.05	100	2.91	95	15	5	6	3	1	2	
167	346.56	349.61	3.05	3.32	109	2.98	98	14	5	6	5	1	2	
167	349.61	352.65	3.04	2.90	95	2.62	86	15	5	6	2	1	2	
167	352.65	355.70	3.05	3.11	102	2.27	74	13	4	6	7	1	3	0.15m unit of H=2 (fault at 50 to c.a.)
167	355.70	358.75	3.05	3.09	101	2.07	68	10	4	6	14	1	3	
167	358.75	361.80	3.05	2.99	98	1.87	61	9	4	6	20	1	3	10 % broken rock
167	361.80	364.85	3.05	3.05	100	2.43	80	13	4	6	12	1	3	
167	364.85	367.89	3.04	3.04	100	2.84	93	14	4	6	5	1	3	gypsum on fractures
167	367.89	370.94	3.05	3.05	100	2.71	89	14	4	6	6	1	3	
167	370.94	373.99	3.05	3.09	101	2.07	68	12	4	6	12	1	3	5% broken core, gouge on fractures
167	373.99	377.04	3.05	3.12	102	2.93	96	15	4	6	4	1	2	
167	377.04	380.09	3.05	3.09	101	3.00	98	15	5	6	2	1	2	
167	380.09	383.13	3.04	2.91	96	2.63	87	13	5	6	9	1	3	5-10% broken core
167	383.13	386.18	3.05	2.82	92	1.99	65	10	5	6	15	1	3	5-10% broken core
167	386.18	389.23	3.05	3.09	101	2.91	95	15	5	6	4	1	2	
167	389.23	392.28	3.05	3.05	100	3.05	100	15	5	6	3	1	2	
167	392.28	395.33	3.05	3.01	99	3.01	99	15	4	6	2	1	3	gypsum on fractures
167	395.33	398.37	3.04	3.05	100	2.99	98	15	4	6	4	1	2	
167	398.37	401.42	3.05	3.00	98	2.33	76	13	4	6	11	1	3	0.45m fault gouge H=2 at 50-60 to c.a.
167	401.42	404.47	3.05	2.92	96	2.80	92	15	5	6	4	1	3	gypsum on fractures
167	404.47	407.52	3.05	3.08	101	2.59	85	14	4	6	6	1	3	minor gouge on fractures
167	407.52	410.57	3.05	3.07	101	3.00	98	15	4	6	3	1	3	
168	3.05	5.18	2.13	0.18	8	0.00	0	1	1	2	20	5	3	broken rock with gouge
168	5.18	8.23	3.05	0.53	17	0.00	0	1	1	2	20	5	3	broken rock with gouge
168	8.23	11.28	3.05	0.15	5	0.00	0	1	0	1	100	5	3	broken rock with gouge
168	11.28	14.33	3.05	0.75	25	0.13	4	1	0	1	50	5	3	broken rock with gouge
168	14.33	17.37	3.04	0.15	5	0.00	0	2	3	2	50	5	3	broken rock with gouge
168	17.37	20.42	3.05	0.11	4	0.00	0	2	3	2	30	5	3	broken rock with gouge
168	36.59	38.71	2.12	0.10	5	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	38.71	41.76	3.05	0.10	3	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	41.76	44.81	3.05	0.15	5	0.00	0	3	2	2	50	5	3	broken rock with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
168	44.81	47.85	3.04	0.05	2	0.00	0	3	2	2	20	5	3	broken rock with gouge
168	47.85	50.96	3.11	0.08	3	0.00	0	3	2	2	20	5	3	broken rock with gouge
168	50.96	53.95	2.99	0.15	5	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	53.95	57.00	3.05	0.15	5	0.00	0	3	2	2	30	5	3	broken rock with gouge
168	57.00	60.05	3.05	0.20	7	0.00	0	3	2	2	30	5	3	broken rock with gouge
168	60.05	63.09	3.04	0.01	0	0.00	0	3	2	2	15	5	3	broken rock with gouge
168	63.09	66.14	3.05	0.35	11	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	66.14	69.19	3.05	0.35	11	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	69.19	72.24	3.05	0.38	12	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	72.24	75.29	3.05	0.15	5	0.00	0	3	2	2	30	5	3	broken rock with gouge
168	75.29	78.33	3.04	0.18	6	0.00	0	3	2	2	30	5	3	broken rock with gouge
168	78.33	81.38	3.05	0.41	13	0.00	0	3	2	2	50	5	3	broken rock with gouge
168	81.38	84.43	3.05	0.52	17	0.00	0	3	2	3	50	5	3	broken rock with gouge
168	84.43	87.48	3.05	0.50	16	0.00	0	3	3	4	50	5	3	broken rock with gouge
168	87.48	91.44	3.96	0.00	0	0.00	0							no recovery
168	91.44	93.57	2.13	1.68	79	1.68	79	14	3	6	3	1	3	
168	93.57	96.62	3.05	3.10	102	2.97	97	15	3	6	4	1	3	gypsum on fractures
168	96.62	99.67	3.05	3.10	102	2.84	93	15	3	6	4	1	3	
168	99.67	102.72	3.05	3.04	100	3.04	100	15	3	6	2	1	3	gypsum on fractures
168	102.72	105.77	3.05	3.09	101	3.09	101	15	3	6	1	1	3	gypsum on fractures
168	105.77	108.81	3.04	3.06	101	3.06	101	15	3	6	2	1	3	
168	108.81	111.86	3.05	3.05	100	2.98	98	15	4	6	4	1	3	gypsum on fractures; dyke
168	111.86	114.91	3.05	3.06	100	3.06	100	15	3	6	3	1	3	gypsum on fractures
168	114.91	117.95	3.04	2.92	96	2.92	96	15	3	6	2	1	3	gypsum on fractures
168	117.95	121.01	3.06	2.90	95	2.72	89	15	5	6	4	1	3	
168	121.01	124.05	3.04	3.01	99	2.89	95	15	4	6	5	1	3	
168	124.05	127.10	3.05	3.05	100	2.80	92	15	4	6	7	1	3	30 cm. healed fault at 60 to c.a.
168	127.10	130.15	3.05	2.97	97	2.97	97	15	4	6	3	1	3	gypsum on frags; 15 cm. fault at 45 to c.a.
168	130.15	133.20	3.05	2.90	95	2.72	89	15	4	6	6	1	3	gypsum on fractures
168	133.20	136.25	3.05	3.11	102	3.00	98	15	4	6	3	1	3	2 cm. fracture w/ gouge at 20 to c.a.
168	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6	4	1	3	
168	139.29	142.34	3.05	3.05	100	3.00	98	15	4	6	4	1	3	20 cm. gypsum fracture at 20 to c.a.
168	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	2	1	3	10% porous rx; 2 cm fault at 45 to c.a.
168	145.39	148.44	3.05	2.62	86	1.84	60	10	4	6	20	5	3	15-20% broken core with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
168	148.44	151.49	3.05	2.95	97	2.95	97	15	4	6	2	1	3	
168	151.49	154.53	3.04	3.12	103	2.98	98	15	4	6	3	1	3	3 minor gouge on fractures
168	154.53	157.58	3.05	3.05	100	2.71	89	15	5	6	1	1	3	
168	157.58	160.63	3.05	3.14	103	3.01	99	15	4	6	2	1	3	3 minor gouge on fractures
168	160.63	163.68	3.05	3.09	101	3.09	101	15	4	6	3	1	3	
168	163.68	166.73	3.05	2.95	97	2.95	97	15	4	6	1	1	3	
168	166.73	169.77	3.04	3.09	102	3.09	102	15	4	6	2	1	3	3 minor gouge on fractures
168	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
168	172.82	175.82	3.00	3.00	100	2.91	97	15	4	6	2	1	3	
168	175.87	178.92	3.05	3.05	100	2.99	98	15	4	6	2	1	3	
168	178.92	181.97	3.05	3.13	103	3.00	98	15	4	6	3	5	3	3 gouge on fractures
168	181.97	185.01	3.04	3.04	100	2.51	83	15	4	6	7	1	3	3 gouge on fractures
168	185.01	188.06	3.05	3.30	108	3.17	104	15	4	6	3	1	3	
168	188.06	191.11	3.05	2.77	91	2.69	88	12	4	6	15	1	3	3 5% broken core with gouge
168	191.11	194.16	3.05	3.35	110	3.20	105	15	4	6	5	1	3	3 gouge on fractures
168	194.16	197.21	3.05	2.88	94	2.69	88	15	4	6	4	1	4	4 sheared rock, gouge on fractures
168	197.21	200.25	3.04	3.07	101	3.07	101	15	4	6	1	1	2	
168	200.25	203.30	3.05	2.97	97	2.91	95	15	4	6	2	1	3	
168	203.30	206.35	3.05	3.11	102	2.88	94	14	4	6	9	1	3	3 15cm healed fault at 30 to c.a.
168	206.35	209.40	3.05	2.92	96	2.00	66	10	4	6	20	5	3	3 5-10% broken core with gouge
168	209.40	212.45	3.05	2.79	91	2.72	89	15	3	6	3	1	3	3 gouge on fractures
168	212.45	215.49	3.04	2.93	96	2.57	85	15	3	6	5	1	3	3 gouge on fractures
168	215.49	218.54	3.05	3.05	100	3.05	100	15	3	6	3	1	3	3 gouge on fractures
168	218.54	221.59	3.05	3.05	100	2.94	96	15	3	6	4	1	3	3 20cm section of H=2
168	221.59	224.64	3.05	3.05	100	2.88	94	15	3	6	4	1	3	
168	224.64	227.69	3.05	3.05	100	3.05	100	15	3	6	3	1	3	3 slip plane at 35 to c.a.
168	227.69	230.73	3.04	3.04	100	3.00	99	15	3	6	4	1	3	3 gouge on fractures
168	230.73	233.78	3.05	3.07	101	2.58	85	13	3	6	15	1	3	3 gouge on fractures
168	233.78	236.83	3.05	2.81	92	1.36	45	10	3	6	20	5	3	3 5-10% broken core with gouge
168	236.83	239.88	3.05	3.10	102	1.26	41	10	3	6	25	5	3	3 10% broken core with gouge
168	239.88	242.93	3.05	3.11	102	3.11	102	15	3	6	3	1	3	
168	242.93	245.97	3.04	2.93	96	2.23	73	15	3	6	5	1	3	3 13cm fault gouge(H=2) at 32 to c.a.
168	245.97	249.02	3.05	3.17	104	3.04	100	15	3	6	3	1	3	
168	249.02	252.07	3.05	2.94	96	1.97	65	12	3	6	16	1	3	3 5% broken core with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
168	252.07	255.12	3.05	3.01	99	2.24	73	14	3	5	10	2	3 gouge on fractures	
168	255.12	258.17	3.05	3.14	103	2.54	83	14	3	5	7	1	3 10cm gouge with H=1 at 25 to c.a.	
168	258.17	261.21	3.04	2.94	97	2.39	79	15	4	6	4	1	3 minor gouge on fractures	
168	261.21	264.26	3.05	3.11	102	3.00	98	15	4	6	3	1	3	
168	264.26	267.31	3.05	3.00	98	2.02	66	15	4	6	5	1	2 5% broken core with gouge	
168	267.31	270.36	3.05	3.07	101	2.89	95	14	4	6	7	1	3 gouge on fractures	
168	270.36	273.41	3.05	3.00	98	3.00	98	15	4	6	3	1	3	
168	273.41	276.45	3.04	3.04	100	3.04	100	15	4	6	2	1	3	
168	276.45	279.50	3.05	3.03	99	3.03	99	15	4	6	1	1	2	
168	279.50	282.55	3.05	2.81	92	2.63	86	15	5	6	2	1	3	
168	282.55	285.60	3.05	3.11	102	3.02	99	15	5	6	4	1	3 minor gouge on fractures	
168	285.60	288.65	3.05	3.05	100	2.67	88	15	4	6	4	1	3	
168	288.65	291.69	3.04	2.94	97	1.43	47	10	4	6	20	1	3 15% broken core with gouge	
168	291.69	294.74	3.05	3.08	101	2.29	75	13	4	6	11	1	3 gouge on fractures	
168	294.74	297.79	3.05	2.92	96	2.60	85	14	4	6	8	1	3 gouge on fractures	
168	297.79	300.84	3.05	3.10	102	2.15	70	14	4	6	7	1	3 gouge on fractures	
168	300.84	303.89	3.05	2.33	76	1.39	46	12	4	6	15	1	3 2cm gouge H=1 at 45 to c.a.	
168	303.89	306.93	3.04	3.04	100	2.92	96	14	3	6	7	1	3 15cm fault at 30 to c.a.	
168	306.93	309.98	3.05	3.13	103	2.67	88	14	3	6	5	1	3 2 2cm faults at 30 to c.a. H=2	
168	309.98	313.03	3.05	3.12	102	3.02	99	15	4	6	2	1	2	
168	313.03	316.08	3.05	3.08	101	3.08	101	15	4	6	3	1	2	
168	316.08	319.13	3.05	3.13	103	2.93	96	14	4	6	9	1	2 5% broken core	
168	319.13	322.17	3.04	3.09	102	3.00	99	15	3	6	4	1	2	
168	322.17	325.22	3.05	2.94	96	1.16	38	12	3	6	17	1	3 20% broken core with minor gouge	
168	325.22	328.27	3.05	3.09	101	3.09	101	15	3	6	2	1	3	
168	328.27	331.32	3.05	2.79	91	2.79	91	15	3	6	1	1	2	
168	331.32	334.37	3.05	3.05	100	2.91	95	15	3	6	4	1	3 minor gouge on fractures	
168	334.37	337.41	3.04	3.17	104	3.00	99	15	3	6	3	1	2	
168	337.41	340.46	3.05	3.00	98	2.49	82	14	3	6	9	5	3 5% broken core with minor gouge	
168	340.46	343.51	3.05	2.97	97	2.13	70	14	3	6	6	1	3 2cm fault at 15 to c.a.	
168	343.51	346.56	3.05	2.71	89	2.71	89	15	3	6	2	1	2	
168	346.56	349.61	3.05	3.17	104	3.09	101	15	3	6	2	2	2	
168	349.61	352.65	3.04	3.10	102	2.23	73	13	3	6	12	1	3 2cm gouge at 20 to c.a.,5% broken core	
168	352.65	355.70	3.05	3.05	100	3.05	100	15	3	6	2	1	3 gouge on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
168	355.70	358.75	3.05	3.05	100	3.05	100	15	3	6	1	1	2	
168	358.75	361.80	3.05	3.05	100	3.00	98	15	3	6	2	1	2	
168	361.80	364.85	3.05	3.03	99	2.83	93	14	3	6	5	1	3	3cm fault at 25 to c.a.
168	364.85	367.89	3.04	2.23	73	1.01	33	9	3	6	25	5	3	40% broken core with gouge
168	367.89	370.94	3.05	2.73	90	1.47	48	9	3	6	25	5	3	35% broken core with gouge
168	370.94	373.99	3.05	3.12	102	3.04	100	14	3	6	5	1	3	gouge & gypsum on fractures
168	373.99	377.04	3.05	3.11	102	2.92	96	15	3	6	4	1	3	5cm fault at 55 to c.a.
169	6.10	8.23	2.13	1.20	56	0.26	12	1	3	3	50	1	3	
169	8.23	11.28	3.05	2.32	76	0.35	11	1	5	4	50	1	3	90% broken rock
169	11.28	13.11	1.83	1.25	68	0.00	0	1	3	4	50	1	3	90% broken rock
169	13.11	14.33	1.22	0.43	35	0.00	0	1	5	4	40	1	3	100% broken rock
169	14.33	16.15	1.82	1.65	91	0.78	43	5	3	4	40	1	3	90 cm broken rock
169	16.15	17.37	1.22	0.74	61	0.00	0	1	5	5	50	1	4	13 cm. crushed rock; H=2
169	17.37	19.20	1.83	1.50	82	0.33	18	1	3	4	50	1	4	10 cm crushed rock; H=2
169	19.20	20.42	1.22	0.60	49	0.00	0	1	5	4	40	1	4	100% broken rock
169	20.42	22.25	1.83	0.85	46	0.46	25	1	3	4	40	1	4	8 cm crushed rock; H=2
169	22.25	25.30	3.05	0.35	11	0.00	0	1	4	4	30	1	3	100% broken rock
169	25.30	26.52	1.22	0.47	39	0.00	0	1	3	3	40	1	4	100% broken rock
169	26.52	29.57	3.05	1.04	34	0.57	19	5	3	4	30	1	3	23 cm fo finely broken core
169	29.57	32.61	3.04	2.06	68	0.65	21	1	3	3	50	1	4	35 cm of crushed rock; H=2
169	32.61	35.66	3.05	2.59	85	2.29	75	13	4	4	7	3	3	10 cm of broken rock
169	35.66	38.71	3.05	2.98	98	2.93	96	13	3	5	12	3	3	8 cm crushed rock
169	38.71	41.76	3.05	3.11	102	3.11	102	15	4	6	1	3	4	
169	41.76	44.81	3.05	3.05	100	2.93	96	15	3	6	3	1	4	
169	44.81	47.85	3.04	3.02	99	3.02	99	15	3	6	2	1	3	
169	47.85	50.90	3.05	3.01	99	3.01	99	15	4	6	3	1	3	
169	50.90	53.95	3.05	3.04	100	3.04	100	15	3	6	0			
169	53.95	57.00	3.05	2.87	94	2.87	94	15	3	6	1	1	3	
169	57.00	60.05	3.05	3.05	100	3.05	100	15	4	6	1	1	4	
169	60.05	63.09	3.04	3.14	103	3.04	100	15	3	6	4	1	4	5 cm fo broken rock
169	63.09	66.14	3.05	2.91	95	2.91	95	15	4	6	0			
169	66.14	69.19	3.05	2.99	98	2.99	98	15	3	6	2	1	4	gouge on fractures
169	69.19	72.24	3.05	2.86	94	2.86	94	15	4	6	2	3	4	
169	72.24	75.29	3.05	3.04	100	3.05	100	15	4	6	2	1	3	first 8 cm redrilled core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
169	75.29	78.33	3.04	3.00	99	3.00	99	15	3	6	1	3	3	
169	78.33	81.38	3.05	3.00	98	2.96	97	14	5	5	5	3	4	8 cm broken rock & gouge to mud
169	81.38	84.43	3.05	3.05	100	3.05	100	15	4	6	2	1	3	23 cm gypsum; H=2
169	84.43	87.48	3.05	2.91	95	2.70	89	15	5	6	4	1	4	
169	87.48	90.53	3.05	3.02	99	3.02	99	15	3	6	2	3	3	
169	90.53	93.57	3.04	3.02	99	3.02	99	15	5	6	1	1	4	
169	93.57	96.62	3.05	3.04	100	3.04	100	15	4	6	1	3	4	
169	96.62	99.67	3.05	3.02	99	3.02	99	15	4	6	1	3	3	
169	99.67	102.72	3.05	2.96	97	2.96	97	15	3	6	2	3	3	
169	102.72	105.77	3.05	2.93	96	2.93	96	15	3	6	0			
169	105.77	108.81	3.04	2.94	97	2.78	91	15	3	5	4	1	3	
169	108.81	111.86	3.05	3.01	99	3.01	99	15	4	5	3	3	3	gypsum; H=2; gouge on fractures
169	111.86	114.91	3.05	3.04	100	3.04	100	15	3	5	2	1	3	gouge on fractures
169	114.91	117.96	3.05	3.15	103	3.15	103	15	3	6	1	1	3	
169	117.96	121.01	3.05	3.01	99	3.01	99	15	4	6	0			
169	121.01	124.05	3.04	3.09	102	3.09	102	15	4	6	1	3	4	28 cm of H=2/3
169	124.05	127.10	3.05	3.06	100	2.94	96	15	4	5	2	1	4	10 cm of H=0 (mud)
169	127.10	130.15	3.05	3.09	101	3.00	98	15	3	6	4	1	3	
169	130.15	133.20	3.05	2.96	97	2.96	97	15	4	6	2	1	3	
169	133.20	136.25	3.05	2.89	95	2.89	95	15	4	6	0	1	2	
169	136.25	139.29	3.04	3.16	104	2.89	95	15	4	6	4	1	2	
169	139.29	142.34	3.05	3.05	100	3.05	100	15	5	6	4	1	2	
169	142.34	145.39	3.05	3.05	100	2.95	97	15	5	6	3	1	2	
169	145.39	148.44	3.05	2.99	98	2.73	90	14	5	6	7	1	2	
169	148.44	151.49	3.05	3.11	102	3.11	102	15	5	6	3	1	2	weakly broken core at top of run
169	151.49	154.53	3.04	3.16	104	3.12	103	15	5	6	3	1	1	2 parallel breaks at 60 to c.a.
169	154.53	157.58	3.05	3.05	100	3.05	100	15	5	6	4	1	2	
169	157.58	160.63	3.05	2.95	97	2.95	97	15	5	6	2	1	2	
169	160.63	163.68	3.05	3.11	102	3.11	102	15	5	6	3	1	1	slips on gypsum veins
169	163.68	166.73	3.05	3.05	100	3.05	100	15	5	6	2	1	2	
169	166.73	169.77	3.04	3.04	100	2.91	96	15	5	6	3	1	2	
169	169.77	172.82	3.05	3.05	100	2.82	92	14	5	6	6	1	2	
169	172.82	175.87	3.05	3.09	101	3.00	98	15	5	6	4	1	2	most breaks on gypsum veins
169	175.87	178.92	3.05	2.90	95	2.90	95	15	5	6	3	1	2	most breaks on gypsum veins

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
169	178.92	181.97	3.05	3.05	100	3.05	100	15	5	6	4	1	2	2 most breaks on gypsum veins
169	181.97	184.40	2.43	2.43	100	2.40	99	15	5	6	3	1	2	2 most breaks on gypsum veins
169	184.40	187.45	3.05	3.09	101	3.09	101	15	5	6	4	1	2	2 most breaks on gypsum veins
169	187.45	190.65	3.20	3.09	97	3.09	97	15	5	6	3	1	2	2 most breaks on gypsum veins
169	190.65	193.85	3.20	3.09	97	2.98	93	14	5	6	7	1	2	2 most breaks on gypsum veins
169	193.85	196.90	3.05	3.12	102	2.94	96	14	5	6	6	1	2	2 most breaks on gypsum veins
169	196.90	200.10	3.20	3.24	101	3.24	101	15	5	6	3	1	2	2 most breaks on gypsum veins
169	200.10	202.69	2.59	2.55	98	1.85	71	12	5	6	14	2	3	3 weakly broken core with gouge
169	202.69	205.89	3.20	3.12	98	2.62	82	14	5	6	7	1	2	2 gouge on fractures
169	205.89	208.94	3.05	3.12	102	3.12	102	15	5	6	4	2	2	2 10cm gouge broken core
169	208.94	212.14	3.20	3.05	95	1.85	58	12	5	6	17	1	2	2 cemented fractures at 40 to c.a.
169	212.14	215.34	3.20	3.01	94	3.01	94	15	5	5	4	1	2	2
169	215.34	218.39	3.05	3.08	101	3.01	99	14	5	6	6	1	2	2 10cm strongly broken angled core
169	218.39	221.59	3.20	3.10	97	3.10	97	15	5	6	5	1	2	2 all breaks on veins
169	221.59	224.64	3.05	3.14	103	3.05	100	15	5	6	4	1	2	2
169	224.64	227.69	3.05	3.08	101	2.83	93	14	5	6	7	1	2	2
169	227.69	230.73	3.04	2.95	97	2.95	97	15	5	6	3	1	2	2
169	230.73	233.78	3.05	3.17	104	3.17	104	15	5	6	4	1	2	2
169	233.78	236.83	3.05	3.05	100	3.05	100	14	5	6	6	1	2	2
169	236.83	239.88	3.05	2.99	98	2.78	91	15	5	6	5	1	1	1 slip with broken core at 25 to c.a.
169	239.88	242.93	3.05	3.05	100	2.98	98	14	5	6	6	1	3	3
169	242.93	245.97	3.04	3.08	101	3.08	101	15	5	6	4	1	2	2
169	245.97	249.02	3.05	3.00	98	2.87	94	15	5	6	4	1	2	2
169	249.02	252.07	3.05	2.95	97	2.44	80	12	5	6	15	1	2	2 broken core in PPHM,50% dikes
169	252.07	255.12	3.05	3.23	106	3.23	106	15	5	6	4	1	2	2
169	255.12	258.16	3.04	3.04	100	2.91	96	15	5	6	5	1	1	1 2cm gouge fracture at 30 to c.a.
169	258.16	261.21	3.05	3.05	100	2.95	97	15	5	6	4	1	2	2
169	261.21	262.43	1.22	1.02	84	0.64	52	13	5	5	4	1	3	3 broken core and gouge on fractures
169	262.43	264.26	1.83	1.78	97	1.78	97	15	5	6	1	1	2	2
169	264.26	267.31	3.05	3.00	98	3.00	98	15	5	6	2	1	3	3 14cm redrilled core
169	267.31	270.36	3.05	3.09	101	3.09	101	15	5	6	2	3	3	3
169	270.36	273.41	3.05	2.97	97	2.90	95	15	4	6	3	3	4	4 gouge on fractures
169	273.41	276.43	3.02	3.00	99	3.00	99	15	4	6	2	1	3	3
169	276.43	279.50	3.07	2.95	96	2.90	94	14	4	6	5	3	4	4

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
169	279.50	282.55	3.05	3.06	100	3.06	100	15	5	6	1	3	3	
169	282.55	285.60	3.05	2.96	97	1.76	58	13	5	6	10	3	3	60cm broken rock H=2,gouge on fract
169	285.60	288.65	3.05	2.94	96	2.51	82	14	4	6	8	3	3	10cm broken rock
169	288.65	291.69	3.04	3.08	101	3.08	101	15	5	6	1	1	3	H=2 36cm healed fault
169	291.69	294.74	3.05	2.96	97	2.39	78	13	4	6	10	3	4	H=2 healed fault 70 to c.a.
169	294.74	297.79	3.05	3.04	100	3.04	100	15	5	6	1	3	3	
169	297.79	300.84	3.05	2.97	97	2.97	97	15	5	6	1	1	3	7 cm redrilled core
169	300.84	303.89	3.05	3.06	100	3.06	100	15	5	6	1	3	3	
169	303.89	306.93	3.04	3.00	99	3.00	99	15	5	6	1	3	3	
169	306.93	309.98	3.05	2.98	98	2.98	98	15	5	6	1	3	4	54cm healed fault H=2
169	309.98	313.03	3.05	2.76	90	2.76	90	15	5	6	2	1	3	47cm healed fault, H=2
169	313.03	316.08	3.05	3.01	99	3.01	99	15	5	6	1	1	2	gouge on fractures
169	316.08	319.13	3.05	2.93	96	2.93	96	15	5	6	1	1	3	
169	319.13	322.17	3.04	2.91	96	2.91	96	15	5	6	1	1	3	gouge on fractures
169	322.17	325.22	3.05	2.92	96	2.92	96	15	5	6	0			
169	325.22	328.27	3.05	2.84	93	2.84	93	15	5	6	0			
169	328.27	331.32	3.05	3.03	99	3.03	99	15	5	6	0			
169	331.32	334.37	3.05	3.06	100	3.06	100	15	5	6	1	3	4	
169	334.37	337.41	3.04	3.04	100	3.04	100	15	5	6	2	3	3	gouge on fractures
169	337.41	340.46	3.05	2.94	96	2.94	96	15	5	6	0			
169	340.46	343.51	3.05	3.34	110	3.34	110	15	5	6	1	1	3	
169	343.51	346.56	3.05	2.82	92	2.82	92	15	5	6	0			
169	346.56	349.61	3.05	2.92	96	2.92	96	15	5	6	0			4cm redrilled core
169	349.61	352.65	3.04	2.98	98	2.93	96	15	4	6	3	3	4	5cm redrilled core with gouge fractures
169	352.65	355.70	3.05	3.06	100	3.06	100	15	4	6	1	3	4	
169	355.70	358.75	3.05	2.97	97	2.97	97	15	5	6	3	3	3	
169	358.75	361.80	3.05	2.93	96	2.93	96	15	5	6	0			
169	361.80	364.85	3.05	2.99	98	2.99	98	15	5	6	1	3	4	
169	364.85	367.89	3.04	3.05	100	3.05	100	15	4	6	1	1	3	9cm redrilled core
169	367.89	370.94	3.05	2.93	96	2.93	96	15	5	6	0			
169	370.94	373.99	3.05	3.09	101	3.09	101	15	5	6	0			
169	373.99	377.04	3.05	3.04	100	3.04	100	15	5	6	0			16cm redrilled core
169	377.04	380.09	3.05	2.98	98	2.98	98	15	5	6	0			
169	380.09	383.13	3.04	3.02	99	3.02	99	15	5	6	0			

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
169	383.13	386.18	3.05	2.96	97	2.81	92	15	5	6	5	3	4	15cm broken core, H=3
169	386.18	389.23	3.05	2.95	97	2.95	97	15	5	6	2	3	4	gouge on fractures
170	3.05	8.23	5.18	1.25	24	0.00	0	5	4	4	50	1	3	limonite on fractures, minor clay gouge
170	8.23	11.28	3.05	1.15	38	0.00	0	5	4	4	50	1	3	rubble/clay
170	11.28	14.33	3.05	2.25	74	0.00	0	5	4	5	50	1	2	rubble/clay
170	14.33	17.37	3.04	1.55	51	0.00	0	5	4	5	50	1	2	rubble/clay
170	17.37	20.42	3.05	1.44	47	0.00	0	5	4	4	50	1	2	rubble/clay
170	20.42	42.37	21.95	0.43	2	0.00	0	5	4	5	50	5	3	triconed/minor gouge
170	42.37	44.50	2.13	0.52	24	0.00	0	5	4	5	50	1	3	minor clay/gouge at 25 to c.a.
170	44.50	46.02	1.52	0.70	46	0.00	0	5	4	5	50	3	3	rubble, gypsum on fractures
170	46.02	96.32	50.30	0.00	0	0.00	0							triconed
170	96.32	99.36	3.04	2.08	68	1.92	63	15	4	5	2	1	2	gypsum fractures/veins
170	99.36	102.41	3.05	3.05	100	2.85	93	15	4	5	3	1	3	gypsum fractures/veins
170	102.41	105.46	3.05	3.05	100	3.00	98	15	4	5	2	3	2	gypsum fractures/veins
170	105.46	108.51	3.05	3.05	100	3.05	100	15	4	5	0			gypsum fractures/veins
170	108.51	111.56	3.05	3.05	100	2.95	97	15	4	5	2	3	2	gypsum fractures/veins
170	111.56	114.60	3.04	3.04	100	2.65	87	15	4	5	4	1	2	gypsum fractures/veins
170	114.60	117.65	3.05	3.05	100	3.05	100	15	4	5	1	1	2	gypsum fractures/veins
170	117.65	120.70	3.05	3.05	100	2.95	97	15	4	5	2	1	2	gypsum fractures/veins
170	120.70	123.75	3.05	3.00	98	3.00	98	15	4	5	1	3	3	gypsum fractures/veins
170	123.75	126.80	3.05	3.10	102	2.80	92	15	4	5	3	3	3	healed shear
170	126.80	130.15	3.35	3.25	97	2.75	82	14	3	5	7	1	2	50 to c.a. 1cm gouge, shears 20 to c.a.
170	130.15	133.20	3.05	2.91	95	2.91	95	15	4	5	2	3	2	DQc.a. 130.15 at 65 to c.a., 130.8m 70 to c.a.
170	133.20	136.25	3.05	3.10	102	2.80	92	14	3	3	6	3	3	healed fault with gouge at 25,30,45 tca
170	136.25	139.29	3.04	3.04	100	2.74	90	14	4	4	5	3	3	gypsum veins/healed fractures w gouge
170	139.29	142.34	3.05	3.15	103	3.15	103	15	4	4	1	3	2	gypsum veins/healed fractures w gouge
170	142.34	145.39	3.05	3.10	102	3.10	102	15	4	5	2	1	2	gypsum veins/healed fractures w gouge
170	145.39	148.44	3.05	3.10	102	3.00	98	15	4	5	4	3	3	
170	148.44	151.49	3.05	3.05	100	2.27	74	13	4	5	10	1	2	40cm shear/gouge at 10 to c.a.
170	151.49	154.53	3.04	2.65	87	0.67	22	9	4	4	30	1	2	Blocky
170	154.53	157.58	3.05	2.22	73	1.00	33	7	4	4	25	1	1	2cm gouge at 15 to c.a.
170	157.58	160.63	3.05	3.10	102	3.00	98	15	4	5	4	1	1	
170	160.63	163.68	3.05	3.05	100	2.95	97	15	4	5	4	3	2	
170	163.68	166.73	3.05	3.00	98	2.60	85	14	4	5	7	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
170	166.73	169.77	3.04	3.10	102	2.90	95	15	4	5	3	1	2	DQCA at 166.6-171.25 m, fract. on carb vn.
170	169.77	172.82	3.05	2.75	90	2.55	84	14	4	5	7	1	2	
170	172.82	175.87	3.05	3.30	108	3.05	100	14	4	5	8	1	2	
170	175.87	178.92	3.05	3.10	102	3.00	98	15	4	5	3	1	2	
170	178.92	181.97	3.05	2.90	95	2.90	95	15	4	5	3	3	3	
170	181.97	185.01	3.04	3.10	102	2.90	95	15	4	5	4	3	3	3 10cm shear with gouge
170	185.01	188.06	3.05	3.15	103	3.15	103	15	4	5	2	3	2	
170	188.06	191.11	3.05	3.05	100	3.05	100	15	4	5	1	1	2	
170	191.11	194.16	3.05	2.95	97	2.50	82	14	4	5	6	3	3	3 40cm blocky area
170	194.16	197.21	3.05	3.05	100	3.05	100	15	4	5	3	5	4	4 fault with gouge
170	197.21	200.25	3.04	3.04	100	3.04	100	15	1	3	4	3	3	3 fault with gouge, shear 45 to c.a.
170	200.25	203.30	3.05	3.05	100	2.90	95	15	2	3	4	3	3	3 Fault with gouge
170	203.30	206.35	3.05	3.05	100	1.39	46	1	0	3	26	3	3	3 lots of gouge 15 to c.a.
170	206.35	209.40	3.05	3.05	100	1.39	46	1	1	3	15	1	2	2 lots of gouge 30 toc.a.
170	209.40	212.45	3.05	3.05	100	2.77	91	15	4	5	5	1	2	2 40cm fault gouge at 40 to c.a.
170	212.45	215.49	3.04	3.04	100	2.90	95	15	4	5	4	1	2	2 1cm Shear at 35 to c.a.
170	215.49	218.54	3.05	3.05	100	3.05	100	15	4	5	2	3	3	
170	218.54	221.59	3.05	3.05	100	3.05	100	15	4	5	3	2	2	
170	221.59	224.64	3.05	3.05	100	3.05	100	15	4	5	0			
170	224.64	227.69	3.05	3.05	100	3.05	100	15	4	5	1	3	3	
170	227.69	230.73	3.04	3.04	100	3.04	100	15	4	5	1	4	2	
170	230.73	233.78	3.05	3.05	100	3.05	100	15	3	3	5	3	2	2 231.0-232.0m healed fault at 45 to c.a.
170	233.78	236.83	3.05	3.05	100	3.05	100	15	4	5	1	3	2	2 small shear 1cm
170	236.83	239.88	3.05	3.05	100	2.60	85	14	4	5	6	1	2	
170	239.88	242.93	3.05	3.05	100	2.95	97	15	4	5	2	1	3	
170	242.93	245.97	3.04	3.04	100	3.04	100	15	4	5	1	2	2	
170	245.97	249.02	3.05	3.05	100	3.05	100	15	4	5	0			
170	249.02	252.07	3.05	3.05	100	2.90	95	15	4	5	5	3	3	3 shear 10cm at 25 to c.a.
170	252.07	255.12	3.05	3.05	100	3.05	100	15	4	5	3	1	3	
170	255.12	258.17	3.05	3.05	100	3.05	100	15	4	5	0			carb healed shearing
170	258.17	261.21	3.04	3.02	99	3.02	99	15	4	5	2	1	3	
170	261.21	264.26	3.05	3.10	102	2.92	96	15	4	5	4	1	3	3 minor gouge on fractures
170	264.26	267.31	3.05	3.06	100	3.06	100	15	4	5	1	1	3	
170	267.31	270.36	3.05	3.09	101	3.09	101	15	4	5	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
170	270.36	273.41	3.05	2.98	98	2.87	94	15	4	5	4	1	3	
170	273.41	276.45	3.04	3.08	101	3.08	101	15	4	5	2	1	3	
170	276.45	279.50	3.05	3.08	101	2.99	98	15	4	5	3	1	3	
170	279.50	282.55	3.05	3.05	100	3.05	100	15	4	5	1	1	3	
170	282.55	285.60	3.05	3.05	100	3.05	100	15	4	5	1	1	3	
170	285.60	288.65	3.05	3.05	100	2.92	96	15	5	5	3	1	3	
170	288.65	291.69	3.04	3.04	100	3.04	100	15	5	5	2	1	3	
170	291.69	294.74	3.05	3.11	102	3.00	98	15	5	5	4	1	3	
170	294.74	297.79	3.05	3.02	99	3.02	99	15	5	5	2	1	3	
170	297.79	300.84	3.05	2.99	98	2.99	98	15	4	5	3	1	3	
170	300.84	303.89	3.05	3.00	98	3.00	98	15	4	5	2	1	3	
170	303.89	306.93	3.04	3.09	102	2.79	92	15	4	5	5	1	3	3 minor gouge on fractures
170	306.93	309.98	3.05	3.11	102	3.11	102	15	4	5	1	1	3	
170	309.98	313.03	3.05	3.05	100	3.05	100	15	4	5	3	1	3	
170	313.03	316.08	3.05	3.05	100	3.00	98	15	4	5	2	1	3	
170	316.08	319.12	3.04	3.17	104	2.69	88	14	4	5	7	1	2	
170	319.12	322.17	3.05	3.05	100	3.00	98	15	4	5	4	1	3	3 minor gouge on fractures
170	322.17	325.22	3.05	3.00	98	2.70	89	15	4	5	8	1	3	
170	325.22	328.27	3.05	2.99	98	2.59	85	15	3	5	9	1	3	3 50cm gouge H=1
170	328.27	331.32	3.05	3.00	98	2.60	85	15	3	5	7	1	3	3 gouge on fractures
170	331.32	334.37	3.05	3.05	100	3.05	100	15	3	5	4	1	3	
170	334.37	337.41	3.04	2.63	87	2.58	85	15	3	5	3	1	3	
170	337.41	340.46	3.05	3.05	100	2.94	96	15	3	5	4	1	3	
170	340.46	343.51	3.05	3.06	100	2.76	90	15	3	5	3	1	3	
170	343.51	346.56	3.05	3.08	101	3.08	101	15	3	5	2	1	3	
170	346.56	349.61	3.05	3.09	101	3.02	99	15	3	5	3	1	3	3 gypsum on fractures
170	349.61	350.82	1.21	1.14	94	1.14	94	15	3	5	1	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
171	4.27	7.62	3.35	1.65	49	0.67	20	9	4	4	20	3	4	15 cm H=2
171	7.62	8.84	1.22	1.17	96	0.44	36	7	3	4	20	3	4	broken core
171	8.84	11.28	2.44	2.35	96	1.22	50	7	3	4	40	3	4	broken core
171	11.28	12.50	1.22	1.00	82	0.00	0	5	5	4	30	3	3	broken core
171	12.50	14.33	1.83	1.38	75	0.00	0	6	5	4	40	1	4	broken core, iron staining
171	14.33	15.54	1.21	0.92	76	0.00	0	5	5	4	30	1	4	broken core, iron staining
171	15.54	16.46	0.92	0.95	103	0.00	0	6	4	4	30	1	4	broken core, iron staining
171	16.46	19.20	2.74	1.76	64	0.00	0	6	4	4	50	1	4	broken core, iron staining
171	19.20	20.42	1.22	0.67	55	0.00	0	2	5	4	40	1	3	broken core, iron staining
171	20.42	21.64	1.22	1.09	89	0.00	0	5	5	4	40	1	3	broken core, iron staining
171	21.64	22.86	1.22	0.97	80	0.00	0	6	4	4	40	1	3	broken core, iron staining
171	22.86	24.69	1.83	1.50	82	0.00	0	6	5	4	50	1	3	broken core, iron staining
171	24.69	25.30	0.61	0.44	72	0.00	0	2	5	4	30	3	3	broken core, iron staining
171	25.30	26.52	1.22	0.73	60	0.00	0	2	5	4	40	3	3	broken core, iron staining
171	26.52	27.43	0.91	0.75	82	0.00	0	5	5	4	50	1	3	broken core, iron staining
171	27.43	28.65	1.22	0.98	80	0.00	0	5	4	4	50	3	4	broken core, iron staining
171	28.65	29.57	0.92	0.70	76	0.00	0	5	5	4	40	3	4	broken core, iron staining
171	29.57	30.18	0.61	0.43	70	0.00	0	2	5	4	30	3	4	broken core, iron staining
171	30.18	31.70	1.52	1.40	92	0.00	0	5	5	4	50	3	4	broken core, iron staining
171	31.70	32.61	0.91	0.70	77	0.00	0	6	5	4	30	3	4	broken core, iron staining
171	32.61	33.22	0.61	0.50	82	0.00	0	6	5	4	20	3	4	broken core, iron staining
171	33.22	33.83	0.61	0.39	64	0.00	0	5	5	4	20	3	4	broken core, iron staining
171	33.83	35.05	1.22	1.00	82	0.00	0	6	5	4	30	3	4	broken core, iron staining
171	35.05	36.27	1.22	0.95	78	0.00	0	6	5	4	30	1	3	broken core, iron staining
171	36.27	37.49	1.22	0.70	57	0.00	0	3	5	4	50	3	3	broken core, iron staining
171	37.49	40.23	2.74	2.45	89	0.00	0	6	5	5	50	3	4	broken core, iron staining
171	40.23	41.76	1.53	1.49	97	1.17	76	13	4	5	5	3	4	broken core, iron staining
171	41.76	44.81	3.05	2.88	94	1.16	38	13	4	5	10	3	3	
171	44.81	47.85	3.04	2.72	89	0.32	11	9	4	5	25	3	4	
171	47.85	49.07	1.22	0.94	77	0.00	0	5	4	5	50	3	4	
171	49.07	50.90	1.83	1.32	72	0.00	0	6	4	5	40	1	3	
171	50.90	52.43	1.53	1.14	75	0.00	0	5	5	4	40	3	3	30 cm H=2
171	52.43	53.95	1.52	1.33	87	0.00	0	5	4	5	50	1	3	5 cm redrilled core
171	53.95	57.00	3.05	2.96	97	0.20	7	7	4	4	50	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
171	57.00	60.05	3.05	3.00	98	2.79	91	15	4	5	3	1	4	
171	60.05	63.09	3.04	2.54	84	2.15	71	12	4	5	15	1	3	
171	63.09	66.14	3.05	3.17	104	2.95	97	14	4	5	6	1	3	
171	66.14	69.19	3.05	3.15	103	3.15	103	15	5	6	5	1	3	
171	69.19	72.24	3.05	3.05	100	2.90	95	14	5	6	6	3	3	3 13 cm H=2, 25 cm fract parallel to c.a.
171	72.24	75.29	3.05	2.85	93	2.47	81	13	4	6	8	3	4	
171	75.29	78.33	3.04	2.82	93	2.42	80	10	5	6	20	1	3	
171	78.33	81.38	3.05	3.16	104	3.16	104	15	4	6	4	3	2	
171	81.38	84.43	3.05	3.02	99	2.96	97	13	5	6	9	1	3	3 8 cm H=2, gouge on fractures
171	84.43	87.48	3.05	2.92	96	2.92	96	15	5	6	0			
171	87.48	90.53	3.05	2.98	98	2.98	98	15	5	6	0			
171	90.53	93.57	3.04	3.02	99	3.02	99	15	5	6	0			15 cm H=2
171	93.57	96.62	3.05	3.08	101	3.08	101	15	5	6	2	1	3	
171	96.62	99.67	3.05	3.00	98	3.00	98	15	5	6	0			
171	99.67	102.72	3.05	3.07	101	3.07	101	15	5	6	1	1	2	
171	102.72	105.77	3.05	3.03	99	3.03	99	15	5	6	2	1	3	3 51 cm core with gouge
171	105.77	108.81	3.04	3.02	99	3.02	99	15	3	6	1	1	2	2 50% core gouge, H=2
171	108.81	111.86	3.05	2.90	95	2.90	95	15	4	6	0			healed fault
171	111.86	114.91	3.05	3.42	112	3.42	112	15	5	6	0			
171	114.91	117.96	3.05	2.61	86	2.61	86	15	5	6	2	1	3	
171	117.96	121.01	3.05	3.02	99	3.02	99	15	5	6	3	1	3	
171	121.01	124.05	3.04	2.85	94	2.85	94	15	4	6	1	3	4	
171	124.05	127.10	3.05	2.94	96	2.94	96	14	4	6	6	3	3	3 45 cm healed fault
171	127.10	130.15	3.05	2.96	97	2.96	97	15	4	6	1	1	3	
171	130.15	133.20	3.05	2.97	97	2.97	97	15	5	6	0			
171	133.20	136.25	3.05	2.98	98	2.98	98	15	4	6	1	1	3	
171	136.25	139.29	3.04	2.98	98	2.98	98	15	4	6	3	3	3	
171	139.29	142.34	3.05	2.98	98	2.98	98	15	3	6	1	1	3	3 1.2 m healed fault
171	142.34	145.39	3.05	2.95	97	2.54	83	13	4	6	10	1	3	3 20 cm broken core, 40 cm H=2
171	145.39	148.44	3.05	3.02	99	3.02	99	15	4	6	2	3	3	
171	148.44	151.49	3.05	3.08	101	3.08	101	15	4	6	2	1	3	
171	151.49	154.53	3.04	2.95	97	2.95	97	15	5	6	3	1	2	
171	154.53	157.58	3.05	3.03	99	3.03	99	15	4	6	2	1	2	
171	157.58	160.63	3.05	2.83	93	2.83	93	15	5	6	1	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
171	264.26	267.31	3.05	3.05	100	3.05	100	15	5	6	3	1	2	
171	267.31	270.36	3.05	2.99	98	2.99	98	15	5	6	0			
171	270.36	273.41	3.05	2.87	94	2.87	94	15	5	6	0			
171	273.41	276.45	3.04	2.99	98	2.94	97	15	5	6	2	1	2	
171	276.45	279.50	3.05	3.20	105	3.00	98	15	5	6	5	1	2	
171	279.50	282.55	3.05	2.94	96	2.94	96	15	5	6	2	3	2	
171	282.55	285.60	3.05	2.96	97	2.96	97	15	5	6	2	1	2	
171	285.60	288.65	3.05	3.02	99	3.02	99	15	5	6	1	1	2	
171	288.65	291.69	3.04	3.01	99	3.01	99	15	5	6	0			5 cm redrilled core
171	291.69	294.74	3.05	3.19	105	3.19	105	15	5	6	5	1	2	
171	294.74	297.79	3.05	2.84	93	2.64	87	14	5	6	6	1	3	
171	297.79	300.84	3.05	3.02	99	2.90	95	15	4	6	5	1	3	
171	300.84	303.89	3.05	2.83	93	2.58	85	14	5	6	8	1	3	
171	303.89	306.93	3.04	2.92	96	2.72	89	15	5	6	4	1	3	
171	306.93	309.98	3.05	3.10	102	3.10	102	15	5	6	1	3	2	
171	309.98	313.03	3.05	2.87	94	2.87	94	15	5	6	3	1	2	5 cm redrilled core
171	313.03	316.08	3.05	2.75	90	2.75	90	15	4	6	2	3	4	
171	316.08	319.13	3.05	2.93	96	2.50	82	10	5	6	20	1	3	10% broken core
171	319.13	322.17	3.04	2.89	95	2.69	88	15	5	6	3	1	2	20 cm H=2
171	322.17	325.22	3.05	3.21	105	3.21	105	15	5	6	1	1	4	
171	325.22	328.27	3.05	3.13	103	3.13	103	14	5	6	6	1	3	40 cm H=2
171	328.27	331.32	3.05	2.83	93	1.25	41	10	4	6	20	1	2	
171	331.32	334.37	3.05	3.07	101	3.07	101	15	5	6	3	1	3	
171	334.37	337.41	3.04	2.97	98	2.97	98	15	4	6	1	1	3	
171	337.41	340.46	3.05	2.76	90	2.76	90	15	5	6	1	1	3	
171	340.46	343.51	3.05	3.03	99	2.98	98	15	4	6	5	1	3	gouge on fractures
171	343.51	346.56	3.05	3.13	103	3.13	103	15	4	6	1	1	4	30 cm redrilled core
171	346.56	349.61	3.05	2.93	96	2.93	96	15	4	6	1	3	3	gouge on fractures
171	349.61	352.65	3.04	3.10	102	3.10	102	15	4	6	4	1	3	gouge on fractures
171	352.65	355.70	3.05	2.96	97	2.59	85	13	3	6	10	3	3	gouge on fractures
171	355.70	358.75	3.05	3.06	100	2.13	70	12	3	6	13	1	2	23 cm gouge H=2
171	358.75	361.80	3.05	2.95	97	2.55	84	15	4	6	4	3	3	20 cm H=2
171	361.80	364.85	3.05	3.05	100	3.00	98	15	5	6	1	5	4	5 cm fault gouge H=1
171	364.85	367.89	3.04	3.07	101	3.07	101	15	5	6	0			

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
171	367.89	370.94	3.05	3.02	99	2.95	97	15	4	6	4	3	4	4 fracture gouge, slip plane 85 to c.a.
171	370.94	373.99	3.05	2.97	97	2.69	88	14	5	6	6	1	3	20 cm broken core, 20 cm healed fault
171	373.99	377.04	3.05	3.00	98	3.00	98	15	5	6	1	1	3	
171	377.04	380.09	3.05	2.91	95	2.91	95	15	4	6	2	1	3	gouge on fractures
171	380.09	383.13	3.04	3.00	99	2.80	92	15	4	6	4	1	3	
171	383.13	386.18	3.05	2.93	96	2.88	94	15	4	6	2	1	3	
171	386.18	389.23	3.05	3.03	99	2.57	84	12	4	6	11	1	3	20 cm fault gouge H=2
171	389.23	392.28	3.05	3.02	99	3.02	99	15	5	6	4	1	3	
171	392.28	395.33	3.05	3.01	99	3.01	99	14	5	6	6	3	3	
171	395.33	398.37	3.04	2.96	97	2.96	97	15	5	6	3	3	3	
171	398.37	401.42	3.05	2.95	97	2.95	97	15	5	6	3	3	3	
171	401.42	404.47	3.05	3.02	99	3.02	99	15	5	6	5	3	4	
171	404.47	407.52	3.05	3.04	100	3.04	100	14	5	6	6	1	3	
171	407.52	410.57	3.05	3.02	99	3.02	99	14	5	6	7	1	3	
171	410.57	413.61	3.04	2.87	94	2.82	93	14	5	6	5	3	3	5 cm fault gouge at 411.49 m
171	413.61	416.66	3.05	3.05	100	3.05	100	15	5	6	1	3	3	gouge on fractures
171	416.66	419.71	3.05	3.20	105	3.20	105	14	5	6	6	1	3	
171	419.71	422.76	3.05	2.98	98	2.98	98	15	5	6	3	1	3	5 cm redrilled core, gouge at 10 to c. a.
171	422.76	425.81	3.05	2.82	92	2.82	92	15	5	6	2	1	3	
171	425.81	428.85	3.04	2.95	97	2.88	95	14	5	6	5	3	3	
172	4.27	7.32	3.05	1.95	64	0.40	13	12	5	5	10	1	3	iron stained, weathered
172	7.32	8.23	0.91	0.85	93	0.85	93	15	4	5	1	5	3	10% healed gouge
172	8.23	11.28	3.05	3.05	100	2.83	93	14	4	5	7	3	3	10% healed gouge
172	11.28	13.11	1.83	1.83	100	1.37	75	12	5	6	11	1	3	
172	13.11	14.33	1.22	0.87	71	0.70	57	9	5	6	9	1	3	calcite on fractures
172	14.33	17.37	3.04	3.02	99	2.52	83	12	5	6	16	1	2	calcite on fractures
172	17.37	19.81	2.44	2.30	94	1.98	81	12	5	6	15	1	3	last 30 cm broken, minor gouge
172	19.81	22.86	3.05	2.95	97	2.61	86	13	4	6	12	3	3	minor gouge on fractures
172	22.86	24.69	1.83	1.77	97	1.77	97	15	5	6	1	3	3	calcite on fractures
172	24.69	26.52	1.83	1.77	97	1.72	94	14	5	6	4	3	3	calcite on fractures
172	26.52	29.57	3.05	3.09	101	2.95	97	15	4	5	3	1	2	27.30 m - 3 cm shear with gouge
172	29.57	32.61	3.04	2.66	88	1.37	45	10	5	6	24	3	3	80% broken, 10% gouge
172	32.61	35.66	3.05	2.70	89	1.20	39	10	5	6	26	1	2	90% broken
172	35.66	38.71	3.05	2.85	93	1.01	33	9	5	6	31	3	3	80% broken

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
172	38.71	41.76	3.05	3.30	108	3.25	107	15	5	6	5	1	3	pyrite on fractures
172	41.76	44.81	3.05	3.02	99	2.76	90	15	5	6	5	3	3	
172	44.81	47.85	3.04	3.07	101	2.91	96	13	5	6	11	1	3	
172	47.85	50.90	3.05	2.92	96	2.80	92	14	4	6	8	1	3	pyrite on fractures
172	50.90	53.95	3.05	2.44	80	1.99	65	10	5	6	24	3	3	pyrite on fractures
172	53.95	57.00	3.05	3.26	107	2.14	70	9	5	6	35	3	3	45% broken
172	57.00	60.05	3.05	2.75	90	0.40	13	7	5	6	45	1	3	100% broken, calcite on fractures
172	60.05	63.09	3.04	2.70	89	0.98	32	7	5	6	45	3	3	100% broken
172	63.09	66.14	3.05	2.55	84	0.15	5	7	4	6	45	1	3	pyrite on fractures
172	66.14	67.97	1.83	2.00	109	1.40	77	9	5	6	25	3	3	minor gouge on fractures
172	67.97	70.41	2.44	2.44	100	0.42	17	10	4	5	20	3	3	minor gouge and calcite on fractures
172	70.41	73.46	3.05	1.22	40	0.40	13	4	3	5	50	3	3	65 cm H=1 (fault gouge)
172	73.46	76.20	2.74	2.20	80	1.68	61	7	2	5	30	5	3	100% fault gouge
172	76.20	78.94	2.74	1.10	40	0.35	13	5	2	5	40	5	3	100% fault gouge
172	78.94	81.38	2.44	1.50	61	0.33	14	5	4	5	40	3	3	broken rock with 10% gouge
172	81.38	84.43	3.05	1.97	65	0.15	5	7	5	6	35	1	3	pyrite on fractures
172	84.43	87.48	3.05	2.05	67	0.00	0	6	5	6	50	3	3	broken rock with 20% gouge
172	87.48	90.53	3.05	2.98	98	2.22	73	10	5	6	25	1	3	30% broken rock
172	90.53	93.57	3.04	3.07	101	3.01	99	15	5	6	4	1	3	gouge on fractures
172	93.57	96.62	3.05	3.01	99	2.92	96	15	5	6	3	3	3	gypsum on fractures
172	96.62	99.67	3.05	3.08	101	3.03	99	15	5	6	5	1	3	gypsum on fractures
172	99.67	102.72	3.05	3.07	101	2.65	87	14	5	6	10	3	3	pyrite on fractures
172	102.72	105.77	3.05	3.05	100	2.90	95	14	5	6	7	3	3	gypsum & pyrite on fractures
172	105.77	108.81	3.04	2.91	96	2.91	96	15	5	6	3	5	3	gypsum on fractures
172	108.81	111.86	3.05	3.05	100	3.05	100	15	5	6	2	1	3	pyrite on fractures
172	111.86	114.91	3.05	2.95	97	2.56	84	14	5	6	9	1	3	minor gouge on fractures
172	114.91	117.96	3.05	3.02	99	2.54	83	13	5	6	11	1	3	calcite on fractures
172	117.96	121.01	3.05	3.05	100	3.05	100	15	5	6	3	3	3	
172	121.01	124.05	3.04	3.04	100	2.11	69	14	4	5	10	3	3	123.30 m healed shr/gouge 10 to c.a.
172	124.05	127.10	3.05	3.05	100	3.05	100	15	3	5	2	3	3	
172	127.10	130.15	3.05	3.00	98	2.76	90	14	5	6	9	3	3	
172	130.15	133.20	3.05	2.82	92	2.76	90	14	5	6	8	5	3	131.3-132.85 healed shear 10 to c.a.
172	133.20	136.25	3.05	3.05	100	2.25	74	9	4	6	35	3	3	50% broken core with gouge
172	136.25	139.29	3.04	3.04	100	2.41	79	9	4	6	35	5	3	53 cm broken core wiyh gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
172	139.29	142.34	3.05	3.08	101	2.93	96	15	3	6	4	1	3	1.15 m fault gouge at 5-10 to c.a.
172	142.34	145.39	3.05	3.02	99	2.79	91	15	3	6	5	1	3	30% gouge H=2
172	145.39	148.44	3.05	2.94	96	2.56	84	14	4	6	6	1	3	5% fault gouge H=2
172	148.44	151.49	3.05	3.13	103	3.01	99	14	5	6	7	1	3	
172	151.49	154.53	3.04	2.99	98	2.99	98	15	5	6	3	1	3	
172	154.53	157.58	3.05	3.02	99	3.02	99	15	5	6	2	1	3	2 cm fault gouge at 45 to c.a.
172	157.58	160.63	3.05	2.99	98	2.63	86	15	5	6	4	1	3	gouge on fractures
172	160.63	163.68	3.05	3.01	99	3.01	99	15	5	6	2	1	3	
172	163.68	166.73	3.05	3.06	100	2.71	89	14	5	6	9	1	3	gouge on fractures
172	166.73	169.77	3.04	3.09	102	3.09	102	15	5	6	2	1	3	
172	169.77	172.82	3.05	2.99	98	2.64	87	14	5	6	5	1	3	
172	172.82	175.87	3.05	3.11	102	2.98	98	15	5	6	4	1	3	3 cm fault gouge H=2
172	175.87	178.92	3.05	3.05	100	2.67	88	15	5	6	4	1	3	gouge on fractures
172	178.92	181.97	3.05	2.96	97	2.85	93	15	5	6	2	1	3	
172	181.97	185.01	3.04	3.04	100	3.04	100	15	5	6	3	1	3	gouge on fractures
172	185.01	188.06	3.05	3.09	101	3.09	101	15	5	6	2	1	3	gypsum on fractures
172	188.06	191.11	3.05	2.75	90	2.41	79	13	5	6	11	1	3	pyrite on factures,2cm mud seam
172	191.11	194.16	3.05	3.20	105	3.11	102	15	5	6	4	3	3	calcite on fractures
172	194.16	197.21	3.05	2.85	93	2.25	74	13	5	6	11	3	3	calcite on fractures
172	197.21	200.25	3.04	3.04	100	1.72	57	10	5	6	21	5	3	fractures parallel to c.a.
172	200.25	203.30	3.05	3.11	102	2.95	97	15	5	6	5	1	2	
172	203.30	206.35	3.05	3.05	100	3.05	100	14	5	6	6	1	3	gypsum on fractures
172	206.35	209.40	3.05	3.01	99	2.92	96	14	5	6	6	3	3	minor gouge on fractures
172	209.40	212.45	3.05	3.03	99	2.75	90	14	5	6	8	1	3	
172	212.45	215.49	3.04	2.89	95	2.62	86	14	5	6	7	1	2	minor gouge on fractures
172	215.49	218.54	3.05	3.10	102	2.92	96	15	5	6	3	3	3	
172	218.54	221.59	3.05	3.00	98	3.00	98	15	5	6	5	3	3	
172	221.59	224.64	3.05	2.98	98	2.92	96	14	5	6	5	3	3	pyrite on fractures
172	224.64	227.69	3.05	3.05	100	2.78	91	14	5	6	7	3	3	pyrite on fractures
172	227.69	230.73	3.04	3.04	100	2.92	96	15	5	6	5	3	3	
172	230.73	233.78	3.05	3.00	98	2.68	88	14	5	6	6	3	1	weak slicks (rake 45)
172	233.78	236.83	3.05	3.08	101	3.00	98	15	5	6	5	3	3	gouge on fractures
172	236.83	239.88	3.05	2.91	95	2.91	95	15	5	6	2	3	3	
172	239.88	242.93	3.05	2.85	93	1.60	52	9	5	6	30	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
172	242.93	245.97	3.04	3.12	103	2.65	87	14	5	6	6	3	3	pyrite on fractures
172	245.97	249.02	3.05	2.97	97	2.88	94	15	5	6	3	1	3	pyrite on fractures
172	249.02	252.07	3.05	2.82	92	2.30	75	14	5	6	9	1	2	calcite on fractures
172	252.07	255.12	3.05	3.03	99	2.87	94	15	5	6	4	3	3	
172	255.12	258.17	3.05	3.16	104	3.01	99	15	5	6	3	3	3	
172	258.17	261.21	3.04	3.17	104	3.11	102	14	5	6	6	1	2	minor gouge on fractures
173	0.00	10.97	10.97	0.64	6	0.15	1	5	3	3	50	5	3	broken rock with gouge
173	10.97	13.72	2.75	0.73	27	0.00	0	5	3	3	50	5	3	broken rock with gouge
173	13.72	16.15	2.43	2.40	99	0.00	0	5	3	4	50	5	3	broken rock with gouge
173	16.15	18.90	2.75	1.26	46	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	18.90	21.34	2.44	0.72	30	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	21.34	23.47	2.13	0.42	20	0.00	0	5	3	4	50	5	3	broken rock with gouge
173	23.47	26.52	3.05	0.93	30	0.00	0	5	3	4	50	5	3	broken rock with gouge
173	26.52	29.57	3.05	1.93	63	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	29.57	30.48	0.91	0.59	65	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	30.48	32.00	1.52	1.18	78	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	32.00	35.05	3.05	1.90	62	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	35.05	36.27	1.22	1.19	98	0.13	11	6	3	4	50	5	3	broken rock with gouge
173	36.27	37.49	1.22	1.20	98	0.21	17	6	3	4	50	5	3	broken rock with gouge
173	37.49	38.40	0.91	0.51	56	0.12	13	6	3	4	50	5	3	broken rock with gouge
173	38.40	39.62	1.22	1.20	98	0.20	16	6	3	4	50	5	3	broken rock with gouge
173	39.62	41.15	1.53	1.21	79	0.11	7	6	3	4	50	5	3	broken rock with gouge
173	41.15	41.76	0.61	0.52	85	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	41.76	42.67	0.91	0.87	96	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	42.67	43.59	0.92	0.78	85	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	43.59	44.81	1.22	0.82	67	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	44.81	47.85	3.04	0.85	28	0.00	0	6	3	4	50	5	3	broken rock with gouge
173	47.85	49.35	1.50	0.65	43	0.20	13	6	3	4	50	5	3	mainly gouge
173	49.35	50.90	1.55	0.73	47	0.00	0	6	3	4	50	5	3	mainly gouge
173	50.90	52.12	1.22	1.10	90	0.00	0	6	3	4	50	5	3	mainly gouge
173	52.12	52.73	0.61	0.35	57	0.00	0	6	3	4	50	5	3	mainly gouge
173	52.73	57.00	4.27	1.40	33	0.00	0	2	2	6	50	5	3	broken rock with gouge
173	57.00	59.13	2.13	0.00	0	0.00	0							sludge samples, triconing
173	59.13	62.18	3.05	0.00	0	0.00	0							sludge samples, triconing

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
173	62.18	65.23	3.05	0.00	0	0.00	0							sludge samples, triconing
173	65.23	68.28	3.05	0.00	0	0.00	0							sludge samples, triconing
173	68.28	71.32	3.04	0.00	0	0.00	0							sludge samples, triconing
173	71.32	73.46	2.14	0.00	0	0.00	0							sludge samples, triconing
173	73.46	75.39	1.93	1.46	76	1.46	76	15	3	6	1	1	3	15 cm gouge, H=1
173	75.39	78.33	2.94	3.08	105	3.08	105	15	3	6	1	1	3	
173	78.33	81.38	3.05	2.94	96	2.57	84	15	3	6	4	1	3	8 cm gouge, H=1
173	81.38	84.43	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
173	84.43	87.48	3.05	3.05	100	2.98	98	15	3	6	3	1	3	gypsum on fractures
173	87.48	90.53	3.05	3.01	99	3.01	99	15	3	6	1	1	3	
173	90.53	92.96	2.43	2.43	100	1.42	58	13	3	6	8	1	3	gypsum on fractures
173	92.96	96.01	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gypsum, gouge on fractures
173	96.01	98.15	2.14	2.08	97	2.08	97	15	3	6	1	1	3	
173	98.15	99.67	1.52	1.46	96	1.46	96	15	3	6	1	1	3	gypsum on fractures
173	99.67	102.72	3.05	2.93	96	2.69	88	15	3	6	4	1	3	
173	102.72	105.77	3.05	3.01	99	3.01	99	15	3	6	3	1	3	
173	105.77	108.81	3.04	3.03	100	3.03	100	15	3	6	2	1	3	
173	108.81	111.86	3.05	3.08	101	3.00	98	15	3	6	3	1	3	25 cm of H=2 (healed gouge)
173	111.86	114.91	3.05	2.64	87	2.07	68	13	3	6	9	1	3	65 cm of H=2 (healed gouge)
173	114.91	117.63	2.72	2.72	100	2.13	78	14	3	6	6	1	3	35 cm of H=2 (healed gouge)
173	117.63	118.87	1.24	0.96	77	0.63	51	10	3	6	8	1	3	10% broken core
173	118.87	121.01	2.14	2.14	100	1.67	78	14	3	6	5	1	3	gypsum on fractures
173	121.01	122.83	1.82	1.46	80	0.94	52	10	3	6	10	1	3	15% broken core
173	122.83	124.05	1.22	1.22	100	1.10	90	14	3	6	3	1	3	
173	124.05	127.10	3.05	2.75	90	2.48	81	7	3	6	8	1	3	last 20 cm broken core with gouge
173	127.10	130.15	3.05	3.08	101	2.93	96	15	3	6	5	1	3	3cm fault gouge at 45 to c.a.
173	130.15	133.20	3.05	2.95	97	2.71	89	15	3	6	4	1	3	40 cm healed fault H=2
173	133.20	136.25	3.05	3.03	99	3.00	98	15	3	6	3	1	3	45 cm healed gouge with pyrite H=2
173	136.25	139.29	3.04	2.86	94	2.65	87	15	3	6	4	1	3	15 cm healed gouge
173	139.29	142.34	3.05	3.05	100	3.00	98	15	3	6	4	1	3	gouge on fractures
173	142.34	145.39	3.05	2.82	92	2.58	85	14	3	6	5	2	3	gouge on fractures
173	145.39	148.44	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
173	148.44	150.57	2.13	1.72	81	0.71	33	10	3	6	15	5	3	25% broken core with gouge H=2
173	150.57	153.62	3.05	2.76	90	2.76	90	15	3	6	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery m.	Recovery %	RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To			Lgth	m.								%
173	153.62	154.53	0.91	1.20	132	1.20	132	15	3	6	1	1	3	
173	154.53	157.58	3.05	3.07	101	2.96	97	15	3	6	3	1	3	
173	157.58	160.63	3.05	3.05	100	2.76	90	14	3	6	6	1	3	40 cm healed gouge H=2
173	160.63	163.68	3.05	3.09	101	2.89	95	15	3	6	3	1	3	
173	163.68	166.73	3.05	2.99	98	2.58	85	14	3	6	5	1	3	
173	166.73	169.77	3.04	3.10	102	3.03	100	15	3	6	3	1	3	gouge on fractures
173	169.77	172.82	3.05	2.85	93	2.80	92	15	3	6	4	1	3	
173	172.82	175.87	3.05	3.01	99	3.01	99	15	3	6	4	1	3	
173	175.87	178.92	3.05	3.12	102	3.00	98	15	3	6	3	1	3	gouge on fractures
173	178.92	181.97	3.05	2.92	96	2.86	94	15	3	6	2	1	3	
173	181.97	185.01	3.04	3.04	100	3.04	100	15	3	6	3	1	3	2cm fault gouge
173	185.01	188.06	3.05	3.02	99	3.02	99	15	3	6	1	1	3	
173	188.06	191.11	3.05	3.07	101	3.02	99	15	3	6	3	1	3	
173	191.11	194.16	3.05	2.98	98	2.08	68	14	3	6	7	2	3	gypsum on fractures
173	194.16	197.21	3.05	3.13	103	2.85	93	13	3	6	10	1	3	gouge on fractures
173	197.21	200.25	3.04	3.19	105	2.83	93	14	3	6	5	1	3	
173	200.25	203.30	3.05	3.10	102	2.99	98	15	3	6	2	1	3	
173	203.30	206.35	3.05	2.83	93	2.83	93	15	3	6	3	1	3	
173	206.35	209.40	3.05	3.09	101	2.94	96	14	3	6	5	1	3	gouge on fractures
173	209.40	212.45	3.05	3.01	99	2.89	95	14	3	6	6	1	3	gouge on fractures
173	212.45	215.49	3.04	3.29	108	3.15	104	15	3	6	4	1	3	16cm healed fault gouge at 40 to c.a.
173	215.49	218.54	3.05	2.66	87	2.21	72	12	3	6	14	1	3	5%broken core with gouge
173	218.54	221.59	3.05	3.15	103	3.06	100	15	4	6	4	1	3	
173	221.59	224.64	3.05	2.82	92	2.38	78	13	3	6	12	1	3	5 cm fault 45-50 to c.a., 5% broken core
173	224.64	227.69	3.05	3.05	100	2.92	96	15	3	6	4	1	3	gouge on fractures
173	227.69	230.73	3.04	3.01	99	3.01	99	15	3	6	3	1	3	gouge on fractures
173	230.73	233.78	3.05	3.05	100	2.31	76	13	3	6	11	2	3	2cm fault gouge, gouge on fractures
173	233.78	236.83	3.05	3.09	101	2.39	78	14	4	6	5	1	3	
173	236.83	238.35	1.52	1.40	92	0.79	52	10	3	6	13	5	3	10%broken core with gouge
173	238.35	239.88	1.53	1.60	105	1.60	105	15	3	6	1	1	3	
173	239.88	242.93	3.05	3.05	100	2.64	87	15	3	6	4	1	3	gouge on fractures
173	242.93	245.97	3.04	3.08	101	3.02	99	15	3	6	2	1	3	
173	245.97	249.02	3.05	2.99	98	2.61	86	15	3	6	4	1	3	
173	249.02	252.07	3.05	3.09	101	2.73	90	14	3	6	6	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
173	252.07	255.12	3.05	2.94	96	2.28	75	14	3	6	6	1	2	
173	255.12	258.17	3.05	2.97	97	2.41	79	14	3	6	8	1	3	gouge on fractures
173	258.17	261.21	3.04	2.93	96	2.06	68	12	3	6	15	1	3	45 cm gouge mat'l at 40-50 to c.a.
173	261.21	264.26	3.05	3.05	100	2.84	93	15	3	6	3	1	3	15 cm fault gouge at 35 to c.a.
173	264.26	267.31	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
173	267.31	270.36	3.05	3.00	98	2.57	84	14	3	6	6	1	3	24cm H=2
173	270.36	273.41	3.05	2.99	98	2.76	90	15	3	6	4	1	3	
173	273.41	276.45	3.04	3.09	102	2.81	92	15	4	6	4	1	2	dike
173	276.45	279.50	3.05	3.00	98	2.51	82	14	3	6	5	1	3	gouge on fractures
173	279.50	282.55	3.05	2.45	80	2.21	72	13	3	6	10	5	3	25 cm gouge H=2
173	282.55	283.77	1.22	0.67	55	0.22	18	6	2	6	20	5	3	50% gouge
173	283.77	284.68	0.91	0.25	27	0.00	0	2	2	6	30	5	3	80% broken rock with gouge
173	284.68	285.61	0.93	0.70	75	0.00	0	13	2	6	30	5	3	100% broken rock with gouge
173	285.61	288.65	3.04	2.02	66	1.21	40	9	3	6	20	5	3	22cm gouge H=2
173	288.65	291.69	3.04	2.89	95	2.71	89	14	3	6	6	1	3	
173	291.69	294.74	3.05	3.17	104	3.03	99	15	3	6	2	1	3	
173	294.74	297.79	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
173	297.79	300.84	3.05	3.07	101	2.92	96	15	3	6	4	1	3	gypsum on fractures
173	300.84	303.89	3.05	2.92	96	2.53	83	14	3	6	5	1	3	3 cm gouge H=2
173	303.89	306.93	3.04	3.08	101	3.08	101	15	3	6	2	1	3	
173	306.93	309.98	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
173	309.98	313.03	3.05	3.05	100	3.00	98	15	3	6	3	1	3	
173	313.03	316.08	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
173	316.08	319.13	3.05	2.97	97	2.97	97	15	3	6	1	1	3	
173	319.13	322.17	3.04	2.94	97	2.94	97	15	3	6	2	1	3	gypsum on fractures
173	322.17	325.22	3.05	3.05	100	2.79	91	15	3	6	4	1	3	
173	325.22	328.27	3.05	3.11	102	3.05	100	15	3	6	2	1	3	gypsum on fractures
173	328.27	331.32	3.05	3.14	103	3.14	103	15	3	6	3	1	3	
173	331.32	334.37	3.05	3.12	102	3.12	102	15	3	6	2	1	3	
173	334.37	337.41	3.04	3.10	102	3.00	99	15	3	6	3	1	3	gypsum on fractures
173	337.41	340.46	3.05	2.99	98	2.99	98	15	3	6	3	1	3	
173	340.46	343.51	3.05	3.02	99	3.02	99	15	3	6	2	1	3	minor gouge on fractures
173	343.51	346.56	3.05	2.97	97	2.97	97	15	3	6	3	1	3	
173	346.56	349.61	3.05	2.95	97	2.95	97	15	3	6	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
174	10.06	11.28	1.22	0.63	52	0.00	0	2	3	3	40	5	3	iron staining with gouge
174	11.28	14.33	3.05	1.78	58	0.00	0	6	3	3	50	5	4	iron staining with gouge
174	14.33	17.37	3.04	2.04	67	0.66	22	7	3	4	30	3	4	100% gouge
174	17.37	20.42	3.05	2.81	92	2.13	70	12	2	4	13	3	3	37 cm H=4
174	20.42	23.47	3.05	2.91	95	2.25	74	15	3	5	10	1	3	
174	23.47	26.52	3.05	2.91	95	2.68	88	14	4	5	6	1	3	
174	26.52	29.57	3.05	2.95	97	2.89	95	14	5	6	7	1	3	undulating fracture parallel to c.a.
174	29.57	32.61	3.04	2.99	98	2.56	84	13	4	6	9	1	3	healed fault at 20 to c.a.
174	32.61	35.66	3.05	3.04	100	2.53	83	13	4	5	13	3	3	gouge on fractures, fault 20 to c.a.
174	35.66	38.71	3.05	2.97	97	2.79	91	14	4	6	6	1	3	
174	38.71	41.76	3.05	3.02	99	2.67	88	14	4	6	8	3	3	
174	41.76	44.81	3.05	2.95	97	2.37	78	13	5	6	10	1	3	gouge on fractures
174	44.81	47.85	3.04	3.05	100	3.05	100	14	4	6	6	3	3	
174	47.85	50.90	3.05	2.97	97	2.59	85	13	3	6	12	1	3	healed fault
174	50.90	53.95	3.05	3.00	98	3.00	98	14	4	6	5	3	3	
174	53.95	57.00	3.05	2.96	97	2.35	77	13	5	6	11	3	3	gouge on fractures
174	57.00	60.05	3.05	3.02	99	2.67	88	14	4	6	7	1	3	
174	60.05	63.09	3.04	2.97	98	2.70	89	14	4	6	7	1	3	
174	63.09	66.14	3.05	2.94	96	2.85	93	14	4	6	6	1	3	
174	66.14	69.19	3.05	2.80	92	1.94	64	10	4	6	25	1	3	
174	69.19	72.24	3.05	3.02	99	2.24	73	14	4	6	8	3	4	1.08 m healed fault
174	72.24	75.29	3.05	3.08	101	2.64	87	14	4	6	9	3	3	27 cm healed fault at 30 to c.a.
174	75.29	78.33	3.04	3.02	99	2.65	87	14	4	6	9	1	3	
174	78.33	81.38	3.05	2.97	97	2.86	94	14	4	6	6	1	3	
174	81.38	84.43	3.05	3.02	99	3.02	99	14	4	6	5	3	3	
174	84.43	87.48	3.05	2.99	98	2.89	95	14	4	6	5	1	3	
174	87.48	90.53	3.05	2.89	95	2.58	85	12	3	6	15	3	4	
174	90.53	93.57	3.04	3.12	103	3.12	103	15	4	6	3	1	3	
174	93.57	96.62	3.05	2.99	98	2.99	98	15	4	6	4	1	3	
174	96.62	99.67	3.05	2.94	96	2.94	96	15	4	6	2	1	2	
174	99.67	102.72	3.05	3.03	99	3.03	99	15	4	6	1	3	4	
174	102.72	105.77	3.05	3.00	98	3.00	98	15	5	6	1	1	2	healed fractures
174	105.77	108.81	3.04	3.02	99	3.02	99	15	4	6	3	1	3	
174	108.81	111.86	3.05	3.08	101	2.84	93	14	4	6	5	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
174	111.86	114.91	3.05	3.04	100	3.04	100	15	4	6	3	1	2	gouge on fractures
174	114.91	117.96	3.05	2.96	97	2.66	87	14	4	6	6	1	3	
174	117.96	121.01	3.05	2.87	94	2.63	86	13	5	6	9	1	3	
174	121.01	124.05	3.04	3.00	99	3.00	99	15	5	6	3	1	3	
174	124.05	127.10	3.05	3.03	99	2.90	95	14	5	6	5	1	3	
174	127.10	130.15	3.05	2.94	96	2.94	96	15	5	6	4	3	3	
174	130.15	133.20	3.05	3.01	99	3.01	99	15	5	6	4	3	3	
174	133.20	136.25	3.05	2.96	97	2.87	94	14	5	6	5	1	3	
174	136.25	139.29	3.04	3.02	99	3.02	99	15	5	6	3	3	3	3 fracture parallel to c.a.
174	139.29	142.34	3.05	2.94	96	2.94	96	15	5	6	3	3	3	3 gouge on fractures
174	142.34	145.39	3.05	3.05	100	2.94	96	14	4	6	5	1	3	
174	145.39	148.44	3.05	3.02	99	3.02	99	15	4	6	1	3	4	
174	148.44	151.49	3.05	3.02	99	3.02	99	15	5	6	4	1	3	
174	151.49	154.53	3.04	3.04	100	3.04	100	15	5	6	3	1	3	
174	154.53	157.58	3.05	3.02	99	3.02	99	15	5	6	4	1	3	
174	157.58	160.63	3.05	2.97	97	2.97	97	15	5	6	2	3	3	3 fracture parallel to c.a.
174	160.63	163.68	3.05	2.92	96	2.92	96	15	4	6	3	1	3	3 gouge on fractures
174	163.68	166.73	3.05	2.89	95	2.89	95	14	5	6	5	1	3	
174	166.73	169.77	3.04	3.00	99	3.00	99	15	5	6	3	3	3	
174	169.77	172.82	3.05	3.03	99	2.96	97	14	5	6	6	1	3	3 gouge on fractures
174	172.82	175.87	3.05	2.91	95	2.44	80	14	5	6	8	1	3	
174	175.87	178.92	3.05	2.96	97	2.92	96	15	4	6	3	1	3	
174	178.92	181.97	3.05	2.97	97	2.75	90	13	4	6	12	1	3	
174	181.97	185.01	3.04	3.08	101	2.76	91	14	4	6	8	1	3	
174	185.01	188.06	3.05	2.97	97	1.59	52	12	5	6	16	1	3	
174	188.06	191.11	3.05	2.86	94	2.48	81	14	5	6	8	1	3	
174	191.11	194.16	3.05	3.22	106	2.88	94	14	5	6	7	3	3	
174	194.16	197.21	3.05	2.99	98	2.61	86	14	5	6	6	1	3	
174	197.21	200.25	3.04	2.81	92	2.67	88	14	5	6	5	1	3	
174	200.25	203.30	3.05	3.12	102	3.07	101	14	5	6	5	1	3	
174	203.30	206.35	3.05	2.95	97	2.95	97	15	5	6	3	1	3	3 fracture parallel to c.a.
174	206.35	209.40	3.05	2.88	94	2.88	94	15	5	6	3	1	3	2 gouge on fractures
174	209.40	212.45	3.05	2.99	98	2.99	98	14	5	6	6	1	3	3 gouge on fractures
174	212.45	215.49	3.04	2.92	96	2.92	96	15	5	6	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
174	215.49	218.54	3.05	3.16	104	3.16	104	15	5	6	3	1	3	
174	218.54	221.59	3.05	2.91	95	2.01	66	12	5	6	15	1	3	gouge on fractures
174	221.59	224.64	3.05	3.15	103	2.26	74	13	5	6	13	1	3	gouge on fractures
174	224.64	227.69	3.05	2.93	96	2.58	85	14	5	6	8	1	3	gouge on fractures
174	227.69	230.73	3.04	3.06	101	2.48	82	13	5	6	11	1	3	gouge on fractures
174	230.73	233.78	3.05	3.01	99	2.76	90	13	5	6	12	1	3	gouge on fractures
174	233.78	236.83	3.05	3.19	105	3.19	105	15	5	6	2	1	3	
174	236.83	239.88	3.05	3.04	100	3.04	100	15	5	6	4	1	3	
174	239.88	242.93	3.05	2.78	91	2.73	90	14	5	6	6	1	2	gouge on fractures
174	242.93	245.97	3.04	2.98	98	2.68	88	14	5	6	6	1	3	
174	245.97	249.02	3.05	3.21	105	3.21	105	15	5	6	4	1	2	gouge on fractures
174	249.02	252.07	3.05	2.95	97	2.95	97	15	5	6	3	1	2	gouge on fractures
174	252.07	255.12	3.05	3.07	101	3.07	101	15	5	6	4	1	2	
174	255.12	258.17	3.05	3.04	100	3.04	100	15	5	6	5	1	3	gouge on fractures
174	258.17	261.21	3.04	3.06	101	3.06	101	15	4	6	2	1	3	
174	261.21	264.26	3.05	2.99	98	2.60	85	14	5	6	7	3	3	gouge on fractures
174	264.26	267.31	3.05	2.92	96	2.87	94	14	5	6	6	1	3	
174	267.31	270.36	3.05	2.93	96	2.82	92	15	5	6	4	1	3	gouge on fractures
174	270.36	273.41	3.05	2.88	94	1.39	46	12	5	6	20	3	3	
174	273.41	276.45	3.04	2.96	97	2.91	96	15	5	6	3	3	3	gouge on fractures
174	276.45	279.50	3.05	3.02	99	3.02	99	15	5	6	4	3	4	gouge on fractures
174	279.50	282.55	3.05	2.99	98	2.99	98	15	5	6	4	3	3	
174	282.55	285.60	3.05	3.03	99	3.03	99	15	5	6	5	3	3	gouge on fractures
174	285.60	288.65	3.05	3.14	103	3.14	103	15	5	6	4	3	3	
174	288.65	291.69	3.04	3.02	99	3.02	99	15	5	6	2	1	3	
174	291.69	294.74	3.05	2.95	97	2.95	97	15	5	6	2	1	3	11 cm redrilled core
174	294.74	297.79	3.05	3.10	102	3.10	102	15	5	6	5	1	2	
174	297.79	300.84	3.05	2.86	94	2.66	87	15	5	6	3	1	3	
175	7.32	11.28	3.96	3.55	90	3.35	85	15	3	5	4	1	3	20 cm overburden
175	11.28	14.33	3.05	2.92	96	2.77	91	14	4	6	7	3	3	50% H=3
175	14.33	17.37	3.04	3.15	104	3.15	104	15	4	6	4	1	3	gouge filled fractures
175	17.37	20.42	3.05	2.86	94	2.71	89	14	3	5	6	1	1	1 wk slick 45 to c.a., partial healed units
175	20.42	23.47	3.05	3.02	99	3.02	99	15	4	6	1	1	2	
175	23.47	26.52	3.05	2.95	97	2.95	97	15	4	6	1	1	4	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
175	26.52	29.57	3.05	3.05	100	3.05	100	15	4	6	1	1	4	
175	29.57	32.61	3.04	2.90	95	2.70	89	14	3	5	6	1	2	gouge filled fractures
175	32.61	35.66	3.05	3.02	99	2.96	97	14	3	5	7	1	2	gouge filled fractures
175	35.66	38.71	3.05	2.98	98	2.78	91	15	4	6	6	1	2	slightly slick fractures
175	38.71	41.76	3.05	3.05	100	2.92	96	15	3	5	7	1	3	
175	41.76	44.81	3.05	3.05	100	3.05	100	15	4	6	4	1	3	
175	44.81	47.85	3.04	3.02	99	3.02	99	15	3	5	4	1	3	
175	47.85	50.90	3.05	2.98	98	2.81	92	14	3	5	7	3	2	healed vertical fracture, slick
175	50.90	53.95	3.05	2.94	96	2.71	89	14	3	5	8	3	2	healed vertical fracture, slick
175	53.95	57.00	3.05	0.97	32	0.00	0	3	1	3	50	1	1	start fault
175	57.00	60.05	3.05	1.08	35	0.16	5	4	2	3	40	1	2	
175	60.05	63.09	3.04	1.35	44	0.17	6	4	2	5	50	1	2	mineralized
175	63.09	66.14	3.05	0.14	5	0.00	0	3	1	3	11	3	3	v.poor recovery
175	66.14	69.19	3.05	0.15	5	0.00	0	3	1	3	12	3	3	v.poor recovery
175	69.19	72.24	3.05	0.17	6	0.00	0	4	2	4	11	3	3	end fault
175	72.24	75.29	3.05	1.81	59	1.68	55	14	2	4	9	3	2	72.50-gouge ends, 100 cm part healed
175	75.29	78.33	3.04	3.13	103	3.13	103	15	3	5	3	1	1	at 78.21 slick 45 to c.a.
175	78.33	81.38	3.05	3.14	103	3.14	103	15	4	5	2	1	2	
175	81.38	84.43	3.05	3.09	101	3.09	101	15	4	5	3	1	2	
175	84.43	87.48	3.05	3.05	100	2.96	97	14	3	5	6	1	2	30% H=2 healed fault
175	87.48	90.53	3.05	3.05	100	2.98	98	14	3	5	6	1	3	10% H=2 healed fault
175	90.53	93.57	3.04	3.05	100	3.05	100	15	3	5	3	3	3	
175	93.57	96.62	3.05	2.97	97	2.97	97	15	4	6	4	1	4	
175	96.62	99.67	3.05	3.13	103	3.13	103	15	4	6	3	1	4	
175	99.67	102.72	3.05	3.05	100	2.99	98	14	3	6	6	3	4	minor gouge on fractures
175	102.72	105.77	3.05	2.92	96	2.92	96	15	4	6	1	1	4	
175	105.77	108.81	3.04	3.20	105	3.20	105	15	4	6	2	3	2	
175	108.81	111.86	3.05	2.98	98	2.98	98	15	4	6	3	1	1	gouge on weak slicks,cont 45 to c.a.
175	111.86	114.91	3.05	3.05	100	3.00	98	15	3	6	5	1	1	gouge on weak slicks,cont 45 to c.a.
175	114.91	117.96	3.05	2.95	97	1.82	60	10	3	5	18	3	2	contact at 116.10 m, 30 to c.a.
175	117.96	121.01	3.05	2.77	91	1.54	50	12	2	5	12	3	2	gouge on fractures
175	121.01	124.05	3.04	3.05	100	3.05	100	15	3	5	4	3	2	
175	124.05	127.10	3.05	3.08	101	3.08	101	15	4	6				mineralized, very hard rock
175	127.10	130.15	3.05	2.97	97	2.70	89	15	3	6	4	3	2	10 cm partially healed material

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To	Lgth	m.	%	m.								%
175	130.15	133.20	3.05	3.05	100	3.05	100	15	4	6	2	3	4	
175	133.20	136.25	3.05	2.98	98	2.98	98	15	4	6	3	1	3	
175	136.25	139.29	3.04	3.10	102	2.97	98	14	3	5	8	3	2	gouge on slick joint
175	139.29	142.34	3.05	2.98	98	2.98	98	15	4	6	6	3	2	
175	142.34	145.39	3.05	3.02	99	2.88	94	15	4	6	8	1	2	gouge filled fractures
175	145.39	148.44	3.05	2.91	95	2.77	91	15	4	6	8	1	1	gouge filled fractures
175	148.44	151.49	3.05	3.08	101	3.08	101	15	4	6	4	1	1	slick gypsum fractures
175	151.49	154.53	3.04	3.15	104	3.15	104	15	4	6				
175	154.53	157.58	3.05	2.94	96	2.94	96	15	4	6	2	1	1	weak slick, 35 to c.a.
175	157.58	160.63	3.05	3.01	99	3.01	99	15	3	5	2	1	2	9 cm redrilled core
175	160.63	163.68	3.05	2.98	98	2.56	84	13	3	5	13	1	1	20 cm of H=2
175	163.68	166.73	3.05	3.05	100	2.95	97	15	4	6	4	1	1	
175	166.73	169.77	3.04	3.04	100	3.04	100	15	4	6	2	1	1	silck joint with gouge
175	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	4	1	2	gouge on fractures
175	172.82	175.87	3.05	3.05	100	2.72	89	14	3	5	8	1	1	15 to c.a. very slick
175	175.87	178.92	3.05	2.99	98	2.99	98	15	4	6	4	3	2	
175	178.92	181.97	3.05	3.05	100	2.81	92	14	3	5	7	1	1	
175	181.97	185.01	3.04	3.10	102	3.10	102	15	4	6	5	1	1	
175	185.01	188.06	3.05	3.02	99	2.87	94	15	3	6	4	1	1	7 cm H=0, brecciated gouge
175	188.06	191.11	3.05	3.10	102	3.02	99	15	3	5	8	1	1	slick 70 to c.a., minor gouge
175	191.11	194.16	3.05	3.05	100	2.96	97	15	4	6	4	1	1	slick 40 to c.a.
175	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6	3	1	1	weak slicks
175	197.21	200.25	3.04	2.91	96	2.72	89	14	3	5	7	1	2	
175	200.25	203.30	3.05	3.00	98	2.81	92	14	3	5	8	1	1	20% H=2 partially healed
175	203.30	206.35	3.05	3.01	99	2.76	90	14	3	5	9	1	1	
175	206.35	209.40	3.05	3.05	100	2.92	96	14	3	5	9	1	1	
175	209.40	212.45	3.05	2.94	96	2.94	96	15	4	5	3	1	1	slick contact 45 to c.a.
175	212.45	215.49	3.04	3.20	105	3.20	105	15	4	6				
175	215.49	218.54	3.05	3.08	101	3.08	101	15	4	5	4	1	1	strong slicks, max. 15 to c.a.
175	218.54	221.59	3.05	3.02	99	3.02	99	15	4	6	5	2	2	
175	221.59	224.64	3.05	1.49	49	1.09	36	15	4	6	10	1	1	40 cm of H=0,1, pyrite
175	224.64	227.69	3.05	2.99	98	2.41	79	15	4	6	14	1	1	slick contacts 45 to c.a.
175	227.69	230.73	3.04	3.10	102	3.10	102	15	4	6	8	1	3	
175	230.73	233.78	3.05	3.00	98	2.92	96	15	4	6	10	1	1	16 cm healed gouge, H=2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
175	233.78	236.83	3.05	3.19	105	3.19	105	15	4	6	2	1	4	
175	236.83	239.88	3.05	3.05	100	2.72	89	14	3	5	8	1	1	1 weak slick, minor gouge at 40 to c.a.
175	239.88	242.93	3.05	3.05	100	3.05	100	15	4	6	5	1	2	
175	242.93	245.97	3.04	2.84	93	0.91	30	9	1	3	30	1	1	1 strong slicks at 35 to c.a.; 2.12 m. of
175	245.97	249.02	3.05	3.10	102	3.10	102	15	4	6				partially healed gouge 243.61-246.00
175	249.02	252.07	3.05	2.80	92	2.80	92	15	4	6				partially healed fault zone; slick
175	252.07	255.12	3.05	1.92	63	0.80	26	9	3	5	20	1	1	1 252.00-255.12 m.-gouge/solid mat'l
175	255.12	258.17	3.05	2.97	97	2.75	90	15	4	6	4	3	3	
175	258.17	261.21	3.04	3.04	100	3.04	100	15	4	6	2	1	3	
175	261.21	264.26	3.05	3.05	100	3.05	100	15	4	6	4	1	1	1 weak slick
175	264.26	267.31	3.05	3.05	100	3.05	100	15	4	6	3	1	3	3 gouge on fractures
175	267.31	270.36	3.05	3.05	100	2.66	87	14	4	6	10	1	1	1 40 cm of gouge material
175	270.36	273.41	3.05	3.00	98	2.72	89	15	3	5	5	1	1	1 30 cm healed gouge
175	273.41	276.45	3.04	2.94	97	2.64	87	13	3	5	15	1	1	1 18 cm of H=1+O591
175	276.45	279.50	3.05	2.99	98	2.26	74	14	3	5	8	1	1	1 sections of gouge; H=1; 20 to c.a.
175	279.50	282.55	3.05	2.42	79	2.15	70	14	3	5	11	1	1	1 27 cm of H=0; 30 to c.a.; start of fault
175	282.55	285.60	3.05	1.45	48	0.00	0	2	0	3	70	1	1	1 80% gouge
175	285.60	288.65	3.05	2.92	96	1.02	33	13	3	5	22	1	1	1 30% gouge; 30% broken; 20 cm H=0
175	288.65	291.69	3.04	1.57	52	1.35	44	8	3	5	25	1	1	1 289.60 m slick at 15 to c.a.
175	291.69	294.74	3.05	2.78	91	2.59	85	11	3	5	16	1	4	4 291.51m slick at 30 to c.a., 15 cm H=0
175	294.74	297.79	3.05	2.91	95	2.91	95	15	4	6	4	1	3	
175	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	1	1	4	
175	300.84	303.89	3.05	2.99	98	2.99	98	15	4	6	3	1	4	
175	303.89	306.93	3.04	2.98	98	2.98	98	15	4	6	2	1	4	4 minor gouge on fracture
175	306.93	309.98	3.05	3.02	99	3.02	99	15	4	6	2	1	4	
175	309.98	313.03	3.05	3.10	102	3.10	102	15	4	6				
175	313.03	316.08	3.05	3.10	102	3.10	102	15	4	6	3	1	3	3 318.5&317.85 m-slick contacts; dyke
175	316.08	319.13	3.05	2.54	83	1.82	60	8	2	3	24	1	1	1 mat'l manually broken
175	319.13	322.17	3.04	3.05	100	2.90	95	15	4	6	2	1	2	2 gouge on fractures
175	322.17	325.22	3.05	2.77	91	2.42	79	14	3	5	10	1	4	
175	325.22	328.27	3.05	3.00	98	2.79	91	15	4	6	4	1	2	2 weak slicks; minor gouge
175	328.27	331.32	3.05	3.09	101	2.94	96	15	4	6	5	1	1	1 slick w/ gouge; 45 to c.a., 15 cm H=2
175	331.32	334.37	3.05	3.05	100	3.05	100	15	4	6	3	1	2	2 15 cm. of H=2
175	334.37	337.41	3.04	3.00	99	2.94	97	15	4	6	3	1	1	1 6 cm of H=1; slick fracture

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
176	24.38	26.52	2.14	1.70	79	1.11	52	10	3	5	12	1	3	
176	26.52	28.35	1.83	1.79	98	0.38	21	9	3	5	20	1	3	
176	28.35	29.57	1.22	1.08	89	0.59	48	7	3	5	20	1	3	
176	29.57	32.61	3.04	2.29	75	0.45	15	6	3	5	50	5	3	At 30.06-31.40 m, all gouge H=1
176	32.61	33.22	0.61	0.43	70	0.00	0	2	2	5	50	5	3	90% gouge
176	33.22	35.05	1.83	0.70	38	0.13	7	2	2	5	50	5	3	50% gouge
176	35.05	36.27	1.22	0.22	18	0.00	0	3	3	5	20	5	3	Broken rock
176	36.27	37.19	0.92	0.64	70	0.12	13	3	3	5	20	5	3	Broken rock
176	37.19	38.71	1.52	0.37	24	0.00	0	3	3	5	15	5	3	Broken rock
176	38.71	41.76	3.05	1.66	54	0.31	10	7	3	5	25	5	3	Broken rock
176	41.76	44.81	3.05	1.30	43	0.00	0	7	3	5	25	5	3	Broken rock
176	44.81	47.85	3.04	1.24	41	0.00	0	3	3	5	50	5	3	Broken rock
176	47.85	60.96	13.11	0.00	0	0.00	0							Triconed
176	60.96	63.09	2.13	1.67	78	1.11	52	10	3	6	15	1	3	
176	63.09	63.70	0.61	0.36	59	0.20	33	9	3	6	7	2	3	10 cm broken rock with gouge
176	63.70	66.14	2.44	2.50	102	2.06	84	14	3	6	5	1	3	
176	66.14	68.58	2.44	2.53	104	1.89	77	14	3	6	7	1	3	
176	68.58	69.80	1.22	0.76	62	0.44	36	12	3	6	8	2	3	
176	69.80	70.71	0.91	0.89	98	0.54	59	12	3	6	5	1	3	
176	70.71	72.24	1.53	1.53	100	1.22	80	12	3	6	9	1	3	5 cm fault gouge
176	72.24	74.68	2.44	2.41	99	2.01	82	15	3	6	3	1	3	gouge on fractures
176	74.68	77.42	2.74	2.71	99	2.58	94	15	3	6	2	1	3	
176	77.42	79.25	1.83	1.44	79	0.94	51	9	3	6	15	2	3	10% broken rock with gouge
176	79.25	81.38	2.13	2.20	103	2.07	97	15	3	6	3	1	3	
176	81.38	82.91	1.53	1.31	86	0.86	56	14	3	6	4	1	3	calcite on fractures
176	82.91	85.65	2.74	2.64	96	1.93	70	12	4	6	15	5	3	dyke, 10% broken rock
176	85.65	87.48	1.83	1.83	100	1.36	74	14	4	6	5	1	3	dyke, gouge on fractures
176	87.48	89.00	1.52	1.29	85	1.08	71	12	3	6	7	1	3	
176	89.00	90.53	1.53	1.14	75	0.64	42	9	3	6	15	1	3	gouge on fractures
176	90.53	93.57	3.04	2.69	88	2.43	80	14	3	6	6	1	3	
176	93.57	96.62	3.05	3.05	100	2.91	95	15	3	6	5	1	3	gouge on fractures
176	96.62	98.15	1.53	1.69	110	1.60	105	14	3	6	3	1	3	
176	98.15	99.67	1.52	1.47	97	0.78	51	10	3	6	10	1	3	5% broken core, pyrite on fractures
176	99.67	102.72	3.05	2.08	68	1.85	61	10	3	6	17	1	3	1st 20 cm is broken rock

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
176	102.72	103.94	1.22	0.42	34	0.17	14	4	3	6	20	5	3	40% broken core
176	103.94	106.98	3.04	3.04	100	2.87	94	15	4	6	5	1	3	gouge on fractures
176	106.98	110.03	3.05	3.07	101	3.07	101	15	4	6	2	1	3	gypsum on fractures
176	110.03	113.08	3.05	3.14	103	3.08	101	15	4	6	1	1	3	gypsum on fractures
176	113.08	116.13	3.05	3.09	101	3.09	101	15	4	6	2	1	3	gypsum on fractures
176	116.13	117.96	1.83	1.77	97	1.77	97	15	4	6	1	1	3	gypsum on fractures
176	117.96	121.01	3.05	3.05	100	3.05	100	15	4	6	4	1	3	gypsum on fractures
176	121.01	124.05	3.04	2.97	98	2.97	98	15	4	6	2	1	3	gypsum on fractures
176	124.05	127.10	3.05	3.05	100	3.00	98	15	3	6	2	1	3	gypsum on fractures
176	127.10	130.15	3.05	3.00	98	3.00	98	15	3	6	4	1	3	gypsum on fractures
176	130.15	133.20	3.05	3.03	99	2.79	91	15	3	6	5	1	3	gypsum on fractures
176	133.20	136.25	3.05	3.05	100	2.97	97	15	3	6	6	1	3	40 cm core of H=2, gouge on fractures
176	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6	2	1	3	gypsum on fractures
176	139.29	142.34	3.05	3.10	102	2.99	98	15	4	6	3	1	3	gypsum on fractures
176	142.34	145.39	3.05	2.96	97	2.61	86	14	4	6	5	1	3	gypsum on fractures
176	145.39	148.44	3.05	3.05	100	1.13	37	12	3	6	20	5	3	30% broken rock
176	148.44	151.49	3.05	3.15	103	2.27	74	13	3	6	15	1	3	gouge on fractures, 10% broken core
176	151.49	154.53	3.04	2.87	94	2.24	74	12	3	6	15	1	3	15% broken core with gouge
176	154.53	157.58	3.05	3.15	103	2.94	96	14	3	6	7	1	3	gypsum on fractures
176	157.58	160.63	3.05	3.05	100	2.72	89	15	3	6	5	1	3	gypsum on fractures
176	160.63	163.68	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
176	163.68	166.73	3.05	2.86	94	2.63	86	14	3	6	7	1	3	4 cm fault gouge at 55 to c.a.
176	166.73	169.77	3.04	3.01	99	3.01	99	15	3	6	3	1	3	gouge on fractures
176	169.77	172.82	3.05	3.05	100	2.94	96	15	3	6	3	1	3	gypsum on fractures
176	172.82	175.87	3.05	3.09	101	2.60	85	15	3	6	5	1	3	gypsum on fractures
176	175.87	178.92	3.05	3.08	101	2.95	97	15	3	6	3	2	3	gypsum on fractures
176	178.92	181.97	3.05	2.99	98	2.64	87	14	3	6	6	1	3	gypsum and gouge on fractures
176	181.97	185.01	3.04	2.95	97	2.57	85	14	3	6	7	1	3	gypsum on fractures
176	185.01	188.06	3.05	3.14	103	2.05	67	14	3	6	9	2	3	gypsum on fractures
176	188.06	191.11	3.05	3.01	99	2.97	97	15	3	6	3	1	3	gypsum on fractures
176	191.11	194.16	3.05	3.09	101	3.01	99	15	3	6	4	1	3	gypsum on fractures
176	194.16	197.21	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
176	197.21	200.25	3.04	3.04	100	3.04	100	15	3	6	3	1	3	gypsum on fractures
176	200.25	203.30	3.05	3.05	100	2.74	90	15	3	6	3	1	3	gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
176	203.30	206.34	3.04	2.92	96	2.15	71	14	3	6	7	1	3 48 cm fault gouge at 50 to c.a. H=1
176	206.34	209.40	3.06	3.15	103	2.91	95	15	3	6	4	1	3
176	209.40	212.45	3.05	2.05	67	1.44	47	13	3	6	7	1	3
176	212.45	215.49	3.04	2.93	96	2.60	86	12	3	6	10	5	3 Last 15 cm broken core with gouge
176	215.49	218.54	3.05	2.95	97	2.05	67	12	4	6	15	1	3
176	218.54	221.59	3.05	3.09	101	1.51	50	10	4	6	25	5	3 35% broken core,4cm gouge 50 to c.a.
176	221.59	224.64	3.05	2.81	92	2.03	67	14	4	6	6	1	3 15% broken core with gouge
176	224.64	227.69	3.05	2.78	91	1.15	38	10	4	6	20	5	3 20% broken core,2cm gouge H=2
176	227.69	230.73	3.04	2.80	92	2.63	87	14	4	6	5	1	3
176	230.73	233.78	3.05	3.15	103	2.31	76	13	4	6	15	1	3 10% broken core
176	233.78	236.83	3.05	3.14	103	2.19	72	14	4	6	7	1	3
176	236.83	239.88	3.05	2.76	90	2.65	87	14	4	6	5	1	3
176	239.88	242.93	3.05	2.64	87	2.03	67	12	3	6	17	1	3 35 cm gouge H=1
176	242.93	245.97	3.04	2.73	90	2.01	66	14	3	6	9	1	3
176	245.97	249.02	3.05	2.98	98	2.11	69	15	3	6	4	1	3 6 cm gouge H=1
176	249.02	252.07	3.05	3.05	100	2.91	95	15	3	6	3	1	3
176	252.07	255.12	3.05	3.05	100	3.05	100	15	3	6	2	1	3
176	255.12	258.17	3.05	3.03	99	3.03	99	15	3	6	2	1	3
176	258.17	261.21	3.04	2.96	97	2.96	97	13	4	6	1	1	3 gouge on fractures
176	261.21	264.26	3.05	3.08	101	3.08	101	15	4	6	1	1	3
176	264.26	267.31	3.05	3.05	100	3.05	100	15	3	6	2	1	3 2 cm gouge at end of interval
176	267.31	270.36	3.05	3.02	99	3.02	99	15	3	6	3	1	3
176	270.36	273.41	3.05	3.05	100	3.05	100	15	3	6	2	1	3
176	273.41	276.45	3.04	3.08	101	3.08	101	15	3	6	1	1	3
176	276.45	279.50	3.05	3.01	99	2.80	92	14	3	6	8	1	3 gouge on fractures
176	279.50	282.55	3.05	2.91	95	2.30	75	13	3	6	14	2	3
176	282.55	284.68	2.13	2.01	94	0.53	25	12	3	6	12	1	3 25 cm gouge H=1,95 cm fault/gouge
176	284.68	287.73	3.05	2.99	98	2.99	98	15	3	6	4	1	2
176	287.73	290.78	3.05	3.06	100	3.06	100	15	3	6	2	1	3
176	290.78	293.83	3.05	3.03	99	3.03	99	15	3	6	1	1	3
176	293.83	295.96	2.13	2.04	96	2.04	96		3	6	0		
176	295.96	297.79	1.83	1.87	102	1.87	102	12	3	6	1	1	3
176	297.79	300.84	3.05	3.07	101	3.07	101	15	3	6	3	1	3 gouge on fractures
176	300.84	303.89	3.05	3.10	102	3.00	98	15	3	6	2	1	3

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
176	303.89	306.93	3.04	3.08	101	2.93	96	15	3	6	3	2	3	15 cm fault gouge H=1 at 40 to c.a.
176	306.93	309.98	3.05	3.07	101	3.07	101		4	6	0			
176	309.98	313.03	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
176	313.03	316.08	3.05	3.00	98	3.00	98	15	3	6	1	1	2	
176	316.08	319.13	3.05	3.07	101	3.07	101	15	3	6	2	1	3	
176	319.13	322.17	3.04	3.02	99	3.02	99	15	4	6	2	1	3	3 mlnor gouge on fractures
176	322.17	325.22	3.05	3.11	102	3.04	100	15	4	6	3	1	3	
176	325.22	328.27	3.05	2.84	93	2.40	79	12	3	6	15	1	3	3 5% broken core
176	328.27	331.32	3.05	2.93	96	2.79	91	14	3	6	5	1	3	
176	331.32	334.37	3.05	3.37	110	3.09	101	15	3	6	4	1	3	3 gouge on fractures
176	334.37	337.41	3.04	3.04	100	3.04	100	15	3	6	3	1	3	3 gouge on fractures
176	337.41	340.46	3.05	3.07	101	3.00	98	15	3	6	3	1	3	3 gouge on fractures
176	340.46	343.51	3.05	3.06	100	3.06	100	15	3	6	2	1	3	
176	343.51	346.56	3.05	3.15	103	3.02	99	15	3	6	3	1	3	
176	346.56	349.61	3.05	3.16	104	3.16	104	15	3	6	2	1	3	
176	349.61	352.65	3.04	3.01	99	3.01	99	15	3	6	1	1	3	
176	352.65	355.70	3.05	3.01	99	3.01	99	15	3	6	3	1	3	3 slip plane with gouge at 25 to c.a.
176	355.70	358.75	3.05	2.92	96	2.68	88	14	3	6	5	1	3	
176	358.75	361.80	3.05	2.95	97	2.95	97	15	3	6	2	1	3	
176	361.80	364.85	3.05	3.02	99	2.89	95	14	3	6	6	2	3	3 gouge on fractures
176	364.85	367.89	3.04	3.11	102	3.04	100	15	3	6	2	2	3	
176	367.89	370.94	3.05	3.17	104	3.17	104	15	3	6	1	1	3	
176	370.94	373.99	3.05	3.05	100	3.05	100	15	3	6	3	1	3	3 gouge on fractures
176	373.99	377.04	3.05	3.02	99	3.02	99	15	3	6	2	1	2	
176	377.04	380.09	3.05	3.03	99	2.92	96	15	3	6	3	1	3	3 gouge on fractures
176	380.09	383.13	3.04	3.04	100	3.04	100	15	3	6	2	1	3	
176	383.13	386.18	3.05	3.07	101	3.07	101	15	3	6	1	1	2	2 weak slick
176	386.18	389.23	3.05	3.05	100	3.05	100	15	3	6	3	2	3	
176	389.23	392.28	3.05	3.07	101	3.07	101	15	3	6	1	1	3	
176	392.28	395.33	3.05	2.92	96	2.87	94	15	3	6	4	1	3	3 25 cm H=2, gouge on fractures
176	395.33	398.37	3.04	2.87	94	2.25	74	15	3	6	10	1	3	3 30 cm H=2, gouge on fractures
176	398.37	401.42	3.05	3.27	107	3.27	107	15	4	6	2	1	2	
176	401.42	404.47	3.05	3.00	98	3.00	98	15	4	6	1	1	2	
176	404.47	407.52	3.05	3.01	99	3.01	99	15	4	6	2	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
176	407.52	410.57	3.05	2.94	96	2.94	96	15	4	6	1	1	3	
176	410.57	413.61	3.04	2.89	95	2.89	95	15	4	6	3	1	3	gouge on fractures
176	413.61	416.66	3.05	3.05	100	2.91	95	15	4	6	4	1	3	
176	416.66	419.71	3.05	3.08	101	3.08	101	15	4	6	1	1	3	
176	419.71	422.76	3.05	3.09	101	2.98	98	15	4	6	3	1	3	gouge on fractures
176	422.76	423.98	1.22	1.05	86	0.61	50	15	4	6	5	1	3	
176	423.98	427.02	3.04	3.04	100	3.04	100	15	4	6	1	1	3	
176	427.02	428.85	1.83	1.94	106	1.94	106	15	3	6	1	1	3	
176	428.85	431.90	3.05	2.89	95	2.89	95	15	3	6	2	1	3	gouge on fractures
176	431.90	434.95	3.05	3.00	98	2.71	89	15	3	6	4	1	3	
176	434.95	438.00	3.05	3.00	98	2.91	95	15	3	6	3	1	3	gouge on fractures
176	438.00	441.05	3.05	3.01	99	3.01	99	15	3	6	4	1	3	
177	13.11	14.33	1.22	0.80	66	0.00	0	5	3	4	15	1	2	blocky
177	14.33	17.37	3.04	1.62	53	0.10	3	5	3	4	30	1	2	blocky
177	17.37	20.42	3.05	1.47	48	0.16	5	6	3	4	30	1	2	blocky
177	20.42	23.47	3.05	1.62	53	0.00	0	6	3	4	30	1	2	blocky
177	23.47	26.52	3.05	2.47	81	0.32	10	6	3	4	25	1	2	3 cm healed shear at 60 to c.a.
177	26.52	29.57	3.05	2.78	91	0.33	11	7	3	4	30	1	2	2 cm shear at 40 to c.a.
177	29.57	32.61	3.04	2.65	87	1.20	39	7	1	2	20	1	2	fault at 30.2 m. to end at 35 to c.a.
177	32.61	35.66	3.05	3.12	102	1.28	42	7	3	4	30	1	2	32.61m-30 cm. healed fault 50-60 to c.a.
177	35.66	38.71	3.05	2.70	89	0.31	10	6	2	4	30	1	2	healed shear throughout
177	38.71	41.76	3.05	2.70	89	0.21	7	6	3	4	30	1	2	41.16 m-60 cm rubble/gouge 60 to c.a.
178	6.10	8.23	2.13	1.61	76	1.32	62	7	2	4	30	1	2	minor gouge
178	8.23	10.06	1.83	1.66	91	1.47	80	8	2	4	20	1	2	minor gouge
178	10.06	11.28	1.22	0.80	66	0.80	66	15	2	4	6	1	2	minor gouge
178	11.28	14.33	3.05	2.53	83	2.40	79	15	2	4	15	1	2	minor gouge
178	14.33	17.37	3.04	2.92	96	2.85	94	15	2	4	5	1	2	minor gouge
178	17.37	20.42	3.05	2.51	82	2.31	76	12	2	4	20	1	2	minor gouge
178	20.42	23.47	3.05	2.86	94	2.80	92	15	2	4	12	1	2	minor gouge
178	23.47	26.52	3.05	2.98	98	2.68	88	10	2	4	30	1	1	minor gouge, slick joints 35 to c.a.
178	26.52	29.57	3.05	2.77	91	2.49	82	10	2	4	30	1	1	secondary fractures 10 to c.a.
178	29.57	32.61	3.04	1.16	38	1.10	36	14	2	4	7	1	2	minor gouge
179	15.24	17.37	2.13	0.10	5	0.00	0	6	3	3	5	5	3	broken rock with gouge
179	17.37	20.42	3.05	0.55	18	0.11	4	6	3	3	20	5	3	broken rock with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
179	20.42	21.95	1.53	0.35	23	0.00	0	6	3	3	12	5	3	3 broken rock with gouge
179	21.95	23.47	1.52	0.33	22	0.00	0	6	3	3	15	5	3	3 iron staining on core
179	23.47	24.69	1.22	0.48	39	0.25	20	7	3	4	10	5	3	
179	24.69	26.52	1.83	0.71	39	0.42	23	7	4	4	13	5	3	3 iron staining on fractures
179	26.52	28.35	1.83	1.56	85	1.19	65	10	3	5	9	5	3	3 last 20 cm gouge, H=1
179	28.35	29.57	1.22	1.06	87	0.97	80	13	3	5	4	2	3	3 35 cm fault gouge, H=1
179	29.57	30.78	1.21	0.92	76	0.43	36	7	3	6	15	1	3	3 17 cm fault H=1, 20 cm broken rock
179	30.78	32.61	1.83	1.83	100	1.29	70	14	3	6	4	1	3	3 gouge on fractures
179	32.61	35.66	3.05	2.93	96	2.93	96	15	3	6	2	1	3	
179	35.66	38.71	3.05	3.03	99	2.25	74	14	3	6	6	2	3	3 18 cm broken rock with gouge
179	38.71	41.76	3.05	2.85	93	1.94	64	14	3	6	9	2	3	3 5 - 10% broken rock
179	41.76	44.50	2.74	2.62	96	2.55	93	14	3	6	5	2	3	3 27 cm gouge, H=1
179	44.50	47.55	3.05	2.97	97	2.97	97	15	3	6	2	1	3	3 gouge on fractures
179	47.55	50.29	2.74	2.51	92	2.51	92	15	3	6	3	1	3	
179	50.29	53.95	3.66	0.00	0	0.00	0							no recovery
179	53.95	57.00	3.05	0.00	0	0.00	0							no recovery
179	57.00	60.05	3.05	0.00	0	0.00	0							no recovery
179	60.05	63.09	3.04	0.11	4	0.00	0	1	1	4	10	5	3	3 90% gouge , H=1
179	63.09	66.14	3.05	0.20	7	0.00	0	4	3	6	12	5	3	
179	66.14	67.06	0.92	0.14	15	0.00	0	6	3	4	5	5	3	
179	67.06	73.15	6.09	0.00	0									casing, triconed
179	73.15	75.90	2.75	0.18	7	0.00	0	6	3	4	5	5	3	
179	75.90	78.03	2.13	0.00	0									casing, triconed
179	78.03	80.47	2.44	0.54	22	0.17	7	9	4	4	6	3	3	3 4 cm fault gouge
179	80.47	81.38	0.91	0.65	71	0.57	63	14	3	5	2	1	3	3 gouge on fractures
179	81.38	84.43	3.05	3.06	100	2.34	77	14	4	5	8	3	3	3 44 cm H=1, weak slick, gypsum fract.
179	84.43	87.48	3.05	3.05	100	1.64	54	13	3	5	11	3	3	3 gouge on fractures, weak slick
179	87.48	90.53	3.05	2.96	97	2.61	86	14	3	5	8	1	3	
179	90.53	93.57	3.04	2.98	98	2.98	98	15	4	5	4	1	3	3 multiple shears 1 cm ± gouge
179	93.57	96.62	3.05	2.89	95	2.89	95	14	4	5	6	3	3	
179	96.62	99.67	3.05	3.04	100	3.04	100	15	4	5	1	1	3	
179	99.67	102.72	3.05	2.96	97	2.96	97	15	5	6	2	3	3	
179	102.72	105.77	3.05	3.02	99	3.02	99	15	4	6	2	1	4	
179	105.77	108.81	3.04	2.99	98	2.99	98	15	5	6	4	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
179	108.81	111.86	3.05	3.07	101	2.88	94	14	4	6	5	1	3	
179	111.86	114.60	2.74	2.50	91	2.23	81	13	5	6	9	1	3	gouge on fractures
179	114.60	117.35	2.75	2.40	87	2.11	77	13	4	6	9	1	3	35 cm broken core at 116.7 - 117.05 m.
179	117.35	118.87	1.52	1.41	93	1.14	75	11	4	6	10	1	3	gouge on fractures
179	118.87	120.09	1.22	0.84	69	0.00	0	9	4	5	8	1	3	100% broken core, gouge on fractures
179	120.09	121.01	0.92	0.85	92	0.43	47	10	4	5	6	5	4	50% broken core
179	121.01	124.05	3.04	2.89	95	2.67	88	14	4	6	8	3	2	gouge on fractures
179	124.05	127.10	3.05	3.04	100	1.75	57	12	4	6	20	3	3	
179	127.10	130.15	3.05	2.94	96	2.94	96	14	4	6	6	1	3	
179	130.15	133.20	3.05	3.05	100	2.56	84	14	5	6	5	3	3	
179	133.20	136.25	3.05	2.93	96	2.93	96	14	5	6	6	1	3	last 20 cm H=2
179	136.25	139.29	3.04	2.99	98	2.24	74	13	4	6	10	1	3	30 cm H=1 gouge on fractures
179	139.29	142.34	3.05	2.99	98	2.65	87	13	4	6	11	1	3	gouge on fractures
179	142.34	145.39	3.05	2.83	93	2.54	83	14	4	6	7	1	3	gouge on fractures
179	145.39	148.44	3.05	2.91	95	2.24	73	13	4	6	12	1	2	
179	148.44	151.49	3.05	2.83	93	1.62	53	12	5	6	18	3	3	10% broken core, gouge on fractures
179	151.49	154.53	3.04	2.99	98	2.99	98	14	5	6	6	1	3	
179	154.53	157.58	3.05	3.13	103	3.13	103	15	4	6	3	3	4	
179	157.58	160.63	3.05	3.05	100	2.66	87	14	4	6	5	1	3	gouge on fractures
179	160.63	163.68	3.05	3.15	103	2.13	70	13	4	6	15	1	3	gouge on fractures
179	163.68	166.73	3.05	3.12	102	3.12	102	15	4	6	2	1	3	weak slick, gouge on fractures
179	166.73	169.77	3.04	3.13	103	3.13	103	15	4	6	1	1	3	
179	169.77	172.82	3.05	2.95	97	2.59	85	14	4	6	7	3	3	gouge on fractures
179	172.82	175.26	2.44	2.34	96	2.34	96	15	4	6	3	1	3	gouge on fractures
179	175.26	178.31	3.05	3.05	100	3.05	100	15	5	6	2	1	3	
179	178.31	181.36	3.05	2.98	98	2.73	90	15	4	6	4	1	3	5 cm fault gouge, slick 10 to c.a.
179	181.36	184.40	3.04	3.10	102	3.07	101	14	3	6	6	1	3	gouge on fractures, weak slick
179	184.40	186.23	1.83	1.92	105	1.92	105	15	4	6	3	3	3	gouge on fractures, slick
179	186.23	188.06	1.83	1.80	98	1.80	98	15	4	6	1	3	3	
179	188.06	191.11	3.05	3.01	99	3.01	99	15	4	6	2	3	3	
179	191.11	194.16	3.05	3.01	99	3.01	99	15	4	6	3	1	3	
179	194.16	197.21	3.05	3.03	99	3.03	99	15	4	6	2	1	3	thick bands of mineralization
179	197.21	200.25	3.04	3.09	102	3.09	102	15	4	6	1	5	3	gouge on fractures, gypsum veining
179	200.25	203.30	3.05	3.07	101	3.07	101	15	4	6	3	1	3	mineralized veins

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
179	203.30	206.35	3.05	3.00	98	3.00	98	15	4	6	2	3	3	
179	206.35	209.40	3.05	3.06	100	3.06	100	15	4	6	2	1	3	
179	209.40	212.45	3.05	3.02	99	3.02	99	15	4	6	2	1	3	
179	212.45	215.49	3.04	3.04	100	3.04	100	15	4	6	2	1	3	3 weak slick
179	215.49	218.54	3.05	3.10	102	3.10	102	15	4	6	1	1	3	3 5 cm gypsum vein
179	218.54	221.59	3.05	3.06	100	3.06	100	15	4	6	3	1	3	3 4 cm healed fault, slick cont w/gouge
179	221.59	224.64	3.05	2.97	97	2.97	97	15	4	6	1	1	3	
179	224.64	227.69	3.05	2.99	98	2.99	98	15	4	6	2	1	3	
179	227.69	230.73	3.04	3.07	101	3.07	101	15	4	6	2	1	3	3 228.2 slick at 18 to c.a.
179	230.73	233.78	3.05	3.11	102	3.11	102	15	4	6	1	1	3	
179	233.78	236.83	3.05	3.00	98	3.00	98	15	4	6	3	1	3	3 gouge on fractures, weak slick
179	236.83	239.88	3.05	2.92	96	2.52	83	14	4	6	6	1	3	
179	239.88	242.93	3.05	3.04	100	3.04	100	15	4	6	4	3	3	3 gouge on fractures
179	242.93	245.97	3.04	3.03	100	3.03	100	15	4	6	1	3	3	3 5 cm redrilled core, gouge on fractures
179	245.97	249.02	3.05	2.98	98	2.98	98	15	4	6	1	3	3	3 slick
179	249.02	252.07	3.05	2.87	94	2.66	87	14	4	6	9	5	3	3 gouge on fractures
179	252.07	255.12	3.05	3.17	104	3.06	100	14	4	6	5	1	3	3 6 cm of H=0
179	255.12	258.17	3.05	2.95	97	2.89	95	15	4	6	4	1	3	3 gouge on fractures, last 5 cm gouge
179	258.17	261.21	3.04	2.96	97	2.96	97	15	5	6	2	1	3	3 heavy mineralization
179	261.21	264.26	3.05	3.17	104	3.17	104	15	5	6	3	1	4	4 weak slick
179	264.26	267.31	3.05	3.02	99	2.46	81	14	4	6	8	3	3	
179	267.31	270.36	3.05	2.92	96	2.17	71	12	5	6	16	1	3	3 slick
179	270.36	273.41	3.05	2.85	93	2.28	75	14	4	6	7	1	3	3 gouge on fractures
179	273.41	276.45	3.04	3.18	105	3.06	101	14	4	6	8	1	3	3 slick
179	276.45	279.50	3.05	2.87	94	2.74	90	14	5	6	7	1	3	3 gouge on fractures
179	279.50	282.55	3.05	2.99	98	2.94	96	15	5	6	4	1	3	3 partially healed sheer/ fault ± gouge
179	282.55	285.60	3.05	3.07	101	2.84	93	14	4	5	8	1	3	3 partially healed sheer/ fault ± gouge
179	285.60	288.65	3.05	3.09	101	2.83	93	15	4	5	4	1	3	3 partially healed sheer/ fault ± gouge
179	288.65	291.69	3.04	3.13	103	3.13	103	14	5	5	5	3	3	3 gouge on fractures
179	291.69	294.74	3.05	3.04	100	3.04	100	15	4	5	2	5	3	3 gouge on fractures
179	294.74	297.79	3.05	2.97	97	2.97	97	15	5	6	1	3	3	
179	297.79	300.84	3.05	3.03	99	2.89	95	14	4	5	6	1	3	3 18 cm partially healed fault
179	300.84	303.89	3.05	2.95	97	2.95	97	14	4	5	5	5	3	3 gouge on fractures
179	303.89	306.93	3.04	3.21	106	2.80	92	14	4	5	9	3	3	3 weak slick

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
179	306.93	309.98	3.05	3.07	101	3.07	101	15	4	6	3	3	3	
179	309.98	313.03	3.05	3.01	99	3.01	99	15	4	6	1	3	2	
179	313.03	316.08	3.05	2.92	96	2.58	85	14	4	6	8	1	3	15 cm broken rx w/ gouge @ 114.20 m.
179	316.08	318.52	2.44	2.17	89	2.17	89	15	4	5	1	1	3	
179	318.52	320.65	2.13	2.25	106	2.25	106	15	4	6	1	5	3	
179	320.65	322.17	1.52	1.53	101	1.53	101	15	3	6	2	1	3	weak slick
179	322.17	325.22	3.05	3.02	99	3.02	99	15	4	6	3	1	3	gouge on fractures, weak slick
179	325.22	328.27	3.05	2.94	96	2.94	96	15	4	6	3	3	3	gouge on fractures
179	328.27	331.32	3.05	2.95	97	2.95	97	15	4	6	2	1	3	
179	331.32	334.37	3.05	3.10	102	3.10	102	14	5	6	5	1	3	
179	334.37	337.41	3.04	2.99	98	2.99	98	15	4	6	3	1	3	
179	337.41	340.46	3.05	3.02	99	3.02	99	15	4	6	1	1	3	gouge on fractures
179	340.46	343.51	3.05	3.02	99	3.02	99	15	4	6	2	1	3	gouge on fractures
179	343.51	346.56	3.05	3.04	100	3.04	100	15	4	6	2	1	3	gouge on fractures, weak slick
179	346.56	349.61	3.05	2.95	97	2.55	84	14	4	6	8	1	3	weak slick
179	349.61	352.65	3.04	3.02	99	3.02	99	14	4	6	5	1	2	
179	352.65	355.70	3.05	3.03	99	3.03	99	15	5	6	1	1	3	
179	355.70	358.75	3.05	3.09	101	3.09	101	15	5	6	2	3	3	gouge on fractures
180	6.10	8.23	2.13	1.46	69	1.07	50	9	2	4	15	1	1	top 20 cm overburden
180	8.23	11.28	3.05	2.95	97	2.25	74	12	2	4	15	1	1	gouge in strongly broken core
180	11.28	14.33	3.05	2.30	75	1.81	59	12	2	4	15	1	1	gouge in strongly broken core
180	14.33	17.37	3.04	2.18	72	1.68	55	12	2	4	18	1	1	gouge in strongly broken core
180	17.37	20.42	3.05	2.38	78	1.76	58	12	2	4	13	1	1	gouge in strongly broken core
180	20.42	23.47	3.05	1.98	65	1.06	35	12	2	4	18	1	2	2 cm gouge at 50 to c.a.
180	23.47	26.52	3.05	2.02	66	1.12	37	12	2	4	25	1	1	slip with gouge at 50 to c.a.
180	26.52	28.35	1.83	1.56	85	1.05	57	9	2	4	20	1	1	gouge in strongly broken core
180	28.35	29.57	1.22	0.27	22	0.00	0	4	2	4	8	1	1	gouge in strongly broken core
181	3.66	5.18	1.52	1.14	75	0.90	59	11	3	4	7	1	4	manual rubble for first 50 cm
181	5.18	8.23	3.05	0.77	25	0.22	7	5	2	3	18	1	3	well weathered zone
181	8.23	11.28	3.05	2.00	66	1.51	50	11	3	4	12	1	3	
181	11.28	14.33	3.05	2.95	97	1.24	41	8	3	3	40	1	3	25 cm H=0
181	14.33	17.37	3.04	2.86	94	2.32	76	13	3	4	14	1	3	at 17 m start of heavy gouge
181	17.37	20.42	3.05	2.40	79	0.90	30	6	2	3	50	1	1	50% H=0, slick contacts?
181	20.42	23.47	3.05	2.93	96	1.04	34	8	2	3	40	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
181	23.47	26.52	3.05	2.38	78	0.74	24	4	2	3	60	1	2	
181	26.52	29.57	3.05	2.87	94	2.54	83	13	2	3	12	1	1	partially healed fault
181	29.57	32.61	3.04	2.86	94	2.50	82	12	2	3	15	1	1	partially healed fault
181	32.61	35.66	3.05	2.97	97	2.27	74	12	2	3	17	3	3	
181	35.66	38.71	3.05	3.10	102	2.40	79	13	2	3	15	1	2	
181	38.71	41.76	3.05	3.10	102	2.76	90	14	3	4	9	1	1	30 cm H=1, many fractures
181	41.76	44.81	3.05	3.00	98	2.62	86	11	3	5	18	1	1	slick contacts, 40 to c.a., 20 cm gouge
181	44.81	47.85	3.04	3.00	99	2.92	96	15	4	5	4	1	2	
181	47.85	50.90	3.05	3.00	98	2.91	95	15	4	5	5	1	2	3 cm rubble section
182	3.05	5.18	2.13	1.67	78	1.67	78	15	3	5	3	3	4	redrilled core, limonite staining
182	5.18	8.23	3.05	2.85	93	2.85	93	15	3	5	4	3	4	limonite staining
182	8.23	11.28	3.05	3.05	100	2.96	97	14	3	5	6	3	4	limonite staining
182	11.28	14.33	3.05	3.05	100	3.05	100	15	4	6	4	1	4	limonite staining
182	14.33	17.37	3.04	3.05	100	3.05	100	15	4	6	2	3	4	limonite staining
182	17.37	20.42	3.05	3.05	100	3.05	100	15	3	5	6	1	3	limonite staining
182	20.42	23.47	3.05	3.05	100	3.05	100	15	3	5	5	1	3	limonite staining
182	23.47	26.52	3.05	2.97	97	2.97	97	15	3	5	5	1	4	limonite staining
182	26.52	29.57	3.05	2.92	96	2.92	96	15	3	5	5	1	4	limonite staining
182	29.57	32.61	3.04	3.02	99	3.02	99	14	3	5	6	1	2	limonite staining
182	32.61	35.66	3.05	2.98	98	2.98	98	15	4	6	1	3	4	carbonate veins
182	35.66	38.71	3.05	2.97	97	2.97	97	15	4	6				
182	38.71	41.76	3.05	3.15	103	3.15	103	15	4	6				
182	41.76	44.81	3.05	2.91	95	2.91	95	15	4	6				
182	44.81	47.85	3.04	3.09	102	3.09	102	15	4	6	1	1	2	carbonate veins
182	47.85	50.90	3.05	3.04	100	3.04	100	15	4	6				
182	50.90	53.95	3.05	2.99	98	2.72	89	13	3	5	12	1	1	slick 20 to c.a., 27 cm of H=0,1
182	53.95	57.00	3.05	3.10	102	3.10	102	15	4	6				
182	57.00	60.05	3.05	2.94	96	2.86	94	14	3	5	8	3	2	
182	60.05	63.09	3.04	2.87	94	2.64	87	13	3	5	7	1	1	vert gouge, 8 cm of H=1, slick 15 to c.a.
182	63.09	66.14	3.05	3.08	101	3.03	99	15	4	6	3	1	3	carbonate veining
182	66.14	69.19	3.05	3.02	99	3.02	99	15	4	6				
182	69.19	72.24	3.05	2.87	94	2.86	94	15	4	6	4	1	2	1 cm gouge on weak slick
182	72.24	75.29	3.05	2.64	87	2.64	87	15	3	6	4	3	3	
182	75.29	78.33	3.04	3.18	105	2.35	77	4	3	5	70	1	1	83 cm of H=0

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
183	3.66	5.18	1.52	1.10	72	0.94	62	12	4	5	4	1	3	3 redrilled core, limonite staining
183	5.18	8.23	3.05	3.12	102	2.75	90	13	3	5	11	3	4	limonite staining
183	8.23	11.28	3.05	2.95	97	2.26	74	10	3	5	26	1	1	li staining, 32 cm of H = 0,15 to c.a.
183	11.28	14.33	3.05	2.60	85	2.41	79	12	4	5	18	1	4	limonite staining
183	14.33	17.37	3.04	3.12	103	2.80	92	12	4	5	16	1	3	limonite staining
183	17.37	20.42	3.05	3.10	102	2.58	85	11	3	5	20	1	1	limonite staining, carbonate w/ gouge
183	20.42	23.47	3.05	2.92	96	2.07	68	10	3	5	22	3	3	limonite staining, carbonate w/gouge
183	23.47	26.52	3.05	2.81	92	1.85	61	9	3	5	30	3	3	limonite staining
183	26.52	29.57	3.05	3.17	104	2.94	96	14	3	5	7	1	3	limonite staining
183	29.57	32.61	3.04	3.05	100	3.05	100	15	4	6	2	2	2	fracture, weak slick 20 to c.a.
183	32.61	35.66	3.05	2.98	98	2.98	98	15	4	6				
183	35.66	38.71	3.05	3.05	100	3.05	100	15	4	6				
183	38.71	41.76	3.05	3.05	100	3.00	98	15	4	6	4	1	2	minor gouge on fractures
183	41.76	44.81	3.05	3.02	99	3.02	99	15	4	6	1	3	3	
183	44.81	47.85	3.04	3.18	105	3.18	105	15	4	6	1	1	2	gouge on fractures
183	47.85	50.90	3.05	3.05	100	3.05	100	15	4	6	3	1	3	contact at 48.85 m
183	50.90	53.95	3.05	3.02	99	3.02	99	14	3	5	5	1	1	50 to c.a.
183	53.95	57.00	3.05	3.00	98	3.00	98	15	5	6				
183	57.00	60.05	3.05	2.97	97	2.81	92	14	4	5	6	1	2	4 cm of H=1
183	60.05	63.09	3.04	3.00	99	2.62	86	14	3	5	9	1	2	38 cm of broken material
183	63.09	66.14	3.05	3.05	100	2.88	94	13	3	5	12	1	3	
183	66.14	69.19	3.05	3.05	100	3.05	100	15	4	6	4	1	1	
183	69.19	72.24	3.05	3.00	98	2.71	89	13	3	5	12	1	2	70 cm of H=2
183	72.24	75.29	3.05	2.96	97	2.96	97	15	4	6	4	1	4	
183	75.29	78.33	3.04	3.07	101	3.07	101	15	5	6	1	3	3	one gypsum fracture
183	78.33	81.38	3.05	3.05	100	3.05	100	15	4	6				very competent rock
183	81.38	84.43	3.05	3.08	101	3.08	101	15	4	6				very competent rock
183	84.43	87.48	3.05	3.02	99	3.02	99	15	4	6				very competent rock
183	87.48	90.53	3.05	2.90	95	2.90	95	15	4	6				very competent rock
183	90.53	91.44	0.91	1.10	121	1.10	121	15	4	6				very competent rock
184	4.27	5.18	0.91	0.80	88	0.70	77	13	4	5	27	1	2	10 cm sand and gravel
184	5.18	8.23	3.05	3.05	100	2.87	94	14	4	5	9	1	3	limonite staining on fract, hard rock
184	8.23	11.28	3.05	3.03	99	2.95	97	14	4	5	7	1	4	limonite staining on fract, hard rock
184	11.28	14.33	3.05	3.17	104	2.97	97	14	4	5	9	1	3	limonite staining on fract, hard rock

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To		m.	%	m.	%								
184	14.33	17.37	3.04	3.10	102	2.61	86	11	3	5	18	1	3	limonite staining on fract, hard rock	
184	17.37	20.42	3.05	2.85	93	2.63	86	13	4	5	10	1	3	limonite staining on fract, hard rock	
184	20.42	23.47	3.05	2.90	95	2.90	95	15	4	5	2	1	3	limonite staining on fract, hard rock	
184	23.47	26.52	3.05	3.05	100	3.05	100	15	4	6	1	1	4		
184	26.52	29.57	3.05	3.00	98	3.00	98	15	4	6	4	1	1	1	slick 30 to c. a. @ 26.55 m
184	29.57	32.61	3.04	3.05	100	3.05	100	15	3	6	6	1	1	1	weak slicks
184	32.61	35.66	3.05	3.05	100	3.05	100	15	4	6	4	3	4	4	
184	35.66	38.71	3.05	2.85	93	2.85	93	15	4	6	5	3	4	4	14 cm redrilled core
184	38.71	41.76	3.05	3.15	103	2.93	96	14	3	6	8	1	1	1	minor gouge, weak slick
184	41.76	44.81	3.05	2.95	97	2.95	97	15	4	6	1	3	2	2	smooth undulated fracture
184	44.81	47.85	3.04	3.04	100	3.01	99	15	4	6	3	1	2	2	
184	47.85	50.90	3.05	3.05	100	3.05	100	15	4	6	2	1	1	1	
184	50.90	53.95	3.05	2.68	88	1.14	37	7	2	4	40	1	1	1	slick 45 to c.a., 20% H=4
184	53.95	57.00	3.05	3.15	103	3.01	99	14	4	6	8	1	2	2	43 cm partially healed material
184	57.00	60.05	3.05	3.08	101	2.98	98	14	4	6	6	1	3	3	
184	60.05	63.09	3.04	2.72	89	2.50	82	14	4	6	7	1	3	3	
184	63.09	66.14	3.05	3.05	100	2.14	70	12	3	5	16	3	3	3	broken material, minor gouge
184	66.14	69.19	3.05	3.05	100	2.40	79	12	3	5	17	1	2	2	broken material, minor gouge
184	69.19	72.24	3.05	3.05	100	2.51	82	13	4	5	12	1	2	2	broken material, minor gouge
184	72.24	75.29	3.05	2.98	98	2.98	98	15	4	6	4	1	1	1	broken material, slick
184	75.29	78.33	3.04	2.99	98	2.77	91	14	4	5	28	1	1	1	part healed breccia and fault, 22cm H=0
184	78.33	81.38	3.05	2.99	98	2.02	66	11	2	5	20	1	1	1	part healed breccia and fault
184	81.38	84.43	3.05	3.07	101	2.42	79	13	3	5	12	1	1	1	part healed breccia , gypsum
184	84.43	87.48	3.05	2.87	94	1.74	57	10	3	5	20	1	1	1	40% H=1,2, v. slick 10 to c.a.
184	87.48	90.53	3.05	3.00	98	2.52	83	13	3	5	13	1	1	1	partly healed fault zone; gypsum
184	90.53	93.57	3.04	3.07	101	2.83	93	13	3	5	10	1	1	1	partly healed fault zone; gypsum
184	93.57	96.62	3.05	3.16	104	2.68	88	13	3	5	14	1	1	1	healed fault; gypsum; very slick 25 to c.a.
184	96.62	99.67	3.05	3.05	100	3.05	100	15	4	6	4	1	2	2	
184	99.67	102.72	3.05	3.05	100	3.05	100	15	4	6	3	1	3	3	
184	102.72	105.77	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3	
184	105.77	108.81	3.04	3.10	102	3.10	102	15	4	6	2	1	4	4	
184	108.81	111.86	3.05	3.05	100	3.05	100	15	4	6	3	3	4	4	
184	111.86	114.91	3.05	2.86	94	2.26	74	13	3	5	14	1	1	1	gouge on slick fractures
184	114.91	117.96	3.05	3.00	98	3.00	98	15	4	6	3	3	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
184	117.96	121.01	3.05	2.97	97	2.60	85	14	3	5	10	1	1 slick at 30 to c.a.; gouge on fractures
184	121.01	124.05	3.04	3.05	100	2.95	97	15	4	6	5	1	3
184	124.05	127.10	3.05	3.05	100	3.05	100	15	4	6	3	4	4
184	127.10	130.15	3.05	3.02	99	3.02	99	15	5	6	2	1	3
184	130.15	133.20	3.05	2.97	97	2.97	97	15	5	6	3	3	3
184	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6	3	1	2
184	136.25	139.29	3.04	3.08	101	3.08	101	15	4	6	3	1	3
184	139.29	142.34	3.05	2.98	98	2.98	98	15	4	6	1	1	4
184	142.34	145.39	3.05	2.94	96	2.94	96	15	5	6			3 cm of redrilled core
184	145.39	148.44	3.05	3.05	100	3.05	100	15	4	6	3	1	4
184	148.44	151.49	3.05	2.79	91	2.79	91	15	4	6	6	3	3 redrilled core; poor recovery
184	151.49	154.53	3.04	2.98	98	2.93	96	15	4	6	4	1	2
184	154.53	157.58	3.05	2.98	98	2.98	98	15	5	6	3	1	3 redrilled core
184	157.58	160.63	3.05	2.97	97	2.97	97	15	5	6	4	1	3
184	160.63	163.68	3.05	3.05	100	2.81	92	14	3	5	9	1	1 part healed sections; slick at 20 to c.a.
184	163.68	166.73	3.05	2.95	97	2.95	97	15	4	6	3	1	4
184	166.73	169.77	3.04	3.02	99	3.02	99	15	4	6	4	1	4
184	169.77	172.82	3.05	3.05	100	3.05	100	15	5	6	1	1	4
184	172.82	175.87	3.05	3.00	98	3.00	98	15	4	6	5	3	3 32 cm of H=3; healed fractures
184	175.87	178.92	3.05	2.95	97	2.95	97	15	4	6	4	1	4
184	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	3	1	1 very slick joint at 35 to c.a.
184	181.97	185.01	3.04	2.96	97	2.96	97	15	4	6	3	1	2
184	185.01	188.06	3.05	3.05	100	3.05	100	15	4	6	5	1	3
184	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	2	1	1 weak slicks; minor gouge
184	191.11	194.16	3.05	3.05	100	3.05	100	15	4	6	5	1	1 weak slicks; minor gouge
184	194.16	197.21	3.05	3.13	103	3.13	103	15	5	6			
184	197.21	200.25	3.04	3.04	100	3.04	100	15	5	6	2	2	2 gouge on fractures; slick?
184	200.25	203.30	3.05	3.05	100	3.05	100	15	4	5	7	3	2 undulating and slick
184	203.30	206.35	3.05	3.05	100	2.91	95	15	4	5	5	3	2 undulating and slick
184	206.35	209.40	3.05	2.96	97	2.96	97	15	3	5	3	1	1 slick contact at 30 to c.a.
184	209.40	212.45	3.05	3.05	100	2.99	98	15	4	6	2	1	2
184	212.45	215.49	3.04	2.92	96	2.92	96	15	4	6			
184	215.49	218.54	3.05	3.02	99	3.02	99	15	4	6	2	1	2
184	218.54	221.59	3.05	2.99	98	2.99	98	15	4	6	1	1	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
184	221.59	224.64	3.05	3.12	102	3.12	102	15	3	6	3	1	1	1 weak slicks; minor gouge
184	224.64	227.69	3.05	3.02	99	2.89	95	15	3	6	4	1	1	1 weak slicks; minor gouge
184	227.69	230.73	3.04	3.00	99	3.00	99	15	4	6	3	1	2	
184	230.73	233.78	3.05	3.05	100	3.05	100	15	3	5	3	3	3	3 healed fractures
184	233.78	236.83	3.05	3.11	102	3.04	100	14	3	5	7	1	1	1 slicks
184	236.83	239.88	3.05	3.05	100	3.05	100	15	3	5	6	1	3	3 many healed fractures
184	239.88	242.93	3.05	3.00	98	2.89	95	15	3	5	5	1	2	2 many healed fractures
184	242.93	245.97	3.04	3.09	102	2.82	93	14	3	5	8	1	2	2 many healed fractures
184	245.97	249.02	3.05	3.05	100	2.95	97	14	4	5	7	1	3	3 many healed fractures
184	249.02	252.07	3.05	3.05	100	2.97	97	14	4	5	8	1	1	1 8 cm of H=0; very slick
184	252.07	255.12	3.05	3.11	102	3.11	102	15	4	6				
184	255.12	258.17	3.05	3.11	102	3.11	102	15	4	6	1	1	3	3 mineralized fracture
184	258.17	261.21	3.04	2.95	97	2.91	96	15	3	6	3	1	2	2 4 cm of H=1
184	261.21	264.26	3.05	3.01	99	2.92	96	14	3	5	9	1	2	2 25 cm of H=2,1
184	264.26	267.31	3.05	2.99	98	2.99	98	15	4	6	2	1	3	3 21 cm of redrilled core
184	267.31	270.36	3.05	2.92	96	2.92	96	15	3	5	2	1	1	1
184	270.36	273.41	3.05	2.99	98	2.99	98	15	3	6	5	1	3	3
184	273.41	276.45	3.04	2.94	97	2.82	93	14	3	5	8	1	1	1 slick at 15 to c.a.
184	276.45	279.50	3.05	3.00	98	3.00	98	15	4	6	1	1	2	2 minor gouge
184	279.50	282.55	3.05	3.00	98	3.00	98	15	3	5	5	1	2	2 54 cm of H=2
184	282.55	285.60	3.05	2.96	97	2.56	84	14	3	5	8	1	1	1 45 to c.a. slick
184	285.60	288.64	3.04	3.00	99	3.00	99	15	4	6	3	3	3	3
184	288.64	291.69	3.05	3.05	100	3.05	100	15	4	6	1	1	1	1 mineralized slick at 22 to c.a.
184	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	1	2	4	4
184	294.74	297.79	3.05	3.17	104	3.17	104	15	4	6	2	1	1	1 weak slick
184	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 gouge on weak slicks
184	300.84	303.88	3.04	2.88	95	2.88	95	15	3	6	4	2	1	1 gouge on weak slicks
184	303.88	306.93	3.05	3.15	103	3.12	102	15	4	6	4	1	1	1 gouge on weak slicks; 3 cm of H=1
184	306.93	309.98	3.05	2.92	96	2.76	90	14	4	5	9	1	1	1 partially healed fractures
184	309.98	313.03	3.05	3.05	100	3.05	100	15	4	6	4	2	1	1 weak slicks at 35 to c.a.
184	313.03	316.08	3.05	3.05	100	2.80	92	13	3	6	14	1	1	1 50 cm H=2, healed shear; slicks 40 to c.a.
184	316.08	319.13	3.05	2.95	97	2.95	97	15	4	6	6	1	1	1
184	319.13	322.17	3.04	3.05	100	3.05	100	15	4	6	4	1	1	1 very slick at 40 to c.a.
184	322.17	325.22	3.05	2.44	80	1.50	49	9	4	5	30	1	1	1 94 cm of H=2,1; fault gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
184	325.22	328.27	3.05	2.98	98	2.43	80	12	4	5	17	1	1	1 slicks and gouge
184	328.27	331.32	3.05	3.05	100	2.61	86	13	3	5	11	1	1	1 many slick contacts; 66 cm of H=2
184	331.32	334.37	3.05	2.86	94	2.80	92	14	4	6	5	1	1	1 weak slicks, sectn of v. soft material
184	334.37	337.41	3.04	2.70	89	2.70	89	14	4	6	5	3	2	
184	337.41	340.46	3.05	3.10	102	3.10	102	15	4	6	2	3	3	
184	340.46	343.51	3.05	2.80	92	2.76	90	15	4	6	2	1	1	1 343.50 m. - v. slick contact at 40 to c.a.
184	343.51	346.56	3.05	3.47	114	3.44	113	15	4	6	4	1	2	2 weak slick?; 3 cm of gouge
184	346.56	349.61	3.05	2.87	94	2.87	94	15	5	6				very hard volcanic rock
184	349.61	352.65	3.04	3.05	100	2.97	98	15	4	6	5	1	1	1 8 cm of gouge
184	352.65	355.70	3.05	3.10	102	3.08	101	15	3	6	6	1	3	3 many healed fractures
184	355.70	358.75	3.05	2.94	96	2.80	92	15	3	6	4	1	1	1 weak slicks with gouge
184	358.75	361.80	3.05	2.99	98	2.99	98	15	4	6	4	3	2	2 gouge-filled fractures
184	361.80	364.85	3.05	3.05	100	3.05	100	14	4	6	7	1	1	1 gouge-filled fractures; weak slick
184	364.85	367.89	3.04	3.10	102	3.07	101	15	4	5	6	1	2	2 gouge-filled fractures
184	367.89	370.94	3.05	2.95	97	2.73	90	15	4	6	4	1	2	2 gouge-filled fractures
184	370.94	373.99	3.05	3.00	98	3.00	98	15	3	6	2	1	2	2 gouge-filled fractures
184	373.99	377.04	3.05	3.05	100	3.05	100	15	4	6	2	1	2	2 gouge-filled fractures
184	377.04	380.09	3.05	3.05	100	3.05	100	15	4	6	1	1	3	3
184	380.09	383.13	3.04	3.04	100	3.04	100	15	4	6	1	3	3	3
184	383.13	386.18	3.05	2.99	98	2.87	94	14	3	6	8	1	1	1 fault H=0 at 383.13 m for 15 cm
184	386.18	389.23	3.05	3.10	102	2.98	98	15	4	6	5	1	2	2
184	389.23	392.28	3.05	3.00	98	2.90	95	15	4	5	7	1	2	2
184	392.28	395.33	3.05	2.83	93	2.68	88	13	3	5	11	1	1	1 weak slicks
184	395.33	398.37	3.04	3.05	100	3.05	100	15	3	5	4	3	3	3
184	398.37	401.42	3.05	2.88	94	2.69	88	14	3	5	7	1	3	3 minor gouge
184	401.42	404.47	3.05	3.05	100	2.86	94	14	3	5	7	1	4	4 minor gouge
184	404.47	407.52	3.05	2.83	93	2.65	87	14	3	4	7	1	4	4 minor gouge
184	407.52	410.57	3.05	2.72	89	2.28	75	9	3	4	30	1	2	2 H=0, heavily gouge filled fractures
184	410.57	413.61	3.04	2.69	88	2.37	78	9	3	5	30	1	2	2 H=0, heavily gouge filled fractures
184	413.61	416.66	3.05	2.88	94	2.88	94	15	3	6	3	1	3	3 healed carbonate veins
184	416.66	419.71	3.05	3.05	100	2.99	98	15	3	6	2	1	1	1 slicks at 40 to c.a.
184	419.71	422.76	3.05	3.05	100	3.05	100	15	4	6	1	3	3	3
184	422.76	425.81	3.05	3.05	100	3.05	100	15	4	6	2	3	3	3
184	425.81	428.85	3.04	3.04	100	3.04	100	15	4	6	2	1	2	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
184	428.85	431.90	3.05	2.91	95	2.91	95	15	4	6	3	3	3	
184	431.90	434.95	3.05	2.83	93	2.83	93	15	4	6	4	1	3	
184	434.95	438.00	3.05	3.05	100	3.05	100	15	4	6	4	1	3	
184	438.00	441.05	3.05	2.84	93	2.49	82	14	3	5	17	1	2	35 cm of H=1
184	441.05	444.09	3.04	2.99	98	2.99	98	15	4	6				
184	444.09	447.14	3.05	2.98	98	2.98	98	15	4	6	2	1	4	
184	447.14	450.19	3.05	3.05	100	3.05	100	15	4	6	2	3	4	
184	450.19	453.24	3.05	2.95	97	2.95	97	15	4	6	1	1	3	calcite veins
184	453.24	456.29	3.05	2.93	96	2.93	96	15	4	6	1	3	3	calcite veins
184	456.29	459.33	3.04	3.05	100	3.05	100	15	4	6				redrilled core
184	459.33	462.38	3.05	3.02	99	3.02	99	15	4	6	1	1	4	
184	462.38	465.43	3.05	3.04	100	3.04	100	15	4	6				
184	465.43	468.48	3.05	2.78	91	2.78	91	15	4	6	3	3	3	3 manual breaks, some gouge
184	468.48	471.53	3.05	2.92	96	2.92	96	15	4	6				
184	471.53	474.57	3.04	3.02	99	2.96	97	14	3	5	7	1	1	1 healed fractures and minor shearing
184	474.57	477.62	3.05	2.75	90	2.65	87	14	3	5	12	1	1	10 cm H=0 - shearing
184	477.62	480.67	3.05	3.05	100	2.99	98	15	3	5	6	1	2	
184	480.67	483.72	3.05	2.80	92	2.20	72	10	3	5	24	1	1	1 minor slicks with gouge
184	483.72	486.77	3.05	2.76	90	2.53	83	14	3	5	8	1	1	1 minor slicks with gouge
184	486.77	489.81	3.04	3.31	109	3.31	109	15	4	6	6	1	2	
184	489.81	492.86	3.05	3.02	99	3.02	99	15	4	6	5	1	2	
184	492.86	495.91	3.05	3.21	105	3.21	105	15	4	6	3	1	1	1 slicks at 35 to c.a. -strong
184	495.91	498.96	3.05	3.02	99	2.90	95	15	4	6	4	3	3	3 gouge on fractures
184	498.96	502.01	3.05	3.00	98	3.00	98	15	4	6	1	3	4	
184	502.01	505.05	3.04	3.04	100	3.02	99	15	4	6	2	3	3	3 gouge filled fractures, 2cm
184	505.05	508.10	3.05	3.00	98	2.75	90	14	4	6	6	2	2	2 trace gouge
184	508.10	511.15	3.05	3.05	100	2.81	92	14	4	6	6	1	1	10 cm strongly broken ang core w/ gouge
184	511.15	514.20	3.05	3.16	104	3.04	100	14	3	6	8	1	1	1 gouge on slips
184	514.20	517.25	3.05	3.05	100	2.54	83	14	3	6	7	1	1	1 gouge on slips
184	517.25	520.29	3.04	3.05	100	2.98	98	14	3	6	6	1	1	1 gouge on slips
184	520.29	523.34	3.05	3.05	100	2.90	95	15	3	6	5	1	1	1 gouge on slips
184	523.34	526.39	3.05	3.11	102	2.71	89	14	3	5	10	1	1	1 gouge on slips
184	526.39	529.44	3.05	3.11	102	2.93	96	14	3	6	9	1	1	1 gouge on slips
184	529.44	532.49	3.05	3.08	101	2.56	84	13	3	5	14	1	1	1 3-4mm gouge 20 to c.a. 50 cm broken

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
184	532.49	535.53	3.04	2.79	92	2.64	87	14	3	6	6	1	1	1 gouge on slips at 40 to c.a.
184	535.53	538.58	3.05	3.05	100	3.01	99	14	4	6	8	1	1	1 gouge on slips
184	538.58	541.63	3.05	3.09	101	2.98	98	15	4	6	5	1	1	1 gouge on slips
184	541.63	544.68	3.05	3.00	98	3.00	98	15	3	5	4	1	1	1 gouge on slips
184	544.68	547.73	3.05	2.95	97	2.95	97	15	3	6	4	1	1	1 weak slicks, gouge on slips
184	547.73	550.77	3.04	3.04	100	2.94	97	14	3	5	7	1	1	1 slick 20 to c.a.
184	550.77	553.82	3.05	3.05	100	3.00	98	14	3	5	8	1	1	1 gypsum and quartz fractures
184	553.82	556.87	3.05	2.95	97	2.94	96	15	3	6	5	1	1	2 one gouge filled fracture
184	556.87	559.92	3.05	3.05	100	2.90	95	13	3	5	12	1	1	2 15 cm of H=1
184	559.92	562.97	3.05	3.11	102	2.94	96	15	3	5	4	1	1	2
184	562.97	566.01	3.04	3.06	101	2.89	95	14	3	5	6	1	1	2
184	566.01	569.06	3.05	3.00	98	2.80	92	14	3	5	7	1	1	2 fault zone begins
184	569.06	572.11	3.05	2.96	97	2.11	69	10	1	2	25	1	1	1 sectons of solid material
184	572.11	575.16	3.05	3.09	101	2.30	75	13	1	2	15	1	1	1 sectns of solid mat'l - v. heavily sheared
184	575.16	578.21	3.05	3.05	100	2.72	89	14	2	4	9	1	1	1 sectns of solid mat'l - v. heavily sheared
184	578.21	581.25	3.04	2.89	95	1.98	65	6	1	4	40	1	1	1 sectns of solid mat'l - v. heavily sheared
184	581.25	584.30	3.05	3.05	100	1.77	58	8	1	2	35	1	1	1 sectns of solid mat'l - v. heavily sheared
184	584.30	587.35	3.05	3.11	102	2.73	90	14	1	2	10	1	1	1 sectns of solid mat'l - v. heavily sheared
184	587.35	590.40	3.05	2.88	94	2.35	77	13	1	2	16	1	1	1 sectns of solid mat'l - v. heavily sheared
184	590.40	593.45	3.05	3.09	101	3.09	101	12	1	3	15	1	1	1 part healed breccia, not many fractures
184	593.45	596.49	3.04	3.00	99	3.00	99	15	2	4	4	1	1	1 still weak
184	596.49	599.54	3.05	2.92	96	0.91	30	12	2	2	24	1	1	1 50% H=1, 50% H=2
184	599.54	602.59	3.05	3.10	102	0.45	15	5	2	2	60	1	1	1 40% H=1, heavily faulted
184	602.59	605.64	3.05	3.20	105	0.34	11	3	0	2	150	1	1	1 vertical shearing, heavily faulted
184	605.64	608.69	3.05	2.85	93	2.20	72	10	1	3	30	1	1	1 fault zone ends
184	608.69	611.73	3.04	2.88	95	2.44	80	12	2	4	15	1	1	1 weak slicks, gouge filled
184	611.73	614.78	3.05	2.90	95	2.55	84	11	2	4	18	1	1	2 35 cm of H=1
184	614.78	617.83	3.05	2.90	95	2.03	67	12	2	5	16	3	3	3 gouge filled fractures
184	617.83	620.88	3.05	3.05	100	3.04	100	15	3	6	3	3	3	2 one gouge filled fracture
184	620.88	623.93	3.05	3.10	102	2.69	88	14	3	5	26	1	1	1 slick contact, section of H=0,1
185	6.10	8.23	2.13	1.58	74	0.23	11	6	1	1	40	1	1	3 Rusty soil fractures - gouge
185	8.23	11.28	3.05	3.05	100	0.95	31	7	1	1	50	1	1	3 Rusty fractures - 5 cm gouge
185	11.28	14.32	3.04	3.20	105	1.37	45	7	4	3	50	1	1	3 Rusty fractures
185	14.32	17.37	3.05	2.81	92	1.85	61	13	4	3	12	1	1	3 Rusty fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
185	17.37	20.42	3.05	3.00	98	1.91	63	13	4	4	14	1	1	1 gouge on slips
185	20.42	21.34	0.92	0.71	77	0.23	25	6	4	4	18	1	1	1 100% strongly broken angular core
185	21.34	22.25	0.91	0.29	32	0.00	0	3	4	4	20	1	1	1 100% strongly broken angular core
185	22.25	23.47	1.22	1.00	82	0.23	19	5	4	4	30	1	1	1 100% strongly broken angular core
185	23.47	24.08	0.61	0.61	100	0.00	0	2	4	4	20	1	1	1 100% strongly broken angular core
185	24.08	25.30	1.22	0.83	68	0.00	0	2	4	4	30	1	1	1 100% strongly broken angular core
185	25.30	26.52	1.22	0.89	73	0.00	0	3	4	4	30	1	1	1 100% strongly broken angular core
185	26.52	27.13	0.61	0.43	70	0.00	0	3	4	4	25	1	1	1 100% strongly broken angular core
185	27.13	27.74	0.61	0.67	110	0.00	0	3	4	4	25	1	1	1 100% strongly broken angular core
185	27.74	28.35	0.61	0.46	75	0.00	0	3	4	4	25	1	1	1 100% strongly broken angular core
185	28.35	29.57	1.22	1.06	87	0.91	75	10	4	4	9	1	1	1 100% strongly broken angular core
185	29.57	31.09	1.52	1.55	102	1.24	82	12	4	6	9	3	2	2 gouge in broken core
185	31.09	31.70	0.61	0.64	105	0.64	105	13	4	6	3	1	1	1 trace gouge subparallel to c.a.
185	31.70	32.92	1.22	1.22	100	1.01	83	12	4	6	6	1	1	1 10 cm broken angular core
185	32.92	35.66	2.74	2.28	83	1.88	69	13	4	6	9	3	2	2
185	35.66	38.71	3.05	2.35	77	1.59	52	13	4	6	10	2	2	2 Dumped box-questionable interval
185	38.71	39.93	1.22	0.62	51	0.38	31	7	4	6	10	2	2	2 Dumped box-questionable interval
185	39.93	41.76	1.83	1.44	79	1.04	57	10	4	6	10	2	2	2 Dumped box-questionable interval
185	41.76	43.28	1.52	1.07	70	0.75	49	9	4	6	11	2	2	2 15 cm strongly broken angular core
185	43.28	44.81	1.53	1.21	79	1.16	76	12	4	6	6	1	1	1 5 cm cemented gouge at 30 to c.a.
185	44.81	47.85	3.04	2.95	97	2.83	93	14	4	6	8	1	1	1 shear zone at 25 to c.a.
185	47.85	50.90	3.05	3.05	100	3.00	98	14	3	6	5	1	1	1 3 cm gouge at 25 to c.a.
185	50.90	53.95	3.05	2.91	95	2.91	95	15	3	6	3	1	1	1 slips along gypsum veins
185	53.95	57.00	3.05	3.05	100	3.05	100	15	3	6	3	2	2	2
185	57.00	60.05	3.05	2.93	96	2.11	69	13	4	6	13	2	2	2 gouge in broken core
185	60.05	63.09	3.04	3.00	99	2.94	97	14	4	6	6	1	1	1 shear zone at 45 to c.a.
185	63.09	66.14	3.05	2.72	89	2.26	74	12	4	6	14	1	1	1 gouge in broken core
185	66.14	69.19	3.05	2.96	97	2.96	97	14	4	6	6	1	1	1 shear zone at 65 to c.a.
185	69.19	72.24	3.05	2.97	97	2.51	82	14	4	6	9	1	1	1 gouge in slip-15 cm mod broken ang core
185	72.24	75.29	3.05	2.82	92	2.11	69	12	4	6	16	1	1	1 weakly-mod broken 1-15 cm angular core
185	75.29	78.33	3.04	2.81	92	2.28	75	13	4	6	10	2	2	2
185	78.33	79.86	1.53	1.60	105	1.48	97	14	4	6	4	2	2	2 trace gouge
185	79.86	81.38	1.52	1.52	100	1.52	100	14	4	6	3	1	1	1 gouge in slip
185	81.38	84.43	3.05	2.96	97	2.68	88	14	4	6	7	1	1	1 1-3 mm gouge in slip at 40-50 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
185	84.43	87.48	3.05	2.87	94	2.50	82	14	4	6	8	2	2	15 cm cemented gouge
185	87.48	90.53	3.05	2.97	97	2.69	88	14	4	6	6	1	1	10 cm mod broken subangular core
185	90.53	93.57	3.04	2.98	98	2.95	97	15	4	6	3	2	2	
185	93.57	96.62	3.05	2.95	97	2.51	82	13	4	6	10	2	2	
185	96.62	99.67	3.05	3.01	99	2.26	74	13	4	6	12	1	1	20 cm strongly broken angular 1-2 cm core
185	99.67	102.72	3.05	3.05	100	2.46	81	14	4	6	10	1	1	2-3 mm gouge in slip at <10 to c.a.
185	102.72	105.77	3.05	3.02	99	2.65	87	13	4	6	11	1	1	gouge in broken core
185	105.77	108.81	3.04	2.77	91	2.18	72	13	4	6	10	1	1	gouge in broken core
185	108.81	111.86	3.05	2.79	91	2.65	87	14	4	6	6	2	2	trace gouge in broken core
185	111.86	114.91	3.05	3.00	98	2.91	95	15	4	6	4	1	1	trace gouge in broken core
185	114.91	117.96	3.05	2.95	97	2.92	96	15	4	6	4	5	2	
185	117.96	121.01	3.05	3.05	100	3.05	100	15	4	6	3	5	2	
185	121.01	124.05	3.04	3.04	100	3.04	100	15	4	6	4	1	1	trace gouge on slip
185	124.05	127.10	3.05	3.11	102	3.11	102	15	4	6	4	2	2	
185	127.10	130.15	3.05	2.89	95	2.89	95	15	4	6	4	2	2	
185	130.15	133.20	3.05	3.05	100	2.81	92	14	4	6	7	1	1	3 cm cemented gouge
185	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6	4	1	2	
185	136.25	139.29	3.04	3.14	103	3.05	100	14	4	6	9	1	1	trace gouge on slip
185	139.29	142.34	3.05	2.96	97	2.76	90	14	4	6	6	1	2	3 cm gouge and 1 cm gouge
185	142.34	145.39	3.05	2.92	96	2.92	96	15	4	6	3	2	3	
185	145.39	148.44	3.05	3.00	98	3.00	98	15	4	6	3	2	2	
185	148.44	151.49	3.05	3.08	101	3.05	100	15	4	6	5	1	1	2 cm gouge
185	151.49	154.53	3.04	3.04	100	3.01	99	15	4	6	4	1	1	gouge on slip at 40 to c.a.
185	154.53	157.58	3.05	3.13	103	3.04	100	15	4	6	5	2	2	
185	157.58	160.63	3.05	3.09	101	3.09	101	15	4	6	5	2	2	
185	160.63	163.68	3.05	3.07	101	3.07	101	15	4	6	3	2	2	
185	163.68	166.73	3.05	3.10	102	3.10	102	15	4	6	4	2	2	
185	166.73	169.77	3.04	3.10	102	3.10	102	15	4	6	4	1	1	gouge on slip
185	169.77	172.82	3.05	2.91	95	2.91	95	15	4	6	2	2	2	3 healed fault zone at 30-40 to c.a.
185	172.82	175.87	3.05	3.05	100	3.02	99	15	4	6	3	2	2	
185	175.87	178.92	3.05	3.00	98	3.00	98	15	4	6	5	1	1	
185	178.92	181.97	3.05	3.08	101	3.03	99	15	4	6	4	2	2	
185	181.97	185.01	3.04	3.08	101	3.08	101	14	4	6	6	2	2	gouge on break at 60 to c.a.
185	185.01	188.06	3.05	3.00	98	2.06	68	13	4	6	15	3	2	80% weakly broken 2-10 cm ang core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
185	188.06	190.20	2.14	2.02	94	1.48	69	10	4	6	14	2	2	50% weakly broken 2-8cm angular core
185	190.20	191.72	1.52	1.55	102	1.38	91	14	4	6	5	1	1	80% v weakly broken 4-10 cm ang core
185	191.72	193.24	1.52	1.33	87	1.22	80	14	4	6	4	1	2	trace gouge in broken core
185	193.24	195.99	2.75	1.56	57	1.56	57	14	4	6	3	5	3	trace gouge in broken core
185	195.99	199.03	3.04	2.96	97	2.31	76	13	4	6	14	1	1	20 cm gouge and rubble
185	199.03	200.25	1.22	1.56	128	1.56	128	15	4	6	2	3	2	
185	200.25	203.30	3.05	2.93	96	2.84	93	15	4	6	3	1	1	2 parallel slips at 45 to c.a.
185	203.30	206.35	3.05	3.07	101	3.07	101	15	4	6	2	3	2	
185	206.35	209.40	3.05	3.10	102	3.10	102	15	4	6	2	3	2	30 cm redrilled core
185	209.40	212.45	3.05	3.05	100	3.05	100	15	4	6	3	2	2	
185	212.45	215.49	3.04	3.13	103	2.88	95	14	4	6	8	1	1	3 mm gouge in fault zone at 28 to c.a.
185	215.49	218.54	3.05	2.94	96	2.63	86	14	4	6	7	1	1	trace gouge on slip at 35 to c.a.
185	218.54	221.59	3.05	2.94	96	2.94	96	15	4	6	3	2	2	
185	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6	3	2	2	
185	224.64	227.69	3.05	3.08	101	3.08	101	15	4	6	2	1	1	
185	227.69	230.73	3.04	3.06	101	3.01	99	15	4	6	4	1	1	5 cm broken core
185	230.73	233.78	3.05	3.00	98	3.00	98	15	4	6	3	2	1	
185	233.78	236.83	3.05	3.05	100	3.01	99	15	4	6	4	2	1	
185	236.83	239.88	3.05	3.05	100	3.05	100	15	4	6	3	2	1	
185	239.88	242.93	3.05	2.94	96	2.94	96	14	4	6	6	1	1	3-5 mm gouge in fault zone at 20 to c.a.
185	242.93	245.97	3.04	3.09	102	3.09	102	15	4	6	2	2	1	
185	245.97	249.02	3.05	2.96	97	2.96	97	15	4	6	3	2	2	
185	249.02	252.07	3.05	3.05	100	3.05	100	15	4	6	3	2	1	
185	252.07	255.12	3.05	3.09	101	3.09	101	15	4	6	1	2	1	
185	255.12	258.17	3.05	3.01	99	2.98	98	15	4	6	4	2	1	
185	258.17	261.21	3.04	3.04	100	3.04	100	15	4	6	3	2	1	
185	261.21	264.26	3.05	3.05	100	3.05	100	15	4	6	2	2	1	
185	264.26	267.31	3.05	3.05	100	3.05	100	15	4	6	2	2	2	
185	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
185	270.36	273.41	3.05	2.97	97	2.97	97	15	4	6	2	1	1	break on carb vein at 10-15 to c.a.
185	273.41	276.45	3.04	2.94	97	2.94	97	15	4	6	2	1	1	trace gouge on slip
185	276.45	279.50	3.05	3.11	102	3.11	102	15	4	6	2	2	2	
185	279.50	282.55	3.05	3.01	99	3.01	99	15	4	6	4	2	2	rough breaks at 15-20 to c.a. with tr gouge
185	282.55	285.60	3.05	3.11	102	2.62	86	14	4	6	10	1	1	50 cm weak broken ang core with tr gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
185	285.60	288.65	3.05	2.98	98	2.77	91	14	4	6	7	2	2	2 locally 10 cm mod broken angular core
185	288.65	291.69	3.04	3.00	99	2.86	94	14	4	6	6	1	1	1 trace gouge on slip
185	291.69	294.74	3.05	3.08	101	3.08	101	15	4	6	4	1	1	1 trace gouge on slip
185	294.74	297.79	3.05	2.98	98	2.68	88	14	4	6	9	1	1	1 trace gouge on slip
185	297.79	300.84	3.05	3.05	100	2.47	81	14	4	6	10	1	1	1 trace gouge on slip
185	300.84	303.89	3.05	3.05	100	2.98	98	15	4	6	4	1	1	1 trace gouge on slip
185	303.89	306.93	3.04	2.93	96	2.54	84	14	4	6	9	1	1	1 trace gouge on slip
185	306.93	309.98	3.05	3.10	102	3.01	99	15	4	6	5	1	1	1 trace gouge on slip
185	309.98	313.03	3.05	3.08	101	3.08	101	14	4	6	6	1	1	1 trace gouge on slip
185	313.03	316.08	3.05	3.14	103	3.14	103	15	4	6	3	1	1	1 trace gouge on slip
185	316.08	319.13	3.05	3.00	98	2.84	93	15	4	6	4	1	1	1 trace gouge on slip
185	319.13	322.17	3.04	3.17	104	3.17	104	15	4	6	3	2	2	
185	322.17	325.22	3.05	2.94	96	2.68	88	14	4	6	6	1	1	1 20 cm cemented gouge at 45 to c.a.
185	325.22	328.27	3.05	2.92	96	2.92	96	15	4	6	5	1	1	1 60 cm with 50% gouge
185	328.27	331.32	3.05	3.21	105	3.21	105	15	4	6	4	1	1	1 10 cm gouge at 65 to c.a.
185	331.32	334.37	3.05	3.00	98	3.00	98	15	4	6	2	1	1	1 2 mm gouge on slip at 35 to c.a.
185	334.37	337.41	3.04	2.84	93	2.82	93	15	4	6	3	2	2	2 3 cm broken core
185	337.41	340.46	3.05	3.05	100	2.75	90	14	4	6	10	1	1	1 10 cm broken core with gouge
185	340.46	343.51	3.05	2.97	97	1.94	64	12	4	6	21	1	1	1 gouge in broken core
185	343.51	346.56	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 gouge on slip - 1.35 m dyke with H=5
185	346.56	349.61	3.05	2.97	97	2.76	90	15	4	6	5	2	1	
185	349.61	352.65	3.04	3.04	100	3.04	100	15	4	6	4	2	2	
185	352.65	355.70	3.05	3.05	100	3.05	100	14	4	6	6	1	1	1 gouge on slip-20 cm wk shr zone 50 to c.a.
185	355.70	358.75	3.05	3.11	102	3.11	102	15	4	6	4	1	1	1 trace gouge on slip
186	14.32	17.37	3.05	1.05	34	0.00	0	5	3	3	25	4	2	2 blocky, limonite on fractures
186	17.37	20.42	3.05	1.90	62	0.23	8	6	3	3	40	4	2	2 blocky, limonite on fractures, 10 cm gouge
186	20.42	23.47	3.05	0.50	16	0.00	0	5	4	4	15	5	3	3 blocky, limonite on fractures
186	23.47	26.52	3.05	1.30	43	0.70	23	8	4	5	15	2	2	2 blocky, limonite on fractures, solid section
186	26.52	29.57	3.05	1.90	62	0.73	24	8	4	5	25	1	2	2 blocky, limonite on fractures, solid section
186	29.57	32.61	3.04	0.50	16	0.00	0	5	4	4	12	3	2	2 blocky, limonite on fractures
186	32.61	33.83	1.22	0.25	20	0.00	0	5	4	3	10	3	4	4 blocky, limonite on fractures
186	33.83	34.44	0.61	0.40	66	0.00	0	5	4	3	10	2	2	2 blocky, limonite on fractures
186	34.44	35.66	1.22	0.40	33	0.00	0	5	4	3	10	1	2	2 blocky, limonite on fractures
186	35.66	36.27	0.61	0.30	49	0.00	0	5	4	3	10	5	3	3 blocky, limonite on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
186	36.27	38.71	2.44	1.30	53	0.50	20	7	4	3	20	2	3	blocky, limonite on fractures
186	38.71	39.93	1.22	0.20	16	0.00	0	5	4	3	10	5	3	blocky, limonite on fractures
186	39.93	41.15	1.22	0.75	61	0.00	0	5	4	3	25	1	2	blocky, limonite on fractures
186	41.15	43.89	2.74	0.45	16	0.10	4	7	4	3	10	5	3	blocky, li on fractures, 20 cm perv. lim.
186	43.89	44.81	0.92	0.25	27	0.00	0	6	4	4	5	3	2	blocky, limonite on fractures
186	44.81	46.63	1.82	0.25	14	0.00	0	5	4	4	10	5	3	blocky, limonite on fractures + gouge/clay
186	46.63	47.24	0.61	0.35	57	0.00	0	6	4	4	10	3	2	blocky, trace limonite
186	47.24	50.90	3.66	0.30	8	0.00	0	3	4	4	10	1	2	blocky, trace limonite
186	50.90	53.95	3.05	0.20	7	0.00	0	5	4	4	10	5	3	blocky, trace limonite
186	53.95	57.00	3.05	0.35	11	0.00	0	3	4	4	10	1	2	blocky, trace limonite + 7 cm gouge
186	57.00	60.05	3.05	0.20	7	0.00	0	5	4	4	6	5	3	blocky, trace limonite
186	60.05	63.09	3.04	0.45	15	0.00	0	5	4	4	12	5	3	blocky, trace limonite
186	63.09	65.53	2.44	0.20	8	0.00	0	5	4	4	10	5	3	blocky
186	65.53	67.06	1.53	0.45	29	0.00	0	5	4	4	15	5	3	blocky
186	67.06	67.67	0.61	0.15	25	0.00	0	5	4	4	10	5	3	blocky
186	67.67	73.15	5.48	0.00	0	0.00	0							casing
186	73.15	74.07	0.92	0.25	27	0.00	0	6	4	5	6	1	2	
186	74.07	75.29	1.22	0.85	70	0.15	12	6	4	5	15	1	2	
186	75.29	75.59	0.30	0.25	83	0.10	33	6	4	5	6	1	2	
186	75.59	76.20	0.61	0.65	107	0.22	36	7	4	5	8	1	2	
186	76.20	76.81	0.61	0.35	57	0.12	20	7	4	5	6	1	2	
186	76.81	77.42	0.61	0.60	98	0.00	0	5	4	5	20	5	3	
186	77.42	78.33	0.91	0.17	19	0.00	0	5	4	5	10	5	3	
186	78.33	80.16	1.83	0.15	8	0.00	0	5	4	5	10	5	3	
186	80.16	81.38	1.22	0.30	25	0.00	0	5	4	5	15	5	3	
186	81.38	83.82	2.44	0.65	27	0.00	0	5	4	5	25	1	2	
186	83.82	84.12	0.30	0.40	133	0.00	0	5	4	5	15	3	2	
186	84.12	84.73	0.61	0.30	49	0.00	0	5	4	5	10	1	2	
186	84.73	85.65	0.92	0.35	38	0.00	0	5	4	5	15	5	3	
186	85.65	87.48	1.83	2.00	109	2.00	109	15	4	6	0			
186	87.48	90.53	3.05	3.05	100	3.05	100	15	4	6	0			
186	90.53	93.57	3.04	3.04	100	3.04	100	15	4	6	1	1	2	along gypsum vein
186	93.57	96.62	3.05	3.05	100	3.05	100	15	4	6	1	3	3	
186	96.62	99.67	3.05	3.05	100	3.05	100	15	4	6	1	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
186	99.67	102.72	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
186	102.72	105.77	3.05	3.05	100	3.05	100	15	4	6	0			
186	105.77	108.81	3.04	3.04	100	3.04	100	15	4	6	2	1	2	
186	108.81	111.86	3.05	3.05	100	3.05	100	15	4	6	0			
186	111.86	114.91	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
186	114.91	117.96	3.05	3.05	100	2.80	92	15	3	5	5	1	2	2 DQCA between 116.3 - 117.7 m
186	117.96	121.01	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
186	121.01	124.05	3.04	3.04	100	3.04	100	15	4	6	0			
186	124.05	127.10	3.05	3.05	100	2.65	87	15	4	6	5	1	2	2 40 cm gypsum shear at 45 to c.a.
186	127.10	130.15	3.05	3.05	100	3.05	100	15	4	6	0			
186	130.15	133.20	3.05	3.05	100	3.05	100	15	4	6	3	1	2	1 polished shear at 25 to c.a.
186	133.20	136.25	3.05	3.05	100	2.80	92	15	2	3	3	1	2	2 aprox. 1 m healed shear
186	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6	0			
186	139.29	142.34	3.05	3.05	100	3.05	100	15	4	6	0			
186	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
186	145.39	148.44	3.05	3.05	100	2.80	92	15	4	6	5	1	2	
186	148.44	151.49	3.05	3.05	100	2.65	87	14	3	5	7	1	2	2 healed fault + gouge at 32 and 45 to c.a.
186	151.49	154.53	3.04	3.04	100	2.80	92	15	4	6	4	1	2	
186	154.53	157.58	3.05	3.05	100	3.05	100	15	4	6	3	1	2	2 gypsum stockwork
186	157.58	160.63	3.05	3.05	100	2.80	92	14	4	6	7	4	2	
186	160.63	163.68	3.05	3.05	100	2.60	85	15	4	6	5	1	2	
186	163.68	166.73	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
186	166.73	169.77	3.04	3.04	100	3.04	100	15	3	5	2	3	3	3 healed shearing
186	169.77	172.82	3.05	3.05	100	3.05	100	15	3	5	1	1	2	2 healed shearing
186	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
186	175.87	178.92	3.05	3.05	100	3.05	100	15	4	6	0		2	50 cm dyke at 80 and 40 to c.a.
186	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	2	3	3	
186	181.97	185.01	3.04	3.04	100	3.04	100	15	4	6	0			
186	185.01	188.06	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
186	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	0			
186	191.11	194.16	3.05	3.05	100	3.05	100	15	4	6	1	5	3	
186	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6	3	1	2	2 gypsum fracture filling
186	197.21	200.25	3.04	3.04	100	3.04	100	15	4	6	2	1	3	3 gypsum fracture filling
186	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	1	3	2	2 gypsum fracture filling

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
186	203.30	206.35	3.05	3.05	100	3.05	100	15	4	6	0			gypsum fracture filling
186	206.35	209.40	3.05	2.85	93	2.85	93	15	4	6	3	3	1	gypsum fracture filling
186	209.40	212.45	3.05	2.90	95	2.90	95	15	4	6	0			gypsum fracture filling
186	212.45	215.49	3.04	3.10	102	3.10	102	15	4	6	2	1	2	gypsum fracture filling
186	215.49	218.54	3.05	2.85	93	2.85	93	15	4	6	0			gypsum fracture filling
186	218.54	221.59	3.05	2.80	92	2.80	92	15	4	6	0			gypsum fracture filling
186	221.59	224.64	3.05	3.10	102	3.10	102	15	4	6	1	1	2	gypsum fracture filling
186	224.64	227.69	3.05	2.95	97	2.95	97	15	4	6	2	1	2	gypsum fracture filling
186	227.69	230.73	3.04	3.15	104	3.15	104	15	4	6	2	1	2	gypsum fracture filling
186	230.73	233.78	3.05	3.10	102	3.10	102	15	4	6	1	1	2	gypsum fracture filling
186	233.78	236.83	3.05	3.20	105	3.20	105	15	4	6	0			gypsum fracture filling
186	236.83	239.88	3.05	3.10	102	3.10	102	15	4	6	0			gypsum fracture filling
186	239.88	242.93	3.05	3.10	102	3.10	102	15	4	6	0			gypsum fracture filling
186	242.93	245.97	3.04	3.15	104	3.15	104	15	4	6	0			gypsum fracture filling
186	245.97	249.02	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum fracture filling
186	249.02	252.07	3.05	3.20	105	3.20	105	15	4	6	3	1	2	gypsum fracture filling
186	252.07	255.12	3.05	3.20	105	3.20	105	15	4	6	0			gypsum fracture filling
186	255.12	258.17	3.05	3.05	100	3.05	100	15	4	6	1	3	3	gypsum fracture filling + breccia
186	258.17	261.21	3.04	3.00	99	3.00	99	15	4	6	3	1	2	breccia
186	261.21	264.26	3.05	3.05	100	3.05	100	15	4	6	3	3	2	dyke between 263.2 - 265.5 m
186	264.26	267.31	3.05	2.90	95	2.70	89	14	4	5	7	1	2	
186	267.31	270.36	3.05	3.10	102	3.10	102	15	4	6	2	3	2	gypsum vein
186	270.36	273.41	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
186	273.41	276.45	3.04	2.95	97	2.95	97	15	4	6	2	3	3	
186	276.45	279.50	3.05	3.10	102	3.10	102	15	4	6	0			
186	279.50	282.55	3.05	3.15	103	3.15	103	15	4	6	0			
186	282.55	285.60	3.05	3.05	100	2.50	82	15	4	6	9	3	2	50 cm frac/shear parallel to c.a.
186	285.60	288.65	3.05	2.95	97	2.95	97	15	4	6	3	1	1	
186	288.65	291.69	3.04	3.15	104	2.70	89	14	4	6	6	1	2	
186	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	5	3	1	
186	294.74	297.79	3.05	3.20	105	3.20	105	15	4	6	0			
186	297.79	300.84	3.05	3.05	100	2.75	90	15	4	6	5	3	2	
186	300.84	303.89	3.05	2.65	87	2.30	75	15	4	6	5	3	2	gypsum stockwork
186	303.89	306.93	3.04	3.20	105	3.20	105	15	4	6	4	1	2	gypsum stockwork

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
186	306.93	309.98	3.05	3.05	100	3.05	100	15	4	6	5	1	3	gypsum stockwork
186	309.98	313.03	3.05	2.95	97	2.95	97	15	4	6	2	1	3	gypsum stockwork
186	313.03	316.08	3.05	2.95	97	2.95	97	15	4	6	3	1	2	gypsum stockwork
186	316.08	319.13	3.05	3.00	98	3.00	98	15	4	6	4	1	2	gypsum stockwork
186	319.13	322.17	3.04	3.35	110	3.30	109	15	4	6	3	3	2	gypsum stockwork
186	322.17	325.22	3.05	3.05	100	3.05	100	15	4	6	3	3	3	3 gy stckwrk w/ two 1 cm go at 30 to c.a.
186	325.22	328.27	3.05	3.05	100	3.05	100	15	4	6	1	5	3	gypsum stockwork
186	328.27	331.32	3.05	3.05	100	3.05	100	15	4	6	0			gypsum stockwork
186	331.32	334.37	3.05	2.70	89	2.70	89	14	4	5	7	1	2	gypsum stockwork
186	334.37	337.41	3.04	2.70	89	2.70	89	14	4	5	5	3	3	gypsum stockwork
186	337.41	340.46	3.05	2.60	85	2.60	85	14	4	6	9	1	2	gy stckwrk w/ one 1 cm shear at 55 to c.a.
186	340.46	343.51	3.05	2.50	82	2.50	82	14	4	6	6	3	3	gypsum stockwork
186	343.51	346.56	3.05	3.00	98	3.00	98	15	4	6	3	3	2	gypsum stockwork
186	346.56	349.61	3.05	3.50	115	3.50	115	15	4	6	0			gypsum stockwork
187	9.14	11.28	2.14	0.61	29	0.00	0	6	3	4	40	2	3	100% broken, minor gouge, bleached
187	11.28	14.33	3.05	1.62	53	0.00	0	6	3	4	50	2	3	100% broken
187	14.33	16.76	2.43	1.82	75	0.00	0	6	2	4	50	1	1	100% broken, 30 cm H=0, py on fractures
187	16.76	18.59	1.83	1.13	62	0.00	0	6	3	4	50	2	3	100% broken
187	18.59	19.81	1.22	1.13	93	0.20	16	6	3	4	30	1	2	100% broken
187	19.81	20.73	0.92	0.73	79	0.00	0	6	3	4	30	2	3	100% broken, py on fract, poor recovery
187	20.73	22.25	1.52	0.50	33	0.00	0	3	3	3	50	1	3	100% broken, poor recovery
187	22.25	24.69	2.44	0.50	20	0.00	0	3	2	3	30	1	1	100% broken, poor recovery
187	24.69	26.52	1.83	0.37	20	0.00	0	3	2	3	40	1	1	100% broken, poor recovery, gouge/dyke
187	26.52	54.86	28.34	0.00	0									triconed, no recovery
187	54.86	57.00	2.14	0.95	44	0.10	5	5	2	3	30	1	2	20 cm of H=0
187	57.00	60.05	3.05	1.83	60	0.20	7	6	2	4	26	1	3	very poor recovery
187	60.05	61.87	1.82	1.27	70	0.80	44	7	3	4	14	1	3	very poor recovery
187	61.87	62.79	0.92	0.73	79	0.24	26	4	2	4	16	1	2	very poor recovery
187	62.79	64.31	1.52	1.19	78	0.35	23	3	3	4	32	1	3	very poor recovery, 12 cm of H=0
187	64.31	65.53	1.22	0.28	23	0.16	13	6	2	4	6	1	3	rubble, poor recovery, gouge
187	65.53	67.97	2.44	1.23	50	0.53	22	5	3	4	40	1	2	poor recovery, 29 cm of H=0
187	67.97	68.88	0.91	0.60	66	0.15	16	5	2	4	20	1	2	minor gouge
187	68.88	71.63	2.75	1.00	36	0.00	0	1	0	2	80	1	1	well weathered material.
187	71.63	73.15	1.52	0.53	35	0.12	8	5	2	4	27	1	3	13 cm of H=0

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
187	73.15	75.29	2.14	1.10	51	0.52	24	6	3	4	25	1	2	redrilled core
187	75.29	78.33	3.04	0.98	32	0.00	0	2	2	3	50	1	1	redrilled core, 25 cm of H=0
187	78.33	79.55	1.22	1.00	82	0.90	74	6	2	4	22	1	2	10 cm gouge
187	79.55	80.47	0.92	0.48	52	0.17	18	5	2	4	13	1	3	poor recovery
187	80.47	81.99	1.52	0.83	55	0.36	24	5	2	4	23	1	3	poor recovery, 12 cm gouge
187	81.99	83.21	1.22	0.75	61	0.00	0	3	1	3	40	1	1	heavy gouge
187	83.21	86.26	3.05	1.07	35	0.15	5	2	0	1	70	1	1	50% of H=0
187	86.26	89.31	3.05	2.57	84	2.02	66	11	2	5	16	1	2	gypsum veins, very weak material
187	89.31	90.22	0.91	1.00	110	1.00	110	15	2	5	3	2	2	gypsum veins, very weak material
187	90.22	93.27	3.05	3.05	100	3.05	100	14	2	5	6	2	2	gypsum veins, very weak material
187	93.27	96.32	3.05	3.05	100	3.05	100	15	2	5	5	2	2	gypsum veins, very weak material
187	96.32	99.36	3.04	3.02	99	3.01	99	14	2	5	6	1	1	1 cm shear @ 96.40 m 30 to c.a.
187	99.36	102.41	3.05	3.02	99	3.02	99	15	2	5	3	1	2	
187	102.41	105.77	3.36	3.31	99	3.09	92	14	2	5	7	3	2	gypsum fractures
187	105.77	108.81	3.04	3.09	102	2.49	82	11	2	4	23	1	1	gouge and slicks
187	108.81	111.86	3.05	3.07	101	3.07	101	15	3	5	4	3	2	gypsum fractures
187	111.86	114.91	3.05	2.94	96	2.81	92	14	3	5	8	1	1	13 cm of H=1
187	114.91	117.96	3.05	3.10	102	3.10	102	15	3	6	2	1	1	
187	117.96	121.00	3.04	3.05	100	3.05	100	15	3	6	5	1	1	slick joints
187	121.00	124.05	3.05	2.95	97	2.91	95	14	3	6	6	1	2	4 cm of H=1
187	124.05	127.10	3.05	3.03	99	3.03	99	15	3	6	3	1	3	
187	127.10	130.15	3.05	3.14	103	3.09	101	15	4	6	2	1	3	
187	130.15	133.20	3.05	3.07	101	2.97	97	15	3	6	3	1	3	gouge on fractures
187	133.20	136.25	3.05	3.05	100	2.86	94	15	3	6	4	1	3	
187	136.25	139.29	3.04	2.92	96	2.92	96	15	4	6	2	1	2	
187	139.29	142.34	3.05	3.10	102	3.01	99	15	4	6	3	1	3	
187	142.34	145.39	3.05	3.12	102	3.12	102	15	3	6	2	1	3	gypsum on fractures
187	145.39	148.44	3.05	3.07	101	2.89	95	15	3	6	4	1	3	gypsum on fractures
187	148.44	151.49	3.05	3.14	103	3.04	100	15	3	6	2	1	3	gypsum on fractures
187	151.49	154.53	3.04	3.11	102	2.97	98	15	3	6	4	1	3	gypsum and gouge on fractures
187	154.53	157.58	3.05	3.05	100	3.05	100	15	3	6	4	1	2	gypsum
187	157.58	160.63	3.05	3.05	100	3.05	100	14	3	5	8	1	1	gouge in sections
187	160.63	163.68	3.05	2.89	95	2.81	92	15	3	5	3	1	3	gouge on fractures
187	163.68	166.73	3.05	3.05	100	2.94	96	15	3	6	2	1	3	gypsum on fractures, 25 cm of H=2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
187	166.73	169.77	3.04	3.04	100	3.04	100	15	3	5	3	1	3	3 gypsum and gouge on fractures
187	169.77	172.82	3.05	3.25	107	3.25	107	15	3	6	2	1	3	
187	172.82	175.87	3.05	2.91	95	2.65	87	15	4	6	4	1	3	3 gouge on fractures, 6 cm H=2
187	175.87	178.92	3.05	3.09	101	2.78	91	15	3	6	6	1	3	3 gypsum on fractures
187	178.92	181.97	3.05	2.97	97	2.68	88	15	3	6	4	1	3	3 fault gouge, 45 to c.a., 15 cm H=2
187	181.97	185.01	3.04	3.17	104	3.17	104	15	3	6	3	1	3	3 gouge on fractures
187	185.01	188.06	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
187	188.06	191.11	3.05	2.96	97	2.84	93	15	3	6	4	1	3	3 fault gouge, 55 to c.a., 14 cm H=2
187	191.11	194.16	3.05	3.08	101	3.08	101	15	3	6	2	1	3	3 gouge on fractures
187	194.16	197.21	3.05	3.09	101	3.09	101	15	3	6	1	2	3	3 7 cm of H=2
187	197.21	200.25	3.04	3.07	101	3.07	101	15	3	6	3	1	3	3 gypsum on fractures
187	200.25	203.30	3.05	3.12	102	3.03	99	15	3	6	4	1	3	3 gypsum on fractures
187	203.30	206.35	3.05	3.05	100	3.05	100	15	3	6	2	2	3	3 gypsum on fractures
187	206.35	209.40	3.05	3.07	101	3.07	101	15	3	6	2	1	3	3 gypsum on fractures
187	209.40	212.45	3.05	3.05	100	3.05	100	15	3	6	3	1	3	3 gypsum on fractures
187	212.45	215.49	3.04	3.04	100	2.83	93	15	3	6	4	1	3	3 gypsum on fractures, 10 cm H=2
187	215.49	218.54	3.05	2.92	96	2.79	91	14	3	6	5	1	3	3 gypsum on fractures, 7 cm H=2
187	218.54	221.59	3.05	3.12	102	3.12	102	15	4	6	1	1	3	3 gypsum on fractures
187	221.59	224.64	3.05	3.03	99	2.96	97	15	3	6	4	2	3	3 gypsum on fractures, 27 cm H=2
187	224.64	227.69	3.05	3.15	103	2.94	96	14	3	6	7	1	3	3 gypsum on fractures
187	227.69	230.73	3.04	3.09	102	3.09	102	15	3	6	4	1	3	3 gypsum on fractures
187	230.73	233.78	3.05	3.19	105	1.10	36	14	2	5	8	2	3	3 healed fault gouge, contacts 45 - 50 to c.a.
187	233.78	236.83	3.05	3.15	103	2.68	88	15	3	5	5	1	3	3 healed fault gouge, contacts 45 - 50 to c.a.
187	236.83	239.88	3.05	3.04	100	3.04	100	15	3	6	2	1	3	
187	239.88	242.93	3.05	2.92	96	2.69	88	15	3	6	4	1	3	
187	242.93	245.36	2.43	2.59	107	2.47	102	15	3	5	4	1	1	1 healed gouge, slick 30 to c.a.
187	245.36	247.80	2.44	2.40	98	2.38	98	15	3	5	4	1	1	1 2 cm shear along fracture
187	247.80	249.02	1.22	1.18	97	0.48	39	4	1	3	40	1	1	1 partially healed fault, brecciated
187	249.02	251.16	2.14	3.16	148	0.67	31	6	1	2	70	1	1	1 partially healed fault, brxx and banded
187	251.16	255.12	3.96	3.12	79	2.12	54	10	3	6	27	1	1	1 252.27 m gouge ends, 1 m H=1,0; W=2
187	255.12	258.17	3.05	2.96	97	2.96	97	15	4	6	2	1	3	
187	258.17	261.21	3.04	2.85	94	2.85	94	15	4	6	0			volcanics
187	261.21	264.26	3.05	3.19	105	3.19	105	15	4	6	0			volcanics
187	264.26	267.31	3.05	3.14	103	2.64	87	12	4	6	16	1	1	1 very slick, W=3, 50 cm of H=2

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
187	267.31	270.36	3.05	2.95	97	2.95	97	15	4	6	0			volcanics
187	270.36	273.41	3.05	3.10	102	3.10	102	15	4	6	0			volcanics
187	273.41	276.45	3.04	2.83	93	2.83	93	15	4	6	2	1	2	volcanics
187	276.45	279.50	3.05	3.25	107	3.18	104	15	4	6	5	1	2	brecciated segments, minor faulting
187	279.50	282.55	3.05	2.79	91	2.79	91	15	4	6	6	3	3	brecciated segments, minor faulting
187	282.55	285.60	3.05	3.30	108	2.07	68	14	3	6	8	1	1	brxx segments, minor faulting, v. slick
187	285.60	288.65	3.05	3.11	102	2.96	97	14	3	6	8	1	1	brxx segments, minor faulting, v. slick
187	288.65	291.69	3.04	3.00	99	3.00	99	15	4	6	6	1	1	brecciated segments, minor faulting
187	291.69	294.74	3.05	3.12	102	3.12	102	15	4	6	3	1	1	brecciated segments, minor faulting
187	294.74	297.79	3.05	2.96	97	2.58	85	8	3	5	40	1	1	unhealed gouge, 38 cm H=0
187	297.79	300.84	3.05	3.05	100	2.92	96	14	4	6	9	1	1	gouge-filled fractures, v. slick
187	300.84	303.89	3.05	3.00	98	2.86	94	14	3	6	8	1	1	
187	303.89	306.93	3.04	3.02	99	2.72	89	12	3	5	12	1	1	70 cm of H=2
187	306.93	309.98	3.05	3.05	100	3.05	100	15	4	6	3	1	1	redrilled core
187	309.98	313.03	3.05	3.05	100	3.05	100	15	4	6	3	1	1	sections of very hard rock
187	313.03	316.08	3.05	3.15	103	3.15	103	15	4	6	2	1	2	
187	316.08	319.13	3.05	2.98	98	2.82	92	14	4	6	7	1	1	infilled fractures; very slick
187	319.13	322.17	3.04	2.90	95	2.81	92	15	4	6	5	1	1	mineralized joints
187	322.17	325.22	3.05	3.07	101	3.07	101	14	4	6	6	1	1	weak slicks
187	325.22	328.27	3.05	2.82	92	2.70	89	14	4	6	5	1	1	1 cm gouge in fault zone at 40 to c.a.
187	328.27	331.32	3.05	3.37	110	3.27	107	15	4	6	5	1	1	weakly broken core w/ gouge
187	331.32	334.37	3.05	3.05	100	2.55	84	13	4	6	13	1	2	weakly broken core w/ no gouge
187	334.37	337.41	3.04	2.82	93	2.78	91	14	4	6	7	1	1	
187	337.41	340.46	3.05	3.00	98	3.00	98	15	4	6	3	1	1	
187	340.46	343.51	3.05	2.88	94	2.88	94	15	4	6	3	1	1	trace gouge on slip
187	343.51	345.03	1.52	1.86	122	1.74	114	14	4	6	3	1	1	carbonate vein subparallel to c.a.
188	40.50	41.76	1.26	1.15	91	0.92	73	13	3	4	10	1	2	missing core?
188	41.76	44.81	3.05	3.10	102	2.63	86	11	3	3	20	1	1	small shear zones
188	44.81	47.85	3.04	3.07	101	2.55	84	10	0	3	25	1	1	small shear zones
188	47.85	50.90	3.05	3.10	102	2.70	89	13	0	2	13	1	2	shear gouge zone 60 cm wide
188	50.90	53.95	3.05	3.00	98	3.00	98	15	3	6	4	1	2	gypsum fractures; breccia unit
188	53.95	57.00	3.05	3.05	100	3.05	100	14	3	6	8	1	1	breccia unit
188	57.00	60.96	3.96	2.75	69	0.35	9	6	3	2	50	1	2	broken rock; ground and lost core
188	60.96	66.14	5.18	1.91	37	1.19	23	6	3	2	50	1	2	lost core; triconed for part of interval

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
188	66.14	69.19	3.05	2.91	95	2.18	71	12	3	6	16	1	2	DPFH dyke
188	69.19	72.24	3.05	2.95	97	1.90	62	12	4	6	17	1	2	
188	72.24	75.29	3.05	3.30	108	1.10	36	6	4	4	50	1	1	sandy section for 10 cm; broken rock
188	75.29	78.33	3.04	2.65	87	0.78	26	6	4	4	50	1	2	broken rock
188	78.33	81.38	3.05	3.00	98	0.32	10	6	3	4	50	1	2	broken rock
188	81.38	84.43	3.05	2.87	94	1.30	43	8	3	5	40	1	2	
188	84.43	87.48	3.05	3.22	106	1.64	54	7	0	3	50	1	2	gouge and broken rock for 50 cm.
188	87.48	90.53	3.05	3.02	99	2.05	67	10	2	5	30	2	2	
188	90.53	93.57	3.04	3.25	107	2.19	72	11	0	4	20	4	3	gouge sections
188	93.57	96.62	3.05	3.08	101	1.96	64	12	0	3	18	2	2	fault gouge (missing block)
188	96.62	99.67	3.05	3.20	105	1.92	63	10	1	4	25	1	2	
188	99.67	102.72	3.05	3.30	108	1.86	61	11	1	4	20	1	2	
188	102.72	105.77	3.05	2.73	90	1.76	58	10	3	5	24	1	2	
188	105.77	108.82	3.05	3.10	102	2.90	95	13	0	5	11	1	2	1 cm gouge zone
188	108.82	111.86	3.04	3.08	101	2.60	86	13	3	4	12	1	1	1-2 cm gouge zone
188	111.86	114.91	3.05	3.05	100	2.83	93	13	3	5	12	1	1	gouge slip plane
188	114.91	117.96	3.05	3.03	99	3.03	99	14	3	6	9	2	2	
188	117.96	121.01	3.05	2.90	95	2.57	84	13	3	6	11	2	2	
188	121.01	124.05	3.04	2.91	96	2.85	94	14	0	4	8	3	1	gypsum slip surface
188	124.05	127.10	3.05	3.13	103	2.89	95	13	3	5	12	3	1	gypsum slip surface
188	127.10	130.15	3.05	3.12	102	3.12	102	15	3	6	5	2	2	
188	130.15	133.20	3.05	3.02	99	3.02	99	15	1	6	4	1	1	slip surface; gypsum vein
188	133.20	136.25	3.05	3.00	98	3.00	98	14	3	6	7	1	1	polished gypsum plane
188	136.25	139.29	3.04	3.05	100	2.98	98	15	3	6	3	1	1	gouge; mud seam slip
188	139.29	142.34	3.05	3.09	101	3.09	101	15	3	6	4	1	3	
188	142.34	145.39	3.05	3.02	99	2.95	97	15	3	6	4	1	1	gouge slip plane 1 cm
188	145.39	148.44	3.05	3.05	100	2.79	91	14	3	5	8	1	3	
188	148.44	151.49	3.05	3.10	102	2.65	87	13	1	3	11	2	2	gouge & crushed rock
188	151.49	154.53	3.04	3.05	100	3.04	100	13	0	3	11	2	2	20 cm of gouge
188	154.53	157.58	3.05	2.93	96	2.91	95	14	3	6	7	2	2	
188	157.58	160.63	3.05	3.17	104	2.88	94	14	3	5	9	2	1	
188	160.63	163.68	3.05	2.94	96	2.70	89	14	3	6	6	1	1	slip plane
188	163.68	166.73	3.05	3.03	99	2.91	95	14	1	4	6	1	2	slip planes; gouge 0.5 to 1 cm
188	166.73	169.16	2.43	2.25	93	2.09	86	12	2	4	13	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
188	169.16	172.82	3.66	3.58	98	3.58	98	15	3	6	5	3	2	
188	172.82	175.87	3.05	3.16	104	3.10	102	15	3	6	3	3	1	gypsum vein gouge
188	175.87	178.92	3.05	3.00	98	3.00	98	15	3	6	4	1	3	
188	178.92	181.97	3.05	2.98	98	2.98	98	14	3	6	5	3	1	
188	181.97	185.01	3.04	3.10	102	2.79	92	14	3	6	8	1	4	gypsum surface
188	185.01	188.06	3.05	3.06	100	3.06	100	15	3	6	4	3	2	gypsum surface
188	188.06	191.11	3.05	3.10	102	3.03	99	15	3	6	5	1	1	gypsum surface shear
188	191.11	194.16	3.05	3.05	100	3.05	100	15	3	6	5	1	2	gypsum on fractures
188	194.16	197.21	3.05	2.98	98	2.98	98	15	3	6	1	1	2	gypsum and minor gouge on fractures
188	197.21	200.25	3.04	3.04	100	3.04	100	15	3	6	2	1	3	gouge on fractures
188	200.25	203.30	3.05	3.18	104	3.18	104	15	3	6	3	2	3	pyrite on fractures
188	203.30	206.35	3.05	3.01	99	3.01	99	15	3	6	2	1	1	weak slicks on fractures at 30 to c.a.
188	206.35	209.40	3.05	3.04	100	3.04	100	15	3	6	3	1	2	gypsum on fractures
188	209.40	212.45	3.05	2.99	98	2.91	95	14	3	6	7	3	1	50 cm of H=2; gypsum slip plane
188	212.45	215.49	3.04	3.02	99	3.02	99	15	3	6	3	3	2	
188	215.49	218.54	3.05	3.02	99	3.02	99	15	3	6	4	2	2	
188	218.54	221.59	3.05	2.87	94	2.87	94	15	3	6	4	3	2	
188	221.59	224.64	3.05	3.20	105	3.14	103	15	3	6	4	3	2	gypsum fractures
188	224.64	227.69	3.05	3.04	100	3.04	100	15	3	6	5	3	3	gypsum fractures
188	227.69	230.73	3.04	3.04	100	2.93	96	14	3	5	6	3	1	gypsum vein shear
188	230.73	233.78	3.05	3.14	103	3.14	103	15	2	5	3	3	1	gypsum vein shear
188	233.78	236.83	3.05	3.10	102	2.98	98	15	3	5	5	2	1	gy vein shear; three 2-3 cm gouge zones
188	236.83	239.88	3.05	3.03	99	3.03	99	15	3	6	2	1	3	pyrite coated fracture
188	239.88	242.93	3.05	3.15	103	3.15	103	15	3	6	4	4	2	
188	242.93	245.97	3.04	2.97	98	2.97	98	15	3	6	4	3	2	
188	245.97	249.02	3.05	3.04	100	3.04	100	15	3	6	4	4	2	
188	249.02	252.07	3.05	2.95	97	2.95	97	15	3	6	3	2	2	gypsum vein fracture
188	252.07	255.12	3.05	3.02	99	3.02	99	15	3	6	4	2	2	gypsum vein fracture
188	255.12	258.17	3.05	3.11	102	3.11	102	15	3	6	2	2	2	
188	258.17	261.21	3.04	3.23	106	3.23	106	15	3	6	2	2	2	
188	261.21	264.26	3.05	3.05	100	2.83	93	15	3	6	5	2	2	gypsum vein fracture
188	264.26	267.31	3.05	3.04	100	3.04	100	15	3	6	4	4	2	
188	267.31	270.36	3.05	3.09	101	3.09	101	15	3	6	3	3	2	
188	270.36	273.41	3.05	3.00	98	3.00	98	15	3	6	4	4	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
188	273.41	276.45	3.04	3.10	102	3.10	102	15	3	6	4	4	1	slip surface but stepped gouge 5 mm
188	276.45	279.50	3.05	2.92	96	2.47	81	14	3	3	8	3	1	slip surface; two gouge zones of 3 cm
188	279.50	282.55	3.05	3.20	105	2.36	77	13	3	4	12	3	1	slip gouge zones; two at 1 cm wide
188	282.55	285.60	3.05	2.91	95	2.91	95	15	3	6	4	3	2	
188	285.60	288.65	3.05	3.30	108	2.86	94	15	3	6	4	3	2	
188	288.65	291.69	3.04	2.95	97	2.95	97	15	3	6	3	4	2	
188	291.69	294.74	3.05	3.12	102	3.12	102	15	2	5	5	2	1	gouge surface & 15 cm gypsum vein
188	294.74	297.79	3.05	3.05	100	2.91	95	15	3	6	2	3	2	gypsum vein
188	297.79	300.84	3.05	3.11	102	3.11	102	15	3	6	4	3	2	
188	300.84	303.89	3.05	3.02	99	3.00	98	15	2	5	4	1	1	shear gouge zone of 3 cm
188	303.89	306.93	3.04	3.11	102	3.11	102	13	2	4	10	3	2	healed gouge pitted; gouge is 2-3 cm
188	306.93	309.98	3.05	3.05	100	3.05	100	14	0	4	7	2	2	two 10 cm gouge zones
188	309.98	313.03	3.05	3.09	101	3.09	101	15	3	5	3	3	1	
188	313.03	316.08	3.05	3.04	100	2.74	90	14	3	6	7	3	2	
188	316.08	319.13	3.05	3.16	104	3.10	102	14	3	6	4	2	2	
188	319.13	322.17	3.04	3.30	109	3.13	103	15	3	6	4	3	2	broken rock over 3 cm
188	322.17	324.61	2.44	2.10	86	2.05	84	14	3	6	4	3	2	small shear of 1 cm
188	324.61	328.27	3.66	3.70	101	3.48	95	15	3	6	5	1	2	
188	328.27	331.32	3.05	3.20	105	3.20	105	15	2	6	5	3	1	
188	331.32	334.06	2.74	2.60	95	2.42	88	15	0	4	3	3	3	40 cm of gouge at 15-20 to c.a.
189	39.62	41.76	2.14	0.80	37	0.00	0	6	3	6	20	3	2	fractured/crush zone; minor gouge
189	41.76	44.50	2.74	1.00	36	0.00	0	6	3	6	30	3	2	fractured/crush zone; pyrite on fracture
189	44.50	46.94	2.44	0.70	29	0.00	0	6	3	6	20	3	2	fractured/crush zone
189	46.94	49.07	2.13	0.50	23	0.00	0	6	3	6	20	3	2	fractured/crush zone
189	49.07	52.12	3.05	1.00	33	0.00	0	5	3	6	40	3	2	fractured/crush zone
189	52.12	55.17	3.05	1.00	33	0.00	0	5	3	6	50	3	2	fractured/crush zone
189	55.17	57.00	1.83	1.10	60	0.00	0	5	3	6	30	3	2	fractured/crush zone
189	57.00	85.34	28.34	0.00	0	0.00	0							Triconing - No Recovery
189	85.34	88.39	3.05	1.40	46	0.00	0	6	3	6	25	1	2	fractured/crush zone; minor gouge
189	88.39	90.53	2.14	0.20	9	0.00	0	6	3	6	3	3	2	fractured/crush zone
189	90.53	93.57	3.04	2.80	92	0.34	11	7	3	6	50	1	2	
189	93.57	96.62	3.05	1.05	34	0.00	0	7	1	6	18	3	2	predominantly crush/gouge zone
189	96.62	99.67	3.05	3.10	102	0.40	13	7	3	6	48	2	3	
189	99.67	102.72	3.05	0.75	25	0.18	6	7	3	6	11	3	3	pyrite on fracture

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
189	102.72	105.77	3.05	3.02	99	3.02	99	14	3	6	8	3	2 pyrite and gypsum on fractures	
189	105.77	108.81	3.04	3.10	102	2.65	87	12	3	6	15	3	2 pyrite and gypsum on fractures	
189	108.81	111.86	3.05	3.10	102	2.50	82	12	3	6	19	3	3	
189	111.86	114.91	3.05	3.03	99	2.83	93	13	3	6	12	3	2 minor gouge on one fracture	
189	114.91	117.35	2.44	2.50	102	0.80	33	9	3	6	28	3	2 minor gouge on few fractures	
189	117.35	120.09	2.74	2.80	102	0.70	26	10	3	6	26	2	2 crush zone from 119.4 to 119.7 m	
189	120.09	122.83	2.74	2.75	100	2.30	84	12	3	6	16	2	2	
189	122.83	124.05	1.22	1.20	98	0.85	70	11	3	6	8	1	2	
189	124.05	127.10	3.05	3.00	98	2.42	79	10	3	6	24	3	2	
189	127.10	130.15	3.05	3.05	100	2.40	79	12	3	6	18	3	2	
189	130.15	133.20	3.05	3.04	100	2.54	83	12	3	6	17	2	2 minor gouge on few fractures; 1-2 mm wide	
189	133.20	135.64	2.44	2.57	105	1.07	44	9	3	6	32	2	1 135.0 m - 1 cm gouge	
189	135.64	138.68	3.04	3.00	99	2.15	71	10	3	6	23	3	2	
189	138.68	141.73	3.05	3.10	102	2.85	93	13	3	6	15	3	1 1-2 mm gouge on few fractures	
189	141.73	144.78	3.05	3.10	102	1.95	64	10	3	6	26	1	1	
189	144.78	147.22	2.44	2.65	109	0.90	37	9	3	6	30	3	1	
189	147.22	150.27	3.05	3.10	102	2.25	74	10	3	6	21	1	1	
189	150.27	151.49	1.22	1.36	111	0.46	38	7	3	6	20	2	1	
189	151.49	154.53	3.04	3.05	100	2.50	82	13	3	6	14	1	2	
189	154.53	157.58	3.05	3.18	104	3.08	101	12	3	6	16	1	1	
189	157.58	160.63	3.05	3.00	98	0.50	16	7	3	6	40	1	1 minor clay gouge at 159.5 m	
189	160.63	163.68	3.05	3.15	103	2.35	77	12	3	6	19	3	2	
189	163.68	166.73	3.05	3.10	102	2.25	74	12	3	6	19	3	2 crush zone at 165.6 to 166.3 m at 30 to c.a.	
189	166.73	169.77	3.04	3.15	104	2.75	90	13	3	6	14	1	2	
189	169.77	172.82	3.05	3.10	102	1.65	54	12	3	6	19	2	2	
189	172.82	175.87	3.05	3.05	100	2.65	87	14	3	6	9	1	1 crush zone from 173.5 to 174.0 m	
189	175.87	178.92	3.05	3.02	99	2.67	88	13	3	6	11	2	2	
189	178.92	181.97	3.05	3.10	102	2.90	95	14	3	6	6	3	1	
189	181.97	185.01	3.04	2.90	95	2.90	95	15	3	6	4	3	3	
189	185.01	188.06	3.05	3.07	101	2.77	91	13	3	6	11	3	2 dykes	
189	188.06	191.11	3.05	3.10	102	3.10	102	14	3	6	6	3	3	
189	191.11	194.16	3.05	3.15	103	2.70	89	13	3	6	13	1	1 graphitic shears from 191 .6 to 192 m	
189	194.16	197.21	3.05	3.15	103	2.40	79	14	3	6	9	3	3	
189	197.21	200.25	3.04	3.02	99	2.82	93	14	3	6	6	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
189	200.25	203.30	3.05	3.10	102	3.00	98	14	3	6	9	3	3	
189	203.30	206.35	3.05	3.10	102	3.10	102	14	3	6	6	3	3	
189	206.35	209.40	3.05	3.08	101	2.83	93	13	3	6	14	3	1	208.35 m - 1 cm gouge
189	209.40	211.53	2.13	2.20	103	1.20	56	10	3	6	19	3	3	minor ground rock on few fractures
189	211.53	214.58	3.05	3.00	98	2.90	95	14	3	6	8	1	2	
189	214.58	215.49	0.91	1.00	110	1.00	110	14	3	6	2	3	1	minor gouge
189	215.49	218.54	3.05	3.05	100	2.85	93	14	3	6	7	3	1	217.9 to 218.4 m - weak crush zone
189	218.54	221.59	3.05	3.00	98	2.70	89	13	2	6	11	1	1	weak crush zone & minor gouge 40 to c.a.
189	221.59	224.64	3.05	3.10	102	2.80	92	13	2	6	14	2	1	weak crush zone & minor gouge 40 to c.a.
189	224.64	227.69	3.05	3.13	103	3.13	103	14	3	6	9	2	1	
189	227.69	230.73	3.04	3.07	101	2.90	95	14	3	6	8	3	1	minor gouge; weak crush zone
189	230.73	233.78	3.05	3.10	102	3.00	98	13	3	6	12	3	3	
189	233.78	236.83	3.05	3.05	100	2.80	92	12	3	6	15	1	1	minor gouge on few fractures
189	236.83	239.88	3.05	3.08	101	3.08	101	13	2	6	13	3	1	weak crush/fault zone at 237.4-238.3 m
189	239.88	242.93	3.05	3.01	99	2.81	92	13	2	6	12	1	1	weak crush zone; minor gouge
189	242.93	245.97	3.04	3.15	104	3.05	100	13	2	6	12	3	1	
189	245.97	249.02	3.05	3.15	103	1.75	57	9	2	6	37	1	2	fractured dyke at 247.53-249.02 m
189	249.02	252.07	3.05	3.05	100	0.45	15	7	2	6	50	3	2	251.2 m-dyke cont; 251.2-252.07 crush
189	252.07	255.42	3.35	3.20	96	2.00	60	9	2	6	36	3	1	crush zone 255.0 m; dyke cont to 255.4 m
189	255.42	258.17	2.75	3.20	116	1.60	58	8	3	6	44	3	2	mostly dyke; crush/gouge at 258 m
189	258.17	261.21	3.04	3.30	109	1.60	53	9	2	6	38	1	1	sporadic crush & minor gouge
189	261.21	264.26	3.05	3.10	102	2.70	89	12	2	6	16	1	2	crush zone; minor gouge; dykes
189	264.26	267.31	3.05	3.15	103	3.15	103	13	2	6	13	3	2	crush zone; minor gouge; dykes
189	267.31	270.36	3.05	3.10	102	2.60	85	13	2	6	12	1	1	crush zone; minor gouge; no dyke
189	270.36	273.41	3.05	3.20	105	2.60	85	12	2	6	20	3	1	crush zone; minor gouge; dykes
189	273.41	276.45	3.04	3.10	102	3.10	102	13	2	6	12	3	1	crush zone; minor gouge; dykes
189	276.45	279.50	3.05	3.10	102	3.10	102	14	3	6	8	3	3	out of crush zone; gypsum stringers
189	279.50	282.55	3.05	2.85	93	2.55	84	13	3	6	10	3	3	crush zone at 282.0-282.4 m
189	282.55	285.60	3.05	3.10	102	3.10	102	13	3	6	11	3	3	gypsum stringers
189	285.60	288.65	3.05	3.00	98	3.00	98	14	3	6	5	3	3	gypsum stringers
189	288.65	291.69	3.04	3.02	99	3.02	99	14	3	6	5	3	3	gypsum stringers
189	291.69	294.74	3.05	3.00	98	3.00	98	15	3	6	4	3	3	gypsum stringers
189	294.74	297.79	3.05	3.15	103	3.15	103	14	3	6	8	3	3	gypsum stringers
189	297.79	300.84	3.05	3.00	98	3.00	98	15	3	6	2	1	2	gypsum stringers

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
189	300.84	303.89	3.05	3.00	98	3.00	98	15	3	6	5	3	2	gypsum stringers
189	303.89	306.93	3.04	3.07	101	3.07	101	15	3	6	5	1	2	gypsum stringers
189	306.93	309.98	3.05	3.10	102	3.10	102	15	3	6	4	3	3	gypsum stringers
189	309.98	313.03	3.05	2.65	87	1.55	51	10	3	6	25	3	2	gypsum stringers
189	313.03	316.08	3.05	3.04	100	3.04	100	14	3	6	7	1	2	gypsum stringers
190	9.14	11.28	2.14	1.28	60	0.50	23	10	3	5	12	2	3	iron staining on fractures
190	11.28	14.33	3.05	2.68	88	1.75	57	9	3	5	35	2	3	70 cm broken rx with minor gouge (H=2)
190	14.33	16.76	2.43	2.20	91	1.55	64	10	3	5	20	2	3	last 30 cm broken with gouge (H=2)
190	16.76	18.29	1.53	1.32	86	0.60	39	9	3	5	15	2	3	gouge on fractures
190	18.29	21.03	2.74	2.38	87	1.20	44	10	3	6	20	2	2	pyrite on fractures; broken
190	21.03	24.08	3.05	2.85	93	1.80	59	10	3	6	20	2	3	pyrite on fractures
190	24.08	26.52	2.44	2.32	95	1.90	78	13	3	6	10	1	2	pyrite on fractures
190	26.52	29.11	2.59	2.47	95	1.13	44	10	3	6	20	1	3	pyrite and minor gouge on fractures
190	29.11	32.61	3.50	3.39	97	2.95	84	14	3	6	8	2	3	gouge on fractures
190	32.61	35.66	3.05	2.64	87	2.16	71	10	3	5	20	2	3	60 cm of H=2 (shear/gouge)
190	35.66	38.71	3.05	2.70	89	2.22	73	12	3	5	14	2	3	30 cm of H=2; healed; gouge on fract
190	38.71	41.76	3.05	2.99	98	2.30	75	13	3	6	13	2	3	minor gouge on fractures
190	41.76	44.81	3.05	2.86	94	2.57	84	13	4	6	11	1	2	gouge on fractures; cb-py fracture fillings
190	44.81	47.85	3.04	3.20	105	2.62	86	13	4	6	11	1	2	minor gouge on fractures
190	47.85	50.90	3.05	3.02	99	2.84	93	15	3	6	4	1	2	carbonate on fractures
190	50.90	53.95	3.05	2.65	87	2.51	82	13	3	6	9	2	3	2 cm gouge 52.1 m 60 to c.a.; gouge fract
190	53.95	57.00	3.05	3.10	102	3.10	102	15	3	6	2	1	2	calcite on fractures
190	57.00	60.05	3.05	2.96	97	2.75	90	15	3	6	4	1	2	py on fractures; minor gouge on fractures
190	60.05	63.09	3.04	2.74	90	2.50	82	15	2	5	21	1	1	very slick joints at 10 to c.a.
190	63.09	66.14	3.05	3.01	99	2.84	93	14	3	5	8	1	1	very slick joints
190	66.14	69.19	3.05	3.17	104	2.65	87	14	3	5	8	1	1	H=1 for 52 cm
190	69.19	72.24	3.05	2.83	93	2.64	87	14	3	5	9	1	1	slick joints at 25 to c.a.
190	72.24	75.29	3.05	2.95	97	2.53	83	13	2	4	30	1	1	74.79-74.99 m - H=0; very slick
190	75.29	78.33	3.04	2.98	98	1.16	38	3	0	1	100	1	1	60% is H=0,1; 40% is H=2
190	78.33	81.38	3.05	2.77	91	0.00	0	1	0	1	180	1	1	46 cm of H=1; major fault gouge
190	81.38	84.43	3.05	3.37	110	2.96	97	13	2	4	19	1	1	26 cm of H=0; gypsum fractures
190	84.43	87.48	3.05	3.09	101	2.96	97	14	2	4	9	1	1	gouge on slicks; 13 cm of H=0
190	87.48	90.53	3.05	3.07	101	2.74	90	12	2	5	18	1	1	gypsum filled; 33 cm of H=1
190	90.53	93.57	3.04	3.05	100	2.87	94	13	3	6	12	1	1	18 cm of H=0; gypsum

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
190	93.57	96.62	3.05	3.12	102	2.95	97	13	3	5	13	1	1 gouge present; gypsum	
190	96.62	99.67	3.05	3.00	98	3.00	98	15	3	6	4	1	1 gypsum	
190	99.67	102.72	3.05	3.15	103	3.02	99	14	3	6	11	2	1 gypsum; very slick fractures	
190	102.72	105.77	3.05	3.05	100	2.94	96	15	3	6	6	1	1 gypsum; 11 cm of H=0; W=1	
190	105.77	108.81	3.04	3.13	103	3.01	99	14	3	5	7	1	1 gypsum; 12 cm of H=1	
190	108.81	111.86	3.05	2.99	98	2.65	87	14	3	5	8	1	1 weak slicks; minor gouge for 34 cm	
190	111.86	114.91	3.05	3.05	100	0.71	23	5	1	2	40	1	1 sections of H=0; altered rx	
190	114.91	117.96	3.05	3.05	100	2.44	80	13	2	4	60	1	1 slick contacts at 30 to c.a.; 61 cm of H=1,0	
190	117.96	121.01	3.05	2.98	98	2.56	84	13	2	3	11	1	1 42 cm of fault	
190	121.01	124.05	3.04	3.09	102	2.80	92	12	2	3	16	3	3 partially healed fault; vertical, undulating	
190	124.05	127.10	3.05	3.05	100	2.24	73	11	2	4	19	1	1 some undulated contacts; 30% fault; H=0	
190	127.10	130.15	3.05	3.11	102	1.75	57	13	2	5	15	1	1 1.36 m of H=1,0; part healed fault	
190	130.15	133.20	3.05	3.05	100	3.05	100	15	3	6	2	1	2 gypsum filled fractures; healed	
190	133.20	136.25	3.05	3.05	100	2.97	97	15	3	6	6	3	3 gypsum filled fractures; 8 cm part healed	
190	136.25	139.29	3.04	3.04	100	3.04	100	15	3	6	2	1	2 gypsum filled fractures	
190	139.29	142.34	3.05	3.05	100	3.05	100	15	3	6	1	1	2 gypsum filled fractures	
190	142.34	145.39	3.05	3.05	100	3.05	100	15	3	6	3	1	2 gypsum filled fractures	
190	145.39	148.44	3.05	3.05	100	3.05	100	15	3	6	2	1	2 gypsum filled fractures	
190	148.44	151.49	3.05	3.05	100	1.85	61	5	3	6	60	1	1 120 cm of H=0, W=2	
190	151.49	154.53	3.04	3.04	100	2.24	74	10	3	6	30	1	1 clay on fractures; slick at 20 to c.a.	
190	154.53	157.58	3.05	3.05	100	2.83	93	10	2	4	27	1	1 clay slicks; slick at 20 to c.a.; 22 cm clay	
190	157.58	160.63	3.05	3.05	100	0.53	17	6	1	2	23	1	1 broken by hand; clay material	
190	160.63	163.68	3.05	3.05	100	2.41	79	13	3	5	15	1	1 64 cm of W=2; gypsum	
190	163.68	166.73	3.05	3.05	100	2.86	94	14	4	6	6	1	2 20 cm of H=1	
190	166.73	169.77	3.04	3.07	101	3.07	101	15	4	6	2	3	2 small sections of gouge; pyrite	
190	169.77	172.82	3.05	3.05	100	2.61	86	9	2	3	30	1	1 healed gouge	
190	172.82	175.87	3.05	3.02	99	1.30	43	11	2	4	24	1	1 very slick contact; 30 cm of H=0	
190	175.87	178.92	3.05	2.98	98	2.58	85	14	3	6	8	1	1 gypsum slicks; 40 cm of H=2	
190	178.92	181.97	3.05	3.16	104	3.10	102	14	3	6	9	1	1 gypsum slicks	
190	181.97	185.01	3.04	2.84	93	2.84	93	15	4	6	4	1	1 gypsum slicks	
190	185.01	188.06	3.05	3.02	99	3.02	99	15	4	6	5	3	3 gypsum slicks	
190	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	4	1	2 gypsum slicks	
190	191.11	194.16	3.05	2.95	97	2.95	97	15	3	6	5	1	1 gypsum slicks	
190	194.16	197.21	3.05	3.10	102	2.87	94	13	3	6	12	1	1 23 cm of H=0; gouge	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
190	197.21	200.25	3.04	2.88	95	2.19	72	10	3	6	27	1	1	1 very slick
190	200.25	203.30	3.05	3.05	100	2.67	88	14	3	5	11	1	1	1 35 cm of H=1
190	203.30	206.35	3.05	3.10	102	1.48	49	3	0	1	60	1	1	1 50% of H=0; hard rx mixed with gouge
190	206.35	209.40	3.05	2.95	97	2.04	67	2	2	3	100	1	1	1 90 cm of H=0
190	209.40	212.45	3.05	2.66	87	2.01	66	5	2	3	50	1	1	1 50 cm of H=0
190	212.45	215.49	3.04	2.95	97	2.66	87	12	2	3	15	1	1	1 partly healed fault; 40 cm of H=1
190	215.49	218.54	3.05	2.94	96	1.44	47	7	1	2	50	1	1	1 partly healed; clay
190	218.54	221.59	3.05	3.20	105	1.57	51	9	1	2	40	1	1	1 partly clay H=0; healed breccia and fault
190	221.59	224.64	3.05	3.05	100	1.78	58	7	1	2	50	1	1	1 23 cm of H=0
190	224.64	227.69	3.05	2.97	97	1.98	65	10	1	2	30	1	1	1 partly faulted and healed
190	227.69	230.73	3.04	2.99	98	1.28	42	7	1	3	50	1	1	1 partly faulted and healed
190	230.73	233.78	3.05	2.92	96	1.87	61	10	1	3	32	1	1	1 partly faulted and healed
190	233.78	236.83	3.05	2.95	97	2.52	83	11	1	3	18	1	1	1 40 cm of H=0; fault zone; very slick 45 to c.a.
190	236.83	239.88	3.05	2.98	98	2.11	69	9	1	3	40	1	1	1 4 cm fo H=0; gouge filled fracture
190	239.88	242.93	3.05	2.77	91	2.02	66	10	2	4	26	1	2	2 50% partially healed fault
190	242.93	245.97	3.04	3.07	101	2.01	66	9	1	3	35	1	2	2 50% partially healed fault; weak material
190	245.97	249.02	3.05	3.23	106	1.27	42	10	1	2	30	1	1	1 slick dyke contact
190	249.02	252.07	3.05	2.97	97	2.69	88	14	3	5	12	3	3	3 minor gouge on fractures
190	252.07	255.12	3.05	2.94	96	2.18	71	10	3	5	30	1	2	2 H=1,0 for 28 cm; fractures at 30 to c.a.
190	255.12	258.17	3.05	3.05	100	2.65	87	13	4	5	12	1	2	2 pyrite on fractures
190	258.17	261.21	3.04	2.67	88	1.53	50	10	4	5	29	1	1	1 gouge sections; brecciated
190	261.21	264.26	3.05	2.97	97	2.71	89	13	4	5	24	1	2	2 20 cm of H=1
190	264.26	267.31	3.05	3.27	107	1.82	60	7	3	4	50	1	1	1 rubble and gouge
190	267.31	270.36	3.05	2.93	96	1.87	61	10	3	5	27	1	2	2 healed fracture; some rubble
190	270.36	273.41	3.05	3.05	100	1.25	41	7	3	4	40	1	2	2
190	273.41	275.23	1.82	1.66	91	1.35	74	7	2	4	30	1	2	2 well weathered material
190	275.23	276.00	0.77	0.70	91	0.14	18	6	2	4	17	1	2	2
190	276.00	276.45	0.45	0.38	84	0.00	0	6	1	3	8	1	2	2 beginning of gouge; gypsum
190	276.45	279.50	3.05	2.64	87	2.10	69	8	2	3	30	1	1	1 brecciated clay fractures; slicks at 50 to c.a.
190	279.50	280.72	1.22	1.32	108	0.87	71	8	2	4	18	1	2	2
190	280.72	282.55	1.83	1.77	97	1.47	80	14	3	6	7	1	2	2 30 cm of fractured material
190	282.55	285.60	3.05	3.16	104	2.61	86	15	3	6	50	1	1	1 56 cm of H=0,1
190	285.60	288.65	3.05	2.95	97	1.56	51	10	2	5	30	1	1	1
190	288.65	291.69	3.04	3.05	100	3.05	100	15	4	6	4	1	3	3 clean fractures; no shearing

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
190	291.69	294.74	3.05	3.10	102	2.92	96	14	4	5	12	1	3	3 minor gouge on fractures
190	294.74	297.79	3.05	2.90	95	2.40	79	15	4	5	8	1	1	50 cm of H=1; partly healed
190	297.79	300.84	3.05	2.98	98	2.81	92	15	4	5	5	1	3	3 healed fractures; carbonate?
190	300.84	303.89	3.05	2.81	92	2.51	82	12	3	6	15	1	2	30 cm of H=0,1; W=2
190	303.89	306.93	3.04	2.80	92	1.93	63	10	3	4	23	1	1	calcite & gouge filled fractures
190	306.93	309.98	3.05	2.76	90	2.22	73	12	3	5	17	1	1	54 cm of H=1
190	309.98	313.94	3.96	3.82	96	2.62	66	11	3	4	24	1	1	very slick contact; one slick
190	313.94	316.08	2.14	2.15	100	1.29	60	10	3	4	18	1	2	50% partially healed gouge; W=2
190	316.08	319.13	3.05	2.18	71	1.58	52	10	4	6	20	1	2	60 cm of H=1; healed gouge
190	319.13	322.17	3.04	2.77	91	2.66	87	11	4	5	17	2	1	11 cm of healed gouge; H=1

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
191	13.41	16.76	3.35	1.40	42	0.10	3	6	3	5	50	3	1 highly fractured throughout (minor gouge)	
191	16.76	19.81	3.05	2.80	92	0.20	7	7	3	5	40	3	1 highly fractured throughout (minor gouge)	
191	19.81	23.16	3.35	2.10	63	0.00	0	6	3	5	50	1	2 highly fractured throughout (minor gouge)	
191	23.16	24.38	1.22	0.90	74	0.00	0	6	3	6	20	2	1 highly fractured throughout (minor gouge)	
191	24.38	25.91	1.53	1.30	85	0.00	0	6	3	6	50	3	2 highly fractured throughout (minor gouge)	
191	25.91	28.35	2.44	0.60	25	0.00	0	6	3	6	50	3	2 highly fractured throughout (minor gouge)	
191	28.35	30.48	2.13	1.10	52	0.10	5	6	3	6	50	1	1 highly fractured throughout (minor gouge)	
191	30.48	33.22	2.74	1.30	47	0.00	0	6	3	6	50	2	2 highly fractured throughout (minor gouge)	
191	33.22	35.66	2.44	1.50	61	0.00	0	7	3	5	50	2	2 highly fract'd; gouge 33.22 to 33.6 m.	
191	35.66	38.71	3.05	1.03	34	0.13	4	4	3	5	30	1	2 32 cm of gouge; H=0	
191	38.71	40.54	1.83	1.14	62	0.23	13	7	3	5	20	1	2 16 cm of gouge; H=0	
191	40.54	41.76	1.22	0.49	40	0.14	11	4	3	5	17	1	2	
191	41.76	44.81	3.05	1.20	39	0.30	10	5	3	5	37	1	2	
191	44.81	47.85	3.04	0.31	10	0.00	0	3	3	4	18	2	2 rubble	
191	47.85	50.90	3.05	1.20	39	0.28	9	4	2	4	40	1	2 21 cm of clay; H=0	
191	50.90	53.95	3.05	0.57	19	0.10	3	3	3	5	30	1	1 11 cm of clay; H=0	
191	53.95	60.05	6.10	1.16	19	0.00	0	2	4	5	100	1	1 missing block; poor rcvry; 10 cm clay; H=0	
191	60.05	63.09	3.04	0.48	16	0.00	0	4	4	6	24	1	2	
191	63.09	66.14	3.05	1.91	63	0.30	10	7	4	6	29	1	2 rubble	
191	66.14	69.19	3.05	1.51	50	0.13	4	7	4	6	24	1	2 rubble	
191	69.19	72.24	3.05	0.51	17	0.00	0	1	0	1	40	1	1	
191	72.24	75.29	3.05	2.80	92	2.41	79	9	4	6	40	1	2 0.39 cm of gouge	
191	75.29	76.81	1.52	1.01	66	0.71	47	10	4	6	30	1	2 30 cm of rubble and gouge	
191	76.81	78.33	1.52	1.30	86	1.30	86	15	5	6	2	1	2	
191	78.33	81.38	3.05	3.20	105	3.16	104	15	5	6	4	1	1 slicks with gouge	
191	81.38	84.43	3.05	2.57	84	2.23	73	9	5	6	30	1	2 H=0, 34 cm of partially healed fault	
191	84.43	87.48	3.05	3.05	100	2.65	87	13	3	5	12	1	1 H=1, 40 cm of partially healed fault	
191	87.48	90.53	3.05	3.02	99	2.82	92	11	4	5	20	1	1 H=0, 20 cm of partially healed fault	
191	90.53	93.57	3.04	2.81	92	2.32	76	14	4	6	9	1	1 manually broken?	
191	93.57	96.62	3.05	2.63	86	0.94	31	12	4	6	23	1	2 manually broken?	
191	96.62	99.67	3.05	2.91	95	2.75	90	13	3	6	18	1	1 brecciated zone, H=3, 15 cm of H=0	
191	99.67	102.72	3.05	3.05	100	2.96	97	14	4	6	10	3	3 competent rock	
191	102.72	105.77	3.05	3.05	100	3.05	100	15	4	6	6	3	3 competent rock	
191	105.77	108.81	3.04	3.04	100	3.04	100	15	4	6	4	3	3 competent rock	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
191	108.81	111.86	3.05	3.05	100	3.05	100	15	4	6	6	3	3	3 competent rock
191	111.86	114.91	3.05	3.05	100	3.00	98	14	5	6	8			minor gouge on fractures
191	114.91	117.96	3.05	3.15	103	2.87	94	13	5	6	10	1	2	28 cm of gouge, H=1
191	117.96	121.01	3.05	3.05	100	3.05	100	15	5	6	3	1	2	very hard rock
191	121.01	124.05	3.04	3.04	100	3.04	100	15	5	6	2	1	1	very hard rock; slick at 45 to c.a.
191	124.05	127.10	3.05	3.05	100	3.05	100	15	5	6	3	1	1	very hard rock; slick at 45 to c.a.
191	127.10	130.15	3.05	3.05	100	3.05	100	15	5	6				very hard rock
191	130.15	133.20	3.05	3.05	100	3.05	100	15	5	6	1	1	2	very hard rock
191	133.20	136.25	3.05	3.05	100	3.05	100	15	5	6	1	2	2	very hard rock
191	136.25	139.29	3.04	3.05	100	3.05	100	15	4	6	1	2	2	very hard rock
191	139.29	142.34	3.05	2.98	98	2.98	98	15	4	6	1	1	4	very hard rock
191	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	4	1	3	
191	145.39	148.44	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
191	148.44	151.49	3.05	3.05	100	3.03	99	15	4	6	4	1	1	
191	151.49	154.53	3.04	3.05	100	3.05	100	15	4	6	1	3	3	
191	154.53	157.58	3.05	3.05	100	3.05	100	15	4	6				
191	157.58	160.63	3.05	3.10	102	3.10	102	15	4	6				
191	160.63	163.68	3.05	2.94	96	2.94	96	15	4	6	4	1	1	1 slick contacts
191	163.68	166.73	3.05	3.05	100	3.00	98	15	4	5	7	1	2	minor gouge on contacts
191	166.73	169.77	3.04	2.63	87	2.01	66	12	4	5	17	1	1	minor gouge, broken sections, slick
191	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	4	2	2	
191	172.82	175.87	3.05	3.10	102	3.10	102	15	4	6	2	1	3	
191	175.87	178.92	3.05	3.00	98	3.00	98	15	4	6	3	1	2	minor gouge on fractures
191	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	4	3	3	
191	181.97	185.01	3.04	3.05	100	3.05	100	15	4	6	1	3	3	
191	185.01	188.06	3.05	3.05	100	3.05	100	15	5	6	2	2	4	
191	188.06	191.11	3.05	3.05	100	3.05	100	15	5	6	2	3	3	
191	191.11	194.16	3.05	2.93	96	2.93	96	15	5	6	1	1	4	calcite fracture
191	194.16	197.20	3.04	3.15	104	3.15	104	15	5	6	3	1	3	
191	197.20	200.25	3.05	2.96	97	2.96	97	15	4	6	6	1	1	1 slick contact
191	200.25	203.30	3.05	3.10	102	3.08	101	14	4	6	9	1	2	minor gouge on fractures
191	203.30	206.35	3.05	3.02	99	2.45	80	7	4	6	60	1	1	sheared zones, H=1,2
191	206.35	209.40	3.05	3.09	101	2.96	97	12	4	6	18	1	2	sheared zones, H=1,2
191	209.40	212.45	3.05	2.99	98	2.85	93	13	4	6	15	1	3	10 cm of H=0

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
191	212.45	215.49	3.04	3.15	104	3.05	100	15	5	6	7	1	1	1 small section of healed gouge
191	215.49	218.54	3.05	3.00	98	3.00	98	15	5	6				
191	218.54	221.59	3.05	3.05	100	3.05	100	15	5	6				
191	221.59	224.64	3.05	2.74	90	2.52	83	13	4	5	12	1	1	1 22 cm of H=0, clay washed, poor recovery
191	224.64	227.69	3.05	3.05	100	3.05	100	15	5	6	1	1	4	
191	227.69	230.73	3.04	3.08	101	3.08	101	15	5	6	2	3	3	
191	230.73	233.78	3.05	3.01	99	3.01	99	15	5	6				
191	233.78	236.83	3.05	3.05	100	1.65	54	3	4	5	100	1	1	1 40% of H=0, W=1; 45 to c.a.
191	236.83	239.88	3.05	3.05	100	2.25	74	15	4	5	40	1	1	1 20% of H=0, W=2; 45 to c.a.
191	239.88	242.93	3.05	3.05	100	2.88	94	13	4	5	12	1	1	1 gouge filled fractures
191	242.93	245.97	3.04	3.04	100	2.93	96	14	4	5	8	1	1	
191	245.97	249.02	3.05	3.05	100	2.74	90	12	4	5	15	1	1	1 30 cm of H=1, W=3
191	249.02	252.07	3.05	3.05	100	3.05	100	15	4	6	4	3	3	
191	252.07	255.12	3.05	3.12	102	3.12	102	15	4	6	2	3	3	
191	255.12	258.17	3.05	2.87	94	2.87	94	15	5	6	4	3	3	3 30 cm of healed breccia, H=3
191	258.17	261.21	3.04	3.12	103	3.12	103	15	4	6	6	3	3	3 40 cm of H=1, W=3
191	261.21	264.26	3.05	2.96	97	2.96	97	14	5	6	11	1	1	1 weak slicks at 35 to c.a.
191	264.26	267.31	3.05	3.05	100	3.05	100	15	5	6	4	1	1	
191	267.31	270.36	3.05	3.05	100	3.04	100	15	5	6	5	1	1	
191	270.36	273.41	3.05	3.05	100	3.00	98	15	5	6	4	1	1	
191	273.41	276.45	3.04	3.04	100	3.04	100	15	5	6	2	3	3	
191	276.45	279.50	3.05	3.12	102	3.12	102	15	5	6	5	3	3	
191	279.50	282.55	3.05	3.05	100	3.05	100	15	5	6	2	1	3	
191	282.55	285.60	3.05	2.95	97	2.95	97	15	5	6				
191	285.60	288.65	3.05	3.15	103	3.15	103	15	5	6	2	3	3	3 rake at 45 to c.a.
191	288.65	291.69	3.04	3.15	104	3.15	104	15	5	6	2	3	3	3 rake at 45 to c.a.
191	291.69	294.74	3.05	3.05	100	3.05	100	15	5	6	2	3	3	
191	294.74	297.79	3.05	3.10	102	3.10	102	15	5	6	4	1	2	
191	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6				
191	300.84	303.89	3.05	3.05	100	3.05	100	14	4	6	6	1	1	1 302.2-307.6 m - partly healed breccia
191	303.89	306.93	3.04	3.05	100	3.00	99	13	4	6	11	1	1	2 partly healed breccia
191	306.93	309.98	3.05	3.05	100	3.05	100	15	5	6	2	1	1	2 306.93-307.6 m - H=2,1; part healed brxx
191	309.98	313.03	3.05	2.93	96	2.93	96	15	5	6	5	1	1	1 carbonate veining
191	313.03	316.08	3.05	3.05	100	3.05	100	15	3	6	4	1	1	2 minor gouge on fractures; chert

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
191	316.08	319.13	3.05	3.00	98	3.00	98	15	5	6	4	1	2 volcanic sediments	
191	319.13	322.17	3.04	3.14	103	3.14	103	15	5	6	6	1	2 30 cm of H=2	
191	322.17	325.22	3.05	3.05	100	3.05	100	15	5	6	4	1	1 weak slicks	
191	325.22	328.27	3.05	3.05	100	2.85	93	14	5	6	8	1	1 30 to c.a.; very slick	
191	328.27	331.32	3.05	2.93	96	2.69	88	13	4	5	12	1	1 weak slicks	
191	331.32	334.37	3.05	3.05	100	3.05	100	15	5	6	4	3	3 minor gouge on fractures	
191	334.37	337.41	3.04	2.84	93	2.84	93	15	5	6	2	3	3 minor gouge on fractures	
191	337.41	340.46	3.05	2.98	98	2.44	80	13	5	6	14	1	1 339.6- 340.5 m - H=2, W=3; fault zone	
191	340.46	343.51	3.05	3.00	98	3.00	98	15	5	6	5	3	4	
191	343.51	346.56	3.05	2.90	95	2.90	95	15	4	6	4	3	3	
191	346.56	349.61	3.05	3.10	102	3.10	102	15	5	6	5	3	3	
192	24.38	26.52	2.14	1.37	64	1.25	58	14	3	5	3	1	3 gouge on fractures	
192	26.52	29.57	3.05	2.96	97	2.81	92	15	3	6	4	2	3	
192	29.57	32.61	3.04	3.01	99	2.75	90	15	3	6	3	1	3	
192	32.61	35.66	3.05	3.10	102	3.02	99	15	3	6	2	1	3	
192	35.66	38.71	3.05	2.95	97	2.95	97	15	3	6	1	1	3	
192	38.71	41.76	3.05	3.09	101	3.19	105	15	3	6	2	1	3	
192	41.76	44.81	3.05	3.11	102	2.90	95	15	3	6	4	2	3 gouge on fractures	
192	44.81	47.85	3.04	3.01	99	3.01	99	15	3	6	2	1	3	
192	47.85	50.90	3.05	3.05	100	3.05	100	15	3	6	3	1	3 gouge on fractures	
192	50.90	53.95	3.05	2.87	94	2.87	94	15	3	6	2	1	3	
192	53.95	57.00	3.05	3.09	101	2.23	73	15	3	6	6	1	3 gouge on fractures	
192	57.00	60.05	3.05	3.14	103	3.06	100	15	3	6	3	1	3	
192	60.05	63.09	3.04	3.04	100	3.04	100	15	3	6	2	1	3	
192	63.09	66.14	3.05	2.90	95	2.90	95	15	3	6	1	1	3	
192	66.14	69.19	3.05	2.84	93	2.69	88	15	5	6	4	1	3 gouge on fractures	
192	69.19	72.24	3.05	3.00	98	3.00	98	15	5	6	2	1	2	
192	72.24	75.29	3.05	3.02	99	2.89	95	15	6	6	3	1	2	
192	75.29	78.33	3.04	3.12	103	2.67	88	15	5	6	5	1	3 gypsum on fractures	
192	78.33	81.38	3.05	2.57	84	2.02	66	13	4	6	10	2	3 80.05 to 80.80 m - 100% gouge	
192	81.38	84.43	3.05	3.02	99	3.02	99	14	4	6	7	1	3	
192	84.43	87.47	3.04	2.91	96	2.69	88	14	4	6	5	1	3	
192	87.47	90.53	3.06	3.10	101	3.10	101	15	3	6	2	2	3	
192	90.53	93.57	3.04	3.00	99	3.00	99	15	3	6	3	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
192	93.57	96.62	3.05	2.98	98	2.98	98	15	3	6	2	1	3	
192	96.62	99.67	3.05	3.09	101	3.09	101	15	3	6	1	1	3	
192	99.67	102.72	3.05	3.12	102	3.01	99	15	3	6	3	1	3	gouge on fractures
192	102.72	105.77	3.05	3.13	103	3.13	103	15	3	6	2	1	3	
192	105.77	108.81	3.04	3.06	101	3.06	101	15	4	6	2	1	3	
192	108.81	111.86	3.05	3.09	101	3.09	101	15	4	6	1	1	3	
192	111.86	114.91	3.05	3.10	102	2.68	88	15	4	6	5	1	3	112.43 m - 4 cm gouge on fract 45 to c.a.
192	114.91	117.96	3.05	3.04	100	3.04	100	15	4	6	1	1	2	
192	117.96	121.01	3.05	3.04	100	3.04	100	15	3	6	2	1	3	
192	121.01	124.05	3.04	3.14	103	3.01	99	15	3	6	3	1	3	
192	124.05	127.10	3.05	2.81	92	2.59	85	14	3	6	7	1	3	
192	127.10	130.15	3.05	3.00	98	2.87	94	15	3	6	3	1	3	
192	130.15	133.20	3.05	3.10	102	3.10	102	15	3	6	2	1	3	
192	133.20	136.25	3.05	3.01	99	3.01	99	15	3	6				
192	136.25	139.29	3.04	3.08	101	3.08	101	15	4	6	2	1	2	
192	139.29	142.34	3.05	2.97	97	2.97	97	15	3	6	3	1	3	
192	142.34	145.39	3.05	2.99	98	2.67	88	14	3	6	5	1	3	
192	145.39	148.44	3.05	3.08	101	3.08	101	15	3	6	1	1	2	
192	148.44	151.49	3.05	3.07	101	3.07	101	15	4	6	3	1	2	
192	151.49	153.31	1.82	1.71	94	1.71	94	14	3	6	3	1	3	gouge on fractures
192	153.31	157.58	4.27	3.01	70	2.91	68	15	3	6	4	1	3	154.72 to 156.34 m - shear zone
192	157.58	160.63	3.05	2.97	97	2.61	86	15	3	6	3	1	3	
192	160.63	163.68	3.05	3.13	103	3.13	103	15	3	6	1	1	3	
192	163.68	166.73	3.05	2.97	97	2.40	79	14	3	6	7	1	3	gouge on fractures
192	166.73	169.77	3.04	2.89	95	2.71	89	14	3	6	5	1	3	10 cm gouge at 167.73 m
192	169.77	172.82	3.05	3.00	98	2.36	77	14	3	6	5	1	3	
192	172.82	175.87	3.05	3.05	100	2.50	82	14	3	6	7	1	3	gouge on fractures
192	175.87	178.92	3.05	2.76	90	2.25	74	14	4	6	9	1	2	5% broken rock with gouge
192	178.92	181.97	3.05	3.00	98	2.87	94	14	4	6	5	1	2	4 cm of gouge at 180.51 m
192	181.97	185.01	3.04	3.14	103	3.14	103	15	4	6	3	1	2	
192	185.01	188.06	3.05	2.79	91	2.79	91	15	4	6	2	1	2	
192	188.06	191.11	3.05	2.90	95	2.19	72	13	3	6	12	2	3	10% broken core with gouge
192	191.11	194.16	3.05	2.99	98	2.99	98	15	4	6	2	1	2	
192	194.16	197.21	3.05	3.18	104	3.04	100	15	3	6	3	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
192	197.21	200.25	3.04	2.64	87	2.09	69	10	3	6	20	2	3	10-15% broken core with gouge
192	200.25	203.30	3.05	2.42	79	2.07	68	10	3	6	20	1	3	200.4 m - 25 cm broken core with gouge
192	203.30	206.35	3.05	2.96	97	2.57	84	14	4	6	6	2	2	
192	206.35	209.40	3.05	3.14	103	3.14	103	15	4	6	2	1	2	
192	209.40	212.45	3.05	3.01	99	3.01	99	15	4	6	3	1	2	
192	212.45	215.49	3.04	2.61	86	2.43	80	13	4	6	10	2	2	
192	215.49	218.54	3.05	3.13	103	2.87	94	14	4	6	12	1	2	5% broken core
192	218.54	221.59	3.05	3.10	102	2.63	86	13	3	6	15	2	3	15% broken core with gouge
192	221.59	224.64	3.05	2.91	95	2.23	73	13	4	6	13	1	3	
192	224.64	227.69	3.05	2.73	90	2.51	82	14	4	6	7	1	2	
192	227.69	230.73	3.04	3.07	101	3.00	99	15	4	6	4	1	2	
192	230.73	233.78	3.05	2.84	93	2.31	76	12	3	6	17	5	3	15-20% broken core with gouge
192	233.78	236.83	3.05	3.14	103	2.74	90	14	4	6	6	2	2	
192	236.83	239.88	3.05	2.99	98	2.51	82	13	4	6	10	1	2	
192	239.88	242.93	3.05	3.08	101	2.82	92	13	3	6	12	1	3	20% shear zone; gouge on fractures
192	242.93	245.97	3.04	3.00	99	3.00	99	15	3	6	3	1	3	shear zone; gouge on fractures
192	245.97	249.02	3.05	3.14	103	3.14	103	15	3	6	2	1	3	gouge on fractures
192	249.02	252.07	3.05	3.00	98	2.91	95	14	3	6	5	1	3	gouge on fractures
192	252.07	255.12	3.05	2.85	93	2.76	90	15	5	6	2	1	2	
192	255.12	258.17	3.05	3.02	99	2.13	70	13	5	6	15	1	2	15% broken core with minor gouge
192	258.17	261.21	3.04	2.90	95	2.62	86	14	5	6	5	1	2	
192	261.21	264.26	3.05	3.10	102	2.72	89	14	5	6	7	1	2	
192	264.26	267.31	3.05	2.89	95	2.65	87	14	4	6	5	1	2	
192	267.31	269.75	2.44	2.79	114	2.67	109	13	4	6	10	1	3	25 cm of broken at beginning of interval
192	269.75	272.80	3.05	2.93	96	2.78	91	15	4	6	4	1	3	
192	272.80	276.15	3.35	2.73	81	1.72	51	12	4	6	15	1	3	5-10 % broken core
192	276.15	278.59	2.44	2.27	93	1.91	78	14	4	6	4	1	3	
192	278.59	281.64	3.05	3.33	109	3.19	105	15	4	6	3	1	2	
192	281.64	282.55	0.91	0.91	100	0.91	100	15	4	6				
192	282.55	285.60	3.05	3.05	100	2.39	78	14	4	6	7	2	2	
192	285.60	288.65	3.05	2.93	96	2.61	86	15	3	6	3	1	3	gouge on fractures
192	288.65	291.69	3.04	2.96	97	2.72	89	15	4	6	2	1	2	
192	291.69	294.74	3.05	2.96	97	2.96	97	15	4	6	1	2	3	
192	294.74	297.79	3.05	3.10	102	3.02	99	15	3	6	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
192	297.79	300.84	3.05	2.87	94	1.95	64	13	4	6	11	2	3	298.31 - 298.70 fault gouge
192	300.84	303.89	3.05	2.98	98	2.72	89	15	4	6	3	2	2	
192	303.89	306.93	3.04	2.93	96	2.80	92	15	5	6	3	1	2	
192	306.93	309.98	3.05	3.05	100	2.62	86	15	5	6	5	1	2	gouge on fractures
192	309.98	313.03	3.05	2.98	98	2.60	85	14	5	6	7	2	2	
192	313.03	316.08	3.05	3.09	101	2.93	96	15	5	6	3	1	2	
192	316.08	319.13	3.05	3.11	102	3.02	99	15	5	6	1	1	1	polished surface, small slicks 35 to c.a.
192	319.13	322.17	3.04	3.14	103	2.99	98	15	5	6	2	1	2	
192	322.17	325.22	3.05	3.04	100	3.04	100	15	5	6	1	1	2	
192	325.22	328.27	3.05	3.05	100	3.05	100	15	5	6	2	1	2	
192	328.27	331.32	3.05	3.05	100	3.05	100	15	5	6				
192	331.32	334.37	3.05	2.92	96	2.44	80	14	5	6	7	1	2	
192	334.37	337.41	3.04	3.11	102	3.11	102	15	5	6	3	1	2	dyke (H=5) ends at 336.70 m
192	337.41	340.46	3.05	2.96	97	2.58	85	14	2	6	5	5	3	95% fault gouge H=2, 25-30 to c.a.
192	340.46	343.51	3.05	3.12	102	3.03	99	15	3	6	3	1	3	
192	343.51	346.56	3.05	2.91	95	2.42	79	15	5	6	4	1	3	
192	346.56	349.61	3.05	2.89	95	2.50	82	13	3	6	13	1	3	96cm H=2 (gouge material)
192	349.61	352.65	3.04	2.68	88	1.77	58	10	3	6	20	5	3	25% broken core with gouge
192	352.65	355.40	2.75	2.75	100	2.70	98	14	3	6	5	2	3	
192	355.40	358.75	3.35	3.03	90	3.03	90	15	3	6	3	1	3	gouge on fractures
192	358.75	361.49	2.74	2.89	105	2.89	105	15	3	6	4	1	3	gouge on fractures
193	9.14	11.28	2.14	0.95	44	0.43	20	6	3	4	25	1	3	first 25 cm stained on joints
193	11.28	12.80	1.52	0.45	30	0.00	0	6	3	4	25	5	3	broken core with gouge
193	12.80	14.33	1.53	1.01	66	0.14	9	6	3	5	25	2	3	broken core with gouge
193	14.33	17.37	3.04	2.32	76	0.51	17	6	3	6	25	5	3	broken core with gouge
193	17.37	20.42	3.05	2.44	80	0.79	26	6	3	6	25	5	3	broken core with gouge
193	20.42	23.47	3.05	0.61	20	0.00	0	6	3	6	25	5	3	broken core with gouge
193	23.47	26.52	3.05	2.39	78	0.82	27	6	3	6	25	5	3	broken core with gouge
193	26.52	29.57	3.05	2.41	79	0.85	28	6	3	6	25	1	3	broken core with gouge, 14 cm H=2
193	29.57	32.61	3.04	2.65	87	1.41	46	6	3	6	25	5	3	broken core with gouge
193	32.61	35.66	3.05	0.79	26	0.58	19	5	3	6	25	5	3	broken core with gouge, 17 cm H=2
193	35.66	38.71	3.05	0.81	27	0.49	16	5	3	6	25	5	3	broken core with gouge, 11 cm H=2
193	38.71	41.76	3.05	1.47	48	0.83	27	6	3	6	25	5	3	broken core with gouge, 3 cm H=2
193	41.76	44.81	3.05	2.49	82	0.67	22	5	3	6	25	1	3	broken core with gouge, 18 cm H=2

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
193	44.81	47.85	3.04	2.75	90	1.98	65	12	5	6	15	1	2 dyke	
193	47.85	50.90	3.05	2.51	82	0.93	30	10	5	6	19	1	3 dyke ends at 48.60 m	
193	50.90	53.95	3.05	2.06	68	0.53	17	10	4	6	25	1	3	
193	53.95	57.00	3.05	0.92	30	0.74	24	6	4	6	25	5	3 31cm H=2, broken core	
193	57.00	60.15	3.15	1.97	63	0.51	16	8	3	6	25	5	3 broken core with gouge, 18 cm H=2	
193	60.15	63.09	2.94	1.18	40	0.31	11	6	3	6	25	5	3 broken core with gouge, 55 cm H=2	
193	63.09	73.15	10.06	0.00	0	0.00	0						No core recovered	
193	73.15	75.29	2.14	0.97	45	0.86	40	13	4	6	5	1	3	
193	75.29	78.33	3.04	2.89	95	2.64	87	15	3	6	2	1	3	
193	78.33	81.38	3.05	3.05	100	2.79	91	15	3	6	5	1	3 gouge on fractures	
193	81.38	84.43	3.05	2.95	97	2.74	90	15	3	6	4	1	3	
193	84.43	87.48	3.05	3.05	100	2.81	92	15	3	6	6	2	3 40 cm H=2	
193	87.48	90.53	3.05	2.95	97	2.69	88	15	3	6	3	1	3	
193	90.53	93.57	3.04	3.11	102	2.41	79	14	3	6	10	1	3 last .5m broken core	
193	93.57	96.62	3.05	2.94	96	1.83	60	10	4	6	25	5	3 60% broken core	
193	96.62	99.67	3.05	3.11	102	3.01	99	15	4	6	3	1	2 dyke	
193	99.67	102.72	3.05	3.05	100	2.19	72	13	4	6	12	2	3 dyke	
193	102.72	105.77	3.05	3.05	100	2.76	90	15	4	6	5	1	2 dyke	
193	105.77	108.81	3.04	3.04	100	2.81	92	14	4	6	6	1	3 dyke, minor gouge on fravtures	
193	108.81	111.86	3.05	2.89	95	2.65	87	15	4	6	4	1	2 dyke	
193	111.86	114.91	3.05	3.05	100	2.79	91	15	4	6	5	1	3 29 cm gouge (H=2) at 40 to c.a.	
193	114.91	117.96	3.05	3.00	98	2.87	94	15	4	6	3	1	2	
193	117.96	121.01	3.05	2.99	98	2.99	98	15	3	6	1	1	2	
193	121.01	124.05	3.04	2.97	98	2.97	98	15	3	6	3	1	3	
193	124.05	127.10	3.05	3.05	100	2.68	88	15	3	6	4	2	3 gouge on fractures	
193	127.10	130.15	3.05	2.88	94	2.49	82	14	3	6	5	1	3 8 cm H=2	
193	130.15	133.20	3.05	3.08	101	2.72	89	15	4	6	3	1	2	
193	133.20	136.25	3.05	3.05	100	2.51	82	13	3	6	12	1	3 10% broken core	
193	136.25	139.29	3.04	3.00	99	2.72	89	14	3	6	7	2	3 27 cm H=2	
193	139.29	142.34	3.05	3.12	102	2.71	89	14	3	6	9	1	3 13 cm H=2 (broken core)	
193	142.34	145.39	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
193	145.39	148.44	3.05	3.09	101	3.01	99	15	3	6	3	1	3	
193	148.44	151.49	3.05	3.04	100	3.04	100	15	3	6	1	1	3 3cm H=2	
193	151.49	154.53	3.04	3.07	101	2.61	86	14	3	6	7	1	3 35 cm H=2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
193	154.53	157.58	3.05	2.48	81	2.31	76	14	3	6	5	1	3	3 cm gouge
193	157.58	160.63	3.05	3.05	100	2.92	96	14	4	6	2	1	3	shear at 45 to c.a.
193	160.63	163.68	3.05	2.88	94	2.88	94	14	4	6	1	1	2	
193	163.68	166.73	3.05	3.00	98	2.79	91	15	4	6	5	1	2	gypsum on fractures
193	166.73	169.77	3.04	3.08	101	3.00	99	15	4	6	3	1	3	gypsum on fractures
193	169.77	172.82	3.05	3.05	100	2.91	95	15	3	6	3	1	3	
193	172.82	175.87	3.05	3.11	102	3.11	102	15	4	6	2	1	2	
193	175.87	178.92	3.05	3.09	101	3.09	101	15	4	6	1	1	2	
193	178.92	181.97	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
193	181.97	185.01	3.04	3.02	99	3.02	99	15	4	6	3	1	2	
193	185.01	188.06	3.05	3.05	100	3.05	100	15	4	6	2	1	2	gypsum on fractures
193	188.06	191.11	3.05	2.85	93	2.69	88	15	5	6	4	1	2	gypsum on fractures
193	191.11	194.16	3.05	3.07	101	2.91	95	15	4	6	5	1	2	gypsum on fractures
193	194.16	197.21	3.05	3.07	101	3.00	98	15	4	6	4	1	2	gypsum on fractures
193	197.21	200.25	3.04	3.08	101	2.86	94	14	4	6	6	2	3	gypsum on fractures
193	200.25	203.30	3.05	3.08	101	3.01	99	15	4	6	2	1	3	gypsum on fractures
193	203.30	206.35	3.05	3.05	100	2.79	91	14	4	6	8	1	3	gypsum on fractures 5 cm H=2
193	206.35	209.40	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gouge on fractures
193	209.40	212.14	2.74	2.37	86	1.92	70	12	3	6	15	2	3	10% broken core with gouge
193	212.14	215.19	3.05	2.93	96	2.54	83	12	3	6	17	5	3	5-10% broken core, 21 cm H=2
193	215.19	218.54	3.35	3.35	100	2.62	78	11	4	6	20	5	3	29 cm H=2, 5-10% broken core
193	218.54	221.59	3.05	2.99	98	2.92	96	15	4	6	3	1	3	5 cm H=2
193	221.59	224.64	3.05	3.08	101	3.08	101	15	4	6	3	1	3	
193	224.64	227.69	3.05	2.98	98	2.98	98	15	4	6	4	2	3	
193	227.69	230.73	3.04	3.09	102	3.09	102	15	4	6	1	1	3	
193	230.73	233.78	3.05	3.07	101	2.68	88	15	4	6	4	1	3	
193	233.78	236.83	3.05	3.00	98	3.00	98	15	4	6	2	1	2	
193	236.83	239.88	3.05	3.04	100	3.04	100	15	4	6	1	1	3	
193	239.88	242.93	3.05	2.94	96	2.88	94	15	4	6	1	1	3	gouge on fractures
193	242.93	245.97	3.04	3.05	100	3.05	100	15	4	6	1	1	2	
193	245.97	249.02	3.05	2.96	97	2.94	96	15	4	6	2	1	1	2 cm gouge slicks, 22 cm gouge/broken rx
193	249.02	252.09	3.07	3.05	99	2.83	92	14	4	6	7	1	1	22 cm gouge & broken rock
193	252.09	255.12	3.03	2.92	96	2.92	96	14	4	6	7	1	2	minor gouge on fractures
193	255.12	258.17	3.05	3.04	100	3.04	100	15	5	6	2	3	3	50 cm near vertical shear, well mineralized

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
193	258.17	261.21	3.04	2.99	98	2.99	98	15	4	6	3	3	4	
193	261.21	264.26	3.05	2.97	97	2.83	93	15	4	6	5	1		1 clay filled fractures
193	264.26	267.31	3.05	2.98	98	2.87	94	15	5	6	5	1		1 clay filled fractures
193	267.31	270.36	3.05	2.67	88	1.33	44	10	5	6	24	1		2 1.34 m rubble & redrilled core
193	270.36	273.41	3.05	3.05	100	3.05	100	15	5	6	3	3		3
193	273.41	276.45	3.04	3.04	100	3.04	100	15	4	6	5	3		2
193	276.45	279.50	3.05	3.00	98	3.00	98	15	5	6	9	1		2 trace healed clay
193	279.50	282.55	3.05	3.00	98	3.00	98	15	5	6	2	1		2
193	282.55	285.60	3.05	2.72	89	1.40	46	5	4	6	70	1		1 50% rubble and gouge fault
193	285.60	288.65	3.04	2.71	89	2.46	81	13	4	6	12	1		1 very slick 5-10 to c.a. zone
193	288.65	291.69	3.05	2.80	92	2.41	79	13	4	6	17	1		1 blocky sections
193	291.69	294.74	3.05	2.90	95	2.62	86	13	4	6	13	1		2
193	294.74	297.79	3.05	3.11	102	3.01	99	14	4	6	7	1		3 gouge on fractures
193	297.79	300.84	3.05	3.00	98	2.67	88	14	4	6	10	2		3 gouge on fractures
193	300.84	303.28	2.44	2.15	88	1.94	80	12	4	6	12	2		3 5% broken core with gouge
193	303.28	305.71	2.43	2.32	95	2.01	83	14	4	6	7	1		3
193	305.71	307.85	2.14	2.09	98	2.09	98	15	4	6	2	1		3 3 cm H=2
193	307.85	309.98	2.13	2.19	103	2.19	103	15	4	6	4	1		3
193	309.98	313.03	3.05	3.05	100	2.83	93	14	4	6	7	1		3 gouge on fractures
193	313.03	316.08	3.05	2.97	97	2.13	70	13	4	6	12	1		3
193	316.08	317.60	1.52	1.57	103	1.39	91	14	4	6	5	1		3 13 cm H=2
194	6.75	8.23	1.48	1.39	94	1.25	84	14	4	5	8	1		3 limonite staining
194	8.23	11.28	3.05	2.65	87	2.36	77	13	4	5	14	1		3 limonite staining
194	11.28	14.33	3.05	2.80	92	2.50	82	12	4	5	15	1		1 limonite staining, 20 cm of fault
194	14.33	17.37	3.04	2.83	93	2.61	86	14	4	5	9	1		3 limonite staining
194	17.37	20.42	3.05	2.76	90	2.51	82	10	3	5	27	1		3 limonite staining, 25 cm of fault
194	20.42	23.47	3.05	2.94	96	2.83	93	14	4	6	9	1		1 slick contact, 10 to c.a.
194	23.47	26.52	3.05	2.92	96	2.92	96	15	4	6	4	1		1 very weak slick, 45 to c.a.
194	26.52	29.57	3.05	2.75	90	2.60	85	14	3	5	6	1		2 slightly weathered
194	29.57	32.61	3.04	2.90	95	2.38	78	12	2	5	15	1		1 partly healed fault
194	32.61	35.66	3.05	2.96	97	2.96	97	15	5	6	3	1		3 gouge, slightly weathered joints
194	35.66	38.71	3.05	2.85	93	2.85	93	15	5	6	4	1		2 gouge, slightly weathered joints
194	38.71	41.76	3.05	2.84	93	2.48	81	13	3	5	10	1		2 gouge, slightly weathered joints
194	41.76	44.81	3.05	3.05	100	3.00	98	14	4	5	8	1		2 gouge, slightly weathered joints

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
194	44.81	47.85	3.04	2.85	94	2.54	84	14	4	5	9	1	1 gouge, slightly weathered joints
194	47.85	50.90	3.05	2.64	87	2.54	83	14	4	5	10	1	2 gouge, slightly weathered joints
194	50.90	51.82	0.92	0.73	79	0.61	66	11	4	5	6	1	2 blocky, more gouge
194	51.82	53.95	2.13	2.10	99	1.99	93	14	4	5	7	1	2 blocky, more gouge
194	53.95	57.00	3.05	3.05	100	2.51	82	11	1	2	19	1	1 fault zone, some clay
194	57.00	60.05	3.05	2.96	97	2.72	89	15	4	5	6	1	2 20 cm of H=0
194	60.05	63.09	3.04	3.05	100	2.85	94	10	1	2	25	1	2 fault zone
194	63.09	66.14	3.05	2.98	98	2.44	80	14	3	5	10	1	2
194	66.14	69.19	3.05	2.95	97	2.95	97	14	4	6	7	1	1 gouge filled fractures, 3cm H=2
194	69.19	72.24	3.05	2.92	96	2.85	93	14	4	6	7	1	2
194	72.24	75.29	3.05	2.91	95	2.10	69	10	4	6	30	1	2 50 % H=2
194	75.29	78.33	3.04	3.05	100	2.56	84	10	3	6	26	1	1 slick joints
194	78.33	81.38	3.05	2.78	91	2.47	81	14	3	6	10	1	2 broken material present
194	81.38	84.43	3.05	2.84	93	2.66	87	14	4	6	9	1	3
194	84.43	87.48	3.05	3.15	103	2.78	91	13	3	6	13	1	2
194	87.48	90.53	3.05	3.02	99	2.99	98	15	4	6	3	1	1 gouge on banded fractures, 3 cm
194	90.53	93.57	3.04	2.96	97	2.96	97	15	4	6	2	3	3
194	93.57	96.62	3.05	3.05	100	3.05	100	14	3	5	6	3	3 fractures slightly weathered
194	96.62	99.67	3.05	3.04	100	2.34	77	15	3	5	30	3	3 30% H=1, shear zone
194	99.67	102.11	2.44	2.61	107	2.24	92	13	3	5	13	1	2 small sections of clay & gouge
194	102.11	105.77	3.66	2.97	81	2.60	71	13	4	5	14	1	1 weak slicks and minor gouge
194	105.77	108.81	3.04	2.77	91	2.62	86	14	4	6	10	1	1 15 cm H=1, gouge
194	108.81	111.86	3.05	2.85	93	2.71	89	14	4	6	7	1	1 weak slicks, minor gouge
194	111.86	114.91	3.05	3.10	102	2.97	97	13	4	6	12	1	1 13 cm H=2,1
194	114.91	117.96	3.05	2.77	91	2.71	89	14	4	6	10	1	1 weak slicks
194	117.96	121.01	3.05	2.63	86	2.23	73	9	3	5	40	1	1 40 cm H=0
194	121.01	124.05	3.04	2.78	91	1.12	37	12	3	5	17	1	1 1.63 m H=2,1
194	124.05	127.10	3.05	2.50	82	2.50	82	14	3	5	7	1	2 healed section 20 cm long, H=2
194	127.10	130.15	3.05	2.80	92	2.80	92	15	4	6	4	1	3
194	130.15	133.20	3.05	2.73	90	2.73	90	15	3	6	4	3	3
194	133.20	136.24	3.04	2.96	97	2.69	88	14	3	5	8	1	2
194	136.24	139.29	3.05	3.29	108	3.03	99	15	3	5	5	3	2 27 cm H=2,1
194	139.29	142.34	3.05	2.90	95	2.38	78	15	4	6	40	1	1 48 cm of H=2, weak slicks
194	142.34	145.39	3.05	3.01	99	3.01	99	15	4	6	4	1	2 minor gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
194	145.39	148.44	3.05	3.05	100	3.05	100	15	4	6	4	1	3	
194	148.44	151.49	3.05	2.97	97	2.71	89	14	4	6	6	1	1	
194	151.49	154.53	3.04	3.05	100	2.73	90	13	3	6	12	3	3	
194	154.53	157.58	3.05	3.05	100	3.05	100	15	3	6	5	3	3	
194	157.58	160.63	3.05	2.60	85	1.08	35	7	2	4	50	3	3	3 152 cm partially healed fault, H=2
194	160.63	163.68	3.05	2.97	97	2.97	97	15	3	5	5	1	1	1 25 cm gouge, H=2
194	163.68	166.73	3.05	3.15	103	1.98	65	11	3	5	20	1	1	1 50% partially healed fault, H=1
194	166.73	169.77	3.04	3.05	100	3.05	100	15	4	6	1	1	2	
194	169.77	172.82	3.05	3.00	98	3.00	98	15	4	6	5	1	1	1 partially healed fault, small sections
194	172.82	175.87	3.05	3.00	98	2.00	66	9	3	5	50	1	1	1 15 to c.a. fault gouge, 1m H=1,0
194	175.87	178.92	3.05	3.00	98	3.00	98	14	3	5	8	1	2	
194	178.92	181.97	3.05	3.05	100	3.05	100	14	3	5	6	1	2	
194	181.97	185.01	3.04	3.23	106	3.23	106	15	4	6	2	1	2	
194	185.01	188.06	3.05	2.92	96	2.72	89	15	4	6	10	1	1	1 20 cm clay, H=0
194	188.06	191.11	3.05	3.13	103	2.95	97	15	4	6	4	1	1	1 weak slicks with minor gouge
194	191.11	194.16	3.05	3.05	100	2.82	92	15	4	6	20	2	1	1 22 cm H=0, fault zone
194	194.16	197.21	3.05	3.05	100	3.05	100	15	5	6	1	1	3	
194	197.21	200.25	3.04	3.00	99	3.00	99	15	5	6	2	3	3	
194	200.25	203.30	3.05	2.81	92	2.81	92	15	5	6	3	3	3	
194	203.30	206.35	3.05	3.15	103	3.15	103	15	5	6	2	3	3	3 mineralized zone, 20 cm H=2
194	206.35	209.40	3.05	3.15	103	3.15	103	15	5	6	2	1	4	
194	209.40	212.45	3.05	3.02	99	3.02	99	15	5	6	2	1	1	1 weak slicks, no gouge
194	212.45	215.49	3.04	3.12	103	3.02	99	15	5	6	2	1	1	1 10 cm gouge, weak slicks
194	215.49	218.54	3.05	2.88	94	2.88	94	15	5	6	2	1	1	1 slick contacts on dyke, 30 to c.a.
194	218.54	221.59	3.05	3.14	103	2.99	98	15	5	6	5	1	2	
194	221.59	224.64	3.05	2.96	97	2.90	95	15	5	6	2	1	2	
194	224.64	227.69	3.05	2.99	98	2.76	90	15	5	6	3	1	1	3 minor gouge on fractures
194	227.69	230.73	3.04	3.04	100	3.04	100	15	5	6	1	1	2	
194	230.73	233.78	3.05	3.25	107	2.91	95	14	5	6	10	1	1	2 5% broken core
194	233.78	236.83	3.05	3.09	101	3.02	99	15	5	6	5	1	1	2 pyrite on fractures
194	236.83	239.88	3.05	3.05	100	3.05	100	15	5	6	2	1	2	
194	239.88	242.93	3.05	2.92	96	2.92	96	15	5	6	1	1	2	
194	242.93	245.97	3.04	3.04	100	2.93	96	15	5	6	3	1	1	3 gouge on fractures
194	245.97	249.02	3.05	2.93	96	2.93	96	15	5	6	1	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
194	249.02	252.07	3.05	3.07	101	3.01	99	15	5	6	2	1	2	
194	252.07	255.12	3.05	3.01	99	3.01	99	15	5	6	3	1	2	pyrite on fractures
194	255.12	258.17	3.05	2.84	93	2.84	93	15	5	6	2	1	2	
194	258.17	261.21	3.04	3.28	108	3.28	108	15	5	6				
194	261.21	264.26	3.05	2.91	95	2.91	95	15	5	6	1	1	2	
194	264.26	267.31	3.05	2.93	96	2.93	96	15	5	6	2	2	2	
194	267.31	270.36	3.05	3.17	104	3.09	101	15	5	6	3	1	3	gouge on fractures
194	270.36	273.41	3.05	3.03	99	2.81	92	15	5	6	5	1	3	
194	273.41	276.45	3.04	3.14	103	3.14	103	15	5	6	1	1	2	
194	276.45	279.50	3.05	2.98	98	2.98	98	15	5	6	2	1	2	
194	279.50	282.55	3.05	3.23	106	2.76	90	15	5	6	15	1	2	5% broken core with cpy & py on frags
194	282.55	285.60	3.05	3.11	102	1.20	39	10	5	6	25	1	2	50% broken core with cpy & py on frags
194	285.60	288.65	3.05	3.14	103	2.37	78	13	5	6	15	1	2	10% broken core with cpy & py on frags
194	288.65	291.69	3.04	3.00	99	3.00	99	15	3	6	5	4	2	Different person teching starting here
194	291.69	294.74	3.05	2.90	95	2.63	86	14	3	6	7	3	2	py & cpy on fractures
194	294.74	297.79	3.05	3.45	113	2.98	98	14	3	6	10	4	2	
194	297.79	300.84	3.05	3.02	99	2.57	84	14	3	6	7	2	2	
194	300.84	303.89	3.05	2.87	94	2.41	79	13	3	6	10	1	1	gypsum on fracture
194	303.89	306.93	3.04	3.32	109	3.25	107	15	3	6	5	1	1	gouge slip plane
194	306.93	309.98	3.05	3.15	103	3.13	103	15	3	6	4	1	2	gypsum on fractures
194	309.98	313.03	3.05	2.81	92	2.67	88	14	3	6	5	1	2	gypsum on fractures
194	313.03	316.08	3.05	2.90	95	2.87	94	15	3	6	4	1	1	gypsum on fractures
194	316.08	319.13	3.05	3.52	115	3.06	100	15	3	6	7	4	1	
194	319.13	322.17	3.04	3.05	100	3.05	100	15	3	6	4	3	3	
194	322.17	325.22	3.05	3.09	101	3.03	99	15	3	6	5	3	1	gouge slip plane
194	325.22	328.27	3.05	3.10	102	2.81	92	12	1	3	20	1	1	gouge, slip plane, gouge & stressed rx
194	328.27	331.32	3.05	2.97	97	2.91	95	14	1	4	10	2	1	gouge, slip plane, gouge & stressed rx
194	331.32	334.37	3.05	3.05	100	2.98	98	13	3	4	12	2	1	
194	334.37	337.41	3.04	2.92	96	2.92	96	14	3	5	6	2	1	gypsum on fractures
194	337.41	340.46	3.05	3.18	104	3.18	104	15	3	6	2	3	2	gypsum on fractures
194	340.46	343.51	3.05	3.04	100	3.04	100	15	3	6	3	3	2	gypsum on fractures
194	343.51	346.56	3.05	3.09	101	3.05	100	15	3	6	4	1	1	graphite-gypsum slip fracture
194	346.56	349.61	3.05	3.05	100	3.05	100	15	3	6	3	1	2	graphite slip fracture
194	349.61	352.65	3.04	3.10	102	2.74	90	14	3	6	10	4	2	reduced bottom 40 cm gypsum on fract

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
194	352.65	355.70	3.05	2.02	66	0.98	32	9	3	6	25	1	2	reduced, lost core
194	355.70	358.75	3.05	2.98	98	2.98	98	15	3	6	3	3	2	gypsum on fracture, dyke contact
194	358.75	361.80	3.05	3.15	103	2.98	98	14	3	4	8	3	1	fault plane, gouge
194	361.80	364.85	3.05	3.03	99	2.66	87	14	3	5	8	3	2	fault, slip plane
194	364.85	367.89	3.04	3.10	102	3.10	102	15	3	6	5	1	1	gypsum on fracture
194	367.89	370.94	3.05	2.95	97	2.01	66	10	3	5	20	3	2	broken rock
194	370.94	373.99	3.05	3.06	100	3.06	100	15	3	6	2	4	1	gypsum on fracture
194	373.99	377.04	3.05	2.88	94	2.88	94	15	3	6	3	4	1	
194	377.04	380.09	3.05	3.10	102	3.10	102	15	3	6	2	1	4	
194	380.09	383.13	3.04	3.06	101	3.06	101	15	3	6	3	1	3	
194	383.13	385.88	2.75	3.10	113	3.10	113	15	3	6	2	4	2	
194	385.88	389.23	3.35	3.30	99	3.30	99	15	3	6	3	4	2	
194	389.23	391.97	2.74	2.67	97	2.67	97	15	3	6	2	3	2	
195	30.48	32.61	2.13	1.27	60	1.27	60	14	3	6	4	1	3	
195	32.61	35.66	3.05	2.95	97	2.95	97	15	3	6	3	1	3	20 cm of H=2
195	35.66	38.71	3.05	2.99	98	2.64	87	14	3	6	7	1	3	
195	38.71	41.76	3.05	3.05	100	2.91	95	15	3	6	4	1	3	
195	41.76	44.81	3.05	3.02	99	3.02	99	15	3	6	2	1	3	
195	44.81	47.85	3.04	3.05	100	3.05	100	15	4	6	2	1	3	
195	47.85	50.90	3.05	3.05	100	2.86	94	15	4	6	3	1	3	gouge on fractures
195	50.90	53.95	3.05	3.05	100	2.94	96	15	4	6	4	2	3	gouge on fractures
195	53.95	57.00	3.05	2.97	97	2.97	97	15	4	6	3	1	3	
195	57.00	60.05	3.05	3.14	103	2.74	90	14	4	6	10	1	3	10% broken core
195	60.05	63.09	3.04	2.98	98	2.98	98	15	4	6	2	2	3	
195	63.09	66.14	3.05	2.99	98	2.99	98	15	4	6	3	1	3	
195	66.14	69.19	3.05	3.10	102	2.87	94	13	4	6	12	1	3	35 cm of H=2, 5% broken core
195	69.19	72.24	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
195	72.24	75.29	3.05	3.05	100	3.05	100	15	4	6	2	1	3	minor gouge on fractures
195	75.29	78.33	3.04	3.02	99	3.02	99	15	4	6	1	1	3	
195	78.33	81.38	3.05	2.99	98	2.90	95	15	4	6	2	1	3	
195	81.38	84.43	3.05	3.00	98	3.00	98	15	4	6	4	1	3	
195	84.43	87.48	3.05	3.10	102	3.02	99	15	4	6	2	1	3	
195	87.48	90.53	3.05	2.89	95	2.89	95	15	4	6	2	1	3	gypsum on fractures
195	90.53	93.57	3.04	3.05	100	3.05	100	15	4	6	1	1	3	gypsum on fractures

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
195	93.57	96.62	3.05	3.05	100	3.05	100	15	4	6				
195	96.62	99.67	3.05	2.91	95	2.91	95	15	4	6	2	1		3 gypsum on fractures
195	99.67	102.72	3.05	3.00	98	3.00	98	15	4	6	4	1		3 gypsum on fractures
195	102.72	105.77	3.05	2.99	98	2.99	98	15	4	6	2	1		3 gypsum on fractures
195	105.77	108.81	3.04	3.10	102	3.10	102	15	4	6	3	1		3 gypsum on fractures
195	108.81	111.86	3.05	3.07	101	2.93	96	15	4	6	4	1		3 dyke at 110.65-111.91 m
195	111.86	114.91	3.05	3.01	99	2.76	90	14	4	6	9	1		3
195	114.91	117.96	3.05	3.05	100	3.05	100	15	4	6	3	1		3 gouge on fractures
195	117.96	121.00	3.04	2.99	98	2.99	98	15	4	6	2	1		3 gypsum on fractures
195	121.00	124.05	3.05	3.00	98	3.00	98	15	3	6	4	1		3
195	124.05	127.10	3.05	3.03	99	3.03	99	15	3	6	1	1		2
195	127.10	130.15	3.05	3.11	102	3.11	102	15	4	6	1	1		2
195	130.15	133.20	3.05	2.97	97	2.97	97	15	4	6	2	1		3 gypsum on fractures
195	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6	2	1		2 gypsum on fractures
195	136.25	139.29	3.04	3.04	100	2.95	97	15	4	6	3	1		3 gypsum on fractures
195	139.29	142.34	3.05	3.04	100	3.04	100	15	4	6	3	1		2 gypsum on fractures
195	142.34	145.39	3.05	2.99	98	2.99	98	15	4	6	2	1		3 gypsum on fractures
195	145.39	148.44	3.05	3.05	100	2.78	91	15	4	6	3	1		3 gypsum on fractures
195	148.44	151.49	3.05	3.05	100	3.00	98	15	4	6	1	1		3 gypsum on fractures
195	151.49	154.53	3.04	2.97	98	2.97	98	15	4	6	2	1		2 gypsum on fractures
195	154.53	157.58	3.05	3.08	101	2.59	85	15	4	6	5	1		2 gypsum on fractures
195	157.58	160.63	3.05	3.06	100	3.00	98	15	4	6	2	1		2 gypsum on fractures
195	160.63	163.68	3.05	3.05	100	3.05	100	15	4	6	3	1		3 gypsum on fractures
195	163.68	166.73	3.05	3.05	100	3.05	100	15	4	6	3	1		3 gypsum on fractures
195	166.73	169.77	3.04	2.85	94	2.85	94	15	4	6	2	1		3 gypsum on fractures
195	169.77	172.82	3.05	3.07	101	3.07	101	15	4	6	1	1		3 gypsum on fractures
195	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6	2	1		2 gypsum on fractures
195	175.87	178.92	3.05	3.00	98	3.00	98	15	4	6	3	1		2 gypsum on fractures
195	178.92	181.97	3.05	3.07	101	3.07	101	15	4	6	1	1		2 gypsum on fractures
195	181.97	185.01	3.04	2.95	97	2.95	97	15	4	6	1	1		2 gypsum on fractures
195	185.01	188.06	3.05	3.00	98	3.00	98	15	4	6				
195	188.06	191.11	3.05	3.00	98	3.00	98	15	4	6	2	1		2 gypsum on fractures
195	191.11	194.16	3.05	3.07	101	2.96	97	15	4	6	3	1		2 gypsum on fractures
195	194.16	197.21	3.05	2.99	98	2.64	87	15	4	6	4	1		2 gy on fractures,dyke at 195.77-196.63 m

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
195	197.21	200.25	3.04	3.00	99	3.00	99	15	4	6	2	1	2	gypsum on fractures
195	200.25	202.69	2.44	2.42	99	2.21	91	15	4	6	3	1	2	gypsum on fractures
195	202.69	205.74	3.05	3.03	99	3.03	99	15	4	6	1	1	2	gypsum on fractures
195	205.74	208.79	3.05	3.14	103	3.14	103	15	4	6	3	1	2	gypsum on fractures
195	208.79	211.84	3.05	3.03	99	2.87	94	15	4	6	4	1	2	gypsum on fractures
195	211.84	213.66	1.82	1.95	107	1.95	107	15	4	6	1	1	2	gypsum on fractures
195	213.66	215.49	1.83	1.79	98	1.79	98	15	4	6	2	1	2	gypsum on fractures
195	215.49	218.54	3.05	3.03	99	3.03	99	15	4	6	3	1	2	gypsum on fractures
195	218.54	221.59	3.05	3.05	100	2.94	96	15	4	6	2	1	2	gypsum on fractures
195	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum on fractures
195	224.64	227.69	3.05	3.09	101	3.00	98	15	4	6	3	1	2	gypsum on fractures
195	227.69	230.73	3.04	3.08	101	3.08	101	15	4	6	2	1	2	gypsum on fractures
195	230.73	233.78	3.05	3.00	98	3.00	98	15	4	6	1	1	2	gypsum on fractures
195	233.78	236.83	3.05	2.98	98	2.98	98	15	4	6	2	1	2	gypsum on fractures
195	236.83	239.88	3.05	3.07	101	3.02	99	15	4	6	2	1	2	gypsum on fractures
195	239.88	242.93	3.05	2.92	96	2.92	96	15	4	6	1	1	2	gypsum on fractures
195	242.93	245.97	3.04	3.08	101	2.98	98	15	4	6	3	1	2	gypsum on fractures
195	245.97	249.02	3.05	3.05	100	3.05	100	15	4	6	2	1	2	gy on fractures, minor gouge fractures
195	249.02	252.07	3.05	3.04	100	3.04	100	15	4	6	3	1	2	gypsum on fractures
195	252.07	255.12	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum on fractures
195	255.12	258.17	3.05	3.03	99	2.91	95	15	4	6	4	1	3	gouge on fractures
195	258.17	261.21	3.04	3.09	102	3.09	102	15	4	6	1	1	2	gypsum on fractures
195	261.21	264.26	3.05	3.10	102	2.89	95	15	4	6	5	1	3	gouge on fractures
195	264.26	267.31	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum on fractures
195	267.31	270.36	3.05	2.98	98	2.78	91	15	4	6	5	1	2	gypsum on fractures
195	270.36	273.41	3.05	3.15	103	2.95	97	15	4	6	4	1	2	gypsum on fractures
195	273.41	276.45	3.04	3.04	100	2.91	96	14	5	6	6	1	3	273.12-276.35 m - dyke
195	276.45	279.50	3.05	2.95	97	2.14	70	14	3	6	8	1	3	shear zone
195	279.50	282.55	3.05	2.96	97	2.96	97	15	3	6	3	2	3	
195	282.55	285.59	3.04	2.88	95	2.71	89	15	3	6	4	1	3	284.93-286.78 m dyke, rest sheared
195	285.59	288.65	3.06	2.90	95	1.87	61	13	3	6	10	1	3	286.78-288.65 m weakly sheared
195	288.65	291.69	3.04	3.10	102	2.94	97	15	3	6	4	1	3	gouge on fractures
195	291.69	294.74	3.05	2.93	96	1.76	58	13	3	6	12	1	3	5-10% broken core with gouge
195	294.74	297.79	3.05	2.96	97	2.69	88	14	3	6	7	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
195	297.79	300.84	3.05	3.05	100	3.00	98	15	3	6	3	1	3	
195	300.84	303.89	3.05	3.05	100	3.05	100	15	3	6	4	1	3	
195	303.89	306.93	3.04	2.90	95	2.90	95	15	3	6	2	1	3	
195	306.93	309.98	3.05	3.05	100	2.92	96	15	3	6	3	1	3	gouge on fractures
195	309.98	313.03	3.05	3.03	99	3.03	99	15	4	6	2	1	3	
195	313.03	316.08	3.05	3.04	100	3.04	100	15	3	6	4	1	3	
195	316.08	319.13	3.05	3.02	99	3.02	99	15	3	6	2	1	3	
195	319.13	322.17	3.04	3.06	101	3.06	101	15	3	6	1	1	3	
195	322.17	325.22	3.05	3.11	102	3.02	99	15	3	6	2	1	3	
195	325.22	328.27	3.05	3.00	98	3.00	98	15	3	6	5	1	3	
195	328.27	331.32	3.05	2.86	94	2.73	90	14	4	6	6	2	3	
195	331.32	334.37	3.05	2.94	96	2.01	66	10	4	6	20	5	3	10-15% broken core with gouge
195	334.37	337.41	3.04	2.99	98	2.99	98	15	4	6	3	1	2	334.97-335.94 m dyke
195	337.41	340.46	3.05	2.95	97	2.95	97	15	4	6	2	1	3	
195	340.46	343.51	3.05	3.05	100	3.00	98	15	4	6	2	1	3	
195	343.51	346.56	3.05	3.12	102	3.02	99	15	4	6	3	1	3	gypsum fractures
195	346.56	349.61	3.05	2.96	97	2.44	80	13	4	6	12	2	3	gypsum fractures
195	349.61	352.65	3.04	2.94	97	2.94	97	14	3	6	5	1	3	40% shear zone
195	352.65	355.70	3.05	2.56	84	1.09	36	10	3	6	25	5	3	60% broken rock with gouge
195	355.70	358.75	3.05	3.06	100	1.67	55	10	3	6	25	5	3	50% broken rock with gouge
195	358.75	361.80	3.05	2.76	90	2.76	90	15	4	6	2	1	2	
195	361.80	365.50	3.70	3.85	104	2.13	58	13	4	6	15	1	2	
196	6.10	8.23	2.13	1.32	62	0.00	0	7	0	2	50	3	2	broken rock, gouge
196	8.23	11.28	3.05	2.67	88	0.46	15	7	0	2	50	3	2	broken rock and gouge zones
196	11.28	14.33	3.05	2.95	97	1.82	60	10	3	3	25	3	3	broken rock, minor slip planes
196	14.33	17.37	3.04	3.08	101	2.52	83	13	0	4	12	1	2	broken rock, gouge, slip planes
196	17.37	20.42	3.05	3.05	100	2.76	90	14	3	5	7	3	2	fault gouge
196	20.42	23.47	3.05	3.15	103	2.23	73	13	0	4	12	3	2	healed gouge, gouge, stressed rock
196	23.47	25.91	2.44	2.39	98	1.78	73	13	0	4	11	3	2	gouge and healed gouge
196	25.91	26.52	0.61	0.50	82	0.50	82	15	3	6	1	3	3	
196	26.52	29.57	3.05	3.02	99	2.76	90	14	3	5	8	3	3	healed gouge and stressed rock
196	29.57	32.61	3.04	3.10	102	2.73	90	13	3	5	14	3	2	minor gouge and stressed rock
196	32.61	35.66	3.05	2.94	96	2.37	78	11	0	4	20	3	2	minor gouge and stressed rock
196	35.66	38.71	3.05	3.05	100	2.31	76	13	3	6	12	3	1	minor gouge and broken rock

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
196	38.71	41.76	3.05	3.08	101	2.44	80	14	3	6	8	3	2	
196	41.76	44.81	3.05	3.05	100	2.87	94	14	3	6	6	1	1	1 minor slip planes
196	44.81	47.86	3.05	2.90	95	2.68	88	15	3	6	5	2	1	1 very minor slip plane
196	47.86	50.90	3.04	3.22	106	3.18	105	13	0	4	11	1	2	2 gouge, slip planes
196	50.90	53.95	3.05	3.17	104	2.67	88	15	3	6	5	3	1	
196	53.95	57.00	3.05	2.89	95	2.70	89	14	3	6	7	3	2	2 minor gouge 6 cm
196	57.00	60.05	3.05	3.25	107	3.19	105	15	3	6	3	3	2	
196	60.05	63.09	3.04	3.07	101	3.07	101	15	3	6	3	3	2	2 minor slip plane
196	63.09	66.14	3.05	2.98	98	2.94	96	15	3	6	3	5	2	
196	66.14	69.19	3.05	3.03	99	2.91	95	15	3	6	5	1	1	1 minor gouge, slip planes
196	69.19	72.24	3.05	3.05	100	2.86	94	15	3	6	2	3	2	
196	72.24	75.29	3.05	3.03	99	3.03	99	15	3	6	4	4	2	
196	75.29	78.33	3.04	3.12	103	2.97	98	15	3	6	5	1	2	2 minor slip planes, stressed rock
196	78.33	81.38	3.05	3.04	100	3.04	100	15	3	6	3	1	2	2 minor slip planes
196	81.38	84.43	3.05	3.02	99	3.02	99	14	3	6	5	3	2	2 minor slip planes
196	84.43	87.48	3.05	3.07	101	3.07	101	15	3	6	3	3	3	
196	87.48	90.53	3.05	3.05	100	3.05	100	15	3	6	3	3	2	2 minor slip plane
196	90.53	93.57	3.04	3.10	102	2.98	98	14	3	5	6	3	3	3 stressed rock
196	93.57	96.62	3.05	3.05	100	2.78	91	14	2	5	10	3	2	2 stressed rock
196	96.62	99.67	3.05	2.88	94	2.45	80	11	1	4	20	3	3	3 gouge and stressed rock
196	99.67	102.72	3.05	2.93	96	2.93	96	14	3	5	6	3	2	2 minor slip planes
196	102.72	105.77	3.05	3.14	103	2.86	94	15	3	5	5	3	2	2 minor gouge
196	105.77	108.81	3.04	3.38	111	3.09	102	14	3	5	10	3	2	2 gouge and stressed rock
196	108.81	111.86	3.05	2.74	90	2.37	78	14	3	6	7	1	3	
196	111.86	114.91	3.05	3.22	106	3.22	106	15	3	6	5	1	2	2 missed block at 114.30 m
196	114.91	117.96	3.05	2.64	87	1.90	62	10	0	4	22	1	2	2 gouge and slip plane
196	117.96	121.01	3.05	3.18	104	3.06	100	14	3	6	6	3	3	
196	121.01	124.05	3.04	3.08	101	2.84	93	14	3	6	7	3	3	3 ground core
196	124.05	127.10	3.05	3.02	99	2.78	91	14	3	5	8	1	2	2 5 cm gouge, slip plane
196	127.10	130.15	3.05	3.25	107	3.13	103	14	3	6	9	1	2	2 gouge, slip planes, start of vol. seds
196	130.15	133.20	3.05	2.78	91	2.50	82	13	3	6	11	2	3	3 ground core
196	133.20	136.25	3.05	2.94	96	2.62	86	14	3	6	8	1	3	3 minor gouge planes
196	136.25	139.29	3.04	3.07	101	2.96	97	15	3	6	4	2	2	2 mud slip plane
196	139.29	142.34	3.05	3.15	103	3.00	98	14	3	6	7	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
196	142.34	145.39	3.05	2.94	96	2.80	92	14	0	5	10	3	1	mud slip plane, 25 cm healed gouge
196	145.39	148.44	3.05	3.09	101	2.92	96	14	3	6	8	2	2	
196	148.44	151.49	3.05	3.02	99	3.00	98	14	3	6	8	3	2	gouge, slip plane
196	151.49	154.53	3.04	3.01	99	2.75	90	14	1	5	7	3	1	gouge and fault zone healed
196	154.53	157.58	3.05	3.11	102	2.73	90	12	2	5	16	1	2	
196	157.58	160.63	3.05	3.30	108	2.70	89	13	1	4	14	3	1	gouge, slip planes & healed gouge
196	160.63	163.68	3.05	2.97	97	2.62	86	13	1	4	14	3	1	gouge, slip planes & healed gouge
196	163.68	166.73	3.05	3.00	98	1.87	61	10	3	5	25	1	2	broken rock
196	166.73	169.77	3.04	2.83	93	2.64	87	13	3	5	12	3	1	gouge, slip planes
196	169.77	172.82	3.05	2.97	97	2.90	95	14	2	4	7	2	2	gouge, slip planes
196	172.82	175.87	3.05	3.08	101	2.91	95	14	3	5	8	2	1	gouge, slip planes, stressed rock
196	175.87	178.92	3.05	2.90	95	2.66	87	12	1	5	11	1	1	stressed rock, slip planes, healed gouge
196	178.92	181.97	3.05	2.97	97	2.17	71	13	3	5	10	1	2	3cm gouge, healed gouge
196	181.97	185.01	3.04	2.96	97	2.16	71	10	3	5	25	3	2	broken rock, possibly mechanical
196	185.01	188.06	3.05	3.19	105	3.19	105	15	3	6	4	3	1	minor slip gouge planes
196	188.06	191.11	3.05	2.85	93	2.33	76	12	3	5	15	2	1	healed gouge, gouge
196	191.11	192.02	0.91	0.85	93	0.62	68	15	3	4	5	1	2	gouge, slip plane
196	192.02	194.16	2.14	2.20	103	1.74	81	12	3	5	16	2	2	gouge, slip planes, healed gouge
196	194.16	197.21	3.05	2.94	96	2.24	73	13	1	4	10	3	2	healed gouge, broken rock
196	197.21	200.25	3.04	2.52	83	1.75	58	10	0	4	25	1	1	gouge & healed gouge, broken rock
196	200.25	203.30	3.05	2.93	96	2.64	87	13	3	4	12	2	1	stressed rock, gouge zone 10 cm
196	203.30	206.35	3.05	3.22	106	3.05	100	12	1	5	11	2	1	gouge, slip planes
196	206.35	209.40	3.05	3.03	99	2.86	94	14	0	5	9	3	1	60 cm gouge
196	209.40	212.45	3.05	2.98	98	2.98	98	15	3	6	3	2	2	
196	212.45	215.49	3.04	3.07	101	3.07	101	15	3	6	3	1	2	slip plane
196	215.49	218.54	3.05	3.16	104	3.16	104	15	3	6	3	1	4	
196	218.54	221.59	3.05	3.10	102	3.10	102	15	3	6	5	3	2	gouge, slip planes
196	221.59	224.64	3.05	2.95	97	2.95	97	15	3	6	2	1	2	
196	224.64	227.69	3.05	3.07	101	3.07	101	15	3	6	2	1	3	
196	227.69	230.73	3.04	2.89	95	2.89	95	15	3	6	3	1	3	pyrite on fractures
196	230.73	233.78	3.05	3.15	103	3.15	103	15	3	6	3	3	3	
196	233.78	236.83	3.05	3.12	102	3.12	102	15	1	5	3	3	2	healed gouge, stressed rock
196	236.83	239.88	3.05	3.05	100	3.05	100	15	3	6	2	3	4	
196	239.88	242.93	3.05	3.00	98	3.00	98	15	3	6	2	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
196	242.93	245.97	3.04	3.05	100	3.05	100	15	3	6	2	1	1 gouge, slip plane	
196	245.97	248.72	2.75	2.78	101	2.75	100	15	3	6	3	1	1 gouge, slip plane	
196	248.72	252.07	3.35	3.44	103	3.36	100	14	3	6	7	3	1 gouge, slip plane, 3 mm gouge	
196	252.07	255.12	3.05	3.02	99	2.97	97	15	3	6	4	1	3 gouge, slip plane	
196	255.12	258.17	3.05	3.07	101	3.07	101	15	3	6	3	1	4	
196	258.17	261.21	3.04	2.65	87	1.73	57	12	3	5	17	2	2 healed gouge, broken rock 2 cm gouge	
196	261.21	264.26	3.05	3.15	103	3.10	102	14	3	6	8	5	4	
196	264.26	267.31	3.05	3.24	106	2.54	83	12	3	4	16	1	2 several gouge zones 1-2 cm wide	
196	267.31	270.36	3.05	3.03	99	3.03	99	14	3	6	7	3	2	
196	270.36	273.41	3.05	3.13	103	2.94	96	15	3	6	6	1	3	
196	273.41	276.45	3.04	3.01	99	3.01	99	15	3	6	3	3	2	
196	276.45	279.50	3.05	3.20	105	2.98	98	15	3	6	5	2	1 gouge, slip plane	
196	279.50	282.55	3.05	2.92	96	2.86	94	15	3	6	6	3	2	
196	282.55	285.60	3.05	3.30	108	3.30	108	15	3	6	6	4	2	
196	285.60	288.65	3.05	2.78	91	2.60	85	14	3	6	9	1	2 1 cm gouge, 5 cm broken core	
196	288.65	291.69	3.04	2.98	98	2.98	98	15	3	6	2	3	2 ground core very minor	
197	9.14	11.28	2.14	0.52	24	0.13	6	9	3	4	6	1	3 iron stained fractures, broken core	
197	11.28	12.80	1.52	1.26	83	0.27	18	7	3	4	17	2	3 iron stained fractures, broken core	
197	12.80	13.41	0.61	0.75	123	0.11	18	7	3	4	13	2	3 iron stained fractures, broken core	
197	13.41	14.33	0.92	0.68	74	0.55	60	6	3	4	7	1	3 iron stained fractures, broken core	
197	14.33	17.37	3.04	2.93	96	2.01	66	10	3	4	28	1	3 iron stained fractures, broken core	
197	17.37	20.42	3.05	2.75	90	2.13	70	10	3	4	24	1	3 iron stained fractures, broken core	
197	20.42	23.47	3.05	2.83	93	1.36	45	7	3	4	40	1	3 iron stained fractures, 30% broken core	
197	23.47	26.52	3.05	2.80	92	1.08	35	7	3	4	40	3	3 iron stained fractures, 50% broken core	
197	26.52	29.57	3.05	2.66	87	0.83	27	7	3	4	40	2	3 iron stained fractures, broken core	
197	29.57	32.61	3.04	3.30	109	1.53	50	10	4	4	25	1	3 iron stained fractures, broken core	
197	32.61	35.66	3.05	2.56	84	1.52	50	10	4	5	20	2	3 35 cm gouge H=2, 10 cm H=1, gouge fract	
197	35.66	38.71	3.05	3.05	100	2.43	80	12	4	5	16	2	3 5 cm gouge H=1, calcite on fractures	
197	38.71	41.76	3.05	2.93	96	1.00	33	9	5	5	30	1	3 calcite on fractures	
197	41.76	44.81	3.05	3.00	98	0.48	16	9	5	5	40	1	3 pyrite on fractures	
197	44.81	47.85	3.04	2.42	80	0.12	4	6	5	5	50	1	3 calcite on fractures	
197	47.85	50.90	3.05	3.00	98	0.46	15	9	5	5	40	1	2 calcite on fractures	
197	50.90	53.95	3.05	2.90	95	0.56	18	9	5	5	35	1	3 pyrite on fractures	
197	53.95	57.00	3.05	3.30	108	1.06	35	10	5	5	30	1	2 16 cm gouge, H=2, pyrite on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
197	57.00	60.05	3.05	2.16	71	0.55	18	7	5	5	40	1	2	40 cm gouge H=2, 40% broken rock
197	60.05	63.09	3.04	2.53	83	1.21	40	7	5	5	35	2	3	calcite on fractures
197	63.09	66.14	3.05	2.25	74	1.05	34	9	5	5	25	2	3	
197	66.14	69.19	3.05	2.93	96	1.87	61	9	5	5	30	1	3	10 cm healed gouge H=2/3, ca fractures
197	69.19	72.24	3.05	0.63	21	0.00	0	3	4	5	50	2	3	100% broken with gouge
197	72.24	75.29	3.05	1.18	39	0.47	15	6	5	5	40	1	3	pyrite on fractures
197	75.29	78.33	3.04	2.80	92	1.21	40	9	5	5	35	1	3	pyrite on fractures
197	78.33	80.16	1.83	1.83	100	1.63	89	14	5	5	6	1	3	calcite on fractures
197	80.16	82.60	2.44	1.95	80	1.37	56	9	5	5	24	2	3	gouge on fractures
197	82.60	83.52	0.92	0.85	92	0.10	11	6	4	5	30	2	3	gouge oin fractures, 100% broken
197	83.52	85.34	1.82	1.36	75	0.40	22	6	5	5	30	2	3	90% broken
197	85.34	86.56	1.22	0.82	67	0.10	8	6	5	5	30	2	3	100% broken
197	86.56	88.39	1.83	0.97	53	0.25	14	6	5	5	40	2	3	100% broken, minor gouge
197	88.39	89.61	1.22	0.86	70	0.00	0	7	5	5	15	2	3	pyrite on fractures
197	89.61	91.44	1.83	0.76	42	0.00	0	6	5	5	25	2	3	100% broken, minor gouge
197	91.44	92.96	1.52	0.94	62	0.00	0	6	5	5	30	1	3	pyrite on fractures, 100% broken
197	92.96	96.01	3.05	0.54	18	0.10	3	6	5	5	20	1	2	70% broken, minor gouge
197	96.01	96.62	0.61	0.42	69	0.10	16	6	4	5	10	2	3	7 cm mud seam, H=2, minor gouge
197	96.62	99.67	3.05	3.07	101	2.65	87	13	4	5	13	2	3	gouge on fractures
197	99.67	102.72	3.05	3.17	104	2.90	95	14	4	5	10	2	2	gypsum on fractures
197	102.72	105.77	3.05	2.93	96	2.93	96	15	4	5	2	1	2	gypsum on fractures
197	105.77	108.81	3.04	3.06	101	3.06	101	15	5	5	4	1	2	gypsum on fractures
197	108.81	111.86	3.05	2.93	96	2.80	92	14	6	5	7	2	3	gypsum on fractures
197	111.86	114.91	3.05	3.06	100	2.86	94	14	6	5	7	1	3	gypsum on fractures
197	114.91	117.96	3.05	2.79	91	2.53	83	14	4	5	8	2	3	gouge on fractures
197	117.96	121.01	3.05	2.97	97	2.83	93	14	5	5	7	2	3	
197	121.01	124.05	3.04	3.08	101	3.08	101	15	5	5	3	2	3	gypsum and gouge on fractures
197	124.05	127.10	3.05	2.86	94	2.86	94	15	5	5	2	2	3	
197	127.10	130.15	3.05	2.96	97	2.90	95	14	5	5	6	2	3	gypsum on fractures
197	130.15	132.59	2.44	1.95	80	1.55	64	13	5	5	9	1	3	gouge on fractures
197	132.59	133.81	1.22	1.22	100	1.22	100	14	6	5	4	1	2	gypsum on fractures
197	133.81	135.33	1.52	1.50	99	1.03	68	9	6	5	18	1	3	
197	135.33	138.38	3.05	3.01	99	3.01	99	15	5	5	5	2	3	gypsum on fractures
197	138.38	138.99	0.61	0.71	116	0.62	102	14	5	5	2	1	2	gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
197	138.99	142.03	3.04	3.08	101	3.01	99	15	5	5	4	2	3	
197	142.03	142.34	0.31	0.22	71	0.18	58	13	5	5	1	5	3	
197	142.34	145.39	3.05	3.10	102	3.10	102	15	4	5	2	2	3	minor gouge on fractures
197	145.39	148.44	3.05	3.03	99	3.03	99	15	4	5	4	1	3	gypsum on fractures
197	148.44	151.49	3.05	3.07	101	3.02	99	15	4	5	3	1	3	pyrite on fractures
197	151.49	154.53	3.04	3.04	100	3.04	100	15	5	5	3	2	2	gypsum on fractures
197	154.53	157.58	3.05	2.95	97	2.88	94	14	4	5	8	1	3	gypsum on fractures
197	157.58	160.63	3.05	2.92	96	2.92	96	15	5	5	1	2	2	gypsum on fractures
197	160.63	163.68	3.05	3.12	102	3.12	102	15	5	5	2	1	2	gypsum on fractures
197	163.68	166.73	3.05	3.07	101	3.07	101	15	5	5	4	2	3	minor gouge on fractures
197	166.73	169.77	3.04	3.04	100	2.97	98	14	5	5	6	2	3	pyrite on fractures, 15 cm H=3
197	169.77	172.82	3.05	3.03	99	3.03	99	15	5	5	3	2	3	gouge on fractures
197	172.82	175.87	3.05	3.08	101	3.08	101	15	5	5	1	1	3	gypsum on fractures
197	175.87	178.92	3.05	3.03	99	3.03	99	15	5	5	2	2	3	gypsum on fractures
197	178.92	181.97	3.05	3.14	103	3.14	103	15	5	5	1	2	3	gypsum on fractures
197	181.97	185.01	3.04	3.04	100	3.04	100	15	5	5	2	2	3	gypsum on fractures
197	185.01	188.06	3.05	2.43	80	2.20	72	13	4	5	10	1	3	gypsum on fractures, 10 cm H=3 gouge
197	188.06	191.11	3.05	3.02	99	3.02	99	15	4	5	3	2	3	gouge on fractures, 15 cm sectns gouge
197	191.11	194.16	3.05	3.00	98	3.00	98	15	5	5	3	2	3	gypsum on fractures
197	194.16	197.21	3.05	3.02	99	3.02	99	15	5	5	3	2	3	gypsum on fractures
197	197.21	200.25	3.04	3.04	100	3.04	100	15	5	5	2	2	3	mineralized fractures
197	200.25	200.56	0.31	0.40	129	0.36	116	14	5	5	1	1	2	gypsum on fractures
198	9.14	11.28	2.14	0.74	35	0.00	0	3	3	5	50	5	3	broken core, iron stained
198	11.28	14.33	3.05	2.29	75	0.41	13	4	3	5	50	5	3	broken core, iron stained
198	14.33	17.37	3.04	0.74	24	0.57	19	3	3	5	50	5	3	broken core, iron stained
198	17.37	20.42	3.05	2.43	80	0.15	5	6	3	5	50	5	3	broken core, iron stained
198	20.42	23.47	3.05	2.39	78	0.43	14	6	3	5	50	5	3	broken core, iron stained
198	23.47	26.52	3.05	1.84	60	0.22	7	4	3	5	50	1	3	broken core
198	26.52	29.57	3.05	0.95	31	0.00	0	4	3	5	50	5	3	broken core
198	29.57	32.61	3.04	1.47	48	0.00	0	6	3	6	50	1	3	broken core
198	32.61	35.36	2.75	1.56	57	0.00	0	4	3	6	50	1	3	broken core
198	35.36	38.71	3.35	2.94	88	0.41	12	7	3	6	50	1	3	broken core
198	38.71	41.45	2.74	2.91	106	0.39	14	7	3	6	50	1	3	broken core
198	41.45	44.81	3.36	2.95	88	0.31	9	7	3	6	50	1	3	broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
198	44.81	47.85	3.04	3.00	99	0.47	15	6	3	6	50	1	3 broken core	
198	47.85	50.90	3.05	1.43	47	0.35	11	6	3	6	50	5	3 broken core	
198	50.90	53.95	3.05	2.71	89	1.07	35	10	4	6	25	1	2 broken core	
198	53.95	57.00	3.05	2.95	97	1.92	63	10	4	6	20	1	2	
198	57.00	60.05	3.05	3.08	101	3.00	98	15	4	6	3	1	2	
198	60.05	63.09	3.04	3.04	100	2.94	97	15	4	6	4	1	3 minor gouge on fractures	
198	63.09	66.14	3.05	2.91	95	2.91	95	15	4	6	1	1	2	
198	66.14	69.19	3.05	3.22	106	3.11	102	15	4	6	2	1	2	
198	69.19	72.24	3.05	3.03	99	3.03	99	15	4	6	3	1	2	
198	72.24	75.29	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
198	75.29	78.33	3.04	3.08	101	3.08	101	15	4	6	1	1	2	
198	78.33	81.38	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
198	81.38	84.43	3.05	3.00	98	2.93	96	15	4	6	3	1	2	
198	84.43	87.48	3.05	3.09	101	3.09	101	15	4	6	2	1	2 gypsum on fractures	
198	87.48	90.53	3.05	2.97	97	2.81	92	15	4	6	3	1	2 gypsum on fractures	
198	90.53	93.00	2.47	3.11	126	3.11	126	15	4	6	1	1	2 gypsum on fractures	
198	93.57	96.62	3.05	3.27	107	3.27	107	15	4	6	2	1	2 gypsum on fractures	
198	96.62	99.67	3.05	3.12	102	3.12	102	15	4	6	2	1	2 gypsum on fractures	
198	99.67	102.72	3.05	2.83	93	2.40	79	14	4	6	7	1	2 gypsum on fractures	
198	102.72	105.77	3.05	3.11	102	3.11	102	15	4	6	2	1	2 gypsum on fractures	
198	105.77	108.81	3.04	3.01	99	3.01	99	15	4	6	1	1	2 gypsum on fractures	
198	108.81	111.86	3.05	3.06	100	3.06	100	15	4	6	3	1	2 dyke at 109.83-11.0 m	
198	111.86	114.91	3.05	3.04	100	2.91	95	15	4	6	3	1	2 gypsum on fractures	
198	114.91	117.96	3.05	3.00	98	2.69	88	15	4	6	4	1	3 60 cm H=3/2, gouge on fractures	
198	117.96	121.01	3.05	2.93	96	2.54	83	14	4	6	5	1	2	
198	121.01	124.05	3.04	3.04	100	3.04	100	15	5	6	2	1	2 dyke at 121.43-123.82 m	
198	124.05	127.10	3.05	3.05	100	2.87	94	15	4	6	2	1	2	
198	127.10	130.15	3.05	2.92	96	2.79	91	15	3	6	4	2	3 gouge on fractures	
198	130.15	133.20	3.05	3.05	100	2.91	95	15	4	6	2	1	2	
198	133.20	136.25	3.05	3.00	98	3.00	98	15	4	6	3	2	3	
198	136.25	139.29	3.04	3.09	102	3.00	99	15	4	6	2	1	3 gouge on fractures	
198	139.29	142.34	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
198	142.34	145.39	3.05	2.96	97	2.96	97	15	4	6	1	1	2	
198	145.39	148.44	3.05	3.08	101	3.08	101	15	4	6	2	1	2 gypsum on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
198	148.44	151.49	3.05	3.07	101	3.07	101	15	4	6	1	1	2	gypsum on fractures
198	151.49	154.53	3.04	3.04	100	3.04	100	15	4	6	2	1	2	gypsum on fractures
198	154.53	157.58	3.05	3.08	101	3.08	101	15	4	6	1	1	2	gypsum on fractures
198	157.58	160.63	3.05	2.86	94	2.86	94	15	4	6	2	1	2	gypsum on fractures
198	160.63	163.68	3.05	3.10	102	3.10	102	15	4	6	1	1	2	gypsum on fractures
198	163.68	166.73	3.05	3.13	103	3.13	103	15	4	6	2	1	3	gypsum on fractures
198	166.73	169.77	3.04	3.08	101	2.91	96	15	4	6	4	1	3	gypsum on fractures
198	169.77	172.82	3.05	3.06	100	3.06	100	15	4	6	3	1	2	gypsum on fractures
198	172.82	175.87	3.05	2.92	96	2.92	96	15	4	6	1	1	2	gypsum on fractures
198	175.87	178.92	3.05	3.10	102	3.10	102	15	4	6	4	1	2	gypsum on fractures
198	178.92	181.97	3.05	3.09	101	3.09	101	15	4	6	1	1	2	gypsum on fractures
198	181.97	185.01	3.04	2.94	97	2.94	97	15	4	6	1	1	2	gypsum on fractures
198	185.01	188.06	3.05	3.00	98	3.00	98	15	5	6	2	1	2	gypsum on fractures
198	188.06	191.11	3.05	3.07	101	3.07	101	15	5	6	2	1	2	gypsum on fractures
198	191.11	194.16	3.05	3.08	101	3.08	101	15	4	6	2	1	3	gouge and gypsum on fractures
198	194.16	197.21	3.05	3.08	101	2.98	98	15	4	6	4	1	2	
198	197.21	200.25	3.04	3.04	100	3.04	100	15	4	6	1	1	2	gypsum on fractures
198	200.25	203.30	3.05	2.99	98	2.99	98	15	5	6	2	1	2	gypsum on fractures
198	203.30	206.35	3.05	3.09	101	3.00	98	15	5	6	4	1	2	gypsum on fractures
198	206.35	209.40	3.05	3.08	101	3.08	101	15	4	6	2	1	2	gypsum on fractures
198	209.40	212.45	3.05	2.91	95	2.68	88	14	4	6	5	1	2	gypsum on fractures
198	212.45	215.49	3.04	2.99	98	2.99	98	15	4	6	1	1	2	
198	215.49	217.93	2.44	2.65	109	2.65	109	15	4	6	2	1	2	
198	217.93	221.59	3.66	3.34	91	3.11	85	15	4	6	2	1	3	25 cm H=2
198	221.59	224.64	3.05	3.08	101	3.00	98	15	3	6	3	1	3	gouge on fractures, fault
198	224.64	227.69	3.05	3.09	101	3.09	101	15	3	6	2	1	3	gouge on fractures, fault
198	227.69	230.73	3.04	3.04	100	2.94	97	15	3	6	4	1	3	fault
198	230.73	233.78	3.05	3.03	99	3.03	99	15	4	6	3	1	3	24 cm H=2, fault ends at 231.85 m
198	233.78	236.83	3.05	3.10	102	2.92	96	15	4	6	2	1	2	
198	236.83	239.88	3.05	3.11	102	3.11	102	15	4	6	2	1	3	gouge on fractures
198	239.88	242.93	3.05	3.05	100	2.89	95	15	4	6	5	1	3	gouge on fractures
198	242.93	245.97	3.04	3.08	101	2.97	98	15	4	6	3	1	3	
198	245.97	249.02	3.05	3.09	101	3.09	101	15	4	6	1	1	2	
198	249.02	252.07	3.05	3.05	100	3.05	100	15	4	6	2	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
198	252.07	255.12	3.05	3.09	101	3.09	101	15	4	6	1	1	2	
198	255.12	258.17	3.05	2.98	98	2.79	91	15	5	6	3	1	2	dyke at 256.14-259.17 m
198	258.17	261.21	3.04	3.11	102	2.82	93	14	4	6	6	1	3	gouge on fractures
198	261.21	264.26	3.05	3.25	107	2.49	82	12	3	6	20	5	3	5-10% broken core
198	264.26	267.31	3.05	2.78	91	1.95	64	14	4	6	8	1	3	gouge on fractures
198	267.31	270.36	3.05	3.02	99	2.73	90	15	4	6	5	1	3	14 cm H=2
198	270.36	273.41	3.05	3.09	101	3.09	101	15	4	6	2	1	2	
198	273.41	276.45	3.04	2.93	96	2.81	92	15	4	6	4	1	3	gouge on fractures
198	276.45	279.50	3.05	3.08	101	3.00	98	15	3	6	3	1	3	gouge and gypsum on fractures
198	279.50	282.55	3.05	2.99	98	2.78	91	15	3	6	2	1	3	gouge and gypsum on fractures
198	282.55	285.60	3.05	3.00	98	3.00	98	15	3	6	1	1	3	
198	285.60	288.65	3.05	2.96	97	2.19	72	12	5	6	15	1	2	dyke
198	288.65	291.69	3.04	3.04	100	2.87	94	14	5	6	10	1	2	dyke
198	291.69	294.74	3.05	2.87	94	2.87	94	15	5	6	4	1	2	
198	294.74	297.79	3.05	3.14	103	3.01	99	15	4	6	4	2	3	gypsum on fractures
198	297.79	300.84	3.05	2.84	93	2.64	87	14	4	6	9	2	3	
198	300.84	303.89	3.05	3.15	103	2.81	92	13	3	6	15	1	3	gouge on fractures
198	303.89	306.93	3.04	2.87	94	2.87	94	15	4	6	2	1	2	
198	306.93	309.98	3.05	3.12	102	3.06	100	15	4	6	2	1	2	
198	309.98	313.03	3.05	3.11	102	3.02	99	15	3	6	4	1	3	40% gypsum vein
198	313.03	316.08	3.05	3.05	100	3.05	100	15	3	6	2	1	3	30% gypsum
198	316.08	319.13	3.05	3.15	103	3.15	103	15	4	6	2	1	2	
198	319.13	322.17	3.04	3.17	104	3.17	104	15	4	6	3	1	3	
198	322.17	325.22	3.05	3.08	101	3.08	101	15	4	6	1	1	3	gypsum on fractures
198	325.22	328.27	3.05	3.11	102	2.99	98	15	4	6	4	1	3	gypsum on fractures
198	328.27	331.32	3.05	3.09	101	3.09	101	15	4	6	2	1	2	
198	331.32	334.37	3.05	3.04	100	3.04	100	15	4	6	2	1	2	
198	334.37	337.41	3.04	2.97	98	2.97	98	15	3	6	3	1	1	slip plane with gouge
198	337.41	340.46	3.05	2.89	95	2.89	95	15	3	6	2	1	2	slip plane with gouge
198	340.46	343.51	3.05	3.13	103	3.13	103	15	3	6	2	3	2	dry gypsum ? talc plane
198	343.51	346.56	3.05	3.08	101	3.08	101	15	3	6	3	1	3	
198	346.56	349.61	3.05	3.07	101	3.07	101	15	3	6	3	1	3	pyrite-gypsum surface
198	349.61	352.65	3.04	3.03	100	3.03	100	15	3	6	4	1	2	
198	352.65	355.70	3.05	3.03	99	3.03	99	15	3	6	2	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
198	355.70	358.75	3.05	3.09	101	3.09	101	15	3	6	1	3	2	
198	358.75	361.80	3.05	3.02	99	3.02	99	15	3	6	2	1	1	gouge, talc-gypsum surface
198	361.80	364.85	3.05	2.96	97	2.89	95	15	3	6	3	3	1	
199	21.33	25.30	3.97	1.40	35	0.34	9	10	3	5	25	5	3	50% broken core
199	25.30	27.43	2.13	0.00	0	0.00	0							
199	27.43	29.57	2.14	0.84	39	0.41	19	15	3	5	4	1	3	
199	29.57	32.61	3.04	2.92	96	2.24	74	14	3	5	7	1	3	
199	32.61	35.66	3.05	2.61	86	1.86	61	10	3	6	25	5	3	15% broken core with gouge
199	35.66	38.71	3.05	2.92	96	2.64	87	15	3	6	5	1	3	
199	38.71	41.76	3.05	3.09	101	2.49	82	15	3	6	3	1	3	
199	41.76	44.81	3.05	3.06	100	2.92	96	15	3	6	2	1	3	
199	44.81	47.85	3.04	3.14	103	3.00	99	15	3	6	4	1	3	
199	47.85	50.90	3.05	3.11	102	3.04	100	15	3	6	2	1	3	
199	50.90	53.95	3.05	3.07	101	2.98	98	15	3	6	4	1	3	
199	53.95	57.00	3.05	3.14	103	2.79	91	15	3	6	5	1	3	10 cm gouge at 50 to c.a.
199	57.00	60.05	3.05	3.04	100	3.04	100	15	3	6	2	1	3	
199	60.05	63.09	3.04	3.04	100	3.04	100	15	3	6	1	1	3	
199	63.09	66.14	3.05	3.05	100	3.05	100	15	3	6	1	1	3	
199	66.14	69.19	3.05	3.01	99	2.87	94	15	3	6	4	1	3	gouge on fractures
199	69.19	72.24	3.05	3.11	102	2.98	98	15	3	6	3	1	3	last 20 cm broken core with gouge
199	72.24	75.29	3.05	3.03	99	3.03	99	15	3	6	1	1	3	
199	75.29	78.33	3.04	3.02	99	3.02	99	15	3	6	1	1	3	41 cm H=2
199	78.33	81.38	3.05	3.11	102	2.84	93	15	3	6	6	1	3	gouge on fractures
199	81.38	84.43	3.05	3.05	100	2.61	86	14	3	6	7	1	3	gouge on fractures
199	84.43	87.49	3.06	3.01	98	2.92	95	15	3	6	3	1	3	
199	87.49	90.53	3.04	3.09	102	3.09	102	15	3	6	2	1	3	
199	90.53	93.57	3.04	3.12	103	3.02	99	15	3	6	5	1	3	65 cm H=2
199	93.57	96.62	3.05	3.00	98	3.00	98	15	4	6	2	1	2	
199	96.62	99.67	3.05	3.03	99	2.89	95	15	4	6	3	1	3	gouge on fractures
199	99.67	102.72	3.05	2.87	94	2.76	90	14	4	6	5	1	2	
199	102.74	105.77	3.03	2.96	98	2.65	87	14	4	6	6	1	2	
199	105.77	108.81	3.04	3.02	99	3.02	99	15	4	6	1	1	2	
199	108.81	111.86	3.05	2.86	94	2.61	86	14	4	6	8	1	2	5% broken rock
199	111.86	114.91	3.05	2.96	97	2.90	95	15	4	6	2	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
199	114.91	117.96	3.05	3.19	105	3.19	105	15	4	6	1	1	2	
199	117.96	121.01	3.05	3.12	102	3.04	100	15	4	6	2	1	2	
199	121.01	124.05	3.04	3.04	100	2.92	96	15	4	6	4	1	2	
199	124.05	127.10	3.05	2.94	96	2.94	96	15	4	6	3	1	2	
199	127.10	130.15	3.05	3.10	102	3.10	102	15	4	6	1	1	2	
199	130.15	133.20	3.05	3.03	99	3.03	99	15	4	6	1	1	2	
199	133.20	136.25	3.05	3.09	101	2.91	95	15	4	6	2	1	2	
199	136.25	139.29	3.04	3.00	99	3.00	99	15	4	6	1	1	2	
199	139.29	142.34	3.05	3.05	100	2.99	98	15	4	6	3	1	3	gouge on fractures
199	142.34	145.39	3.05	3.11	102	3.11	102	15	4	6	2	1	2	
199	145.39	148.44	3.05	3.03	99	3.03	99	15	4	6	1	1	2	
199	148.44	151.49	3.05	2.97	97	2.97	97	15	4	6				
199	151.49	154.53	3.04	3.04	100	3.04	100	15	4	6	1	1	2	
199	154.53	157.58	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
199	157.58	160.63	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
199	160.63	163.68	3.05	3.05	100	3.05	100	15	4	6				
199	163.68	166.73	3.05	3.05	100	3.00	98	15	4	6	4	1	3	7 cm H=2, gouge on fractures
199	166.73	169.77	3.04	3.04	100	3.04	100	15	4	6	3	1	2	
199	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gouge on fractures
199	172.82	175.87	3.05	3.00	98	2.74	90	15	3	4	3	1	3	gouge
199	175.87	178.92	3.05	2.97	97	2.90	95	15	3	6	3	1	3	20 cm gouge, H=2
199	178.92	181.97	3.05	3.13	103	3.04	100	15	3	6	2	1	3	5 cm gouge, H=2
199	181.97	185.01	3.04	3.05	100	3.05	100	15	3	6	1	1	3	gypsum on fractures
199	185.01	188.06	3.05	3.05	100	3.05	100	15	3	6	1	1	3	
199	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
199	191.11	194.16	3.05	3.03	99	3.03	99	15	4	6	2	1	2	
199	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
199	197.21	200.25	3.04	3.03	100	3.03	100	15	4	6	1	1	2	
199	200.25	203.30	3.05	3.04	100	3.04	100	15	4	6	3	1	2	
199	203.30	206.35	3.05	3.07	101	3.07	101	15	4	6				
199	206.35	209.40	3.05	3.08	101	3.08	101	15	4	6	2	1	2	
199	209.40	212.45	3.05	3.13	103	2.97	97	15	4	6	4	1	3	gouge on fractures
199	212.45	215.49	3.04	3.05	100	3.05	100	15	3	6	5	1	3	gouge on fractures
199	215.49	218.54	3.05	3.00	98	3.00	98	15	3	6	1	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
199	218.54	221.59	3.05	3.06	100	3.06	100	15	3	6	4	1	3	gouge on fractures
199	221.59	224.64	3.05	3.03	99	3.03	99	15	3	6	5	1	3	gouge on fractures, 10 cm H=2
199	224.64	227.69	3.05	3.07	101	2.90	95	14	3	6	6	1	3	
199	227.69	230.73	3.04	3.03	100	2.93	96	15	3	6	3	2	3	
199	230.73	233.78	3.05	3.10	102	2.74	90	15	3	6	4	1	3	gouge on fractures
199	233.78	236.83	3.05	3.13	103	2.23	73	14	3	6	7	1	3	12' cm H=2, gouge on fractures
199	236.83	239.88	3.05	3.00	98	2.90	95	15	4	6	1	1	2	
199	239.88	242.93	3.05	3.06	100	3.02	99	15	4	6	3	1	2	
199	242.93	245.97	3.04	3.17	104	2.92	96	15	4	6	2	1	2	
199	245.97	249.02	3.05	3.02	99	2.91	95	15	4	6	1	1	2	
199	249.02	252.07	3.05	3.05	100	3.01	99	15	4	6	2	1	2	
199	252.07	255.12	3.05	3.10	102	3.10	102	15	4	6	2	1	2	
199	255.12	258.17	3.05	3.02	99	3.02	99	15	4	6	1	1	2	
199	258.17	261.21	3.04	3.04	100	3.04	100	15	3	6	1	1	3	
199	261.21	264.26	3.05	3.10	102	3.10	102	15	3	6	2	1	2	
199	264.26	267.31	3.05	3.00	98	3.00	98	15	4	6				
199	267.31	270.36	3.05	3.13	103	3.13	103	15	4	6	1	1	2	
199	270.36	273.41	3.05	2.98	98	2.98	98	15	3	6	2	1	3	
199	273.41	276.45	3.04	3.08	101	3.05	100	15	4	6	2	1	2	dyke at 275.47-278.37 m
199	276.45	279.50	3.05	3.09	101	2.95	97	15	2	6	3	1	2	
199	279.50	282.55	3.05	3.07	101	3.07	101	15	3	6	3	1	2	slip plane
199	282.55	285.60	3.05	3.04	100	2.90	95	15	3	6	7	2	2	gypsum fracture
199	285.60	287.43	1.83	1.80	98	1.31	72	10	3	5	16	1	2	broken rock
199	287.43	288.04	0.61	0.63	103	0.10	16	5	3	5	14	1	2	broken rock
199	288.04	288.95	0.91	0.40	44	0.00	0	5	3	5	15	1	2	broken rock
199	288.95	291.69	2.74	3.01	110	2.48	91	2	0	1	14	1	2	sand section, 1 m fault
199	291.69	294.74	3.05	3.10	102	3.10	102	15	3	6	4	3	2	
199	294.74	297.79	3.05	3.10	102	3.10	102	15	3	6	3	3	4	
199	297.79	300.84	3.05	2.99	98	2.99	98	15	3	6	4	3	2	gypsum on fracture
199	300.84	303.89	3.05	3.08	101	3.04	100	14	0	3	7	3	2	healed gouge, stressed rock
199	303.89	306.93	3.04	2.99	98	2.99	98	15	3	6	3	1	1	gouge, slip surface
199	306.93	309.98	3.05	3.09	101	3.09	101	15	3	6	4	3	1	
199	309.98	313.03	3.05	3.09	101	3.09	101	15	3	5	5	3	1	
200	18.29	20.12	1.83	0.43	23	0.16	9	4	3	5	20	5	3	iron stained, broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
200	20.12	23.16	3.04	2.65	87	1.87	62	10	3	5	20	5	3	32 cm gouge, H=1/2, broken core
200	23.16	25.30	2.14	1.37	64	0.47	22	6	3	5	20	5	3	25 cm H=0/1 (mud)
200	25.30	26.52	1.22	1.13	93	0.68	56	6	4	6	20	5	3	broken core
200	26.52	27.43	0.91	0.87	96	0.52	57	7	4	6	15	1	3	broken core with gouge
200	27.43	29.57	2.14	2.19	102	1.87	87	10	4	6	15	1	3	broken core
200	29.57	32.61	3.04	2.89	95	2.89	95	15	3	6	2	1	3	40 cm gouge, H=1/2
200	32.61	35.66	3.05	2.96	97	2.06	68	10	3	6	20	5	3	10% broken core
200	35.66	38.71	3.05	3.11	102	2.21	72	14	3	6	10	1	3	45 cm H=2, gouge
200	38.71	41.76	3.05	2.96	97	2.30	75	12	3	6	17	1	3	20 cm H=1/2
200	41.76	44.81	3.05	2.99	98	2.14	70	12	3	6	15	1	3	16 cm H=1/2
200	44.81	47.85	3.04	2.75	90	2.51	83	14	3	6	8	1	3	gouge on fractures
200	47.85	50.90	3.05	2.95	97	2.76	90	14	3	6	5	1	3	gouge on fractures
200	50.90	53.95	3.05	3.17	104	2.89	95	14	3	6	7	1	3	gouge on fractures
200	53.95	57.00	3.05	2.96	97	2.78	91	15	4	6	4	1	2	dyke
200	57.00	60.05	3.05	3.05	100	3.05	100	15	3	6	3	1	3	gouge on fractures
200	60.05	63.09	3.04	2.94	97	2.94	97	15	4	6	2	1	2	gouge on fractures
200	63.09	66.14	3.05	3.05	100	2.69	88	14	3	6	7	1	3	
200	66.14	69.19	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
200	69.19	72.24	3.05	2.70	89	2.04	67	13	4	6	13	1	2	dyke
200	72.24	75.29	3.05	3.09	101	2.59	85	13	4	6	15	1	2	
200	75.29	78.33	3.04	2.83	93	1.13	37	10	3	6	20	2	3	20-30% broken core with gouge
200	78.33	81.38	3.05	2.91	95	2.25	74	14	3	6	7	1	3	7 cm gouge H=1/2
200	81.38	84.43	3.05	3.05	100	2.73	90	14	3	6	5	1	3	gouge on fractures
200	84.43	87.48	3.05	3.14	103	3.01	99	15	4	6	4	1	2	
200	87.48	90.53	3.05	2.87	94	2.68	88	15	4	6	3	1	2	15 cm H=1/2
200	90.53	93.57	3.04	3.08	101	3.08	101	15	4	6	3	1	3	gouge on fractures
200	93.57	96.62	3.05	2.95	97	2.81	92	13	4	6	11	1	3	35 cm H=1/2, gouge on fractures
200	96.62	99.67	3.05	3.07	101	3.07	101	15	4	6	1	1	2	
200	99.67	102.72	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gouge on fractures
200	102.72	105.77	3.05	2.57	84	1.52	50	10	4	6	25	5	3	20% broken core
200	105.77	106.98	1.21	1.23	102	0.69	57	6	4	6	20	1	2	
200	106.98	110.03	3.05	3.21	105	3.00	98	13	4	6	15	1	2	
200	110.03	111.86	1.83	1.90	104	1.25	68	13	4	6	7	2	2	
200	111.86	114.91	3.05	3.15	103	2.98	98	14	3	6	9	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
200	114.91	117.96	3.05	3.18	104	2.78	91	13	3	6	12	1	3	gouge on fractures
200	117.96	121.01	3.05	2.94	96	2.94	96	15	3	6	2	1	3	
200	121.01	124.05	3.04	3.09	102	2.96	97	15	3	6	5	1	3	
200	124.05	127.10	3.05	3.17	104	3.01	99	15	4	6	4	1	3	gouge on fractures
200	127.10	130.15	3.05	3.10	102	3.10	102	15	4	6	3	1	3	carbonate on fractures
200	130.15	133.20	3.05	3.01	99	1.37	45	13	4	6	15	2	3	hematite staining on fractures
200	133.20	135.94	2.74	2.68	98	2.68	98	15	4	6	3	1	2	
200	135.94	136.86	0.92	0.65	71	0.33	36	7	4	6	10	1	3	gouge on fractures
200	136.86	139.29	2.43	2.37	98	1.87	77	14	4	6	6	1	2	gouge on fractures
200	139.29	142.34	3.05	3.08	101	3.08	101	15	3	6	2	1	3	gouge on fractures
200	142.34	145.39	3.05	3.03	99	2.89	95	14	3	6	6	1	3	gypsum on fractures
200	145.39	148.44	3.05	2.98	98	2.98	98	15	3	6	3	1	3	gypsum on fractures
200	148.44	151.49	3.05	3.09	101	3.09	101	15	3	6	4	1	3	gypsum on fractures
200	151.49	154.53	3.04	2.95	97	2.90	95	15	3	6	4	1	3	22 cm H=1/2, gouge on fractures
200	154.53	157.58	3.05	3.06	100	3.03	99	15	3	6	2	1	3	12 cm H=1/2, gouge on fractures
200	157.58	160.63	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
200	160.63	163.68	3.05	3.07	101	3.07	101	15	4	6	2	1	2	
200	163.68	166.73	3.05	3.00	98	3.00	98	15	4	6	1	1	2	
200	166.73	169.77	3.04	3.07	101	3.07	101	15	4	6	2	1	2	gouge on fractures
200	169.77	172.82	3.05	3.09	101	3.09	101	15	3	6	3	1	3	gouge on fractures
200	172.82	175.87	3.05	3.07	101	3.07	101	15	3	6	3	1	3	
200	175.87	178.92	3.05	2.99	98	2.84	93	15	3	6	4	2	2	gouge on fractures
200	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	3	2	2	dyke 180.14-180.63 m
200	181.97	185.01	3.04	2.59	85	1.46	48	10	3	6	25	5	3	10% broken core with gouge
200	185.01	188.06	3.05	2.95	97	2.23	73	10	3	6	25	5	3	gypsum on fractures, 10% broken core
200	188.06	191.11	3.05	3.00	98	3.00	98	15	4	6	2	1	3	
200	191.11	194.16	3.05	2.98	98	2.72	89	15	3	6	5	1	3	18 cm H=1/2, gouge on fractures
200	194.16	197.21	3.05	3.14	103	3.14	103	15	3	6	2	1	3	gypsum on fractures
200	197.21	200.25	3.04	3.04	100	3.04	100	15	4	6	2	1	2	
200	200.25	203.30	3.05	3.08	101	3.08	101	15	4	6	1	1	3	gypsum on fractures
200	203.30	206.35	3.05	3.08	101	3.08	101	15	4	6	3	1	3	gypsum on fractures
200	206.35	209.40	3.05	3.00	98	3.00	98	15	4	6	3	1	3	gypsum on fractures
200	209.40	212.45	3.05	3.04	100	3.04	100	15	4	6	2	1	3	gouge on fractures
200	212.45	215.49	3.04	3.07	101	3.07	101	15	4	6	1	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
200	215.49	218.54	3.05	3.05	100	3.05	100	15	4	6	2	1	3	gouge on fractures
200	218.54	221.59	3.05	2.99	98	2.71	89	15	4	6	3	1	3	gypsum on fractures
200	221.59	224.64	3.05	3.00	98	3.00	98	15	4	6	2	1	3	gypsum on fractures
200	224.64	227.69	3.05	3.05	100	3.05	100	15	4	6	2	1	3	gypsum on fractures
200	227.69	230.73	3.04	3.04	100	3.04	100	15	4	6	1	1	2	
200	230.73	233.78	3.05	3.02	99	3.02	99	15	4	6	2	1	2	
200	233.78	236.83	3.05	2.99	98	2.99	98	15	4	6	1	1	2	
200	236.83	239.88	3.05	3.11	102	3.11	102	15	4	6	2	1	3	gypsum on fractures
200	239.88	242.93	3.05	3.09	101	3.09	101	15	4	6	3	1	2	
200	242.93	245.97	3.04	3.18	105	3.18	105	15	4	6	2	1	2	
200	245.97	249.02	3.05	3.00	98	3.00	98	15	4	6	2	2	3	gypsum on fractures
200	249.02	252.07	3.05	3.13	103	3.13	103	15	4	6	3	1	3	gypsum on fractures
200	252.07	255.12	3.05	3.00	98	3.00	98	15	3	6	3	1	3	gypsum on fractures
200	255.12	258.17	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gouge on fractures
200	258.17	261.21	3.04	3.00	99	3.00	99	15	3	6	2	2	3	34 cm H=2, gouge on fractures
200	261.21	264.26	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
200	264.26	267.31	3.05	2.95	97	2.95	97	15	4	6	1	1	2	gypsum on fracture
200	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	2	1	2	pyrite on fracture
200	270.36	273.41	3.05	3.03	99	3.03	99	15	4	6	3	1	2	
200	273.41	276.45	3.04	3.04	100	3.04	100	15	4	6	2	1	2	
200	276.45	279.50	3.05	2.96	97	2.96	97	15	4	6	2	1	3	gypsum on fractures
200	279.50	282.55	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gypsum on fractures
200	282.55	285.60	3.05	3.00	98	2.94	96	15	4	6	4	1	3	gypsum on fractures
200	285.60	288.65	3.05	2.90	95	2.81	92	15	4	6	4	2	3	gypsum on fractures
200	288.65	291.69	3.04	3.00	99	2.76	91	15	4	6	6	1	3	gypsum on fractures
201	6.10	8.84	2.74	1.81	66	0.93	34	7	3	3	25	1	2	rusty broken core, minor gouge
201	8.84	10.67	1.83	1.33	73	0.81	44	7	3	3	25	1	2	rubble zones
201	10.67	11.58	0.91	0.81	89	0.47	52	10	3	4	7	1	3	oxidized to 11m
201	11.58	14.33	2.75	2.22	81	0.92	33	9	3	3	25	1	3	gouge zones 1-2 cm wide
201	14.33	16.76	2.43	2.54	105	1.45	60	10	3	3	25	2	2	broken rock, gouge zones 1-2 cm wide
201	16.76	18.90	2.14	1.98	93	1.53	71	12	3	3	10	2	2	
201	18.90	20.12	1.22	0.59	48	0.13	11	7	0	1	9	2	2	gouge zones 30 cm (fault)
201	20.12	21.34	1.22	0.93	76	0.48	39	7	0	1	15	3	2	fault
201	21.34	23.16	1.82	1.76	97	1.20	66	12	0	2	10	3	2	fault

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
201	23.16	25.60	2.44	1.88	77	1.20	49	10	2	3	16	1	2	broken rock
201	25.60	26.62	1.02	0.95	93	0.85	83	13	3	6	4	1	2	
201	26.62	29.26	2.64	2.67	101	2.60	98	15	3	6	4	1	3	gouge, slip plane
201	29.26	29.87	0.61	0.35	57	0.00	0	6	3	3	8	1	4	broken rock
201	29.87	32.61	2.74	2.67	97	1.89	69	13	3	4	12	3	3	broken rock
201	32.61	35.66	3.05	3.15	103	2.30	75	13	3	3	11	3	2	
201	35.66	38.71	3.05	2.98	98	2.70	89	13	3	5	12	3	2	minor stressed rock
201	38.71	41.76	3.05	3.11	102	2.37	78	14	1	4	10	3	1	stressed rock
201	41.76	44.81	3.05	2.40	79	1.19	39	9	0	3	25	3	1	fault, gouge, stressed rock
201	44.81	47.85	3.04	2.96	97	2.43	80	14	3	5	6	3	2	stressed rock
201	47.85	50.90	3.05	3.20	105	2.73	90	13	3	5	16	3	1	slip planes
201	50.90	53.95	3.05	3.02	99	2.85	93	14	3	5	8	1	1	minor gouge 2-50 cm zones
201	53.95	57.00	3.05	2.60	85	1.78	58	10	3	3	25	3	2	fault zones, gouge
201	57.00	60.05	3.05	3.04	100	2.94	96	14	1	4	7	3	2	stresses rock, slip planes
201	60.05	63.09	3.04	2.40	79	1.82	60	10	0	3	20	3	2	fault gouge
201	63.09	66.14	3.05	2.25	74	1.49	49	10	0	3	20	3	2	fault gouge
201	66.14	69.19	3.05	3.04	100	2.70	89	14	3	6	9	3	1	
201	69.19	72.24	3.05	3.12	102	2.94	96	12	3	5	16	3	2	stressed rock
201	72.24	75.29	3.05	2.97	97	2.80	92	14	3	6	5	3	4	
201	75.29	78.33	3.04	3.07	101	2.88	95	14	3	6	8	1	2	
201	78.33	81.38	3.05	2.70	89	1.91	63	12	3	5	15	1	2	
201	81.38	84.43	3.05	2.80	92	1.40	46	13	3	5	12	1	2	
201	84.43	87.48	3.05	2.95	97	2.47	81	10	0	3	25	1	1	broken rock, gouge
201	87.48	90.53	3.05	3.00	98	1.62	53	10	1	5	20	1	2	broken rock
201	90.53	93.57	3.04	2.80	92	1.65	54	12	3	5	16	1	2	broken rock
201	93.57	96.62	3.05	3.15	103	2.90	95	14	3	6	10	3	2	
201	96.62	99.67	3.05	2.45	80	1.74	57	12	3	5	15	1	3	minor gouge
201	99.67	102.72	3.05	3.12	102	3.02	99	15	3	6	4	3	3	
201	102.72	105.77	3.05	3.01	99	2.87	94	15	3	6	5	3	1	slip plane
201	105.77	108.81	3.04	2.90	95	2.73	90	15	3	6	4	3	4	minor gouge 1 cm
201	108.81	111.86	3.05	3.20	105	3.03	99	15	3	6	3	1	2	
201	111.86	114.91	3.05	3.10	102	3.10	102	15	3	6	3	2	3	
201	114.91	117.96	3.05	3.03	99	3.03	99	14	0	4	6	1	1	10 cm gouge
201	117.96	121.01	3.05	3.10	102	2.78	91	14	3	5	7	1	1	5 cm gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
201	121.01	124.05	3.04	3.10	102	2.94	97	15	3	6	5	3	2	
201	124.05	127.10	3.05	2.93	96	2.93	96	15	3	6	4	3	2	
201	127.10	130.15	3.05	3.15	103	3.10	102	14	3	6	6	1	3	
201	130.15	133.20	3.05	3.10	102	3.03	99	14	3	6	6	3	2	
201	133.20	136.25	3.05	3.00	98	2.96	97	15	3	6	5	3	2	
201	136.25	139.29	3.04	3.00	99	2.68	88	15	3	6	5	3	4	
201	139.29	142.34	3.05	2.80	92	1.72	56	10	3	4	20	1		2 broken rock, 1 slip plane
201	142.34	145.39	3.05	2.82	92	0.22	7	10	3	4	25	1		3 broken rock
201	145.39	148.44	3.05	2.95	97	0.94	31	10	3	4	25	1		3 broken rock
201	148.44	151.49	3.05	2.87	94	2.49	82	13	1	4	10	1		1 gouge and stressed rock
201	151.49	154.53	3.04	2.99	98	1.25	41	12	0	3	15	1		2 gouge, fault
201	154.53	157.58	3.05	2.65	87	1.44	47	10	3	5	20	5		3 25% broken core with gouge
201	157.58	160.63	3.05	2.72	89	2.59	85	14	3	5	5	1		3 gouge on fractures
201	160.63	163.68	3.05	3.13	103	3.02	99	15	3	6	3	1		3 gouge on fractures
201	163.68	166.73	3.05	3.05	100	3.05	100	15	3	6	3	1		3 gouge on fractures
201	166.73	169.77	3.04	3.00	99	3.00	99	15	3	6	2	1		3 gouge on fractures
201	169.77	172.82	3.05	2.99	98	2.72	89	15	3	6	4	1		3 gouge on fractures
201	172.82	175.87	3.05	2.96	97	2.83	93	15	3	6	5	1		3 gouge on fractures
201	175.87	178.92	3.05	3.09	101	2.79	91	14	3	6	6	1		3 gouge on fractures
201	178.92	181.97	3.05	3.07	101	3.02	99	15	4	6	3	1	2	
201	181.97	185.01	3.04	3.00	99	3.00	99	15	4	6	2	1	2	
201	185.01	188.06	3.05	3.07	101	3.07	101	15	4	6	1	1	2	
201	188.06	191.11	3.05	2.89	95	2.89	95	15	4	6	2	1	2	
201	191.11	194.16	3.05	2.93	96	2.71	89	15	4	6	4	2	2	
201	194.16	197.21	3.05	3.17	104	2.92	96	14	4	6	8	2	2	
201	197.21	199.03	1.82	1.57	86	1.22	67	15	4	6	4	1	2	
201	199.03	202.08	3.05	2.75	90	2.51	82	14	4	6	7	2		2 5% broken core with gouge
201	202.08	203.30	1.22	1.08	89	0.98	80	12	4	6	6	5	3	
201	203.30	206.35	3.05	2.82	92	2.61	86	14	4	6	9	1	2	
201	206.35	209.40	3.05	3.09	101	2.87	94	14	4	6	8	2	2	
201	209.40	212.45	3.05	3.00	98	2.67	88	14	4	6	10	5		3 gouge on fractures
201	212.45	215.49	3.04	2.99	98	2.85	94	15	4	6	3	1	2	
201	215.49	218.54	3.05	2.99	98	2.99	98	15	4	6	2	1		2 gouge on fractures
201	218.54	221.59	3.05	2.68	88	2.06	68	14	4	6	7	1		3 35 cm H=0, 1

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
201	221.59	224.64	3.05	3.13	103	3.03	99	15	4	6	3	1	3	
201	224.64	227.69	3.05	2.84	93	2.59	85	14	4	6	5	1	2	
201	227.69	230.73	3.04	2.89	95	2.89	95	15	4	6	2	1	2	
201	230.73	233.78	3.05	3.22	106	3.04	100	14	4	6	6	1	3	gouge on fractures
201	233.78	236.83	3.05	2.93	96	2.68	88	14	4	6	5	1	3	gouge on fractures
201	236.83	239.88	3.05	3.14	103	2.29	75	13	4	6	15	5	3	10% broken core
201	239.88	242.93	3.05	2.86	94	0.94	31	10	4	6	25	5	3	20-25% broken core with gouge
201	242.93	245.97	3.04	3.30	109	3.07	101	15	4	6	5	1	3	
201	245.97	249.62	3.65	2.92	80	2.78	76	15	4	6	4	1	2	
201	249.62	252.07	2.45	2.96	121	2.41	98	15	4	6	8	1	2	
201	252.07	255.12	3.05	3.05	100	1.95	64	13	4	6	15	1	3	5% broken core
201	255.12	258.17	3.05	3.08	101	2.97	97	14	4	6	6	2	3	
201	258.17	261.21	3.04	2.91	96	2.80	92	14	3	6	6	1	2	
201	261.21	264.26	3.05	3.28	108	2.65	87	14	3	5	8	2	2	2 gouge zones 2 cm
201	264.26	267.31	3.05	3.07	101	3.07	101	14	3	6	6	3	2	
201	267.31	270.36	3.05	3.17	104	3.07	101	15	3	6	3	3	2	
201	270.36	273.41	3.05	3.05	100	3.05	100	15	3	6	2	3	2	
201	273.41	276.45	3.04	3.10	102	3.10	102	15	3	6	2	2	1	slip plane
201	276.45	279.50	3.05	3.00	98	3.00	98	15	3	6	1	1	2	
201	279.50	282.55	3.05	3.10	102	3.10	102	15	3	6	2	3	1	gypsum on fracture
201	282.55	285.60	3.05	3.03	99	2.98	98	15	3	6	3	3	2	gypsum on fracture
201	285.60	288.65	3.05	3.00	98	3.00	98	15	3	6	3	3	2	gypsum on fracture
201	288.65	291.69	3.04	3.10	102	3.00	99	15	3	6	5	3	1	gouge on fractures
201	291.69	294.74	3.05	3.07	101	3.00	98	15	3	6	2	3	1	gypsum on fractures
201	294.74	297.79	3.05	3.04	100	3.04	100	15	3	6	2	3	1	gypsum on fractures
201	297.79	300.84	3.05	3.01	99	3.01	99	15	3	6	2	3	1	gypsum on fractures
201	300.84	303.89	3.05	2.97	97	2.97	97	15	3	6	2	3	1	gypsum on fractures
201	303.89	306.93	3.04	3.04	100	3.04	100	15	3	6	2	3	1	gypsum on fractures
201	306.93	309.98	3.05	3.03	99	3.03	99	15	3	6	5	3	1	gypsum on fractures
201	309.98	313.03	3.05	3.00	98	3.00	98	13	0	3	11	2	1	fault
201	313.03	316.08	3.05	2.95	97	2.92	96	13	0	3	10	3	1	fault ground core, reduced section
201	316.08	319.13	3.05	3.02	99	2.95	97	14	1	4	7	1	2	healed fault
201	319.13	322.17	3.04	3.06	101	3.03	100	14	2	4	6	3	1	fault, slip plane
201	322.17	325.22	3.05	3.00	98	2.91	95	15	3	5	3	3	1	slip plane

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To	Lgth	m.	%	m.								%
201	325.22	328.27	3.05	3.07	101	3.07	101	15	3	6	2	3	1	
201	328.27	331.32	3.05	3.02	99	3.02	99	15	3	6	2	1	2	
202	3.66	5.18	1.52	0.72	47	0.44	29	7	3	5	12	2	3	iron stained fractures, broken core
202	5.18	8.23	3.05	2.87	94	1.58	52	12	3	5	15	2	3	iron stained fractures with gouge, broken
202	8.23	11.28	3.05	2.37	78	0.38	12	9	3	5	25	5	3	iron stained fractures with gouge, broken
202	11.28	14.33	3.05	2.52	83	1.11	36	10	3	5	25	5	3	iron stained fractures with gouge, broken
202	14.33	17.37	3.04	2.54	84	0.80	26	10	3	5	25	5	3	broken core with gouge
202	17.37	20.42	3.05	2.12	70	1.08	35	9	3	6	25	5	3	broken core with gouge
202	20.42	23.47	3.05	2.56	84	1.54	50	10	3	6	25	5	3	broken core with gouge
202	23.47	26.62	3.15	2.84	90	1.09	35	12	3	6	15	5	3	broken core with gouge, 8 cm H=0, 1
202	26.62	29.57	2.95	2.62	89	1.35	46	12	3	6	15	5	3	broken core with gouge, 10 cm H=0, 1
202	29.57	32.61	3.04	2.89	95	1.52	50	10	3	6	20	5	3	broken core with gouge
202	32.61	35.66	3.05	3.03	99	2.49	82	14	4	6	10	2	3	
202	35.66	38.71	3.05	3.05	100	2.71	89	14	4	6	10	1	3	
202	38.71	41.76	3.05	3.11	102	2.04	67	12	3	6	20	1	3	broken core (30%) with gouge
202	41.76	44.81	3.05	3.05	100	2.91	95	15	3	6	5	1	3	
202	44.81	47.85	3.04	2.70	89	2.27	75	14	3	6	6	1	3	gouge on fractures
202	47.85	50.90	3.05	3.14	103	2.98	98	15	3	6	4	1	3	gouge on fractures
202	50.90	53.95	3.05	2.94	96	2.71	89	14	3	6	7	1	3	15 cm H=1,2, gouge on fractures
202	53.95	57.00	3.05	3.10	102	3.10	102	15	3	6	3	1	3	8 cm H=1,2
202	57.00	60.05	3.05	3.14	103	2.09	69	13	3	6	15	1	3	10% broken core
202	60.05	62.18	2.13	2.13	100	1.35	63	13	3	6	8	2	3	5% broken core with gouge
202	62.18	64.62	2.44	2.41	99	1.34	55	13	3	6	12	2	3	5% broken core with gouge
202	64.62	66.75	2.13	2.13	100	2.07	97	14	3	6	4	1	3	gouge on fractures
202	66.75	69.19	2.44	2.51	103	2.26	93	14	4	6	5	1	3	gouge on fractures
202	69.19	72.24	3.05	2.96	97	2.62	86	14	4	6	7	1	3	gouge on fractures
202	72.24	75.29	3.05	3.14	103	2.89	95	15	4	6	5	1	3	gouge on fractures
202	75.29	78.33	3.04	3.04	100	2.91	96	15	4	6	3	1	2	
202	78.33	81.38	3.05	3.04	100	2.13	70	13	4	6	15	5	3	10% broken core with gouge
202	81.38	84.43	3.05	3.15	103	2.98	98	15	4	6	5	1	3	10 cm H= 1,2, gouge on fractures
202	84.43	87.48	3.05	3.07	101	3.07	101	15	4	6	2	1	3	
202	87.48	90.53	3.05	3.09	101	3.01	99	15	4	6	3	1	2	dyke
202	90.53	93.57	3.04	3.10	102	3.06	101	15	4	6	2	1	3	gouge on fractures
202	93.57	96.62	3.05	3.05	100	2.89	95	15	4	6	5	1	3	gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
202	96.62	99.67	3.05	3.03	99	2.91	95	15	4	6	4	2	3	15 cm H=1,2, gouge on fractures
202	99.67	102.72	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
202	102.72	105.77	3.05	3.03	99	3.03	99	15	4	6	2	1	2	
202	105.77	108.81	3.04	3.04	100	3.04	100	15	4	6	3	1	3	gypsum on fractures
202	108.81	111.86	3.05	3.11	102	2.88	94	15	4	6	5	1	3	gypsum on fractures
202	111.86	114.91	3.05	3.03	99	3.00	98	15	4	6	3	1	3	gypsum on fractures, 6 cm H=1 (gouge)
202	114.91	117.96	3.05	3.02	99	3.02	99	15	4	6	4	1	3	gypsum on fractures
202	117.96	121.01	3.05	3.08	101	3.08	101	15	4	6	2	1	3	gypsum on fractures
202	121.01	124.05	3.04	3.04	100	3.04	100	15	4	6	4	1	3	gypsum on fractures
202	124.05	127.10	3.05	2.99	98	2.99	98	15	4	6	4	1	3	gypsum on fractures
202	127.10	130.15	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gypsum on fractures
202	130.15	133.20	3.05	3.08	101	3.00	98	15	4	6	2	1	3	gypsum on fractures
202	133.20	136.25	3.05	3.02	99	3.02	99	15	4	6	1	1	3	gypsum on fractures
202	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6	3	1	3	gypsum on fractures
202	139.29	142.34	3.05	3.06	100	3.06	100	15	4	6	1	1	3	gypsum on fractures
202	142.34	145.39	3.05	3.08	101	3.08	101	15	4	6	2	1	3	gypsum on fractures
202	145.39	148.39	3.00	3.03	101	2.78	93	15	4	6	5	1	3	gypsum on fractures
202	148.44	151.49	3.05	2.95	97	2.95	97	15	4	6	2	1	3	gypsum on fractures
202	151.49	154.53	3.04	3.08	101	3.08	101	15	4	6	3	1	2	gypsum veining-reduces rock strength
202	154.53	157.58	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum veining-reduces rock strength
202	157.58	160.63	3.05	3.00	98	3.00	98	15	4	6	1	1	2	gypsum veining-reduces rock strength
202	160.63	163.68	3.05	3.09	101	3.09	101	15	4	6	1	1	2	gypsum veining-reduces rock strength
202	163.68	166.73	3.05	3.05	100	3.05	100	15	4	6	2	1	2	gypsum veining, 50 cm H=3
202	166.73	169.77	3.04	3.04	100	3.04	100	15	4	6	3	1	2	gypsum veining-reduces rock strength
202	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum veining-reduces rock strength
202	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6				gypsum veining-reduces rock strength
202	175.87	178.92	3.05	3.05	100	3.05	100	15	4	6				gypsum veining-reduces rock strength
202	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	2	1	2	gypsum veining-reduces rock strength
202	181.97	185.01	3.04	3.04	100	3.04	100	15	5	6	1	1	1	1 fault begins
202	185.01	188.06	3.05	2.98	98	2.76	90	15	5	6	24	1	1	20 cm H=0, 50% H=4
202	188.06	191.11	3.05	3.10	102	2.90	95	13	5	6	14	1	1	1 fault ends, part healed sections
202	191.11	194.16	3.05	3.05	100	3.03	99	15	4	6	6	1	2	gypsum veining-reduces rock strength
202	194.16	197.21	3.05	3.07	101	3.07	101	15	4	6	2	1	2	gypsum veining-reduces rock strength
202	197.21	200.25	3.04	3.05	100	3.05	100	15	4	6	1	1	2	gypsum veining-reduces rock strength

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
202	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6			gypsum veining-reduces rock strength
202	203.30	206.35	3.05	3.02	99	3.02	99	15	4	6			gypsum veining-reduces rock strength
202	206.35	209.40	3.05	2.87	94	2.70	89	14	4	6	8	1	2 minor gouge, gypsum veining
202	209.40	212.45	3.05	3.05	100	3.05	100	15	4	6	1	1	2 gypsum veining-reduces rock strength
202	212.45	215.49	3.04	3.04	100	3.05	100	15	4	6	2	1	2 gypsum veining-reduces rock strength
202	215.49	218.54	3.05	3.05	100	3.05	100	15	4	6	1	1	2 gypsum veining-reduces rock strength
202	218.54	221.59	3.05	3.05	100	2.73	90	14	3	6	9	1	1 32 cm H=1,2, part healed gouge
202	221.59	224.64	3.05	2.99	98	2.99	98	15	4	6	2	1	1 gypsum veining-reduces rock strength
202	224.64	227.69	3.05	3.22	106	3.22	106	15	5	6	1	1	1 very slick 45 to c.a.
202	227.69	230.73	3.04	2.85	94	2.85	94	15	5	6	1	1	2
202	230.73	233.78	3.05	2.97	97	2.69	88	14	4	6	7	1	2 partly healed sections
202	233.78	236.83	3.05	3.10	102	3.10	102	15	5	6			
202	236.83	239.88	3.05	3.08	101	3.08	101	15	5	6			
202	239.88	242.93	3.05	3.07	101	2.85	93	13	4	5	18	1	1 minor gouge
202	242.93	245.97	3.04	3.05	100	3.05	100	15	5	6	3	1	2
202	245.97	249.02	3.05	2.38	78	1.03	34	6	3	4	40	1	1 70% fault material
202	249.02	252.07	3.05	3.02	99	2.99	98	15	4	6	3	1	3
202	252.07	255.12	3.05	2.98	98	2.64	87	15	4	6	4	1	3 gouge on fractures
202	255.12	258.17	3.05	3.01	99	3.01	99	15	4	6	1	2	3
202	258.17	261.21	3.04	3.04	100	3.00	99	15	4	6	3	1	3
202	261.21	264.26	3.05	3.01	99	2.93	96	15	4	6	3	2	3 gouge on fractures
202	264.26	267.31	3.05	3.05	100	2.74	90	15	4	6	5	1	3 9 cm H=1, gouge on fractures
202	267.31	270.36	3.05	2.86	94	2.45	80	15	4	6	4	1	3 10 cm H=2, gouge on fractures
202	270.36	273.41	3.05	3.10	102	2.69	88	15	4	6	5	2	3 gouge on fractures
202	273.41	276.45	3.04	2.95	97	2.36	78	15	4	6	8	1	3 gouge on fractures, 11 cm H=2
202	276.45	279.50	3.05	3.07	101	2.47	81	15	4	6	15	2	3 5% broken core with gouge
202	279.50	282.55	3.05	3.08	101	2.91	95	15	4	6	7	1	3 gouge on fractures
202	282.55	285.60	3.05	3.04	100	3.04	100	15	4	6	1	1	2
202	285.60	288.65	3.05	3.05	100	2.94	96	15	4	6	3	5	3 gouge on fractures
202	288.65	291.69	3.04	3.02	99	2.87	94	15	4	6	5	1	3 gouge on fractures
202	291.69	294.74	3.05	3.09	101	2.95	97	15	4	6	5	1	3 gouge on fractures
202	294.74	297.79	3.05	3.14	103	3.14	103	15	4	6	2	1	2
202	297.79	300.84	3.05	2.95	97	2.95	97	15	4	6	1	1	2
202	300.84	303.89	3.05	3.11	102	2.92	96	15	4	6	2	1	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
202	303.89	306.93	3.04	3.10	102	2.51	83	14	4	6	6	2	3	6 cm H=2, gouge on fractures
202	306.93	309.98	3.05	3.03	99	3.03	99	15	4	6	2	1	2	
202	309.98	313.03	3.05	2.99	98	2.99	98	15	4	6	1	1	2	
202	313.03	316.08	3.05	3.11	102	3.02	99	15	4	6	4	1	3	gouge on fractures
202	316.08	319.13	3.05	3.05	100	2.89	95	15	4	6	3	1	3	33 cm H=1,2 (gouge), gouge on fractures
202	319.13	322.17	3.04	3.04	100	3.04	100	15	4	6	2	1	3	gouge on fractures
202	322.17	325.22	3.05	2.96	97	2.63	86	15	4	6	4	1	3	slip plane
202	325.22	328.27	3.05	3.09	101	3.09	101	15	4	6	2	1	2	
202	328.27	331.32	3.05	3.13	103	3.13	103	15	4	6	3	1	3	gouge on fractures
202	331.32	334.37	3.05	3.00	98	3.00	98	15	4	6	2	2	2	
202	334.37	337.41	3.04	3.06	101	3.06	101	15	4	6	1	1	2	gouge on fractures
202	337.41	340.46	3.05	2.95	97	2.95	97	15	4	6	2	1	3	gypsum on fractures
202	340.46	343.51	3.05	3.15	103	3.15	103	15	4	6	3	1	2	
202	343.51	346.56	3.05	3.13	103	3.12	102	15	4	6	4	1	2	
202	346.56	349.61	3.05	3.12	102	3.04	100	14	4	6	8	1	1	trace gouge on slip
202	349.61	352.65	3.04	2.92	96	2.92	96	15	4	6	3	1	1	
202	352.65	355.70	3.05	3.07	101	3.03	99	15	4	6	4	1	2	trace gouge in break
202	355.70	358.75	3.05	3.05	100	2.90	95	15	4	6	4	1	1	shear zone with trace gouge
202	358.75	361.80	3.05	3.00	98	3.00	98	15	4	6	3	1	1	shear zone with trace gouge
202	361.80	364.85	3.05	3.02	99	3.02	99	15	4	6	5	1	1	shear zone with trace gouge
202	364.85	367.89	3.04	3.04	100	3.04	100	15	4	6	4	1	1	trace gouge on contact
202	367.89	370.94	3.05	3.03	99	3.03	99	14	4	6	7	2	3	
202	370.94	373.99	3.05	3.08	101	3.08	101	15	4	6	4	1	1	
202	373.99	377.04	3.05	3.00	98	3.00	98	15	4	6	5	1	1	2-3 mm gouge on slip
203	3.66	4.27	0.61	0.80	131	0.00	0	4	2	3	50	3	3	rubble
203	4.27	6.40	2.13	2.18	102	1.00	47	7	3	5	32	1	3	
203	6.40	8.23	1.83	1.25	68	0.22	12	4	1	5	27	1	3	zones of gouge and crush to 10 cm
203	8.23	11.28	3.05	1.85	61	0.56	18	7	1	5	27	3	3	zones of gouge and crush to 10 cm
203	11.28	14.33	3.05	2.20	72	0.32	10	6	2	6	50	1	3	
203	14.33	17.37	3.04	1.43	47	0.46	15	6	2	6	40	3	3	
203	17.37	20.42	3.05	2.65	87	0.61	20	7	2	6	50	1	2	minor zones gouge
203	20.42	23.47	3.05	2.10	69	0.44	14	6	2	6	50	3	3	zones of crush and gouge
203	23.47	26.52	3.05	2.50	82	0.93	30	7	2	6	42	2	3	
203	26.52	29.57	3.05	2.35	77	0.98	32	7	2	6	33	2	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
203	29.57	32.61	3.04	2.35	77	0.55	18	6	2	6	50	2	2 zones of crush, minor gouge	
203	32.61	35.66	3.05	2.30	75	0.45	15	6	2	6	50	3	3 zones of crush, minor gouge	
203	35.66	38.71	3.05	0.60	20	0.00	0	3	2	6	50	1	3 crush zone, minor gouge	
203	38.71	41.76	3.05	2.90	95	0.62	20	7	2	6	50	2	2 zones of crush, minor gouge	
203	41.76	44.81	3.05	2.45	80	0.76	25	6	2	6	50	1	1 zones of crush, minor gouge	
203	44.81	47.85	3.04	2.40	79	0.56	18	6	2	6	50	3	3 zones of crush, minor gouge	
203	47.85	50.90	3.05	1.60	52	0.12	4	6	2	6	41	1	2 zones of crush, minor gouge	
203	50.90	53.95	3.05	2.00	66	0.43	14	6	2	6	44	2	2 zones of crush, minor gouge	
203	53.95	57.00	3.05	1.20	39	0.11	4	6	2	6	30	2	2 zones of crush, minor gouge	
203	57.00	60.05	3.05	2.20	72	0.37	12	6	2	6	50	1	1 zones of crush, minor gouge	
203	60.05	63.10	3.05	1.15	38	0.62	20	7	2	6	22	2	3 zones of crush, minor gouge	
203	63.10	66.14	3.04	2.65	87	0.87	29	7	2	6	50	1	2 zones of crush, minor gouge	
203	66.14	69.19	3.05	2.90	95	1.05	34	7	2	6	50	1	1 zones of crush, minor gouge	
203	69.19	71.32	2.13	2.47	116	0.95	45	7	2	6	45	2	3 zones of crush, minor gouge	
203	71.32	73.76	2.44	2.65	109	0.55	23	6	2	6	50	1	2 crush gouge to 10 cm	
203	73.76	76.20	2.44	1.35	55	0.00	0	6	2	6	50	3	3 crush zone	
203	76.20	77.11	0.91	0.60	66	0.00	0	6	2	6	24	3	3 rubble, minor gouge	
203	77.11	78.33	1.22	0.73	60	0.18	15	6	2	6	21	2	3	
203	78.33	80.77	2.44	0.95	39	0.00	0	6	2	6	40	1	2	
203	80.77	83.21	2.44	1.80	74	0.00	0	6	2	6	43	2	3 minor gouge	
203	83.21	84.43	1.22	1.10	90	0.00	0	7	2	6	20	1	3 pyrite on fracture surfaces	
203	84.43	85.34	0.91	0.75	82	0.22	24	6	2	6	21	1	3 pyrite on fracture surfaces	
203	85.34	86.56	1.22	1.05	86	0.36	30	7	2	6	21	2	3 pyrite on fracture surfaces	
203	86.56	88.70	2.14	2.00	93	0.56	26	6	2	6	44	2	3 pyrite, chalcopyrite on fracture surfaces	
203	88.70	90.53	1.83	0.90	49	0.00	0	6	2	6	30	2	3 pyrite, chalcopyrite on fracture surfaces	
203	90.53	92.35	1.82	1.25	69	0.59	32	6	2	6	38	2	3 pyrite, chalcopyrite on fracture surfaces	
203	92.35	94.49	2.14	1.28	60	0.23	11	7	3	5	21	2	3 pyrite, chalcopyrite on fractures, rubble	
203	94.49	96.62	2.13	1.00	47	0.30	14	7	3	5	20	2	3 poor recovery, rubble and gouge	
203	96.62	99.67	3.05	1.28	42	0.41	13	9	3	5	14	3	3 clay material, rubble and gouge	
203	99.67	102.72	3.05	1.37	45	0.32	10	3	3	5	35	1	3 clay material, rubble and gouge	
203	102.72	105.77	3.05	1.90	62	1.03	34	7	3	5	36	1	1 clay mat'l, rubble and gouge, weak slicks	
203	105.77	108.81	3.04	1.85	61	0.77	25	6	3	5	38	1	2 clay material, rubble and gouge	
203	108.81	111.86	3.05	2.43	80	1.18	39	11	3	5	19	1	2 clay material, rubble and gouge	
203	111.86	114.91	3.05	2.01	66	0.69	23	8	3	5	28	1	1 clay material, rubble and gouge	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
203	114.91	117.96	3.05	1.51	50	0.52	17	7	3	5	24	1	2 clay material, rubble and gouge	
203	117.96	121.01	3.05	0.68	22	0.18	6	7	3	5	12	1	3 broken, no rubble, manual breaks	
203	121.01	124.05	3.04	2.08	68	0.76	25	7	4	5	32	1	3 minor rubble, manual breaks	
203	124.05	126.19	2.14	1.17	55	0.56	26	10	4	5	12	1	2 rubble and gouge, manual breaks	
203	126.19	127.41	1.22	1.04	85	0.49	40	7	4	5	15	1	2 rubble and gouge, manual breaks	
203	127.41	128.93	1.52	1.25	82	1.15	76	13	4	5	5	1	2 minor gouge on fractures	
203	128.93	131.98	3.05	3.10	102	3.10	102	15	5	6	2	1	1 gypsum on fractures	
203	131.98	135.03	3.05	3.04	100	3.04	100	15	5	6	4	1	1 gypsum on fractures	
203	135.03	138.07	3.04	2.98	98	2.98	98	15	5	6	3	1	1 gypsum on fractures	
203	138.07	141.12	3.05	2.95	97	2.88	94	15	5	6	4	1	1 gypsum on fractures, very slick, 20 to c.a.	
203	141.12	144.17	3.05	2.97	97	2.97	97	15	5	6	2	1	1 gypsum on fractures	
203	144.17	147.22	3.05	3.20	105	3.20	105	15	5	6	4	1	2 gypsum on fractures	
203	147.22	149.35	2.13	2.10	99	2.10	99	15	5	6	2	3	3 gypsum on fractures	
203	149.35	151.49	2.14	2.21	103	2.21	103	15	5	6	3	1	1 gypsum on fractures, healed gouge	
203	151.49	154.53	3.04	3.00	99	2.93	96	15	5	6	5	1	1 gypsum on fractures, healed gouge	
203	154.53	157.58	3.05	3.16	104	2.41	79	15	5	6	14	1	1 healed fault gouge, 70 cm H=1	
203	157.58	160.63	3.05	3.05	100	3.05	100	15	5	6	5	1	1	
203	160.63	163.68	3.05	3.05	100	3.00	98	15	5	6	8	1	1 5 cm of clay at 162.10m	
203	163.68	166.73	3.05	2.94	96	2.75	90	14	4	6	11	1	1 gypsum, minor gouge on weak slicks	
203	166.73	169.77	3.04	3.05	100	3.05	100	13	4	6	3	1	1	
203	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	2	1	1 minor gouge on weak slicks	
203	172.82	175.87	3.05	3.10	102	3.10	102	15	4	6	2	1	1 minor gouge on weak slicks	
203	175.87	178.92	3.05	3.00	98	3.00	98	15	4	6	3	1	1 minor gouge on weak slicks	
203	178.92	181.97	3.05	2.90	95	2.78	91	15	4	6	8	1	1 minor gouge on weak slicks	
203	181.97	185.01	3.04	2.92	96	2.85	94	15	4	6	3	1	1 minor gouge on weak slicks	
203	185.01	188.06	3.05	3.00	98	3.00	98	15	4	6	3	1	2 part healed breccia 40 cm, slicks	
203	188.06	191.11	3.05	3.00	98	2.77	91	13	4	6	10	1	1 15 cm of H=2,1 slicks at 35 to c.a.	
203	191.11	194.16	3.05	3.10	102	3.10	102	15	5	6	4	1	1	
203	194.16	197.21	3.05	3.11	102	3.11	102	15	5	6	5	1	1	
203	197.21	200.25	3.04	3.05	100	2.97	98	14	5	6	8	1	1 some healed gouge	
203	200.25	203.30	3.05	3.08	101	3.08	101	15	5	6	2	1	2	
203	203.30	206.35	3.05	2.99	98	2.99	98	15	5	6				
203	206.35	209.40	3.05	2.98	98	2.85	93	15	5	6	4	1	2	
203	209.40	211.23	1.83	1.72	94	1.42	78	14	4	6	9	3	3 broken material	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
203	211.23	213.06	1.83	1.63	89	1.33	73	13	4	6	13	1	2	35 cm healed breccia
203	213.06	215.49	2.43	2.51	103	2.38	98	15	4	6	6	3	3	healed fractures
203	215.49	218.54	3.05	3.02	99	3.02	99	15	4	6	4	3	3	healed fractures
203	218.54	221.59	3.05	2.93	96	2.71	89	13	4	6	14	1	2	healed fractures
203	221.59	224.64	3.05	3.05	100	2.92	96	13	4	6	11	1	1	brecciated zones, healed, weak slicks
203	224.64	227.69	3.05	2.96	97	2.96	97	15	4	6	5	3	2	brecciated zones, healed, weak slicks
203	227.69	230.73	3.04	2.99	98	2.99	98	15	4	6	6	1	1	brecciated zones, healed, weak slicks
203	230.73	233.78	3.05	3.08	101	2.96	97	15	4	6	5	1	1	brecciated zones, healed, weak slicks
203	233.78	236.83	3.05	2.99	98	2.99	98	15	4	6	3	1	1	brecciated zones, healed, weak slicks
203	236.83	239.88	3.05	3.10	102	3.02	99	15	4	6	4	3	3	brecciated zones, healed, weak slicks
203	239.88	242.93	3.05	3.15	103	3.08	101	15	3	6	6	1	2	brecciated zones, healed, weak slicks
203	242.93	245.97	3.04	3.18	105	3.01	99	14	3	6	8	1	1	brecciated zones, healed, weak slicks
203	245.97	249.02	3.05	3.00	98	3.00	98	15	3	6	5	1	1	brecciated zones, healed, weak slicks
203	249.02	252.07	3.05	3.05	100	3.05	100	15	3	6	4	1	1	brecciated zones, healed, weak slicks
203	252.07	255.12	3.05	3.05	100	3.05	100	15	3	6	4	1	1	brecciated zones, healed, weak slicks
203	255.12	258.17	3.05	3.05	100	3.05	100	15	5	6				
203	258.17	261.21	3.04	3.04	100	3.04	100	15	5	6				
203	261.21	264.26	3.05	3.05	100	3.05	100	15	5	6				
203	264.26	267.31	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
203	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
203	270.36	273.41	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
203	273.41	276.45	3.04	3.04	100	3.04	100	15	4	6	2	1	2	
203	276.45	279.50	3.05	3.08	101	2.81	92	11	4	6	16	1	1	27 cm of fault gouge, brecciated
203	279.50	282.55	3.05	3.05	100	3.05	100	14	4	6	10	1	2	minor gouge, broken materail
203	282.55	285.60	3.05	3.05	100	3.05	100	15	4	6	3	2	3	
203	285.60	288.65	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
203	288.65	291.69	3.04	3.05	100	3.05	100	15	5	6	1	1	1	very weak slick
203	291.69	294.75	3.06	3.05	100	2.95	96	15	5	6	3	1	2	section of gouge, 10 cm
203	294.75	295.96	1.21	1.21	100	1.21	100	15	5	6				
204	4.19	5.18	0.99	0.75	76	0.15	15	3	3	4	25	5	3	broken rock with gouge
204	5.18	8.23	3.05	3.08	101	0.00	0	2	3	4	50	5	3	broken rock with gouge, 43 cm H=0, 1
204	8.23	11.28	3.05	2.30	75	0.41	13	1	0	4	50	5	3	broken rock with gouge, 1.65m gouge H=0
204	11.28	14.33	3.05	1.14	37	0.72	24	2	0	4	50	5	3	broken rock with gouge, 32 cm gouge H=0
204	14.33	17.37	3.04	0.31	10	0.00	0	1	0	5	50	5	3	broken rock with gouge, 15 cm H=0

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
204	17.37	20.42	3.05	0.10	3	0.00	0	2	3	5	25	5	3	3 broken rock with gouge
204	20.42	23.47	3.05	0.26	9	0.00	0	2	3	5	25	5	3	3 broken rock with gouge
204	23.47	26.53	3.06	0.95	31	0.18	6	2	3	5	25	5	3	3 broken rock with gouge
204	26.53	29.57	3.04	1.00	33	0.00	0	2	3	5	25	5	3	3 broken rock with gouge
204	29.57	32.61	3.04	1.61	53	0.21	7	2	3	5	50	5	3	3 broken rock with gouge
204	32.61	35.66	3.05	1.07	35	0.00	0	2	3	5	50	5	3	3 broken rock with gouge
204	35.66	38.71	3.05	3.05	100	0.00	0	2	3	5	50	5	3	3 broken rock with gouge
204	38.71	41.76	3.05	0.85	28	0.00	0	2	3	5	25	5	3	3 broken rock with gouge
204	41.76	44.81	3.05	0.74	24	0.00	0	2	3	5	25	5	3	3 50% broken core with gouge
204	44.81	60.05	15.24	0.65	4	0.43	3	13	3	6	3	1	3	3 lost core
204	60.05	63.09	3.04	2.71	89	2.65	87	15	3	6	3	1	3	3 8 cm gouge H=1, gouge on fractures
204	63.09	66.14	3.05	3.00	98	2.58	85	15	3	6	4	2	3	3 6 cm fault gouge at 5 to c.a.
204	66.14	69.19	3.05	3.11	102	1.86	61	14	3	6	10	5	3	3 75 cm fault gouge at 25 to c.a.
204	69.19	72.24	3.05	3.10	102	2.99	98	15	3	6	4	1	3	3 gypsum on fractures
204	72.24	75.29	3.05	3.00	98	2.87	94	15	3	6	5	5	3	3 35 cm gouge at 10 to c.a.
204	75.29	78.33	3.04	3.04	100	3.04	100	15	4	6	1	1	2	2 gypsum on fractures
204	78.33	81.38	3.05	3.05	100	3.05	100	15	4	6	1	1	2	2 gouge on fractures
204	81.38	84.43	3.05	3.07	101	3.07	101	15	4	6	2	1	2	2 gouge on fractures
204	84.43	87.48	3.05	3.06	100	3.06	100	15	4	6	1	2	2	2 gouge on fractures
204	87.48	90.53	3.05	3.05	100	3.05	100	15	4	6	3	1	2	2 30% dyke H=5, gouge on fractures
204	90.53	93.57	3.04	3.02	99	2.82	93	15	4	6	4	1	3	3 14 cm H=1,2, faults at 35 to c.a.
204	93.57	96.62	3.05	3.05	100	3.05	100	15	4	6	2	5	3	3
204	96.62	99.67	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3 gypsum on fractures
204	99.67	102.72	3.05	3.05	100	3.05	100	15	4	6	1	1	3	3 gypsum on fractures
204	102.72	105.97	3.25	2.98	92	2.98	92	15	4	6	4	1	2	2 gypsum on fractures
204	105.97	108.81	2.84	3.19	112	3.19	112	15	4	6	2	1	3	3 gypsum on fractures
204	108.81	111.86	3.05	2.99	98	2.99	98	15	4	6	2	1	3	3 gypsum on fractures
204	111.86	114.91	3.05	2.98	98	2.79	91	14	4	6	5	1	3	3 gypsum and gouge on fractures
204	114.91	117.96	3.05	2.95	97	2.73	90	14	3	6	6	2	3	3 sheared rock with gypsum
204	117.96	121.01	3.05	2.96	97	2.61	86	14	3	6	5	1	3	3 13 cm H=1,2, shear at 25-35 to c.a.
204	121.01	124.05	3.04	3.01	99	3.01	99	15	4	6	4	1	3	3 gypsum on fractures
204	124.05	127.10	3.05	3.21	105	3.21	105	15	4	6	3	1	3	3 gypsum on fractures
204	127.10	130.15	3.05	2.93	96	2.65	87	13	4	6	10	1	3	3 5% broken rock, gouge on fractures
204	130.15	133.20	3.05	3.06	100	3.06	100	15	4	6	2	1	3	3

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
204	133.20	136.25	3.05	3.00	98	2.93	96	15	3	6	4	1	3	gouge on fractures
204	136.25	139.29	3.04	3.00	99	2.96	97	15	3	6	5	1	3	sheared rock
204	139.29	142.34	3.05	2.98	98	2.69	88	15	3	6	4	1	3	gouge on fractures
204	142.34	145.39	3.05	3.06	100	3.06	100	15	3	6	3	1	3	gypsum on fractures
204	145.39	148.44	3.05	2.92	96	2.92	96	15	3	6	4	1	3	gypsum and gouge on fractures
204	148.44	151.49	3.05	3.05	100	2.94	96	15	3	6	2	1	3	3 cm gouge at 45 to c.a.
204	151.49	154.53	3.04	2.97	98	2.97	98	15	3	6	1	1	3	gouge on fractures
204	154.53	157.58	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
204	157.58	160.63	3.05	2.96	97	2.96	97	14	3	6	5	1	3	gouge and gypsum on fractures
204	160.63	163.68	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gouge and gypsum on fractures
204	163.68	166.73	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
204	166.73	169.77	3.04	3.05	100	3.05	100	15	4	6	2	1	3	gypsum on fractures
204	169.77	172.82	3.05	3.11	102	3.11	102	15	4	6	3	1	2	
204	172.82	175.87	3.05	2.85	93	2.76	90	15	3	6	3	1	3	gouge and gypsum on fractures
204	175.87	178.92	3.05	3.14	103	3.06	100	15	4	6	3	2	3	gouge and gypsum on fractures
204	178.92	181.97	3.05	3.13	103	3.09	101	14	4	6	5	1	3	gouge and gypsum on fractures
204	181.97	185.01	3.04	3.00	99	2.97	98	15	3	6	4	1	3	gouge on fractures
204	185.01	188.06	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gypsum on fractures
204	188.06	191.11	3.05	3.04	100	3.04	100	15	3	6	4	1	3	gypsum on fractures
204	191.11	194.16	3.05	2.96	97	2.96	97	15	3	6	3	2	3	gypsum on fractures
204	194.16	197.21	3.05	3.09	101	2.86	94	14	3	6	8	1	3	7 cm H=1, gouge and gy on fractures
204	197.21	200.25	3.04	3.04	100	2.90	95	14	3	6	7	1	3	vuggy core, 18 cm H=1,2
204	200.25	203.30	3.05	3.13	103	2.09	69	14	2	5	10	1	3	fault, H=1,2 (U.C at 30, L.C. at 35 to c.a.)
204	203.30	206.35	3.05	2.74	90	2.74	90	15	5	6	1	1	2	
204	206.35	209.40	3.05	3.15	103	3.15	103	15	5	6	1	1	2	
204	209.40	212.45	3.05	3.00	98	2.74	90	15	5	6	7	2	3	5% broken core with minor gouge
204	212.45	215.49	3.04	3.32	109	3.21	106	15	5	6	3	1	2	
204	215.49	218.54	3.05	3.04	100	3.04	100	15	5	6	2	1	2	
204	218.54	221.59	3.05	3.14	103	3.14	103	15	5	6	2	1	2	carbonate on fractures
204	221.59	224.64	3.05	3.05	100	3.05	100	15	5	6	3	1	2	carbonate on fractures
204	224.64	227.69	3.05	3.08	101	3.08	101	15	5	6	4	1	2	carbonate on fractures
204	227.69	230.73	3.04	2.81	92	2.74	90	15	5	6	4	1	2	carbonate on fractures
204	230.73	233.78	3.05	2.32	76	3.13	103	15	5	6	9	2	2	carbonate on fractures, 5% broken core
204	233.78	236.83	3.05	3.05	100	3.05	100	15	5	6	5	1	2	carbonate on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
204	236.83	239.88	3.05	3.07	101	3.07	101	15	5	6	1	1	2	
204	239.88	242.93	3.05	3.05	100	3.05	100	15	5	6				
204	242.93	245.97	3.04	3.13	103	3.13	103	15	5	6	1	1	2	
204	245.97	249.02	3.05	3.04	100	3.04	100	15	5	6	2	1	3	minor gouge on fractures
204	249.02	252.07	3.05	2.99	98	2.99	98	15	5	6	1	1	2	carbonate on fractures
204	252.07	255.12	3.05	3.00	98	3.00	98	15	5	6	2	1	2	
204	255.12	258.17	3.05	2.86	94	2.12	70	10	5	6	20	5	3	10-15% broken core with minor gouge
204	258.17	261.21	3.04	2.88	95	2.72	89	14	5	6	6	2	2	minor gouge on fractures
204	261.21	264.26	3.05	3.58	117	3.40	111	14	5	6	7	2	2	
204	264.26	267.31	3.05	2.98	98	2.98	98	15	5	6	4	1	3	minor gouge on fractures
204	267.31	270.36	3.05	3.00	98	3.00	98	15	5	6	0			
204	270.36	273.41	3.05	3.01	99	3.01	99	15	5	6	1	1	2	
204	273.41	276.45	3.04	3.04	100	3.00	99	15	5	6	2	2	2	
204	276.45	279.50	3.05	3.08	101	3.08	101	15	5	6	4	1	2	carbonate on fractures
204	279.50	282.55	3.05	3.02	99	3.02	99	15	5	6	1	1	2	carbonate on fractures
204	282.55	285.60	3.05	3.15	103	3.15	103	15	5	6	3	1	2	carbonate on fractures
204	285.60	288.65	3.05	2.95	97	2.95	97	15	5	6	0			
204	288.65	291.69	3.04	3.14	103	3.14	103	15	5	6	1	1	2	
204	291.69	294.74	3.05	3.13	103	3.13	103	15	5	6	0			
204	294.74	297.79	3.05	2.92	96	2.80	92	15	5	6	4	1	2	
204	297.79	300.84	3.05	3.04	100	3.04	100	15	4	6	4	1	2	carbonate on fractures
204	300.84	303.89	3.05	3.05	100	2.97	97	15	4	6	4	1	3	4 cm gouge at 70 to c.a.
204	303.89	306.93	3.04	3.04	100	3.04	100	15	4	6	3	2	3	minor shear, 2 slip planes at 18 to c.a.
204	306.93	309.98	3.05	3.04	100	3.04	100	15	4	6	3	2	3	gypsum on fractures
204	309.98	313.03	3.05	3.01	99	3.01	99	15	4	6	4	1	3	gypsum on fractures
204	313.03	316.08	3.05	3.07	101	3.07	101	15	4	6	2	1	3	gypsum on fractures
204	316.08	319.13	3.05	3.08	101	3.08	101	15	4	6	4	1	3	gypsum on fractures
204	319.13	322.17	3.04	3.09	102	3.09	102	15	5	6	2	1	2	gypsum on fractures
204	322.17	325.22	3.05	2.99	98	2.99	98	14	5	6	5	2	2	gypsum on fractures
204	325.22	328.27	3.05	3.03	99	3.03	99	15	5	6	4	1	2	gypsum on fractures
204	328.27	331.32	3.05	3.11	102	3.11	102	15	5	6	2	1	2	gypsum on fractures
204	331.32	334.37	3.05	2.95	97	2.95	97	15	5	6	2	1	2	gypsum on fractures
205	3.66	5.79	2.13	1.04	49	0.55	26	5	3	4	24	2	2	20 cm H=0, W=1, weathered material
205	5.79	8.84	3.05	1.05	34	0.37	12	6	3	4	15	2	3	weathered material

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
205	8.84	10.36	1.52	1.68	111	0.32	21	6	3	4	34	2	2 gouge and clay, weathered material
205	10.36	11.89	1.53	1.31	86	0.92	60	10	4	5	11	1	2 weathered material
205	11.89	14.94	3.05	2.64	87	2.64	87	15	5	5	3	1	2 manual breaks
205	14.94	17.37	2.43	2.09	86	2.09	86	15	5	5	3	3	3 manual breaks
205	17.37	20.42	3.05	1.91	63	0.99	32	7	4	5	27	1	2 clay and rubble, and minor gouge
205	20.42	23.47	3.05	2.32	76	0.68	22	8	4	5	28	1	2 clay and rubble, and minor gouge
205	23.47	26.52	3.05	0.90	30	0.43	14	6	4	5	18	1	1 clay and rubble, and minor gouge
205	26.52	29.57	3.05	2.00	66	1.36	45	12	4	5	16	1	2 clay and rubble, and minor gouge
205	29.57	32.61	3.04	2.28	75	1.48	49	13	4	5	12	1	2 clay and rubble, and minor gouge
205	32.61	35.66	3.05	2.19	72	1.38	45	10	4	5	22	1	2 clay and rubble, and minor gouge
205	35.66	38.71	3.05	2.13	70	1.38	45	10	4	5	19	1	1 clay and rubble, and minor gouge
205	38.71	41.76	3.05	2.82	92	2.22	73	13	4	5	11	1	2 clay and rubble, and minor gouge
205	41.76	44.81	3.05	2.15	70	1.16	38	13	4	5	10	1	2 clay and rubble, and minor gouge
205	44.81	47.85	3.04	2.45	81	1.67	55	12	4	5	18	1	2 clay and rubble, and minor gouge
205	47.85	50.90	3.05	2.57	84	2.21	72	14	4	6	5	1	2 clay and rubble, and minor gouge
205	50.90	53.95	3.05	2.44	80	1.78	58	12	4	5	18	1	1 clay and rubble, and minor gouge
205	53.95	57.00	3.05	2.70	89	2.37	78	13	4	5	13	1	2 clay and rubble, and minor gouge
205	57.00	60.05	3.05	2.98	98	2.98	98	15	5	6	3	1	2 clay and rubble, and minor gouge
205	60.05	63.09	3.04	2.87	94	2.51	83	13	5	5	12	1	2 massive chalcopyrite vein
205	63.09	66.14	3.05	2.09	69	1.78	58	11	4	5	16	1	1 40 cm H=1, clay and rubble present
205	66.14	69.19	3.05	2.64	87	2.14	70	13	4	5	13	1	2 50 cm H=2, clay and rubble present
205	69.19	72.24	3.05	2.31	76	2.87	94	9	4	5	25	1	2 40 cm H=1, clay and rubble present
205	72.24	75.29	3.05	2.90	95	2.90	95	15	4	6	2	1	2
205	75.29	78.33	3.04	3.10	102	3.04	100	15	4	6	2	3	3
205	78.33	81.38	3.05	2.96	97	2.96	97	15	4	6	2	1	2
205	81.38	84.43	3.05	3.10	102	2.85	93	14	4	6	6	1	1 28 cm of H=0,1
205	84.43	87.48	3.05	3.00	98	2.01	66	13	4	6	13	1	2 minor rubble and gouge
205	87.48	90.53	3.05	3.06	100	2.91	95	14	4	6	6	1	2
205	90.53	93.57	3.04	3.12	103	2.87	94	14	4	6	6	1	2
205	93.57	96.62	3.05	2.95	97	2.85	93	15	4	6	3	3	3
205	96.62	99.67	3.05	3.05	100	3.05	100	15	4	6			
205	99.67	102.72	3.05	3.08	101	2.94	96	15	4	6	3	1	2
205	102.72	105.77	3.05	3.05	100	3.05	100	15	4	6	5	1	2
205	105.77	108.81	3.04	3.11	102	3.08	101	15	5	6	3	1	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
205	108.81	111.86	3.05	3.11	102	2.75	90	14	4	6	7	1	2	
205	111.86	114.91	3.05	3.10	102	1.93	63	15	4	6	18	1	2	2 manual breaks
205	114.91	117.96	3.05	2.82	92	2.01	66	13	4	6	11	1	2	
205	117.96	120.70	2.74	2.26	82	2.10	77	14	4	6	4	1	1	
205	120.70	123.44	2.74	2.84	104	2.60	95	15	4	6	3	1	2	
205	123.44	124.97	1.53	1.45	95	0.86	56	7	4	6	23	1	1	1 32 cm of H=1, well weathered
205	124.97	127.10	2.13	1.95	92	1.95	92	15	5	6	5	1	1	1 very slick contact at 4o to c.a.
205	127.10	130.15	3.05	3.07	101	3.07	101	15	5	6				
205	130.15	132.28	2.13	2.34	110	2.28	107	15	5	6				
205	132.28	135.33	3.05	3.10	102	3.10	102	15	5	6	2	1	2	
205	135.33	136.25	0.92	0.78	85	0.78	85	15	5	6				
205	136.25	139.29	3.04	3.05	100	3.05	100	15	5	6	1	1	2	
205	139.29	142.34	3.05	3.00	98	3.00	98	15	5	6	2	1	2	
205	142.34	145.39	3.05	3.13	103	3.08	101	15	5	6	3	3	3	
205	145.39	148.44	3.05	3.03	99	2.95	97	15	4	6	2	1	2	
205	148.44	151.49	3.05	3.10	102	3.00	98	15	5	6	3	1	2	
205	151.49	154.53	3.04	3.13	103	3.06	101	15	5	6	2	4	1	1 sheeted gypsum fracture
205	154.53	157.58	3.05	2.90	95	2.85	93	15	5	6	2	2	3	
205	157.58	160.63	3.05	3.10	102	3.10	102	15	5	6				
205	160.63	163.68	3.05	3.03	99	2.83	93	15	5	6	3	3	3	
205	163.68	166.73	3.05	3.18	104	2.89	95	15	5	6	5	3	3	
205	166.73	169.77	3.04	2.93	96	2.79	92	10	4	5	17	1	1	1 very slick, partly healed fault
205	169.77	172.82	3.05	3.07	101	2.80	92	14	4	6	9	1	1	1 very slick, partly healed fault
205	172.82	175.87	3.05	3.14	103	2.36	77	10	4	6	28	1	1	1 very slick, partly healed fault
205	175.87	178.92	3.05	3.03	99	2.89	95	14	4	6	10	1	1	1 very slick, partly healed fault
205	178.92	181.97	3.05	3.01	99	3.01	99	15	4	6	5	1	1	1 very slick, partly healed fault
205	181.97	185.01	3.04	3.04	100	3.04	100	15	4	6				
205	185.01	188.06	3.05	3.05	100	3.05	100	15	4	6	2	3	2	
205	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	2	3	2	
205	191.11	194.16	3.05	3.05	100	2.73	90	15	4	6	4	3	2	
205	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6				
205	197.21	200.25	3.04	3.04	100	3.04	100	15	4	6	1	1	2	
205	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	4	1	1	
205	203.30	206.35	3.05	3.15	103	3.15	103	15	4	6	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
205	206.35	209.40	3.05	2.95	97	2.86	94	15	3	5	3	1	3	
205	209.40	212.45	3.05	3.05	100	2.83	93	14	3	5	7	3	1	
205	212.45	215.49	3.04	3.04	100	3.00	99	15	3	5	3	1	2	
205	215.49	218.54	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
205	218.54	221.59	3.05	3.05	100	3.05	100	15	3	5	2	3	2	
205	221.59	224.64	3.05	3.10	102	3.10	102	15	4	6				
205	224.64	227.69	3.05	3.00	98	3.00	98	15	4	6	2	3	2	
205	227.69	230.73	3.04	3.04	100	3.04	100	15	4	6				
205	230.73	233.78	3.05	3.05	100	3.05	100	15	3	5	3	1	3	
206	4.57	5.81	1.24	0.57	46	0.00	0	3	3	4	25	5	3	3 broken rock with minor gouge
206	5.81	8.23	2.42	2.36	98	0.00	0	7	3	5	25	2	3	3 broken rock with minor gouge
206	8.23	11.28	3.05	1.71	56	0.12	4	6	3	5	50	5	3	3 broken rock with minor gouge
206	11.28	14.33	3.05	2.92	96	0.90	30	7	3	5	40	2	3	3 broken rock with minor gouge
206	14.33	17.37	3.04	3.29	108	3.18	105	15	3	6	2	1	3	
206	17.37	20.42	3.05	3.11	102	2.75	90	14	3	6	6	1	3	3 7 cm mud, gouge on fractures
206	20.42	23.47	3.05	3.03	99	2.97	97	15	3	6	4	1	3	
206	23.47	26.52	3.05	3.13	103	3.13	103	15	3	6	2	1	3	
206	26.52	29.57	3.05	3.05	100	2.87	94	15	3	6	4	1	3	3 gouge on fractures
206	29.57	32.61	3.04	2.83	93	2.79	92	12	3	6	15	2	3	3 5% broken core, 11 cm gouge at 10 to c.a.
206	32.61	35.66	3.05	3.25	107	3.08	101	15	3	6	4	1	3	3 5 cm fault at 15 to c.a.
206	35.66	38.71	3.05	3.06	100	3.06	100	15	3	6	2	1	3	
206	38.71	41.76	3.05	3.08	101	3.08	101	15	3	6	2	1	3	3 gouge on fractures
206	41.76	44.81	3.05	3.09	101	3.09	101	15	3	6	1	1	2	
206	44.81	47.85	3.04	2.99	98	2.99	98	15	3	6	2	1	3	3 gouge on fractures
206	47.85	50.90	3.05	3.16	104	3.16	104	15	3	6	1	1	2	
206	50.90	53.95	3.05	3.14	103	3.14	103	15	3	6	1	1	3	3 gouge on fractures
206	53.95	57.00	3.05	3.05	100	3.00	98	15	3	6	2	1	3	3 3 cm gouge at 35 to c.a.
206	57.00	60.05	3.05	3.11	102	2.44	80	14	3	6	7	2	3	3 gouge on fractures
206	60.05	63.09	3.04	3.12	103	3.12	103	15	3	6	2	1	3	
206	63.09	66.14	3.05	2.99	98	2.99	98	15	3	6	1	1	3	3 gouge on fractures
206	66.14	69.19	3.05	3.04	100	2.55	84	15	3	6	5	2	3	3 43 cm fault at 25 to c.a.
206	69.19	72.24	3.05	2.90	95	2.79	91	15	3	6	2	2	3	3 2 cm fault at 10 to c.a.
206	72.24	75.29	3.05	3.05	100	2.59	85	15	3	6	5	3	3	3 10 cm fault 10 to c.a., 2 cm fault 12 to c.a.
206	75.29	78.33	3.04	3.07	101	2.75	90	15	3	6	5	1	3	3 6 cm gouge 32 to c.a., 1 cm fault 12 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
206	78.33	81.38	3.05	3.05	100	3.00	98	15	3	6	3	2	3	gouge on fractures
206	81.38	84.43	3.05	3.05	100	3.05	100	15	3	6	4	2	3	
206	84.43	87.48	3.05	2.96	97	1.91	63	12	3	6	15	2	3	19 cm H=0,1, 30 to c.a. 5-10% broken
206	87.48	90.53	3.05	3.06	100	3.00	98	15	3	6	5	5	3	5 cm fault 5 to c.a., 7 cm H=0,1 @ 30 to c.a.
206	90.53	93.57	3.04	2.99	98	2.72	89	15	4	6	4	3	3	2 cm gouge H=0 at 70 to c.a.
206	93.57	96.62	3.05	3.03	99	3.03	99	15	4	6	2	1	3	
206	96.62	99.67	3.05	3.02	99	3.02	99	15	5	6	2	2	3	
206	99.67	102.72	3.05	2.97	97	2.87	94	15	5	6	4	1	2	
206	102.72	105.77	3.05	3.09	101	3.09	101	15	3	6	1	1	3	
206	105.77	108.81	3.04	3.07	101	3.07	101	15	3	6	4	1	2	
206	108.81	111.86	3.05	3.10	102	3.00	98	15	3	6	3	1	3	gouge on Fractures
206	111.86	114.91	3.05	3.10	102	3.10	102	15	3	6	2	1	2	
206	114.91	117.96	3.05	2.94	96	2.94	96	15	3	6	2	1	3	gouge on fractures
206	117.96	121.01	3.05	2.99	98	2.90	95	15	4	6	4	2	3	gouge on fractures
206	121.01	124.05	3.04	3.14	103	3.03	100	15	4	6	2	1	2	
206	124.05	127.10	3.05	2.95	97	2.81	92	15	4	6	3	2	3	4 cm breccia H=3
206	127.10	130.15	3.05	2.94	96	2.94	96	15	4	6	2	1	3	gouge on fractures
206	130.15	133.20	3.05	3.07	101	3.00	98	15	4	6	3	1	3	gouge on fractures
206	133.20	136.25	3.05	3.11	102	3.07	101	15	4	6	3	2	3	minor gouge on fractures
206	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6	4	2	3	minor gouge on fractures
206	139.29	142.34	3.05	3.03	99	3.03	99	15	4	6	1	1	2	
206	142.34	145.39	3.05	3.05	100	3.05	100	15	5	6	2	1	2	
206	145.39	148.44	3.05	3.02	99	3.02	99	15	5	6	2	1	2	
206	148.44	151.49	3.05	3.25	107	2.91	95	14	4	6	7	1	3	minor gouge on fractures
206	151.49	154.53	3.04	3.10	102	2.89	95	14	4	6	8	1	2	3 cm gouge at 55 to Ca
206	154.53	157.58	3.05	2.97	97	2.97	97	15	4	6	2	2	3	
206	157.58	160.63	3.05	3.24	106	2.31	76	13	4	6	15	5	3	38 cm gouge, 5% broken core
206	160.63	163.73	3.10	3.23	104	3.23	104	15	4	6	2	2	2	
206	163.63	166.68	3.05	2.96	97	2.19	72	12	4	6	15	2	3	5% broken core
206	166.68	169.77	3.09	2.99	97	2.87	93	15	3	6	4	1	3	gouge on fractures
206	169.77	172.82	3.05	3.29	108	3.29	108	15	5	6	3	2	2	
206	172.82	175.87	3.05	3.00	98	3.00	98	15	4	6	2	2	3	
206	175.87	178.92	3.05	3.05	100	3.05	100	15	4	6	5	1	3	gouge on fractures
206	178.92	181.97	3.05	2.79	91	2.48	81	15	4	6	4	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
206	181.97	185.01	3.04	3.12	103	3.12	103	15	4	6	1	1	2	
206	185.01	188.06	3.05	3.14	103	2.92	96	14	4	6	6	2	2	
206	188.06	191.11	3.05	3.07	101	2.87	94	15	5	6	4	1	2	dyke
206	191.11	194.16	3.05	3.25	107	3.09	101	15	5	6	5	5	3	dyke
206	194.16	197.21	3.05	3.08	101	3.00	98	15	5	6	3	2	3	
206	197.21	200.25	3.04	2.96	97	2.96	97	15	4	6	2	1	2	
206	200.25	203.30	3.05	3.05	100	2.92	96	15	3	6	3	1	3	10 cm H=1.2 (fault at 5 to c.a.)
206	203.30	206.35	3.05	3.07	101	3.07	101	15	3	6	2	2	2	
206	206.35	209.40	3.05	3.05	100	2.92	96	14	3	6	7	1	3	11 cm gouge H=1,2 at 40 to c.a.
206	209.40	212.45	3.05	3.09	101	3.00	98	15	3	6	2	1	2	gouge on fractures
206	212.45	215.49	3.04	3.07	101	3.07	101	15	3	6	1	1	3	
206	215.49	218.54	3.05	3.03	99	3.03	99	15	3	6	3	1	3	gouge on fractures
206	218.54	221.59	3.05	3.14	103	3.04	100	15	3	6	4	5	3	
206	221.59	224.64	3.05	3.05	100	2.89	95	15	4	6	3	2	2	
206	224.64	227.69	3.05	2.86	94	2.43	80	14	4	6	9	5	3	5% broken core with minor gouge
206	227.69	230.73	3.04	3.03	100	2.97	98	15	3	6	4	1	3	gouge on fractures
206	230.73	233.78	3.05	3.31	109	3.17	104	15	3	6	5	1	3	
206	233.78	236.83	3.05	3.12	102	3.01	99	15	3	6	4	2	3	
206	236.83	239.88	3.05	3.08	101	3.08	101	15	3	6	3	1	2	
206	239.88	242.93	3.05	2.96	97	2.96	97	15	3	6	2	1	3	
206	242.93	245.97	3.04	3.02	99	3.02	99	15	3	6	4	1	3	gouge on fractures (60 to c.a.)
206	245.97	249.02	3.05	2.99	98	2.94	96	15	3	6	3	1	3	
206	249.02	252.07	3.05	3.02	99	2.91	95	15	3	6	3	2	3	
206	252.07	255.12	3.05	3.05	100	3.05	100	15	3	6	1	1	2	
206	255.12	258.17	3.05	3.05	100	3.05	100	15	3	6	2	1	2	
206	258.17	261.21	3.04	3.03	100	3.03	100	15	4	6	2	1	3	minor gouge on fractures
206	261.21	264.26	3.05	2.95	97	2.88	94	15	4	6	4	2	3	2 cm H= 1.2 minor gouge on fractures
206	264.26	267.31	3.05	3.07	101	3.07	101	15	4	6	3	1	3	25 cm shear (fault) at LC 35 UC 55
206	267.31	270.36	3.05	3.00	98	3.00	98	15	3	6	4	1	3	gouge on fractures
206	270.36	273.41	3.05	3.05	100	3.05	100	15	5	6	1	1	2	
206	273.41	276.45	3.04	3.14	103	3.14	103	15	5	6	2	1	2	pyrite on fractures
206	276.45	279.50	3.05	3.00	98	3.00	98	15	4	6	3	1	3	minor shear 30 to c.a., gouge on fractures
206	279.50	282.55	3.05	3.09	101	2.92	96	15	3	6	4	1	3	gouge on fractures
206	282.55	285.60	3.05	2.96	97	2.90	95	15	3	6	3	2	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
206	285.60	288.65	3.05	3.07	101	2.89	95	15	3	6	5	1	3	gouge on fractures
206	288.65	291.69	3.04	3.13	103	3.13	103	15	4	6	2	1	2	
206	291.69	294.74	3.05	2.95	97	2.84	93	15	4	6	3	5	3	50 cm shear (fault) LC 35, UC 35
206	294.74	297.79	3.05	3.08	101	2.61	86	14	3	6	10	5	3	sheared, 4 cm fault at 20 to c.a.
206	297.79	300.84	3.05	3.09	101	2.80	92	14	3	6	6	5	3	sheared, 15 cm fault at 12 to c.a.
206	300.84	303.89	3.05	3.00	98	3.00	98	15	3	6	2	2	3	
206	303.89	306.93	3.04	3.07	101	3.07	101	15	3	6	3	1	2	
206	306.93	309.98	3.05	3.05	100	3.05	100	15	3	6	2	1	3	gouge on fractures
206	309.98	313.03	3.05	2.96	97	2.81	92	15	4	6	3	2	3	
206	313.03	316.08	3.05	3.05	100	3.05	100	15	3	6	2	1	3	
206	316.08	319.13	3.05	2.88	94	2.84	93	15	3	6	3	1	3	gouge on fractures
206	319.13	322.17	3.04	3.00	99	2.55	84	14	4	6	10	1	2	5% broken core
206	322.17	325.22	3.05	3.32	109	2.30	75	13	4	6	15	1	3	5-10% broken core
206	325.22	328.27	3.05	2.97	97	2.97	97	15	4	6	1	1	2	
206	328.27	331.32	3.05	3.00	98	3.00	98	15	4	6	1	1	2	
206	331.32	334.37	3.05	3.07	101	3.07	101	15	4	6	2	1	3	minor gouge on fractures
206	334.37	337.41	3.04	3.12	103	3.01	99	15	4	6	4	1	3	2 cm H=0,1 (gouge)
206	337.41	340.46	3.05	2.99	98	2.84	93	15	4	6	2	1	3	4 cm H=0,1 (gouge)
206	340.46	343.51	3.05	3.05	100	3.05	100	15	4	6	2	2	3	gouge on fractures
206	343.51	346.56	3.05	3.01	99	3.01	99	15	3	6	2	1	2	
206	346.56	349.61	3.05	3.00	98	2.75	90	15	4	6	4	2	3	
206	349.61	352.65	3.04	3.18	105	3.00	99	15	4	6	5	2	2	
206	352.65	355.70	3.05	2.90	95	2.79	91	15	4	6	3	1	3	minor gouge on fractures
206	355.70	358.75	3.05	2.98	98	2.98	98	15	4	6	4	1	3	
206	358.75	361.80	3.05	3.05	100	2.98	98	15	4	6	4	2	3	11 cm fault gouge at 25 to c.a.
206	361.80	364.85	3.05	3.17	104	3.02	99	15	3	6	3	2	3	
206	364.85	367.89	3.04	3.12	103	2.98	98	15	3	6	3	2	3	
206	367.89	370.94	3.05	3.05	100	2.94	96	15	3	6	5	2	3	2 cm gouge at 25 to c.a.
206	370.94	373.99	3.05	3.00	98	3.00	98	15	3	6	2	1	3	gouge on fractures
206	373.99	377.04	3.05	3.10	102	3.10	102	15	3	6	2	1	3	gouge on fractures
206	377.04	380.09	3.05	3.06	100	2.86	94	15	3	6	5	2	3	
206	380.09	383.13	3.04	3.04	100	3.04	100	15	3	6	4	1	3	
206	383.13	386.18	3.05	3.11	102	3.11	102	15	3	6	4	2	3	gouge on fractures
206	386.18	389.23	3.05	2.99	98	2.99	98	15	4	6	3	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
206	389.23	392.28	3.05	3.10	102	3.10	102	15	4	6	2	2	3 gouge on fractures
206	392.28	395.33	3.05	3.02	99	3.02	99	15	4	6	2	1	2
206	395.33	398.37	3.04	2.99	98	2.99	98	15	5	6	2	1	3 gouge on fractures
206	398.37	401.42	3.05	3.00	98	3.00	98	15	5	6	4	1	2 gypsum on fractures
207	6.10	8.53	2.43	0.21	9	0.00	0	3	3	4	20	5	3 broken core with minor iron staining
207	8.53	10.36	1.83	0.71	39	0.00	0	2	3	5	30	5	3 broken core with gouge
207	10.36	11.58	1.22	1.31	107	0.00	0	3	3	5	50	5	3 broken core with gouge
207	11.58	12.80	1.22	0.59	48	0.00	0	3	3	5	15	5	3 broken core with gouge
207	12.80	14.94	2.14	0.51	24	0.00	0	2	3	4	25	5	3 broken core with gouge
207	14.94	16.76	1.82	0.07	4	0.00	0	1	1	4	10	5	3 100% gouge
207	16.76	17.98	1.22	0.76	62	0.00	0	1	1	4	25	5	3 90% gouge
207	17.98	20.12	2.14	0.65	30	0.00	0	2	3	4	25	5	3 broken core with gouge
207	20.12	21.34	1.22	1.27	104	0.24	20	2	3	4	25	5	3 broken core with gouge
207	21.34	22.56	1.22	0.91	75	0.11	9	2	3	4	25	5	3 broken core with gouge
207	22.56	24.08	1.52	1.05	69	0.37	24	2	3	4	25	5	3 broken core with gouge
207	24.08	26.52	2.44	1.05	43	0.00	0	2	3	4	25	5	3 broken core with gouge
207	26.52	28.04	1.52	0.75	49	0.00	0	3	3	4	25	5	3 broken core with gouge
207	28.04	28.96	0.92	1.14	124	0.00	0	3	3	5	25	5	3 broken core with gouge
207	28.96	30.18	1.22	0.33	27	0.00	0	3	3	5	15	2	3 broken core with gouge
207	30.18	31.39	1.21	0.94	78	0.39	32	7	3	5	10	2	3 broken core with gouge
207	31.39	32.31	0.92	0.74	80	0.00	0	5	3	5	25	5	3 broken core with gouge
207	32.31	33.22	0.91	0.79	87	0.15	16	6	3	5	25	5	3 broken core with gouge
207	33.22	34.44	1.22	0.57	47	0.00	0	6	3	5	25	5	3 broken core with gouge
207	34.44	35.66	1.22	1.21	99	0.00	0	1	1	4	25	5	3 90% gouge
207	35.66	38.71	3.05	0.22	7	0.00	0	3	3	5	25	5	3 broken core with gouge
207	38.71	39.62	0.91	0.36	40	0.00	0	2	2	4	25	5	3 broken core with gouge
207	39.62	41.76	2.14	0.71	33	0.00	0	6	3	5	25	5	3 broken core
207	41.76	43.59	1.83	0.95	52	0.00	0	3	3	4	25	5	3 broken core with gouge
207	43.59	46.33	2.74	0.21	8	0.00	0	3	3	4	25	5	3 broken core with gouge
207	46.33	47.85	1.52	0.56	37	0.00	0	2	3	4	25	5	3 strongly broken core with gouge
207	47.85	50.90	3.05	0.92	30	0.00	0	3	3	4	30	5	3 strongly broken core with gouge
207	50.90	53.95	3.05	0.19	6	0.00	0	5	4	4	30	5	3 strongly broken core with gouge
207	53.95	57.00	3.05	0.18	6	0.00	0	5	4	4	30	5	3 strongly broken core with gouge
207	57.00	60.05	3.05	0.30	10	0.00	0	5	4	4	30	5	3 strongly broken core with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
207	60.05	63.09	3.04	0.61	20	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	63.09	66.14	3.05	0.17	6	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	66.14	69.19	3.05	0.82	27	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	69.19	72.24	3.05	0.77	25	0.00	0	6	4	4	30	5	3 strongly broken core with gouge	
207	72.24	75.29	3.05	0.62	20	0.00	0	6	4	4	30	5	3 strongly broken core with gouge	
207	75.29	78.33	3.04	0.46	15	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	78.33	81.38	3.05	0.09	3	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	81.38	84.43	3.05	0.14	5	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	84.43	87.48	3.05	0.32	10	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	87.48	90.53	3.05	0.29	10	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	90.53	93.57	3.04	0.36	12	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	93.57	96.62	3.05	0.17	6	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	96.62	99.67	3.05	2.15	70	0.00	0	5	4	4	30	5	3 strongly broken core with gouge	
207	99.67	102.72	3.05	2.17	71	1.66	54	8	4	4	20	2	2 1st 30 cm is strongly broken	
207	102.72	105.77	3.05	2.96	97	2.96	97	15	4	6	3	1	1	
207	105.77	108.81	3.04	3.04	100	3.04	100	15	4	6	2	1	1	
207	108.81	111.86	3.05	3.01	99	3.01	99	15	4	6	1	1	1 breaks on gypsum veins	
207	111.86	114.91	3.05	2.99	98	2.88	94	15	4	6	4	1	1 breaks on gypsum veins	
207	114.91	117.96	3.05	3.14	103	3.08	101	15	4	6	4	1	1 breaks on gypsum veins	
207	117.96	121.01	3.05	2.88	94	2.72	89	13	4	6	12	1	1	
207	121.01	124.05	3.04	1.67	55	0.84	28	6	4	6	25	2	2 60% strongly broken angular core	
207	124.05	125.27	1.22	0.31	25	0.00	0	6	4	6	30	2	2 100% strongly broken angular core	
207	125.27	126.80	1.53	1.13	74	0.66	43	6	4	6	25	2	2 60% strongly broken angular core	
207	126.80	129.84	3.04	3.06	101	3.06	101	15	4	6	4	1	1	
207	129.84	132.89	3.05	3.05	100	3.05	100	15	4	6	3	2	1	
207	132.89	135.64	2.75	2.75	100	2.64	96	15	4	6	4	2	1	
207	135.64	137.46	1.82	1.90	104	1.90	104	15	4	6	1	1	1	
207	137.46	139.29	1.83	1.81	99	1.81	99	15	4	6	3	1	1	
207	139.29	142.34	3.05	3.00	98	2.95	97	15	4	6	2	1	1	
207	142.34	145.39	3.05	3.00	98	2.93	96	15	4	6	4	3	1 undulating shear zone 20 to c.a. , gouge	
207	145.39	148.44	3.05	3.02	99	3.02	99	15	4	6	2	2	2	
207	148.44	151.49	3.05	3.00	98	3.00	98	15	4	6	2	2	2 trace gouge on break	
207	151.49	154.53	3.04	2.64	87	2.44	80	15	4	6	8	2	2 5 cm & 15 cm broken subangular core	
207	154.53	157.58	3.05	0.77	25	0.21	7	7	4	6	30	2	2 gouge in broken core	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
207	157.58	159.41	1.83	0.93	51	0.61	33	7	4	6	30	2	2 3 cm gouge in shear zone at 30 to c.a.	
207	159.41	161.24	1.83	0.33	18	0.00	0	7	4	6	30	2	2 100% strongly broken angular core	
207	161.24	161.85	0.61	0.29	48	0.00	0	7	4	6	30	2	2 100% strongly broken angular core	
207	161.85	163.68	1.83	1.83	100	1.63	89	13	4	6	8	1	1	
207	163.68	165.81	2.13	1.80	85	1.41	66	13	4	6	13	2	2 gouge in broken core	
207	165.81	168.25	2.44	2.07	85	1.77	73	13	5	6	13	2	2 dyke starts at 166.27m	
207	168.25	170.69	2.44	2.31	95	2.24	92	13	5	6	5	2	2	
207	170.69	172.82	2.13	2.20	103	2.03	95	13	5	6	5	2	2	
207	172.82	175.87	3.05	2.85	93	2.23	73	13	5	6	7	2	2	
207	175.87	178.00	2.13	2.25	106	2.25	106	15	5	6	0		no breaks in dyke	
207	178.00	181.05	3.05	3.14	103	3.14	103	15	5	6	3	1	1 dyke ends at 180.43m	
207	181.05	182.88	1.83	1.78	97	1.78	97	15	5	6	3	1	1 1.09m of dyke	
207	182.88	185.01	2.13	2.13	100	2.13	100	15	4	6	3	1	1 no gouge on slip	
207	185.01	188.06	3.05	2.94	96	2.94	96	15	4	6	3	2	2 1st 20 cm of shear zone at 50 to c.a.	
207	188.06	191.11	3.05	3.08	101	2.94	96	14	4	6	6	1	1 2nd 91 cm of shear zone at 50 to c.a.	
207	191.11	194.16	3.05	3.05	100	3.05	100	15	4	6	2	3	1 slip on undulating surface	
207	194.16	197.21	3.05	3.00	98	2.95	97	15	4	6	2	1	2 73 cm shear zone at 30 to c.a.	
207	197.21	200.25	3.04	3.01	99	3.01	99	15	4	6	2	1	1 72 cm shear zone at 40 to c.a.	
207	200.25	203.30	3.05	2.98	98	2.98	98	15	4	6	5	1	1	
207	203.30	206.35	3.05	3.01	99	3.01	99	15	4	6	4	2	2	
207	206.35	209.40	3.05	3.05	100	2.99	98	15	4	6	2	2	2	
207	209.40	212.45	3.05	2.92	96	2.92	96	15	4	6	3	1	1	
207	212.45	215.49	3.04	3.08	101	3.08	101	15	4	6	3	1	1	
207	215.49	218.54	3.05	2.96	97	2.96	97	15	4	6	3	2	2	
207	218.54	221.59	3.05	2.95	97	2.89	95	15	4	6	4	1	1 gouge on slip	
207	221.59	224.64	3.01	3.01	100	3.07	102	15	4	6	2	2	2	
207	224.64	227.69	3.05	2.96	97	2.85	93	14	4	6	6	2	2 trace gouge in broken core	
207	227.69	230.73	3.04	3.01	99	2.99	98	15	4	6	2	2	2	
207	230.73	233.78	3.05	3.03	99	3.03	99	15	4	6	1	2	2	
207	233.78	236.83	3.05	3.05	100	3.05	100	15	4	6	2	2	2 2 cm gypsum vein subparallel for 1.5m	
207	236.83	239.88	3.05	3.02	99	3.02	99	15	4	6	3	1	1	
207	239.88	242.93	3.05	3.00	98	2.93	96	15	4	6	5	1	1 2-3mm gouge on slip	
207	242.93	245.97	3.04	3.04	100	2.95	97	15	4	6	5	2	2 15cm broken core with no gouge	
207	245.97	249.02	3.05	2.98	98	2.98	98	15	4	6	2	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
207	249.02	252.07	3.05	3.07	101	3.07	101	15	4	6	3	1	1	
207	252.07	255.12	3.05	3.01	99	2.97	97	15	4	6	4	1	1	
207	255.12	258.17	3.05	3.13	103	3.13	103	15	4	6	2	2	2	
207	258.17	261.21	3.04	2.89	95	2.89	95	15	5	6	2	1	1	5 cm broken core at end of run
207	261.21	264.26	3.05	3.07	101	3.07	101	15	5	6	3	1	1	
207	264.26	267.31	3.05	2.98	98	2.98	98	15	5	6	3	1	1	1 breaks on veins
207	267.31	270.36	3.05	3.00	98	2.93	96	15	5	6	6	1	1	1 breaks on veins
207	270.36	273.41	3.05	3.07	101	3.07	101	15	5	6	4	1	1	1 breaks on veins
207	273.41	276.45	3.04	3.04	100	3.00	99	15	5	6	3	1	1	1 breaks on veins
207	276.45	279.50	3.05	3.05	100	3.05	100	15	5	6	4	1	1	1 breaks on veins
207	279.50	282.55	3.05	2.95	97	2.95	97	15	5	6	3	1	1	1 breaks on veins
207	282.55	285.60	3.05	3.03	99	2.96	97	14	5	6	8	1	1	1 breaks on veins
207	285.60	288.65	3.05	3.05	100	2.85	93	14	5	6	7	1	1	1 breaks on veins
207	288.65	291.69	3.04	3.04	100	3.04	100	15	5	6	3	1	1	1 breaks on veins
207	291.69	294.74	3.05	3.05	100	3.05	100	15	5	6	4	1	1	1 trace gouge on slip
208	6.10	8.23	2.13	1.72	81	0.94	44	9	4	4	21	1	3	3 iron stained fractures
208	8.23	11.28	3.05	1.81	59	1.10	36	7	5	4	25	1	3	3 iron stained fractures, 10% gouge, H=1
208	11.28	14.33	3.05	1.29	42	0.90	30	9	5	5	15	1	3	3 10% gouge, H=1
208	14.33	17.37	3.04	2.36	78	1.98	65	10	5	5	17	1	3	3 10% broken rock
208	17.37	20.42	3.05	3.12	102	2.97	97	14	5	5	9	2	3	3 gouge on fractures
208	20.42	23.47	3.05	2.18	71	1.30	43	7	5	4	35	2	3	3 35% broken with minor gouge, H=2
208	23.47	26.52	3.05	2.68	88	1.95	64	9	5	4	27	2	3	3 iron stained fractures, 10% gouge
208	26.52	29.57	3.05	1.95	64	0.54	18	6	6	4	50	2	3	3 iron stained fractures, 90% broken
208	29.57	32.61	3.04	1.75	58	0.32	11	6	6	4	50	2	3	3 100% broken rock
208	32.61	35.66	3.05	2.00	66	0.63	21	6	6	4	40	2	3	3 80% broken rock, minor gouge
208	35.66	38.71	3.05	2.40	79	0.83	27	7	6	5	45	1	3	3 10% gouge H=1, 60% broken rock
208	38.71	41.76	3.05	2.96	97	1.70	56	9	6	5	30	2	3	3 30% broken rock, pyrite on fractures
208	41.76	44.81	3.05	2.29	75	1.64	54	9	6	5	25	1	3	3 20% broken rock
208	44.81	47.85	3.04	3.02	99	2.81	92	12	5	5	17	2	3	3 gouge on fractures
208	47.85	50.90	3.05	2.98	98	1.63	53	13	5	5	14	2	3	3 10% broken rock
208	50.90	53.95	3.05	3.05	100	2.83	93	14	5	5	10	1	3	3 minor gouge on fractures
208	53.95	57.00	3.05	3.12	102	2.89	95	13	5	5	11	2	3	3 gypsum on fractures
208	57.00	60.05	3.05	3.05	100	2.40	79	12	6	5	18	1	3	3 gypsum on fractures
208	60.05	63.09	3.04	2.57	85	1.98	65	12	5	5	17	1	3	3 gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
208	63.09	66.14	3.05	3.05	100	1.76	58	13	5	5	12	1	3 gypsum on fractures, minor gouge	
208	66.14	69.19	3.05	2.80	92	1.60	52	13	5	5	13	1	3 gypsum on fractures, minor gouge	
208	69.19	72.24	3.05	2.70	89	2.34	77	10	5	5	19	1	3 gypsum on fractures	
208	72.24	75.29	3.05	2.72	89	2.30	75	12	5	5	15	1	3 gypsum on fractures	
208	75.29	78.33	3.04	3.07	101	3.00	99	15	5	6	5	1	3 gypsum on fractures	
208	78.33	81.38	3.05	3.12	102	3.12	102	15	5	6	3	1	3 gypsum on fractures	
208	81.38	84.43	3.05	3.05	100	3.05	100	15	5	6	2	1	2 gypsum on fractures	
208	84.43	87.48	3.05	3.05	100	3.05	100	15	5	6	3	1	2 gypsum on fractures	
208	87.48	90.53	3.05	3.01	99	3.01	99	15	5	6	1	2	3 gypsum on fractures	
208	90.53	93.57	3.04	3.04	100	3.04	100	15	5	6	2	2	3 gypsum on fractures	
208	93.57	96.62	3.05	2.93	96	2.93	96	15	5	6	4	1	2 gypsum on fractures	
208	96.62	99.67	3.05	3.03	99	3.03	99	15	5	6	3	1	2 gypsum on fractures	
208	99.67	102.72	3.05	3.08	101	3.08	101	15	5	6	2	2	3 gypsum on fractures	
208	102.72	105.77	3.05	2.99	98	2.99	98	15	5	6	1	1	3 gypsum on fractures	
208	105.77	108.81	3.04	3.04	100	2.86	94	14	5	6	8	2	3 minor gouge on fractures	
208	108.81	110.64	1.83	1.62	89	1.08	59	10	5	6	14	2	3 minor gouge on fractures	
208	110.64	112.78	2.14	2.27	106	2.27	106	15	5	6	2	2	3 gypsum on fractures	
208	112.78	114.91	2.13	2.23	105	2.23	105	14	5	6	4	2	3 gypsum on fractures	
208	114.91	116.43	1.52	1.21	80	0.65	43	10	5	6	10	2	3 minor gouge on fractures	
208	116.43	118.87	2.44	2.50	102	2.32	95	14	5	6	7	1	2 gypsum on fractures	
208	118.87	121.01	2.14	2.11	99	2.11	99	15	5	6	1	1	2 gypsum on fractures	
208	121.01	124.05	3.04	3.03	100	2.98	98	14	5	6	6	2	3 gouge on fractures	
208	124.05	127.10	3.05	2.96	97	2.96	97	15	5	6	1	2	3 gypsum on fractures	
208	127.10	130.15	3.05	3.05	100	3.00	98	14	5	6	6	2	3	
208	130.15	133.20	3.05	3.05	100	2.85	93	15	5	6	4	2	3	
208	133.20	136.25	3.05	3.00	98	3.00	98	15	5	6	4	2	3 gy on fractures with weak slickensides	
208	136.25	139.29	3.04	3.00	99	2.75	90	14	5	6	9	2	3 minor gouge on fractures	
208	139.29	142.34	3.05	3.05	100	2.75	90	14	5	6	8	2	3 minor gouge on fractures	
208	142.34	145.39	3.05	2.94	96	2.88	94	15	5	6	3	2	3 minor gouge on fractures	
208	145.39	148.44	3.05	3.01	99	3.01	99	15	5	6	3	1	3 gypsum on fractures	
208	148.44	151.49	3.05	3.00	98	3.00	98	15	5	6	3	1	3 gypsum on fractures	
208	151.49	154.53	3.04	3.09	102	3.09	102	15	5	6	3	1	3 gouge on fractures	
208	154.53	157.58	3.05	3.02	99	3.02	99	15	5	6	2	1	2	
208	157.58	160.63	3.05	3.05	100	3.05	100	15	5	6	2	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
208	160.63	163.68	3.05	3.05	100	3.05	100	15	5	6	2	1	2	2 gypsum on fractures
208	163.68	166.73	3.05	3.05	100	3.05	100	15	5	6	2	2	2	2 gypsum on fractures
208	166.73	169.77	3.04	2.99	98	2.91	96	14	3	6	5	1	3	3 gouge on fractures
208	169.77	172.82	3.05	2.98	98	2.87	94	15	3	6	4	1	3	3 gypsum on fractures
208	172.82	175.87	3.05	3.01	99	2.95	97	15	4	6	3	1	3	3 gypsum on fractures
208	175.87	178.92	3.05	2.97	97	2.97	97	14	4	6	5	2	3	3 gypsum on fractures
208	178.92	181.97	3.05	3.06	100	3.06	100	15	4	6	3	1	3	3 gypsum on fractures
208	181.97	185.01	3.04	3.10	102	2.79	92	15	3	6	5	1	3	3 gouge + gypsum on fractures
208	185.01	188.06	3.05	3.06	100	3.06	100	15	4	6	2	1	3	3 gypsum on fractures
208	188.06	191.11	3.05	2.99	98	2.99	98	15	4	6	2	1	2	2
208	191.11	194.16	3.05	3.05	100	3.05	100	15	4	6	1	1	2	2
208	194.16	197.21	3.05	3.05	100	3.00	98	15	4	6	2	1	3	3 gypsum on fractures
208	197.21	200.25	3.04	3.04	100	3.04	100	15	4	6	4	1	3	3 gouge on fractures
208	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3 gypsum on fractures
208	203.30	206.35	3.05	3.02	99	2.93	96	15	4	6	4	1	3	3 gypsum on fractures
208	206.35	209.40	3.05	2.98	98	2.98	98	15	4	6	1	1	3	3 gypsum on fractures
209	6.10	7.92	1.82	1.10	60	0.44	24	7	3	2	15	1	3	3 broken core, iron stained
209	7.92	10.67	2.75	2.11	77	0.38	14	5	3	2	30	5	3	3 broken core, iron stained
209	10.67	13.41	2.74	2.83	103	1.88	69	7	3	3	20	1	3	3 15% broken core, iron stained
209	13.41	16.46	3.05	3.05	100	1.79	59	9	3	3	20	1	3	3 15% broken core, iron stained
209	16.46	19.51	3.05	3.93	129	1.99	65	9	3	3	20	1	3	3 15% broken core, iron stained
209	19.51	20.12	0.61	0.75	123	0.00	0	7	4	3	50	1	3	3 broken core, iron stained
209	20.12	21.03	0.91	0.79	87	0.22	24	6	4	3	15	5	3	3 broken core, iron stained
209	21.03	23.77	2.74	3.30	120	1.18	43	6	4	3	25	5	3	3 broken core with gouge, iron stained
209	23.77	25.91	2.14	2.14	100	1.15	54	9	3	3	20	5	3	3 15% broken core w/ gouge, iron stained
209	25.91	28.96	3.05	3.21	105	2.94	96	10	3	3	13	1	3	3
209	28.96	31.70	2.74	2.74	100	2.01	73	13	3	4	10	5	3	3 iron stained, gouge on fractures
209	31.70	34.75	3.05	3.11	102	2.04	67	10	3	5	25	5	3	3 10-15% broken core with gouge
209	34.75	38.71	3.96	2.93	74	2.23	56	13	3	6	10	1	3	3 gouge on fractures
209	38.71	41.45	2.74	2.71	99	2.64	96	15	3	6	3	1	2	2 gypsum on fractures
209	41.45	44.50	3.05	3.02	99	3.02	99	15	3	6	4	1	2	2
209	44.50	46.94	2.44	2.33	95	2.33	95	15	4	6	4	2	3	3 gouge on fractures
209	46.94	49.07	2.13	2.28	107	2.28	107	15	4	6	3	1	2	2
209	49.07	50.90	1.83	1.71	93	1.59	87	15	3	6	2	1	3	3 gouge on fractures, 12 cm gouge H=0,1

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
209	50.90	53.95	3.05	3.08	101	2.98	98	15	4	6	4	1	2	
209	53.95	57.00	3.05	3.00	98	2.90	95	15	4	6	5	5	3	
209	57.00	60.05	3.05	2.90	95	2.82	92	15	4	6	4	2	2	2 trace gouge
209	60.05	63.09	3.04	3.04	100	3.01	99	15	4	6	4	1	1	
209	63.09	66.14	3.05	3.08	101	3.08	101	15	4	6	3	1	1	1 slip @ low angle to c.a.
209	66.14	69.19	3.05	2.90	95	2.60	85	13	4	6	11	2	2	2 20% moderately broken angular core
209	69.19	72.24	3.05	3.00	98	3.00	98	15	4	6	2	2	2	
209	72.24	75.29	3.05	2.83	93	2.61	86	13	4	6	12	5	3	3 10% mod. broken ang core, trace gouge
209	75.29	78.33	3.04	3.04	100	2.83	93	14	4	6	9	5	3	3 strongly broken core @ end of run
209	78.33	81.38	3.05	2.89	95	2.67	88	14	4	6	9	2	2	2 two 10 cm sectns of strongly broken core
209	81.38	84.43	3.05	3.05	100	3.05	100	15	4	6	3	2	2	
209	84.43	87.48	3.05	3.00	98	3.00	98	15	4	6	3	2	2	
209	87.48	90.53	3.05	3.00	98	2.95	97	15	4	6	4	2	2	
209	90.53	93.57	3.04	3.06	101	3.06	101	15	4	6	1	4	2	
209	93.57	96.62	3.05	2.99	98	2.94	96	15	4	6	5	1	1	1 trace gouge on slip @ 40 deg.
209	96.62	99.67	3.05	2.95	97	2.87	94	15	4	6	5	2	2	
209	99.67	102.72	3.05	2.88	94	2.61	86	14	4	6	8	5	3	3 10% mod. broken angular core with gouge
209	102.72	105.77	3.05	3.00	98	3.00	98	15	4	6	3	1	1	
209	105.77	108.81	3.04	2.89	95	2.58	85	14	4	6	8	5	3	3 broken core with gouge
209	108.81	111.86	3.05	3.08	101	2.99	98	15	4	6	4	2	2	2 trace gouge on slip
209	111.86	114.91	3.05	2.96	97	2.56	84	14	4	6	8	5	3	3 40 cm moderately broken angular core
209	114.91	117.96	3.05	2.99	98	2.89	95	14	4	6	6	1	1	
209	117.96	121.01	3.05	2.95	97	2.95	97	15	4	6	4	1	1	1 trace gouge on slip
209	121.01	124.05	3.04	3.04	100	3.04	100	15	4	6	3	2	2	
209	124.05	127.10	3.05	3.08	101	3.08	101	15	4	6	3	1	1	
209	127.10	130.15	3.05	2.85	93	2.85	93	14	4	6	8	1	1	1 slip on gypsum vein
209	130.15	133.20	3.05	3.11	102	3.11	102	15	4	6	2	1	1	1 gouge on slip
209	133.20	136.25	3.05	3.01	99	3.01	99	15	4	6	3	1	1	
209	136.25	139.30	3.05	3.05	100	3.05	100	15	4	6	2	1	1	
209	139.30	142.34	3.04	3.04	100	3.04	100	15	3	6	2	2	2	2 70 cm carb-gy with sphalerite-galena
209	142.34	145.39	3.05	2.99	98	2.99	98	15	4	6	2	1	1	
209	145.39	148.44	3.05	3.00	98	3.00	98	15	4	6	2	5	3	
209	148.44	151.49	3.05	3.08	101	3.08	101	15	4	6	1	5	3	
209	151.49	154.53	3.04	3.04	100	3.04	100	15	4	6	1	1	1	1 70 cm of DMAF

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
209	154.53	157.58	3.05	3.02	99	3.00	98	15	4	6	4	1	1	1 trace gouge on slip @ 70 deg.
209	157.58	160.63	3.05	3.00	98	3.00	98	15	4	6	1	2	2	
209	160.63	163.68	3.05	2.87	94	2.85	93	15	4	6	2	2	2	
209	163.68	166.73	3.05	2.94	96	2.94	96	15	4	6	3	1	1	1 trace gouge on slip @ 30 deg.
209	166.73	169.77	3.04	2.84	93	2.84	93	15	4	6	3	1	1	1 trace gouge on slip @ 30 deg.
209	169.77	172.82	3.05	3.08	101	2.68	88	13	4	6	11	1	1	1 gouge on slips in broken core
209	172.82	175.87	3.05	2.77	91	2.59	85	14	4	6	7	1	1	1 5 cm sections strongly broken core
209	175.87	178.92	3.05	2.95	97	2.55	84	13	4	6	13	5	3	3 gouge in breaks
209	178.92	181.97	3.05	2.78	91	2.61	86	14	4	6	7	1	1	1 gouge in broken core
209	181.97	185.01	3.04	3.08	101	3.08	101	15	4	6	3	1	1	1 trace gouge
209	185.01	188.06	3.05	3.05	100	3.02	99	14	5	6	7	1	1	1 25% of run is DMAF
209	188.06	191.11	3.05	2.75	90	2.58	85	14	4	6	6	5	3	3 gouge in broken core
209	191.11	194.16	3.05	3.23	106	3.18	104	15	4	6	5	1	1	
209	194.16	197.21	3.05	2.23	73	1.93	63	14	4	6	7	1	1	1 1.5 m of DMAF
209	197.21	198.42	1.21	1.55	128	1.34	111	13	4	6	6	5	3	3 gouge in broken core
209	198.42	200.25	1.83	1.74	95	1.69	92	14	4	6	5	1	1	1 trace gouge
209	200.25	203.30	3.05	3.00	98	3.00	98	15	4	6	4	5	3	
209	203.30	206.35	3.05	3.05	100	3.05	100	15	4	6	4	1	1	
209	206.35	209.40	3.05	3.11	102	3.11	102	15	4	6	5	1	1	1 trace gouge on slips
209	209.40	212.45	3.05	2.99	98	2.99	98	15	4	6	4	1	1	
209	212.45	215.50	3.05	3.05	100	2.92	96	14	4	6	6	1	1	1 gouge on slips and in broken core
209	215.50	218.54	3.04	2.97	98	2.95	97	14	4	6	7	5	3	3 gouge in broken core
209	218.54	221.59	3.05	2.92	96	2.92	96	15	4	6	3	1	1	
209	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6	3	1	1	
209	224.64	227.69	3.05	3.02	99	2.76	90	15	4	6	6	5	3	3 gouge in broken core
209	227.69	230.73	3.04	2.78	91	2.61	86	14	4	6	6	5	3	3 gouge in broken core
209	230.73	233.17	2.44	2.42	99	2.25	92	14	4	6	7	5	3	3 gouge in broken core
209	233.17	235.92	2.75	2.40	87	2.27	83	13	4	6	11	5	3	3 gouge in broken core
209	235.92	238.66	2.74	3.08	112	3.08	112	15	4	6	3	1	1	
209	238.66	239.88	1.22	1.35	111	1.35	111	15	4	6	2	1	1	
209	239.88	242.93	3.05	2.92	96	2.92	96	14	4	6	4	5	3	3 gouge on slips
209	242.93	245.97	3.04	3.04	100	2.86	94	13	4	6	10	5	3	3 gouge in broken core
209	245.97	249.02	3.05	3.03	99	3.03	99	15	4	6	2	2	2	
209	249.02	252.07	3.05	2.96	97	2.96	97	14	4	6	6	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
209	252.07	255.12	3.05	3.03	99	3.03	99	15	4	6	3	1	1	1 gouge on slips
209	255.12	258.17	3.05	3.09	101	3.09	101	15	4	6	5	1	1	1 gouge on slips
209	258.17	261.21	3.04	3.00	99	3.00	99	15	4	6	3	5	3	
210	12.10	14.32	2.22	0.89	40	0.00	0	10	2	2	25	5	3	3 highly weathered, fe stained, broken core
210	14.32	17.37	3.05	0.19	6	0.00	0	7	2	2	10	5	3	3 highly weathered, iron stained
210	17.37	20.42	3.05	0.24	8	0.00	0	6	3	3	25	5	3	3 moderately weathered, broken core
210	20.42	23.47	3.05	0.55	18	0.00	0	6	3	3	30	5	3	3 broken core with 30% gouge
210	23.47	26.52	3.05	2.74	90	1.55	51	9	4	3	25	2	3	3 30% broken core
210	26.52	29.57	3.05	3.19	105	2.00	66	9	4	3	15	2	3	3 5% broken core, iron stained
210	29.57	32.61	3.04	3.02	99	3.02	99	15	4	6	2	1	2	2 gypsum on fractures
210	32.61	35.66	3.05	2.99	98	2.99	98	15	4	6	2	1	2	2 gypsum on fractures
210	35.66	38.71	3.05	3.07	101	3.07	101	15	4	6	1	1	2	2 gypsum on fractures, sheared rock
210	38.71	41.76	3.05	3.00	98	2.81	92	15	4	6	3	5	3	3 gypsum on fractures, sheared rock
210	41.76	44.81	3.05	3.10	102	2.80	92	15	4	6	4	5	3	3 gouge + gypsum on fractures, sheared
210	44.81	47.85	3.04	3.09	102	3.09	102	15	4	6	2	2	3	3
210	47.85	50.90	3.05	3.13	103	3.13	103	15	4	6	2	4	3	3
210	50.90	53.95	3.05	3.03	99	3.03	99	15	4	6	1	1	2	2 minor gouge on fractures
210	53.95	57.00	3.05	2.87	94	2.73	90	15	4	6	3	2	3	3 3 cm slip plane @ 35 to c.a.
210	57.00	60.05	3.05	2.99	98	2.99	98	15	4	6	2	2	3	3
210	60.05	63.09	3.04	3.13	103	2.39	79	14	4	6	6	1	3	3 fault @ 5-10 to c.a., gouge on fractures
210	63.09	66.14	3.05	3.09	101	3.09	101	15	4	6	3	2	3	3
210	66.14	69.19	3.05	3.05	100	3.05	100	15	4	6	2	2	3	3 slip plane 15 to c.a., gouge on fractures
210	69.19	72.24	3.05	3.11	102	3.11	102	15	4	6	3	1	3	3
210	72.24	75.29	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3 minor gouge on fractures, weak slick
210	75.29	78.33	3.04	3.07	101	3.07	101	15	4	6	2	1	3	3 gouge on fractures
210	78.33	81.38	3.05	2.93	96	2.61	86	15	5	6	4	2	3	3 5 cm fault @ 25 to c.a. (H=0,1)
210	81.38	84.43	3.05	3.00	98	2.87	94	15	4	6	3	1	2	2 pyrite on fractures
210	84.43	87.48	3.05	3.12	102	3.01	99	15	4	6	4	1	2	2
210	87.48	90.53	3.05	2.95	97	2.49	82	14	5	6	6	1	3	3 dyke, minor gouge + carbon on fractures
210	90.53	93.57	3.04	3.16	104	3.09	102	15	4	6	3	1	2	2
210	93.57	96.62	3.05	2.95	97	2.95	97	15	4	6	4	1	3	3 minor gouge on fractures
210	96.62	99.67	3.05	2.79	91	2.51	82	13	4	6	10	1	3	3 5% broken core with gouge
210	99.67	102.72	3.05	2.97	97	2.34	77	14	5	6	6	1	2	2
210	102.72	105.77	3.05	3.00	98	3.00	98	15	5	6	3	1	2	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
210	105.77	108.81	3.04	3.15	104	3.15	104	15	4	6	2	1	2	gouge on one fracture another with slicks
210	108.81	111.86	3.05	3.01	99	3.01	99	15	4	6	3	1	2	
210	111.86	114.91	3.05	3.00	98	2.54	83	13	5	6	13	5	3	5% broken core with gouge
210	114.91	117.96	3.05	2.95	97	2.61	86	12	4	6	15	1	2	10% broken core (man-made?)
210	117.96	121.01	3.05	3.25	107	3.25	107	15	4	6	3	1	2	gypsum on fractures
210	121.01	124.05	3.04	3.11	102	3.11	102	15	4	6	2	1	2	gypsum on fractures
210	124.05	127.10	3.05	3.12	102	3.12	102	15	4	6	3	1	2	gypsum and pyrite on fractures
210	127.10	130.15	3.05	2.99	98	2.99	98	15	4	6	2	1	2	
210	130.15	133.20	3.05	2.85	93	2.85	93	15	5	6	3	1	3	gypsum + gouge on fractures
210	133.20	136.25	3.05	3.10	102	3.00	98	15	4	6	3	1	3	1 cm fault @ 40 to c.a., gypsum fractures
210	136.25	139.29	3.04	3.13	103	3.13	103	15	4	6	2	1	3	
210	139.29	142.34	3.05	3.06	100	3.06	100	15	5	6	3	2	3	gypsum on fractures
210	142.34	145.39	3.05	3.10	102	3.10	102	15	5	6	2	1	3	gypsum on fractures
210	145.39	148.44	3.05	3.00	98	3.00	98	15	5	6	3	1	3	gypsum on fractures
210	148.44	151.49	3.05	3.03	99	2.90	95	15	5	6	4	1	3	gypsum on fractures
210	151.49	154.53	3.04	3.09	102	3.09	102	15	5	6	2	1	2	
210	154.53	157.58	3.05	3.00	98	3.00	98	15	5	6	3	1	2	
210	157.58	160.63	3.05	3.05	100	3.05	100	15	5	6	1	1	2	
210	160.63	163.68	3.05	3.03	99	3.03	99	15	5	6	2	1	3	minor gouge on fractures
210	163.68	166.73	3.05	3.07	101	3.07	101	15	4	6	2	2	3	
210	166.73	169.77	3.04	3.06	101	2.94	97	15	4	6	4	2	3	minor gouge on fractures
210	169.77	172.82	3.05	2.99	98	2.99	98	15	4	6	3	1	3	
210	172.82	175.87	3.05	3.09	101	3.09	101	15	4	6	5	1	2	
210	175.87	178.92	3.05	2.93	96	2.93	96	15	4	6	3	1	2	
210	178.92	181.97	3.05	2.97	97	2.84	93	15	4	6	4	1	2	
210	181.97	185.01	3.04	3.04	100	2.91	96	15	4	6	3	2	3	
210	185.01	188.06	3.05	2.96	97	2.59	85	15	4	6	4	1	3	11 cm H=1,2; gouge on fractures
210	188.06	191.11	3.05	2.95	97	2.95	97	15	4	6	3	1	2	
210	191.11	194.16	3.05	3.05	100	3.05	100	15	5	6	2	1	2	
210	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6	1	1	3	
210	197.21	200.25	3.04	3.04	100	3.04	100	15	3	6	1	1	3	
210	200.25	203.30	3.05	3.05	100	2.91	95	15	3	6	2	1	3	
210	203.30	206.35	3.05	2.99	98	2.99	98	15	3	6	1	1	2	
210	206.35	209.40	3.05	2.90	95	2.84	93	15	3	6	2	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
210	209.40	212.45	3.05	2.91	95	2.91	95	15	3	6	2	2	3	gouge on fractures
210	212.45	215.49	3.04	3.04	100	3.04	100	15	3	6	3	1	3	gouge on fractures
210	215.49	218.54	3.05	3.05	100	3.05	100	15	3	6	4	2	3	gouge on fractures
210	218.54	221.59	3.05	2.99	98	2.71	89	15	3	6	4	1	3	gouge on fractures
210	221.59	224.64	3.05	3.00	98	3.00	98	15	4	6	3	1	3	gouge on fractures
210	224.64	227.69	3.05	3.05	100	2.84	93	14	4	6	7	2	3	gouge on fractures
210	227.69	230.73	3.04	3.01	99	2.31	76	15	3	6	5	2	3	gouge on fractures
210	230.73	233.78	3.05	2.98	98	2.98	98	15	3	6	2	1	2	gouge on fractures
210	233.78	236.83	3.05	3.05	100	3.05	100	15	4	6	2	1	3	gouge on fractures
210	236.83	239.88	3.05	2.89	95	2.62	86	15	3	6	5	2	3	gouge on fractures, sheared
210	239.88	242.93	3.05	2.98	98	1.91	63	13	3	6	12	5	3	gouge on fractures, sheared
210	242.93	245.97	3.04	3.09	102	2.83	93	14	3	6	7	5	3	gouge on fractures, sheared
210	245.97	249.02	3.05	3.05	100	2.90	95	14	3	6	6	5	3	gouge on fractures, sheared
210	249.02	252.07	3.05	2.92	96	2.03	67	13	3	6	11	2	3	sheared, faulted with 45 cm H=1,2
210	252.07	255.12	3.05	2.01	66	1.23	40	13	3	6	10	2	3	mainly manual breaks
210	255.12	258.17	3.05	3.20	105	3.20	105	15	4	6	2	2	3	gouge on fractures
210	258.17	261.21	3.04	2.88	95	2.88	95	15	4	6	1	1	3	gouge on fractures
210	261.21	264.26	3.05	3.11	102	2.90	95	15	4	6	4	1	3	gouge on fractures
210	264.26	267.31	3.05	2.93	96	2.87	94	15	4	6	4	1	3	gouge on fractures
210	267.31	270.36	3.05	3.08	101	2.71	89	14	3	6	9	2	3	gouge on fractures
210	270.36	273.41	3.05	3.11	102	2.14	70	13	3	6	12	1	3	50% unit is a fault with H=0,1 at 35 to c.a.
210	273.41	276.45	3.04	3.16	104	3.16	104	15	3	6	2	1	2	
210	276.45	279.50	3.05	2.99	98	2.99	98	15	4	6	2	1	2	
210	279.50	282.55	3.05	3.05	100	3.05	100	15	4	6	2	1	3	3 cm gouge 70 to c.a. with H=0,1
210	282.55	285.60	3.05	3.05	100	3.05	100	15	3	6	4	1	3	minor gouge on fractures
210	285.60	288.65	3.05	2.95	97	2.87	94	15	3	6	3	1	3	2 cm H=0,1; gouge on fractures
210	288.65	291.69	3.04	3.06	101	2.79	92	14	3	6	7	2	3	23 cm H=0,1; fractures 35-45 to c.a.
210	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
210	294.74	297.79	3.05	3.00	98	2.94	96	15	4	6	3	1	2	
210	297.79	300.84	3.05	3.12	102	3.01	99	15	4	6	4	1	2	
210	300.84	303.89	3.05	3.16	104	2.83	93	15	4	6	5	1	3	slip plane @ 15 to c.a., gouge @ 38 to c.a.
210	303.89	306.93	3.04	2.87	94	2.79	92	15	4	6	2	3	3	
210	306.93	309.98	3.05	3.09	101	2.42	79	14	4	6	6	2	3	pyrite on some fractures
210	309.98	313.03	3.05	3.05	100	2.64	87	15	4	6	5	2	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
210	313.03	316.08	3.05	3.03	99	2.59	85	14	4	6	7	1	3	gouge on fractures
210	316.08	319.13	3.05	3.12	102	2.64	87	14	4	6	8	2	3	8 cm gouge at 50 to c.a.
210	319.13	322.17	3.04	3.11	102	3.11	102	15	4	6	3	1	3	slip plane at 12 to c.a.
210	322.17	325.22	3.05	2.83	93	2.83	93	15	4	6	3	1	2	
210	325.22	328.27	3.05	3.05	100	2.61	86	14	4	6	6	1	3	gouge on fractures
210	328.27	331.32	3.05	3.05	100	2.49	82	15	3	6	3	5	3	9 cm gouge H=0,1 at 50 to c.a., sheared
210	331.32	334.37	3.05	3.05	100	3.05	100	15	3	6	2	1	2	
210	334.37	337.41	3.04	2.85	94	2.85	94	15	4	6	2	1	3	slip plane at 38 to c.a., gouge on fractures
210	337.41	340.46	3.05	3.05	100	3.05	100	15	4	6	2	2	2	
210	340.46	343.51	3.05	3.07	101	3.07	101	15	4	6	1	1	3	1 cm gouge on fracture
210	343.51	346.56	3.05	3.07	101	3.07	101	15	3	6	2	1	3	gypsum on fractures
210	346.56	349.61	3.05	3.12	102	3.12	102	15	4	6	2	2	3	1-2 cm fault 28 to c.a., 1-8 cm fault 35 tca
210	349.61	352.65	3.04	3.04	100	2.72	89	15	3	6	5	1	3	gouge on fractures
210	352.65	355.70	3.05	3.05	100	2.84	93	15	3	6	4	2	3	gouge on fractures
210	355.70	358.75	3.05	3.05	100	2.35	77	14	3	6	9	2	3	sheared with 10% gouge, H=0, 1
210	358.75	361.80	3.05	3.00	98	2.34	77	14	3	6	6	5	3	5% gouge, H=0,1 at 30-45 to c.a.
210	361.80	364.85	3.05	2.84	93	2.84	93	15	4	6	2	1	3	gouge on fractures
210	364.85	367.89	3.04	3.20	105	3.20	105	15	5	6	1	1	2	
210	367.89	370.94	3.05	3.08	101	3.08	101	15	5	6	3	2	3	
210	370.94	373.99	3.05	2.96	97	2.81	92	15	5	6	2	5	2	
210	373.99	377.04	3.05	3.12	102	3.12	102	15	5	6	3	1	3	gypsum on fractures
210	377.04	380.09	3.05	3.13	103	3.13	103	15	5	6	2	2	3	gypsum on fractures
210	380.09	383.13	3.04	3.08	101	3.04	100	15	5	6	4	2	3	gypsum and gouge on fractures
210	383.13	386.18	3.05	3.20	105	3.09	101	15	5	6	2	2	3	gypsum and gouge on fractures
210	386.18	389.23	3.05	3.87	127	3.71	122	15	5	6	3	2	2	
210	389.23	392.28	3.05	2.97	97	2.73	90	12	5	6	10	2	3	slip plane with gouge at 45 to c.a.
210	392.28	395.33	3.05	3.20	105	3.07	101	15	5	6	5	2	3	gypsum on fractures
210	395.33	398.37	3.04	3.08	101	3.08	101	15	5	6	3	1	2	
210	398.37	401.42	3.05	3.03	99	3.03	99	15	5	6	3	2	3	
210	401.42	404.46	3.04	3.04	100	3.04	100	15	5	6	2	5	3	
210	404.46	407.52	3.06	2.88	94	2.88	94	15	5	6	2	1	2	
210	407.52	410.57	3.05	3.28	108	2.76	90	14	5	6	7	5	3	
210	410.57	413.61	3.04	3.24	107	2.05	67	14	4	6	8	1	3	gypsum and gouge on fractures
210	413.61	416.66	3.05	2.99	98	2.57	84	14	4	6	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
210	416.66	419.71	3.05	2.90	95	2.13	70	14	4	6	7	1	2	gypsum on fractures
210	419.71	422.76	3.05	2.97	97	2.69	88	13	4	6	10	5	3	5% broken core, manual breaks
210	422.76	425.81	3.05	3.10	102	3.01	99	15	5	6	3	1	2	
210	425.81	428.85	3.04	3.11	102	3.11	102	15	5	6	4	1	3	
210	428.85	431.90	3.05	2.90	95	2.90	95	15	5	6	3	1	2	
210	431.90	434.95	3.05	2.82	92	2.65	87	14	5	6	7	2	3	redrilled core
210	434.95	438.00	3.05	3.07	101	2.91	95	15	5	6	3	2	3	gouge on fractures
210	438.00	441.05	3.05	3.07	101	3.07	101	15	5	6	3	1	3	gypsum on fractures
210	441.05	444.09	3.04	3.06	101	3.06	101	15	5	6	4	1	3	gypsum on fractures
210	444.09	447.14	3.05	3.05	100	3.05	100	15	5	6	1	1	2	gypsum on fractures
210	447.14	450.19	3.05	3.09	101	3.00	98	15	5	6	3	1	2	gypsum on fractures
210	450.19	453.23	3.04	2.84	93	2.84	93	15	5	6	2	1	3	gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
211	6.10	8.23	2.13	1.19	56	0.11	5	7	3	4	23	1	3 iron stained, broken core	
211	8.23	11.28	3.05	2.90	95	2.25	74	10	5	5	23	2	3 iron stained, 50% broken core	
211	11.28	14.33	3.05	2.61	86	1.17	38	9	5	5	30	2	3 iron stained	
211	14.33	17.37	3.04	2.18	72	0.56	18	6	4	5	50	2	3 80% broken core, 10% gouge	
211	17.37	20.42	3.05	2.30	75	0.28	9	6	5	5	50	2	3 70% broken core, gypsum on fractures	
211	20.42	23.47	3.05	2.85	93	0.66	22	9	5	5	35	2	3 50% broken core, gypsum on fractures	
211	23.47	26.52	3.05	2.00	66	0.99	32	7	5	5	35	2	3 10 cm gouge H=2, gypsum on fractures	
211	26.52	29.57	3.05	2.42	79	0.69	23	7	5	5	35	2	3 70% broken, gypsum on fractures	
211	29.57	32.61	3.04	1.18	39	0.18	6	6	5	5	40	2	3 15 cm gouge H=1, 70% broken core	
211	32.61	35.66	3.05	1.57	51	0.44	14	7	5	5	30	2	1 weak slicks on fractures	
211	35.66	37.80	2.14	0.94	44	0.45	21	7	5	5	15	2	3 carbonate on fractures	
211	37.80	39.62	1.82	0.53	29	0.00	0	6	5	5	20	2	3 pyrite on fractures	
211	39.62	41.76	2.14	0.52	24	0.00	0	6	5	5	20	1	2 pyrite on fractures	
211	41.76	44.81	3.05	0.62	20	0.00	0	6	5	5	25	1	2 pyrite on fractures	
211	44.81	47.85	3.04	1.21	40	0.80	26	10	5	5	10	2	3	
211	47.85	50.90	3.05	0.63	21	0.31	10	7	5	5	10	2	3 30% broken core	
211	50.90	53.95	3.05	0.27	9	0.00	0	3	5	5	30	2	3 100% broken core	
211	53.95	57.00	3.05	0.63	21	0.00	0	6	5	5	40	2	3 100% broken core	
211	57.00	60.05	3.05	0.58	19	0.00	0	6	5	5	30	2	3 100% broken core	
211	60.05	63.09	3.04	0.46	15	0.15	5	6	5	5	20	2	3 70% broken core	
211	63.09	66.14	3.05	3.05	100	3.05	100	15	5	6	5	2	3 gypsum on fractures	
211	66.14	69.19	3.05	3.01	99	3.01	99	15	5	6	3	2	3 10 cm gouge H=3	
211	69.19	72.24	3.05	2.70	89	2.43	80	13	4	6	10	2	3 gypsum on fractures	
211	72.24	75.29	3.05	3.03	99	3.03	99	15	4	6	1	2	4 50 cm healed gouge/gouge H=3	
211	75.29	78.33	3.04	3.04	100	2.77	91	13	4	6	11	1	3 gypsum on fractures	
211	78.33	81.38	3.05	2.91	95	2.10	69	12	5	6	17	2	3	
211	81.38	84.43	3.05	3.11	102	3.11	102	15	5	6	1	2	3	
211	84.43	87.48	3.05	3.05	100	3.05	100	15	5	6	1	2	3 gypsum on fractures	
211	87.48	90.53	3.05	3.02	99	3.02	99	15	5	6	2	2	3 gypsum on fractures	
211	90.53	93.57	3.04	2.81	92	2.71	89	14	5	6	8	2	3 gypsum on fractures	
211	93.57	96.62	3.05	3.09	101	3.02	99	15	5	6	3	2	4 gouge on fractures	
211	96.62	99.67	3.05	3.07	101	3.07	101	15	4	6	1	1	3 gypsum on fractures, 10 cm gouge H=3	
211	99.67	102.72	3.05	3.07	101	3.07	101	15	5	6	3	2	3 gypsum on fractures	
211	102.72	105.77	3.05	3.00	98	3.00	98	15	5	6	1	2	3 gypsum on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
211	105.77	108.81	3.04	3.04	100	3.04	100	15	5	6	2	2	3	gypsum on fractures
211	108.81	111.86	3.05	3.08	101	3.08	101	15	5	6	1	2	3	gypsum on fractures
211	111.86	114.91	3.05	3.00	98	3.00	98	15	5	6	2	2	3	gypsum on fractures
211	114.91	117.96	3.05	3.03	99	3.03	99	15	5	6	2	2	3	gypsum on fractures
211	117.96	121.01	3.05	3.05	100	3.05	100	15	5	6	3	2	3	gypsum on fractures
211	121.01	124.05	3.04	3.13	103	3.13	103	15	5	6	2	2	3	gypsum on fractures
211	124.05	127.10	3.05	3.05	100	3.05	100	15	5	6	2	2	3	gypsum on fractures
211	127.10	130.15	3.05	3.02	99	3.02	99	15	5	6	4	1	2	gypsum on fractures
211	130.15	133.20	3.05	2.95	97	2.95	97	14	5	6	6	2	3	gypsum on fractures
211	133.20	136.25	3.05	2.98	98	2.98	98	15	5	6	2	2	3	pyrite on fractures
211	136.25	139.30	3.05	3.12	102	3.07	101	14	5	6	6	1	3	gypsum on fractures
211	139.30	142.34	3.04	3.00	99	3.00	99	15	5	6	4	2	3	pyrite on fractures
211	142.34	145.39	3.05	3.09	101	3.09	101	15	5	6	4	2	3	gypsum on fractures
211	145.39	148.44	3.05	2.94	96	2.94	96	15	5	6	1	2	3	gypsum on fractures
211	148.44	151.49	3.05	2.98	98	2.98	98	15	5	6	4	2	3	minor gouge on fractures
211	151.49	154.53	3.04	3.09	102	3.09	102	15	5	6	2	2	3	gypsum on fractures
211	154.53	157.58	3.05	3.12	102	3.12	102	15	5	6	4	2	3	gypsum on fractures
211	157.58	160.63	3.05	2.89	95	2.71	89	14	5	6	6	2	3	minor gouge on fractures
211	160.63	163.68	3.05	3.02	99	2.83	93	14	5	6	8	2	3	gypsum on fractures, minor gouge
211	163.68	166.73	3.05	2.94	96	2.94	96	15	5	6	3	1	2	gypsum on fractures
211	166.73	169.77	3.04	2.98	98	2.58	85	14	5	6	7	2	3	gypsum on fractures
211	169.77	172.82	3.05	2.92	96	2.59	85	14	5	6	9	2	3	gypsum on fractures
211	172.82	175.87	3.05	3.05	100	2.97	97	15	5	6	4	2	3	
211	175.87	178.92	3.05	3.08	101	3.03	99	14	5	6	6	2	3	
211	178.92	181.97	3.05	3.03	99	3.00	98	14	5	6	7	2	3	gypsum on fractures
211	181.97	185.01	3.04	3.08	101	3.08	101	15	5	6	4	2	3	gypsum on fractures
211	185.01	188.06	3.05	3.07	101	2.87	94	14	5	6	7	1	3	gypsum on fractures
211	188.06	191.11	3.05	2.97	97	2.97	97	15	5	6	3	2	3	gypsum on fractures
211	191.11	194.16	3.05	3.05	100	3.05	100	14	5	6	6	2	3	gypsum on fractures
211	194.16	197.21	3.05	3.05	100	3.05	100	15	5	6	2	2	3	gypsum on fractures
211	197.21	200.25	3.04	2.97	98	2.97	98	15	5	6	2	2	3	gypsum on fractures
211	200.25	203.30	3.05	3.07	101	3.07	101	15	5	6	4	1	2	gypsum on fractures
211	203.30	206.35	3.05	3.18	104	3.18	104	15	5	6	3	1	2	gypsum + minor gouge
211	206.35	209.40	3.05	2.94	96	2.94	96	15	5	6	2	1	3	box 33 dropped, gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
211	209.40	212.45	3.05	3.05	100	3.05	100	15	5	6	5	2	3	box 33 dropped, minor gouge on fract
211	212.45	215.49	3.04	2.94	97	2.94	97	15	5	6	3	2	3	gypsum on fractures
211	215.49	218.54	3.05	3.01	99	2.80	92	14	5	6	10	1	3	pyrite on fractures
211	218.54	221.59	3.05	3.21	105	3.21	105	15	5	6	4	2	3	gypsum on fractures
211	221.59	224.64	3.05	2.89	95	2.86	94	14	5	6	7	2	3	gypsum on fractures
211	224.64	227.69	3.05	2.91	95	2.91	95	15	5	6	4	2	3	gypsum on fractures
211	227.69	230.73	3.04	3.28	108	3.05	100	14	5	6	6	2	3	gypsum on fractures
211	230.73	233.78	3.05	3.01	99	3.01	99	15	5	6	4	2	3	gypsum on fractures
211	233.78	236.83	3.05	3.05	100	3.05	100	15	5	6	1	2	3	
211	236.83	239.88	3.05	3.03	99	2.97	97	15	5	6	5	1	2	
211	239.88	242.93	3.05	3.05	100	3.05	100	15	5	6	5	1	2	gypsum on fractures
211	242.93	245.97	3.04	2.97	98	2.97	98	14	5	6	5	2	3	1 cm shear at 35 to c.a.
211	245.97	249.02	3.05	2.97	97	2.97	97	15	5	6	3	1	3	gypsum on fractures
211	249.02	252.07	3.05	2.98	98	2.98	98	15	5	6	2	2	3	15 cm redrilled core, minor gouge
211	252.07	255.12	3.05	3.13	103	3.13	103	15	5	6	2	1	3	5 cm redrilled core, gypsum on fractures
211	255.12	258.17	3.05	3.07	101	2.97	97	15	5	6	2	2	3	
211	258.17	261.21	3.04	3.04	100	3.04	100	15	5	6	2	2	3	gypsum on fractures
211	261.21	264.26	3.05	3.05	100	3.05	100	15	5	6	5	2	3	gypsum on fractures
211	264.26	267.31	3.05	3.05	100	3.05	100	15	5	6	4	1	3	gypsum on fractures
211	267.31	270.36	3.05	3.10	102	3.10	102	14	5	6	7	1	3	gypsum on fractures
211	270.36	273.41	3.05	3.01	99	3.01	99	15	5	6	1	2	3	gypsum on fractures
211	273.41	276.45	3.04	3.14	103	3.14	103	15	4	5	2	2	3	12 cm gouge, H=3
211	276.45	279.50	3.05	3.06	100	3.06	100	15	5	6	1	2	3	shear at 75 to c.a.
211	279.50	282.55	3.05	3.05	100	3.05	100	15	5	6	5	2	3	minor gouge on fractures
211	282.55	285.60	3.05	3.05	100	3.05	100	15	5	6	1	2	3	
211	285.60	288.65	3.05	3.03	99	3.03	99	15	5	6	1	2	3	
211	288.65	291.69	3.04	3.10	102	3.10	102	15	5	6	1	2	3	
211	291.69	294.74	3.05	3.10	102	2.81	92	14	5	6	8	1	2	gypsum on fractures
211	294.74	297.79	3.05	2.91	95	2.83	93	15	4	6	3	2	3	minor gouge on fractures
211	297.79	300.84	3.05	2.98	98	1.62	53	9	4	5	30	2	3	1.78m broken rock with gouge, H=3,4
211	300.84	303.89	3.05	2.98	98	2.89	95	15	5	6	2	2	3	gouge on fractures
211	303.89	306.93	3.04	3.11	102	3.11	102	15	4	5	2	2	3	20 cm healed gouge, H=3
211	306.93	309.98	3.05	3.00	98	3.00	98	15	5	6	1	2	3	
211	309.98	313.03	3.05	3.03	99	2.91	95	14	5	6	6	2	3	minor gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
211	313.03	316.08	3.05	3.10	102	3.10	102	15	5	6	2	2	3	
211	316.08	319.13	3.05	3.05	100	3.05	100	15	5	6	5	2	3	
211	319.13	321.56	2.43	2.38	98	2.26	93	13	5	6	9	2	3	
211	321.56	324.61	3.05	3.13	103	3.00	98	14	5	6	8	2	3	
211	324.61	327.05	2.44	2.51	103	2.51	103	13	5	6	9	2	3	
211	327.05	330.10	3.05	3.08	101	2.93	96	14	5	6	7	2	3	gypsum on fractures
211	330.10	331.32	1.22	1.22	100	0.98	80	13	5	6	6	2	3	
211	331.32	332.54	1.22	1.22	100	1.07	88	13	5	6	5	2	3	
211	332.54	334.37	1.83	1.83	100	1.58	86	14	5	6	4	2	3	
211	334.37	335.58	1.21	1.30	107	1.20	99	13	5	6	5	2	3	
211	335.58	338.33	2.75	2.82	103	2.82	103	14	5	6	5	1	3	
211	338.33	340.46	2.13	1.92	90	1.92	90	13	5	6	8	2	3	gypsum on fractures
211	340.46	343.51	3.05	3.05	100	3.05	100	14	5	6	6	2	3	
211	343.51	346.56	3.05	3.06	100	3.06	100	15	5	6	2	2	3	
211	346.56	349.61	3.05	2.98	98	2.98	98	15	4	5	4	2	3	346.90-347.20 m shear at 45 to c.a., H=3
212	16.46	17.37	0.91	0.85	93	0.65	71	13	4	5	4	1	1	1 limonite staining
212	17.37	20.42	3.05	2.44	80	1.63	53	12	4	5	20	1	1	1 limonite staining, 5 cm gouge
212	20.42	23.47	3.05	2.55	84	2.00	66	10	4	5	23	1	1	1 limonite staining
212	23.47	26.52	3.05	2.53	83	1.64	54	10	4	6	24	1	1	1 limonite staining, trace gouge
212	26.52	29.57	3.05	2.87	94	2.13	70	10	4	6	23	1	1	1 limonite staining
212	29.57	32.61	3.04	2.66	88	1.92	63	12	4	6	16	1	1	1 limonite staining, trace gouge
212	32.61	35.66	3.05	2.55	84	2.03	67	13	4	6	11	1	1	1 limonite staining
212	35.66	36.27	0.61	0.56	92	0.56	92	12	4	6	3	1	1	1
212	36.27	36.58	0.31	0.27	87	0.22	71	10	4	6	3	1	1	1 gouge on slip
212	36.58	38.40	1.82	1.48	81	1.38	76	13	4	6	7	1	1	1 gouge on broken core
212	38.40	39.62	1.22	1.19	98	1.05	86	10	4	6	9	1	1	1 gouge on broken core
212	39.62	42.37	2.75	2.50	91	2.46	89	15	4	6	4	1	1	1 trace limonite
212	42.37	43.28	0.91	0.36	40	0.00	0	10	4	6	9	1	1	1 trace limonite
212	43.28	44.20	0.92	0.65	71	0.28	30	10	4	6	8	1	1	1 trace limonite, 5 cm rubble
212	44.20	46.63	2.43	2.01	83	1.95	80	14	4	6	5	1	1	1
212	46.63	47.85	1.22	1.22	100	0.91	75	9	4	6	16	1	1	1 trace gouge
212	47.85	48.46	0.61	0.52	85	0.26	43	7	4	6	7	1	1	1 limonite on fractures
212	48.46	49.07	0.61	0.38	62	0.00	0	7	4	6	10	1	1	1 limonite on fractures
212	49.07	50.90	1.83	1.40	77	0.75	41	9	4	6	17	1	1	1 gouge in rubble

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
212	50.90	52.12	1.22	1.47	120	0.15	12	5	4	5	15	1	1	1 limonite stains and trace gouge
212	52.12	53.95	1.83	0.74	40	0.31	17	5	4	5	15	1	1	1 limonite stains and trace gouge
212	53.95	54.56	0.61	0.40	66	0.00	0	5	4	5	15	1	1	1 limonite stains and trace gouge
212	54.56	55.47	0.91	0.89	98	0.67	74	9	4	5	8	1	1	1 limonite stains and trace gouge
212	55.47	56.69	1.22	1.13	93	0.70	57	9	4	5	13	1	1	1 limonite stains and trace gouge
212	56.69	57.91	1.22	1.22	100	0.87	71	9	4	5	12	1	1	1 limonite stains and trace gouge
212	57.91	59.44	1.53	1.02	67	0.47	31	5	4	5	15	1	1	1 limonite stains and trace gouge
212	59.44	60.66	1.22	0.32	26	0.13	11	5	4	5	15	1	1	1 limonite stains and trace gouge
212	60.66	62.18	1.52	0.89	59	0.00	0	5	4	5	15	1	1	1 limonite stains and trace gouge
212	62.18	64.62	2.44	1.22	50	0.00	0	5	4	5	25	1	1	1 limonite stains and trace gouge
212	64.62	66.14	1.52	1.39	91	0.93	61	10	4	5	12	1	1	1 limonite stains and trace gouge
212	66.14	67.67	1.53	0.82	54	0.00	0	5	4	5	15	1	1	1 limonite stains and trace gouge
212	67.67	69.19	1.52	1.11	73	0.61	40	5	4	5	15	1	1	1 limonite stains and trace gouge
212	69.19	70.10	0.91	0.39	43	0.00	0	5	4	5	15	1	1	1 limonite stains and trace gouge
212	70.10	71.02	0.92	0.48	52	0.00	0	5	4	5	15	1	1	1 limonite stains and trace gouge
212	71.02	71.93	0.91	0.43	47	0.24	26	5	4	5	15	1	1	1 limonite stains and trace gouge
212	71.93	73.46	1.53	0.49	32	0.00	0	5	4	5	15	1	1	1 limonite stains and trace gouge
212	73.46	75.60	2.14	2.14	100	0.50	23	5	4	5	15	1	1	1 limonite stains and trace gouge
212	75.60	76.50	0.90	0.60	67	0.11	12	5	4	6	15	1	1	1 limonite stains and trace gouge
212	76.50	78.64	2.14	1.55	72	0.89	42	5	4	6	15	1	1	1 limonite stains and trace gouge
212	78.64	79.55	0.91	0.71	78	0.49	54	6	4	6	7	1	2	2 limonite stains and trace gouge
212	79.55	80.16	0.61	0.58	95	0.44	72	7	4	6	8	1	1	1 limonite stains and trace gouge
212	80.16	81.38	1.22	0.84	69	0.55	45	7	4	6	11	1	1	1 limonite stains and trace gouge
212	81.38	82.60	1.22	0.91	75	0.14	11	5	4	6	15	1	1	1 limonite stains and trace gouge
212	82.60	83.52	0.92	0.34	37	0.00	0	5	4	6	15	1	1	1 limonite stains and trace gouge
212	83.52	84.43	0.91	0.64	70	0.21	23	5	4	6	15	1	1	1 no limonite
212	84.43	85.95	1.52	0.22	14	0.00	0	5	4	6	10	5	3	3
212	85.95	88.09	2.14	0.22	10	0.00	0	5	4	6	10	5	3	3 redrilled rubble
212	88.09	91.14	3.05	2.87	94	2.41	79	13	4	6	10	1	1	1 gouge on slip
212	91.14	93.57	2.43	2.38	98	2.35	97	15	4	6	4	1	1	1 trace gouge
212	93.57	96.62	3.05	2.95	97	2.82	92	14	4	6	7	1	1	1
212	96.62	99.67	3.05	2.52	83	2.26	74	14	4	6	7	1	1	1 gouge in broken core
212	99.67	102.72	3.05	2.92	96	2.89	95	14	4	6	8	1	1	1 gouge on slips
212	102.72	105.77	3.05	2.98	98	2.93	96	14	4	6	6	1	1	1 gouge on slips

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
212	105.77	108.81	3.04	2.88	95	2.88	95	15	4	6	3	1	1	gouge on slips
212	108.81	111.86	3.05	3.07	101	2.77	91	14	4	6	7	1	3	12 cm H=0,1; gouge on fractures
212	111.86	114.91	3.05	3.23	106	2.45	80	14	4	6	8	5	3	gouge + gypsum on fractures
212	114.91	117.96	3.05	3.05	100	2.64	87	15	4	6	5	1	3	21 cm H=0,1 (gouge)
212	117.96	121.01	3.05	3.02	99	3.02	99	15	4	6	2	1	2	gypsum on fractures
212	121.01	124.05	3.04	3.00	99	3.00	99	15	4	6	3	1	3	gypsum on fractures
212	124.05	127.10	3.05	3.16	104	3.16	104	15	3	6	2	1	3	gypsum on fractures
212	127.10	130.15	3.05	2.94	96	2.89	95	15	3	6	3	2	3	gypsum on fractures
212	130.15	133.20	3.05	2.99	98	2.93	96	15	3	6	2	1	3	gypsum on fractures
212	133.20	136.25	3.05	3.05	100	3.00	98	15	3	6	4	2	3	gypsum on fractures
212	136.25	139.29	3.04	3.04	100	3.04	100	15	3	6	4	1	3	gypsum on fractures
212	139.29	142.34	3.05	3.05	100	3.05	100	15	3	6	3	1	3	gypsum on fractures
212	142.34	145.39	3.05	2.97	97	2.97	97	15	4	6	1	1	2	gypsum on fractures
212	145.39	148.44	3.05	3.07	101	3.07	101	15	3	6	5	1	3	gypsum + gouge on fractures
212	148.44	151.49	3.05	3.08	101	3.00	98	15	3	6	3	2	3	gypsum + gouge on fractures
212	151.49	154.53	3.04	3.04	100	3.04	100	15	4	6	3	1	2	gypsum on fractures
212	154.53	157.58	3.05	3.02	99	2.77	91	14	3	6	7	2	3	2 cm H=0 (mud); gy + gouge on fracture
212	157.58	160.63	3.05	3.06	100	2.68	88	14	3	6	8	2	3	157.90-159.25m shear zone H=1,2
212	160.63	163.68	3.05	2.73	90	2.04	67	13	3	6	12	2	3	10 cm H=0,1 (gouge)
212	163.68	166.73	3.05	2.96	97	2.71	89	14	4	6	6	1	3	gypsum on fractures
212	166.73	169.77	3.04	3.04	100	2.69	88	14	4	6	7	2	3	12 cm H=0,1 (gouge)
212	169.77	172.82	3.05	2.95	97	2.88	94	15	3	6	2	1	3	gouge on fractures, 2 cm H=0,1
212	172.82	175.87	3.05	3.00	98	3.00	98	15	3	6	4	2	3	dyke @ 174.57-175.50 m
212	175.87	178.92	3.05	3.06	100	2.61	86	14	3	6	8	2	3	33 cm gouge H=0,1
212	178.92	181.97	3.05	3.09	101	3.09	101	15	3	6	2	1	3	gypsum on fractures
212	181.97	185.01	3.04	3.04	100	3.04	100	15	3	6	2	1	3	gypsum on fractures
212	185.01	188.06	3.05	2.99	98	2.91	95	15	3	6	3	5	3	2 cm H=0,1 (gouge)
212	188.06	191.11	3.05	3.00	98	3.00	98	15	3	6	1	1	3	gypsum on fractures
212	191.11	194.16	3.05	3.00	98	3.00	98	15	3	6	2	1	3	gypsum on fractures
212	194.16	197.21	3.05	3.09	101	3.09	101	15	3	6	2	1	3	gypsum on fractures
212	197.21	200.25	3.04	3.07	101	3.07	101	15	3	6	1	2	3	gypsum on fractures
212	200.25	203.30	3.05	2.95	97	2.95	97	15	3	6	4	1	3	gypsum on fractures
213	14.33	17.37	3.04	2.36	78	0.58	19	9	3	4	25	3	3	limonite / wk-mod blocky
213	17.37	20.42	3.05	2.44	80	0.88	29	9	3	4	25	3	3	limonite / wk-mod blocky

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
213	20.42	23.47	3.05	3.40	111	0.66	22	10	3	4	25	3	2 limonite / wk-mod blocky	
213	23.47	26.52	3.05	3.45	113	0.95	31	13	3	4	16	1	2 limonite / wk-mod blocky	
213	26.52	29.57	3.05	2.75	90	1.35	44	12	3	4	14	1	2 limonite / wk-mod blocky	
213	29.57	32.62	3.05	3.00	98	1.75	57	13	3	4	13	1	3 limonite / wk-mod blocky	
213	32.62	35.66	3.04	2.90	95	1.05	35	10	3	4	20	1	2 limonite on frac / strong blocky	
213	35.66	38.71	3.05	2.80	92	0.17	6	6	4	5	25	1	2 limonite on frac / strong blocky	
213	38.71	41.76	3.05	3.15	103	0.00	0	6	4	5	25	1	2 limonite on frac / strong blocky	
213	41.76	44.81	3.05	2.70	89	0.00	0	6	4	5	25	3	2 limonite on frac / strong blocky	
213	44.81	47.85	3.04	2.90	95	0.52	17	7	4	5	25	1	2 limonite on frac / strong blocky	
213	47.85	50.90	3.05	2.40	79	0.00	0	6	4	5	25	1	2	
213	50.90	53.95	3.05	2.20	72	0.00	0	5	4	5	25	3	3	
213	53.95	57.00	3.05	1.38	45	0.15	5	6	4	5	20	3	3	
213	57.00	60.05	3.05	3.10	102	2.85	93	15	4	6	4	1	2	
213	60.05	63.09	3.04	3.05	100	2.65	87	14	4	6	9	1	2	
213	63.09	66.14	3.05	3.00	98	2.50	82	14	4	6	10	1	2	
213	66.14	69.19	3.05	3.00	98	3.00	98	15	4	6	3	1	1 10 cm black fault gouge	
213	69.19	72.24	3.05	2.65	87	2.10	69	13	3	5	12	3	3	
213	72.24	75.29	3.05	2.70	89	1.30	43	8	3	5	20	4	3	
213	75.29	78.33	3.04	2.65	87	0.26	9	9	3	5	35	2	3 80% broken core	
213	78.33	81.38	3.05	2.90	95	1.16	38	7	3	5	40	2	3 80% broken core with minor gouge	
213	81.38	84.43	3.05	1.74	57	0.51	17	6	3	5	40	3	3 35 cm gouge	
213	84.43	87.48	3.05	2.50	82	0.26	9	7	3	5	45	3	3 90% broken core with minor gouge	
213	87.48	90.53	3.05	2.70	89	0.00	0	7	3	5	50	3	3	
213	90.53	93.57	3.04	3.45	113	1.62	53	9	3	5	40	1	3 pyrite on fractures	
213	93.57	96.62	3.05	3.04	100	3.04	100	15	4	6	2	3	3 gypsum on fractures	
213	96.62	99.67	3.05	3.08	101	3.08	101	15	4	6	3	2	3 gypsum on fractures	
213	99.67	102.72	3.05	3.02	99	3.02	99	15	4	6	2	1	2 gypsum on fractures	
213	102.72	105.77	3.05	3.08	101	3.08	101	15	4	6	2	3	3	
213	105.77	108.81	3.04	3.05	100	3.05	100	15	4	6	3	2	3	
213	108.81	111.86	3.05	3.04	100	3.04	100	14	4	6	6	1	2 gypsum on fractures, 33cm shear H=3	
213	111.86	114.91	3.05	3.05	100	3.05	100	15	4	6	1	3	3	
213	114.91	117.96	3.05	3.10	102	3.10	102	15	4	6	1	3	3	
213	117.96	121.01	3.05	3.05	100	3.05	100	15	4	6	1	1	2 pyrite on fracture	
213	121.01	124.05	3.04	3.02	99	3.02	99	15	4	6	2	3	3 gypsum on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
213	124.05	127.10	3.05	3.18	104	3.05	100	15	4	6	3	2	2	pyrite on fractures
213	127.10	130.15	3.05	2.85	93	2.85	93	15	4	6	4	2	2	pyrite on fractures
213	130.15	133.20	3.05	3.13	103	3.13	103	15	4	6	3	2	3	pyrite on fractures
213	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6	4	1	3	pyrite on fractures
213	136.25	139.29	3.04	3.03	100	3.03	100	15	4	6	2	2	3	
213	139.29	142.34	3.05	3.08	101	2.96	97	15	4	6	4	1	2	gypsum on fractures
213	142.34	145.39	3.05	3.03	99	3.03	99	15	4	6	2	2	2	pyrite on fractures
213	145.39	148.44	3.05	3.08	101	3.08	101	15	4	6	5	2	3	
213	148.44	151.49	3.05	3.01	99	3.01	99	15	4	6	2	3	3	
213	151.49	154.53	3.04	3.05	100	3.05	100	15	4	6	5	2	3	gypsum on fractures
213	154.53	157.58	3.05	3.02	99	3.02	99	15	4	6	4	3	3	gypsum on fractures
213	157.58	160.63	3.05	3.02	99	3.02	99	15	4	6	3	2	3	20 cm shear 45 deg to c.a., H=3
213	160.63	163.68	3.05	3.15	103	3.15	103	15	4	6	5	2	3	7cm shear 40 deg to c.a., H=3
213	163.68	166.73	3.05	3.05	100	3.05	100	15	4	6	3	2	3	
213	166.73	169.77	3.04	3.05	100	3.05	100	15	4	6	3	3	3	
213	169.77	172.82	3.05	2.98	98	2.86	94	15	4	6	2	2	3	
213	172.82	175.87	3.05	2.96	97	2.96	97	14	4	6	5	3	3	minor gouge on fractures
213	175.87	178.92	3.05	3.00	98	3.00	98	15	4	6	4	2	3	minor gouge on fractures
213	178.92	181.97	3.05	3.03	99	3.03	99	15	3	5	3	2	3	181.42-181.62m =healed go 35 to c.a.
213	181.97	185.01	3.04	3.10	102	2.75	90	14	3	5	8	1	2	183.42-183.65m=shear with go 50 to c.a.
213	185.01	188.06	3.05	2.93	96	2.93	96	15	4	6	4	2	3	gouge on fractures
213	188.06	191.11	3.05	3.12	102	3.12	102	15	4	6	4	2	3	
213	191.11	194.16	3.05	2.98	98	2.98	98	15	4	6	3	2	3	
213	194.16	197.21	3.05	3.13	103	3.13	103	15	4	6	2	2	3	
213	197.21	200.25	3.04	3.07	101	2.90	95	15	4	6	2	3	3	
213	200.25	203.30	3.05	3.04	100	3.04	100	15	4	6	3	3	2	small 1cm shears
213	203.30	206.35	3.05	3.05	100	3.05	100	15	4	6	1	3	3	203.25-204.05= dmaf 25 to c.a.
213	206.35	209.40	3.05	3.10	102	3.10	102	15	4	6	0			
213	209.40	212.45	3.05	3.10	102	2.90	95	14	4	5	6	1	2	healed faulting
213	212.45	215.49	3.04	3.00	99	3.00	99	15	4	6	1	1	2	
213	215.49	218.54	3.05	3.10	102	3.10	102	15	4	6	0			
213	218.54	221.59	3.05	3.05	100	3.05	100	15	4	6	0			
213	221.59	224.64	3.05	3.00	98	3.00	98	15	4	6	3	1	3	
213	224.64	227.69	3.05	3.10	102	3.10	102	15	4	6	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
213	227.69	230.73	3.04	3.10	102	3.10	102	15	4	6	2	3	2	
213	230.73	233.78	3.05	3.00	98	3.00	98	15	4	6	2	4	3	
213	233.78	236.83	3.05	3.05	100	3.05	100	15	4	6	3	3	1	
213	236.83	239.88	3.05	3.25	107	3.25	107	15	4	6	2	1	2	
213	239.88	242.93	3.05	3.00	98	3.00	98	15	4	6	2	1	2	
213	242.93	245.97	3.04	2.85	94	2.85	94	15	4	6	4	1	2	
213	245.97	249.02	3.05	3.35	110	3.35	110	15	4	6	3	3	2	
213	249.02	252.07	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
213	252.07	255.12	3.05	3.20	105	3.00	98	15	4	6	3	3	1	
213	255.12	258.17	3.05	2.80	92	2.80	92	15	4	6	0			
213	258.17	261.21	3.04	3.04	100	3.04	100	15	4	6	1	1	2	
213	261.21	264.26	3.05	3.05	100	3.05	100	15	4	6	4	3	2	
213	264.26	267.31	3.05	3.05	100	2.85	93	15	4	6	3	1	1	
213	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	4	1	2	
213	270.36	273.41	3.05	2.80	92	0.47	15	5	4	6	30	1	2	2 very blocky -dpfh
213	273.41	276.45	3.04	2.55	84	0.42	14	5	4	6	30	1	2	2 very blocky -dpfh
213	276.45	279.50	3.05	2.98	98	2.78	91	15	4	6	3	1	2	
213	279.50	282.55	3.05	3.15	103	3.15	103	15	4	6	4	1	2	
213	282.55	285.60	3.05	2.90	95	2.90	95	15	4	6	0			
213	285.60	288.65	3.05	2.92	96	2.88	94	15	4	6	2	1		1 weak slicks, 45 to c.a.
213	288.65	291.69	3.04	3.02	99	3.02	99	15	4	6	0			
213	291.69	294.74	3.05	2.98	98	2.98	98	15	4	6	1	3	3	
213	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	2	1	3	
213	297.79	300.84	3.05	3.08	101	3.08	101	15	4	6	2	3	3	
213	300.84	303.89	3.05	3.05	100	3.05	100	15	4	6	2	1		1 weak slicks
213	303.89	306.93	3.04	2.98	98	2.98	98	15	4	6	1	2		1 slick, aprox 10 to c.a.
213	306.93	309.98	3.05	3.05	100	3.05	100	15	4	6	0			
213	309.98	313.03	3.05	3.05	100	3.05	100	15	4	6	1	3	3	
213	313.03	316.08	3.05	3.02	99	3.02	99	15	4	6	1	1	2	
213	316.08	319.13	3.05	3.10	102	3.00	98	14	4	6	6	3		3 10 cm fault 30 to c.a.
213	319.13	322.17	3.04	3.04	100	3.04	100	15	4	6	1	4	2	
213	322.17	325.22	3.05	3.05	100	2.90	95	15	4	6	5	1	2	
213	325.22	328.27	3.05	2.90	95	2.90	95	15	4	6	2	1	2	
213	328.27	331.32	3.05	3.15	103	3.10	102	15	4	6	2	3		3 1cm gouge on fracture 20 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
213	331.32	334.37	3.05	2.70	89	2.70	89	15	4	6	0			
213	334.37	337.41	3.04	3.04	100	3.04	100	15	4	6	2	3	2	
214	3.05	5.18	2.13	0.25	12	0.00	0	4	3	4	10	5	4	limonite; blocky and poor recovery
214	5.18	7.62	2.44	0.25	10	0.00	0	4	3	4	15	5	3	limonite; blocky and poor recovery
214	7.62	11.28	3.66	0.33	9	0.00	0	4	3	5	10	1	2	limonite; blocky and poor recovery
214	11.28	14.33	3.05	0.42	14	0.00	0	4	3	5	25	3	2	limonite; blocky and poor recovery
214	14.33	17.37	3.04	0.25	8	0.00	0	4	3	4	20	3	2	limonite; blocky and poor recovery
214	17.37	18.29	0.92	0.00	0	0.00	0							cave
214	18.29	20.42	2.13	0.30	14	0.00	0	4	3	5	15	3	2	blocky and poor recovery
214	20.42	22.25	1.83	0.65	36	0.00	0	3	3	4	10	5	3	blocky and poor recovery
214	22.25	25.30	3.05	3.05	100	1.80	59	12	3	5	15	1	2	
214	25.30	26.52	1.22	1.22	100	0.20	16	9	3	5	13	1	2	blocky
214	26.52	29.57	3.05	3.05	100	2.70	89	14	3	5	6	1	2	
214	29.57	32.61	3.04	2.75	90	1.57	52	8	3	5	20	1	3	blocky
214	32.61	35.66	3.05	3.16	104	2.90	95	14	3	5	9	1	2	
214	35.66	38.40	2.74	2.50	91	1.70	62	12	3	5	14	3	2	
214	38.40	41.45	3.05	3.05	100	2.70	89	14	3	5	10	1	2	
214	41.45	45.11	3.66	3.40	93	3.00	82	14	3	5	7	1	2	
214	45.11	47.85	2.74	2.60	95	2.00	73	12	3	5	14	3	2	
214	47.85	50.29	2.44	1.90	78	0.60	25	10	3	5	15	3	2	blocky
214	50.29	51.21	0.92	0.92	100	0.82	89	14	4	5	3	5	3	
214	51.21	53.95	2.74	2.62	96	2.25	82	14	4	6	6	1	2	gypsum veins
214	53.95	57.00	3.05	3.05	100	3.05	100	15	4	6	0			gypsum veins
214	57.00	60.05	3.05	3.15	103	3.15	103	15	4	6	2	1	2	gypsum veins
214	60.05	63.09	3.04	3.04	100	3.04	100	15	4	6	0			fractures along gypsum veins
214	63.09	66.14	3.05	3.05	100	3.05	100	15	4	6	0			gypsum veins
214	66.14	69.19	3.05	3.05	100	3.05	100	15	4	6	1	1	2	gypsum veins
214	69.19	72.24	3.05	3.05	100	3.05	100	15	4	6	0			fractures on gypsum veins
214	72.24	75.29	3.05	3.05	100	3.05	100	15	4	6	0			fractures on gypsum veins
214	75.29	78.33	3.04	3.04	100	2.80	92	15	4	6	3	1	2	fractures on gypsum veins
214	78.33	81.38	3.05	2.80	92	2.80	92	15	4	6	0			strong fractures on gypsum veins
214	81.38	84.43	3.05	3.05	100	3.05	100	15	4	6	0			strong fractures on gypsum veins
214	84.43	87.48	3.05	2.90	95	2.90	95	15	4	6	2	1	2	strong fractures on gypsum veins
214	87.48	90.53	3.05	2.85	93	2.85	93	15	4	6	3	1	2	strong fractures on gypsum veins

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
214	90.53	93.57	3.04	3.20	105	2.85	94	14	4	6	8	1	2 fractures on gypsum veins	
214	93.57	96.62	3.05	3.05	100	3.05	100	15	4	6	3	1	3	
214	96.62	99.67	3.05	3.05	100	3.05	100	15	4	6	2	5	4	
214	99.67	102.72	3.05	2.80	92	1.60	52	13	3	6	18	1	2	
214	102.72	105.77	3.05	3.00	98	3.00	98	15	4	6	0			gypsum on fractures
214	105.77	108.81	3.04	3.04	100	3.04	100	15	4	6	0			gypsum on fractures
214	108.81	111.86	3.05	3.00	98	2.60	85	14	4	6	9	3	3	
214	111.86	114.91	3.05	3.00	98	0.80	26	7	4	5	25	3	2	
214	114.91	117.96	3.05	2.80	92	0.72	24	7	4	5	25	1	2	
214	117.96	121.01	3.05	2.85	93	2.20	72	13	4	6	10	1	2	
214	121.01	124.05	3.04	3.15	104	2.70	89	14	4	6	7	1	3	2 cm gouge
214	124.05	127.10	3.05	2.30	75	1.05	34	12	4	6	13	3	2	
214	127.10	130.15	3.05	2.60	85	1.40	46	12	3	5	15	5	3	
214	130.15	133.20	3.05	3.10	102	2.75	90	14	4	6	6	3	3	
214	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6	0			
214	136.25	139.29	3.04	2.94	97	2.94	97	15	4	6	1	3	2	
214	139.29	142.34	3.05	3.15	103	3.15	103	15	4	6	1	1	2	
214	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	0			
214	145.39	148.44	3.05	3.05	100	3.05	100	15	4	6	1	1	3	3 fractures along gypsum veins
214	148.44	151.49	3.05	3.05	100	3.05	100	15	4	6	0			fractures along gypsum veins
214	151.49	154.53	3.04	3.04	100	3.04	100	15	4	6	0			fractures along gypsum veins
214	154.53	157.58	3.05	3.05	100	3.05	100	15	4	6	1	1	2	2 fractures along gypsum veins
214	157.58	160.63	3.05	3.05	100	3.05	100	15	4	6	0			fractures along gypsum veins
214	160.63	163.07	2.44	2.28	93	2.28	93	15	4	6	0			fractures along gypsum veins
214	163.07	166.12	3.05	3.15	103	3.15	103	15	4	6	3	3	2	2 fractures along gypsum veins
214	166.12	167.64	1.52	1.55	102	1.55	102	15	4	6	0			fractures along gypsum veins
214	167.64	169.77	2.13	2.30	108	2.30	108	15	4	6	0			fractures along gypsum veins
214	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	3	3	3	3 fractures along gypsum veins
214	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6	3	3	2	2 fractures along gypsum veins
214	175.87	178.92	3.05	3.05	100	3.05	100	15	4	6	2	1	1	1 fractures along gypsum veins
214	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	0			fractures along gypsum veins
214	181.97	185.01	3.04	3.04	100	3.04	100	15	4	6	0			fractures along gypsum veins
214	185.01	188.06	3.05	3.05	100	3.05	100	15	4	6	1	3	2	2 fractures along gypsum veins
214	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	0			fractures along gypsum veins

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
214	191.11	194.16	3.05	3.05	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6	1	1	3 fractures along gypsum veins
214	197.21	200.25	3.04	3.04	100	3.04	100	15	4	6	0		fractures along gypsum veins
214	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	1	1	2 fractures along gypsum veins
214	203.30	206.35	3.05	3.00	98	3.00	98	15	4	6	0		fractures along gypsum veins
214	206.35	209.40	3.05	3.10	102	3.10	102	15	4	6	1	1	2 fractures along gypsum veins
214	209.40	212.45	3.05	3.10	102	3.10	102	15	4	6	0		fractures along gypsum veins
214	212.45	215.49	3.04	3.04	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	215.49	218.54	3.05	3.05	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	218.54	221.59	3.05	3.00	98	3.00	98	15	4	6	0		fractures along gypsum veins
214	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	224.64	227.69	3.05	3.05	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	227.69	230.73	3.04	3.04	100	3.04	100	15	4	6	0		fractures along gypsum veins
214	230.73	233.78	3.05	3.00	98	3.00	98	15	4	6	2	1	3 10 cm fault gouge, gypsum on fractures
214	233.78	236.83	3.05	3.05	100	3.05	100	15	4	4	2	3	3 60 cm fault gouge, gypsum on fractures
214	236.83	239.88	3.05	3.05	100	3.05	100	15	3	5	2	3	2 fractures along gypsum veins
214	239.88	242.93	3.05	3.05	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	242.93	245.97	3.05	3.04	100	3.04	100	15	4	6	0		fractures along gypsum veins
214	245.97	249.02	3.05	3.05	100	3.05	100	15	4	6	0		fractures along gypsum veins
214	249.02	252.07	3.05	2.90	95	2.90	95	15	4	6	0		fractures along gypsum veins
214	252.07	255.12	3.05	3.10	102	3.10	102	15	4	6	2	1	2 fractures along gypsum veins
214	255.12	258.17	3.05	3.05	100	2.85	93	15	4	5	4	1	2 gouge sections, gypsum on fractures
214	258.17	261.21	3.05	3.04	100	2.94	96	15	3	5	1	3	2 fractures along gypsum veins
214	261.21	264.26	3.05	3.05	100	3.05	100	15	3	5	4	3	2 fractures along gypsum veins
214	264.26	267.31	3.05	3.05	100	3.05	100	15	4	6	1	3	2 fractures along gypsum veins
214	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	0		20 cm blocky due to drilling
214	270.36	273.41	3.05	3.03	99	3.03	99	15	4	6	5	2	3
214	273.41	276.45	3.04	3.04	100	3.04	100	15	4	6	0		
214	276.45	279.50	3.05	3.01	99	3.01	99	15	4	6	2	2	3
214	279.50	282.55	3.05	2.94	96	2.94	96	15	4	6	1	2	3 last 15 cm redrilled
214	282.55	285.60	3.05	3.10	102	3.10	102	15	4	6	4	1	3 first 5 cm redrilled, gypsum on fractures
214	285.60	288.65	3.05	3.05	100	3.05	100	15	4	6	0		
214	288.65	291.39	2.74	2.60	95	2.60	95	15	4	6	1	3	3 gypsum on fractures
214	291.39	294.44	3.05	3.05	100	3.05	100	15	4	6	1	1	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
214	294.44	297.48	3.04	3.01	99	3.01	99	15	4	6	3	3	3	
214	297.48	300.53	3.05	3.18	104	3.18	104	15	4	6	1	3	3	5 cm gouge 35 to c.a., H=3
214	300.53	303.58	3.05	2.96	97	2.96	97	15	4	6	4	2	3	minor gouge on fractures
214	303.58	306.63	3.05	2.84	93	2.84	93	13	3	5	10	3	3	gouge sections
214	306.63	309.68	3.05	2.95	97	2.72	89	13	4	6	11	2	3	
214	309.68	312.72	3.04	3.02	99	2.92	96	15	4	6	4	3	3	minor gouge on fractures
214	312.72	313.03	0.31	0.33	106	0.33	106	14	4	6	1	2	3	mineralized fractures
214	313.03	316.08	3.05	3.00	98	3.00	98	14	4	6	6	2	3	
214	316.08	319.13	3.05	3.05	100	2.88	94	14	4	6	7	3	3	minor gouge on fractures
214	319.13	322.17	3.04	3.12	103	2.89	95	14	4	6	7	2	3	20 cm gouge H=3
214	322.17	325.22	3.05	3.06	100	3.01	99	14	4	6	6	3	3	gouge on fractures
214	325.22	328.27	3.05	2.96	97	2.87	94	14	4	6	6	3	3	minor gouge sections
214	328.27	331.01	2.74	2.78	101	2.53	92	14	4	6	7	2	3	
214	331.01	334.06	3.05	3.05	100	3.05	100	15	4	6	2	3	3	5 cm gouge 20 to c.a. H=3
214	334.06	334.67	0.61	0.89	146	0.89	146	15	4	6	0			
215	6.10	8.23	2.13	0.40	19	0.00	0	5	3	4	10	1	2	limonite, blocky
215	8.23	11.28	3.05	1.65	54	0.60	20	7	3	5	15	3	2	limonite, blocky
215	11.28	14.33	3.05	2.45	80	1.18	39	7	3	5	20	1	2	limonite, blocky
215	14.33	17.37	3.04	1.64	54	0.40	13	6	3	5	25	3	2	limonite, blocky
215	17.37	20.42	3.05	2.80	92	0.72	24	6	3	6	25	1	4	blocky; gypsum veins
215	20.42	23.47	3.05	2.50	82	1.40	46	10	3	6	18	3	2	15 cm gouge, blocky, gypsum veins
215	23.47	26.52	3.05	3.05	100	3.05	100	15	3	6	3	3	1	fractures on gypsum veins
215	26.52	29.57	3.05	3.05	100	3.05	100	15	3	5	0			fractures on gypsum veins
215	29.57	32.61	3.04	3.04	100	3.04	100	15	3	5	1	3	3	fractures on gypsum veins
215	32.61	35.66	3.05	3.00	98	3.00	98	15	3	5	4	3	4	fractures on gypsum veins
215	35.66	38.71	3.05	3.10	102	3.10	102	15	3	5	5	4	4	fractures on gypsum veins
215	38.71	41.76	3.05	3.00	98	3.00	98	15	3	5	0			fractures on gypsum veins
215	41.76	44.81	3.05	3.10	102	3.10	102	15	3	5	0			fractures on gypsum veins
215	44.81	47.85	3.04	3.00	99	3.00	99	15	3	5	0			fractures on gypsum veins
215	47.85	50.90	3.05	2.85	93	2.85	93	15	3	5	1	1	3	fractures on gypsum veins
215	50.90	53.95	3.05	3.00	98	2.60	85	14	3	5	6	1	2	fractures on gypsum veins
215	53.95	57.00	3.05	3.05	100	3.05	100	15	3	5	3	3	1	fractures on gypsum veins
215	57.00	60.05	3.05	3.10	102	3.10	102	15	3	5	5	3	4	fractures on gypsum veins
215	60.05	63.09	3.04	3.04	100	3.04	100	15	3	5	0			fractures on gypsum veins

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
215	63.09	66.14	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	66.14	69.19	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	69.19	72.24	3.05	3.00	98	2.92	96	15	3	6	2	2		1 fractures on gypsum veins
215	72.24	75.29	3.05	3.20	105	3.00	98	15	3	6	5	5		4 fractures on gypsum veins
215	75.29	78.33	3.04	3.00	99	3.00	99	15	3	6	0			fractures on gypsum veins
215	78.33	81.38	3.05	2.90	95	2.90	95	15	3	6	1	1		2 fractures on gypsum veins
215	81.38	84.43	3.05	3.25	107	3.25	107	15	3	6	0			fractures on gypsum veins
215	84.43	87.48	3.05	2.85	93	2.85	93	15	3	6	1	3		2 fractures on gypsum veins
215	87.48	90.53	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	90.53	93.57	3.04	3.04	100	3.04	100	15	3	6	0			fractures on gypsum veins
215	93.57	96.62	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	96.62	99.67	3.05	3.00	98	3.00	98	15	3	6	1	3		2 fractures on gypsum veins
215	99.67	102.72	3.05	3.10	102	3.10	102	15	3	6	1	3		2 fractures on gypsum veins
215	102.72	105.77	3.05	3.08	101	3.08	101	15	3	6	0			fractures on gypsum veins
215	105.77	108.81	3.04	3.04	100	2.78	91	14	4	6	7	1		2 fractures on gypsum veins, fract'd dyke
215	108.81	111.86	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	111.86	114.91	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	114.91	117.96	3.05	3.05	100	3.05	100	15	3	6	3	1	2	
215	117.96	121.01	3.05	3.05	100	3.05	100	15	3	6	3	3	3	
215	121.01	124.05	3.04	2.85	94	2.80	92	15	3	6	3	1		1 5 cm gouge
215	124.05	127.10	3.05	3.15	103	3.10	102	15	3	6	3	4	3	
215	127.10	130.15	3.05	3.10	102	3.05	100	15	3	6	2	3	2	
215	130.15	133.20	3.05	3.08	101	3.08	101	15	3	6	2	3	2	
215	133.20	136.25	3.05	3.08	101	3.08	101	15	3	6	2	2	2	
215	136.25	139.29	3.04	3.10	102	3.10	102	15	3	6	2	5	3	
215	139.29	142.34	3.05	3.10	102	3.10	102	15	3	6	2	2	3	
215	142.34	145.39	3.05	3.05	100	3.05	100	15	3	6	3	3	2	
215	145.39	148.44	3.05	2.95	97	2.45	80	14	3	6	9	1	2	
215	148.44	151.49	3.05	2.90	95	2.25	74	13	3	5	12	1	2	
215	151.49	154.53	3.04	2.95	97	2.45	81	14	3	4	8	3		4 40 cm fault + gouge @ 15 to c.a.
215	154.53	157.58	3.05	3.05	100	2.75	90	14	3	5	7	3	1	
215	157.58	160.63	3.05	3.05	100	2.95	97	15	3	6	3	3		3 fractures on gypsum veins
215	160.63	163.68	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	163.68	166.73	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
215	166.73	169.77	3.04	3.04	100	3.04	100	15	3	6	1	1	1	1 fractures on gypsum veins
215	169.77	172.82	3.05	3.10	102	3.10	102	15	3	6	1	1	3	3 fractures on gypsum veins
215	172.82	175.87	3.05	3.00	98	3.00	98	15	3	6	0			fractures on gypsum veins
215	175.87	178.92	3.05	2.80	92	2.80	92	15	3	6	1	2	3	3 fractures on gypsum veins
215	178.92	181.97	3.05	3.10	102	3.10	102	15	3	6	0			fractures on gy veins, shear at 5 to c.a.
215	181.97	185.01	3.04	3.04	100	3.04	100	15	3	6	3	4	2	2 fractures on gypsum veins
215	185.01	188.06	3.05	3.25	107	3.25	107	15	3	6	0			fractures on gypsum veins
215	188.06	191.11	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	191.11	194.16	3.05	3.10	102	3.10	102	15	3	6	3	1	1	1 fractures on gypsum veins
215	194.16	197.21	3.05	3.08	101	3.08	101	15	3	6	2	4	2	2 fractures on gypsum veins
215	197.21	200.25	3.04	3.04	100	3.04	100	15	3	6	0			fractures on gypsum veins
215	200.25	203.30	3.05	2.95	97	2.95	97	15	3	6	2	3	4	4 fractures on gypsum veins
215	203.30	206.35	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	206.35	209.40	3.05	3.00	98	3.00	98	15	3	6	0			fractures on gypsum veins
215	209.40	212.45	3.05	3.15	103	3.15	103	15	3	6	0			fractures on gypsum veins
215	212.45	215.49	3.04	2.95	97	2.95	97	15	3	6	0			fractures on gypsum veins
215	215.49	218.54	3.05	3.05	100	2.85	93	15	3	6	4	1	2	2 fractures on gypsum veins
215	218.54	221.59	3.05	3.15	103	3.15	103	15	3	6	4	3	2	2 fractures on gypsum veins
215	221.59	224.64	3.05	3.05	100	3.05	100	15	3	6	1	3	2	2 fractures on gypsum veins
215	224.64	227.69	3.05	3.05	100	3.05	100	15	3	6	0			fractures on gypsum veins
215	227.69	230.73	3.04	3.00	99	3.00	99	15	3	6	1	1	1	1 fractures on gypsum veins
215	230.73	233.78	3.05	3.10	102	3.10	102	15	3	6	2	1	1	1 fractures on gypsum veins
215	233.78	236.83	3.05	3.02	99	3.02	99	15	4	6	2	1	1	1
215	236.83	239.88	3.05	3.10	102	3.10	102	15	4	6	2	1	1	1 70 cm of dyke, H=5
215	239.88	242.93	3.05	2.96	97	2.96	97	15	4	6	1	1	1	1 gouge on slip @ 55 to c.a.
215	242.93	245.97	3.04	3.16	104	3.16	104	15	4	6	3	1	1	1 slips on gypsum veins
215	245.97	249.02	3.05	3.07	101	3.07	101	15	4	6	4	1	1	1 trace gouge on slip @ 10 to c.a.
215	249.02	252.07	3.05	3.05	100	3.05	100	15	4	6	2	1	1	1
215	252.07	255.12	3.05	2.99	98	2.99	98	15	4	6	3	1	1	1 breaks on gypsum veins
215	255.12	258.17	3.05	3.10	102	3.10	102	15	4	6	2	1	1	1 breaks on gypsum veins
215	258.17	261.21	3.04	3.01	99	3.01	99	15	4	6	2	1	1	1 breaks on gypsum veins
215	261.21	264.26	3.05	3.00	98	3.00	98	15	4	6	4	1	1	1 breaks on 1 cm dykes
215	264.26	267.31	3.05	3.08	101	3.08	101	15	4	6	2	1	1	1 trace gouge on slip
215	267.31	270.36	3.05	2.94	96	2.85	93	15	4	6	3	1	1	1

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
215	270.36	273.41	3.05	3.07	101	2.84	93	14	4	6	8	1	1	1 gouge on slip
215	273.41	276.45	3.04	3.01	99	3.01	99	15	4	6	4	1	1	1 trace gouge on slips
215	276.45	279.50	3.05	3.11	102	3.11	102	15	4	6	3	1	1	1 trace gouge on slips
215	279.50	282.55	3.05	3.02	99	3.02	99	15	4	6	2	1	1	1 trace gouge on slips
215	282.55	285.60	3.05	3.03	99	3.03	99	15	4	6	1	1	1	1
215	285.60	288.65	3.05	3.03	99	3.03	99	15	4	6	1	1	1	1 local shears but only one break
215	288.65	291.69	3.04	2.93	96	2.93	96	15	4	6	2	1	1	1 last 10 cm is redrilled core
215	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	1	5	3	
215	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 trace gouge on slip
215	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	5	1	1	1 gouge on slips in shear zone
216	6.71	7.92	1.21	1.05	87	0.00	0	6	2	4	22	3	3	3 minor gouge
216	7.92	10.97	3.05	3.20	105	0.40	13	6	1	6	50	3	3	3 crushed rocks & gouge
216	10.97	12.19	1.22	0.95	78	0.00	0	6	1	6	18	2	1	1 crushed rocks, minor slickensides
216	12.19	14.63	2.44	2.10	86	0.00	0	7	1	6	33	1	2	
216	14.63	17.37	2.74	2.70	99	0.70	26	10	2	6	18	1	2	2 healed crush zone; minor gouge
216	17.37	20.12	2.75	0.65	24	0.00	0	5	1	6	17	2	1	1 crush & minor gouge at 30 to c.a.
216	20.12	21.03	0.91	0.57	63	0.00	0	7	2	6	9	2	2	2 minor zones of crush & gouge
216	21.03	23.47	2.44	2.65	109	1.75	72	12	2	6	14	2	1	1 minor gouge on shears at 30 to c.a.
216	23.47	25.91	2.44	2.65	109	1.30	53	10	2	6	20	2	1	1 minor gouge on shears at 30 to c.a.
216	25.91	28.35	2.44	2.30	94	1.05	43	9	2	6	25	3	1	1 minor gouge
216	28.35	29.57	1.22	1.30	107	0.45	37	10	2	6	12	3	1	1 minor gouge
216	29.57	32.61	3.04	2.90	95	1.25	41	10	2	6	24	3	2	2 minor crush zone
216	32.61	35.66	3.05	2.92	96	2.63	86	13	2	6	10	3	1	1 one gougy slip; rest fractures 3/3
216	35.66	38.71	3.05	2.90	95	2.32	76	13	2	6	13	3	1	1 minor crush zones to cm w/ slickensides
216	38.71	41.76	3.05	3.05	100	2.70	89	13	2	6	12	1	2	2 minor crush zones; no slickensides
216	41.76	44.81	3.05	3.10	102	2.50	82	13	2	6	13	1	1	1 crush zone to 1 m with slickensides
216	44.81	47.85	3.04	3.00	99	1.83	60	12	2	6	18	2	1	
216	47.85	50.90	3.05	3.10	102	3.10	102	14	3	6	9	3	3	
216	50.90	53.95	3.05	3.10	102	3.00	98	14	3	6	10	1	1	1 several smooth joints in interval
216	53.95	57.00	3.05	3.00	98	1.93	63	13	3	6	11	1	2	
216	57.00	60.05	3.05	3.00	98	2.85	93	14	3	6	8	3	2	
216	60.05	63.09	3.04	3.10	102	2.50	82	13	3	6	12	2	1	
216	63.09	66.14	3.05	3.10	102	3.10	102	15	3	6	5	3	3	
216	66.14	69.19	3.05	3.10	102	2.90	95	14	3	6	6	3	2	2 30 cm crush zone at end of interval

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
216	69.19	72.24	3.05	3.10	102	2.45	80	13	2	6	11	3	1	most of interval is healed crush
216	72.24	75.29	3.05	3.00	98	2.80	92	13	3	6	10	1	1	minor gouge on few fractures
216	75.29	78.33	3.04	3.05	100	2.60	86	14	3	6	9	3	1	
216	78.33	81.38	3.05	3.03	99	3.03	99	14	3	6	8	3	2	minor gouge on one surface
216	81.38	84.43	3.05	3.05	100	3.05	100	15	3	6	5	1	2	most fractures are 3/3
216	84.43	87.48	3.05	3.03	99	2.70	89	14	2	6	8	2	1	last metre is healed crush zone
216	87.48	90.53	3.05	3.00	98	2.85	93	14	2	6	8	3	2	
216	90.53	93.57	3.04	3.10	102	3.00	99	14	2	6	9	3	1	
216	93.57	96.62	3.05	2.97	97	2.77	91	13	3	6	14	1	1	
216	96.62	99.67	3.05	3.10	102	3.10	102	14	3	6	6	2	1	
216	99.67	102.72	3.05	3.08	101	3.08	101	14	3	6	6	1	2	pyrite on some fractures
216	102.72	105.77	3.05	3.05	100	3.05	100	14	3	6	10	1	2	minor gouge on fractures surfaces
216	105.77	108.81	3.04	3.00	99	3.00	99	15	3	6	5	3	3	
216	108.81	111.86	3.05	3.05	100	3.05	100	14	3	6	7	3	3	minor zones of healed crush at 30 to c.a.
216	111.86	114.91	3.05	3.05	100	2.95	97	14	3	6	8	3	2	
216	114.91	117.96	3.05	3.03	99	3.03	99	14	2	6	9	1	2	minor zones of healed crush
216	117.96	121.01	3.05	3.05	100	1.20	39	10	2	6	24	3	2	healed crush; minor gouge; shrs 50 to c.a.
216	121.01	124.05	3.04	3.15	104	2.10	69	13	1	6	15	3	2	poorly healed crush; gouge; 30 to c.a.
216	124.05	127.10	3.05	3.00	98	2.15	70	13	1	6	12	3	3	upper same; more competent w/ depth
216	127.10	130.15	3.05	3.15	103	1.25	41	10	2	6	24	1	2	
216	130.15	133.20	3.05	3.00	98	2.00	66	12	3	6	17	2	2	
216	133.20	136.25	3.05	2.80	92	1.80	59	10	3	6	24	2	2	134.44-135 m - rubble; some healed crush
216	136.25	139.29	3.04	3.20	105	2.25	74	12	3	6	19	1	2	
216	139.29	142.34	3.05	3.15	103	1.34	44	9	3	6	36	2	2	
216	142.34	145.39	3.05	3.05	100	3.05	100	15	3	6	5	3	3	
216	145.39	148.44	3.05	3.10	102	3.10	102	14	3	6	6	2	2	minor gouge on one slip
216	148.44	151.49	3.05	3.15	103	2.90	95	14	3	6	8	2	2	
216	151.49	154.53	3.04	3.00	99	3.00	99	15	3	6	4	2	1	one polished fracture; others rough
216	154.53	157.58	3.05	3.10	102	3.10	102	15	3	6	5	3	3	
216	157.58	160.63	3.05	3.20	105	2.95	97	14	3	6	9	3	3	
216	160.63	163.68	3.05	2.84	93	2.84	93	14	3	6	6	3	2	most fractures rough
216	163.68	166.73	3.05	3.15	103	2.45	80	12	3	6	17	3	3	minor gouge on shears at 30 to c.a.
216	166.73	169.77	3.04	3.00	99	2.82	93	14	3	6	9	2	2	
216	169.77	172.82	3.05	3.05	100	2.87	94	14	3	6	9	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
216	172.82	175.87	3.05	3.10	102	2.57	84	13	3	6	13	2	2	
216	175.87	178.92	3.05	3.00	98	2.90	95	14	3	6	9	2	2	176.8 - 177.25 m-healed shear zone 35 to c.a.
216	178.92	181.05	2.13	2.05	96	0.45	21	9	3	6	22	2	2	
216	181.05	184.10	3.05	3.20	105	1.28	42	10	2	6	31	1	2	2 healed crush zone to 40 cm 40-70 to c.a.
216	184.10	185.10	1.00	0.90	90	0.15	15	9	3	6	11	1	2	2 blocky core
216	185.10	188.06	2.96	3.15	106	2.65	90	13	3	6	14	2	2	
216	188.06	191.11	3.05	3.10	102	2.75	90	15	3	6	5	3	2	
216	191.11	194.16	3.05	3.05	100	3.05	100	14	3	6	6	2	3	3 pyrite on fracture surfaces
216	194.16	197.21	3.05	3.03	99	3.03	99	15	3	6	5	1	2	
216	197.21	200.25	3.04	3.15	104	3.15	104	15	3	6	5	2	2	
216	200.25	203.30	3.05	3.01	99	3.01	99	14	3	6	7	1	3	
216	203.30	206.35	3.05	3.10	102	2.90	95	15	3	6	5	3	2	
216	206.35	209.40	3.05	3.00	98	2.80	92	14	3	6	9	1	2	
216	209.40	212.45	3.05	3.10	102	3.00	98	14	3	6	6	2	2	
216	212.45	215.49	3.04	3.08	101	2.88	95	14	3	6	8	2	2	
216	215.49	218.54	3.05	3.00	98	2.85	93	14	3	6	7	3	2	
216	218.54	221.59	3.05	3.05	100	3.05	100	14	3	6	10	1	2	
216	221.59	224.64	3.05	3.08	101	2.28	75	13	3	6	14	1	2	
216	224.64	227.69	3.05	3.20	105	2.30	75	10	3	6	23	3	2	2 crush zones & minor gouge to 20 cm
216	227.69	230.73	3.04	3.20	105	0.80	26	8	3	6	45	1	2	2 blocky core; minor gouge; crush zones
216	230.73	233.78	3.05	3.00	98	1.25	41	10	2	6	24	2	2	
216	233.78	236.83	3.05	3.20	105	2.90	95	13	3	6	11	2	3	
216	236.83	239.88	3.05	3.00	98	2.60	85	13	3	6	14	3	2	
216	239.88	242.93	3.05	3.10	102	2.75	90	13	2	6	11	1	2	2 weak crush zone; graphitic(?) slips
216	242.93	245.97	3.04	3.10	102	3.00	99	14	4	6	7	2	2	
216	245.97	249.02	3.05	3.05	100	2.90	95	14	4	6	8	3	3	
216	249.02	252.07	3.05	2.85	93	2.70	89	14	4	6	6	2	2	
216	252.07	255.12	3.05	3.00	98	2.90	95	14	4	6	7	1	3	
216	255.12	258.17	3.05	3.10	102	3.00	98	14	4	6	6	1	2	2 minor ground rocks on few surfaces
216	258.17	261.21	3.04	3.10	102	3.10	102	15	4	6	5	1	3	3 minor ground rocks; trace gouge
216	261.21	264.26	3.05	3.10	102	3.10	102	14	4	6	6	2	2	
216	264.26	267.31	3.05	3.10	102	3.10	102	15	4	6	4	3	2	2 pyrite on some fractures
216	267.31	270.36	3.05	3.05	100	3.05	100	15	4	6	1	5	4	4 vug-like cavity
216	270.36	273.41	3.05	3.05	100	3.05	100	15	4	6				

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
216	273.41	276.45	3.04	3.05	100	3.05	100	15	4	6	1	1	1	1 slick at 25 to c.a.
216	276.45	279.50	3.05	3.08	101	3.08	101	15	4	6				
216	279.50	282.55	3.05	3.05	100	3.05	100	15	4	6	3	1	3	3 pyrite on fractures
216	282.55	285.60	3.05	3.05	100	3.05	100	15	4	6	2	3	3	
216	285.60	288.65	3.05	2.85	93	2.64	87	13	4	6	14	1	1	1 20 cm of gouge; slick at 30 to c.a.
216	288.65	291.69	3.04	3.18	105	3.18	105	15	4	6	4	3	3	
216	291.69	294.74	3.05	2.94	96	2.94	96	15	4	6	5	3	3	
216	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	3	1	3	
216	297.79	300.84	3.05	3.11	102	3.08	101	15	4	6	6	1	1	1 3 cm of partly healed shear
216	300.84	303.89	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 slick contact at 45 to c.a.
216	303.89	306.93	3.04	2.98	98	2.98	98	15	5	6	1	1	1	1 dyke material; very hard
216	306.93	309.98	3.05	3.05	100	3.05	100	15	3	6	2	1	1	1 slick contact at 50 to c.a.
216	309.98	313.03	3.05	3.18	104	3.18	104	15	3	6	5	1	1	2 sections of healed gouge
216	313.03	316.08	3.05	2.97	97	2.97	97	15	3	6	5	1	1	2 sections of healed gouge
216	316.08	319.13	3.05	3.05	100	3.05	100	15	4	6				
216	319.13	322.17	3.04	3.05	100	3.05	100	15	4	6				
216	322.17	325.22	3.05	3.05	100	3.05	100	15	4	6	1	1	1	1 weak slick
216	325.22	328.27	3.05	3.05	100	3.05	100	15	4	6				
216	328.27	331.32	3.05	3.05	100	3.05	100	15	5	6				quartz flooded; well mineralized
216	331.32	334.37	3.05	2.99	98	2.99	98	15	5	6	2	1	1	2 quartz flooded; well mineralized
216	334.37	337.41	3.04	2.98	98	2.98	98	15	5	6	1	3	3	3 quartz flooded; well mineralized
216	337.41	340.46	3.05	3.02	99	3.02	99	15	5	6	2	3	3	
216	340.46	343.51	3.05	3.17	104	3.17	104	15	5	6	1	1	4	
216	343.51	346.56	3.05	3.00	98	3.00	98	15	4	6	1	1	4	
216	346.56	349.61	3.05	3.00	98	3.00	98	15	4	6	1	1	1	1 slick at 60 to c.a.
216	349.61	352.65	3.04	3.10	102	3.09	102	15	4	6	3	1	1	1 1 cm of gouge; slip plane
216	352.65	355.70	3.05	3.08	101	3.08	101	15	4	6	1	3	3	
216	355.70	358.75	3.05	3.02	99	3.02	99	15	5	6				
216	358.75	361.30	2.55	2.53	99	2.53	99	15	5	6	1	1	1	2 cave; fracture/contact at 60 to c.a.
216	361.30	364.24	2.94	2.97	101	2.77	94	15	4	6	6	3	3	3 cave, rubble & gouge zones
216	364.24	367.28	3.04	2.89	95	2.89	95	15	4	6	3	3	3	
216	367.28	370.33	3.05	2.40	79	2.40	79	15	4	6				
216	370.33	373.38	3.05	3.10	102	2.10	69	15	5	6	5	3	3	3 pyrite on fractures
216	373.38	376.43	3.05	3.02	99	3.02	99	15	5	6	2	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
216	376.43	379.48	3.05	3.15	103	3.15	103	15	5	6	3	1	3 quartz flooding; very hard	
216	379.48	382.52	3.04	2.98	98	2.98	98	15	5	6	3	3	3 quartz flooding; very hard	
216	382.52	385.57	3.05	3.05	100	3.05	100	15	5	6			quartz flooding; very hard	
216	385.57	388.62	3.05	3.05	100	3.05	100	15	5	6			quartz flooding; very hard	
216	388.62	391.67	3.05	3.00	98	3.00	98	15	5	6	3	1	1 quartz flooding; very hard; weak slick	
216	391.67	394.72	3.05	3.10	102	3.10	102	15	5	6	2	1	1 quartz flooding; very hard	
216	394.72	397.76	3.04	3.07	101	3.07	101	15	5	6	1	1	1 quartz flooding; very hard	
216	397.76	400.81	3.05	2.96	97	2.95	97	15	5	6	1	1	1 strong slick at 40 to c.a.; quartz flooding	
216	400.81	401.12	0.31	0.37	119	0.34	110	15	4	6	1	1	1 gouge and faulting	
216	401.12	404.47	3.35	3.45	103	3.30	99	14	4	6	6	3	2	
216	404.47	407.52	3.05	3.15	103	3.15	103	15	4	6	1	3	1	
216	407.52	410.57	3.05	2.80	92	2.65	87	15	4	6	4	4	1	
216	410.57	413.61	3.04	3.04	100	3.04	100	15	4	6	2	3	2	
216	413.61	416.66	3.05	2.90	95	2.65	87	15	4	6	4	1	2 gypsum on fractures	
216	416.66	419.71	3.05	3.00	98	3.00	98	15	5	6	3	1	2 gy on fractures; X-joints on gy fractures	
216	419.71	422.76	3.05	2.65	87	2.35	77	14	5	6	7	1	2 gy on fractures; 30 cm shear & fracturing	
216	422.76	424.28	1.52	1.52	100	1.12	74	13	5	6	6	1	2 gypsum on fractures and veins	
216	424.28	425.81	1.53	1.60	105	1.60	105	15	5	6	2	1	2 gypsum on fractures	
216	425.81	428.85	3.04	2.90	95	2.50	82	14	5	6	5	3	3 gypsum on fractures	
216	428.85	431.90	3.05	3.00	98	1.95	64	14	5	6	9	1	2 gypsum on fractures	
216	431.90	434.95	3.05	3.10	102	2.50	82	14	4	6	10	1	2	
216	434.95	438.00	3.05	2.80	92	2.65	87	15	4	6	3	3	2 1 cm shear at 45 to c.a.	
217	3.05	5.18	2.13	1.19	56	0.77	36	9	4	5	15	2	3 6 cm gouge	
217	5.18	8.23	3.05	2.90	95	1.50	49	9	4	5	30	1	3	
217	8.23	11.28	3.05	2.95	97	1.38	45	10	4	5	25	3	3 minor gouge & pyrite on fractures	
217	11.28	14.33	3.05	2.15	70	1.00	33	9	4	5	23	2	3	
217	14.33	17.37	3.04	2.31	76	2.15	71	7	3	5	35	3	3 minor gouge	
217	17.37	20.42	3.05	2.50	82	2.10	69	13	3	4	12	2	3 fault starts @ 17.90 m	
217	20.42	23.47	3.05	3.12	102	2.92	96	15	3	4	5	5	3 fault	
217	23.47	26.52	3.05	2.13	70	1.37	45	7	3	4	30	5	3 fault; 40% gouge	
217	26.52	29.57	3.05	1.87	61	1.33	44	10	3	4	15	3	3 fault; 30% gouge	
217	29.57	32.61	3.04	2.96	97	2.93	96	15	3	4	3	2	2 fault	
217	32.61	35.66	3.05	2.55	84	1.96	64	9	3	4	27	2	2 fault	
217	35.66	38.71	3.05	2.01	66	1.63	53	9	3	4	22	2	2 fault ends at 38.55 m	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
217	38.71	41.76	3.05	1.68	55	0.98	32	9	4	4	20	3	3	30% broken with gouge
217	41.76	44.81	3.05	2.02	66	1.13	37	9	4	5	25	2	3	10% gouge
217	44.81	47.85	3.04	2.51	83	2.04	67	10	4	4	24	3	3	15% gouge; gouge on fractures
217	47.85	50.90	3.05	2.43	80	1.65	54	10	3	4	20	2	3	
217	50.90	53.95	3.05	2.41	79	1.36	45	9	4	5	25	2	3	pyrite on fractures
217	53.95	57.00	3.05	1.96	64	1.89	62	7	4	5	30	2	3	gouge on fractures
217	57.00	60.05	3.05	2.10	69	0.97	32	7	4	4	30	3	3	
217	60.05	63.09	3.04	2.89	95	2.18	72	12	3	4	18	1	3	minor gouge on fractures
217	63.09	66.14	3.05	3.03	99	3.03	99	15	3	4	5	3	3	
217	66.14	69.19	3.05	3.12	102	2.90	95	14	4	4	6	2	3	
217	69.19	72.24	3.05	2.70	89	1.78	58	10	4	4	25	1	3	25% broken with minor gouge
217	72.24	75.29	3.05	2.90	95	2.52	83	13	4	5	14	2	3	minor gouge on fractures
217	75.29	78.33	3.04	3.20	105	2.06	68	10	4	5	25	1	2	
217	78.33	81.38	3.05	2.91	95	2.04	67	10	4	5	27	1	2	
217	81.38	84.43	3.05	3.05	100	2.57	84	12	4	5	16	2	3	gouge on fractures
217	84.43	87.48	3.05	2.95	97	1.92	63	9	4	5	30	2	3	minor gouge on fractures
217	87.48	90.53	3.05	2.58	85	1.67	55	10	3	4	25	3	3	gouge on fractures
217	90.53	93.57	3.04	3.04	100	1.90	63	10	4	5	30	2	3	gouge on fractures
217	93.57	96.62	3.05	2.55	84	0.87	29	9	4	5	28	1	2	pyrite on fractures
217	96.62	99.67	3.05	2.53	83	1.50	49	10	4	5	20	1	2	55 cm gouge, H=3
217	99.67	102.72	3.05	3.16	104	2.88	94	14	4	5	9	2	3	minor gouge on fractures
217	102.72	105.77	3.05	2.70	89	1.96	64	10	4	5	23	2	3	
217	105.77	108.81	3.04	2.05	67	0.80	26	7	5	5	35	1	2	
217	108.81	110.95	2.14	2.28	107	1.70	79	10	5	5	18	2	2	
217	110.95	111.86	0.91	0.91	100	0.41	45	7	4	4	16	3	3	gouge on fractures
217	111.86	114.91	3.05	2.86	94	2.65	87	14	3	4	7	2	2	
217	114.91	117.96	3.05	2.68	88	2.36	77	14	4	4	7	2	3	
217	117.96	119.79	1.83	0.93	51	0.12	7	6	4	4	25	2	3	50% broken core with gouge
217	119.79	121.01	1.22	1.09	89	0.54	44	9	4	4	12	1	2	pyrite on fractures
217	121.01	123.44	2.43	2.30	95	1.55	64	9	4	4	30	1	2	pyrite on fractures; 35% broken core
217	123.44	126.80	3.36	3.16	94	2.51	75	10	5	6	24	1	2	dyke starts at 125.10 m.
217	126.80	129.54	2.74	2.93	107	2.47	90	12	5	6	16	2	2	dyke
217	129.54	132.59	3.05	3.01	99	1.25	41	10	5	6	30	1	2	dyke ends at 130.35 m.
217	132.59	133.20	0.61	0.70	115	0.12	20	9	4	5	9	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
217	133.20	134.42	1.22	1.15	94	0.34	28	7	4	5	18	1	2	
217	134.42	136.25	1.83	1.27	69	0.00	0	6	4	5	40	3	3	100% broken with gouge
217	136.25	139.29	3.04	3.04	100	2.86	94	14	3	5	9	3	3	gouge on fractures
217	139.29	141.12	1.83	1.75	96	0.60	33	7	5	5	27	2	3	gouge on fractures
217	141.12	143.26	2.14	2.26	106	2.26	106	15	3	4	1	2	2	fault starts at 141.41 m
217	143.26	145.39	2.13	2.10	99	2.10	99	15	3	4	2	1	2	fault
217	145.39	148.44	3.05	3.05	100	2.72	89	12	3	4	17	2	3	fault
217	148.44	151.49	3.05	3.05	100	2.82	92	14	3	4	6	2	3	fault
217	151.49	154.53	3.04	3.08	101	3.08	101	15	3	4	1	1	3	fault
217	154.53	157.58	3.05	2.76	90	2.30	75	13	3	4	13	3	3	fault ends at 156.65 m
217	157.58	159.72	2.14	2.07	97	0.98	46	7	4	5	30	1	2	
217	159.72	161.85	2.13	1.11	52	0.38	18	7	4	5	18	2	2	50% broken core
217	161.85	163.07	1.22	0.99	81	0.11	9	6	4	5	20	2	2	70% broken core
217	163.07	164.29	1.22	1.27	104	0.19	16	7	4	4	18	3	3	50% broken core
217	164.29	165.81	1.52	1.03	68	0.00	0	6	4	4	30	3	3	100% broken core
217	165.81	168.55	2.74	1.96	72	1.06	39	9	4	4	25	2	3	minor gouge
217	168.55	169.77	1.22	0.92	75	0.20	16	7	4	5	15	2	3	
217	169.77	172.82	3.05	0.73	24	0.31	10	6	4	5	17	2	3	
217	172.82	174.04	1.22	0.76	62	0.19	16	7	4	5	15	3	3	fault starts at 172.95 m; 45% broken core
217	174.04	175.87	1.83	1.76	96	1.73	95	14	3	4	4	3	3	fault
217	175.87	178.92	3.05	3.07	101	2.87	94	14	3	4	6	5	3	fault
217	178.92	181.97	3.05	3.03	99	3.03	99	15	3	4	1	2	2	fault
217	181.97	185.01	3.04	3.15	104	3.06	101	15	4	4	2	3	3	gouge on fractures
217	185.01	188.06	3.05	2.93	96	2.67	88	13	4	5	11	3	3	gouge on fractures
217	188.06	191.11	3.05	3.05	100	3.05	100	15	5	5	1	2	3	
217	191.11	194.16	3.05	3.05	100	2.83	93	13	5	5	11	2	3	
217	194.16	197.21	3.05	3.00	98	2.86	94	14	5	5	5	3	3	
217	197.21	200.25	3.04	3.00	99	2.65	87	12	5	5	15	2	3	
217	200.25	203.30	3.05	2.88	94	2.61	86	13	5	5	12	3	3	
217	203.30	206.35	3.05	3.08	101	2.96	97	14	4	5	6	2	3	
217	206.35	209.40	3.05	2.82	92	1.92	63	10	4	5	25	3	3	
217	209.40	212.45	3.05	3.08	101	2.20	72	10	4	5	23	3	3	gouge on fractures
217	212.45	215.49	3.04	2.80	92	2.65	87	14	4	5	9	3	3	minor gouge on fractures
217	215.49	218.54	3.05	3.05	100	2.93	96	14	4	5	8	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
217	218.54	221.59	3.05	2.93	96	2.93	96	15	4	5	2	2	3	
217	221.59	224.64	3.05	3.28	108	2.87	94	13	4	5	14	3	3	gouge on fractures
217	224.64	227.69	3.05	2.98	98	2.55	84	12	3	5	16	3	3	
217	227.69	230.12	2.43	2.26	93	1.25	51	10	4	5	18	2	2	
217	230.12	231.95	1.83	2.05	112	1.76	96	10	4	5	14	2	3	gouge on fractures
217	231.95	233.78	1.83	1.92	105	1.92	105	15	3	4	2	2	2	70 cm of healed gouge
217	233.78	236.83	3.05	3.07	101	3.02	99	15	3	4	4	2	3	
217	236.83	239.88	3.05	3.00	98	3.00	98	14	3	4	6	3	2	
217	239.88	241.71	1.83	1.87	102	1.01	55	7	4	5	27	3	3	50% broken core
217	241.71	244.75	3.04	2.91	96	2.61	86	13	4	5	12	3	3	
217	244.75	247.80	3.05	3.05	100	2.79	91	14	4	5	8	2	3	gouge on fractures
217	247.80	250.24	2.44	2.38	98	2.17	89	13	4	5	9	3	3	gouge on fractures
217	250.24	253.29	3.05	3.05	100	2.94	96	14	4	5	10	1	2	
218	6.10	8.53	2.43	1.15	47	0.00	0	6	0	1	50	1	1	1 fault zone; very weak fabric
218	8.53	9.75	1.22	0.61	50	0.00	0	6	1	4	30	1	3	fault zone; very weak fabric
218	9.75	11.28	1.53	0.93	61	0.12	8	6	2	4	27	1	3	fault zone; very weak fabric
218	11.28	14.33	3.05	2.95	97	2.21	72	12	3	5	19	1	2	healed gouge-filled fractures
218	14.33	15.54	1.21	1.20	99	0.55	45	7	3	5	17	1	2	healed gouge-filled fractures
218	15.54	18.59	3.05	2.58	85	2.21	72	12	3	5	13	1	1	very slick, gouge-filled fractures at 22 to c.a.
218	18.59	21.03	2.44	1.56	64	1.07	44	9	3	5	19	1	2	gouge-filled fractures
218	21.03	22.86	1.83	1.31	72	0.83	45	9	4	5	17	1	2	start of fault with 30% gouge
218	22.86	25.91	3.05	2.86	94	0.69	23	7	1	3	50	1	1	fault zone; shearing
218	25.91	28.65	2.74	1.11	41	0.00	0	6	1	3	40	1	1	very heavy gouge
218	28.65	30.16	1.51	0.65	43	0.00	0	6	1	3	21	1	1	slick at 15 to c.a.
218	30.16	31.70	1.54	1.13	73	0.43	28	7	1	3	18	1	1	fault
218	31.70	34.75	3.05	2.92	96	0.48	16	9	1	3	30	1	1	fault
218	34.75	35.66	0.91	0.68	75	0.37	41	7	1	3	13	1	1	fault
218	35.66	38.71	3.05	2.77	91	0.72	24	10	2	4	22	1	1	fault 45 to c.a.; very slick; cont at 38.05 m.
218	38.71	39.93	1.22	1.15	94	0.62	51	7	4	6	18	3	3	
218	39.93	40.54	0.61	0.36	59	0.00	0	6	2	4	12	1	1	gouge & fault material
218	40.54	42.00	1.46	1.48	101	1.48	101	15	4	6	1	1	3	
218	42.00	44.81	2.81	2.55	91	2.55	91	15	4	6	3	3	3	redrilled core; 60 cm
218	44.81	46.94	2.13	2.09	98	1.87	88	13	4	6	10	2	3	
218	46.94	48.46	1.52	1.30	86	1.12	74	14	4	6	4	1	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
218	48.46	50.90	2.44	2.20	90	1.84	75	12	4	6	13	1	2	
218	50.90	53.95	3.05	2.71	89	2.66	87	14	4	6	6	1	2	pyrite on fractures
218	53.95	55.47	1.52	1.82	120	1.73	114	14	4	6	4	2	3	
218	55.47	57.00	1.53	1.43	93	1.21	79	14	4	6	4	3	3	
218	57.00	60.05	3.05	2.80	92	1.97	65	12	4	6	14	2	3	
218	60.05	62.79	2.74	2.74	100	2.47	90	14	4	6	8	1	2	
218	62.79	65.84	3.05	3.05	100	2.91	95	13	4	6	11	1	2	
218	65.84	68.88	3.04	3.01	99	2.89	95	14	4	6	9	3	3	
218	68.88	71.93	3.05	3.10	102	3.10	102	15	5	6	5	3	3	
218	71.93	74.98	3.05	3.11	102	2.93	96	14	5	6	8	2	3	
218	74.98	78.03	3.05	2.92	96	2.50	82	13	4	5	11	3	3	gouge on fractures
218	78.03	81.08	3.05	3.05	100	3.05	100	15	4	6	2	3	3	minor gouge on fractures
218	81.08	83.82	2.74	2.33	85	2.33	85	15	4	6	2	3	3	pyrite on fractures
218	83.82	86.87	3.05	3.18	104	3.18	104	15	4	6	3	3	3	pyrite on fractures
218	86.87	88.70	1.83	1.93	105	1.81	99	14	4	6	5	2	2	pyrite on fractures
218	88.70	90.53	1.83	1.91	104	1.80	98	14	4	6	4	1	2	
218	90.53	93.57	3.04	2.97	98	2.97	98	15	4	6	3	2	3	
218	93.57	96.62	3.05	3.03	99	3.03	99	15	4	6	2	3	3	
218	96.62	99.67	3.05	3.07	101	3.05	100	14	4	6	7	2	2	healed gouge-filled fractures at 15 to c.a.
218	99.67	102.72	3.05	3.08	101	2.78	91	14	4	6	10	2	3	gouge on fractures
218	102.72	105.77	3.05	3.02	99	2.95	97	14	4	6	7	2	3	pyrite on fractures
218	105.77	108.81	3.04	2.60	86	2.25	74	12	3	5	13	3	3	gouge on fractures
218	108.81	111.86	3.05	2.97	97	2.65	87	13	3	5	14	3	3	fault 110.73-111.55 m; gouge on fractures
218	111.86	114.60	2.74	2.50	91	1.76	64	10	4	6	22	3	3	gouge on fractures
218	114.60	117.04	2.44	2.41	99	1.91	78	13	4	6	10	1	2	healed gouge-filled fractures
218	117.04	120.09	3.05	3.15	103	2.95	97	14	4	6	10	2	3	
218	120.09	122.22	2.13	2.19	103	1.98	93	13	4	6	9	2	3	minor shearing
218	122.22	123.75	1.53	1.22	80	0.82	54	9	4	6	13	2	3	
218	123.75	126.80	3.05	3.07	101	2.95	97	13	4	6	13	2	3	
218	126.80	129.84	3.04	2.76	91	2.20	72	12	4	5	15	3	3	gouge on fractures
218	129.84	131.37	1.53	1.53	100	1.40	92	12	4	5	8	3	3	
218	131.37	133.20	1.83	1.69	92	1.33	73	9	4	5	20	1	2	5% broken core
218	133.20	135.03	1.83	1.80	98	1.75	96	13	4	5	7	1	2	
218	135.03	138.07	3.04	2.81	92	2.62	86	13	4	5	13	3	3	minor gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
218	138.07	139.29	1.22	1.52	125	1.37	112	14	4	5	5	2	3	
218	139.29	141.12	1.83	1.70	93	1.07	58	9	4	5	18	2	3	minor gouge on fractures
218	141.12	144.17	3.05	3.05	100	3.05	100	15	4	5	1	1	3	
218	144.17	147.22	3.05	3.12	102	2.86	94	13	4	5	13	3	3	gouge on fractures
218	147.22	149.35	2.13	2.20	103	1.40	66	9	4	5	25	3	3	gouge on fractures
218	149.35	150.88	1.53	1.19	78	0.85	56	9	4	6	12	2	2	
218	150.88	153.92	3.04	3.18	105	2.66	88	12	4	6	18	2	3	gouge on fractures
218	153.92	156.97	3.05	3.16	104	2.62	86	10	4	6	26	2	2	
218	156.97	160.02	3.05	3.27	107	2.70	89	13	4	6	14	1	2	
218	160.02	163.07	3.05	3.00	98	2.30	75	10	4	6	24	2	2	
218	163.07	166.11	3.04	3.04	100	2.76	91	13	4	6	15	2	2	
218	166.11	168.25	2.14	2.20	103	1.51	71	9	4	6	26	3	3	10% broken core
218	168.25	170.08	1.83	1.49	81	0.95	52	7	3	5	25	2	3	minor gouge
218	170.08	171.60	1.52	0.54	36	0.40	26	7	3	5	8	3	3	fault starts 171.35 m - gouge/healed gouge
218	171.60	173.13	1.53	0.79	52	0.56	37	7	3	5	13	3	3	fault
218	173.13	174.35	1.22	0.73	60	0.13	11	6	3	5	20	3	3	fault
218	174.35	175.87	1.52	0.93	61	0.24	16	6	4	5	30	3	3	fault
218	175.87	176.78	0.91	0.52	57	0.20	22	6	4	5	25	3	3	fault
218	176.78	177.70	0.92	0.17	18	0.00	0	3	4	5	20	3	3	100% broken core; fault
218	177.70	178.61	0.91	0.82	90	0.36	40	6	4	5	20	3	3	50% broken core; minor gouge, fault
218	178.61	181.66	3.05	3.05	100	2.48	81	13	3	6	12	1	1	25% gouge and fault zone
218	181.66	185.32	3.66	2.26	62	0.29	8	10	3	6	25	1	1	20% gouge in broken core
218	185.32	187.15	1.83	1.66	91	1.48	81	12	3	6	10	5	3	20% gouge
218	187.15	190.20	3.05	2.79	91	2.53	83	13	4	6	7	1	1	DQCA between 187.2-189.3 m
218	190.20	192.02	1.82	1.91	105	1.38	76	12	3	6	12	1	1	50% gouge and faults
218	192.02	194.16	2.14	2.05	96	2.05	96	15	3	6	3	5	3	70% cemented gouge at 20-25 to c.a.
218	194.16	196.90	2.74	2.65	97	2.65	97	15	4	6	2	1	1	
218	196.90	199.95	3.05	3.05	100	3.05	100	15	4	6	3	1	1	
218	199.95	203.00	3.05	3.00	98	3.00	98	15	4	6	4	1	1	
218	203.00	206.04	3.04	3.04	100	3.04	100	15	4	6	3	1	1	
218	206.04	209.09	3.05	2.95	97	2.95	97	15	4	6	2	1	3	trace gouge on breaks
218	209.09	212.45	3.36	3.26	97	3.26	97	15	4	6	4	1	1	
218	212.45	215.49	3.04	3.08	101	3.08	101	15	4	6	1	1	2	
218	215.49	218.54	3.05	2.98	98	2.91	95	15	4	6	3	1	1	trace gouge on slips

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
218	218.54	220.37	1.83	1.29	70	0.60	33	7	4	6	20	1	1	
218	220.37	220.98	0.61	0.15	25	0.00	0	3	4	6	20	1	1	
218	220.98	224.03	3.05	2.98	98	2.98	98	15	4	6	3	1	1	
218	224.03	227.08	3.05	2.94	96	2.94	96	15	4	6	3	1	1	
218	227.08	228.90	1.82	1.73	95	1.71	94	14	4	6	4	1	1	
218	228.90	230.73	1.83	1.81	99	1.59	87	13	4	6	7	1	1	
218	230.73	232.87	2.14	1.72	80	0.98	46	12	4	6	9	1	1	
218	232.87	235.92	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
218	235.92	238.96	3.04	3.02	99	3.02	99	15	4	6	3	1		1 trace gouge on slips
218	238.96	242.01	3.05	3.01	99	3.01	99	15	4	6	3	1		1 trace gouge on slips
218	242.01	245.06	3.05	2.96	97	2.96	97	15	4	6	4	1		1 trace gouge on slips
218	245.06	248.11	3.05	2.93	96	2.93	96	15	4	6	1	1	1	
218	248.11	251.16	3.05	3.19	105	3.19	105	15	4	6	2	3	1	
218	251.16	253.29	2.13	2.20	103	2.00	94	13	4	6	8	1		1 20 cm of moderately broken core
218	253.29	255.42	2.13	1.78	84	1.74	82	15	4	6	3	1	1	
218	255.42	258.17	2.75	2.71	99	2.56	93	14	4	6	6	1		1 gouge on slips
218	258.17	261.21	3.04	2.94	97	2.78	91	15	4	6	4	1		1 gouge on slips
218	261.21	264.26	3.05	2.88	94	2.68	88	14	4	6	7	1		1 gouge on slips
218	264.26	267.31	3.05	3.00	98	2.41	79	13	4	6	12	1		1 gouge on slips
218	267.31	270.36	3.05	3.00	98	2.92	96	15	4	6	3	1	1	
218	270.36	273.41	3.05	3.05	100	3.05	100	15	4	6	3	5	3	
218	273.41	276.45	3.04	3.01	99	3.01	99	15	4	6	2	1	3	
218	276.45	279.50	3.05	2.90	95	2.73	90	14	4	6	8	1		1 65 cm of gouge and rubble
218	279.50	282.55	3.05	2.72	89	2.55	84	15	4	6	5	1		1 trace gouge on slip
218	282.55	285.60	3.05	3.05	100	3.05	100	15	4	6	2	1	1	
218	285.60	288.65	3.05	3.10	102	2.90	95	15	4	6	5	1		1 gouge on slip
218	288.65	291.69	3.04	3.09	102	3.09	102	15	4	6	2	5	3	
218	291.69	294.74	3.05	3.02	99	3.02	99	15	4	6	3	1	1	
218	294.74	297.79	3.05	3.05	100	3.05	100	15	4	6	2	1	1	
218	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	2	1	1	
218	300.84	303.88	3.04	3.13	103	3.13	103	15	4	6	3	2		3 gouge on break
218	303.88	306.93	3.05	3.09	101	3.09	101	15	4	6	2	1		1 trace gouge
218	306.93	309.98	3.05	3.03	99	3.03	99	15	4	6	3	1		1 gouge on slip
218	309.98	313.03	3.05	2.92	96	2.92	96	15	4	6	2	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
218	313.03	316.08	3.05	3.10	102	3.06	100	15	4	6	3	1	1	
218	316.08	319.13	3.05	3.10	102	3.10	102	15	4	6	1	1	1	
218	319.13	322.17	3.04	3.04	100	2.85	94	15	4	6	5	1	1	1 3-5 mm gouge on slip
218	322.17	325.22	3.05	3.05	100	2.87	94	15	4	6	4	5	3	
218	325.22	328.27	3.05	2.98	98	2.98	98	15	4	6	2	1	1	
219	7.92	8.23	0.31	0.35	113	0.35	113	12	4	5	1	1	1	
219	8.23	11.28	3.05	0.38	12	0.12	4	6	4	5	10	5	3	
219	11.28	13.11	1.83	0.75	41	0.00	0	4	4	5	25	1	1	1 gouge on slips and broken core
219	13.11	15.24	2.13	1.67	78	1.23	58	10	4	6	15	1	1	1 gouge on slips
219	15.24	18.29	3.05	2.83	93	2.54	83	14	4	6	9	1	1	1 gouge on slips
219	18.29	20.42	2.13	2.05	96	1.95	92	14	4	6	5	1	1	
219	20.42	23.47	3.05	2.84	93	2.71	89	14	4	6	7	1	1	1 3-4 mm gouge in slip
219	23.47	25.30	1.83	1.36	74	0.96	52	9	4	6	15	5	3	3 gouge in broken core
219	25.30	27.74	2.44	2.44	100	1.85	76	10	4	6	17	1	1	1 gouge on slips
219	27.74	29.57	1.83	1.80	98	1.34	73	10	4	6	13	1	1	1 gouge on slips and on broken core
219	29.57	32.61	3.04	3.01	99	2.73	90	14	4	6	7	1	1	
219	32.61	34.44	1.83	1.83	100	1.60	87	14	4	6	6	1	1	1 4 mm gouge on slip
219	34.44	35.66	1.22	0.94	77	0.88	72	13	4	6	4	1	1	1 trace gouge on slip
219	35.66	38.71	3.05	2.82	92	2.64	87	13	4	6	9	1	1	1 2-3 mm gouge on 50% of slips
219	38.71	41.76	3.05	3.01	99	3.01	99	15	4	6	2	1	1	1 gouge on slip
219	41.76	44.81	3.05	2.95	97	2.85	93	13	4	6	10	1	1	1 gouge on slips
219	44.81	47.85	3.04	3.04	100	3.04	100	15	4	6	3	1	1	
219	47.85	50.90	3.05	3.03	99	3.03	99	15	4	6	4	1	1	
219	50.90	53.95	3.05	2.85	93	2.63	86	14	4	6	8	1	1	
219	53.95	57.00	3.05	2.58	85	1.92	63	10	4	6	24	1	1	1 gouge in broken core
219	57.00	60.05	3.05	2.98	98	2.84	93	14	4	6	7	1	1	
219	60.05	63.09	3.04	2.87	94	2.69	88	14	4	6	8	1	1	
219	63.09	66.14	3.05	2.85	93	2.33	76	12	4	6	15	1	1	1 gouge on slips and in broken core
219	66.14	69.19	3.05	3.08	101	3.08	101	15	4	6	4	1	1	1 3 cm of gouge & rubble in break
219	69.19	72.24	3.05	2.72	89	2.54	83	13	4	6	12	1	1	1 2-4 mm gouge on slip
219	72.24	75.29	3.05	3.05	100	2.74	90	14	4	6	7	1	1	1 gouge on slip
219	75.29	78.33	3.04	2.91	96	2.91	96	15	4	6	1	5	3	
219	78.33	81.38	3.05	3.08	101	3.08	101	15	4	6	3	1	1	1 2-3 mm gouge on slip
219	81.38	84.43	3.05	2.93	96	2.93	96	15	4	6	2	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
219	84.43	87.48	3.05	3.05	100	3.05	100	15	4	6	2	1	1 gouge on slip	
219	87.48	90.53	3.05	3.07	101	2.88	94	14	4	6	8	1	1 20 cemented gouge and rubble	
219	90.53	93.57	3.04	3.08	101	3.06	101	15	4	6	3	1	1 gouge on breaks	
219	93.57	96.62	3.05	3.05	100	2.56	84	13	4	6	14	1	1 5 cm cemented gouge and rubble	
219	96.62	99.67	3.05	2.96	97	2.91	95	15	4	6	4	1	1 3 cm gouge & rubble on slip	
219	99.67	102.72	3.05	3.02	99	3.02	99	15	4	6	1	5	3	
219	102.72	105.77	3.05	3.02	99	3.00	98	15	4	6	4	5	3	
219	105.77	108.81	3.04	3.04	100	3.01	99	15	4	6	4	1	1	
219	108.81	111.86	3.05	2.98	98	2.84	93	14	4	6	8	1	1 gouge on slip	
219	111.86	113.69	1.83	1.80	98	1.15	63	9	4	6	16	1	1 gouge on slip	
219	113.69	116.13	2.44	2.19	90	0.76	31	9	4	6	30	1	1	
219	116.13	117.96	1.83	1.90	104	1.90	104	14	4	6	4	5	3 trace gouge on break	
219	117.96	121.01	3.05	2.98	98	2.53	83	10	4	6	21	1	1 gouge on slip	
219	121.01	124.05	3.04	3.04	100	2.98	98	15	4	6	5	1	1	
219	124.05	126.19	2.14	1.73	81	0.62	29	9	3	6	25	1	1 50% broken core and gouge	
219	126.19	129.24	3.05	2.95	97	2.43	80	12	4	6	16	1	1 local gouge with rubble	
219	129.24	132.28	3.04	2.86	94	2.86	94	15	4	6	3	1	1	
219	132.28	135.64	3.36	3.36	100	3.01	90	13	4	6	12	1	1 gouge on slips and in broken core	
219	135.64	138.68	3.04	2.86	94	2.11	69	10	4	6	22	1	1 gouge on slips and in broken core	
219	138.68	141.73	3.05	2.93	96	2.45	80	13	4	6	12	1	1 gouge on slips and in broken core	
219	141.73	144.78	3.05	2.74	90	1.44	47	9	3	6	30	1	1 gouge on slips and in broken core	
219	144.78	147.83	3.05	2.73	90	1.92	63	10	3	6	30	1	1 gouge on slips and in broken core	
219	147.83	148.44	0.61	0.61	100	0.24	39	7	3	6	10	1	1 gouge on slips and in broken core	
219	148.44	151.49	3.05	0.80	26	0.00	0	6	3	6	20	1	1 gouge on slips and in broken core	
220	30.48	32.61	2.13	0.02	1	0.00	0	3	5	5	25	3	3 rubble, poor recovery	
220	32.61	41.76	9.15	0.20	2	0.00	0	6	5	5	10	3	3 Triconed, rubble, poor recovery	
220	41.76	45.72	3.96	0.38	10	0.00	0	6	5	5	20	3	3 Triconed, rubble, poor recovery	
220	45.72	48.46	2.74	0.14	5	0.00	0	6	5	5	10	3	3 rubble, poor recovery	
220	48.46	50.60	2.14	2.14	100	1.55	72	10	4	5	20	2	3 DQCA - good recovery in dyke, trace gouge	
220	50.60	51.82	1.22	0.85	70	0.30	25	7	4	5	17	1	2	
220	51.82	53.64	1.82	0.85	47	0.46	25	6	4	5	20	3	3 10% gouge	
220	53.64	55.78	2.14	0.70	33	0.00	0	6	4	5	20	3	3 100% broken, trace gouge	
220	55.78	57.00	1.22	0.65	53	0.11	9	6	4	5	15	3	3 90% broken core	
220	57.00	59.44	2.44	0.82	34	0.00	0	6	4	5	30	3	3 100% broken, trace gouge	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
220	59.44	61.57	2.13	1.40	66	0.15	7	6	4	5	30	2	3	
220	61.57	63.09	1.52	1.12	74	0.18	12	7	4	4	20	3	3	
220	63.09	64.62	1.53	0.65	42	0.00	0	7	3	4	13	3	3	3 broken, poor recovery
220	64.62	65.53	0.91	0.36	40	0.00	0	6	3	4	12	3	3	3 broken, poor recovery
220	65.53	66.14	0.61	0.61	100	0.23	38	7	4	4	12	2	3	
220	66.14	66.75	0.61	0.70	115	0.00	0	6	4	4	20	3	3	3 pyrite on fractures, 100% broken core
220	66.75	68.58	1.83	1.10	60	0.00	0	6	4	4	25	2	2	2 pyrite on fractures, 100% broken core
220	68.58	69.80	1.22	0.76	62	0.10	8	7	5	4	15	3	3	3 90% broken core
220	69.80	72.85	3.05	0.62	20	0.00	0	6	4	4	20	3	3	3 100% broken core
220	72.85	74.37	1.52	0.96	63	0.00	0	6	4	4	25	3	3	3 100% broken core
220	74.37	75.29	0.92	0.26	28	0.00	0	6	4	4	15	3	3	3 100% broken core
220	75.29	77.72	2.43	0.60	25	0.00	0	6	4	4	20	3	3	3 100% broken core
220	77.72	79.25	1.53	0.27	18	0.00	0	6	4	4	15	2	2	2 100% broken core
220	79.25	80.47	1.22	0.25	20	0.00	0	6	4	4	15	3	3	3 100% broken core
220	80.47	81.38	0.91	0.38	42	0.10	11	6	4	4	15	3	3	3 60% broken core
220	81.38	82.91	1.53	0.75	49	0.00	0	6	4	4	20	3	3	3 100% broken core
220	82.91	84.43	1.52	0.71	47	0.00	0	6	4	4	25	3	3	
220	84.43	86.87	2.44	1.10	45	0.60	25	7	3	4	20	2	2	2 10 cm gouge
220	86.87	90.53	3.66	3.12	85	2.45	67	12	4	4	30	2	2	2 35 cm healed gouge H=3
220	90.53	91.44	0.91	0.91	100	0.65	71	10	4	5	8	2	2	
220	91.44	92.96	1.52	1.24	82	0.64	42	9	4	5	15	2	3	
220	92.96	94.49	1.53	1.27	83	0.73	48	9	4	5	14	3	3	
220	94.49	96.93	2.44	2.33	95	1.61	66	10	4	5	23	2	2	2 gypsum on fractures
220	96.93	99.67	2.74	2.85	104	2.80	102	13	4	5	10	2	2	2 gypsum on fractures
220	99.67	102.72	3.05	3.05	100	2.90	95	14	4	5	8	2	2	2 gypsum on fractures
220	102.72	105.77	3.05	3.09	101	3.00	98	15	4	5	4	2	2	2 gypsum on fractures
220	105.77	108.81	3.04	3.13	103	3.13	103	15	4	5	5	3	3	3 gypsum on fractures
220	108.81	111.86	3.05	3.02	99	3.02	99	15	4	5	5	3	3	3 gypsum on fractures
220	111.86	114.96	3.10	3.06	99	3.06	99	14	4	5	6	2	2	2 gypsum on fractures
220	114.96	116.43	1.47	1.53	104	0.76	52	10	4	4	15	2	2	2 gypsum on fractures, 30 cm gouge H=1,2
220	116.43	119.48	3.05	3.01	99	2.55	84	12	4	5	20	3	3	3 15 cm gouge H=2,3
220	119.48	121.01	1.53	1.47	96	1.47	96	14	4	5	4	1	1	2 gypsum on fractures
220	121.01	124.05	3.04	3.10	102	2.97	98	14	4	5	7	3	3	2 gypsum on fractures
220	124.05	127.10	3.05	3.08	101	3.00	98	14	4	5	10	1	1	2 gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
220	127.10	130.15	3.05	3.02	99	3.02	99	14	4	5	6	3	3	gypsum on fractures
220	130.15	133.20	3.05	3.12	102	3.07	101	14	4	5	9	1	2	gypsum on fractures
220	133.20	136.25	3.05	3.02	99	3.02	99	14	4	5	7	2	2	gypsum on fractures
220	136.25	139.29	3.04	3.04	100	3.00	99	14	4	5	10	2	3	gouge on fractures
220	139.29	142.34	3.05	3.10	102	3.10	102	15	4	5	1	2	3	
220	142.34	145.39	3.05	3.05	100	2.90	95	14	4	5	6	3	3	gouge on fractures
220	145.39	148.44	3.05	2.97	97	2.97	97	14	4	5	5	1	2	
220	148.44	151.49	3.05	3.07	101	2.85	93	14	4	5	7	1	3	
220	151.49	154.53	3.04	3.15	104	2.78	91	14	4	5	9	2	3	gouge on fractures
220	154.53	157.58	3.05	3.05	100	2.92	96	14	4	5	9	2	3	
220	157.58	160.63	3.05	3.05	100	3.05	100	15	4	5	5	3	3	8 cm healed gouge H=3
220	160.63	163.37	2.74	2.55	93	1.52	55	9	4	5	30	3	3	163.12 - 163.37 m gouge H=3
220	163.37	166.42	3.05	3.15	103	2.92	96	14	4	5	10	3	3	gouge on fractures
220	166.42	169.47	3.05	3.07	101	2.94	96	13	4	5	12	5	3	
220	169.47	170.69	1.22	1.32	108	1.22	100	13	4	5	6	3	3	
220	170.69	172.82	2.13	1.78	84	1.44	68	10	4	5	15	2	3	two 10 cm intervals of gouge H=2
220	172.82	175.87	3.05	3.05	100	2.78	91	12	4	4	18	2	1	weak slicks
220	175.87	178.92	3.05	3.01	99	3.01	99	14	3	4	6	2	3	gouge on fractures
220	178.92	181.97	3.05	2.90	95	2.50	82	12	3	4	16	2	3	2 - 6 cm gouge-filled fractures
220	181.97	185.01	3.04	2.94	97	2.94	97	15	4	4	1	3	3	gouge on fracture
220	185.01	188.06	3.05	3.05	100	2.50	82	12	3	4	20	2	3	185.35 - 185.95 m sheared H=2,3
220	188.06	191.11	3.05	3.10	102	2.30	75	10	3	4	22	3	3	gouge intervals
220	191.11	194.16	3.05	3.05	100	3.00	98	15	4	4	5	3	3	191.43 - 191.55 m shears 30 to c.a.
220	194.16	197.21	3.05	3.05	100	2.95	97	15	4	5	4	2	3	
220	197.21	200.25	3.04	3.04	100	2.75	90	13	4	5	12	2	3	
220	200.25	203.30	3.05	2.94	96	2.67	88	12	4	5	16	2	3	201.80 - 202.35 m shear 50 to c.a.
220	203.30	206.35	3.05	3.00	98	2.98	98	14	4	5	7	3	3	gouge on fractures
220	206.35	209.40	3.05	3.05	100	3.05	100	15	4	5	3	3	3	pyrite on fractures
220	209.40	212.45	3.05	3.11	102	3.11	102	15	4	5	5	3	3	
220	212.45	215.49	3.04	3.10	102	2.98	98	14	4	5	8	2	3	
220	215.49	218.54	3.05	3.05	100	2.80	92	13	4	5	14	3	1	weak slicks, minor gouge on fractures
220	218.54	221.59	3.05	3.05	100	2.87	94	14	5	5	8	2	1	chalcopryite and slicks on fractures
220	221.59	224.64	3.05	3.05	100	2.85	93	13	4	5	11	2	2	chalcopryite on fractures
220	224.64	227.69	3.05	3.08	101	3.08	101	15	4	5	5	3	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
220	227.69	230.73	3.04	3.10	102	3.05	100	14	4	5	7	2	2	gouge on fractures
220	230.73	233.78	3.05	2.95	97	2.67	88	14	4	5	8	2	2	pyrite on fractures
220	233.78	236.83	3.05	3.10	102	3.00	98	13	4	5	11	2	3	
220	236.83	239.88	3.05	3.02	99	3.02	99	14	4	5	6	2	2	weak slickensides
220	239.88	242.93	3.05	3.20	105	2.76	90	14	4	5	10	3	3	gouge on fractures
220	242.93	245.97	3.04	2.94	97	2.72	89	13	4	5	10	2	3	weak slickensides on slips
220	245.97	249.02	3.05	3.00	98	2.72	89	13	4	5	12	2	2	weak slickensides
220	249.02	252.07	3.05	2.96	97	2.92	96	14	4	5	6	2	2	
220	252.07	255.12	3.05	3.08	101	3.05	100	14	4	5	6	2	2	
220	255.12	258.17	3.05	3.03	99	3.03	99	15	4	5	3	1	2	
220	258.17	261.21	3.04	3.05	100	3.05	100	15	4	5	4	2	2	
220	261.21	264.26	3.05	3.10	102	3.10	102	15	4	5	2	2	3	gouge on fractures
220	264.26	267.31	3.05	2.99	98	2.99	98	15	4	5	4	3	3	
220	267.31	270.36	3.05	3.02	99	3.02	99	14	4	5	9	2	2	minor gouge on fractures
220	270.36	273.41	3.05	3.10	102	3.10	102	14	4	5	6	2	3	minor gouge on fractures
220	273.41	276.45	3.04	3.06	101	3.06	101	14	4	5	6	2	1	weak slickensides
220	276.45	279.50	3.05	3.05	100	3.05	100	15	4	5	4	2	2	gouge on fractures
220	279.50	282.55	3.05	3.08	101	3.02	99	15	4	5	5	2	2	
220	282.55	285.60	3.05	2.94	96	2.94	96	14	3	4	5	3	2	
220	285.60	288.65	3.05	3.05	100	2.72	89	14	3	4	10	2	3	285.80 - 286.27 m shear 50 to c.a.
220	288.65	291.69	3.04	3.07	101	3.07	101	15	4	5	2	2	2	
220	291.69	294.74	3.05	3.00	98	3.00	98	14	4	5	5	2	2	
220	294.74	297.79	3.05	3.02	99	3.02	99	15	4	5	2	3	2	
220	297.79	300.84	3.05	3.05	100	3.05	100	15	4	5	5	2	2	2 slick joints
220	300.84	303.89	3.05	3.02	99	3.02	99	15	4	5	2	2	3	minor gouge on fractures
220	303.89	306.93	3.04	2.95	97	2.88	95	14	4	5	5	2	3	minor gouge on fractures
221	8.23	11.28	3.05	3.40	111	0.75	25	10	3	5	33	1	2	most fractures rough
221	11.28	14.33	3.05	2.80	92	1.95	64	12	3	6	18	1	3	13.0 - 13.7 m crush zone
221	14.33	17.37	3.04	3.05	100	1.90	63	10	3	6	26	2	2	
221	17.37	20.42	3.05	3.10	102	2.15	70	10	3	6	24	2	2	
221	20.42	23.47	3.05	3.15	103	1.53	50	10	3	6	22	3	2	minor clay/gouge on slips
221	23.47	26.52	3.05	3.35	110	2.45	80	12	3	6	18	2	2	
221	26.52	29.57	3.05	3.20	105	2.65	87	12	3	6	18	3	1	minor gouge
221	29.57	32.61	3.04	3.07	101	2.27	75	12	3	6	18	3	2	minor crush and gouge 29.57 - 29.80 m

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
221	32.61	35.66	3.05	3.10	102	2.40	79	10	3	6	22	1	2	2 minor gouge
221	35.66	38.71	3.05	3.10	102	2.65	87	13	3	6	15	3	1	38.00 - 38.71 m fault, shear 33 to c.a.
221	38.71	41.76	3.05	2.95	97	1.50	49	10	3	6	26	3	2	
221	41.76	44.81	3.05	3.02	99	3.02	99	14	3	6	9	1	2	most fractures rough
221	44.81	47.85	3.04	3.10	102	2.50	82	10	3	6	21	3	2	47.00-47.20 m crush zone, gouge 53 to c.a.
221	47.85	50.90	3.05	3.10	102	2.95	97	14	3	6	6	2	2	
221	50.90	53.95	3.05	3.08	101	2.60	85	13	3	6	13	2	2	
221	53.95	57.00	3.05	3.10	102	2.60	85	13	3	6	15	1	2	
221	57.00	60.05	3.05	3.02	99	2.82	92	13	3	6	14	3	2	some healed crush, H=2
221	60.05	63.09	3.04	3.02	99	2.70	89	12	3	6	18	3	2	some healed crush, H=2
221	63.09	65.23	2.14	1.90	89	0.00	0	6	3	6	50	2	2	
221	65.23	68.28	3.05	3.00	98	2.80	92	10	3	6	21	2	2	minor gouge
221	68.28	71.02	2.74	2.60	95	1.50	55	10	3	6	22	3	3	pyrite on fracture surfaces
221	71.02	74.06	3.04	3.15	104	2.95	97	12	3	6	16	2	2	
221	74.06	77.11	3.05	3.00	98	3.00	98	15	3	6	3	3	2	
221	77.11	80.16	3.05	3.02	99	2.50	82	10	3	6	21	2	1	blocky core 79.00 - 80.16m
221	80.16	81.38	1.22	1.03	84	0.87	71	10	3	6	7	3	3	
221	81.38	83.21	1.83	1.60	87	1.45	79	14	3	6	4	3	3	5 cm gouge at end of interval
221	83.21	86.26	3.05	2.67	88	2.20	72	12	1	6	14	2	2	fault, healed crush zone (sand and gouge)
221	86.26	89.00	2.74	0.75	27	0.00	0	5	1	6	30	3	3	rubble, gouge
221	89.00	92.05	3.05	0.35	11	0.19	6	5	3	6	10	1	2	rubble, gouge
221	92.05	93.57	1.52	1.38	91	1.38	91	15	1	6	2	3	3	fault, healed crush, mylonite
221	93.57	96.62	3.05	3.00	98	2.95	97	15	1	6	3	3	2	healed crush, gouge
221	96.62	99.67	3.05	3.05	100	3.05	100	15	1	6	2	3	3	healed crush zone
221	99.67	102.72	3.05	3.10	102	3.10	102	14	1	6	7	3	3	healed crush zone
221	102.72	105.77	3.05	3.00	98	3.00	98	14	1	6	9	3	3	healed crush zone, competent lower part
221	105.77	108.81	3.04	3.05	100	3.05	100	14	1	6	8	3	2	healed crush zone, shearing 40 to c.a.
221	108.81	111.86	3.05	2.92	96	2.62	86	14	3	6	8	3	3	fault
221	111.86	114.91	3.05	3.20	105	2.30	75	7	1	6	45	3	2	rubble and healed crush zone, gouge
221	114.91	117.96	3.05	2.95	97	2.95	97	14	1	6	8	3	3	healed crush zone
221	117.96	121.01	3.05	3.10	102	3.10	102	14	1	6	7	2	2	healed crush zone
221	121.01	124.05	3.04	3.05	100	3.05	100	14	2	6	10	3	3	healed crush zone
221	124.05	127.10	3.05	3.15	103	0.65	21	10	1	6	31	1	3	rubble and healed crush
221	127.10	130.15	3.05	3.02	99	3.02	99	14	2	6	8	3	2	healed crush zone

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
221	130.15	133.20	3.05	3.10	102	2.20	72	10	2	6	27	1	2 in part healed crush zone, shear 35 to c.a.	
221	133.20	136.25	3.05	3.04	100	2.80	92	14	3	6	10	3	3 minor crushed rock	
221	136.25	139.29	3.04	3.10	102	2.90	95	12	3	6	17	1	2 minor crushed rock	
221	139.29	142.34	3.05	2.95	97	2.75	90	12	2	6	17	3	1 50% interval crushed rock (healed)	
221	142.34	145.44	3.10	3.10	100	2.10	68	10	3	6	29	1	2 minor gouge on slips	
221	145.44	148.44	3.00	3.03	101	2.70	90	13	3	6	14	1	2 minor gouge on slips	
221	148.44	151.49	3.05	3.20	105	1.75	57	13	2	6	15	1	2 zones of rubble and minor gouge	
221	151.49	154.53	3.04	2.98	98	2.65	87	12	2	6	19	2	2	
221	154.53	157.58	3.05	3.04	100	2.50	82	12	2	6	16	3	2 healed crush	
221	157.58	160.63	3.05	3.07	101	3.07	101	13	3	6	12	1	2	
221	160.63	163.68	3.05	3.05	100	2.15	70	10	3	6	22	3	2 pyrite on fractures	
221	163.68	166.73	3.05	3.05	100	2.95	97	13	2	6	11	2	2 166.00 - 166.73 m weak crush zone	
221	166.73	169.77	3.04	3.06	101	2.71	89	13	2	6	11	1	2 169.00 - 169.77 m weak crush zone	
221	169.77	172.82	3.05	3.20	105	3.05	100	13	2	6	13	3	2 weak crush in most of interval	
221	172.82	175.87	3.05	3.05	100	2.90	95	12	2	6	17	3	2 weak crush in most of interval	
221	175.87	178.92	3.05	3.10	102	2.60	85	13	3	6	11	3	3 pyrite on fractures	
221	178.92	181.97	3.05	3.00	98	0.45	15	7	3	6	50	3	2 rubble and minor gouge	
221	181.97	185.01	3.04	3.10	102	2.20	72	10	3	6	21	3	2	
221	185.01	188.06	3.05	3.15	103	2.35	77	9	3	6	34	3	2 187.00 - 188.00 m blocky core	
221	188.06	191.11	3.05	3.00	98	1.80	59	9	2	6	32	3	2 minor crush	
221	191.11	194.16	3.05	3.00	98	2.10	69	9	2	6	33	1	2 some crush	
221	194.16	197.21	3.05	3.20	105	2.00	66	10	2	6	30	3	2 weak crush zone	
221	197.21	200.25	3.04	3.10	102	2.00	66	12	2	6	18	2	2 crush zone	
221	200.25	203.30	3.05	3.20	105	1.75	57	9	2	6	33	1	2 crush zone	
221	203.30	206.35	3.05	3.20	105	2.70	89	13	2	6	15	3	2 crush, minor gouge	
221	206.35	209.40	3.05	2.95	97	1.50	49	7	1	6	40	2	2	
221	209.40	212.45	3.05	3.10	102	1.20	39	7	1	6	50	1	1 sporadic intervals of crush	
221	212.45	213.66	1.21	1.15	95	0.80	66	10	1	6	10	2	2	
221	213.66	214.27	0.61	0.55	90	0.10	16	6	3	6	14	3	2 rubble, minor gouge	
221	214.27	217.32	3.05	2.90	95	2.10	69	10	3	6	27	3	2 216.70 m shear with 2 cm gouge 32 to c.a.	
221	217.32	220.37	3.05	3.20	105	1.50	49	9	0	6	36	5	3 strong crush/fault zone 45 to c.a.	
221	220.37	220.98	0.61	0.55	90	0.12	20	6	1	6	15	3	3 rubble, crush	
221	220.98	224.03	3.05	2.90	95	1.70	56	10	1	6	27	3	2 some crush zones	
221	224.03	226.77	2.74	2.80	102	0.73	27	7	2	6	46	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
221	226.77	229.82	3.05	2.90	95	1.70	56	10	1	6	28	3	2 sporadic crush/gouge	
221	229.82	232.56	2.74	2.80	102	0.50	18	7	3	6	44	1	2 DQCA dyke most of interval	
221	232.56	233.17	0.61	0.55	90	0.00	0	5	4	6	23	3	3 rubble and broken quartz	
221	233.17	233.78	0.61	0.20	33	0.00	0	3	4	6	15	3	3 mostly quartz rubble	
221	233.78	235.61	1.83	0.80	44	0.10	5	5	1	6	30	3	3 quartz rubble and gouge	
221	235.61	237.44	1.83	1.30	71	0.00	0	5	1	6	30	1	2 minor gouge on slips, rubble and crush	
221	237.44	238.35	0.91	1.05	115	0.00	0	5	1	6	50	3	2 rubble	
221	238.35	239.57	1.22	1.50	123	0.00	0	5	3	6	50	3	3 rubble, minor clay/sand on fractures	
221	239.57	241.10	1.53	0.70	46	0.00	0	5	1	6	30	3	2 rubble, minor clay/sand on fractures	
221	241.10	243.84	2.74	0.70	26	0.00	0	6	1	6	20	3	2 rubble, minor clay/sand on fractures	
221	243.84	245.06	1.22	0.90	74	0.10	8	6	1	6	20	3	3 rubble, minor clay/sand on fractures	
222	3.66	5.18	1.52	0.65	43	0.00	0	5	3	5	20	2	2 blocky	
222	5.18	8.23	3.05	2.76	90	0.88	29	6	3	5	20	1	3 blocky	
222	8.23	10.67	2.44	2.10	86	0.70	29	7	3	5	20	1	2 blocky	
222	10.67	11.28	0.61	0.52	85	0.00	0	7	3	6	8	1	2	
222	11.28	14.33	3.05	2.93	96	2.55	84	14	3	6	5	3	2	
222	14.33	15.85	1.52	1.52	100	0.41	27	15	3	5	13	3	3	
222	15.85	18.29	2.44	2.20	90	1.30	53	10	3	5	15	1	1 blocky	
222	18.29	20.12	1.83	1.50	82	0.60	33	9	3	5	16	1	2 areas of rubble	
222	20.12	23.16	3.04	3.04	100	2.63	87	14	3	6	8	1	1 areas of rubble	
222	23.16	26.21	3.05	2.92	96	2.43	80	14	3	6	6	1	2	
222	26.21	29.57	3.36	3.25	97	1.67	50	14	1	4	10	2	2 fault gouge	
222	29.57	32.61	3.04	3.04	100	2.83	93	15	2	4	5	1	2 shearing + gouge	
222	32.61	35.66	3.05	3.00	98	1.45	48	12	2	4	18	1	2 shearing + gouge	
222	35.66	38.71	3.05	3.00	98	2.46	81	14	3	5	7	1	1 shearing + gouge	
222	38.71	41.76	3.05	3.00	98	2.70	89	15	3	6	4	1	1	
222	41.76	44.81	3.05	3.00	98	2.32	76	14	3	6	10	1	1 shearing + gouge	
222	44.81	47.85	3.04	2.80	92	1.40	46	11	3	5	19	1	1 shearing + gouge	
222	47.85	50.90	3.05	3.05	100	2.35	77	14	3	6	7	3	2 fault + gouge	
222	50.90	53.95	3.05	2.88	94	2.45	80	14	3	6	7	3	4 shearing + gouge	
222	53.95	57.00	3.05	3.00	98	1.75	57	14	3	6	10	1	1 healed shearing + gouge	
222	57.00	60.05	3.05	2.92	96	1.80	59	12	3	5	17	1	2 healed shearing + gouge	
222	60.05	63.09	3.04	3.10	102	2.47	81	14	3	6	8	1	1 healed shearing + gouge	
222	63.09	66.14	3.05	2.95	97	2.60	85	14	3	6	7	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
222	66.14	69.19	3.05	2.95	97	2.38	78	14	3	5	8	4	1	1 fault
222	69.19	72.24	3.05	3.05	100	2.20	72	14	3	5	9	2	2	2 fault/dyke
222	72.24	75.29	3.05	2.95	97	2.05	67	12	4	6	16	1	1	1 dyke
222	75.29	78.33	3.04	2.95	97	1.97	65	13	3	5	11	3	2	2 healed shearing + gouge
222	78.33	81.38	3.05	3.05	100	2.80	92	14	4	5	7	1	1	1 healed shearing + gouge
222	81.38	84.43	3.05	3.00	98	2.80	92	15	4	6	5	1	2	2
222	84.43	87.48	3.05	3.05	100	3.05	100	15	4	6	4	1	2	2
222	87.48	90.53	3.05	3.05	100	3.05	100	15	3	6	4	1	2	2
222	90.53	93.57	3.04	3.10	102	2.85	94	14	3	6	8	1	3	3
222	93.57	96.62	3.05	3.05	100	2.65	87	14	3	6	9	2	2	2
222	96.62	99.67	3.05	3.05	100	2.65	87	14	3	6	6	2	2	2
222	99.67	102.72	3.05	3.10	102	2.50	82	13	4	6	13	2	3	3
222	102.72	105.77	3.05	3.05	100	2.30	75	13	4	6	12	2	2	2
222	105.77	108.81	3.04	2.90	95	0.88	29	12	3	5	19	2	1	1 healed fault/black color
222	108.81	111.86	3.00	3.00	100	1.65	55	12	3	4	18	3	2	2 healed fault/black color/blocky
222	111.86	114.91	3.05	2.80	92	1.00	33	10	3	4	20	3	2	2 healed fault/black color/blocky
222	114.91	117.96	3.05	3.05	100	2.20	72	14	3	5	10	1	2	2
222	117.96	121.01	3.05	3.05	100	2.85	93	15	3	6	5	3	3	3
222	121.01	124.05	3.04	2.95	97	2.58	85	15	4	6	4	2	3	3
222	124.05	127.10	3.05	3.05	100	3.05	100	15	2	4	5	2	2	2 partially healed fault
222	127.10	130.76	3.66	3.66	100	2.25	61	10	2	4	15	1	3	3 partially healed fault/1m very blocky
222	130.76	131.98	1.22	1.22	100	0.37	30	8	3	5	12	1	2	2 partially healed fault/1m very blocky
222	131.98	135.03	3.05	2.75	90	0.66	22	8	3	4	20	3	1	1 partially healed fault/1m very blocky
222	135.03	138.07	3.04	3.00	99	1.75	58	13	4	5	11	2	2	2
222	138.07	141.12	3.05	3.05	100	2.87	94	14	4	6	7	2	1	1
222	141.12	144.17	3.05	3.10	102	2.02	66	13	3	5	15	3	1	1
222	144.17	147.22	3.05	3.00	98	2.90	95	15	4	6	5	3	2	2
222	147.22	149.05	1.83	1.83	100	0.49	27	10	2	4	18	2	3	3 fault
222	149.05	151.49	2.44	2.60	107	2.60	107	14	3	6	5	2	2	2
222	151.49	154.53	3.04	3.04	100	3.04	100	14	3	6	7	1	2	2
222	154.53	157.58	3.05	3.00	98	2.70	89	14	4	6	8	1	2	2
222	157.58	160.63	3.05	2.90	95	2.11	69	14	4	6	9	2	2	2
222	160.63	163.68	3.05	3.15	103	1.94	64	13	2	4	12	3	2	2 minor faulting
222	163.68	166.73	3.05	3.00	98	2.13	70	13	3	5	12	2	1	1 minor faulting

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
222	166.73	169.77	3.04	3.15	104	2.62	86	14	4	6	6	1	2	
222	169.77	172.82	3.05	3.05	100	2.95	97	14	4	6	6	1	3	
222	172.82	175.87	3.05	3.10	102	3.00	98	14	4	6	8	1	2	
222	175.87	178.92	3.05	2.90	95	2.58	85	14	4	6	8	1	2	
222	178.92	181.97	3.05	3.10	102	2.78	91	14	4	6	9	1	2	
222	181.97	185.01	3.04	3.15	104	2.58	85	14	4	5	10	2	1	
222	185.01	188.06	3.05	3.05	100	2.85	93	1	1	2	3	3		2 fault + 80% gouge at 185.55m
222	188.06	191.11	3.05	3.10	102	2.15	70	1	1	2	14	2		3 fault + 80% gouge
222	191.11	194.16	3.05	3.00	98	2.55	84	1	1	2	10	2		3 fault + 80% gouge
222	194.16	197.21	3.05	3.05	100	3.05	100	1	1	2	1	3		4 fault + 80% gouge
222	197.21	200.25	3.04	3.00	99	2.30	76	1	1	2	12	1		2 fault + 50% gouge
222	200.25	203.30	3.01	2.80	93	0.78	26	1	2	2	25	3		3 fault + 70% gouge, very blocky
222	203.30	206.35	3.00	2.88	96	2.62	87	14	2	5	8	1		1 20% gouge
222	206.35	209.09	2.74	2.62	96	1.36	50	10	2	5	25	5		3 20% gouge, sections strongly broken core
222	209.09	212.14	3.05	2.79	91	1.88	62	10	3	5	22	1		3 1-2cm sections of gouge
222	212.14	212.75	0.61	0.48	79	0.00	0	5	4	6	10	1		1 gouge in broken core
222	212.75	215.49	2.74	2.32	85	0.46	17	7	4	6	30	1		1 gouge in broken core
222	215.49	217.93	2.44	2.44	100	1.19	49	7	4	6	30	1		1 gouge in broken core
222	217.93	220.98	3.05	2.82	92	1.13	37	10	4	6	20	1		1 gouge in broken core
222	220.98	224.03	3.05	2.73	90	2.46	81	13	4	6	11	1		1 92 cms cemented gouge + rubble
222	224.03	227.08	3.05	2.90	95	2.90	95	14	3	6	6	1		1 gouge on slip at 30 to c.a., 70% gouge
222	227.08	230.12	3.04	2.95	97	2.29	75	13	3	6	14	1		1 gouge in broken core/30% cemented gouge
222	230.12	233.17	3.05	2.75	90	2.44	80	13	3	6	10	1		1 gouge in broken core/30% cemented gouge
222	233.17	236.22	3.05	2.93	96	2.67	88	13	3	6	11	1		1 gouge in broken core/30% cemented gouge
222	236.22	239.27	3.05	2.95	97	2.85	93	14	3	6	6	5		3 20% cemented gouge
222	239.27	239.57	0.30	0.33	110	0.17	57	7	3	6	5	5		3 100% cemented gouge
222	239.57	242.62	3.05	2.55	84	1.74	57	10	3	6	20	5		3 80% cemented gouge
222	242.62	242.93	0.31	0.63	203	0.61	197	14	2	5	2	5		3 100% cemented gouge
222	242.93	245.97	3.04	2.83	93	2.56	84	14	4	6	9	1		1 gouge zone ends at 20 to c.a.
222	245.97	248.72	2.75	2.67	97	1.85	67	10	4	6	20	1		1 gouge in broken core
222	248.72	249.02	0.30	0.26	87	0.26	87	10	4	6	2	1		1
222	249.02	251.76	2.74	2.53	92	1.69	62	10	4	6	17	1		1 gouge in broken core
223	45.72	47.24	1.52	1.28	84	0.92	61	14	4	5	8	1		2 fractured & blocky
223	47.24	49.07	1.83	1.70	93	0.21	11	6	4	5	25	1		2 fractured & blocky

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
223	49.07	50.90	1.83	1.25	68	0.10	5	6	4	4	20	1	2 gouge / rubble	
223	50.90	52.73	1.83	1.05	57	0.10	5	5	4	5	20	2	1 gouge / rubble	
223	52.73	54.86	2.13	0.12	6	0.00	0	5	4	5	15		gouge / rubble	
223	54.86	55.17	0.31	0.10	32	0.00	0	5	4	5	10		gouge / rubble	
223	55.17	56.69	1.52	0.10	7	0.00	0	5	4	5	10		gouge / rubble	
223	56.69	58.83	2.14	0.23	11	0.00	0	5	4	5	15		gouge / rubble	
223	58.83	60.05	1.22	0.10	8	0.00	0	5	4	5	12		gouge / rubble	
223	60.05	63.09	3.04	0.30	10	0.00	0	5	4	5	20	2	2 gouge / rubble	
223	63.09	64.01	0.92	0.34	37	0.00	0	5	4	5	20	1	3 gouge / rubble	
223	64.01	66.14	2.13	0.45	21	0.00	0	5	4	5	25	1	4 gouge / rubble	
223	66.14	68.28	2.14	0.55	26	0.00	0	5	4	5	12	2	3 gouge / rubble	
223	68.28	72.24	3.96	0.15	4	0.00	0	5	4	5	15		gouge / rubble	
223	72.24	75.29	3.05	0.85	28	0.33	11	7	3	5	12	1	2 gypsum veins/fracturing on gypsum veins	
223	75.29	78.33	3.04	3.04	100	2.53	83	13	3	5	15	1	1 gypsum veins/fracturing on gypsum veins	
223	78.33	81.38	3.05	3.10	102	2.50	82	14	3	5	8	1	1 gypsum veins/fracturing on gypsum veins	
223	81.38	84.43	3.05	3.05	100	3.05	100	15	4	5	3	1	1 gypsum veins/fracturing on gypsum veins	
223	84.43	87.48	3.05	3.07	101	3.07	101	15	4	5	3	4	3 gypsum veins/fracturing on gypsum veins	
223	87.48	90.53	3.05	2.85	93	2.55	84	14	4	5	10	1	2 gypsum veins/fracturing on gypsum veins	
223	90.53	93.57	3.04	3.00	99	2.70	89	14	4	5	9	4	4 gypsum veins/fracturing on gypsum veins	
223	93.57	96.62	3.05	3.10	102	2.95	97	14	4	5	7	3	2 gypsum veins/fracturing on gypsum veins	
223	96.62	99.67	3.05	3.00	98	3.00	98	15	4	5	5	4	3 gypsum veins/fracturing on gypsum veins	
223	99.67	102.72	3.05	2.80	92	2.80	92	15	4	5	3	3	2 gypsum veins/fracturing on gypsum veins	
223	102.72	105.77	3.05	3.12	102	3.12	102	15	4	5	4	4	3 gypsum veins/fracturing on gypsum veins	
223	105.77	108.81	3.04	2.90	95	2.90	95	15	4	5	3	1	2 fracturing on gypsum veins	
223	108.81	111.86	3.05	3.12	102	3.02	99	15	4	5	4	1	3 fracturing on gypsum veins	
223	111.86	114.91	3.05	3.12	102	3.12	102	15	4	5	3	1	1 fracturing on gypsum veins	
223	114.91	117.96	3.05	3.10	102	2.90	95	14	4	5	6	1	2 fracturing on gypsum veins	
223	117.96	121.01	3.05	3.10	102	3.10	102	15	4	5	4	1	2 fracturing on gypsum veins	
223	121.01	124.05	3.04	3.15	104	3.15	104	15	4	5	4	1	1 fracturing on gypsum veins	
223	124.05	127.10	3.05	3.00	98	3.00	98	15	4	5	1	1	1 fracturing on gypsum veins	
223	127.10	130.15	3.05	3.00	98	3.00	98	15	4	5	4	5	3 fracturing on gypsum veins	
223	130.15	133.20	3.05	3.05	100	3.05	100	15	4	5	4	2	2 fracturing on gypsum veins	
223	133.20	136.25	3.05	3.10	102	1.95	64	13	3	4	11	1	1 fracturing on gypsum veins, healed shearing	
223	136.25	139.90	3.65	3.00	82	1.85	51	10	3	4	22	1	3 fracturing on gypsum veins, healed shearing	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
223	139.90	142.34	2.44	2.34	96	2.05	84	13	3	5	11	1	2	fracturing on gypsum veins
223	142.34	144.17	1.83	1.55	85	1.35	74	13	4	5	6	2	3	fracturing on gypsum veins
223	144.17	147.22	3.05	2.85	93	2.45	80	13	4	5	11	3	3	fracturing on gypsum veins
223	147.22	150.27	3.05	3.05	100	2.65	87	14	4	5	9	1	2	fracturing on gypsum veins
223	150.27	153.31	3.04	3.10	102	3.10	102	15	4	5	5	1	1	fracturing on gypsum veins
223	153.31	156.36	3.05	3.00	98	3.00	98	14	4	5	8	1	1	fracturing on gypsum veins
223	156.36	159.41	3.05	2.97	97	2.80	92	14	4	5	9	1	2	fracturing on gypsum veins
223	159.41	162.46	3.05	3.10	102	3.10	102	15	4	5	4	3	2	fracturing on gypsum veins
223	162.46	165.51	3.05	2.93	96	2.28	75	12	4	5	17	3	3	fracturing on gypsum veins
223	165.51	168.25	2.74	2.67	97	2.67	97	14	4	5	5	2	2	fracturing on gypsum veins
223	168.25	171.30	3.05	3.00	98	3.00	98	15	4	5	3	2	2	fracturing on gypsum veins
223	171.30	174.35	3.05	3.05	100	3.05	100	15	4	5	3	5	4	fracturing on gypsum veins
223	174.35	177.39	3.04	3.04	100	3.04	100	15	4	5	4	2	2	fracturing on gypsum veins
223	177.39	180.44	3.05	3.10	102	2.95	97	14	4	5	9	1	1	fracturing on gypsum veins
223	180.44	183.49	3.05	3.10	102	3.10	102	14	4	5	9	1	2	fracturing on gypsum veins
223	183.49	186.54	3.05	3.10	102	3.10	102	15	4	5	5	3	2	fracturing on gypsum veins
223	186.54	188.06	1.52	1.35	89	1.35	89	14	4	5	3	3	2	fracturing on gypsum veins
223	188.06	191.11	3.05	3.00	98	2.95	97	14	4	5	9	1	2	fracturing on gypsum veins
223	191.11	194.16	3.05	3.05	100	2.95	97	14	4	5	6	2	2	fracturing on gypsum veins
223	194.16	197.21	3.05	3.03	99	2.93	96	14	4	6	7	1	2	fracturing on gypsum veins
223	197.21	200.25	3.04	2.97	98	2.97	98	15	4	6	3	1	2	fracturing on gypsum veins
223	200.25	203.30	3.05	3.05	100	3.05	100	15	4	6	2	1	2	fracturing on gypsum veins
223	203.30	206.35	3.05	3.02	99	2.87	94	15	4	6	5	2	2	fracturing on gypsum veins
223	206.35	209.40	3.05	2.51	82	1.19	39	12	3	5	15	5	3	50% gouge, H=2
223	209.40	212.45	3.05	2.89	95	2.89	95	15	3	6	4	2	2	fracturing on gypsum veins
223	212.45	215.49	3.04	3.04	100	2.83	93	14	4	6	7	2	2	fracturing on gypsum veins
223	215.49	219.46	3.97	3.64	92	3.07	77	15	4	6	6	2	2	fracturing on gypsum veins
223	219.46	221.59	2.13	2.16	101	1.92	90	14	4	6	5	2	2	3 cm gouge, H=2
223	221.59	224.64	3.05	2.90	95	2.84	93	14	4	6	6	2	2	fracturing on gypsum veins
223	224.64	227.69	3.05	3.05	100	2.91	95	14	4	6	6	1	3	fracturing on gypsum veins, gouge fractures
223	227.69	230.73	3.04	2.95	97	2.95	97	15	4	6	2	1	2	fracturing on gypsum veins
223	230.73	233.78	3.05	3.12	102	3.12	102	15	4	6	4	1	2	fracturing on gypsum veins
223	233.78	236.83	3.05	3.09	101	3.03	99	15	4	6	3	1	3	fracturing on gypsum veins, 3cm gouge
223	236.83	239.88	3.05	2.94	96	2.94	96	15	4	6	2	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
223	239.88	242.93	3.05	2.96	97	2.90	95	15	4	6	2	1	2	2 fracturing on gypsum veins
223	242.93	245.97	3.04	2.92	96	2.81	92	15	4	6	4	2	3	3 fracturing on gypsum veins, gouge fractures
223	245.97	249.02	3.05	3.05	100	2.90	95	15	4	6	5	1	3	3 fracturing on gypsum veins, gouge fractures
223	249.02	252.07	3.05	3.05	100	3.05	100	15	4	6	2	1	2	2 fracturing on gypsum veins
223	252.07	255.12	3.05	3.02	99	2.89	95	15	4	6	4	1	2	2 fracturing on gypsum veins, gouge fractures
223	255.12	258.17	3.05	2.95	97	2.90	95	15	4	6	4	1	2	2 fracturing on gypsum veins
223	258.17	261.21	3.04	2.67	88	2.36	78	14	4	6	5	2	3	3 gouge on fractures
223	261.21	262.74	1.53	1.05	69	0.54	35	13	4	6	4	2	3	3 14 cm gouge H=1,2
223	262.74	265.79	3.05	3.05	100	3.05	100	15	4	6	3	1	2	2
223	265.79	268.83	3.04	3.00	99	2.31	76	14	4	6	10	1	3	3 gouge on fractures
223	268.83	271.88	3.05	3.07	101	2.17	71	14	4	6	7	2	3	3 gouge on fractures, 13 cm gouge H=1,2
223	271.88	274.93	3.05	2.96	97	2.88	94	15	4	6	4	1	3	3 50% dyke, gouge on fractures
223	274.93	277.98	3.05	3.05	100	3.05	100	15	4	6	1	1	2	2
223	277.98	281.03	3.05	3.00	98	2.87	94	15	4	6	5	2	3	3
223	281.03	284.07	3.04	3.08	101	3.08	101	15	4	6	3	1	2	2 fracturing on gypsum veins
223	284.07	287.12	3.05	2.09	69	2.00	66	15	4	6	3	2	3	3 fracturing on gypsum veins, gouge fractures
223	287.12	288.65	1.53	1.11	73	0.23	15	7	4	6	20	2	3	3 fracturing on gypsum veins
223	288.65	290.17	1.52	1.67	110	1.03	68	12	4	6	10	2	3	3 gouge on fractures
223	290.17	293.22	3.05	2.77	91	2.63	86	15	4	6	4	1	3	3 gouge on fractures
223	293.22	296.27	3.05	3.08	101	2.84	93	13	4	6	11	2	3	3 gouge on fractures
223	296.27	299.31	3.04	2.91	96	2.68	88	14	4	6	5	2	3	3 gouge on fractures, 23 cm gouge H=1,2
223	299.31	302.36	3.05	3.05	100	3.05	100	15	4	6	1	2	2	2 gouge on fractures
223	302.36	305.41	3.05	2.96	97	2.96	97	15	4	6	2	1	2	2
223	305.41	308.46	3.05	3.13	103	3.13	103	15	4	6	2	1	2	2
223	308.46	311.51	3.05	3.10	102	3.10	102	15	4	6	3	1	2	2
223	311.51	314.25	2.74	2.70	99	2.53	92	14	4	6	6	2	3	3 gouge on fractures
223	314.25	317.60	3.35	2.79	83	2.04	61	10	4	6	20	5	3	3 30% broken core
223	317.60	319.13	1.53	1.39	91	0.38	25	7	3	5	24	3	3	3 70% broken material
223	319.13	322.17	3.04	2.97	98	2.97	98	15	4	6	0			
223	322.17	324.92	2.75	2.66	97	2.66	97	15	4	6	2	2	3	3 tube pulled
223	324.92	327.96	3.04	3.09	102	3.09	102	15	5	6	1	2	2	2
223	327.96	331.01	3.05	3.05	100	3.05	100	15	5	6	1	2	1	1 slightly curved slip plane at 35 to c.a.
223	331.01	334.37	3.36	3.36	100	3.36	100	15	5	6	2	3	3	3 tube pulled at 332.23m, ring locked
223	334.37	337.41	3.04	2.98	98	2.98	98	15	5	6	2	3	3	3

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
223	337.41	340.46	3.05	2.96	97	2.34	77	14	4	6	9	1	1	1 at 377.76 slick at 35 to c.a., gouge
223	340.46	343.51	3.05	2.98	98	2.98	98	15	4	6	3	3	3	
223	343.51	346.56	3.05	3.05	100	3.05	100	15	5	6	0			
223	346.56	349.61	3.05	3.07	101	3.07	101	15	5	6	0			
223	349.61	352.65	3.04	2.89	95	2.89	95	15	5	6	0			
223	352.65	355.70	3.05	3.00	98	3.00	98	15	5	6	0			
223	355.70	358.75	3.05	3.15	103	3.15	103	15	5	6	0			
223	358.75	361.80	3.05	2.93	96	2.93	96	15	4	6	0			
223	361.80	364.85	3.05	3.05	100	3.05	100	15	4	6	1	1	2	
223	364.85	367.89	3.04	3.12	103	3.12	103	15	5	6	0			
223	367.89	370.94	3.05	3.05	100	3.04	100	15	4	6	1	1	1	1 slick with 1 cm gouge
223	370.94	373.99	3.05	2.93	96	2.86	94	15	5	6	3	1	3	
223	373.99	377.04	3.05	2.97	97	2.97	97	15	5	6	3	3	3	
223	377.04	380.09	3.05	3.26	107	3.26	107	15	5	6	1	1	1	1 weak slicks
223	380.09	382.52	2.43	2.40	99	2.40	99	15	5	6	1	3	3	
223	382.52	385.57	3.05	3.05	100	3.05	100	15	5	6	0			
223	385.57	388.62	3.05	2.98	98	2.98	98	15	4	6	5	1	1	1 weak slicks
223	388.62	391.67	3.05	3.05	100	3.05	100	15	4	6	3	1	1	
223	391.67	394.72	3.05	3.10	102	3.10	102	15	4	6	0			
223	394.72	397.76	3.04	3.20	105	3.20	105	15	4	6	1	3	3	
223	397.76	400.81	3.05	3.10	102	3.10	102	15	4	6	2	3	3	
223	400.81	403.86	3.05	3.12	102	3.12	102	15	5	6	4	1	1	1 gouge on slips
223	403.86	406.30	2.44	2.30	94	2.30	94	15	5	6	1	1	1	
223	406.30	408.74	2.44	2.42	99	2.42	99	15	5	6	0			
224	3.66	8.23	4.57	1.17	26	0.77	17	7	4	5	11	1	1	1 gouge on slips
224	8.23	11.28	3.05	2.03	67	0.60	20	7	3	5	30	1	1	1 gouge on slips
224	11.28	14.33	3.05	1.77	58	1.42	47	10	2	5	11	1	1	1 50% cemented gouge
224	14.33	17.37	3.04	2.97	98	2.88	95	14	2	5	7	5	3	3 80% cemented gouge
224	17.37	20.42	3.05	2.63	86	1.11	36	9	3	5	27	1	1	1 30% cemented gouge
224	20.42	23.47	3.05	2.39	78	2.08	68	14	2	5	7	1	1	1 80% cemented gouge, gouge on slips
224	23.47	26.52	3.05	2.84	93	2.84	93	14	3	3	7	1	1	1 gouge ends at 24.90 m
224	26.52	29.57	3.05	2.87	94	2.87	94	15	4	6	4	1	1	1 competent rock
224	29.57	32.61	3.04	2.97	98	2.94	97	14	4	6	6	1	1	1 trace gouge on slips
224	32.61	35.66	3.05	2.85	93	2.63	86	14	4	6	6	1	1	1 local gouge zones

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
224	35.66	38.71	3.05	3.00	98	2.88	94	14	4	6	6	1	1	1 local gouge zones
224	38.71	41.76	3.05	1.20	39	0.55	18	9	4	6	19	1	1	1 gouge on slips and in broken core
224	41.76	44.81	3.05	2.96	97	2.55	84	13	4	6	10	1	1	1
224	44.81	47.85	3.04	2.75	90	2.50	82	13	4	6	11	1	1	1
224	47.85	50.29	2.44	2.37	97	1.12	46	9	4	6	24	1	1	1 rubble in broken core
224	50.29	52.73	2.44	1.46	60	0.18	7	9	4	6	17	1	1	1 gouge on slips and in broken core
224	52.73	55.17	2.44	0.52	21	0.00	0	6	4	6	15	1	1	1 gouge on slips and in broken core
224	55.17	56.69	1.52	0.65	43	0.00	0	7	4	6	10	1	1	1 gouge on slips and in broken core
224	56.69	59.74	3.05	3.13	103	3.08	101	15	4	6	4	1	1	1
224	59.74	62.79	3.05	2.44	80	1.73	57	13	4	6	11	1	1	1 gouge on slips
224	62.79	64.92	2.13	2.08	98	1.70	80	14	4	6	4	1	1	1 gouge and rubble in broken core
224	64.92	66.75	1.83	1.83	100	1.15	63	11	4	6	11	1	1	1
224	66.75	69.19	2.44	2.16	89	1.39	57	13	4	6	8	1	1	1 gouge on slips
224	69.19	70.41	1.22	1.09	89	0.44	36	10	4	6	9	1	1	1
224	70.41	71.63	1.22	1.07	88	0.00	0	9	4	6	13	1	1	1 gouge on slips
224	71.63	74.68	3.05	3.08	101	2.46	81	13	3	6	12	1	1	1 30% cemented gouge
224	74.68	77.72	3.04	3.08	101	2.89	95	14	4	6	8	1	1	1 gouge on slips
224	77.72	80.77	3.05	3.07	101	2.52	83	13	4	6	10	1	1	1 gouge on slips
224	80.77	83.82	3.05	2.89	95	2.63	86	14	4	6	5	1	1	1 local gouge
224	83.82	86.87	3.05	3.16	104	3.06	100	15	4	6	4	1	1	1 gouge on slips
224	86.87	89.92	3.05	3.05	100	3.05	100	15	4	6	4	1	1	1
224	89.92	92.96	3.04	2.96	97	2.59	85	14	4	6	7	1	1	1
224	92.96	96.01	3.05	2.89	95	1.89	62	10	4	6	25	1	1	1 gouge on slips and in broken core
224	96.01	97.84	1.83	1.69	92	1.44	79	13	4	6	7	1	1	1 trace gouge
224	97.84	99.67	1.83	1.76	96	1.56	85	14	4	6	5	1	1	1
224	99.67	102.72	3.05	3.05	100	2.85	93	15	4	6	4	1	1	1
224	102.72	105.77	3.05	2.97	97	2.85	93	15	4	6	4	1	1	1
224	105.77	108.81	3.04	3.10	102	3.10	102	15	4	6	3	1	1	1
224	108.81	111.86	3.05	2.93	96	2.37	78	12	4	6	16	1	1	1
224	111.86	114.91	3.05	2.55	84	1.82	60	10	4	6	20	1	1	1 gouge and rubble in broken core
224	114.91	117.96	3.05	3.11	102	3.00	98	15	4	6	4	1	1	1 gouge and rubble in breaks
224	117.96	121.00	3.04	3.04	100	2.96	97	15	4	6	4	1	1	1 gouge on slip
224	121.00	124.05	3.05	2.97	97	2.81	92	14	4	6	7	1	1	1 gouge on slip and in broken core
224	124.05	127.10	3.05	3.03	99	2.80	92	14	4	6	6	1	1	1

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
224	127.10	130.15	3.05	3.08	101	2.96	97	14	4	6	6	1	1	1 gouge on slips
224	130.15	133.20	3.05	2.90	95	2.56	84	13	4	6	10	1	1	1 gouge on slips and in broken core
224	133.20	136.25	3.05	2.99	98	2.66	87	14	4	6	6	1	1	
224	136.25	139.29	3.04	2.98	98	2.81	92	14	4	6	8	1	1	
224	139.29	142.34	3.05	2.93	96	2.62	86	14	4	6	7	1	1	
224	142.34	145.39	3.05	3.01	99	3.01	99	15	4	6	3	1	1	
224	145.39	148.44	3.05	3.10	102	2.83	93	14	4	6	7	1	1	1 gouge on slips
224	148.44	151.49	3.05	3.00	98	3.00	98	15	4	6	3	1	1	
224	151.49	154.53	3.04	3.08	101	3.08	101	15	4	6	5	1	1	1 gouge on slips
224	154.53	157.58	3.05	2.99	98	2.94	96	15	4	6	3	1	1	1 gouge on slips
224	157.58	160.63	3.05	3.05	100	3.05	100	15	4	6	3	1	1	
224	160.63	163.68	3.05	3.02	99	2.96	97	14	4	6	6	1	1	1 gouge on slips and in broken core
224	163.68	166.73	3.05	2.88	94	2.60	85	14	4	6	8	1	1	1 gouge on slips and on breaks
224	166.73	169.77	3.04	2.91	96	2.18	72	12	4	6	16	1	1	1 gouge on slips and on breaks
224	169.77	170.38	0.61	0.38	62	0.00	0	14	4	6	8	1	1	
224	170.38	171.60	1.22	1.12	92	0.70	57	10	4	6	11	1	1	
224	171.60	174.65	3.05	2.82	92	2.65	87	14	4	6	8	1	1	1 gouge on slips
224	174.65	177.70	3.05	2.96	97	2.96	97	15	4	6	4	1	1	1 gouge on slips and breaks
224	177.70	180.75	3.05	3.18	104	2.89	95	14	4	6	7	1	1	1 gouge on slips and in broken core
224	180.75	183.79	3.04	3.00	99	3.00	99	15	4	6	4	1	1	1 4mm gouge on slip
224	183.79	185.32	1.53	1.68	110	1.12	73	13	4	6	6	1	1	
224	185.32	188.06	2.74	2.48	91	2.48	91	15	4	6	3	1	1	
224	188.06	191.11	3.05	3.05	100	2.32	76	13	4	6	13	1	1	
224	191.11	194.16	3.05	3.05	100	2.30	75	13	4	6	12	1	1	1 gouge on slips
224	194.16	197.21	3.05	3.07	101	2.41	79	13	4	6	11	1	1	
224	197.21	200.25	3.04	2.93	96	1.73	57	12	4	6	15	5	3	3 10% broken rock with gouge
224	200.25	201.78	1.53	1.65	108	1.01	66	10	4	6	15	1	3	3 gouge on fractures
224	201.78	203.61	1.83	1.93	105	1.20	66	13	4	6	8	1	3	3 gouge on fractures
224	203.61	206.35	2.74	2.49	91	2.28	83	15	4	6	4	1	3	3 5% fault H=2,3
224	206.35	209.40	3.05	3.05	100	2.98	98	15	4	6	4	1	3	
224	209.40	212.45	3.05	2.90	95	2.71	89	15	4	6	3	1	3	3 gouge on fractures
224	212.45	215.49	3.04	2.92	96	2.36	78	13	3	5	12	5	3	3 70% fault H=1,2
224	215.49	218.54	3.05	3.05	100	2.89	95	14	3	5	8	5	3	3 last 1.35m fault gouge H=1,2
224	218.54	221.59	3.05	2.71	89	1.76	58	12	3	5	15	5	3	3 90% fault H=1,2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
224	221.59	224.64	3.05	3.00	98	1.79	59	13	3	5	15	2	3	40% fault material H=1,2
224	224.64	227.69	3.05	2.87	94	1.94	64	13	3	5	10	2	3	50% fault H=2,3, gouge on fractures
224	227.69	230.73	3.04	3.08	101	2.11	69	13	3	5	11	2	3	50% fault H=2,3, gouge on fractures
224	230.73	233.78	3.05	3.16	104	3.00	98	15	3	6	5	1	3	gouge on fractures
224	233.78	236.83	3.05	2.93	96	2.33	76	14	3	6	9	1	3	gouge on fractures
224	236.83	239.88	3.05	2.90	95	1.73	57	13	2	5	11	5	3	90% fault material
224	239.88	242.93	3.05	2.52	83	1.43	47	12	3	6	15	5	3	5-10% broken core with gouge
224	242.93	245.97	3.04	3.08	101	2.98	98	14	3	6	6	5	3	gouge on fractures
224	245.97	249.02	3.05	3.05	100	2.65	87	14	3	6	7	1	3	40% gouge, H=1,2
224	249.02	252.07	3.05	2.87	94	2.72	89	14	4	6	7	1	3	
224	252.07	255.12	3.05	3.00	98	2.69	88	13	4	6	15	5	3	15% broken core with gouge
224	255.12	258.17	3.05	3.23	106	2.19	72	13	4	6	12	2	3	gouge on fractures
224	258.17	261.21	3.04	3.02	99	2.91	96	14	4	6	9	2	3	gouge on fractures
224	261.21	264.26	3.05	3.09	101	2.97	97	14	4	6	6	2	3	gouge on fractures
225	27.43	28.96	1.53	0.84	55	0.44	29	7	4	5	15	1	3	gouge on fractures
225	28.96	29.88	0.92	0.81	88	0.60	65	7	4	4	12	2	3	
225	29.88	30.78	0.90	0.76	84	0.00	0	6	4	4	20	2	2	
225	30.78	32.00	1.22	0.37	30	0.00	0	6	4	4	10	2	3	100% broken core, minor gouge
225	32.00	32.61	0.61	0.45	74	0.00	0	6	4	4	14	2	2	100% broken core, gouge, pyrite fractures
225	32.61	34.44	1.83	0.35	19	0.00	0	6	4	4	20	2	3	100% broken core, minor gouge
225	34.44	35.66	1.22	0.50	41	0.00	0	6	4	4	20	3	3	100% broken core, minor gouge
225	35.66	37.19	1.53	0.76	50	0.24	16	6	4	4	18	2	3	90% broken core
225	37.19	38.40	1.21	0.77	64	0.16	13	7	4	4	15	2	3	90% broken core
225	38.40	40.23	1.83	0.81	44	0.00	0	6	4	5	25	2	2	100% broken core, pyrite on fractures
225	40.23	41.45	1.22	0.70	57	0.00	0	6	4	5	20	2	3	pyrite on fractures
225	41.45	42.37	0.92	0.25	27	0.00	0	6	4	5	6	3	3	
225	42.37	44.20	1.83	0.36	20	0.10	5	6	4	5	15	2	2	
225	44.20	44.50	0.30	0.28	93	0.00	0	6	4	5	10	1	2	dyke
225	44.50	46.63	2.13	1.57	74	1.26	59	9	4	5	17	2	2	dyke
225	46.63	47.85	1.22	0.78	64	0.45	37	7	3	4	12	3	3	dyke to 47.66m
225	47.85	50.29	2.44	0.52	21	0.00	0	6	2	4	20	2	3	minor gouge
225	50.29	52.93	2.64	0.28	11	0.00	0	6	4	5	15	3	3	
225	52.93	53.95	1.02	0.56	55	0.00	0	6	4	5	15	1	2	pyrite on fractures
225	53.95	54.86	0.91	0.36	40	0.00	0	6	4	5	15	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
225	54.86	55.47	0.61	0.48	79	0.00	0	6	4	5	20	1	3	pyrite on fractures, 100% broken core
225	55.47	57.00	1.53	0.59	39	0.12	8	7	3	5	10	2	3	minor gouge
225	57.00	60.05	3.05	0.37	12	0.00	0	6	4	5	20	3	3	100% broken core
225	60.05	63.09	3.04	0.50	16	0.10	3	6	4	5	15	2	3	
225	63.09	66.14	3.05	0.27	9	0.00	0	3	4	5	20	3	3	
225	66.14	67.97	1.83	0.50	27	0.11	6	6	4	5	15	2	3	
225	67.97	68.88	0.91	0.28	31	0.00	0	6	4	5	15	3	3	100% broken core
225	68.88	69.49	0.61	0.57	93	0.11	18	6	3	4	15	3	3	
225	69.49	71.63	2.14	1.54	72	0.90	42	7	3	4	25	2	3	dyke, 15 cm H=2
225	71.63	72.85	1.22	0.80	66	0.16	13	6	4	4	20	2	3	pyrite on fractures
225	72.85	75.29	2.44	2.50	102	1.15	47	9	3	4	30	2	3	
225	75.29	77.11	1.82	1.82	100	1.13	62	10	4	5	18	2	3	gouge on fractures
225	77.11	78.94	1.83	1.71	93	0.98	54	10	4	5	14	3	3	
225	78.94	80.47	1.53	1.37	90	0.60	39	7	4	5	20	3	3	1 weak slicks
225	80.47	81.99	1.52	1.17	77	0.76	50	10	4	5	11	3	3	25 cm shear H=4,3
225	81.99	83.82	1.83	1.60	87	1.18	64	10	4	4	13	3	3	35 cm healed shear, H=3
225	83.82	86.87	3.05	3.13	103	2.81	92	13	4	5	12	2	3	gypsum on fractures
225	86.87	87.17	0.30	0.16	53	0.00	0	6	3	5	10	3	3	gouge H=2,1, 5 cm
225	87.17	90.22	3.05	2.52	83	1.40	46	9	2	4	30	2	2	gypsum on fractures, 88-90.22m shear
225	90.22	91.44	1.22	1.25	102	1.25	102	15	3	4	0			
225	91.44	93.57	2.13	1.73	81	1.47	69	10	3	4	12	2	2	80 cm healed gouge, H=2
225	93.57	96.62	3.05	3.08	101	2.93	96	14	4	5	8	3	3	
225	96.62	99.67	3.05	3.13	103	2.83	93	14	4	5	8	3	3	minor gouge on fractures
225	99.67	102.72	3.05	3.15	103	2.73	90	12	4	5	16	3	3	minor gouge on fractures
225	102.72	105.77	3.05	3.14	103	3.06	100	14	4	5	9	2	3	minor gouge on fractures
225	105.77	108.20	2.43	2.25	93	2.01	83	13	4	5	11	3	3	minor gouge on fractures
225	108.20	111.25	3.05	3.15	103	3.15	103	15	4	5	5	3	3	
225	111.25	113.08	1.83	1.86	102	1.73	95	12	4	5	10	2	2	
225	113.08	114.91	1.83	1.88	103	1.83	100	14	4	5	5	3	2	gouge on fractures
225	114.91	117.96	3.05	2.97	97	2.84	93	14	4	5	9	3	3	gouge on fractures
225	117.96	121.01	3.05	3.03	99	3.03	99	15	4	5	2	3	2	
225	121.01	124.05	3.04	3.07	101	3.07	101	15	4	5	4	3	3	
225	124.05	127.10	3.05	2.95	97	2.95	97	14	4	5	5	2	2	clay on slips
225	127.10	130.15	3.05	3.10	102	2.85	93	14	4	5	6	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
225	130.15	133.20	3.05	3.12	102	3.12	102	15	4	5	5	3	2	gouge and clay on slips
225	133.20	136.25	3.05	3.13	103	2.87	94	14	4	5	9	3	3	gouge and clay on slips
225	136.25	139.30	3.05	3.03	99	3.03	99	15	4	5	4	2	3	gouge and clay on slips
225	139.30	142.34	3.04	3.10	102	2.80	92	14	4	5	10	3	3	
225	142.34	143.56	1.22	1.20	98	0.72	59	7	3	5	20	3	3	30% broken core with minor gouge
225	143.56	145.39	1.83	1.70	93	1.70	93	14	4	5	3	3	3	
225	145.39	148.44	3.05	3.02	99	3.02	99	15	4	5	2	2	2	
225	148.44	150.27	1.83	1.95	107	1.95	107	14	4	5	6	3	3	
225	150.27	153.31	3.04	2.90	95	2.38	78	10	4	5	21	2	2	
225	153.31	155.75	2.44	2.08	85	2.03	83	14	4	5	4	2	2	
225	155.75	157.58	1.83	2.01	110	1.87	102	13	4	5	9	2	2	clay on slips
225	157.58	160.63	3.05	3.15	103	3.15	103	14	4	5	9	2	2	
225	160.63	163.68	3.05	3.04	100	3.04	100	15	4	5	4	2	2	
225	163.68	166.73	3.05	3.05	100	3.05	100	15	4	5	5	2	3	
225	166.73	169.77	3.04	3.12	103	3.12	103	15	4	5	3	2	3	calcite on fractures
225	169.77	172.82	3.05	2.94	96	2.87	94	14	4	5	6	2	3	
225	172.82	175.87	3.05	3.08	101	3.02	99	14	4	5	8	2	2	
225	175.87	178.92	3.05	3.10	102	3.10	102	15	4	5	3	1	1	slicks at 45 to c.a. rake
225	178.92	181.97	3.05	3.03	99	3.03	99	15	4	5	4	3	1	weak slicks
225	181.97	185.01	3.04	2.95	97	2.95	97	15	4	5	1	3	3	
225	185.01	188.06	3.05	3.02	99	2.71	89	14	4	5	8	2	3	
225	188.06	191.11	3.05	2.97	97	2.80	92	14	4	5	8	2	3	
225	191.11	194.16	3.05	2.97	97	2.87	94	14	4	5	5	3	3	
225	194.16	195.68	1.52	1.40	92	1.31	86	13	4	5	7	2	3	
225	195.68	197.51	1.83	1.90	104	1.72	94	12	4	5	10	2	3	
225	197.51	200.25	2.74	2.70	99	2.65	97	14	4	5	7	2	3	
225	200.25	203.30	3.05	3.03	99	2.94	96	15	4	5	5	2	2	gouge and clay on fractures
225	203.30	206.35	3.05	3.08	101	2.95	97	14	4	5	8	2	3	minor gouge on fractures
225	206.35	209.40	3.05	2.54	83	2.23	73	13	3	5	10	2	3	15 cm healed gouge H=2
225	209.40	212.45	3.05	3.00	98	2.81	92	12	3	4	16	2	2	gouge and clay on slips
225	212.45	215.49	3.04	3.10	102	3.05	100	14	4	5	6	3	3	
225	215.49	218.54	3.05	3.01	99	2.90	95	13	4	5	11	2	3	
225	218.54	221.28	2.74	2.86	104	2.15	78	10	4	5	20	1	2	pyrite on fractures
225	221.28	221.89	0.61	0.61	100	0.53	87	14	4	5	2	2	2	pyrite on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
225	221.89	224.64	2.75	2.67	97	2.67	97	14	4	5	7	3	2	pyrite on fractures
225	224.64	227.08	2.44	2.42	99	2.30	94	14	4	5	6	3	3	minor gouge on fractures
225	227.08	230.12	3.04	3.07	101	3.07	101	14	4	5	8	3	3	minor gouge on fractures
225	230.12	232.56	2.44	2.54	104	2.54	104	15	4	5	3	3	3	minor gouge on fractures
225	232.56	234.70	2.14	2.14	100	2.14	100	15	4	5	3	2	3	
225	234.70	236.83	2.13	2.06	97	2.06	97	14	4	5	5	2	3	
225	236.83	239.88	3.05	3.02	99	2.90	95	14	4	5	9	1	2	
225	239.88	242.93	3.05	2.98	98	2.90	95	14	4	5	7	2	3	
225	242.93	244.75	1.82	1.80	99	1.80	99	14	4	5	3	1	2	
225	244.75	246.89	2.14	2.16	101	2.12	99	13	4	5	8	2	3	
225	246.89	249.02	2.13	1.99	93	1.92	90	14	4	5	6	2	3	
225	249.02	252.07	3.05	3.05	100	2.78	91	13	4	5	12	2	2	clay on slips
225	252.07	255.12	3.05	3.05	100	3.00	98	14	4	5	10	2	3	gouge on fractures
225	255.12	258.17	3.05	3.05	100	2.95	97	15	4	5	4	3	3	
225	258.17	261.21	3.04	3.10	102	3.10	102	15	4	5	3	3	3	
225	261.21	264.26	3.05	3.03	99	3.03	99	15	4	5	3	2	2	pyrite on fractures
225	264.26	266.09	1.83	2.22	121	1.96	107	14	4	5	7	1	2	box 39 dropped, pyrite on fractures
225	266.09	266.70	0.61	0.20	33	0.00	0	7	4	5	4	1	3	box 39 dropped
225	266.70	269.75	3.05	2.83	93	2.68	88	14	4	5	7	3	3	box 39 dropped, gouge on fractures
225	269.75	272.80	3.05	3.15	103	2.33	76	12	4	5	18	3	2	
225	272.80	275.84	3.04	3.17	104	2.82	93	13	4	5	14	3	3	
225	275.84	278.89	3.05	3.09	101	2.57	84	13	4	5	13	2	2	clay on slips
225	278.89	281.94	3.05	3.09	101	2.92	96	13	4	5	11	2	2	
225	281.94	282.85	0.91	0.80	88	0.55	60	13	4	5	4	3	3	
225	282.85	285.29	2.44	2.44	100	2.05	84	13	3	5	12	2	2	
225	285.29	288.34	3.05	2.85	93	2.67	88	13	4	5	11	1	2	18 cm healed gouge H=3
225	288.34	291.39	3.05	3.07	101	3.03	99	14	4	5	9	3	3	
225	291.39	294.44	3.05	3.05	100	2.81	92	13	4	5	12	2	3	gouge and clay on slips
225	294.44	297.48	3.04	3.07	101	2.92	96	14	4	5	8	1	3	
225	297.48	300.53	3.05	2.97	97	2.97	97	14	4	5	8	1	2	
225	300.53	303.58	3.05	3.15	103	2.29	75	12	3	5	19	1	2	clay and gouge on fractures
225	303.58	306.63	3.05	2.95	97	2.76	90	13	4	5	11	2	2	clay on slips
225	306.63	309.07	2.44	2.68	110	2.46	101	13	4	5	13	1	2	clay on slips
225	309.07	309.98	0.91	0.88	97	0.88	97	13	4	5	3	3	2	clay on slips

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
225	309.98	310.90	0.92	0.98	107	0.98	107	14	4	5	2	1	2 clay on slips	
226	4.57	5.18	0.61	0.30	49	0.00	0	6	3	4	7	5	4 blocky	
226	5.18	6.40	1.22	0.80	66	0.18	15	6	3	4	15	1	2 blocky	
226	6.40	7.62	1.22	0.53	43	0.18	15	5	3	4	12	2	3 blocky	
226	7.62	10.67	3.05	3.05	100	2.20	72	13	3	6	12	1	2	
226	10.67	13.72	3.05	2.12	70	1.22	40	10	3	5	17	3	2 blocky	
226	13.72	15.54	1.82	1.58	87	0.25	14	7	3	5	21	2	2 blocky	
226	15.54	17.37	1.83	1.85	101	1.57	86	14	3	6	5	2	1	
226	17.37	18.90	1.53	0.68	44	0.00	0	7	3	5	10	2	3 blocky	
226	18.90	21.64	2.74	2.74	100	1.80	66	13	3	6	10	3	2 partially blocky	
226	21.64	23.47	1.83	1.95	107	0.80	44	12	3	6	12	3	2 partially blocky	
226	23.47	26.52	3.05	3.05	100	2.13	70	14	3	6	9	1	2 partially blocky	
226	26.52	29.57	3.05	2.75	90	2.44	80	14	3	6	7	2	3 partially blocky	
226	29.57	32.61	3.04	2.72	89	1.65	54	13	3	5	13	2	4 partially blocky	
226	32.61	35.66	3.05	2.83	93	2.05	67	13	3	5	12	3	1 partially blocky	
226	35.66	38.71	3.05	3.20	105	2.62	86	13	3	5	13	3	1 partially blocky, fault	
226	38.71	41.76	3.05	2.95	97	1.83	60	12	2	4	15	3	4 partially blocky, fault + gouge	
226	41.76	44.81	3.05	2.65	87	1.13	37	11	2	4	17	4	2 partially blocky, fault + gouge	
226	44.81	47.85	3.04	2.65	87	1.18	39	12	2	4	15	2	1 partially blocky, fault + gouge	
226	47.85	50.90	3.05	3.05	100	2.73	90	14	2	4	8	1	2 partially blocky, fault + gouge	
226	50.90	53.95	3.05	2.85	93	2.15	70	13	3	5	11	1	2 partially blocky	
226	53.95	57.00	3.05	3.00	98	2.02	66	12	3	4	16	1	1 partially blocky, fault + gouge	
226	57.00	60.05	3.05	3.10	102	2.35	77	13	3	5	11	1	1	
226	60.05	63.09	3.04	2.90	95	2.90	95	15	4	6	3	4	2	
226	63.09	66.14	3.05	3.05	100	2.85	93	15	4	6	5	1	1	
226	66.14	69.19	3.05	3.05	100	3.05	100	15	4	6	3	2	4	
226	69.19	72.24	3.05	3.10	102	3.10	102	15	4	6	4	3	2	
226	72.24	75.29	3.05	3.00	98	2.40	79	14	4	6	8	1	3	
226	75.29	78.33	3.04	3.04	100	1.80	59	14	4	6	8	2	4 fracture parallel to c.a.	
226	78.33	81.38	3.05	3.05	100	2.95	97	14	4	6	7	1	1	
226	81.38	84.43	3.05	3.05	100	2.35	77	13	4	6	14	1	2	
226	84.43	87.48	3.05	3.05	100	2.52	83	12	4	6	17	1	2	
226	87.48	90.53	3.05	3.05	100	2.80	92	14	3	4	10	1	2 fault	
226	90.53	93.57	3.04	3.05	100	2.70	89	14	2	4	9	1	1 fault +/- gouge	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
226	93.57	96.62	3.05	3.00	98	3.00	98	15	3	4	4	5	3	3 healed fault/shear
226	96.62	99.67	3.05	3.05	100	2.70	89	14	3	5	7	2	2	2 minor shearing
226	99.67	102.72	3.05	3.00	98	2.55	84	14	3	5	6	5	4	4 minor shearing
226	102.72	105.77	3.05	2.60	85	2.60	85	14	3	5	7	1	1	1 minor shearing
226	105.77	108.81	3.04	3.10	102	2.69	88	13	3	5	14	2	1	1 minor shearing
226	108.81	111.86	3.05	3.10	102	2.89	95	14	3	4	9	1	1	1 healed fault/shear
226	111.86	114.91	3.05	3.10	102	2.63	86	14	3	5	7	1	2	
226	114.91	117.96	3.05	3.05	100	2.85	93	15	3	5	5	3	2	
226	117.96	121.01	3.05	3.10	102	2.80	92	14	3	5	8	5	3	3 healed fault/shear
226	121.01	124.05	3.04	3.04	100	3.04	100	15	4	6	4	2	4	
226	124.05	127.10	3.05	2.80	92	2.60	85	14	4	6	7	1	1	
226	127.10	130.15	3.05	3.10	102	2.53	83	14	4	6	9	3	4	
226	130.15	133.20	3.05	3.10	102	2.65	87	14	3	5	9	2	1	
226	133.20	136.25	3.05	3.15	103	2.78	91	14	4	6	6	3	2	
226	136.25	139.29	3.04	3.00	99	2.85	94	15	4	6	5	2	3	
226	139.29	142.34	3.05	3.00	98	2.10	69	13	3	5	11	3	4	4 fault last metre
226	142.34	142.95	0.61	0.61	100	0.15	25	10	3	5	6	3	4	4 fault for 40 cm
226	142.95	145.39	2.44	2.29	94	2.95	121	15	3	5	4	3	3	3 gouge on fractures
226	145.39	148.44	3.05	2.90	95	0.57	19	11	3	5	20	3	2	2 fault for 1m
226	148.44	151.49	3.05	3.05	100	2.90	95	14	3	5	6	1	3	
226	151.49	154.53	3.04	3.04	100	1.83	60	14	4	6	10	3	2	2 blocky
226	154.53	157.58	3.05	3.05	100	2.67	88	14	4	5	6	2	1	1 solid core/healed faulting/shearing
226	157.58	160.63	3.05	3.05	100	2.65	87	14	4	6	6	3	2	2 solid core/healed faulting/shearing
226	160.63	163.68	3.05	3.05	100	2.30	75	13	4	5	12	3	4	4 solid core/healed faulting/shearing
226	163.68	165.51	1.83	1.83	100	0.64	35	10	3	5	18	4	2	2 solid core/healed faulting/shearing\blocky
226	165.51	167.03	1.52	1.52	100	0.22	14	7	3	5	21	2	3	3 blocky
226	167.03	169.77	2.74	2.50	91	2.45	89	14	3	4	5	2	1	1 fault
226	169.77	172.82	3.05	3.05	100	2.80	92	14	3	4	8	3	2	2 fault
226	172.82	175.87	3.05	3.05	100	3.00	98	15	4	6	5	2	2	
226	175.87	178.92	3.05	3.00	98	2.35	77	13	4	6	14	2	2	
226	178.92	181.97	3.05	2.90	95	2.50	82	14	4	6	10	2	2	
226	181.97	185.01	3.04	3.09	102	2.65	87	14	4	6	8	3	3	
226	185.01	188.06	3.05	3.05	100	2.50	82	14	4	6	10	2	2	
226	188.06	191.11	3.05	3.10	102	2.60	85	14	4	6	8	4	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To	Lgth	m.	%	m.								%
226	191.11	194.16	3.05	2.80	92	2.67	88	15	4	6	4	1	3	
226	194.16	197.21	3.05	3.05	100	2.00	66	13	4	5	12	4	1	1 minor fault gouge
226	197.21	200.25	3.04	3.10	102	2.20	72	13	4	5	14	3	2	
226	200.25	203.30	3.05	3.00	98	2.45	80	14	3	4	8	1	1	1 fault gouge to 200.85m
226	203.30	206.35	3.05	3.10	102	2.40	79	13	4	6	13	1	1	
226	206.35	209.40	3.05	3.10	102	1.58	52	10	2	4	22	2	1	1 fault gouge throughout
226	209.40	212.45	3.05	3.05	100	1.95	64	12	3	4	19	2	2	2 minor faulting
226	212.45	215.49	3.04	2.85	94	1.53	50	10	2	2	20	2	2	2 80% gouge
226	215.49	218.54	3.05	2.95	97	2.20	72	2	0	1	12	3	4	4 fault gouge
226	218.54	220.98	2.44	2.25	92	0.35	14	2	0	1	20	3	4	4 fault gouge
226	220.98	221.89	0.91	0.60	66	0.00	0	3	2	3	15	1	2	2 crushed rock
226	221.89	224.64	2.75	1.83	67	0.15	5	3	3	3	20	1	3	3 fault gouge
226	224.64	227.69	3.05	2.10	69	0.39	13	3	3	3	20	1	2	2 fault gouge
226	227.69	230.73	3.04	2.90	95	0.62	20	2	2	3	20	3	3	3 fault gouge
226	230.73	233.78	3.05	2.87	94	0.90	30	2	0	1	8	5	4	4 fault gouge
226	233.78	236.83	3.05	0.61	20	0.00	0	2	2	2	15	5	4	4 gouge + crushed rock
226	236.83	239.88	3.05	1.57	51	0.27	9	2	1	1	15	5	4	4 fault gouge
226	239.88	242.93	3.05	2.10	69	0.39	13	2	0	1	30	3	4	4 fault gouge
227	12.19	14.33	2.14	0.20	9	0.00	0	3	4	5	10	1	1	1 strongly broken core
227	14.33	15.34	1.01	0.69	68	0.00	0	5	4	5	20	1	1	1 strongly broken core local limonite & rubble
227	15.34	16.46	1.12	0.45	40	0.00	0	5	4	5	20	1	1	1 strongly broken core, limonite & rubble
227	16.46	17.07	0.61	0.38	62	0.00	0	5	4	5	15	1	1	1 strongly broken core, limonite & rubble
227	17.07	20.42	3.35	0.33	10	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	20.42	22.25	1.83	0.49	27	0.00	0	5	4	5	15	1	1	1 strongly broken core, limonite & rubble
227	22.25	23.47	1.22	0.35	29	0.00	0	5	4	5	15	1	1	1 strongly broken core, limonite & rubble
227	23.47	24.08	0.61	0.37	61	0.00	0	5	4	5	15	1	1	1 strongly broken core, limonite & rubble
227	24.08	25.30	1.22	0.52	43	0.00	0	5	4	5	15	1	1	1 strongly broken core, limonite & rubble
227	25.30	29.57	4.27	0.99	23	0.12	3	5	4	5	20	1	1	1 strongly broken core, limonite & rubble
227	29.57	32.61	3.04	0.18	6	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	32.61	35.66	3.05	0.44	14	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	35.66	38.71	3.05	0.49	16	0.14	5	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	38.71	39.93	1.22	0.35	29	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	39.93	40.54	0.61	0.12	20	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	40.54	41.45	0.91	0.28	31	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
227	41.45	42.36	0.91	0.33	36	0.00	0	5	4	5	10	1	1	1 strongly broken core, limonite & rubble
227	42.36	43.28	0.92	0.50	54	0.00	0	5	4	6	15	1	1	1 strongly broken core
227	43.28	44.81	1.53	0.27	18	0.00	0	5	4	6	10	1	1	1 strongly broken core
227	44.81	45.72	0.91	0.36	40	0.00	0	5	4	6	10	1	1	1 strongly broken core
227	45.72	46.33	0.61	0.37	61	0.00	0	5	4	6	10	1	1	1 strongly broken core
227	46.33	47.85	1.52	1.26	83	0.51	34	9	4	6	16	1	1	1 gouge on slip planes
227	47.85	49.05	1.20	0.64	53	0.00	0	7	4	6	10	1	1	1 trace gouge in broken core on slips
227	49.05	50.90	1.85	1.15	62	0.11	6	9	3	6	14	1	1	1 30% cemented gouge
227	50.90	51.81	0.91	0.62	68	0.14	15	6	4	6	15	1	1	1 gouge in broken core
227	51.81	53.04	1.23	0.88	72	0.13	11	7	4	6	15	1	1	1 gouge on slips & in broken core
227	53.04	53.95	0.91	0.87	96	0.45	49	7	4	6	12	1	1	1 gouge on slips & in broken core
227	53.95	56.08	2.13	1.99	93	1.62	76	12	3	6	12	1	1	1 20% cemented gouge with rubble
227	56.08	59.13	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 gouge on slips
227	59.13	62.18	3.05	3.02	99	2.95	97	15	4	6	3	1	1	1 gouge on slips
227	62.18	65.23	3.05	3.09	101	3.04	100	15	4	6	4	1	1	1 gouge on slips
227	65.23	68.58	3.35	3.05	91	3.00	90	14	4	6	8	1	1	1 gouge on slips
227	68.58	71.63	3.05	2.96	97	2.74	90	14	4	6	6	1	1	1 gouge on slips
227	71.63	74.68	3.05	2.86	94	2.58	85	13	4	6	12	1	1	1 gouge on slips
227	74.68	77.72	3.04	2.99	98	2.81	92	14	4	6	6	1	1	1 gouge on slips
227	77.72	79.25	1.53	1.26	82	1.11	73	13	4	6	6	1	1	1 gouge on slips
227	79.25	82.30	3.05	3.02	99	2.52	83	13	4	6	14	1	1	1 gouge on slips
227	82.30	84.73	2.43	2.07	85	1.78	73	14	4	6	6	1	1	1 gouge on slips + 8 cm. of gouge
227	84.73	87.48	2.75	2.57	93	2.48	90	14	4	6	5	1	1	1 gouge on slips
227	87.48	90.53	3.05	2.85	93	2.62	86	14	4	6	7	1	1	1 gouge on slips
227	90.53	93.57	3.04	2.89	95	2.67	88	14	4	6	6	1	1	1 gouge on slips + 2 cm. gouge 5 - 10 to c.a.
227	93.57	96.62	3.05	2.98	98	2.82	92	14	4	6	7	1	1	1 gouge on slips + cemented gouge in shear
227	96.62	99.67	3.05	2.85	93	2.68	88	14	4	6	7	1	1	1
227	99.67	101.19	1.52	1.62	107	1.62	107	15	4	6	2	1	1	1
227	101.19	104.24	3.05	2.88	94	2.88	94	14	4	6	5	1	1	1 2-5 cm shear zones
227	104.24	105.77	1.53	1.42	93	1.36	89	14	4	6	4	1	1	1 gouge on slips
227	105.77	108.81	3.04	2.85	94	2.72	89	14	4	6	8	1	1	1 61cm shear zone at 25 to c.a.
227	108.81	111.86	3.05	1.74	57	1.49	49	13	4	6	7	1	1	1 15 cm gouge
227	111.86	114.91	3.05	2.60	85	1.99	65	12	4	6	14	1	1	1 gouge on slips
227	114.91	117.96	3.05	3.03	99	2.83	93	14	4	6	6	1	1	1 trace gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To	Lgth	m.	%	m.								%
227	117.96	121.01	3.05	3.12	102	2.97	97	15	4	6	3	1	1	
227	121.01	124.05	3.04	2.77	91	2.54	84	15	4	6	4	1	1	
227	124.05	127.10	3.05	2.52	83	1.38	45	10	4	6	17	1	1	1 trace gouge on slips
227	127.10	128.93	1.83	1.55	85	1.18	64	12	4	6	9	1	1	1 trace gouge on slips
227	128.93	132.59	3.66	3.11	85	2.70	74	14	4	6	9	1	1	
227	132.59	136.25	3.66	3.77	103	3.77	103	15	4	6	4	1	1	1 2.05m shear zone, gouge on slips
227	136.25	139.29	3.04	2.95	97	2.95	97	15	4	6	2	1	1	1 gouge on slips
227	139.29	142.34	3.05	3.10	102	3.10	102	15	4	6	3	1	1	1 breaks on gypsum veins
227	142.34	145.39	3.05	2.97	97	2.97	97	15	4	6	2	1	1	
227	145.39	148.44	3.05	3.02	99	3.02	99	15	4	6	4	1	1	
227	148.44	151.49	3.05	3.09	101	3.09	101	15	4	6	3	1	1	
227	151.49	154.53	3.04	2.95	97	1.95	64	15	4	6	1	1	1	2 break on gypsum veins
227	154.53	157.58	3.05	3.01	99	2.91	95	15	4	6	3	3	3	
227	157.58	160.63	3.05	2.99	98	2.99	98	15	4	6	4	3	1	
227	160.63	163.68	3.05	3.02	99	2.90	95	15	4	6	3	5	3	
227	163.68	166.73	3.05	2.95	97	2.95	97	15	4	6	2	1	1	1 gouge on slip
227	166.73	169.77	3.04	3.08	101	3.04	100	15	4	6	3	1	1	1 gouge on slip
227	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	1	1	1	
227	172.82	175.87	3.05	3.03	99	2.88	94	15	4	6	4	1	1	
227	175.87	178.92	3.05	2.98	98	2.98	98	15	4	6	3	1	1	
227	178.92	181.36	2.44	2.30	94	1.78	73	13	4	6	10	1	1	1 2 cm gouge in break
227	181.36	184.40	3.04	2.86	94	2.03	67	10	4	6	21	1	1	1 gouge on slips and in breaks
227	184.40	186.54	2.14	3.03	142	2.03	95	15	4	6	3	1	1	
227	186.54	189.59	3.05	3.05	100	2.89	95	14	4	6	10	1	1	1 gouge on slips
227	189.59	192.63	3.04	2.95	97	2.63	87	14	4	6	5	1	1	1 gouge on slips
227	192.63	195.68	3.05	2.92	96	2.92	96	15	4	6	4	1	1	1 gouge on slips
227	195.68	198.73	3.05	3.00	98	2.96	97	14	4	6	8	1	1	1 2-3mm gouge on slips
227	198.73	201.78	3.05	3.05	100	3.05	100	15	3	6	4	1	1	1 1 m of cemented gouge
227	201.78	204.83	3.05	2.99	98	2.93	96	15	4	6	5	2	2	2 trace gouge in broken core
227	204.83	207.87	3.04	3.04	100	3.00	99	15	4	6	4	1	1	1 trace gouge
227	207.87	210.92	3.05	3.02	99	3.02	99	15	4	6	3	1	1	1 trace gouge
227	210.92	213.97	3.05	3.09	101	3.06	100	15	4	6	4	1	1	1 trace gouge
227	213.97	217.02	3.05	3.05	100	3.05	100	15	4	6	3	1	1	
227	217.02	220.09	3.07	3.00	98	3.00	98	15	4	6	2	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
227	220.09	223.11	3.02	3.00	99	3.00	99	15	4	6	2	2	2	
227	223.11	226.16	3.05	3.07	101	3.07	101	15	4	6	4	1	1	1 breaks are on gypsum veins
227	226.16	229.21	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 pyrite and gouge on slip
227	229.21	232.26	3.05	3.05	100	3.05	100	15	4	6	4	1	1	
227	232.26	235.31	3.05	3.02	99	3.02	99	15	4	6	1	2	1	
227	235.31	238.35	3.04	3.04	100	3.04	100	15	4	6	2	1	1	1 breaks are on gypsum veins
227	238.35	241.40	3.05	3.05	100	3.05	100	15	4	6	1	1	1	1 30 cm grey dyke
227	241.40	244.45	3.05	3.02	99	3.02	99	15	4	6	1	3	2	
227	244.45	247.50	3.05	3.08	101	3.08	101	15	4	6	2	1	1	
227	247.50	250.55	3.05	2.93	96	2.93	96	15	4	6	4	1	1	
227	250.55	253.59	3.04	3.11	102	3.11	102	15	4	6	3	1	1	1 trace gouge-most breaks on gypsum veins
227	253.59	256.64	3.05	3.00	98	3.00	98	15	4	6	3	1	1	1 gouge on slips
227	256.64	259.69	3.05	2.96	97	2.96	97	15	4	6	5	1	1	1 gouge on slips
227	259.69	262.74	3.05	3.03	99	3.03	99	15	4	6	3	1	1	1 gouge on slips
227	262.74	265.79	3.05	3.05	100	3.05	100	14	4	6	6	1	1	1 local 5-10 cm cemented gouge
227	265.79	268.83	3.04	2.99	98	2.99	98	15	4	6	3	1	1	
227	268.83	271.88	3.05	2.97	97	2.97	97	15	4	6	2	1	1	
227	271.88	274.93	3.05	3.05	100	3.02	99	15	4	6	4	1	1	1 2 mm gouge on slip
227	274.93	277.98	3.05	3.02	99	3.02	99	15	4	6	1	1	1	1 breaks are on gypsum veins
227	277.98	280.42	2.44	2.24	92	2.24	92	15	4	6	2	2	2	2 breaks are on gypsum veins
227	280.42	283.46	3.04	2.98	98	2.98	98	15	4	6	1	1	1	
227	283.46	286.51	3.05	2.83	93	2.79	91	15	4	6	3	1	1	1 2 cm cemented gouge
227	286.51	289.56	3.05	3.02	99	3.02	99	15	4	6	2	1	1	
227	289.56	291.69	2.13	2.13	100	2.13	100	15	4	6	1	1	1	
227	291.69	294.74	3.05	1.74	57	1.32	43	9	4	6	20	1	1	1 last 40 cm is rubble-core loss
227	294.74	296.88	2.14	0.14	7	0.00	0	3	4	6	20	1	1	1 redrilled rubble and gouge
227	296.88	299.31	2.43	0.86	35	0.18	7	3	4	6	20	1	1	1 10 cm is dyke
227	299.31	302.36	3.05	0.00	0	0.00	0	1						no recovery
228	3.96	8.23	4.27	0.40	9	0.00	0							boulder and brown sill
228	8.23	11.28	3.05	0.70	23	0.00	0							soil/till
228	11.28	14.33	3.05	1.00	33	0.50	16		0	5			5	soil to gouge
228	14.33	17.37	3.04	3.20	105	3.00	99	14	0	5	8		5	3 crush/gouge
228	17.37	20.42	3.05	2.00	66	0.80	26	7	0	5	34		3	2
228	20.42	23.47	3.05	3.10	102	2.15	70	10	1	5	23		3	2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
228	23.47	26.52	3.05	3.25	107	2.45	80	10	1	6	23	3	2	
228	26.52	29.57	3.05	2.90	95	1.50	49	9	1	6	31	3	2	
228	29.57	32.61	3.04	2.90	95	1.55	51	10	2	6	27	1	2	
228	32.61	35.66	3.05	2.75	90	2.10	69	12	3	6	17	1	2	
228	35.66	38.71	3.05	2.80	92	1.70	56	10	3	6	24	2	2	
228	38.71	41.76	3.05	3.40	111	3.25	107	13	3	6	14	3	2	
228	41.76	44.81	3.05	3.08	101	2.28	75	13	3	6	14	3	2	
228	44.81	47.85	3.04	3.05	100	2.39	79	10	3	6	24	1	2	
228	47.85	50.90	3.05	3.20	105	2.84	93	13	3	6	14	3	2	
228	50.90	53.95	3.05	2.90	95	2.70	89	14	3	6	9	3	2	
228	53.95	57.00	3.05	2.85	93	2.70	89	14	3	6	7	3	2	
228	57.00	60.05	3.05	2.90	95	2.40	79	13	3	6	12	3	2	2 minor clay on slips
228	60.05	63.09	3.04	3.10	102	2.40	79	12	3	6	16	3	2	
228	63.09	66.14	3.05	3.15	103	3.05	100	14	3	6	6	3	2	
228	66.14	69.19	3.05	3.15	103	3.15	103	14	3	6	8	3	2	2 minor clay on slips
228	69.19	72.24	3.05	3.05	100	3.05	100	14	3	6	7	2	2	2 minor clay on slips
228	72.24	75.29	3.05	3.10	102	3.10	102	14	3	6	6	3	2	2 minor clay on slips
228	75.29	78.33	3.04	3.10	102	3.10	102	14	3	6	10	2	2	2 minor clay on slips
228	78.33	81.38	3.05	3.05	100	3.00	98	14	2	6	7	3	2	2 minor clay on slips, weak crush zone
228	81.38	84.43	3.05	3.05	100	2.95	97	14	3	6	6	3	2	1 one joint with slicks
228	84.43	87.48	3.05	3.05	100	3.05	100	15	3	6	5	3	2	
228	87.48	90.53	3.05	3.07	101	2.95	97	14	3	6	9	3	2	2 minor clay on joints
228	90.53	93.57	3.04	3.10	102	3.00	99	14	1	6	10	3	2	2 weak crush zone
228	93.57	96.62	3.05	3.00	98	3.00	98	14	2	6	7	3	2	
228	96.62	99.67	3.05	3.10	102	2.60	85	13	1	6	14	3	2	1 weak crush zone, minor gouge
228	99.67	102.72	3.05	2.98	98	2.98	98	14	3	6	7	3	2	2 minor clay on fractures
228	102.72	105.77	3.05	2.98	98	2.78	91	14	3	6	9	3	2	2 minor clay on fractures
228	105.77	108.81	3.04	3.20	105	2.90	95	13	3	6	12	3	2	2 minor clay on fractures
228	108.81	111.86	3.05	3.10	102	3.05	100	14	1	6	9	2	2	
228	111.86	114.91	3.05	3.00	98	2.70	89	13	2	6	13	1	2	2 minor crush zone
228	114.91	117.96	3.05	2.95	97	2.25	74	12	2	6	15	2	2	2 minor crush zone
228	117.96	121.01	3.05	2.90	95	1.85	61	10	1	6	22	1	2	1 minor crush, clay on fractures at 35 to c.a.
228	121.01	124.05	3.04	2.90	95	2.80	92	13	1	6	10	1	2	2 minor crush, clay on fractures
228	124.05	127.10	3.05	2.90	95	1.60	52	10	2	6	26	1	2	2 minor crush, clay on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
228	127.10	130.15	3.05	3.40	111	3.20	105	13	2	6	12	1	2	2 minor crush clay on fractures, some pyrite
228	130.15	133.20	3.05	3.20	105	2.45	80	13	2	6	15	3	1	1 minor crush, clay on fractures at 35 to c.a.
228	133.20	136.25	3.05	3.05	100	1.85	61	10	2	6	23	3	2	2 minor clay on fractures, minor crush
228	136.25	139.29	3.04	2.95	97	2.65	87	13	3	6	12	3	2	2 minor clay on fractures
228	139.29	142.34	3.05	2.95	97	2.55	84	12	3	6	15	3	2	2 minor clay on fractures, shearing 20 to c.a.
228	142.34	145.39	3.05	2.80	92	1.55	51	10	2	6	19	1	2	2 minor crush, clay on fractures, shearing 50 to c.a.
228	145.39	148.44	3.05	3.05	100	2.35	77	12	2	6	17	1	1	1 minor clay on fractures
229	9.14	12.80	3.66	0.75	20	0.22	6	7	3	4	12	5	3	3 35 % broken core with gouge
229	12.80	15.84	3.04	0.33	11	0.00	0	3	3	4	20	5	3	3 broken core with gouge
229	15.84	17.37	1.53	0.62	41	0.00	0	6	3	4	20	5	3	3 broken core with gouge
229	17.37	20.42	3.05	0.76	25	0.00	0	6	3	4	20	5	3	3 broken core with gouge
229	20.42	23.47	3.05	1.72	56	0.21	7	2	2	4	10	5	3	3 90 % fault gouge
229	23.47	24.99	1.52	1.47	97	0.32	21	8	2	5	10	2	3	3 10 - 15 % gouge
229	24.99	26.52	1.53	0.87	57	0.22	14	2	2	5	15	5	3	3 50 % gouge
229	26.52	27.43	0.91	0.37	41	0.11	12	7	2	5	12	5	3	3 broken rock with gouge
229	27.43	28.96	1.53	1.16	76	0.56	37	9	3	6	15	2	3	3 broken rock with gouge
229	28.96	29.57	0.61	0.53	87	0.13	21	9	3	6	15	5	3	3 broken rock with gouge
229	29.57	30.78	1.21	0.83	69	0.49	40	13	3	6	5	1	3	3 4 cm. gouge H = 2
229	30.78	32.00	1.22	0.86	70	0.53	43	13	3	6	12	1	3	3 gouge on fractures
229	32.00	34.14	2.14	0.52	24	0.11	5	6	3	6	13	2	3	3 30 % gouge H = 2
229	34.14	35.05	0.91	0.50	55	0.36	40	7	3	6	10	2	3	3
229	35.05	36.27	1.22	0.15	12	0.00	0	5	3	6	10	5	3	3
229	36.27	38.71	2.44	0.28	11	0.13	5	5	3	6	15	5	3	3
229	38.71	40.23	1.52	1.44	95	0.67	44	12	3	6	17	5	3	3 15% gouge
229	40.23	42.67	2.44	1.90	78	0.45	18	5	2	5	20	5	3	3 50 % gouge H - 2
229	42.67	45.72	3.05	3.12	102	3.12	102	15	3	6	3	1	3	3 gouge on fractures
229	45.72	47.85	2.13	2.03	95	2.03	95	15	3	6	3	1	3	3 gypsum veins on fractures
229	47.85	50.90	3.05	3.02	99	3.02	99	15	3	6	4	1	3	3 gypsum veins on fractures
229	50.90	53.95	3.05	3.05	100	2.91	95	15	3	6	5	2	3	3 30 % fault, H = 2
229	53.95	57.00	3.05	2.96	97	2.96	97	15	3	6	2	2	3	3 fracturing on gypsum veins
229	57.00	60.05	3.05	3.10	102	3.00	98	15	3	6	4	1	3	3 8 cm. gouge, H = 1,2
229	60.05	62.49	2.44	2.46	101	2.12	87	15	3	6	13	1	3	3 gouge and gypsum on fractures
229	62.49	65.53	3.04	2.98	98	2.13	70	14	3	6	9	1	3	3 gouge and gypsum on fractures
229	65.53	68.58	3.05	2.86	94	2.78	91	14	3	6	5	1	3	3 gouge and gypsum on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
229	68.58	71.63	3.05	3.07	101	3.01	99	15	4	6	2	1	3 gouge and gypsum on fractures	
229	71.63	74.68	3.05	3.05	100	3.05	100	15	4	6	2	1	3 gouge and gypsum on fractures	
229	74.68	77.24	2.56	3.05	119	2.96	116	15	4	6	4	5	3 1 m. crush zone H = 1,2 ,gouge	
229	77.24	81.08	3.84	3.02	79	2.72	71	14	4	6	6	5	3 0.5 m. crush zone H =1, 2	
229	81.08	84.12	3.04	3.07	101	2.90	95	14	4	6	8	2	3 1.0 m. crush zone H =1, 2	
229	84.12	87.17	3.05	3.04	100	3.04	100	15	4	6	2	2	3	
229	87.17	90.22	3.05	3.07	101	3.07	101	15	4	6	1	1	3 fracture on gypsum veins	
229	90.22	93.27	3.05	3.08	101	3.08	101	15	4	6	1	1	3 7 cm. gouge H = 1	
229	93.27	96.32	3.05	3.07	101	3.07	101	15	4	6	3	1	3 fractures on gypsum veins	
229	96.32	99.36	3.04	3.10	102	3.10	102	15	4	6	1	1	3 fractures on gypsum veins	
229	99.36	102.72	3.36	3.03	90	3.03	90	15	4	6	3	1	3 fractures on gypsum veins	
229	102.72	105.77	3.05	3.02	99	3.02	99	15	4	6	2	1	3 fractures on gypsum veins	
229	105.77	108.81	3.04	3.08	101	3.08	101	15	4	6	1	2	3 fractures on gypsum veins	
229	108.81	111.86	3.05	3.09	101	3.09	101	15	4	6	2	2	3 fractures on gypsum veins	
229	111.86	114.91	3.05	3.14	103	3.14	103	15	4	6	2	1	3 fractures on gypsum veins	
229	114.91	117.96	3.05	3.08	101	3.08	101	15	4	6	1	1	3 fractures on gypsum veins	
229	117.96	121.01	3.05	3.00	98	3.00	98	15	4	6	4	1	3 fractures on gypsum veins	
229	121.01	124.05	3.04	2.97	98	2.69	88	14	4	6	6	2	3 121.7 - 125.05 m. crush zone	
229	124.05	127.10	3.05	3.08	101	3.08	101	15	4	6	4	1	3 fracturing on gypsum veins	
229	127.10	130.15	3.05	3.10	102	3.10	102	15	4	6	2	1	3 fracturing on gypsum veins	
229	130.15	133.20	3.05	3.05	100	3.05	100	15	4	6	4	2	3 fracturing on gypsum veins	
229	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6	3	2	3 fracturing on gypsum veins	
229	136.25	139.29	3.04	3.07	101	2.90	95	15	4	6	4	2	3 138.3 - 140.77 m., crush zone	
229	139.29	142.34	3.05	3.05	100	3.00	98	15	4	6	3	1	3	
229	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	2	1	3 fracturing on gypsum veins	
229	145.39	148.44	3.05	3.00	98	3.00	98	15	4	6	2	1	3 fracturing on gypsum veins	
229	148.44	151.49	3.05	3.12	102	3.12	102	15	4	6	3	1	3 fracturing on gypsum veins	
229	151.49	154.53	3.04	3.11	102	3.11	102	15	4	6	1	1	3 fracturing on gypsum veins	
229	154.53	157.58	3.05	3.02	99	3.02	99	15	4	6	2	1	3 fracturing on gypsum veins	
229	157.58	160.63	3.05	3.03	99	2.46	81	14	4	6	10	5	3 fracturing on gypsum veins	
229	160.63	163.68	3.05	3.07	101	3.07	101	15	4	6	1	1	3 fracturing on gypsum veins	
229	163.68	166.73	3.05	3.02	99	3.02	99	15	4	6	3	1	3 fracturing on gypsum veins	
229	166.73	169.77	3.04	3.13	103	3.13	103	15	4	6	2	1	3 fracturing on gypsum veins	
229	169.77	172.82	3.05	3.05	100	3.05	100	15	4	6	3	1	3 fracturing on gypsum veins	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
229	172.82	175.87	3.05	3.05	100	3.05	100	15	4	6	2	1	3	5 cm. gouge gypsum veins
229	175.87	178.92	3.05	3.11	102	3.11	102	15	4	6	2	1	3	fracturing on gypsum veins
229	178.92	181.97	3.05	3.05	100	3.05	100	15	4	6	3	1	3	fracturing on gypsum veins
229	181.97	185.01	3.04	2.94	97	2.94	97	15	4	6	4	1	3	fracturing on gypsum veins
229	185.01	188.06	3.05	3.10	102	3.10	102	15	4	6	3	1	3	fracturing and gouge on gypsum veins
229	188.06	191.11	3.05	3.05	100	3.05	100	15	4	6	1	1	3	fracturing on gypsum veins
229	191.11	194.16	3.05	3.13	103	3.00	98	15	4	6	4	2	3	50 % crush zone
229	194.16	197.21	3.05	3.05	100	3.05	100	15	4	6	2	1	3	fracture on gypsum veins
230	3.66	4.57	0.91	0.83	91	0.00	0	4	4	4	15	1	1	pervasive limonite
230	4.57	5.49	0.92	0.63	68	0.00	0	4	4	4	15	1	1	pervasive limonite
230	5.49	7.01	1.52	0.86	57	0.00	0	4	4	5	15	1	1	limonite on fractures
230	7.01	9.14	2.13	1.84	86	1.28	60	13	4	6	8	1	1	trace gouge on fractures and broken core
230	9.14	10.36	1.22	1.10	90	0.69	57	13	4	6	5	1	1	trace gouge on fractures and broken core
230	10.36	13.41	3.05	2.07	68	1.89	62	14	4	6	4	1	1	
230	13.41	15.85	2.44	2.50	102	1.64	67	10	4	6	20	1	1	gouge in broken core
230	15.85	18.29	2.44	1.93	79	0.58	24	10	4	6	17	1	1	gouge in broken core
230	18.29	21.03	2.74	2.23	81	0.49	18	10	4	6	20	1	1	gouge in broken core
230	21.03	22.86	1.83	1.70	93	1.57	86	13	4	6	7	1	1	gouge in broken core
230	22.86	25.91	3.05	2.98	98	2.64	87	14	4	6	10	1	1	
230	25.91	28.96	3.05	2.92	96	2.44	80	14	4	6	10	1	1	gouge on fractures
230	28.96	29.57	0.61	0.65	107	0.65	107	15	4	6	1	1	1	
230	29.57	32.61	3.04	2.67	88	2.51	83	15	4	6	4	2	3	
230	32.61	35.66	3.05	2.94	96	2.82	92	15	4	6	3	2	3	gouge on fractures
230	35.66	38.71	3.05	3.14	103	3.00	98	15	4	6	2	1	3	
230	38.71	41.76	3.05	3.05	100	2.82	92	15	4	6	4	5	3	gouge on fractures
230	41.76	44.81	3.05	3.09	101	3.09	101	15	4	6	4	2	3	gouge on fractures
230	44.81	47.85	3.04	2.91	96	2.91	96	15	4	6	3	2	3	gouge on fractures
230	47.85	50.90	3.05	3.11	102	2.78	91	15	4	6	5	2	3	gouge on fractures
230	50.90	53.95	3.05	3.05	100	2.52	83	13	4	6	12	2	3	gouge on fractures, 5 - 10 % broken core
230	53.95	57.00	3.05	3.13	103	2.56	84	15	4	6	3	2	3	gouge on fractures
230	57.00	60.05	3.05	2.78	91	2.61	86	15	4	6	3	2	3	
230	60.05	63.09	3.04	3.17	104	3.05	100	15	4	6	3	2	3	
230	63.09	66.14	3.05	3.18	104	2.99	98	15	4	6	4	1	3	30 cm. fault H = 2
230	66.14	69.19	3.05	3.01	99	2.86	94	15	4	6	3	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
230	69.19	72.24	3.05	3.05	100	2.81	92	15	4	6	4	5	3	gouge on fractures
230	72.24	75.29	3.05	2.84	93	2.84	93	15	4	6	3	1	3	gouge on fractures and gypsum
230	75.29	78.33	3.04	3.14	103	2.79	92	15	4	6	6	2	3	gouge on fractures and gypsum
230	78.33	81.38	3.05	3.15	103	2.65	87	13	4	6	15	5	3	gouge on fractures
230	81.38	84.43	3.05	2.67	88	2.14	70	15	4	6	4	2	3	
230	84.43	87.48	3.05	3.05	100	3.05	100	15	4	6	2	2	2	
230	87.48	90.53	3.05	3.09	101	3.09	101	15	4	6	2	1	3	gouge on fractures
230	90.53	93.57	3.04	2.94	97	2.26	74	14	4	6	8	1	3	some fractures very slick others gouge
230	93.57	96.62	3.05	3.17	104	3.17	104	15	4	6	3	1	3	gouge on fractures
230	96.62	99.67	3.05	3.00	98	3.00	98	15	4	6	2	1	2	
230	99.67	102.72	3.05	3.10	102	3.10	102	15	4	6	1	1	3	gouge on fractures
230	102.72	105.77	3.05	3.07	101	2.96	97	15	4	6	2	1	3	14 cm. gouge at 55 to c.a.
230	105.77	108.81	3.04	3.00	99	2.81	92	15	4	6	3	2	2	
230	108.81	111.86	3.05	3.07	101	3.07	101	15	4	6	4	1	3	slick fracture at 30 to c.a. others gouge
230	111.86	114.91	3.05	2.98	98	2.79	91	15	4	6	1	2	3	
230	114.91	117.96	3.05	3.05	100	2.23	73	14	4	6	6	2	3	5 % broken core with gouge
230	117.96	121.01	3.05	2.97	97	2.97	97	15	4	6	4	2	3	4 cm. gouge at 8 to c.a.
230	121.01	124.05	3.04	2.94	97	2.09	69	12	4	6	15	1	3	10 % broken core with gouge 45 to c.a.
230	124.05	127.10	3.05	2.96	97	2.96	97	15	4	6	4	1	2	pyrite on fractures, slip plane 35 to c.a.
230	127.10	130.15	3.05	2.88	94	2.81	92	15	4	6	3	1	3	pyrite on fractures, slick
230	130.15	133.20	3.05	3.15	103	2.93	96	13	4	6	15	2	3	20 % broken core
230	133.20	136.25	3.05	2.97	97	2.59	85	14	4	6	9	1	3	gouge on fractures
230	136.25	139.29	3.04	3.04	100	2.27	75	14	4	6	7	1	3	40 cm. fault 40 to c.a., gouge fault
230	139.29	142.34	3.05	2.96	97	2.15	70	14	4	6	6	1	2	some fractures with gouge, others slick
230	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
230	145.39	148.44	3.05	3.17	104	3.17	104	15	4	6	1	1	2	
230	148.44	151.49	3.05	3.05	100	3.05	100	15	4	6	3	1	1	
230	151.49	154.53	3.04	2.95	97	2.95	97	15	4	6	2	1	2	
230	154.53	157.58	3.05	3.15	103	3.15	103	15	4	6	2	1	3	
230	157.58	160.63	3.05	2.89	95	2.89	95	15	4	6	3	1	2	
230	160.63	163.68	3.05	2.82	92	2.82	92	15	4	6	1	1	1	
230	163.68	166.73	3.05	3.16	104	3.16	104	15	4	6	1	2	3	minor gouge on fracture
230	166.73	169.77	3.04	2.68	88	1.80	59	13	4	6	10	2	3	
230	169.77	172.82	3.05	3.05	100	2.67	88	14	4	6	6	2	3	

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
230	172.82	175.87	3.05	3.05	100	2.80	92	14	4	6	7	2	3	5% broken core with gouge
230	175.87	178.92	3.05	3.12	102	3.12	102	15	4	6	3	1	3	
230	178.92	181.97	3.05	3.13	103	2.96	97	15	4	6	3	2	3	
230	181.97	185.01	3.04	2.91	96	2.39	79	14	4	6	9	5	3	5% broken core with gouge
230	185.01	188.06	3.05	2.86	94	2.86	94	15	4	6	2	1	2	
230	188.06	191.11	3.05	3.40	111	2.31	76	13	4	6	12	2	3	5-10% broken core with gouge
230	191.11	194.16	3.05	2.79	91	2.70	89	14	4	6	5	1	3	gouge on fractures
230	194.16	197.21	3.05	3.10	102	2.73	90	15	4	6	5	2	3	
230	197.21	200.25	3.04	2.92	96	2.70	89	15	4	6	4	1	2	
230	200.25	203.30	3.05	3.01	99	3.01	99	15	4	6	3	1	2	
230	203.30	206.35	3.05	3.03	99	3.03	99	15	4	6	2	1	2	
230	206.35	209.40	3.05	3.05	100	3.05	100	15	4	6	3	1	3	minor gouge on fractures
230	209.40	212.45	3.05	2.96	97	2.96	97	15	4	6	1	1	2	
230	212.45	215.49	3.04	3.04	100	2.81	92	15	4	6	5	1	3	13 cm gouge H=1,2
230	215.49	218.54	3.05	2.99	98	2.74	90	15	4	6	3	1	3	gouge on fractures
230	218.54	221.59	3.05	3.02	99	3.02	99	15	4	6	1	1	1	
230	221.59	224.64	3.05	3.20	105	3.20	105	15	4	6	2	1	1	
230	224.64	227.69	3.05	2.67	88	2.67	88	15	4	6	2	2	3	
230	227.69	230.73	3.04	3.14	103	3.14	103	15	5	6	1	1	2	
230	230.73	233.78	3.05	2.87	94	2.87	94	15	5	6	0			
230	233.78	236.83	3.05	3.14	103	3.14	103	15	5	6	2	1	2	
230	236.83	239.88	3.05	3.04	100	3.04	100	15	5	6	0			
230	239.88	242.93	3.05	3.02	99	2.83	93	15	5	6	4	1	3	fault @ 242.25m @ 35 to c.a.
230	242.93	245.97	3.04	3.07	101	2.57	85	9	3	5	6	5	3	fault with intermittent gouge sections
230	245.97	249.02	3.05	2.92	96	2.39	78	9	3	5	7	5	3	fault with intermittent gouge sections
230	249.02	252.07	3.05	3.05	100	2.19	72	9	3	5	5	5	3	fault with intermittent gouge sections
230	252.07	255.12	3.05	2.66	87	2.59	85	9	3	5	15	5	3	fault with intermittent gouge sections
230	255.12	258.17	3.05	2.53	83	1.30	43	9	3	5	11	5	3	fault with intermittent gouge sections
230	258.17	261.21	3.04	2.94	97	2.19	72	9	3	5	14	5	3	fault with intermittent gouge sections
230	261.21	264.26	3.05	2.85	93	2.00	66	8	3	5	10	5	3	fault with intermittent gouge sections
230	264.26	267.31	3.05	3.20	105	3.02	99	7	3	5	8	5	3	fault with intermittent gouge sections
230	267.31	270.36	3.05	2.96	97	1.84	60	7	3	5	12	5	3	fault with intermittent gouge sections
230	270.36	273.41	3.05	2.97	97	1.99	65	7	3	5	9	5	3	fault with intermittent gouge sections
230	273.41	276.45	3.04	3.23	106	2.83	93	13	3	5	14	2	3	fault with intermittent gouge sections

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
230	276.45	279.50	3.05	1.60	52	0.36	12	7	3	5	25	3	3	3 fault with intermittent gouge sections
230	279.50	282.55	3.05	2.09	69	1.20	39	9	2	5	25	5	3	3 fault with intermittent gouge sections
230	282.55	285.60	3.05	2.57	84	1.14	37	9	3	5	30	3	3	3 fault with intermittent gouge sections
230	285.60	288.65	3.05	2.26	74	1.02	33	9	2	4	30	5	3	3 fault with intermittent gouge sections
230	288.65	291.69	3.04	2.95	97	2.37	78	10	3	4	20	2	2	2 fault ends @ 289.50 m
230	291.69	294.74	3.05	2.97	97	2.72	89	13	3	5	13	2	2	
230	294.74	297.79	3.05	2.66	87	0.67	22	7	3	4	40	2	3	3 fault @ 294.83m with gouge
230	297.79	299.31	1.52	0.70	46	0.00	0	6	3	5	20	3	3	3 fault with gouge and broken core

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
231	9.14	11.28	2.14	0.11	5	0.00	0	4	3	3	12	5	4 rubble, very poor recovery	
231	11.28	14.33	3.05	0.19	6	0.00	0	4	3	3	22	5	4 rubble, very poor recovery	
231	14.33	17.37	3.04	0.24	8	0.00	0	4	3	3	30	5	4 rubble, very poor recovery	
231	17.37	20.42	3.05	0.20	7	0.00	0	3	3	4	40	5	4 rubble, very poor recovery	
231	20.42	38.71	18.29	0.24	1	0.00	0	3	3	4	19	5	4 rubble, very poor recovery	
231	38.71	39.62	0.91	0.20	22	0.00	0	3	3	4	20	5	4 rubble, very poor recovery, cave?	
231	39.62	40.23	0.61	0.08	13	0.00	0	3	3	4	8	5	4 rubble, very poor recovery	
231	40.23	42.98	2.75	0.16	6	0.00	0	3	3	4	24	5	4 rubble, very poor recovery	
231	42.98	43.57	0.59	0.12	20	0.00	0	3	3	4	12	5	4 rubble, very poor recovery	
231	43.57	45.11	1.54	0.22	14	0.00	0	3	3	4	20	5	4 rubble, very poor recovery	
231	45.11	47.85	2.74	0.07	3	0.00	0	3	3	4	5	5	4 rubble, very poor recovery	
231	47.85	50.90	3.05	0.18	6	0.00	0	2	3	4	24	5	4 rubble, very poor recovery	
231	50.90	53.95	3.05		0		0						no core, washed away	
231	53.95	55.78	1.83	0.32	17	0.00	0	3	3	4	30	5	4 rubble, very poor recovery	
231	55.78	56.69	0.91	0.17	19	0.00	0	2	3	4	20	5	4 gouge and rubble mixed	
231	56.69	58.52	1.83	0.31	17	0.00	0	2	2	4	50	5	4 gouge and rubble mixed	
231	58.52	60.05	1.53	1.48	97	0.97	63	7	3	4	19	5	4 gouge and rubble mixed, 59.55 m end dyke	
231	60.05	63.09	3.04	0.32	11	0.00	0	3	3	4	30	1	1 gouge at 58.95 m, contact	
231	63.09	64.62	1.53	0.41	27	0.00	0	4	3	4	20	1	3 rubble and gouge	
231	64.62	65.84	1.22	0.45	37	0.12	10	5	3	4	15	1	3 rubble and gouge	
231	65.84	67.67	1.83	0.41	22	0.18	10	4	3	4	26	1	3 rubble and gouge	
231	67.67	68.88	1.21	0.53	44	0.32	26	5	3	4	18	1	1 partly hraled material, slicks	
231	68.88	71.93	3.05	2.50	82	1.77	58	5	3	4	12	1	1 competent rock, slicks	
231	71.93	73.46	1.53	1.01	66	0.75	49	4	3	4	8	1	1 competent rock, slicks	
231	73.46	75.29	1.83	1.62	89	1.00	55	5	2	3	5	1	3 rubble and gouge, very poor recovery	
231	75.29	77.42	2.13	0.19	9	0.00	0	3	2	3	14	1	2 rubble and gouge, very poor recovery	
231	77.42	81.38	3.96	0.54	14	0.00	0	4	2	3	22	1	3 rubble and gouge, very poor recovery	
231	81.38	84.43	3.05	0.40	13	0.24	8	5	3	4	12	1	3 rubble	
231	84.43	86.87	2.44	0.38	16	0.00	0	3	3	4	30	5	4 rubble	
231	86.87	87.78	0.91	0.43	47	0.15	16	6	3	4	9	1	3 rubble, redrilled core	
231	87.78	89.31	1.53	0.15	10	0.00	0	3	2	3	15	5	4 rubble and gouge	
231	89.31	89.92	0.61	0.52	85	0.20	33	7	3	4	9	3	3 rubble	
231	89.92	90.83	0.91	0.48	53	0.19	21	6	3	4	16	3	3 poor recovery	
231	90.83	91.74	0.91	0.46	51	0.12	13	7	3	4	9	3	3 poor recovery	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
231	91.74	92.66	0.92	0.20	22	0.00	0	4	3	4	12	5	4 rubble	
231	92.66	96.62	3.96	0.28	7	0.00	0	3	3	4	20	5	4 rubble	
231	96.62	97.54	0.92	0.34	37	0.00	0	4	3	4	18	5	4 rubble	
231	97.54	97.84	0.30	0.17	57	0.00	0	5	3	4	25	5	4 rubble	
231	97.84	98.15	0.31	0.13	42	0.00	0	4	3	4	8	5	4 rubble, redrilled core	
231	98.15	98.45	0.30	0.26	87	0.00	0	4	3	4	17	5	4	
231	98.45	99.67	1.22	1.24	102	1.00	82	10	4	6	12	1	1 end fault mat'l or rubble at 98.57m	
231	99.67	102.72	3.05	3.10	102	3.10	102	15	4	6	5	3	3	
231	102.72	105.77	3.05	2.73	90	2.54	83	10	4	6	21	1	1 very slick at 105.15 m, at 30 to c.a.	
231	105.77	108.81	3.04	3.04	100	2.96	97	14	4	6	7	3	3	
231	108.81	111.86	3.05	3.09	101	3.09	101	15	4	6	2	3	4	
231	111.86	114.91	3.05	3.05	100	3.05	100	15	4	6	4	1	1	
231	114.91	117.96	3.05	2.88	94	2.88	94	15	4	6	3	1	1 slick at 45 to c.a.	
231	117.96	121.01	3.05	3.11	102	3.05	100	15	4	6	2	1	1 slick at 30 to c.a.	
231	121.01	124.05	3.04	3.00	99	3.00	99	15	4	6	2	1	1 slick at 45 to c.a., well polished	
231	124.05	127.10	3.05	3.08	101	3.08	101	15	4	6	2	1	1 gypsum fractures, very slick at 30 to c.a.	
231	127.10	130.15	3.05	3.10	102	2.90	95	15	4	6	4	1	1 gypsum veins, very slick	
231	130.15	133.20	3.05	3.02	99	3.02	99	15	4	6	5	1	1 gypsum veins, very slick	
231	133.20	136.25	3.05	3.05	100	2.99	98	15	4	6	4	1	1 slick contacts, gypsum veins	
231	136.25	139.29	3.04	3.06	101	3.06	101	15	4	6	3	1	1 gypsum veins, very slick	
231	139.29	142.34	3.05	3.05	100	3.05	100	15	5	6	2	1	1 gypsum veins, very slick	
231	142.34	145.39	3.05	3.05	100	2.28	75	15	3	6	4	1	1 gypsum veining on dyke	
231	145.39	148.44	3.05	3.05	100	2.94	96	15	3	5	3	1	1 weathered dyke with gouge and slicks	
231	148.44	149.96	1.52	1.40	92	1.14	75	9	3	5	16	1	1 weathered dyke with gouge and slicks	
231	149.96	153.01	3.05	3.05	100	2.66	87	13	3	5	13	1	1 weathered dyke with gouge and slicks	
231	153.01	156.06	3.05	3.15	103	2.70	89	13	3	5	15	1	1 weathered dyke with gouge and slicks	
231	156.06	159.11	3.05	3.05	100	2.59	85	13	3	5	12	1	1 weathered dyke with gouge and slicks, 10 tca	
231	159.11	162.15	3.04	3.04	100	2.96	97	14	3	5	7	1	1 weathered dyke with gouge and slicks	
231	162.15	165.35	3.20	3.10	97	2.75	86	12	3	5	18	1	1 weathered dyke with gouge and slicks	
231	165.35	168.55	3.20	3.05	95	3.05	95	15	3	5	4	1	1 weathered dyke with gouge and slicks	
231	168.55	171.60	3.05	3.16	104	3.16	104	15	4	6	2	1	2 main phase rock	
231	171.60	174.65	3.05	3.05	100	3.05	100	15	4	6	4	1	1 main phase rock	
231	174.65	177.70	3.05	3.02	99	3.02	99	15	4	6	3	1	1 main phase rock, slick 25 to c.a.	
231	177.70	180.75	3.05	2.99	98	2.99	98	15	4	6	2	1	1 main phase rock	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
231	180.75	183.79	3.04	3.09	102	3.09	102	15	4	6	1	3	3 main phase rock	
231	183.79	186.84	3.05	3.05	100	2.99	98	15	4	6	5	1	1 main phase rock	
231	186.84	189.89	3.05	2.89	95	2.58	85	15	3	5	4	1	1 50% partly healed fault gouge	
231	189.89	192.94	3.05	2.98	98	2.90	95	14	3	5	7	1	1 50% partly healed fault gouge	
231	192.94	195.98	3.04	2.98	98	2.76	91	12	3	5	15	1	1 50% partly healed fault gouge	
231	195.98	199.03	3.05	3.05	100	2.76	90	13	5	6	13	1	1 50% dyke, very hard-50% healed	
231	199.03	202.08	3.05	2.73	90	2.64	87	15	5	6	2	1	1 all dyke, very hard, weak slicks	
231	202.08	205.13	3.05	2.91	95	2.91	95	15	5	6	1	1	1 dyke, very hard, polished slick @ 70 to c.a.	
231	205.13	207.57	2.44	2.60	107	2.60	107	15	5	6	4	3	2 all dyke, very hard, weak slicks	
231	207.57	210.62	3.05	3.05	100	2.97	97	14	5	6	7	1	1 sections of dyke material @ 30 to c.a.	
231	210.62	213.66	3.04	3.16	104	2.52	83	10	3	6	30	1	1 mineralized brecciated sections, clay	
231	213.66	215.49	1.83	1.78	97	1.78	97	15	3	6	4	1	1 weak slicks @ 30 to c.a., healed breccia	
231	215.49	218.54	3.05	2.97	97	2.87	94	14	3	6	6	1	1 fault and sections of healed fault	
231	218.54	221.59	3.05	2.99	98	2.88	94	14	2	5	11	1	1 very slick, sections of healed fault	
231	221.59	224.64	3.05	2.93	96	2.70	89	13	2	5	18	1	1 sections of healed fault	
231	224.64	227.69	3.05	3.05	100	2.95	97	14	3	5	10	1	1 sections of healed fault	
231	227.69	230.73	3.04	2.11	69	1.87	62	15	3	6	5	1	1 sections of healed fault, slicks @ 20 to c.a.	
231	230.73	233.78	3.05	3.09	101	2.63	86	13	2	5	17	1	1 sections of healed fault, slicks @ 25 to c.a.	
231	233.78	236.83	3.05	3.89	128	3.74	123	13	3	5	13	1	1 sections of healed fault, slicks @ 45 to c.a.	
231	236.83	239.88	3.05	2.94	96	2.85	93	14	3	6	10	1	1 gouge-filled slickensides @ 45 to c.a.	
231	239.88	242.93	3.05	3.10	102	3.05	100	15	3	6	5	1	1 5 cm section of gouge	
231	242.93	245.97	3.04	3.08	101	3.05	100	15	3	6	5	1	1 3 cm section of gouge	
231	245.97	249.02	3.05	3.12	102	2.97	97	14	3	6	8	1	1 slick joints, minor gouge	
231	249.02	252.07	3.05	3.05	100	3.03	99	14	3	6	6	1	1 2 cm gouge	
231	252.07	255.12	3.05	3.12	102	3.09	101	15	4	6	5	1	1 3 cm gouge, slickenside @ 25 to c.a.	
231	255.12	258.17	3.05	2.97	97	2.97	97	15	4	6	1	1	2	
231	258.17	261.21	3.04	3.05	100	3.05	100	15	4	6	4	1	2	
231	261.21	264.26	3.05	3.05	100	3.05	100	15	3	6	2	1	2 gypsum veining	
231	264.26	267.31	3.05	3.05	100	3.05	100	15	3	6	3	1	1 gypsum veining, 3 cm gouge	
231	267.31	270.36	3.05	3.13	103	3.05	100	15	3	6	8	1	1 gypsum veining, 8 cm gouge	
231	270.36	273.41	3.05	3.10	102	3.08	101	15	3	6	9	1	1 gypsum veining, 2 cm gouge	
231	273.41	276.45	3.04	3.09	102	3.09	102	15	3	6	2	1	2 gypsum veining	
231	276.45	279.50	3.05	3.10	102	3.10	102	15	3	6	4	1	2 gypsum veining	
231	279.50	282.55	3.05	3.05	100	3.05	100	15	3	6	2	1	2 gypsum veining	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
231	282.55	285.60	3.05	3.05	100	3.05	100	15	3	6	4	1	2 gypsum veining	
231	285.60	288.65	3.05	3.05	100	3.05	100	15	3	6	2	1	2 gypsum veining	
231	288.65	291.69	3.04	3.14	103	3.14	103	15	3	6	2	1	2 gypsum veining	
231	291.69	294.74	3.05	3.05	100	3.05	100	15	3	6	3	1	1 gypsum veining, slick contact	
231	294.74	297.79	3.05	3.04	100	3.04	100	15	4	6	2	1	1 gypsum veining	
232	42.67	44.50	1.83	0.87	48	0.10	5	6	3	5	20	1	1 blocky, but no gouge	
232	44.50	46.02	1.52	0.50	33	0.00	0	5	3	5	15	1	2 blocky, but no gouge	
232	46.02	47.85	1.83	1.30	71	0.22	12	5	3	5	20	1	2 blocky, but no gouge	
232	47.85	50.90	3.05	0.25	8	0.00	0	5	3	5	5	3	4 blocky, but no gouge	
232	50.90	53.95	3.05	0.77	25	0.00	0	4	3	3	25	5	4 blocky, but no gouge	
232	53.95	57.00	3.05	0.50	16	0.10	3	1	0	1	15	5	4 mostly gouge	
232	57.00	60.05	3.05	1.77	58	0.67	22	1	0	1	20	2	2 mostly gouge	
232	60.05	63.09	3.04	1.00	33	0.12	4	1	0	1	25	1	2 mostly gouge	
232	63.09	66.14	3.05	2.95	97	2.38	78	12	2	2	15	3	3 fault, partially healed with gouge	
232	66.14	69.19	3.05	3.00	98	2.88	94	14	3	5	7	3	2 fractures on gypsum veins	
232	69.19	72.24	3.05	3.05	100	3.05	100	15	3	6	3	3	3 fractures on gypsum veins	
232	72.24	75.29	3.05	3.05	100	3.05	100	15	3	6	5	1	2 fractures on gypsum veins	
232	75.29	78.33	3.04	3.04	100	3.04	100	15	3	6	3	3	3 fractures on gypsum veins	
232	78.33	81.38	3.05	3.05	100	3.05	100	15	3	6	5	3	3 fractures on gypsum veins	
232	81.38	84.43	3.05	3.05	100	3.05	100	15	3	6	3	2	2 fractures on gypsum veins	
232	84.43	87.48	3.05	3.05	100	3.05	100	15	3	6	2	2	3 fractures on gypsum veins	
232	87.48	90.53	3.05	3.05	100	3.05	100	15	3	6	3	3	2 fractures on gypsum veins	
232	90.53	93.57	3.04	3.04	100	3.04	100	15	3	6	4	3	3 fractures on gypsum veins	
232	93.57	96.62	3.05	3.05	100	2.95	97	15	3	6	5	2	2 fractures on gypsum veins	
232	96.62	99.67	3.05	3.05	100	3.05	100	15	3	6	2	5	4 fractures on gypsum veins	
232	99.67	102.72	3.05	3.05	100	3.05	100	15	3	6	4	1	2 fractures on gypsum veins	
232	102.72	105.77	3.05	3.05	100	3.05	100	15	3	6	3	3	3 fractures on gypsum veins	
232	105.77	108.81	3.04	3.00	99	2.82	93	14	2	5	8	1	2 fault, fractures on gypsum veins	
232	108.81	111.86	3.05	3.05	100	2.53	83	14	3	5	10	2	1 healed fault, fractures on gypsum veins	
232	111.86	114.91	3.05	3.10	102	3.00	98	14	3	5	9	3	1 healed fault, fractures on gypsum veins	
232	114.91	117.96	3.05	3.00	98	3.00	98	15	3	6	5	2	2 minor clay on slips, gypsum	
232	117.96	121.01	3.05	3.07	101	2.95	97	14	3	6	9	1	2 gypsum	
232	121.01	124.05	3.04	3.13	103	1.93	63	12	3	6	19	1	2 gypsum	
232	124.05	127.10	3.05	3.07	101	2.84	93	14	3	6	10	3	2 minor clay on slips	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
232	127.10	130.15	3.05	3.10	102	2.70	89	13	1	6	13	1	2	2 most interval H=3, some crush + minor gouge
232	130.15	133.20	3.05	3.10	102	2.80	92	13	1	6	11	3	2	2 crush zone
232	133.20	136.25	3.05	3.10	102	3.10	102	14	3	6	6	3	3	3
232	136.25	139.29	3.04	3.10	102	3.10	102	14	3	6	9	3	3	3
232	139.29	142.34	3.05	3.00	98	2.90	95	13	1	6	11	1	2	2 minor crush, most interval H=3
232	142.34	145.39	3.05	3.05	100	2.70	89	13	2	6	15	1	1	1 minor crush, most interval H=3
232	145.39	148.44	3.05	3.10	102	3.00	98	13	3	6	13	1	2	2 minor clay on fractures
232	148.44	151.49	3.05	3.03	99	3.03	99	15	3	6	5	3	2	
232	151.49	154.53	3.04	3.15	104	3.15	104	14	2	6	10	3	2	2 minor crush, clay on fracture
232	154.53	157.58	3.05	3.02	99	3.02	99	15	0	6	5	3	2	2 154.53-154.8m, clay gouge 20 to c.a.
233	8.23	11.28	3.05	1.70	56	0.00	0	5	3	5	50	3	3	3 rubble
233	11.28	13.72	2.44	2.70	111	0.00	0	6	2	6	50	3	1	1 rubble, minor gouge, shear at 20 to c.a.
233	13.72	14.33	0.61	0.40	66	0.34	56	9	3	6	5	3	3	3 blocky
233	14.33	15.85	1.52	1.40	92	0.45	30	7	3	6	25	2	3	3 blocky
233	15.85	18.90	3.05	2.65	87	0.19	6	7	3	6	50	1	2	2 blocky, rubble, sandy crush
233	18.90	20.42	1.52	1.80	118	0.78	51	9	3	6	23	2	3	3 blocky, minor pyrite on fractures
233	20.42	23.47	3.05	2.96	97	1.00	33	10	3	6	21	1	2	2 minor gouge, weak crush
233	23.47	26.52	3.05	3.20	105	2.95	97	13	3	6	11	3	3	3 pyritumen on fractures
233	26.52	29.57	3.05	3.20	105	1.85	61	13	2	6	16	1	2	2 minor gouge and crush
233	29.57	32.61	3.04	3.05	100	2.65	87	13	2	6	14	3	2	2 minor gouge on fractures
233	32.61	35.66	3.05	2.92	96	2.72	89	13	3	6	12	3	3	3
233	35.66	38.71	3.05	3.20	105	1.90	62	12	3	6	19	1	2	2
233	38.71	41.76	3.05	3.10	102	1.55	51	9	3	6	32	2	2	2 minor clay on slips, blocky
233	41.76	44.20	2.44	2.33	95	1.12	46	10	2	6	20	3	2	2 intervals of crush, rubble, minor gouge
233	44.20	47.24	3.04	3.20	105	1.15	38	9	2	6	33	1	2	2 minor crush, clay on slips
233	47.24	50.60	3.36	3.20	95	2.00	60	11	2	6	21	3	3	3 minor crush, clay on slips
233	50.60	53.64	3.04	3.15	104	2.50	82	13	1	6	12	3	2	2 crush cemented with gouge, sheared at 24tca
233	53.64	56.69	3.05	3.00	98	2.70	89	14	1	6	8	2	2	2 crush cemented with gouge, sheared at 24tca
233	56.69	59.74	3.05	3.15	103	1.65	54	10	1	6	30	2	2	2 blocky, minor crush, gouge
233	59.74	63.09	3.35	3.05	91	1.77	53	10	1	6	23	3	3	3 intervals of crush and gouge
233	63.09	66.14	3.05	3.08	101	1.38	45	10	1	6	26	2	2	2 intervals of crush and gouge
233	66.14	69.19	3.05	3.10	102	1.40	46	9	1	6	31	3	2	2 intervals of crush and gouge to 1 M
233	69.19	72.24	3.05	3.05	100	2.15	70	9	1	6	36	3	2	2 sporadic crush throughout
233	72.24	75.29	3.05	2.95	97	1.70	56	10	1	6	21	2	2	2 sporadic crush throughout

RED - CHRIS PROPERTY
1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
233	75.29	78.33	3.04	3.05	100	2.70	89	13	1	6	11	3	2	
233	78.33	81.38	3.05	3.15	103	1.60	52	10	3	6	23	1	1	pyrite on few slips, some blocky core
233	81.38	84.43	3.05	3.00	98	1.80	59	12	3	6	17	1	2	
233	84.43	87.48	3.05	3.10	102	1.60	52	10	1	6	25	1	2	intervals crush to 30 cm
233	87.48	90.53	3.05	2.90	95	2.00	66	12	1	6	16	3	2	minor crush
233	90.53	93.57	3.04	3.04	100	3.04	100	15	3	6	4	3	2	minor gouge
233	93.57	96.62	3.05	2.85	93	2.41	79	13	4	6	14	1	1	gouge on slips and in broken core
233	96.62	99.67	3.05	3.02	99	1.86	61	10	4	6	22	1	1	gouge on slips and in broken core
233	99.67	102.72	3.05	3.01	99	1.59	52	10	4	6	25	1	1	gouge on slips and in broken core
233	102.72	105.77	3.05	3.01	99	2.80	92	14	4	6	8	1	1	trace gouge
233	105.77	108.81	3.04	3.01	99	2.96	97	15	4	6	4	1	1	20 cm cemented black gouge
233	108.81	111.86	3.05	2.99	98	2.99	98	15	4	6	2	5	3	trace gouge
233	111.86	114.91	3.05	2.97	97	2.75	90	14	4	6	7	1	1	gouge on slips and in broken core
233	114.91	117.96	3.05	2.88	94	2.63	86	14	4	6	8	1	1	gouge on slips and in broken core
233	117.96	121.01	3.05	3.05	100	2.51	82	13	4	6	11	1	1	5-6mm gouge on slip at 50 to c.a.
233	121.01	124.05	3.04	2.95	97	2.91	96	14	4	6	5	1	1	
233	124.05	127.10	3.05	2.94	96	2.62	86	14	4	6	9	1	1	50 cm of cemented gouge with rubble
233	127.10	130.15	3.05	2.95	97	2.95	97	15	3	6	4	5	3	fault or shear zone starts at 128.43m
233	130.15	133.20	3.05	2.98	98	2.79	91	14	3	6	6	1	1	fault or shear zone ends at 131.38m
233	133.20	136.25	3.05	2.88	94	2.02	66	14	4	6	8	1	1	trace gouge
233	136.25	139.29	3.04	2.87	94	2.74	90	14	3	6	6	1	1	1.45 m cemented gouge in shear zone
233	139.29	142.34	3.05	2.78	91	2.29	75	13	4	6	13	1	1	
233	142.34	145.39	3.05	2.98	98	2.90	95	15	3	6	4	1	1	gouge in broken core, fault starts at 144.55 m
233	145.39	148.44	3.05	3.05	100	3.05	100	15	3	6	2	5	3	cemented gouge and shears
233	148.44	151.49	3.05	3.01	99	3.01	99	15	4	6	4	1	1	fault ends at 150.65 at 35 to c.a.
233	151.49	154.53	3.04	2.91	96	2.91	96	15	4	6	3	1	1	3 cm cemented black gouge
233	154.53	157.58	3.05	2.88	94	2.58	85	13	4	6	10	1	1	gouge on slips and in broken core
233	157.58	160.63	3.05	2.80	92	2.24	73	13	3	6	11	1	1	fault zone starts at 157.73m
233	160.63	163.68	3.05	2.95	97	2.67	88	14	3	6	8	1	1	shears, cemented gouge with rubble
233	163.68	166.73	3.05	3.00	98	3.00	98	15	3	6	5	5	3	shears, cemented gouge with rubble
233	166.73	169.77	3.04	2.99	98	2.99	98	15	3	6	4	3	3	shears, cemented gouge with rubble
233	169.77	172.82	3.05	3.05	100	3.05	100	15	3	6	2	1	1	shears, cemented gouge with rubble
233	172.82	175.87	3.05	3.05	100	3.05	100	15	3	6	2	5	3	shears, cemented gouge with rubble
233	175.87	178.92	3.05	2.93	96	2.93	96	15	3	6	4	1	1	shears, cemented gouge with rubble

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
233	178.92	181.97	3.05	3.01	99	3.01	99	15	3	6	1	5	3	3 fault zone ends at 180.97m at 35 to c.a.
233	181.97	185.01	3.04	3.00	99	3.00	99	15	4	6	3	1	1	
233	185.01	188.06	3.05	3.00	98	2.98	98	15	4	6	3	1	1	1 local cemented gouge
233	188.06	191.11	3.05	3.07	101	2.89	95	15	4	6	5	1	1	1 fault between 188.16-188.70 m
233	191.11	194.16	3.05	2.92	96	2.64	87	14	4	6	6	3	1	
233	194.16	197.21	3.05	3.10	102	3.10	102	15	3	6	2	1	1	1 fault zone between 194.16-195.70 m
233	197.21	200.25	3.04	2.88	95	2.74	90	14	4	6	6	1	1	1 trace gouge on slips
233	200.25	203.30	3.05	2.90	95	2.59	85	14	3	6	7	1	1	1 fault zone between 201.20-203.45 m
233	203.30	206.35	3.05	3.02	99	3.02	99	15	4	6	4	1	1	
233	206.35	209.40	3.05	2.96	97	2.28	75	12	3	6	15	1	1	1 gouge on slips and in broken core
233	209.40	212.45	3.05	2.94	96	2.94	96	15	4	6	4	1	1	1 local cemented gouge with rubble
234	3.05	5.18	2.13	1.47	69	1.00	47	11	3	5	10	1	1	1 moderately blocky/ limonite
234	5.18	7.62	2.44	2.44	100	1.10	45	10	3	5	23	3	2	2 moderately blocky/ limonite
234	7.62	10.67	3.05	2.90	95	2.00	66	12	3	5	17	1	1	1 moderately blocky
234	10.67	13.72	3.05	3.05	100	2.37	78	12	3	5	19	3	2	2 moderately blocky
234	13.72	16.46	2.74	2.65	97	1.72	63	12	3	5	14	4	2	2 moderately blocky
234	16.46	19.51	3.05	2.95	97	2.00	66	12	3	5	18	2	1	1 moderately blocky
234	19.51	22.55	3.04	3.00	99	2.20	72	11	3	5	19	3	2	2 moderately blocky
234	22.55	25.91	3.36	2.93	87	1.90	57	10	3	5	23	2	1	1 moderately blocky
234	25.91	28.96	3.05	3.05	100	2.33	76	12	3	5	16	2	1	1 moderately blocky
234	28.96	32.00	3.04	3.04	100	2.34	77	13	3	5	13	3	2	2 moderately blocky
234	32.00	34.75	2.75	2.50	91	1.42	52	12	3	5	18	3	1	1 moderately blocky
234	34.75	37.80	3.05	3.05	100	1.90	62	11	3	5	21	3	3	3 moderately blocky
234	37.80	39.93	2.13	2.10	99	1.51	71	12	3	5	11	1	3	
234	39.93	41.45	1.52	1.38	91	1.02	67	12	3	5	8	2	3	
234	41.45	44.50	3.05	3.10	102	2.85	93	14	3	5	9	2	2	
234	44.50	47.24	2.74	2.74	100	1.78	65	10	3	5	19	1	2	2 moderately blocky
234	47.24	49.07	1.83	1.55	85	0.72	39	10	3	5	15	3	2	2 moderately blocky
234	49.07	50.90	1.83	1.90	104	1.12	61	10	3	5	14	1	2	2 moderately blocky
234	50.90	53.95	3.05	3.15	103	2.80	92	13	3	5	11	1	2	
234	53.95	57.00	3.05	3.05	100	2.30	75	12	3	6	16	2	2	
234	57.00	60.05	3.05	3.00	98	2.50	82	13	3	6	11	1	2	
234	60.05	63.09	3.04	3.10	102	2.50	82	13	3	6	14	1	2	
234	63.09	66.14	3.05	3.10	102	2.35	77	12	3	6	17	2	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
234	66.14	69.19	3.05	2.95	97	2.40	79	12	3	5	16	2	2	
234	69.19	72.24	3.05	3.00	98	1.90	62	12	2	4	17	1	1	1 fault gouge, 20 cm
234	72.24	75.29	3.05	3.05	100	2.27	74	11	3	5	20	1	2	
234	75.29	78.33	3.04	2.95	97	2.23	73	12	3	5	16	2	2	
234	78.33	79.86	1.53	1.28	84	0.34	22	6	3	5	20	2	2	2 blocky, DPFH starts
234	79.86	82.00	2.14	1.83	86	1.30	61	10	3	6	13	1	2	2 blocky, DPFH
234	82.00	84.43	2.43	2.52	104	1.98	81	12	3	6	14	2	2	2 blocky, DPFH
234	84.43	87.48	3.05	2.90	95	2.38	78	13	3	6	13	1	2	2 blocky, DPFH
234	87.48	90.53	3.05	3.15	103	2.70	89	14	3	6	9	1	2	2 blocky, DPFH
234	90.53	93.57	3.04	3.15	104	2.67	88	13	3	5	16	1	2	
234	93.57	96.62	3.05	3.20	105	2.42	79	13	3	6	13	1	1	
234	96.62	99.67	3.05	3.10	102	3.02	99	14	3	6	8	1	2	
234	99.67	102.72	3.05	3.05	100	2.90	95	13	3	6	12	1	2	
234	102.72	105.77	3.05	3.10	102	2.80	92	14	3	6	8	1	2	2 10 cm gouge
234	105.77	108.81	3.04	3.04	100	3.04	100	15	3	6	5	1	3	
234	108.81	111.25	2.44	2.35	96	2.10	86	13	3	6	9	2	2	
234	111.25	114.30	3.05	3.10	102	2.40	79	13	3	6	16	1	2	
234	114.30	117.04	2.74	3.05	111	2.80	102	13	3	6	11	3	2	
234	117.04	120.09	3.05	3.05	100	2.10	69	12	3	6	17	1	2	2 blocky
234	120.09	122.53	2.44	2.44	100	2.28	93	13	3	6	12	3	2	
234	122.53	125.58	3.05	2.95	97	2.30	75	13	3	6	11	1	2	
234	125.58	128.63	3.05	3.10	102	2.90	95	14	3	6	9	3	1	
234	128.63	132.59	3.96	3.96	100	3.20	81	13	3	6	16	2	3	
234	132.59	135.63	3.04	2.95	97	2.42	80	13	3	6	14	1	2	
234	135.63	138.68	3.05	3.10	102	3.00	98	15	3	6	5	3	2	
234	138.68	141.73	3.05	3.10	102	3.00	98	14	3	6	9	1	2	
234	141.73	144.78	3.05	3.15	103	2.82	92	13	2	5	16	1	3	3 shearing throughout
234	144.78	147.83	3.05	3.05	100	2.90	95	15	3	6	8	3	3	
234	147.83	150.88	3.05	3.05	100	2.68	88	13	3	6	11	3	1	
234	150.88	153.92	3.04	3.04	100	2.73	90	13	2	5	11	3	2	2 shearing + gouge
234	153.92	156.97	3.05	3.05	100	2.30	75	12	3	6	19	2	2	2 moderately blocky
234	156.97	160.17	3.20	3.05	95	2.35	73	11	3	6	20	3	2	2 moderately blocky
234	160.17	163.98	3.81	4.00	105	2.08	55	11	3	6	28	1	1	1 moderately blocky
234	163.98	166.42	2.44	2.33	95	0.55	23	9	3	6	25	1	1	1 strongly blocky

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
234	166.42	167.64	1.22	1.15	94	0.10	8	7	3	6	15	2	1	strongly blocky
234	167.64	169.77	2.13	2.13	100	2.00	94	14	3	6	4	2	1	
234	169.77	172.82	3.05	3.10	102	2.83	93	13	3	6	11	2	2	
234	172.82	174.04	1.22	1.20	98	1.03	84	12	3	6	7	1	2	
234	174.04	175.87	1.83	1.82	99	1.51	83	14	4	6	5	1	2	
234	175.87	178.92	3.05	2.82	92	2.33	76	14	4	6	8	1	2	2 DQCA at 176.73-177.18m
234	178.92	181.66	2.74	2.74	100	2.48	91	14	4	6	5	1	2	
234	181.66	184.10	2.44	2.35	96	1.92	79	13	4	6	8	1	2	2 pyrite on fractures
234	184.10	186.23	2.13	2.02	95	1.53	72	14	4	6	6	2	2	2 pyrite on fractures
234	186.23	188.67	2.44	2.40	98	2.12	87	15	3	6	2	2	3	
234	188.67	191.11	2.44	2.38	98	2.38	98	15	3	6	3	1	3	
234	191.11	194.16	3.05	2.95	97	2.23	73	14	3	6	5	2	3	3 7 cm gouge, H=1,2
234	194.16	197.21	3.05	3.02	99	2.53	83	15	3	6	5	2	3	3 gouge on fractures
234	197.21	200.25	3.04	2.81	92	2.33	77	14	3	6	6	1	3	
234	200.25	203.30	3.05	3.00	98	3.00	98	15	3	6	2	1	2	
234	203.30	206.35	3.05	3.03	99	2.63	86	14	3	6	9	1	3	3 10 cm gouge H=1,2, gouge on fractures
234	206.35	209.40	3.05	3.07	101	3.07	101	15	3	6	2	2	3	
234	209.40	212.45	3.05	3.13	103	3.13	103	15	3	6	2	1	2	
234	212.45	215.49	3.04	2.99	98	2.99	98	15	4	6	2	1	3	3 gouge on fractures
234	215.49	218.54	3.05	3.09	101	3.00	98	15	4	6	4	1	3	3 3 cm gouge H=0,1
234	218.54	221.59	3.05	2.99	98	2.99	98	15	4	6	2	1	2	
234	221.59	224.64	3.05	2.85	93	2.53	83	14	4	6	5	1	2	2 pyrite on fractures
234	224.64	227.69	3.05	3.00	98	3.00	98	15	4	6	2	1	2	2 pyrite on fractures
234	227.69	230.73	3.04	3.09	102	3.00	99	15	4	6	4	1	2	2 pyrite on fractures
234	230.73	233.78	3.05	3.05	100	3.05	100	15	4	6	4	1	2	2 pyrite on fractures
234	233.78	236.83	3.05	3.05	100	3.00	98	15	4	6	2	1	2	
234	236.83	239.88	3.05	3.05	100	2.19	72	13	3	6	12	2	3	3 5 cm gouge H=0, 1, gouge on fractures
234	239.88	242.93	3.05	3.13	103	1.93	63	12	3	6	14	2	3	3 25 cm gouge H=0, 1, gouge on fractures
234	242.93	245.92	2.99	3.07	103	1.99	67	13	3	6	11	2	3	3 gouge on fractures
234	245.92	249.02	3.10	3.03	98	1.84	59	13	3	6	15	2	3	3 6 cm gouge H=0, 1, gouge on fractures
234	249.02	252.07	3.05	3.05	100	3.05	100	15	3	6	2	1	2	2 DQCA at 250.50-251.25 m, H=5
235	5.79	8.23	2.44	0.61	25	0.15	6	6	3	4	21	5	4	4 overburden
235	8.23	11.28	3.05	2.12	70	0.26	9	5	3	5	50	5	4	4 20 cm of gouge
235	11.28	14.33	3.05	2.96	97	2.81	92	15	4	6	3	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery m.	Recovery %	RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To			Lgth	m.							
235	14.33	17.37	3.04	2.81	92	2.01	66	11	4	6	19	1	1 1.00 m of H=0, slicks 5-30 to c.a.
235	17.37	20.42	3.05	2.82	92	2.58	85	13	3	6	12	1	1 slick contact 45 to c.a.
235	20.42	23.47	3.05	2.56	84	2.27	74	13	3	6	14	1	1 weak slicks at contact 40 to c.a.
235	23.47	26.52	3.05	2.93	96	2.43	80	13	3	6	13	1	1 weak slicks with gouge and clay
235	26.52	29.57	3.05	3.00	98	2.40	79	13	3	6	12	1	1 weak slicks with gouge and clay, 20 to c.a.
235	29.57	32.61	3.04	2.70	89	2.41	79	12	3	6	30	1	1 weak slicks with gouge and clay, 30 cm H=0
235	32.61	35.66	3.05	3.05	100	3.05	100	15	4	6	3	1	4 sulfide veins 5-10 cm wide, 25-10 to c.a.
235	35.66	38.71	3.05	3.05	100	3.05	100	15	4	6	2	1	4 sulfide veins 5-10 cm wide, 25-10 to c.a.
235	38.71	41.76	3.05	2.90	95	2.90	95	15	3	6	3	1	1 possible slip planes 15-25 to c.a.
235	41.76	44.81	3.05	3.05	100	3.05	100	15	3	6	6	1	1 possible slip planes 15-25 to c.a.
235	44.81	47.85	3.04	2.99	98	2.11	69	13	3	5	13	1	1 30% gouge and clay, friable material
235	47.85	50.90	3.05	3.01	99	3.01	99	15	4	6	3	1	4 mineralized fractures
235	50.90	53.95	3.05	2.98	98	2.98	98	15	4	6	2	1	3 mineralized fractures
235	53.95	57.00	3.05	2.95	97	2.95	97	15	4	6	4	2	3 mineralized fractures
235	57.00	60.05	3.05	3.10	102	3.10	102	15	4	6	2	3	4 mineralized fractures
235	60.05	63.09	3.04	3.08	101	3.08	101	15	4	6	2	1	1 very weak slicks
235	63.09	66.14	3.05	3.05	100	3.05	100	15	4	6			
235	66.14	69.19	3.05	3.05	100	3.05	100	15	4	6			
235	69.19	72.24	3.05	3.05	100	3.05	100	15	4	6			
235	72.24	75.29	3.05	2.89	95	2.80	92	15	4	5	6	1	1 gouge on slick 20 to c.a.
235	75.29	78.33	3.04	3.05	100	3.05	100	15	4	6	3	1	1
235	78.33	81.38	3.05	2.95	97	2.95	97	15	4	6	4	1	1 gouge on slick 70 to c.a.
235	81.38	84.43	3.05	3.12	102	3.12	102	15	4	6			
235	84.43	87.48	3.05	3.05	100	3.12	102	15	4	6			
235	87.48	90.53	3.05	2.85	93	2.82	92	15	4	6	5	1	1 3 cm of gouge on slick at 80 to c.a.
235	90.53	93.57	3.04	2.94	97	2.92	96	15	4	6	4	1	2
235	93.57	96.62	3.05	3.05	100	3.05	100	15	4	6			dyke, very hard material
235	96.62	99.67	3.05	2.97	97	2.97	97	15	4	6			
235	99.67	102.72	3.05	2.99	98	2.81	92	14	4	6	9	1	1 18 cm of H=0, clay
235	102.72	105.77	3.05	3.00	98	2.96	97	15	4	6	3	1	1 4 cm of H=0, clay
235	105.77	108.81	3.04	3.05	100	3.05	100	15	4	6			quartz veins
235	108.81	111.86	3.05	3.00	98	3.00	98	15	4	6			quartz veins
235	111.86	114.91	3.05	2.83	93	2.83	93	15	4	6	1	1	1 quartz veins, weak slick
235	114.91	117.96	3.05	3.10	102	3.10	102	15	4	6			quartz veins

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To		m.	%	m.	%								
235	117.96	121.01	3.05	3.39	111	3.39	111	15	4	6	4	1		3 quartz veins, mineralized fracture	
235	121.01	124.05	3.04	2.83	93	2.83	93	15	4	6	1	1		3 quartz veins, mineralized fracture	
235	124.05	127.10	3.05	3.00	98	3.00	98	15	4	6	1	1		1 quartz veins, weak slick	
235	127.10	130.15	3.05	3.02	99	3.02	99	15	4	6	1	1		1 quartz veins	
235	130.15	133.20	3.05	3.05	100	3.05	100	15	4	6				quartz veins	
235	133.20	136.25	3.05	3.05	100	3.05	100	15	4	6				quartz veins	
235	136.25	139.29	3.04	3.04	100	3.04	100	15	4	6				quartz veins	
235	139.29	142.34	3.05	3.05	100	3.05	100	15	4	6				quartz veins	
235	142.34	145.39	3.05	3.05	100	3.05	100	15	4	6				quartz veins	
235	145.39	148.44	3.05	3.05	100	3.05	100	15	4	6	3	1		1 quartz veins, weak slicks	
235	148.44	151.49	3.05	3.05	100	3.05	100	15	4	6				dyke starts at 151.30 m	
235	151.49	154.53	3.04	3.04	100	2.91	96	15	5	6	3	1	2		
235	154.53	157.58	3.05	3.07	101	2.99	98	15	5	6	3	1	2		
235	157.58	160.63	3.05	3.05	100	3.05	100	15	5	6	4	1	2	2	2 minor gouge on fractures
235	160.63	163.68	3.05	3.09	101	2.81	92	15	5	6	5	2	2	2	
235	163.68	166.73	3.05	2.85	93	2.85	93	15	5	6	4	1	2	2	2 minor gouge on fractures
235	166.73	169.77	3.04	3.00	99	3.00	99	15	5	6	3	1	2	2	
235	169.77	172.82	3.05	2.90	95	2.90	95	15	5	6	1	1	2	2	1 15 cm fault gouge H=2,3
235	172.82	175.87	3.05	3.03	99	2.79	91	15	5	6	4	2	2	2	
235	175.87	178.92	3.05	3.03	99	2.84	93	15	5	6	3	3	2	2	2 dyke ends at 177.35 m
235	178.92	181.97	3.05	3.05	100	3.05	100	15	5	6					
235	181.97	185.01	3.04	3.04	100	3.04	100	15	5	6	1	1	2		
235	185.01	188.06	3.05	3.05	100	3.05	100	15	5	6	2	1	2		
235	188.06	191.11	3.05	3.14	103	3.14	103	15	5	6					
235	191.11	194.16	3.05	3.05	100	3.05	100	15	5	6					
235	194.16	197.21	3.05	3.05	100	3.05	100	15	5	6	2	1	2		3 12 cm fault at 40-60 to c.a.
235	197.21	200.25	3.04	3.00	99	3.00	99	15	5	6	2	1	2		2
235	200.25	203.30	3.05	3.21	105	3.04	100	15	5	6	1	2	2		3 gouge on fracture
235	203.30	206.35	3.05	3.05	100	3.05	100	15	5	6	1	1	2		3 3 cm fault at 55 to c.a.
235	206.35	209.40	3.05	3.00	98	2.84	93	15	5	6	2	2	2		3 5 cm fault gouge at 30 to c.a.
235	209.40	212.45	3.05	3.12	102	2.78	91	15	5	6	6	1	2		3 gouge on fractures
235	212.45	215.49	3.04	3.02	99	2.74	90	15	5	6	4	2	2		3 10 cm fault gouge at 40 to c.a.
235	215.49	218.54	3.05	2.95	97	2.95	97	15	5	6	3	1	2		3 gouge on fractures
235	218.54	221.59	3.05	2.87	94	2.87	94	15	5	6	1	1	2		2

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
235	221.59	224.64	3.05	3.19	105	3.19	105	15	5	6	2	1	3	2 cm fault gouge at 15 to c.a.
235	224.64	227.69	3.05	3.17	104	3.17	104	15	5	6	3	1	2	
235	227.69	230.73	3.04	3.04	100	3.04	100	15	5	6	4	3	3	
235	230.73	233.78	3.05	3.11	102	3.11	102	15	5	6	2	1	2	2 pyrite on fractures
235	233.78	236.83	3.05	2.80	92	2.62	86	14	5	6	5	2	2	3 3 cm gouge at 20 to c.a., H=0, 1
235	236.83	239.88	3.05	3.17	104	3.17	104	15	5	6	2	2	2	
235	239.88	242.93	3.05	2.96	97	2.96	97	15	5	6	1	2	2	
235	242.93	245.97	3.04	3.08	101	3.08	101	15	5	6	2	1	1	3 minor gouge on fractures
235	245.97	249.02	3.05	2.99	98	2.71	89	15	5	6	2	1	1	3 1-3cm gouge at 18 to c.a., 1-8 cm fault at 48tca
235	249.02	252.07	3.05	3.03	99	3.03	99	15	5	6	1	1	2	
235	252.07	255.12	3.05	3.13	103	3.00	98	15	5	6	3	1	1	3 gouge on fractures
235	255.12	258.17	3.05	3.05	100	2.84	93	15	5	6	5	2	2	3 gouge on fractures, 4cm gouge at 30 to c.a.
235	258.17	261.21	3.04	3.07	101	2.79	92	14	5	6	10	5	5	3 5% broken core with gouge
235	261.21	264.26	3.05	3.02	99	2.88	94	15	5	6	4	2	2	3 2-4cm faults, 1 at 40 to c.a., other at 30 to c.a.
235	264.26	267.31	3.05	2.83	93	2.79	91	15	5	6	5	1	1	3 gouge on fractures
235	267.31	270.36	3.05	3.14	103	2.98	98	15	5	6	7	1	1	3 gouge on fractures
235	270.36	273.41	3.05	2.85	93	2.69	88	15	5	6	5	1	1	3 broken up dyke at 272.98-273.72m
235	273.41	276.45	3.04	3.04	100	2.56	84	15	5	6	4	1	2	
235	276.45	279.50	3.05	2.90	95	2.90	95	15	5	6	1	1	1	3 gouge on fractures
235	279.50	282.55	3.05	3.13	103	3.13	103	15	5	6	2	1	1	3 gouge on fractures
235	282.55	285.60	3.05	2.84	93	2.68	88	15	5	6	2	1	1	3 gouge on fractures
235	285.60	288.65	3.05	3.05	100	2.60	85	15	5	6	6	1	1	3 287.14-288.10 m, dyke U.C & L.C. at 45 to c.a.
235	288.65	291.69	3.04	3.16	104	3.16	104	15	5	6	1	1	2	
235	291.69	294.74	3.05	3.00	98	2.68	88	15	3	6	5	2	2	3 clay/ gouge on fractures
235	294.74	297.79	3.05	3.00	98	3.00	98	15	3	6	4	2	2	3 clay/ gouge on fractures
235	297.79	300.83	3.04	3.04	100	3.04	100	15	5	6				
235	300.83	303.88	3.05	2.84	93	2.84	93	15	6	6	1	1	1	1 dyke begins at 302.19m
235	303.88	306.93	3.05	3.05	100	2.51	82	14	5	6	10	1	1	3 minor gouge on fractures
235	306.93	309.98	3.05	3.10	102	3.10	102	15	6	6	3	2	2	
235	309.98	313.03	3.05	3.18	104	3.18	104	15	6	6				
235	313.03	316.08	3.05	2.85	93	2.85	93	15	6	6	2	1	1	
235	316.08	319.13	3.05	3.14	103	3.14	103	15	6	6				
235	319.13	322.17	3.04	2.84	93	2.59	85	15	4	6	5	2	2	3 dyke ends at 320.17m, and is at 12 to c.a.
235	322.17	325.22	3.05	2.93	96	2.80	92	15	4	6	3	1	1	3 gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
235	325.22	328.27	3.05	3.30	108	3.21	105	15	4	6	1	1	2	
235	328.27	331.32	3.05	2.96	97	2.78	91	15	4	6	4	1	3	gouge on fractures
235	331.32	334.36	3.04	3.04	100	3.04	100	15	4	6	2	1	2	
235	334.36	337.41	3.05	2.97	97	2.97	97	15	4	6	1	1	2	
235	337.41	340.46	3.05	3.00	98	2.01	66	14	4	6	10	2	3	gouge on fractures
235	340.46	343.51	3.05	2.97	97	2.97	97	15	4	6	2	1	3	gouge on fractures
235	343.51	346.56	3.05	3.05	100	3.05	100	15	4	6	3	1	3	gouge on fractures
235	346.56	349.61	3.05	3.15	103	3.00	98	15	4	6	3	1	2	
235	349.61	351.13	1.52	1.67	110	1.49	98	14	4	6	4	1	3	15 cm H=1,2, gouge on fractures
235	351.13	352.65	1.52	1.40	92	1.40	92	15	4	6	1	1	2	
235	352.65	355.70	3.05	3.05	100	3.05	100	15	4	6	3	1	2	
235	355.70	358.75	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
235	358.75	361.80	3.05	3.05	100	3.05	100	15	4	6	4	1	2	
235	361.80	364.24	2.44	2.50	102	2.15	88	14	4	6	8	1	2	
235	364.24	367.28	3.04	3.20	105	2.64	87	13	4	6	11	2	3	gouge on fractures
235	367.28	370.33	3.05	2.40	79	1.97	65	15	4	6	3	2	2	
235	370.33	373.08	2.75	3.20	116	3.06	111	14	4	6	7	2	2	
235	373.08	376.12	3.04	3.12	103	3.00	99	15	4	6	5	2	3	gouge on fractures
235	376.12	379.17	3.05	3.11	102	2.98	98	14	4	6	10	1	3	last 20 cm broken core with gouge
235	379.17	382.22	3.05	3.14	103	3.07	101	15	4	6	5	1	2	
235	382.22	385.27	3.05	3.11	102	3.11	102	15	4	6	4	1	2	
235	385.27	388.32	3.05	3.12	102	3.00	98	15	4	6	4	1	3	minor gouge on fractures
235	388.32	391.36	3.04	2.96	97	2.62	86	14	4	6	8	1	3	minor gouge on fractures
235	391.36	394.11	2.75	2.45	89	2.31	84	14	4	6	7	2	3	minor gouge on fractures
235	394.11	396.85	2.74	3.06	112	3.06	112	15	4	6	2	1	2	
235	396.85	399.90	3.05	2.87	94	2.67	88	15	4	6	5	1	3	1 cm gouge H=1,2 at 30 to c.a.
235	399.90	402.03	2.13	2.23	105	2.23	105	15	5	6	2	1	2	
235	402.03	405.08	3.05	3.00	98	3.00	98	15	5	6				
235	405.08	407.52	2.44	2.41	99	2.41	99	15	5	6				
235	407.52	410.57	3.05	3.10	102	3.10	102	15	5	6	3	3	3	
235	410.57	413.61	3.04	3.15	104	3.15	104	15	5	6	2	1	2	
235	413.61	416.05	2.44	2.30	94	2.30	94	15	5	6	1	3	3	
235	416.05	419.10	3.05	3.05	100	3.05	100	15	5	6				
235	419.10	422.15	3.05	3.10	102	3.10	102	15	5	6	1	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
235	422.15	425.20	3.05	3.02	99	2.92	96	15	4	6	6	3	3	
235	425.20	428.24	3.04	3.02	99	2.93	96	14	4	6	9	3	3	
235	428.24	431.29	3.05	2.88	94	2.84	93	15	4	5	3	1	1	1 slicks approx at 40 to c.a.
235	431.29	434.34	3.05	2.87	94	2.60	85	15	4	5	8	1	1	1 weak slicks, 30 cm of healed fault breccia
235	434.34	437.39	3.05	2.57	84	2.57	84	15	4	6	3	1	1	2 pyrite veining
235	437.39	440.14	2.75	2.90	105	2.87	104	15	3	6	3	1	1	1 no pyrite veining, weak slicks
236	6.10	8.23	2.13	1.31	62	0.60	28	9	3	4	14	3	3	3 iron stained, 14 cm overburden
236	8.23	11.28	3.05	3.00	98	2.95	97	14	3	4	8	2	2	3 iron stained fractures to 9m
236	11.28	12.80	1.52	1.60	105	0.88	58	9	4	5	17	2	2	
236	12.80	15.85	3.05	3.05	100	2.78	91	14	4	6	10	2	2	2 mineralized fractures
236	15.85	18.59	2.74	2.57	94	2.22	81	12	4	6	15	3	3	3 mineralized fractures
236	18.59	21.64	3.05	3.05	100	2.88	94	14	4	6	7	2	3	
236	21.64	24.69	3.05	3.10	102	2.60	85	13	4	6	12	2	2	2 pyrite on fractures
236	24.69	27.74	3.05	3.05	100	3.05	100	15	4	6	4	2	2	2 pyrite on fractures
236	27.74	29.57	1.83	1.65	90	1.65	90	15	4	6				
236	29.57	32.61	3.04	3.00	99	2.80	92	14	4	6	7	1	1	2 7cm healed gouge at 60 to c.a. , H=2,3
236	32.61	35.66	3.05	3.00	98	2.80	92	14	4	6	7	3	3	3 minor gouge on fractures
236	35.66	38.71	3.05	3.00	98	2.83	93	13	4	6	10	2	2	2 pyrite on fractures
236	38.71	40.54	1.83	1.75	96	1.75	96	13	4	6	7	3	3	3 pyrite on fractures
236	40.54	43.28	2.74	2.67	97	2.61	95	14	4	6	6	2	2	2 pyrite on fractures
236	43.28	46.33	3.05	3.02	99	2.85	93	14	4	6	7	2	2	2 pyrite on fractures, minor gouge
236	46.33	49.38	3.05	3.10	102	2.73	90	13	4	6	12	2	2	2 pyrite on fractures
236	49.38	52.43	3.05	3.08	101	3.03	99	15	4	6	5	3	3	3 pyrite on fractures
236	52.43	55.47	3.04	3.04	100	3.04	100	15	4	6	4	1	1	2 minor gouge, clay on fractures
236	55.47	58.52	3.05	3.25	107	3.11	102	14	4	6	8	3	3	3 minor gouge, clay on fractures
236	58.52	61.57	3.05	3.07	101	2.81	92	13	4	6	13	3	3	3 5 cm healed gouge, H=2,3 , gouge fractures
236	61.57	64.62	3.05	3.08	101	2.91	95	13	3	6	13	3	3	3 minor gouge on fractures
236	64.62	67.82	3.20	3.04	95	2.95	92	14	4	6	9	1	1	3 minor gouge on fractures
236	67.82	71.02	3.20	3.08	96	3.01	94	15	4	6	3	2	3	
236	71.02	74.07	3.05	3.10	102	3.10	102	15	4	6	3	1	2	
236	74.07	77.11	3.04	3.16	104	3.16	104	15	4	6	4	2	2	
236	77.11	80.16	3.05	3.05	100	3.05	100	15	4	6	3	1	1	2 mineralized fractures
236	80.16	83.21	3.05	3.09	101	3.05	100	14	3	6	8	1	1	3 gouge on fractures, 15 cm healed gouge
236	83.21	86.26	3.05	3.07	101	3.07	101	15	4	6	3	1	1	3 gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
236	86.26	89.31	3.05	3.03	99	2.73	90	13	3	6	12	3	3	gouge on fractures
236	89.31	92.35	3.04	3.07	101	3.04	100	14	3	6	9	2	2	gouge on fractures
236	92.35	95.40	3.05	3.01	99	3.01	99	15	4	6	4	1	2	
236	95.40	98.45	3.05	3.10	102	2.68	88	12	3	6	16	1	2	
236	98.45	101.50	3.05	2.85	93	2.60	85	13	3	6	14	1	2	
236	101.50	104.55	3.05	3.00	98	2.83	93	13	3	6	13	2	3	gouge on fractures
236	104.55	107.60	3.05	3.08	101	3.08	101	15	4	6	5	3	3	
236	107.60	110.64	3.04	3.03	100	2.95	97	14	4	6	9	3	3	calcite on fractures
236	110.64	113.39	2.75	2.67	97	2.67	97	15	4	6	4	2	3	
236	113.39	114.91	1.52	1.72	113	1.72	113	15	4	6	2	1	2	
236	114.91	117.96	3.05	3.05	100	2.87	94	13	3	6	12	2	2	gouge on fractures, 12 cm gouge, H=2
236	117.96	121.01	3.05	2.99	98	2.99	98	15	4	6	3	2	3	gouge on fractures
236	121.01	124.05	3.04	3.02	99	3.02	99	15	4	6	4	2	2	
236	124.05	127.10	3.05	3.10	102	3.02	99	15	4	6	4	2	2	pyrite on fractures
236	127.10	130.15	3.05	2.98	98	2.98	98	15	3	6	4	1	2	minor gouge/ clay on fractures
236	130.15	133.20	3.05	3.02	99	2.87	94	14	3	6	10	3	3	gouge on fractures
236	133.20	136.25	3.05	2.60	85	2.27	74	12	3	6	14	3	3	gouge on fractures
236	136.25	138.99	2.74	2.80	102	2.80	102	14	3	6	6	1	2	
236	138.99	139.90	0.91	0.88	97	0.88	97	15	4	6	1	2	3	gouge on fractures
236	139.90	142.34	2.44	2.34	96	2.32	95	14	4	6	7	2	3	gouge on fractures
236	142.34	145.39	3.05	3.14	103	3.06	100	14	4	6	6	1	2	
236	145.39	148.13	2.74	2.58	94	2.58	94	14	3	6	7	3	3	DQCA starts at 147.61 m
236	148.13	150.27	2.14	1.96	92	1.80	84	13	3	5	7	1	2	DQCA ends at 149.08m
236	150.27	152.70	2.43	2.35	97	2.35	97	15	4	6	3	1	2	pyrite on fractures
236	152.70	154.53	1.83	1.93	105	1.93	105	14	4	6	4	1	2	
236	154.53	157.58	3.05	3.00	98	3.00	98	15	4	6	2	1	2	clay on slips
236	157.58	160.63	3.05	2.95	97	2.95	97	15	4	6	4	3	3	4 cm healed gouge, gouge on fractures
236	160.63	163.68	3.05	3.08	101	3.08	101	14	4	6	6	1	2	
236	163.68	166.73	3.05	3.05	100	3.05	100	14	4	6	7	2	2	pyrite on fractures
236	166.73	169.77	3.04	2.95	97	2.95	97	14	4	6	6	2	2	gouge on fractures
236	169.77	172.82	3.05	3.02	99	3.02	99	15	4	6	3	2	2	pyrite on fractures
236	172.82	175.87	3.05	2.90	95	2.90	95	14	4	6	6	2	2	pyrite on fractures
236	175.87	178.92	3.05	2.92	96	2.92	96	14	4	6	6	2	2	pyrite on fractures
236	178.92	181.97	3.05	2.97	97	2.92	96	15	4	6	4	2	2	pyrite on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
236	181.97	185.01	3.04	2.93	96	2.81	92	14	4	6	6	2	2	2 pyrite on fractures
236	185.01	188.06	3.05	3.12	102	3.12	102	14	4	6	6	2	2	2 pyrite on fractures
236	188.06	190.20	2.14	2.07	97	2.07	97	14	4	6	4	3	2	
236	190.20	193.24	3.04	2.88	95	2.66	87	14	3	6	8	3	3	3 12 cm healed gouge H=2,3
236	193.24	196.29	3.05	3.05	100	2.91	95	14	3	6	7	3	3	3 gouge filled fractures
236	196.29	198.73	2.44	1.87	77	1.87	77	14	4	6	4	1	2	
236	198.73	200.25	1.52	2.13	140	2.02	133	14	4	6	5	1	2	2 slips at 60 to c.a.
236	200.25	203.30	3.05	2.98	98	2.98	98	15	4	6	3	2	2	2 pyrite on fractures
236	203.30	206.35	3.05	3.12	102	3.12	102	15	4	6	3	1	2	2 slips at 50 to c.a.
236	206.35	209.40	3.05	3.13	103	3.13	103	15	4	6	3	1	2	
236	209.40	212.45	3.05	3.10	102	3.10	102	15	4	6	4	1	2	2 pyrite on fractures
236	212.45	215.49	3.04	3.12	103	3.02	99	15	4	6	5	2	3	3 gouge on fractures
236	215.49	218.54	3.05	3.10	102	3.10	102	15	3	6	4	3	3	3 33 cm healed gouge, H=2,3 m
236	218.54	221.59	3.05	3.01	99	2.89	95	14	4	6	7	1	2	
236	221.59	224.64	3.05	3.03	99	3.03	99	15	3	5	5	2	3	3 1 m sheared 20-30 to c.a., H=2
236	224.64	227.69	3.05	3.19	105	3.10	102	14	2	4	7	3	3	3 sheared, gouge on fractures
236	227.69	230.12	2.43	2.40	99	1.96	81	10	3	4	18	3	3	3 10 cm intervals of gouge, H=2,3
236	230.12	233.17	3.05	3.00	98	2.73	90	13	3	5	11	3	2	2 intervals of gouge, clay
236	233.17	236.22	3.05	3.11	102	2.80	92	13	3	5	13	3	3	3 gouge on fractures
236	236.22	239.27	3.05	3.09	101	2.99	98	14	3	5	7	3	2	2 sheared at 30-40 to c.a., minor gouge
236	239.27	242.32	3.05	2.98	98	2.65	87	13	4	5	13	3	3	3 gouge on fractures
236	242.32	245.36	3.04	3.07	101	3.07	101	15	4	6	2	2	2	
236	245.36	248.41	3.05	3.11	102	3.05	100	15	4	6	2	2	2	2 clay on slips
236	248.41	251.46	3.05	3.10	102	3.10	102	15	4	6	4	2	3	
236	251.46	254.51	3.05	3.10	102	3.10	102	15	4	6	4	2	2	2 251.80-251.95 shear 30 to c.a.
236	254.51	257.56	3.05	3.06	100	3.06	100	14	4	6	6	2	2	2 clay on slips
236	257.56	260.60	3.04	3.04	100	3.04	100	14	4	6	8	2	2	2 clay on slips
236	260.60	263.65	3.05	3.14	103	3.14	103	15	4	6	3	3	3	
236	263.65	266.70	3.05	3.02	99	3.02	99	15	4	6	3	2	2	2 mineralized fractures
236	266.70	269.90	3.20	3.05	95	3.05	95	15	4	6	2	2	2	2 mineralized fractures
236	269.90	273.10	3.20	3.07	96	3.07	96	15	4	6	3	2	2	
236	273.10	276.15	3.05	3.08	101	3.08	101	15	4	6	5	3	2	
236	276.15	279.20	3.05	3.11	102	3.03	99	14	4	6	9	2	3	3 gouge on fractures
236	279.20	282.24	3.04	3.06	101	3.06	101	15	4	6	2	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
236	282.24	285.29	3.05	3.12	102	3.12	102	15	4	6	1	3	2	
236	285.29	288.34	3.05	3.12	102	2.97	97	14	4	6	9	3	3	gouge on fractures
236	288.34	289.56	1.22	0.89	73	0.89	73	15	4	6	1	3	3	
236	289.56	291.69	2.13	2.15	101	2.15	101	15	4	6	2	2	3	
236	291.69	294.74	3.05	3.05	100	3.05	100	15	4	6	4	3	3	gouge on fractures
236	294.74	297.79	3.05	3.10	102	3.10	102	15	4	6	4	3	3	
236	297.79	300.84	3.05	3.07	101	3.07	101	14	4	6	6	3	3	
236	300.84	303.89	3.05	3.13	103	3.13	103	15	4	6	3	1	3	3 cm gouge H=1,2
236	303.89	305.71	1.82	1.61	88	1.07	59	10	4	6	12	1	3	5% broken core
236	305.71	308.15	2.44	2.79	114	2.79	114	15	4	6	3	1	2	
236	308.15	309.98	1.83	1.83	100	1.83	100	15	4	6				
236	309.98	313.03	3.05	3.07	101	3.07	101	15	4	6	3	1	2	pyrite on fractures
236	313.03	316.08	3.05	3.08	101	3.08	101	15	4	6	1	1	2	
236	316.08	319.13	3.05	3.05	100	3.05	100	15	4	6	5	1	2	
236	319.13	322.17	3.04	3.03	100	3.03	100	15	4	6	3	1	3	
236	322.17	324.92	2.75	2.31	84	1.79	65	12	3	6	15	5	3	10% broken core with gouge
236	324.92	326.14	1.22	1.28	105	0.45	37	9	4	6	15	2	3	10-15% broken core, pyrite on fractures
236	326.14	329.79	3.65	3.32	91	3.07	84	14	4	6	7	1	3	gouge on fractures
236	329.79	332.84	3.05	3.12	102	3.12	102	15	4	6	2	1	2	pyrite on fractures
237	3.05	5.18	2.13	0.76	36	0.21	10	13	2	4	10	3	4	overburden
237	5.18	6.10	0.92	0.76	83	0.58	63	10	3	4	7	2	3	weathered joints
237	6.10	8.23	2.13	1.75	82	1.68	79	14	4	5	5	3	3	
237	8.23	9.45	1.22	0.73	60	0.38	31	7	2	4	19	1	2	50% fault material, partly healed
237	9.45	12.50	3.05	3.01	99	2.69	88	10	4	6	24	1	2	32 cm fault gouge
237	12.50	14.33	1.83	1.51	83	1.51	83	14	4	6	4	1	2	mineralized fractures
237	14.33	15.85	1.52	1.33	88	1.33	88	10	4	6	10	1	2	
237	15.85	17.37	1.52	1.46	96	1.37	90	13	4	6	6	1	1	slick 45 to c.a.
237	17.37	20.42	3.05	2.97	97	2.97	97	14	4	6	9	1	2	
237	20.42	23.47	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
237	23.47	26.52	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
237	26.52	28.96	2.44	2.24	92	1.78	73	9	5	5	26	1	1	46 cm of H=0
237	28.96	31.39	2.43	2.26	93	2.11	87	11	5	5	15	1	1	washed away gouge
237	31.39	34.44	3.05	3.00	98	3.00	98	15	4	6	1	2	2	
237	34.44	37.49	3.05	2.81	92	2.81	92	15	3	6	1	1	3	rock without quartz

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
237	37.49	40.54	3.05	3.01	99	3.01	99	15	4	6	2	1	1	1 steep slicks with gouge, no rake
237	40.54	43.59	3.05	3.05	100	3.05	100	15	4	6	2	1	2	
237	43.59	46.33	2.74	2.85	104	2.35	86	14	3	5	8	3	3	3 broken sections
237	46.33	47.85	1.52	1.14	75	0.87	57	5	3	5	30	1	1	1 27 cm H=0, gouge + poor recovery
237	47.85	49.38	1.53	1.65	108	1.65	108	15	4	6	2	1	2	
237	49.38	52.73	3.35	3.05	91	1.72	51	7	3	5	60	1	2	2 40% healed gouge, H=1
237	52.73	55.78	3.05	3.11	102	2.56	84	10	3	6	30	1	2	2 20% healed gouge, H=1
237	55.78	58.83	3.05	3.05	100	2.76	90	14	4	6	9	1	2	2 10 % healed gouge, H=1
237	58.83	60.05	1.22	1.16	95	1.16	95	15	4	6				
237	60.05	63.09	3.04	3.10	102	3.10	102	15	4	6	1	1	2	
237	63.09	65.23	2.14	1.87	87	1.62	76	10	4	6	15	5	4	4 small sections of rubble
237	65.23	67.97	2.74	2.88	105	2.87	105	15	4	6	3	1	1	1 very slick, 80 to c.a.
237	67.97	70.41	2.44	2.20	90	2.20	90	15	4	6	2	1	2	
237	70.41	72.24	1.83	1.72	94	1.72	94	15	5	6				
237	72.24	75.29	3.05	2.75	90	2.75	90	13	4	6	12	1	2	2 moderate rubble in places
237	75.29	78.33	3.04	2.93	96	2.93	96	15	3	6	4	1	2	
237	78.33	81.38	3.05	2.81	92	2.81	92	15	4	6	2	3	3	
237	81.38	84.43	3.05	2.98	98	2.63	86	14	4	6	9	1	1	1 weak slicks with gouge, mineralized
237	84.43	87.48	3.05	2.89	95	2.89	95	15	4	6				redrilled core
237	87.48	90.53	3.05	3.05	100	3.05	100	15	4	6				
237	90.53	93.57	3.04	2.71	89	2.71	89	15	4	6	2	1	4	
237	93.57	96.32	2.75	2.85	104	2.85	104	15	4	6	4	1	3	
237	96.32	98.76	2.44	2.07	85	1.80	74	7	4	5	30	1	2	2 sections of rubble
237	98.76	101.19	2.43	2.25	93	2.05	84	9	4	5	26	1	2	2 20 cm of gouge, H=1
237	101.19	102.72	1.53	1.35	88	1.35	88	14	4	6	3	1	3	
237	102.72	105.77	3.05	3.10	102	2.96	97	14	3	6	7	1	1	1 weak slicks, 45 to c.a.
237	105.77	108.81	3.04	2.43	80	2.37	78	15	4	6	4	1	3	
237	108.81	111.86	3.05	2.89	95	2.79	91	15	4	6	8	1	2	2 10 cm gouge, H=0
237	111.86	114.30	2.44	2.30	94	2.17	89	14	3	6	7	1	2	2 13 cm gouge, H=0
237	114.30	117.35	3.05	2.86	94	2.53	83	13	3	6	14	1	2	2 minor gouge and rubble
237	117.35	120.09	2.74	2.71	99	2.71	99	15	4	6	1	1	4	4 redrilled core, mineralized fracture
237	120.09	122.53	2.44	2.05	84	2.05	84	14	3	6	5	3	3	
237	122.53	124.05	1.52	1.82	120	1.82	120	15	5	6	2	1	3	
237	124.05	127.10	3.05	3.05	100	3.05	100	15	5	6				

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
237	127.10	130.15	3.05	2.31	76	1.93	63	15	4	6	40	1	1	40 cm of gouge, H=0, slick
237	130.15	132.59	2.44	2.65	109	2.65	109	15	4	6	2	3	4	
237	132.59	134.72	2.13	1.32	62	0.74	35	10	3	6	10	3	3	50 cm of rubble, no gouge
237	134.72	136.25	1.53	1.66	108	1.66	108	15	4	6	2	3	3	mineralized veins, gypsum on fractures
237	136.25	139.29	3.04	2.96	97	2.96	97	15	4	6	2	1	2	redrilled core
237	139.29	142.34	3.05	3.05	100	3.05	100	15	4	6	2	1	1	slicks 70 to c.a.
237	142.34	144.17	1.83	1.54	84	1.54	84	15	4	6	3	1	3	
237	144.17	146.00	1.83	1.70	93	1.70	93	15	4	6	2	1	3	
237	146.00	148.44	2.44	2.31	95	2.26	93	15	3	6	4	1	1	weak slicks 45 to c.a.
237	148.44	151.49	3.05	3.05	100	3.05	100	15	3	6	5	1	1	slick 70 to c.a.
237	151.49	154.53	3.04	2.85	94	2.51	83	14	3	6	9	1	1	minor gouge on fractures
237	154.53	159.41	4.88	1.65	34	1.40	29	9	3	6	17	1	2	missing block, 20 cm gouge H=0
237	159.41	160.32	0.91	0.88	97	0.51	56	10	3	6	8	1	3	blocky ground
237	160.32	163.37	3.05	2.56	84	2.45	80	14	3	6	8	1	1	very weak slicks, gouge on fractures
237	163.37	164.90	1.53	1.49	97	0.47	31	9	3	6	17	1	1	50% part healed fault, weak slicks
237	164.90	167.34	2.44	2.23	91	1.77	73	10	3	5	22	1	1	slicks 45 to c.a., 50 cm H=1
237	167.34	169.77	2.43	2.53	104	2.53	104	15	4	6	2	1	3	
237	169.77	172.52	2.75	2.64	96	2.64	96	15	4	6	5	3	3	
237	172.52	175.56	3.04	2.95	97	2.95	97	15	4	6	2	3	3	
237	175.56	178.00	2.44	2.07	85	1.00	41	7	3	5	40	1	1	50% healed fault gouge
237	178.00	180.75	2.75	2.70	98	0.85	31	6	1	3	70	1	1	70% healed fault gouge
237	180.75	183.49	2.74	2.55	93	2.32	85	11	3	6	16	1	3	
237	183.49	186.23	2.74	2.68	98	2.33	85	12	3	5	15	1	1	gypsum on fractures, minor gouge
237	186.23	188.06	1.83	1.92	105	1.80	98	13	3	5	9	1	1	gypsum on fractures, minor gouge
237	188.06	188.98	0.92	0.67	73	0.31	34	5	3	5	18	1	1	gypsum on fractures, minor gouge
237	188.98	192.02	3.04	2.94	97	2.48	82	13	3	5	12	1	1	gypsum on fractures, minor gouge
237	192.02	194.16	2.14	1.90	89	1.90	89	14	4	5	4	1	1	gypsum on fractures, minor gouge
237	194.16	196.60	2.44	2.44	100	2.27	93	14	4	6	6	1	1	gypsum on fractures
237	196.60	198.73	2.13	2.01	94	1.81	85	13	4	6	9	3	3	gypsum on fractures, minor gouge
237	198.73	201.78	3.05	3.11	102	3.11	102	15	4	6	2	1	1	gypsum on fractures
237	201.78	204.83	3.05	3.05	100	3.05	100	15	4	6	2	1	1	gypsum on fractures
237	204.83	207.87	3.04	2.97	98	2.65	87	13	4	6	14	1	1	some partly healed gouge
237	207.87	210.92	3.05	2.96	97	2.96	97	14	3	6	6	3	3	some partly healed gouge
237	210.92	213.97	3.05	2.90	95	2.10	69	13	4	6	10	1	3	some partly healed gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
237	213.97	214.88	0.91	0.61	67	0.00	0	6	4	6	15	1	2 some partly healed gouge
237	214.88	216.41	1.53	1.50	98	0.68	44	7	3	5	22	1	2 some partly healed gouge
237	216.41	216.71	0.30	0.30	100	0.17	57	7	3	5	5	1	2 some partly healed gouge
237	216.71	219.76	3.05	3.05	100	1.90	62	13	3	5	24	3	3 1.15 m of partly healed gouge
237	219.76	222.20	2.44	2.28	93	2.00	82	11	3	5	16	1	2 H=0, minor gouge in sections
237	222.20	225.25	3.05	2.93	96	2.74	90	14	4	6	8	1	2 minor gouge in sections
237	225.25	228.30	3.05	2.82	92	2.68	88	14	4	6	8	1	2 minor gouge in sections
237	228.30	231.34	3.04	2.91	96	2.87	94	15	3	6	4	1	1 gouge filled slicks 30 to c.a.
237	231.34	234.39	3.05	2.99	98	1.90	62	6	3	6	60	1	1 1.09m of gouge H=0,1, slicks
237	234.39	236.83	2.44	2.64	108	2.51	103	14	4	6	8	1	2
237	236.83	239.88	3.05	3.05	100	2.80	92	14	4	6	8	1	1 weak slicks, gypsum
237	239.88	242.93	3.05	3.15	103	3.15	103	15	4	6	3	1	1 weak slicks, gypsum
237	242.93	245.97	3.04	2.95	97	2.95	97	15	4	6	2	1	1 weak slicks, gypsum
237	245.97	249.02	3.05	3.05	100	2.91	95	14	3	6	9	1	1 weak slicks, gypsum, 14 cm gouge
237	249.02	252.07	3.05	3.00	98	2.92	96	14	3	6	8	1	1 weak slicks, gypsum, 8 cm gouge
237	252.07	255.12	3.05	3.05	100	2.71	89	10	3	5	28	1	1 slicks with gouge
237	255.12	258.17	3.05	3.05	100	2.63	86	10	3	5	30	1	1 slicks with gouge
237	258.17	261.21	3.04	3.11	102	1.03	34	11	1	3	19	1	1 possible slicks, 10 to c.a.
237	261.21	264.26	3.05	2.88	94	1.08	35	9	2	5	30	1	1 partly healed gouge, slicks
237	264.26	267.31	3.05	2.98	98	1.89	62	8	1	3	40	1	1 weak slicks, gouge
237	267.31	270.36	3.05	3.05	100	2.04	67	8	1	3	40	1	1 weak slicks, gouge
237	270.36	273.41	3.05	3.05	100	0.87	29	5	1	3	80	5	4 very weak fabric, healed ?
237	273.41	276.45	3.04	3.05	100	0.21	7	5	1	3	100	5	4 very weak fabric, healed ?
237	276.45	279.50	3.05	3.05	100	0.62	20	5	1	3	80	5	4 very weak fabric, healed ?
237	279.50	282.55	3.05	2.81	92	0.41	13	14	1	3	60	1	1 slicks with gouge and rubble
237	282.55	285.60	3.05	2.83	93	2.56	84	14	4	6	8	1	2 solid material
237	285.60	286.82	1.22	0.91	75	0.50	41	11	3	6	6	1	4 gouge filled fractures, manual breaks
238	32.31	35.66	3.35	0.11	3	0.00	0	3	3	4	15	5	3 little recovery, broken up core
238	35.66	38.71	3.05	0.25	8	0.00	0	3	3	4	20	5	3 little recovery, broken up core
238	38.71	41.76	3.05	0.12	4	0.00	0	3	3	4	15	5	3 little recovery, broken up core
238	41.76	43.28	1.52	0.14	9	0.00	0	3	1	4	4	5	3 little recovery, 11 cm. gouge H = 0
238	43.28	44.81	1.53	0.71	46	0.00	0	3	3	4	25	5	3 broken up core with gouge
238	44.81	46.94	2.13	0.41	19	0.00	0	3	3	4	25	5	3 broken up core with gouge
238	46.94	49.01	2.07	1.13	55	0.42	20	5	3	5	25	5	3 broken up core with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
238	49.01	50.29	1.28	0.19	15	0.00	0	5	3	5	7	5	3	broken up core with gouge
238	50.29	51.28	0.99	0.22	22	0.00	0	4	3	5	15	5	3	broken up core
238	51.28	52.43	1.15	0.25	22	0.00	0	4	3	5	15	5	3	broken up core
238	52.43	53.95	1.52	0.28	18	0.00	0	4	3	5	15	5	3	broken up core
238	53.95	54.86	0.91	0.46	51	0.00	0	5	3	5	20	5	3	broken up core with gouge
238	54.86	57.00	2.14	0.54	25	0.11	5	3	3	5	25	5	3	broken up core with gouge
238	57.00	57.91	0.91	0.69	76	0.38	42	7	3	5	12	2	3	broken up core with gouge
238	57.91	60.05	2.14	0.66	31	0.00	0	3	3	5	20	5	3	broken up core with gouge
238	60.05	60.65	0.60	0.19	32	0.00	0	4	3	5	15	5	3	broken up core
238	60.65	61.57	0.92	0.49	53	0.00	0	4	3	5	25	5	3	broken up core
238	61.57	63.09	1.52	0.21	14	0.00	0	4	3	5	15	5	3	broken up core
238	63.09	65.23	2.14	0.30	14	0.00	0	4	3	5	15	5	3	broken up core
238	65.23	66.45	1.22	0.68	56	0.21	17	6	3	5	15	2	3	gouge on fractures, 11 cm. gouge H = 0
238	66.45	67.36	0.91	0.52	57	0.22	24	12	3	6	4	5	2	
238	67.36	69.19	1.83	2.09	114	2.09	114	15	3	6	2	1	3	4cm gouge H = 0, 1
238	69.19	72.24	3.05	2.95	97	2.88	94	15	3	6	4	2	3	gypsum on fractures
238	72.24	75.29	3.05	2.91	95	2.68	88	14	3	6	5	1	3	gypsum on fractures, 4 cm. gouge
238	75.29	77.11	1.82	1.74	96	1.05	58	12	3	6	10	2	3	5% broken up core
238	77.11	78.64	1.53	1.72	112	1.19	78	10	3	6	12	2	3	fault gouge 78.29 - 80.97, H = 0, 1
238	78.64	80.47	1.83	1.27	69	0.30	16	7	0	5	20	2	3	fault gouge 78.29 - 80.97, H = 0, 1
238	80.47	81.38	0.91	0.48	53	0.00	0	3	3	5	15	2	3	broken up core with gouge
238	81.38	82.60	1.22	1.50	123	1.21	99	10	3	6	15	2	2	gouge on fractures
238	82.60	84.43	1.83	1.71	93	0.95	52	10	3	6	15	2	2	gouge on fractures
238	84.43	85.65	1.22	1.24	102	1.24	102	14	3	6	3	1	3	
238	85.65	88.09	2.44	2.36	97	1.98	81	13	3	6	8	1	3	pyrite on fractures
238	88.09	90.83	2.74	2.68	98	2.45	89	14	3	6	5	1	3	gouge on fractures
238	90.83	91.44	0.61	0.45	74	0.26	43	6	3	6	10	2	3	gouge on fractures
238	91.44	94.49	3.05	3.08	101	3.00	98	15	3	6	4	1	3	gouge on fractures
238	94.49	95.40	0.91	0.65	71	0.16	18	6	3	6	20	5	3	broken core with gouge
238	95.40	96.62	1.22	1.20	98	0.29	24	9	3	6	15	2	3	broken core with gouge
238	96.62	98.76	2.14	2.12	99	1.59	74	13	3	6	10	2	3	5 % broken core
238	98.76	101.50	2.74	2.79	102	2.41	88	14	3	6	6	1	3	gouge on fractures
238	101.50	103.63	2.13	2.09	98	1.97	92	14	3	6	5	2	3	13 cm gouge H = 1, 2
238	103.63	105.77	2.14	2.00	93	1.41	66	10	3	6	15	1	3	pyrite and gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
238	105.77	108.20	2.43	2.54	105	2.03	84	14	3	6	8	1	2	pyrite on fractures
238	108.20	109.73	1.53	1.27	83	1.20	78	13	3	6	5	1	2	
238	109.73	111.56	1.83	1.85	101	1.60	87	13	3	6	9	1	2	pyrite on fractures
238	111.56	113.69	2.13	2.34	110	1.21	57	13	3	6	10	1	2	
238	113.69	116.74	3.05	3.12	102	3.01	99	15	3	6	5	1	3	gouge on fractures
238	116.74	118.26	1.52	1.60	105	1.21	80	14	3	6	5	1	2	
238	118.26	119.18	0.92	0.75	82	0.36	39	9	3	6	9	1	2	
238	119.18	119.79	0.61	0.52	85	0.29	48	4	3	6	20	2	3	50% broken core with gouge
238	119.79	121.00	1.21	1.31	108	0.90	74	10	3	6	10	2	3	
238	121.00	123.44	2.44	2.47	101	2.30	94	15	3	6	4	1	2	
238	123.44	126.49	3.05	3.00	98	2.91	95	13	4	6	11	1	3	gouge on some fractures
238	126.49	128.63	2.14	1.81	85	1.16	54	10	4	6	15	2	2	10 % broken core
238	128.63	130.15	1.52	1.49	98	1.49	98	15	4	6	2	1	2	
238	130.15	131.98	1.83	1.94	106	1.90	104	15	4	6	3	1	2	
238	131.98	134.42	2.44	2.09	86	1.59	65	10	4	6	20	1	3	last 40 cm, broken core with gouge
238	134.42	135.69	1.27	1.09	86	0.68	54	9	3	6	13	1	2	broken up core
238	135.69	136.86	1.17	1.20	103	0.59	50	7	3	6	20	2	3	50 % broken up core with gouge
238	136.86	138.38	1.52	1.41	93	1.04	68	9	3	6	15	1	2	last 0.25 m. , broken up core
238	138.38	140.21	1.83	1.71	93	1.06	58	12	3	6	9	2	3	gouge on fractures
238	140.21	140.51	0.30	0.12	40	0.00	0	3	3	6	15	5	2	broken up core
238	140.51	142.34	1.83	0.93	51	0.87	48	13	3	6	4	1	3	gouge on fractures
238	142.34	145.08	2.74	2.49	91	2.07	76	13	3	6	12	1	3	gouge on fractures
238	145.08	148.13	3.05	3.00	98	2.51	82	20	3	6	15	5	3	gouge on fractures
238	148.13	151.18	3.05	3.08	101	2.90	95	14	3	6	6	2	2	pyrite on fractures
238	151.18	154.23	3.05	2.70	89	1.98	65	12	3	6	15	2	3	5 % broken core with gouge
238	154.23	157.28	3.05	3.08	101	2.89	95	13	3	6	12	2	3	DMAF at 155.74 - 156.24
238	157.28	160.33	3.05	3.12	102	3.12	102	15	3	6	3	3	2	
238	160.33	163.37	3.04	2.83	93	2.68	88	14	3	6	6	2	3	gouge on fractures
238	163.37	164.59	1.22	1.06	87	1.06	87	15	3	6	1	1	1	
238	164.59	166.73	2.14	2.07	97	2.07	97	15	3	6	2	1	2	
238	166.73	169.77	3.04	3.09	102	3.00	99	15	3	6	4	1	2	DMAF at 164.84 - 169.79
238	169.77	172.82	3.05	3.00	98	2.92	96	14	3	6	6	2	3	gouge on fractures
238	172.82	175.87	3.05	2.93	96	2.71	89	14	3	6	5	2	3	gouge on fractures
238	175.87	178.92	3.05	2.98	98	2.98	98	15	3	6	4	1	3	gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments	
	From	To	Lgth	m.	%	m.								%
238	178.92	181.45	2.53	2.02	80	1.51	60	13	3	6	10	1	2	
238	181.45	183.79	2.34	2.82	121	2.69	115	14	3	6	7	1	2	
238	183.79	185.62	1.83	1.76	96	0.89	49	12	3	6	9	1	2	
238	185.62	188.88	3.26	3.34	102	2.08	64	12	3	6	20	2	2	2 blocky, broken core
238	188.88	192.94	4.06	3.22	79	2.19	54	12	3	6	20	1	3	3 blocky, broken core with gouge
238	192.94	195.68	2.74	2.81	103	2.73	100	14	3	6	5	1	3	3 gouge on fractures
238	195.68	197.82	2.14	2.11	99	2.00	93	14	3	6	6	1	3	3 gouge on fractures
238	197.82	200.86	3.04	3.00	99	2.81	92	13	3	6	15	2	3	3 blocky, broken core
238	200.86	203.30	2.44	2.13	87	1.84	75	10	3	6	15	2	3	3 blocky, broken core
238	203.30	205.74	2.44	2.73	112	2.31	95	14	3	6	5	1	2	
238	205.74	208.79	3.05	2.80	92	2.80	92	15	3	6	4	2	2	
238	208.79	211.84	3.05	3.05	100	3.05	100	15	3	6	3	1	3	3 gouge on fractures
238	211.84	213.36	1.52	1.31	86	0.46	30	10	3	6	12	1	3	3 50 % gouge, H = 0, l
238	213.36	216.41	3.05	2.96	97	2.49	82	14	3	6	6	1	3	3 gouge on fractures
239	3.05	4.57	1.52	1.24	82	0.62	41	9	3	4	15	3	3	3 limonite staining, overburden
239	4.57	7.62	3.05	2.64	87	2.30	75	13	4	5	12	3	3	3 limonite staining, redrilled core
239	7.62	10.06	2.44	2.23	91	2.23	91	15	4	6	2	3	4	
239	10.06	13.11	3.05	2.95	97	2.95	97	15	4	6	2	3	3	
239	13.11	14.33	1.22	1.05	86	0.81	66	13	3	6	5	1	1	1 50% healed fault, weak slicks
239	14.33	17.37	3.04	3.05	100	2.91	96	14	4	5	8	3	3	3 small sections of clay and gouge
239	17.37	20.42	3.05	3.01	99	2.70	89	15	4	5	30	1	2	2 31 cm H = 0, clay and gouge
239	20.42	23.47	3.05	3.05	100	2.82	92	14	2	5	9	1	1	1 part healed gouge, slicks 45 to c.a.
239	23.47	26.52	3.05	2.75	90	2.64	87	14	2	5	7	1	1	1 part healed gouge, slicks 45 to c.a.
239	26.52	29.57	3.05	3.02	99	2.49	82	13	2	5	12	1	1	1 part healed gouge, slicks 45 to c.a.
239	29.57	32.00	2.43	2.40	99	1.24	51	11	2	4	40	1	1	1 50% fault gouge, H = 0
239	32.00	34.44	2.44	1.93	79	1.13	46	7	3	5	36	1	1	1 40% fault gouge, H = 0
239	34.44	36.88	2.44	2.50	102	1.87	77	8	2	5	32	1	1	1 67 cm. gouge, part healed H = 1
239	36.88	39.93	3.05	2.70	89	2.08	68	11	3	6	18	1	1	1 62 cm. H = 1, part healed
239	39.93	41.76	1.83	1.74	95	0.93	51	11	2	5	13	1	1	1 slick contact 35 to c.a., 50 % gouge
239	41.76	43.28	1.52	1.23	81	0.48	32	6	1	3	30	1	1	1 gouge and rubble
239	43.28	45.72	2.44	2.41	99	1.66	68	9	3	4	28	1	1	1 slick 25 to c.a., section of gouge
239	45.72	47.85	2.13	2.07	97	1.02	48	9	3	4	24	1	1	1 slick 25 to c.a., section of gouge
239	47.85	50.90	3.05	2.96	97	2.96	97	15	4	6	5	1	2	2 gypsum on fractures
239	50.90	53.95	3.05	3.00	98	3.00	98	15	4	6	3	3	4	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
239	53.95	57.00	3.05	2.83	93	2.83	93	15	4	6	4	1	1	35 to c.a.
239	57.00	60.05	3.05	2.94	96	2.94	96	15	4	6	2	1	2	
239	60.05	63.09	3.04	3.00	99	3.00	99	15	4	6	1	1	3	
240	4.27	5.18	0.91	0.28	31	0.00	0	7	3	4	15	2	3	3 broken up core
240	5.18	6.40	1.22	1.28	105	0.00	0	8	3	5	20	5	3	3 broken up core with gouge
240	6.40	8.23	1.83	1.51	83	0.55	30	8	3	5	20	5	3	3 broken up core with gouge
240	8.23	11.28	3.05	2.51	82	1.36	45	9	4	6	20	5	3	3 20% broken core with gouge
240	11.28	12.50	1.22	1.19	98	0.21	17	8	4	6	15	2	3	3 15% broken core with gouge
240	12.50	14.33	1.83	1.66	91	1.26	69	15	4	6	3	2	2	
240	14.33	15.85	1.52	1.60	105	0.45	30	13	4	6	20	5	3	3 40% broken core with gouge
240	15.85	17.37	1.52	1.10	72	0.41	27	13	4	6	12	5	3	3 10% gouge H = 1
240	17.37	20.42	3.05	2.93	96	1.92	63	14	4	6	7	2	3	3 49 cm. fault gouge H = 0, 1
240	20.42	22.25	1.83	1.84	101	0.31	17	8	3	6	20	5	3	3 70% broken core with gouge
240	22.25	24.69	2.44	1.68	69	0.40	16	8	4	6	20	5	3	
240	24.69	26.52	1.83	1.85	101	1.33	73	13	4	6	7	2	3	3 10 cm. gouge H = 1, 2
240	26.52	29.57	3.05	3.05	100	2.79	91	14	4	6	9	1	2	
240	29.57	32.61	3.04	2.95	97	2.62	86	14	4	6	5	1	2	
240	32.61	35.66	3.05	2.92	96	2.81	92	15	4	6	4	2	3	3 pyrite on fractures
240	35.66	38.71	3.05	3.05	100	2.93	96	15	4	6	5	3	3	3 gouge on fractures
240	38.71	41.76	3.05	3.12	102	3.12	102	15	4	6	2	1	2	
240	41.76	44.81	3.05	3.00	98	2.58	85	14	4	6	7	2	3	3 gouge on fractures, 12cm. gouge H = 1
240	44.81	47.85	3.04	2.97	98	2.97	98	15	4	6	3	1	2	
240	47.85	50.90	3.05	3.14	103	2.64	87	15	4	6	3	1	2	
240	50.90	53.95	3.05	3.05	100	2.81	92	15	4	6	4	1	3	3 gouge on fractures
240	53.95	57.00	3.05	3.09	101	3.00	98	15	4	6	3	1	2	
240	57.00	60.05	3.05	3.22	106	3.22	106	15	4	6				
240	60.05	63.09	3.04	2.93	96	2.46	81	14	4	6	7	2	3	3 26 cm. fault gouge H = 1, 2
240	63.09	66.14	3.05	2.81	92	2.81	92	14	4	6	5	1	3	3 gouge on fractures
240	66.14	69.19	3.05	3.10	102	2.99	98	15	4	6	3	1	3	3 gouge on fractures
240	69.19	72.24	3.05	2.93	96	2.72	89	14	4	6	7	2	3	3 shear zone, fault starts at 71.85 m.
240	72.24	75.29	3.05	3.06	100	2.82	92	14	3	5	9	2	3	3 shear zone, fault ends at 74.85 m.
240	75.29	78.33	3.04	3.04	100	2.87	94	15	4	6	5	3	3	
240	78.33	81.38	3.05	3.09	101	3.02	99	15	4	6	3	1	3	3 gouge on fractures
240	81.38	84.43	3.05	2.83	93	2.78	91	15	4	6	3	5	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
240	84.43	87.48	3.05	3.02	99	2.84	93	15	4	6	4	1	2	
240	87.48	90.53	3.05	3.05	100	2.96	97	15	4	6	3	2	3	gouge on fractures
240	90.53	93.57	3.04	2.96	97	2.84	93	15	4	6	4	1	3	gouge on fractures
240	93.57	96.62	3.05	3.20	105	2.99	98	14	5	6	8	2	3	20 cm. shear zone
240	96.62	99.67	3.05	2.90	95	2.90	95	15	5	6	4	1	2	
240	99.67	102.72	3.05	3.15	103	3.15	103	15	5	6	2	1	2	
240	102.72	105.77	3.05	2.95	97	2.90	95	15	5	6	3	1	3	gouge on fractures
240	105.77	108.81	3.04	2.79	92	2.79	92	15	5	6	4	2	3	gouge on fractures
240	108.81	111.86	3.05	3.28	108	3.04	100	15	5	6	5	2	3	10% interval is sheared
240	111.86	114.91	3.05	3.05	100	2.79	91	15	5	6	7	1	3	6 cm. gouge H = 0, 1
240	114.91	117.96	3.05	3.15	103	3.15	103	15	5	6	2	1	2	
240	117.96	121.01	3.05	3.09	101	3.09	101	15	5	6	1	1	2	
240	121.01	124.05	3.04	3.11	102	3.02	99	15	5	6	2	2	3	DMAF dyke 123.45 - 124.90
240	124.05	127.10	3.05	2.90	95	2.90	95	15	5	6	2	1	3	
240	127.10	130.15	3.05	3.06	100	2.96	97	15	5	6	3	2	3	gouge on fractures
240	130.15	133.20	3.05	3.10	102	3.07	101	15	5	6	4	2	3	black shear zone 132.98 - 133.32
240	133.20	136.25	3.05	2.95	97	2.92	96	15	5	6	3	1	3	
240	136.25	139.29	3.04	3.12	103	3.00	99	15	4	6	3	1	3	gouge on fractures
240	139.29	142.34	3.05	3.08	101	3.08	101	15	4	6	4	1	2	
240	142.34	145.39	3.05	2.95	97	2.95	97	15	4	6	1	1	2	
240	145.39	148.44	3.05	3.12	102	3.12	102	15	4	6	2	2	2	
240	148.44	151.49	3.05	2.93	96	2.80	92	15	4	6	3	1	2	
240	151.49	154.53	3.04	3.04	100	2.79	92	15	4	6	4	1	3	gouge on fractures
240	154.53	157.58	3.05	3.24	106	3.24	106	15	4	6	2	2	2	
240	157.58	160.63	3.05	2.84	93	2.69	88	15	4	6	4	2	2	
240	160.63	163.68	3.05	2.92	96	2.92	96	15	4	6	3	1	2	pyrite on fractures
240	163.68	166.73	3.05	3.10	102	2.89	95	15	4	6	2	2	3	minor gouge on fractures
240	166.73	169.77	3.04	3.05	100	3.05	100	15	4	6	2	1	2	
240	169.77	172.82	3.05	3.09	101	3.09	101	15	4	6	5	1	2	
240	172.82	175.87	3.05	3.11	102	2.91	95	15	4	6	3	2	3	gouge on fractures
240	175.87	178.92	3.05	2.80	92	2.80	92	15	4	6	3	1	2	
240	178.92	181.97	3.05	3.00	98	3.00	98	15	4	6	4	1	2	minor gouge on fractures
240	181.97	185.01	3.04	3.08	101	3.08	101	15	4	6	2	1	2	
240	185.01	188.06	3.05	2.83	93	2.71	89	14	4	6	6	1	3	gouge on fractures, 3 cm. gouge H = 0, 1

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
240	188.06	191.11	3.05	3.00	98	2.94	96	15	4	6	5	1	3	gouge on fractures
240	191.11	194.16	3.05	3.05	100	3.05	100	15	4	6	2	1	3	gouge on fractures
240	194.16	197.21	3.05	3.03	99	2.71	89	15	4	6	3	1	2	pyrite on fractures
240	197.21	200.25	3.04	3.01	99	3.01	99	15	4	6	2	1	1	DPFH starts at 199.75 m.
240	200.25	202.69	2.44	2.82	116	2.82	116	15	4	6	2	1	2	
240	202.69	205.74	3.05	3.10	102	3.10	102	15	4	6	3	1	2	
240	205.74	208.79	3.05	3.00	98	3.00	98	15	4	6	4	1	2	
240	208.79	211.84	3.05	3.03	99	3.03	99	15	4	6	4	1	2	minor gouge on fractures
240	211.84	214.58	2.74	2.59	95	2.56	93	15	4	6	2	1	3	2 cm. gouge H = 0, 1
240	214.58	217.63	3.05	3.18	104	3.02	99	15	4	6	2	2	2	DPFH ends at 216.70 m.
240	217.63	220.68	3.05	2.88	94	2.88	94	15	4	6	1	5	2	
240	220.68	223.72	3.04	3.06	101	3.06	101	15	4	6	2	2	2	
240	223.72	224.64	0.92	1.06	115	1.06	115	15	4	6	1	3	3	gouge on fractures
240	224.64	227.69	3.05	3.13	103	3.13	103	15	4	6	1	1	2	
240	227.69	230.73	3.04	3.04	100	3.04	100	15	4	6	2	1	2	pyrite on fractures
240	230.73	233.78	3.05	3.11	102	3.11	102	15	4	6	1	1	2	pyrite on fractures
240	233.78	236.83	3.05	3.12	102	3.12	102	15	4	6	1	1	2	pyrite on fractures
240	236.83	239.88	3.05	3.10	102	3.10	102	15	4	6	3	1	2	pyrite on fractures
240	239.88	242.93	3.05	3.05	100	3.05	100	15	4	6	3	3	2	
240	242.93	245.97	3.04	3.04	100	3.00	99	15	4	6	3	3	2	
240	245.97	249.02	3.05	2.95	97	2.95	97	15	4	6	5	1	1	
240	249.02	252.07	3.05	3.08	101	3.08	101	15	4	6	2	1	2	
240	252.07	255.12	3.05	3.10	102	2.90	95	14	4	6	10	1	1	
240	255.12	258.17	3.05	2.90	95	1.40	46	12	3	5	18	2	2	blocky and clay altered
240	258.17	261.21	3.04	3.25	107	1.85	61	13	3	6	15	2	3	
240	261.21	264.26	3.05	2.87	94	1.37	45	12	4	5	16	2	2	30 cm shear and clay altered
240	264.26	267.31	3.05	2.97	97	2.67	88	14	4	6	9	1	2	
240	267.31	270.36	3.05	3.05	100	2.70	89	13	4	6	14	1	2	
240	270.36	273.41	3.05	3.20	105	1.51	50	11	4	6	21	1	2	
240	273.41	276.45	3.04	3.04	100	1.95	64	13	4	6	13	1	2	
240	276.45	279.50	3.05	3.05	100	1.26	41	10	3	5	25	2	2	
240	279.50	282.55	3.05	3.20	105	1.92	63	13	4	6	14	2	2	
240	282.55	285.60	3.05	3.15	103	2.65	87	14	4	6	10	1	2	
240	285.60	288.04	2.44	2.44	100	1.20	49	13	4	6	9	3	3	fractures parallel to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
240	288.04	291.08	3.04	3.04	100	2.22	73	12	4	6	16	2	2	
240	291.08	294.44	3.36	3.36	100	2.25	67	13	4	6	14	2	2	
240	294.44	297.48	3.04	3.00	99	2.65	87	14	4	6	9	1	2	
240	297.48	299.92	2.44	2.60	107	1.95	80	11	4	6	16	2	2	
240	299.92	302.97	3.05	3.20	105	2.95	97	12	4	6	15	2	2	
240	302.97	306.02	3.05	2.85	93	1.87	61	12	4	6	15	1	2	
240	306.02	308.76	2.74	2.74	100	2.05	75	13	4	6	11	1	1	
240	308.76	311.81	3.05	3.00	98	3.00	98	15	4	6	5	1	1	
240	311.81	313.03	1.22	1.15	94	1.15	94	15	4	6	1	3	4	
240	313.03	316.08	3.05	3.15	103	2.82	92	15	4	6	5	3	3	
240	316.08	319.13	3.05	3.20	105	3.20	105	14	4	6	8	1	1	
240	319.13	322.17	3.04	3.04	100	2.85	94	14	4	6	6	1	1	
240	322.17	325.22	3.05	3.10	102	2.70	89	14	4	6	10	1	2	
240	325.22	328.27	3.05	3.10	102	2.95	97	14	3	5	7	2	3	
240	328.27	331.32	3.05	3.05	100	3.05	100	15	4	6				
240	331.32	334.37	3.05	3.05	100	2.80	92	15	3	5	8	3	2	
240	334.37	337.72	3.35	3.25	97	3.18	95	15	4	6	3	1	2	
240	337.72	339.85	2.13	1.74	82	1.49	70	10	4	6	15	5	3	reduced to NQ core
240	339.85	342.90	3.05	3.03	99	3.03	99	15	4	6	2	1	2	
240	342.90	345.95	3.05	3.07	101	2.83	93	15	4	6	5	2	3	fracture parallel to c.a, gouge on fractures.
240	345.95	349.00	3.05	3.00	98	2.72	89	14	4	6	9	2	3	fracture parallel to c.a, gouge on fractures.
240	349.00	351.74	2.74	3.06	112	1.52	55	10	3	5	25	2	3	20% broken core with gouge
240	351.74	354.79	3.05	2.89	95	2.40	79	14	3	6	9	1	3	gouge on fractures
240	354.79	357.84	3.05	3.03	99	2.91	95	14	3	6	6	1	3	gouge on fractures
240	357.84	359.87	2.03	2.03	100	2.03	100	15	4	6	2	1	2	
240	359.87	361.80	1.93	1.61	83	1.61	83	15	4	6	2	1	2	
240	361.80	364.24	2.44	1.77	73	1.74	71	15	4	6	2	1	2	
240	364.24	366.37	2.13	3.06	144	3.07	144	15	4	6	3	2	3	minor gouge on fractures
240	366.37	369.11	2.74	2.87	105	2.55	93	14	4	6	7	1	3	gouge on fractures
240	369.11	372.16	3.05	3.00	98	2.95	97	15	4	6	5	1	3	gouge on fractures
240	372.16	373.99	1.83	1.97	108	1.97	108	15	4	6				
240	373.99	377.04	3.05	2.91	95	2.91	95	15	4	6	1	1	2	
240	377.04	380.09	3.05	3.08	101	3.08	101	15	4	6	3	1	2	
240	380.09	383.13	3.04	3.00	99	3.00	99	15	4	6	3	1	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
240	383.13	386.18	3.05	3.07	101	2.98	98	14	4	6	8	2	3	7 cm gouge H=1,2, gouge on fractures
240	386.18	389.23	3.05	2.78	91	2.69	88	14	3	5	6	2	3	fault/shear starts at 388.92m
240	389.23	392.28	3.05	2.88	94	2.65	87	14	3	5	6	2	3	
240	392.28	395.33	3.05	3.05	100	2.21	72	13	3	5	11	2	3	fault/shear ends at 393.52m
240	395.33	398.37	3.04	3.04	100	2.49	82	14	3	5	8	1	3	weakly sheared, last 25 cm broken core
240	398.37	401.42	3.05	2.96	97	2.03	67	13	3	5	10	2	3	50% fault material H=1
240	401.42	402.95	1.53	1.51	99	0.40	26	12	3	5	8	2	3	50% fault material H=1
240	402.95	405.99	3.04	2.76	91	1.44	47	12	3	5	15	5	3	sheared
240	405.99	406.91	0.92	0.35	38	0.10	11	6	3	5	10	5	3	sheared
241	25.30	25.60	0.30	0.28	93	0.28	93	15	4	6				dyke, hole triconed to 25.30 m
241	25.60	27.43	1.83	1.02	56	0.94	51	15	4	6	50	1	1	dyke, washed away material
241	27.43	28.35	0.92	0.67	73	0.50	54	15	4	6	30	1	1	dyke, begin fault
241	28.35	32.61	4.26	0.32	8	0.00	0	2	2	3	30	5	4	rubble and fault gouge
241	32.61	35.66	3.05	0.30	10	0.00	0	2	2	3	40	5	4	rubble and fault gouge
241	35.66	38.71	3.05	0.36	12	0.00	0	2	2	3	50	5	4	rubble and fault gouge
241	38.71	41.46	2.75	0.15	5	0.00	0	2	2	3	30	5	4	rubble and fault gouge
241	41.46	48.77	7.31	0.16	2	0.00	0	2	2	3	30	5	4	rubble and fault gouge
241	48.77	50.90	2.13	0.23	11	0.00	0	3	2	3	30	5	4	rubble and fault gouge
241	50.90	53.95	3.05	0.26	9	0.00	0	1	0	1	40	5	4	rubble and fault gouge
241	53.95	59.74	5.79	0.15	3	0.00	0	2	2	3	30	5	4	rubble and fault gouge
241	59.74	63.09	3.35	0.14	4	0.00	0	2	2	3	30	5	4	rubble and fault gouge
241	63.09	66.14	3.05	0.15	5	0.00	0	2	2	3	30	5	4	rubble and fault gouge
241	66.14	69.19	3.05	0.08	3	0.00	0	1	2	3	22	5	4	rubble and fault gouge
241	69.19	72.24	3.05	0.08	3	0.00	0	1	2	3	20	5	4	rubble and fault gouge
241	72.24	75.29	3.05	0.32	10	0.00	0	2	2	3	50	5	4	rubble and fault gouge
241	75.29	78.33	3.04	0.23	8	0.00	0	1	0	2	50	5	4	rubble and fault gouge
241	78.33	81.38	3.05	0.24	8	0.00	0	1	0	2	50	5	4	rubble and fault gouge
241	81.38	84.43	3.05	0.22	7	0.00	0	1	0	2	50	5	4	rubble and fault gouge
241	84.43	86.87	2.44	0.41	17	0.00	0	2	2	3	40	5	4	rubble and fault gouge
241	86.87	90.53	3.66	0.00	0	0.00	0							no recovery
241	90.53	92.96	2.43	0.13	5	0.00	0	3	2	3	19	5	4	rubble
241	92.96	96.62	3.66	0.15	4	0.00	0	3	3	5	11	3	4	rubble
241	96.62	97.54	0.92	0.17	18	0.00	0	3	3	5	18	3	4	rubble
241	97.54	98.45	0.91	0.21	23	0.00	0	3	3	5	16	3	4	rubble

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
241	98.45	99.97	1.52	1.31	86	1.13	74	13	3	6	5	3	4	minor rubble
241	99.97	102.72	2.75	2.40	87	2.27	83	14	3	6	5	3	4	gypsum veins, no slicks
241	102.72	105.77	3.05	2.93	96	2.93	96	15	3	6	3	3	3	gypsum veins, no slicks
241	105.77	108.81	3.04	3.18	105	2.97	98	13	3	5	15	1	2	gypsum veins, no slicks
241	108.81	111.86	3.05	3.15	103	3.15	103	15	3	6	4	1	2	gypsum veins, no slicks
241	111.86	114.91	3.05	3.03	99	3.03	99	15	3	6				gypsum veins, no slicks
241	114.91	117.96	3.05	3.00	98	2.86	94	14	3	6	10	1	1	minor gouge, weak slicks
241	117.96	121.01	3.05	3.02	99	2.97	97	14	3	6	7	1	2	sharp contacts at dyke
241	121.01	124.05	3.04	3.05	100	3.05	100	15	4	6	4	1	2	very hard rock
241	124.05	127.10	3.05	3.05	100	3.05	100	15	4	6				very hard rock
241	127.10	130.15	3.05	3.05	100	3.05	100	15	4	6				very hard rock
241	130.15	133.20	3.05	2.92	96	2.57	84	13	3	6	11	1	1	
241	133.20	136.25	3.05	3.05	100	3.05	100	15	3	6	4	1	2	localized gouge with quartz flooded rock
241	136.25	139.30	3.05	2.98	98	2.52	83	13	4	5	14	1	2	localized gouge with quartz flooded rock
241	139.30	141.43	2.13	1.93	91	0.90	42	8	4	6	23	1	2	50 % fault gouge, Intense stockwork
241	141.43	142.34	0.91	0.54	59	0.25	27	5	4	6	14	1	2	50 % fault gouge, Intense stockwork
241	142.34	145.39	3.05	3.16	104	2.92	96	13	3	5	13	1	1	weak slicks, gouge filled fractures
241	145.39	148.44	3.05	2.95	97	2.95	97	15	3	6	4	3	3	
241	148.44	149.96	1.52	0.71	47	0.71	47	15	3	6				
241	149.96	151.49	1.53	1.53	100	1.41	92	12	3	6	9	3	4	rubble at 149.96 m
241	151.49	154.23	2.74	2.76	101	2.54	93	14	3	6	7	1	1	slicks , 45 to c.a.
241	154.23	157.28	3.05	3.05	100	2.71	89	12	3	5	17	1	1	gouge and slicks, 45 to c.a.
241	157.28	160.32	3.04	3.00	99	2.77	91	14	3	6	7	1	1	faulting, strong slicks, 45 to c.a.
241	160.32	163.37	3.05	2.98	98	2.36	77	11	3	5	22	1	1	H=0,1 for 60 cm
241	163.37	166.42	3.05	3.15	103	2.59	85	11	3	5	23	1	1	many fractures
241	166.42	167.64	1.22	0.94	77	0.94	77	14	3	6	3	1	2	gypsum on fractures
241	167.64	169.77	2.13	2.14	100	2.14	100	14	4	6	4	1	2	gypsum on fractures
241	169.77	172.82	3.05	3.00	98	2.83	93	14	3	6	8	1	2	gypsum on fractures
241	172.82	175.87	3.05	2.98	98	2.98	98	15	4	6	4	1	2	gypsum on fractures
241	175.87	177.04	1.17	1.21	103	1.21	103	15	4	6	2	1	2	gypsum on fractures
241	177.04	178.92	1.88	1.71	91	1.55	82	13	3	5	7	1	1	faulting, partly healed
241	178.92	181.66	2.74	1.97	72	0.79	29	5	3	5	60	1	1	50% fault + clay, partly healed
241	181.66	184.10	2.44	2.25	92	1.07	44	5	3	5	60	1	1	50% fault + clay, partly healed
241	184.10	187.15	3.05	3.05	100	1.24	41	8	2	5	40	1	1	40% fault + clay, partly healed

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
241	187.15	190.20	3.05	2.96	97	2.56	84	13	3	5	13	1	1	1 40% fault + clay, partly healed, very slick
241	190.20	193.24	3.04	2.90	95	2.70	89	14	3	5	9	1	1	1 40% fault + clay, partly healed
241	193.24	195.99	2.75	2.82	103	2.70	98	13	4	6	11	1	1	1 weak slicks, 12 cm gouge, H=0
241	195.99	197.21	1.22	1.20	98	1.16	95	13	4	6	6	1	1	1 weak slicks, 4 cm gouge, H=0
241	197.21	200.25	3.04	3.05	100	2.90	95	13	4	6	12	1	1	1 weak slicks, 15 cm gouge, H=0
241	200.25	203.30	3.05	3.05	100	3.00	98	15	4	6	4	1	1	1 weak slicks, 4 cm gouge, H=0
241	203.30	206.35	3.05	3.00	98	3.00	98	15	4	6	2	3	3	
241	206.35	209.40	3.05	2.98	98	2.98	98	15	4	6	2	3	3	
241	209.40	212.45	3.05	3.05	100	2.88	94	14	3	5	18	1	1	1 weak slicks
241	212.45	215.49	3.04	2.96	97	2.34	77	10	3	6	50	1	1	1 slip planes with gouge, 45 to c.a.
241	215.49	218.54	3.05	2.94	96	2.94	96	15	4	6	3	2	2	
241	218.54	221.59	3.05	3.05	100	3.05	100	15	4	6	7	1	2	
241	221.59	224.64	3.05	3.05	100	3.05	100	15	4	6				
241	224.64	227.69	3.05	2.99	98	2.99	98	15	5	6	3	1		3 volcanics, very hard rock
241	227.69	230.73	3.04	3.04	100	2.95	97	15	4	6	6	1		1 weak slicks
241	230.73	233.78	3.05	3.00	98	3.00	98	15	4	6	2	1	1	
241	233.78	236.22	2.44	2.58	106	2.49	102	14	3	6	5	1	1	
241	236.22	239.27	3.05	3.05	100	3.05	100	15	4	6	3	1	1	1 slick 30 to c.a.
241	239.27	242.32	3.05	3.05	100	3.00	98	15	4	6	5	1	1	1 broken core, redrilled
241	242.32	245.36	3.04	3.10	102	3.10	102	15	4	6	2	1	1	1 weak slicks
241	245.36	248.41	3.05	2.93	96	2.93	96	15	4	6	3	3	3	
241	248.41	251.46	3.05	3.10	102	3.08	101	15	5	6	2	1	1	
241	251.46	254.81	3.35	3.15	94	2.95	88	13	4	6	10	1	1	1 gouge filled fractures
241	254.81	257.25	2.44	2.23	91	1.97	81	12	3	6	12	1	1	1 weak mineralized slick
241	257.25	260.30	3.05	3.05	100	3.00	98	15	4	6	2	1	1	1 73cm of massive sulfide, slick, contacts 45tca
241	260.30	261.21	0.91	0.79	87	0.51	56	10	4	6	20	1	1	1 30 cm of H=0, gouge
241	261.21	264.26	3.05	2.95	97	2.17	71	12	3	5	17	1	1	1 broken core, gouge 70 cm
241	264.26	267.31	3.05	2.93	96	2.93	96	15	4	6	2	3	3	
241	267.31	270.36	3.05	2.92	96	2.86	94	14	4	6	7	1	1	1 weak slicks
241	270.36	273.41	3.05	2.99	98	2.99	98	15	4	6				
241	273.41	276.45	3.04	3.02	99	3.02	99	15	4	6	1	1	3	
241	276.45	279.50	3.05	3.00	98	2.92	96	15	4	6	5	1	1	1 4 cm gouge, weak slick
241	279.50	282.55	3.05	3.12	102	3.12	102	15	4	6	1	3	3	
241	282.55	285.60	3.05	3.02	99	3.02	99	15	4	6	1	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
241	285.60	288.65	3.05	3.04	100	3.04	100	15	4	6				
241	288.65	291.69	3.04	3.02	99	3.02	99	15	4	6	2	1	2	
241	291.69	294.74	3.05	2.99	98	2.99	98	15	4	6	1	1	2	
241	294.74	297.79	3.05	3.08	101	3.08	101	15	4	6				
241	297.79	300.84	3.05	3.05	100	3.05	100	15	4	6	2	3		2 undulating fractures, slick ?
241	300.84	303.89	3.05	3.10	102	3.10	102	15	5	6				
241	303.89	306.93	3.04	3.05	100	3.05	100	15	5	6	1	3	3	
241	306.93	309.98	3.05	2.92	96	2.92	96	15	5	6				
241	309.98	313.03	3.05	3.08	101	3.08	101	15	5	6	2	1	1	
241	313.03	316.08	3.05	3.05	100	3.05	100	15	5	6	3	3	3	
241	316.08	319.13	3.05	2.80	92	2.53	83	13	5	6	12	1		1 slicks at 10-15 to c.a.
241	319.13	322.17	3.04	3.00	99	2.99	98	15	4	6	1	1		1 slip plane at 5 to c.a.
241	322.17	324.31	2.14	1.95	91	1.95	91	15	5	6				
241	324.31	327.36	3.05	3.16	104	3.16	104	15	5	6				
241	327.36	330.40	3.04	3.10	102	3.10	102	15	4	6	2	1	2	
241	330.40	333.45	3.05	3.08	101	3.07	101	15	4	6	3	3	3	
241	333.45	336.50	3.05	3.07	101	3.07	101	15	4	6	2	1	2	
241	336.50	339.55	3.05	3.05	100	3.00	98	15	3	6	5	1		2 gouge on fractures
241	339.55	342.90	3.35	3.08	92	2.87	86	15	3	5	12	1		1 clay ad gouge on fractures; 21 cm of H=1
241	342.90	344.12	1.22	1.21	99	0.88	72	8	3	5	15	1		1 33 cm of H=1,2
241	344.12	347.17	3.05	2.98	98	2.98	98	15	4	6	3	1	2	
241	347.17	350.22	3.05	3.05	100	3.05	100	15	4	6	5	3	4	
241	350.22	353.26	3.04	2.96	97	2.14	70	11	5	5	22	1		1 25% of H=2-0; weak shear zone with slicks
241	353.26	356.31	3.05	3.00	98	2.98	98	15	4	6	1	1		1 3 cm shear
241	356.31	359.36	3.05	3.05	100	3.03	99	15	4	6	5	1	2	
241	359.36	362.10	2.74	2.53	92	1.56	57	12	4	6	13	1		1 broken core, weak slick, no gouge
241	362.10	364.85	2.75	2.89	105	2.89	105	14	4	6	6	1		3 broken core, no slicks; no gouge
241	364.85	367.89	3.04	3.05	100	3.02	99	15	4	6	4	1		1 slick at 15 to c.a.
241	367.89	370.94	3.05	2.99	98	2.90	95	14	3	5	9	1		1 slick at 15 to c.a.
241	370.94	373.99	3.05	3.05	100	3.05	100	15	4	6	4	3	3	
241	373.99	377.04	3.05	2.74	90	2.51	82	14	4	6	7	1	2	
241	377.04	380.09	3.05	3.05	100	2.90	95	13	4	6	13	1		1 15 cm of fault gouge, H=0,1
241	380.09	383.13	3.04	3.02	99	2.95	97	15	4	6	2	1		1 very slick; 30 to c.a.
241	383.13	386.18	3.05	3.05	100	3.03	99	15	5	6	3	1		1 very slick; 45 to c.a.

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
241	386.18	389.23	3.05	3.05	100	3.03	99	15	5	6	2	1	1	1 very slick; 45 to c.a.
241	389.23	392.28	3.05	3.05	100	3.05	100	15	5	6	4	1	2	
241	392.28	395.33	3.05	3.05	100	3.01	99	15	5	6	5	1	1	1 weak slicks
241	395.33	398.37	3.04	3.10	102	2.98	98	14	3	5	9	1	2	2 broken sections of rock
241	398.37	401.42	3.05	2.96	97	2.53	83	14	3	5	50	1	1	1 43 cm of fault gouge; H=0; very slick 45 to c.a.
241	401.42	404.47	3.05	3.00	98	2.87	94	14	3	5	7	1	1	1 weak slicks
242	10.97	11.28	0.31	1.12	361	0.15	48	6	3	3	30	5	3	3 weathered, iron stained fractures
242	11.28	14.02	2.74	0.55	20	0.00	0	6	3	3	25	3	3	3 weathered, iron stained fractures
242	14.02	16.15	2.13	1.30	61	0.15	7	6	3	3	45	3	3	3 weathered, iron stained to 15.90 m, gouge
242	16.15	18.29	2.14	1.70	79	0.61	29	7	4	5	30	5	3	3
242	18.29	19.81	1.52	1.62	107	0.55	36	7	4	5	25	3	3	3
242	19.81	21.03	1.22	1.22	100	0.00	0	6	4	5	25	3	3	3
242	21.03	23.47	2.44	2.25	92	1.86	76	13	4	5	10	3	3	3
242	23.47	26.52	3.05	2.93	96	2.75	90	14	4	5	6	1	2	2 clay on fractures
242	26.52	29.57	3.05	3.08	101	2.47	81	13	3	5	15	2	3	3 10 cm sections healed gouge H=3, gouge
242	29.57	32.61	3.04	2.92	96	2.92	96	14	3	4	6	2	1	1 32.57-32.75 m shear 40 to c.a. with slicks
242	32.61	35.66	3.05	3.03	99	2.65	87	12	3	4	17	2	1	1 shears with weak slicks
242	35.66	38.71	3.05	3.15	103	2.82	92	14	3	4	8	2	3	3 gouge on fractures
242	38.71	41.76	3.05	3.10	102	2.63	86	13	3	4	11	2	3	3 39.94-40.45 m shear 45 to c.a., gouge fractures
242	41.76	44.81	3.05	3.10	102	2.93	96	15	3	5	5	2	3	3
242	44.81	47.85	3.04	3.04	100	2.70	89	14	3	5	10	2	2	2 clay and gouge on fractures
242	47.85	50.90	3.05	3.00	98	3.00	98	15	4	5	2	2	3	3
242	50.90	53.95	3.05	2.96	97	2.92	96	14	4	5	7	1	3	3 gouge on fractures
242	53.95	57.00	3.05	3.15	103	2.50	82	12	3	5	17	2	2	2 15 cm healed shear H=2,3
242	57.00	60.05	3.05	3.05	100	3.05	100	15	4	5	4	2	3	3 minor gouge on fractures
242	60.05	63.09	3.04	3.04	100	3.04	100	15	4	5	3	1	2	2 clay on fractures
242	63.09	66.14	3.05	3.05	100	2.92	96	15	4	5	4	2	3	3 gouge on fractures
242	66.14	69.19	3.05	3.00	98	2.95	97	15	4	5	4	3	3	3
242	69.19	72.24	3.05	3.10	102	3.10	102	15	5	5	3	2	3	3 pyrite on fractures
242	72.24	75.29	3.05	3.00	98	2.83	93	14	5	5	5	3	2	2
242	75.29	78.33	3.04	3.00	99	2.93	96	14	5	5	5	3	3	3 3 cm gouge seam at 35 to c.a.
242	78.33	81.38	3.05	3.08	101	3.08	101	14	4	5	6	3	3	3
242	81.38	84.43	3.05	3.24	106	2.82	92	14	3	4	10	2	3	3 sheared
242	84.43	87.48	3.05	2.85	93	2.58	85	9	3	4	30	2	2	2 84.58-85.93m sheared with gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
242	87.48	90.53	3.05	3.13	103	2.92	96	14	3	4	8	1	2	89.86-95.17m shear/fault U.C 30 to c.a.
242	90.53	93.57	3.04	2.62	86	1.63	54	9	3	4	30	2	2	shear/gouge; clay slips
242	93.57	96.62	3.05	2.98	98	2.55	84	12	3	4	17	3	2	L.C. of shear at 95.17m is 30 to c.a.
242	96.62	99.67	3.05	3.13	103	3.13	103	14	4	5	7	3	3	
242	99.67	102.72	3.05	3.10	102	3.10	102	15	4	5	5	3	3	
242	102.72	105.77	3.05	3.15	103	3.00	98	14	4	5	9	1	2	clay on slips, 10 cm shear H=2,3
242	105.77	108.81	3.04	3.08	101	2.63	87	13	4	5	11	3	3	gouge on fractures
242	108.81	111.86	3.05	2.92	96	2.04	67	10	4	5	21	3	3	
242	111.86	114.91	3.05	3.00	98	2.85	93	15	4	5	4	3	3	111.97-112.07m shear at 25-30 to c.a.
242	114.91	117.96	3.05	3.16	104	3.16	104	15	5	5	4	2	2	
242	117.96	121.01	3.05	3.05	100	3.05	100	15	5	6	3	3	3	
242	121.01	124.05	3.04	3.08	101	3.08	101	15	5	6	2	2	2	clay on slips
242	124.05	127.10	3.05	3.05	100	3.05	100	15	5	6	1	2	3	
242	127.10	129.50	2.40	2.35	98	2.21	92	13	4	6	8	2	3	gouge and clay on fractures
242	129.50	130.15	0.65	0.56	86	0.30	46	12	5	6	3	2	2	clay on slips
242	130.15	133.20	3.05	3.00	98	2.78	91	14	5	6	8	2	3	gouge on fractures
242	133.20	136.25	3.05	2.98	98	2.85	93	14	5	6	6	2	2	shear with pyrite 13 cm at 40 to c.a.
242	136.25	139.29	3.04	3.17	104	2.67	88	14	5	6	9	2	2	
242	139.29	142.34	3.05	3.03	99	2.95	97	14	5	6	8	2	2	clay on slips
242	142.34	144.78	2.44	2.49	102	2.49	102	15	5	6	3	2	2	
242	144.78	148.44	3.66	3.80	104	3.80	104	15	5	6	6	3	3	
242	148.44	151.49	3.05	3.07	101	2.81	92	15	5	6	4	2	3	clay and gouge on slips
242	151.49	154.53	3.04	3.15	104	3.15	104	15	5	6	3	2	2	
242	154.53	157.58	3.05	3.02	99	3.02	99	15	5	6	3	3	2	clay on slips
242	157.58	160.63	3.05	3.10	102	2.57	84	14	5	6	8	2	2	clay on slips
242	160.63	163.68	3.05	3.12	102	3.12	102	15	4	6	4	3	3	gouge on fractures
242	163.68	166.73	3.05	3.03	99	3.03	99	15	4	5	4	5	3	164.80-165.15 m shear at 20 to c.a. H=2,3
242	166.73	169.77	3.04	3.00	99	3.00	99	14	3	5	5	3	3	shears throughout
242	169.77	172.82	3.05	2.93	96	2.70	89	14	4	5	5	1	2	169.77-170.15 m healed shear at 45 to c.a.
242	172.82	175.87	3.05	3.12	102	3.12	102	14	5	6	6	2	2	clay on slips
242	175.87	178.92	3.05	3.12	102	3.12	102	15	5	6	4	3	3	
242	178.92	181.97	3.05	2.81	92	2.81	92	15	5	6	4	3	3	gouge on fractures
242	181.97	185.01	3.04	3.38	111	3.38	111	15	5	6	5	3	2	clay and gouge on fractures
242	185.01	188.06	3.05	3.04	100	3.04	100	15	5	6	4	3	3	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
242	188.06	190.50	2.44	2.51	103	2.51	103	15	5	6	3	3	3	
242	190.50	193.55	3.05	3.13	103	3.13	103	15	5	6	3	2	3	
242	193.55	196.60	3.05	3.14	103	3.14	103	15	5	6	3	2	2	
242	196.60	199.64	3.04	3.15	104	2.67	88	14	5	6	6	2	3	gypsum on fractures
242	199.64	203.00	3.36	3.14	93	3.14	93	15	5	6	5	2	3	gypsum on fractures
242	203.00	206.04	3.04	3.12	103	3.12	103	15	5	6	3	2	3	gypsum on fractures
242	206.04	209.09	3.05	3.13	103	3.13	103	15	5	6	2	2	3	gypsum on fractures
242	209.09	212.14	3.05	2.65	87	2.65	87	15	5	6	2	3	3	
242	212.14	212.45	0.31	0.37	119	0.37	119	14	5	6	1	2	3	
242	212.45	215.49	3.04	3.08	101	3.08	101	15	5	6	3	2	2	clay and gouge on fracture
242	215.49	218.54	3.05	3.10	102	2.73	90	14	5	6	10	2	2	15 cm shear at 35 to c.a., clay on slips
242	218.54	220.98	2.44	2.30	94	2.30	94	14	5	6	4	3	3	gypsum on fractures
242	220.98	224.03	3.05	3.05	100	3.05	100	15	5	6	2	2	3	
242	224.03	227.08	3.05	3.06	100	3.06	100	15	5	6	2	2	3	10 cm shear at 50 to c.a. H=3
242	227.08	229.82	2.74	2.57	94	2.57	94	15	5	6	3	2	3	
242	229.82	232.87	3.05	3.18	104	3.18	104	15	4	5	4	2	3	gypsum on fractures
242	232.87	235.92	3.05	2.94	96	2.94	96	14	4	5	6	2	2	gypsum on fractures
242	235.92	238.96	3.04	3.00	99	3.00	99	15	4	5	2	3	3	gypsum on fractures
242	238.96	242.01	3.05	3.20	105	3.20	105	15	4	5	5	3	3	
242	242.01	245.06	3.05	3.00	98	3.00	98	15	3	5	3	3	3	sheared at 30 to c.a.
242	245.06	248.11	3.05	2.97	97	2.97	97	15	3	5	4	2	3	gypsum on fractures
242	248.11	249.02	0.91	0.94	103	0.94	103	14	4	5	2	3	3	
242	249.02	252.07	3.05	3.12	102	3.12	102	15	4	5	5	3	3	gypsum on fractures
242	252.07	255.12	3.05	3.00	98	3.00	98	14	3	5	5	1	2	clay on slips; sheared at 45 to c.a.
242	255.12	258.17	3.05	3.01	99	3.01	99	15	3	5	5	2	3	
242	258.17	261.21	3.04	3.01	99	3.01	99	15	3	5	4	3	2	gypsum on fractures
242	261.21	264.26	3.05	2.96	97	2.96	97	15	4	6	2	1	2	gypsum on fractures
242	264.26	267.31	3.05	2.78	91	2.78	91	14	4	6	5	1	2	clay on slips
242	267.31	270.36	3.05	3.17	104	3.17	104	15	4	6	5	3	2	
242	270.36	272.30	1.94	2.83	146	2.83	146	15	4	6	4	2	2	gypsum on fractures
242	272.30	275.84	3.54	3.06	86	3.06	86	14	4	6	6	3	3	gypsum on fractures
242	275.84	278.89	3.05	2.90	95	2.72	89	14	4	6	7	3	3	7 cm healed gouge at 35 to c.a.
242	278.89	281.94	3.05	3.05	100	3.05	100	15	4	6	4	2	2	gypsum on fractures
242	281.94	284.99	3.05	3.11	102	2.91	95	14	4	6	7	2	2	clay on slips

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
242	284.99	288.04	3.05	2.98	98	2.88	94	14	4	5	7	3	3	3 clay on slips
242	288.04	290.78	2.74	2.55	93	2.27	83	14	4	5	8	2	2	2 clay on slips
242	290.78	293.83	3.05	3.10	102	2.69	88	13	3	4	11	1	2	2 clay on slips, shears throughout
242	293.83	296.88	3.05	3.27	107	2.85	93	13	3	4	14	2	2	2 296.68-297.75 m shear at 40-45 to c.a.
242	296.88	299.92	3.04	2.86	94	2.67	88	15	3	4	4	2	2	2 clay on slips
242	299.92	302.97	3.05	3.02	99	3.02	99	15	5	6	1	3	3	3 gouge on fractures
242	302.97	306.02	3.05	3.00	98	3.00	98	15	5	6	2	3	3	3
242	306.02	306.93	0.91	1.02	112	1.02	112	14	5	6	2	2	3	3
242	306.93	309.98	3.05	2.90	95	2.90	95	14	5	6	6	2	3	3
242	309.98	313.03	3.05	2.91	95	2.91	95	14	4	6	5	3	3	3 gouge on fractures
242	313.03	316.08	3.05	2.95	97	1.98	65	10	4	5	22	3	3	3 gouge and clay on fractures, sheared
242	316.08	319.13	3.05	3.07	101	2.87	94	14	4	5	6	3	3	3 gouge on fractures
242	319.13	322.17	3.04	3.04	100	2.52	83	14	4	5	9	3	3	3 gouge on fractures
242	322.17	325.22	3.05	2.98	98	2.98	98	14	4	5	5	2	3	3 minor gouge on fractures
242	325.22	328.27	3.05	3.04	100	3.04	100	15	4	5	2	2	3	3 minor gouge on fractures
242	328.27	331.32	3.05	2.92	96	2.59	85	14	4	5	8	2	3	3 10 cm sheared intervals, 45 to c.a.
242	331.32	334.37	3.05	3.00	98	2.60	85	12	4	5	17	2	3	3 gouge on fractures
242	334.37	337.41	3.04	3.01	99	3.01	99	15	4	5	5	3	3	3
242	337.41	340.46	3.05	3.18	104	2.24	73	12	4	5	18	3	3	3
242	340.46	343.51	3.05	2.88	94	2.51	82	12	4	5	18	3	3	3 clay and gouge on fractures
242	343.51	346.56	3.05	3.13	103	2.51	82	13	4	6	11	3	3	3 343.98-344.21m healed shear at 45 to c.a.
242	346.56	349.61	3.05	3.05	100	3.05	100	15	4	6	2	3	3	3 gouge on fractures
242	349.61	352.65	3.04	2.89	95	2.89	95	15	4	6	4	3	3	3 gouge on fractures
242	352.65	355.70	3.05	3.01	99	3.01	99	14	4	6	6	2	3	3 gouge on fractures
242	355.70	358.75	3.05	3.08	101	2.81	92	14	4	6	7	3	3	3 gouge on fractures
242	358.75	361.80	3.05	3.03	99	3.03	99	15	4	6	4	3	3	3 gouge on fractures
242	361.80	364.85	3.05	3.00	98	2.93	96	14	4	6	5	2	3	3
242	364.85	367.89	3.04	3.00	99	3.00	99	15	4	6	3	3	3	3
242	367.89	370.94	3.05	2.93	96	2.47	81	13	4	6	11	3	3	3 gouge and clay on fractures
242	370.94	373.99	3.05	3.08	101	3.08	101	14	4	6	6	2	3	3 gouge and clay on fractures
242	373.99	377.04	3.05	3.07	101	3.02	99	14	4	6	6	3	3	3 gouge on fractures
242	377.04	380.09	3.05	2.87	94	2.25	74	13	4	6	12	3	3	3 gouge on fractures
242	380.09	383.13	3.04	3.22	106	1.94	64	12	3	5	18	3	3	3 sheared with gouge and clay
242	383.13	386.18	3.05	2.95	97	2.85	93	14	4	5	6	2	3	3 gouge on fractures

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
242	386.18	389.23	3.05	2.90	95	2.85	93	14	5	6	5	3	3	gouge on fractures
242	389.23	392.28	3.05	3.08	101	3.08	101	15	5	6	5	3	3	gouge on fractures
242	392.28	395.33	3.05	3.35	110	3.02	99	13	5	6	13	2	2	clay on fractures
242	395.33	398.07	2.74	2.60	95	2.52	92	15	5	6	4	2	2	clay on fractures
243	42.67	44.81	2.14	0.45	21	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	44.81	50.90	6.09	0.29	5	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	50.90	53.45	2.55	0.05	2	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	53.45	56.39	2.94	0.04	1	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	56.39	57.91	1.52	0.01	1	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	57.91	60.05	2.14	0.05	2	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	60.05	63.09	3.04	0.05	2	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	63.09	66.14	3.05	0.03	1	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	66.14	69.19	3.05	0.12	4	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	69.19	71.02	1.83	0.13	7	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	71.02	74.37	3.35	0.15	4	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	74.37	76.20	1.83	0.38	21	0.00	0	3	3	2	50			rubble zone, pebble and gravel
243	76.20	77.72	1.52	0.10	7	0.00	0	2	3	2	50			rubble zone, pebble and gravel
243	77.72	78.64	0.92	0.45	49	0.00	0	3	3	2	25			rubble zone, pebble and gravel
243	78.64	79.25	0.61	0.27	44	0.00	0	3	3	2	25			rubble zone, pebble and gravel
243	79.25	79.55	0.30	0.07	23	0.00	0	3	3	2	15			rubble zone, pebble and gravel
243	79.55	81.38	1.83	0.97	53	0.00	0	3	3	2	50	5	2	rubble zone, pebble and gravel
243	81.38	84.43	3.05	0.10	3	0.00	0	3	3	3	10	5	2	rubble zone, pebble and gravel
243	84.43	86.26	1.83	0.11	6	0.00	0	3	3	3	10	5	2	rubble zone, pebble and gravel
243	86.26	89.92	3.66	0.84	23	0.00	0	3	3	3	20	5	2	rubble zone, pebble and gravel
243	89.92	91.14	1.22	0.62	51	0.00	0	3	3	3	15	5	2	rubble zone, pebble and gravel
243	91.14	92.96	1.82	0.26	14	0.00	0	3	3	3	15	5	2	rubble zone, pebble and gravel
243	92.96	93.88	0.92	0.57	62	0.19	21	3	3	4	15	2	2	rubble zone, pebble and gravel
243	93.88	95.10	1.22	0.42	34	0.00	0	4	3	4	15	2	2	rubble zone, pebble and gravel
243	95.10	97.84	2.74	0.56	20	0.00	0	4	3	4	20	5	3	rubble zone, pebble and gravel
243	97.84	98.45	0.61	0.51	84	0.11	18	6	3	4	20	5	2	rubble zone, pebble and gravel
243	98.45	99.36	0.91	0.75	82	0.21	23	6	3	4	20	5	2	rubble zone, pebble and gravel
243	99.36	99.97	0.61	0.35	57	0.00	0	6	3	4	20	5	2	rubble zone, pebble and gravel
243	99.97	101.19	1.22	0.36	30	0.14	11	7	3	5	10	2	2	rubble zone, pebble and gravel
243	101.19	102.72	1.53	0.27	18	0.00	0	6	3	5	15	5	2	rubble zone, pebble and gravel

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
243	102.72	104.24	1.52	0.46	30	0.16	11	8	3	5	15	5	3 rubble zone, pebble and gravel	
243	104.24	105.77	1.53	1.29	84	0.00	0	5	3	4	30	5	3 broken up core	
243	105.77	106.98	1.21	0.62	51	0.00	0	5	3	4	25	5	3 broken up core, pyrite on fractures	
243	106.98	109.42	2.44	1.13	46	0.12	5	5	3	4	25	5	3 broken up core	
243	109.42	110.03	0.61	0.61	100	0.00	0	7	3	4	15	2	2 broken up core, pyrite on fractures	
243	110.03	111.86	1.83	0.56	31	0.14	8	7	3	4	12	2	2 broken up core, pyrite on fractures	
243	111.86	114.91	3.05	0.06	2	0.00	0	3	3	5	10	5	3 broken up core, pyrite on fractures	
243	114.91	115.52	0.61	0.17	28	0.00	0	5	3	5	10	5	2 broken up core, pyrite on fractures	
243	115.52	116.13	0.61	0.19	31	0.00	0	4	3	5	20	5	2 broken up core, pyrite on fractures	
243	116.13	117.04	0.91	0.33	36	0.00	0	7	3	5	8	2	2 broken up core, pyrite on fractures	
243	117.04	117.65	0.61	0.31	51	0.20	33	8	3	6	15	5	2 broken up core, pyrite on fractures	
243	117.65	118.87	1.22	0.91	75	0.56	46	10	3	6	15	1	2 5 % broken core, pyrite on fractures	
243	118.87	121.01	2.14	1.94	91	1.94	91	15	3	6	4	1	2	
243	121.01	124.05	3.04	3.06	101	2.94	97	13	3	6	15	1	3 minor gouge on fractures	
243	124.05	127.10	3.05	3.05	100	1.92	63	13	3	6	15	1	2 minor gouge on fractures	
243	127.10	130.15	3.05	3.05	100	1.70	56	13	3	6	15	1	3 10% broken core with gouge	
243	130.15	133.20	3.05	3.11	102	3.00	98	14	4	6	10	1	2	
243	133.20	136.25	3.05	3.06	100	3.06	100	15	4	6	4	1	2	
243	136.25	138.07	1.82	1.62	89	1.30	71	12	4	6	10	2	2 9 cm broken up core	
243	138.07	141.12	3.05	2.84	93	2.43	80	13	4	6	12	2	3	
243	141.12	144.17	3.05	3.14	103	2.84	93	14	3	6	10	1	3 gouge on fractures	
243	144.17	146.91	2.74	2.70	99	2.19	80	12	3	6	15	1	3 gouge on fractures	
243	146.91	148.44	1.53	1.60	105	0.94	61	13	3	6	6	1	2 pyrite on fractures	
243	148.44	149.35	0.91	0.76	84	0.51	56	12	3	6	5	1	2 pyrite on fractures	
243	149.35	151.49	2.14	1.81	85	1.52	71	12	3	6	11	2	3 gouge on fractures	
243	151.49	154.53	3.04	2.97	98	2.78	91	14	3	6	5	2	2	
243	154.53	156.97	2.44	1.91	78	0.80	33	12	3	6	12	2	3 gouge on fractures	
243	156.97	158.80	1.83	1.51	83	0.54	30	9	3	6	20	5	3 10% broken core with gouge	
243	158.80	160.63	1.83	1.90	104	1.58	86	12	4	6	10	2	3 10 cm gouge, H=1,2	
243	160.63	163.68	3.05	3.05	100	1.95	64	14	3	5	8	2	3 15 cm H=0, 1, gouge on fractures	
243	163.68	166.73	3.05	3.05	100	1.50	49	14	3	6	10	5	3 1.24m fault gouge H=1,2	
243	166.73	169.77	3.04	3.11	102	3.00	99	14	4	6	7	1	3 gypsum on fractures	
243	169.77	172.82	3.05	3.02	99	3.02	99	15	3	6	3	1	3 gypsum on fractures	
243	172.82	175.87	3.05	3.00	98	3.00	98	15	3	6	2	1	3 gypsum on fractures	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
243	175.87	178.92	3.05	3.05	100	3.05	100	15	3	6	5	1	3 gypsum on fractures
243	178.92	181.97	3.05	3.03	99	3.03	99	15	3	6	1	1	3 gypsum on fractures
243	181.97	185.01	3.04	3.07	101	3.07	101	15	3	6	3	1	3 gypsum on fractures
243	185.01	188.06	3.05	3.03	99	3.03	99	15	3	6	1	1	3 gypsum on fractures
243	188.06	191.11	3.05	3.05	100	2.99	98	15	3	6	4	1	3 gypsum on fractures
243	191.11	194.16	3.05	3.05	100	2.92	96	15	3	6	2	1	3 gypsum on fractures
243	194.16	197.21	3.05	2.97	97	2.97	97	15	3	6	4	1	3 gypsum on fractures, + gouge
243	197.21	200.25	3.04	3.04	100	3.04	100	15	3	6	2	1	2
243	200.25	203.30	3.05	3.05	100	3.00	98	15	3	6	3	2	3 5 cm gouge H=1,2
243	203.30	206.35	3.05	3.01	99	3.01	99	15	3	6			
243	206.35	209.40	3.05	3.05	100	3.05	100	15	3	6	1	1	2
243	209.40	212.45	3.05	3.05	100	3.05	100	15	3	6	2	3	2
243	212.45	213.66	1.21	1.21	100	0.83	69	11	3	6	8	3	3
243	213.66	216.71	3.05	2.92	96	2.74	90	14	3	6	7	3	3
243	216.71	219.76	3.05	3.15	103	2.82	92	15	3	6	4	2	3
243	219.76	222.81	3.05	3.05	100	3.05	100	15	3	6	0		
243	222.81	225.86	3.05	3.10	102	2.72	89	14	3	6	6	1	2
243	225.86	228.30	2.44	2.65	109	2.21	91	14	3	6	9	2	2 ends in 5 cm rubble
243	228.30	230.73	2.43	2.35	97	2.00	82	14	3	6	7	1	2 broken carbonate vein
243	230.73	233.78	3.05	3.05	100	2.56	84	14	3	6	9	2	2
243	233.78	236.83	3.05	2.90	95	2.90	95	14	3	6	6	1	2
243	236.83	239.88	3.05	3.00	98	3.00	98	15	3	6	4	1	2
243	239.88	242.93	3.05	3.05	100	3.05	100	15	3	6	5	2	2
243	242.93	244.14	1.21	1.06	88	1.06	88	14	3	6	3	5	4
243	244.14	247.19	3.05	3.00	98	2.26	74	12	3	5	16	1	1 sheared section
243	247.19	249.02	1.83	2.15	117	1.55	85	12	3	6	13	2	1
243	249.02	252.07	3.05	2.70	89	1.70	56	11	3	6	18	1	2
243	252.07	255.12	3.05	3.10	102	2.90	95	14	3	6	7	1	2
243	255.12	258.17	3.05	3.10	102	3.10	102	15	3	6	5	3	2
243	258.17	261.21	3.04	3.10	102	3.10	102	15	3	6	3	5	4
243	261.21	264.26	3.05	3.10	102	2.70	89	13	3	6	13	1	2
243	264.26	267.31	3.05	3.20	105	2.36	77	13	3	6	15	1	2
243	267.31	270.36	3.05	3.05	100	3.05	100	14	3	6	8	1	2
243	270.36	273.41	3.05	3.00	98	2.85	93	13	3	6	11	1	2 10 cm gouge

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
243	273.41	276.45	3.04	3.10	102	3.10	102	14	3	6	6	3	2	
243	276.45	279.50	3.05	3.10	102	3.10	102	15	3	6	5	1	1	
243	279.50	282.55	3.05	2.98	98	2.98	98	15	3	6	4	3	3	
243	282.55	285.60	3.05	3.10	102	3.10	102	15	3	6	3	1	2	
243	285.60	288.65	3.05	3.10	102	3.10	102	15	3	6	3	3	2	
243	288.65	291.69	3.04	3.02	99	3.02	99	15	3	6	3	3	4	
243	291.69	294.74	3.05	3.05	100	3.05	100	15	3	6	3	3	2	
243	294.74	297.79	3.05	3.02	99	2.90	95	15	3	6	4	3	2	
243	297.79	300.84	3.05	3.00	98	2.89	95	14	3	6	6	1	2	
243	300.84	303.89	3.05	3.10	102	2.91	95	15	3	6	4	1	1	
243	303.89	306.63	2.74	2.60	95	2.60	95	15	3	6	2	2	2	
243	306.63	309.68	3.05	3.05	100	2.99	98	15	3	6	2	3	3	
243	309.68	312.72	3.04	3.10	102	3.10	102	15	3	6	0			
243	312.72	315.77	3.05	3.05	100	2.70	89	14	3	6	7	3	2	
243	315.77	316.08	0.31	0.39	126	0.39	126	15	3	6	0			
243	316.08	319.13	3.05	2.90	95	2.90	95	14	3	6	7	3	2	
243	319.13	322.17	3.04	3.04	100	2.92	96	15	3	6	4	3	2	
243	322.17	325.22	3.05	2.95	97	2.64	87	14	3	6	9	2	2	
243	325.22	328.27	3.05	3.00	98	3.00	98	15	3	6	5	2	1	
243	328.27	331.32	3.05	3.10	102	2.82	92	14	3	6	7	1	1	
243	331.32	334.37	3.05	3.10	102	2.24	73	13	3	6	13	3		2 fracture parallel to c.a.
243	334.37	337.41	3.04	2.90	95	2.90	95	15	3	6	4	3	2	
243	337.41	340.16	2.75	2.57	93	2.10	76	12	3	6	13	2	1	
244	4.87	8.23	3.36	1.57	47	0.21	6	9	4	5	16	1		1 trace limonite-gouge in broken core
244	8.23	11.28	3.05	2.95	97	2.15	70	14	4	6	7	1		1 gouge on slips
244	11.28	14.33	3.05	3.05	100	2.55	84	15	4	6	4	1		1 gouge on slips
244	14.33	17.37	3.04	3.04	100	2.47	81	15	4	6	5	1	1	
244	17.37	20.42	3.05	2.88	94	2.53	83	15	4	6	5	1	1	
244	20.42	23.47	3.05	3.00	98	2.86	94	15	4	6	4	1		1 10 cm moderately broken core
244	23.47	26.52	3.05	3.02	99	3.02	99	15	4	6	3	1	1	
244	26.52	29.57	3.05	3.05	100	2.55	84	14	4	6	9	1		1 30 cm weakly broken core
244	29.57	32.61	3.04	2.90	95	2.39	79	14	4	6	8	1	1	
244	32.61	35.66	3.05	3.03	99	2.83	93	15	4	6	5	1	1	
244	35.66	38.71	3.05	3.00	98	2.80	92	15	4	6	4	1	1	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)			Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.	%							
244	38.71	41.76	3.05	3.02	99	2.82	92	14	4	6	7	1	1	1 gouge on slips and in broken core
244	41.76	44.81	3.05	2.69	88	1.85	61	12	4	6	14	1	1	1 gouge on slips and local cemented gouge
244	44.81	47.85	3.04	2.97	98	2.69	88	14	4	6	6	1	1	1 gouge on slips
244	47.85	50.90	3.05	2.87	94	2.83	93	15	4	6	3	1	1	
244	50.90	53.95	3.05	3.02	99	2.98	98	15	4	6	4	1	1	
244	53.95	57.00	3.05	3.89	128	3.33	109	14	4	6	10	1	1	1 gouge in broken core and on slips
244	57.00	60.05	3.05	1.51	50	1.31	43	12	4	6	8	1	1	1 gouge on slips
244	60.05	63.09	3.04	3.17	104	2.78	91	14	4	6	6	1	1	1 local cemented gouge
244	63.09	66.14	3.05	3.07	101	2.82	92	15	4	6	4	1	1	1 gouge on slips
244	66.14	69.19	3.05	3.01	99	3.01	99	15	4	6	4	1	1	1 gouge on slips
244	69.19	72.24	3.05	3.00	98	3.00	98	15	4	6	4	1	1	
244	72.24	75.29	3.05	3.02	99	2.96	97	15	4	6	3	1	2	
244	75.29	78.33	3.04	3.01	99	3.01	99	15	4	6	4	3	3	2 low angle breaks
244	78.33	81.38	3.05	3.00	98	3.00	98	15	4	6	4	1	1	1 dyke between 79.30-81.54 m
244	81.38	84.43	3.05	2.93	96	2.93	96	14	4	6	5	1	1	1 trace gouge
244	84.43	87.48	3.05	2.99	98	2.99	98	15	4	6	3	1	1	1 dyke starts at 84.57 m
244	87.48	90.53	3.05	2.90	95	2.80	92	15	4	6	3	1	1	1 gouge on slips
244	90.53	93.57	3.04	2.88	95	2.88	95	15	4	6	4	1	1	
244	93.57	96.62	3.05	2.95	97	2.63	86	14	4	6	5	1	1	1 gouge on slips
244	96.62	99.67	3.05	2.65	87	2.49	82	14	4	6	7	1	1	1 gouge on slips
244	99.67	102.72	3.05	2.84	93	2.18	71	14	4	6	6	1	1	1 dyke ends at 100.22 m
244	102.72	105.77	3.05	2.95	97	2.74	90	13	4	6	10	1	1	1 trace gouge
244	105.77	108.81	3.04	2.83	93	2.59	85	14	4	6	8	1	1	
244	108.81	111.86	3.05	2.92	96	2.82	92	14	4	6	7	1	3	
244	111.86	114.91	3.05	2.92	96	2.14	70	13	4	6	11	1	1	1 gouge on slips and in broken core
244	114.91	117.96	3.05	2.44	80	1.67	55	13	4	6	16	1	1	1 moderately- strongly broken core with gouge
244	117.96	121.00	3.04	2.02	66	0.20	7	10	4	6	20	1	1	1 moderately-strongly broken core throughout
244	121.00	124.05	3.05	2.59	85	2.16	71	13	4	6	11	1	1	1 local moderate-strong broken core with gouge
244	124.05	127.10	3.05	2.84	93	1.42	47	13	4	6	14	1	1	1 gouge on slips/breccia starts at 126.1 m
244	127.10	130.15	3.05	3.10	102	3.10	102	15	4	6	3	1	1	1 gouge on slips
244	130.15	131.98	1.83	1.80	98	1.62	89	15	4	6	3	1	1	1 gouge on slips
244	131.98	134.72	2.74	2.83	103	2.83	103	15	4	6	1	3	2	
244	134.72	136.25	1.53	1.35	88	1.35	88	15	4	6	1	3	2	
244	136.25	138.99	2.74	2.59	95	2.59	95	15	4	6	1	3	2	

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To	Lgth	m.	%	m.							
244	138.99	142.04	3.05	2.93	96	2.88	94	15	4	6	3	1	1 gouge on slips
244	142.04	145.08	3.04	3.01	99	3.01	99	15	4	6	1	3	2
244	145.08	148.13	3.05	3.03	99	3.01	99	15	4	6	2	1	1 gouge in 5 cm of broken core
244	148.13	151.49	3.36	3.31	99	3.07	91	14	4	6	6	1	1 gouge in broken core and on slips
244	151.49	154.53	3.04	2.87	94	2.28	75	15	4	6	5	1	1 breccia ends and dyke starts at 153.23m
244	154.53	157.58	3.05	3.01	99	2.65	87	14	4	6	6	1	1
244	157.58	160.63	3.05	3.08	101	2.72	89	14	4	6	10	1	1 dyke ends at 158.02
244	160.63	163.68	3.05	3.05	100	3.05	100	15	4	6	2	1	1 dyke between 158.70-159.50 m
244	163.68	166.73	3.05	3.07	101	3.07	101	15	4	6	2	2	1
244	166.73	169.77	3.04	2.99	98	2.58	85	15	4	6	5	2	1
244	169.77	172.82	3.05	2.96	97	2.96	97	15	4	6	3	1	1 trace gouge
244	172.82	175.87	3.05	3.11	102	2.59	85	14	4	6	8	1	1 trace gouge
244	175.87	178.92	3.05	2.60	85	2.42	79	14	4	6	5	5	3 trace gouge
244	178.92	181.97	3.05	2.90	95	2.70	89	14	4	6	6	1	1 gouge on slips
244	181.97	185.01	3.04	3.09	102	3.04	100	15	4	6	3	1	1
244	185.01	188.06	3.05	2.93	96	2.30	75	14	4	6	6	1	1 gouge on slips
244	188.06	191.11	3.05	3.11	102	2.88	94	15	4	6	4	1	1
244	191.11	194.16	3.05	2.94	96	1.99	65	13	4	6	11	3	3
244	194.16	197.21	3.05	3.05	100	2.78	91	14	4	6	8	1	1 gouge on slip
244	197.21	200.25	3.04	3.01	99	3.01	99	15	4	6	3	1	1
244	200.25	203.30	3.05	3.02	99	2.73	90	15	4	6	3	1	1 trace gouge
244	203.30	206.35	3.05	2.86	94	2.86	94	15	4	6	4	1	1 8mm gouge on slip
244	206.35	209.40	3.05	3.08	101	2.86	94	14	4	6	7	1	1 gouge on slips
244	209.40	212.45	3.05	3.01	99	2.65	87	15	4	6	5	1	1 gouge on slips
244	212.45	215.49	3.04	3.04	100	2.02	66	13	4	6	12	1	1 gouge on slips
244	215.49	218.54	3.05	2.93	96	2.14	70	13	4	6	10	1	1 gouge on slips
244	218.54	221.59	3.05	2.89	95	2.08	68	14	4	6	8	1	1 up to 5 mm gouge on slips
244	221.59	224.64	3.05	2.84	93	2.38	78	13	4	6	9	1	1 32 cm cemented gouge
244	224.64	227.69	3.05	2.80	92	2.51	82	13	4	6	12	1	1 50 cm moderately broken core with gouge
244	227.69	230.73	3.04	3.01	99	1.88	62	13	4	6	15	1	1 gouge on slips
244	230.73	233.78	3.05	2.95	97	2.83	93	14	4	6	7	1	1
244	233.78	236.83	3.05	2.97	97	2.59	85	14	4	6	8	1	1 gouge on slips
244	236.83	239.88	3.05	2.88	94	2.02	66	12	4	6	16	1	1 70 cm moderately broken core
244	239.88	242.93	3.05	3.02	99	2.98	98	15	4	6	3	1	1

RED - CHRIS PROPERTY

1995 Diamond Drilling Program - Rock Quality Data

DDH No.	Interval (m)		Lgth	Recovery		RQD		Brkg	Hard	Wthr	XJnt	Shape	Rgh	Comments
	From	To		m.	%	m.	%							
244	242.93	245.97	3.04	2.83	93	2.53	83	14	4	6	9	3	3	
244	245.97	249.02	3.05	2.82	92	1.52	50	13	4	6	14	1	1	1 gouge on most slips
244	249.02	252.07	3.05	2.75	90	1.62	53	13	4	6	11	1	1	1 gouge on most slips
244	252.07	255.12	3.05	2.81	92	2.69	88	13	4	6	10	1	1	1 two 5 cm cemented gouge
244	255.12	258.17	3.05	2.75	90	2.11	69	13	4	6	10	1	1	1 gouge on most slips
244	258.17	261.21	3.04	2.90	95	2.34	77	13	3	6	12	1	1	1 fault zone starts at 258.85 m
244	261.21	264.26	3.05	3.11	102	2.99	98	14	3	6	8	1	1	1 100% cemented gouge with fragments
244	264.26	267.31	3.05	2.82	92	2.73	90	14	3	6	6	1	1	1 60% cemented gouge
244	267.31	270.36	3.05	2.93	96	2.62	86	14	4	6	8	1	1	1 fault zone ends at 268.31 m
244	270.36	273.41	3.05	3.08	101	2.43	80	12	4	6	17	1	1	1 trace gouge on slips
244	273.41	276.45	3.04	2.95	97	2.44	80	13	3	6	10	1	1	1 gouge on slips/30% cemented gouge
244	276.45	279.50	3.05	2.92	96	2.04	67	13	3	6	12	1	1	1 gouge on slips/30% cemented gouge
244	279.50	282.55	3.05	2.92	96	2.04	67	14	3	6	6	1	1	1 gouge on slips/30% cemented gouge
244	282.55	285.29	2.74	2.56	93	2.30	84	14	3	6	7	1	1	1 local gouge
244	285.29	288.34	3.05	3.05	100	2.67	88	14	3	6	7	1	1	1 50% cemented gouge with fragments
244	288.34	291.39	3.05	3.05	100	2.59	85	14	3	6	8	1	1	1 60% cemented gouge with fragments
244	291.39	294.44	3.05	2.90	95	2.68	88	15	3	6	5	1	1	1 15% cemented gouge
244	294.44	297.48	3.04	2.83	93	2.42	80	14	3	6	6	1	1	1 local cemented gouge
244	297.48	300.53	3.05	2.79	91	2.05	67	13	3	6	13	1	1	1 30 cm strongly broken core/50% gouge