GEOLOGICAL, DRILLING and MAGNETOMETER ASSESSMENT REPORT on the IRON ROSS PROJECT

(TENURE #389167, 389168,389169)
MX-8-216
SAYWARD AREA, ELK CREEK
NANAIMO MINING DIVISION
N.T.S. 92K/05W (92K.031)
LONGITUDE 125°58'20"/ LATITUDE 50°18'42"N

For

Hillsborough Resources Limited
#925-1200 West 73rd Ave.
Vancouver, B.C.
V6P 6G5
Phone: 604-684-9288/Fax: 604-684-3178

By

J. T. Shearer, M.Sc., P.Geo.
#5-2330 Tyner St.
Port Coquitlam, B.C.
V3C 2Z1
Phone: 604-970-6402/Fax: 604-944-6102
Consulting Geologist
Quarry Supervisor #98-3550

27,438

January 31, 2004

Fieldwork between October 20,2002 and December 15, 2002 and May 15, 2003 and September 30, 2003

TABLE of CONTENTS

LIST of ILLUSTRATIONS and TABLES

TABLES

SUMMARY

1) The Ross, Iron Ross and Iron Bethea Claims (totalling 22 units) cover 4 main magnetite showings. The Iron Mike and Iron Joe (2 units) cover past producer Iron Mike.

2) The area is 6 km from tidewater on Kelsey Bay at the town of Sayward and about 52 km north of Menzies Bay.

3) The Iron Ross and Iron Bethea magnetite showings are a short distance (400m) west of the Iron Mike past producer.

4) Initial ore reserves at the Iron Mike mine were approximately 700,000 tons to 1.15 million tons @ 62% Fe (Atherton, 1983). Mining took place in 1965-1966. Drilling by 1965 delineated reserves of 688,277 tonnes proven and 266,983 tonnes probable grading 43.5% iron (Hill & Stark, 1965). Production by Orecan Mines Ltd. in 1965-1966 totalled 168,735 tonnes (82,862 tonnes of 62.25% concentrate). A further 29,937 tonnes of concentrate was shipped in 1969.

5) Extensive geological mapping, airborne and ground magnetometer work was completed by Dickenson Mines Limited in 1983. Four large ground magnetic anomalies coinciding with massive magnetite outcrops were identified by the 1983 work by Dickenson Mines Ltd.

6) The claims are underlain by garnet-epidote-magnetite skarn, which occurs along the contact between underlying Upper Triassic Karmutsen Formation volcanics and overlying Upper Triassic Quatsino Formation Limestone. Drilling in 2002 confirmed the presence of magnetite and skarn zone also totally within the limestone.

7) The largest 1983 magnetic anomaly is called the Iron Ross (formerly the Iron Dick). As defined by the 5000 gamma fluxgate contour its dimensions are 120m by 60m. Massive magnetite assayed (in 1983) 64.15% soluble Fe. A small massive magnetite showing 500m northwest of the anomaly was sampled in 1997 using a saw to cut a channel sample (now called the Iron Steve Zone).

8) Trenching in February 2002 has exposed the massive magnetite outcrop on the Iron Ross Zone over a length of 60m and thickness of at least 4m. Thirteen diamond drill holes were drilled at the Iron Ross Zone prior to 1965. However, the results of this drilling is not currently available.

9) Specific Gravity measurements average 5.1 with the following assay results

Al_2O_3	CaO	Fe_2O_3	K_2O	MgO	MnO	Na_2O	P_2O_5	SiO_2	Zn	V	S
0.46	0.47	91.00	0.79	0.16	0.21	0.29	0.05	2.95	330	14	<0.01

10) 400m south of the Iron Ross is the Iron Bethea (formerly the Iron Mac) anomaly measuring 60m by 40m indicates a shallow southwest dip. Massive magnetite assayed (in 1983) 63.1% soluble Fe. Eight diamond drill holes were completed at the Iron Bethea Zone prior to 1965. However, the results of this drilling is not currently available.

11) The Iron Herb I and Iron Herb II magnetometer anomalies occur 750m north of the Iron Ross showing. Assays for skarn and magnetite at the poorly exposed Iron Herb II (1983) is 26.0% soluble Fe.

12) Bulk samples of 150 tonnes was excavated in November 2002 and continuing geological mapping completed.

13) Trenching was completed in February and October 2002 along line 11W (65m) and along 10+70W (75m) within gently dipping Quatsino limestone. The massive magnetite outcrop was stripped along a width of 65m.

14) A small bulk sample was excavated, trucked to Port Hardy and crushed to 7/8" minus. Various tests were conducted by OCL Industries for sandblasting purposes and by Ocean Cement for super heavy concrete.

15) Percussion drilling in October 2002 on the Iron Ross totalled 970 feet (295.66m) in 17 holes mainly around the Iron Ross surface showing and 2002 trenching.

16) Assays indicate zinc is uniformly low, likewise tungsten, mercury and cobalt. Lead, copper and arsenic are geochemically elevated in some samples especially the lower skarn zones. Sulphur is uniformly low. The gold shows more variation but the highest is only 0.5 ppm in hole 17.

The XRF major elements shows some variation in the lower intervals logged as magnetite. The silica is elevated and this could be a function of sample collection. However, the limestone samples also have relatively higher SiO_2.

17) A ground magnetometer survey was completed in the summer of 2003 on well cut out lines totalling 12.0 line kilometres.

18) The Iron Steve Zone exhibits an intense, well defined, ground magnetometer anomaly approximately 30m wide by at least 150m long. Much of the anomaly has a 20,000 gamma contrast. The exact width is poorly constrained due to fewer lines to the south and the deposit appears to swing to the northwest. <u>At least 25 drillholes are recommended</u>.

19) The Iron Mike produced a limited tonnage in 1965-1966. The present survey indicates a lens of magnetite dipping to the southwest. A decline was collared on this lens but was not economically feasible. Old drill data shows a considerable zone of magnetite, which would only be amenable to underground mining methods. No drilling recommended.

20) A small magnetite zone is suggested by higher readings on Lines 18 and 20 between the West Pit and the Main Pit. <u>Three holes are recommended</u>.

21) A low order magnetic anomaly is present to the west of the West Pit. <u>Two to four drill holes are warranted</u>.

22) The area between the Main Pit and the Iron Bethea Zone has a small anomalous zone near the south side of a hill. Prospecting and mapping are recommended.

23) The Iron Herb I Zone is a strong, continuous magnetic high extending a distance of at least 290 metres in length. Several drill holes are recommended as constrained by road access. Some new road and excavator trenching will need to be built to access the eastern part of the anomaly.

24) The Iron Herb II Zone is outlined by a magnetic anomaly about 120 metres long. At least four drill holes should be positioned along the main road and north branch to test the subsurface of the zone near Lines 39 and 61.

25) Line 41 is situated on the trench and drill fence on the south side of the Iron Ross deposit. From percussion drill data, the Iron Ross deposit is covered by 10 to 15 metres of limestone in the vicinity of 4000 to 7000 gamma total field magnetic response. Four holes are recommended to test for south continuations indicated on Line 42.

26) An area of 4000 gamma readings is present on the west side of Lines 45 and 46 in steeper terrain. Detail prospecting is recommended.

27) Iron Bethea is misplotted. The Iron Bethea deposit is indicated on Line 11, Line 53 and Line 52. The zone covers an area 60 to 90 metres long by 20 to 40 metres wide. Road extension of 190m and drilling is recommended.

28) The lines southeast of the Iron Bethea deposit (Lines 55-58) all exhibit low background values suggesting low magnetite potential.

29) Further percussion drilling was completed in the fall of 2003 on the Iron Steve zone and farther east for a total of 31 holes of 1403 feet (427.64m) of drilling.

30) Hillsborough Resources was successful in excavating a high grade magnetite bulk sample of 150 tonnes, which was used in a super-heavy concrete application in a Vancouver construction project.

31) A follow-up diamond drill program is recommended for 2004, as outlined in this report, to explore for magnetite mineralization and define geological structure.

Respectfully submitted,

J. T. Shearer, M.Sc., P.Geo.
January 31, 2004



HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS LOCATION MAP

NTS 92K/05W	September 2001	SCALE as shown
WORK BY J. T. Shearer, M.Sc., P. Geo	FIGURE 1	

INTRODUCTION

The Iron Ross Project is approximately 6 km from tidewater, west of the Community of Sayward, B.C. The main showings of massive magnetite are 400m west of the Iron Mike Mine, which operated in 1965-1966, producing from 168,735 tonnes about 112,799 tonnes of 62.26% iron concentrate.

Extensive airborne and ground magnetometer surveys were completed by 1983 by Dickenson Mines Limited, which outline 4 additional large massive to skarnified magnetite zones to the west of the Iron Mike main pit.

Magnetite concentrates from the Iron Mike were apparently shipped (by ocean-going vessel) out of Menzies Bay 52.2 km to the south. However, as part of a major reorganization of their island operations, the large dryland Log sort operated in Sayward by Weyerhaeuser is scheduled to be phased out during the near future, which may open up opportunities to barge out of Kelsey Bay. Most Weyerhaeuser logs will now go out of Menzies Bay. The Eve River log sort to the north has already been shut down.

Much of the magnetite produced in British Columbia at the present time is from a sophisticated reprocessing of tailings (Craigmont) or small time hit and miss reprocessing coarse waste dumps (Texada Island and elsewhere). Possible markets for magnetite are: heavy aggregate for high-density concrete, heavy media for coal washing, sandblasting abrasives, high-density filter media and radiation shielding aggregates. Two major construction projects that may start in early 2002 are the expansion of the sub-atomic research TRIUMF facility at the University of British Columbia and the Sumas-Duncan Natural Gas Pipeline (for pipe anchors) by BC Hydro and Williams Pipeline Company. There may also be increasing application to special designed heavy concrete foundations in areas of high hydrostatic ground pressure in areas like Richmond, B.C.

An alternative market may be as a raw material for cement plant use. The current supply from Anyox slag assays 36.4% SiO_2, 5.1% Al_2O_3 but only 45% Fe_2O_3. Anyox slag also assays typically about 3% SO_3 and has a relatively high Bond work index of >23. Bond work index of 10.7 and 15.0 have been obtained for magnetite from other properties on Vancouver Island. The average specific gravity for 3 samples from the Iron Ross Zone is 5.1.

Specifications for sandblasting are minus 20 mesh plus 100 mesh with most of the size distribution in the 50 to 70 mesh fractions. Arsenic should be below 50 ppm for total metals.

Product constraints for use as heavy media coal washing include (1) greater than 4.7 specific gravity, (2) greater than 95% magnetics, (3) not less than 90% passing 235 mesh (45 microns) and (4) not more than 30% passing 10 microns. Testing was conducted in 2003 to produce heavy media concentrate for use in marketing and market evaluation.



HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS ACCESS MAP

NTS 92K/05W	September 2001	SCALE 1:125,000
WORK BY J. T. Shearer, M.Sc., P. Geo	FIGURE 2	



HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS ACCESS MAP

NTS 92K/05W	September 2001	SCALE 1:125,000
WORK BY J. T. Shearer, M.Sc., P. Geo		FIGURE 2

LOCATION and ACCESS

The Iron Ross Project is located about 6 km from tidewater at the town of Sayward B.C. Access is currently from the Elk Creek Mainline logging road, which crosses the Island Highway (Hwy 19) just east of the Keta Lake rest stop.

The magnetite showing on the Iron Ross (formerly the Iron Dick) is at 5.13 km along the Elk Creek Mainline from the Highway.

The area is within Tree Farm License #39 owned by Weyerhaeuser (North Island Timberlands, Block 2). Some of the logging in the Sayward Area is done on contract to Weyerhaeuser by Dyer Logging, Superintendent: Bruce Flower, phone 250-282-3381.

Formerly, the Iron Mike Mine area was accessed by the White River road, Branch A and then along the Branch A-32. However, the Bridge on A-30 and 4-32 over Tlowlis (lower Elk) Creek has been recently removed but recent plans call for this bridge to be re-installed and road construction built to access stands of old growth around the Iron Bethea area.

The claims have a variety of second growth and old growth patches of forest. Some of the second growth dates to the 1950's and 1960's along A-32 road. The second growth on the Elk Creek Mainline appears to be in the late 1980's and some harvesting is still taking place along A-30 and Elk Creek 500 branch. Elevations range from 800 feet on the east to 3000 feet on the west.



HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS
TRIM MAP

NTS 92K/05W	September 2001	SCALE 1:20,000

WORK BY J. T. Shearer, M.Sc., P. Geo. | Figure 3

CLAIM STATUS

The Iron Ross (Sayward) Project consists of 5 claims as listed in Table I and shown on Figure 3.

TABLE I

List of Claims

Claim Name	Tenure #	Size	Units	Date Located	Current Anniversary Date*	Owner
Ross	389167	4N4W	20	August 30, 2001	April 1, 2007	J. T. Shearer
Iron Bethea	389168	2 post	1	August 29, 2001	April 1, 2007	J. T. Shearer
Iron Ross	389169	2 post	1	August 29, 2001	April 1, 2007	J. T. Shearer
Iron Joe	231489	2 post	1	March 9, 2002 1958	March 9, 2007	Hartt et.al.
Iron Mike	231490	2 post	1	March 9, 2002 1958	March 9, 2007	Hartt et.al.
			Total 24 Units			

*by application of assessment work documented in this report.

Mineral title is acquired in British Columbia via the Mineral Act and regulations, which require approved assessment work to be filed each year in the amount of $100 per unit per year for the first three years and then $200 per unit per year thereafter to keep the claim in good standing.

Under the present status of mineral claims in British Columbia, the consideration of industrial minerals requires careful designation of the products end use. An industrial mineral is a rock or naturally occurring substance that can be mined and processed for its unique qualities and used for industrial purposes (as defined in the *Mineral Tenure Act*). It does not include "Quarry Resources". Quarry Resources includes earth, soil, marl, peat, sand and gravel, and rock, rip-rap and stone products that are used for construction purposes (as defined in the *Land Act*). Construction means the use of rock or other natural substances for roads, buildings, berms, breakwaters, runways, rip-rap and fills and includes crushed rock. Dimension stone means any rock or stone product that is cut or split on two or more sides, but does not include crushed rock.

The northeast part of the Ross Claim is taken up by 2-post claims Iron Mike (231490) and Iron Joe (231489). These two claims are owned by Margret Birkenhead 33.3334%, Eileen Hartt 33.3322%, and Audrey Larsen 33.3334% and presently are also under option to Hillsborough as of 2003.

In August 2002 the Iron Ross claims were optioned to Hillsborough Resources Limited.



HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS
CLAIM MAP

NTS 92K/05W	September 2001	SCALE 1:31,680
WORK BY J. T. Shearer, M.Sc., P. Geo	FIGURE 4	

HISTORY

The mining history of the area is closely tied to the development of the Iron Mike mine. A summary of the main events is as follows:

1959 - Iron ore discovered by R. Hartt.

1960 - Property optioned to Marwell Construction from R. Hartt.
- 19 drill holes for 1924 feet (Ex diameter)
- 13 were drilled on Iron Mike claim.
- Dip needle survey over Iron Mike (Main Zone) deposit and Iron Mac, Iron Dick and West Zone deposits (all on Ross Claim)

1961 - Hartt & Associates diamond drilling (Ex diameter) (24 drill holes of 2100 feet) and prospecting of claim.

1963 - Inter-Can Development Ltd. optioned the property on a ten year renewable lease royalty agreement.
- Stripping and diamond drilling began, claims assigned to Orecan Mine Ltd.

1964 - 5,000 feet diamond drilling by Orecan.
-Stripping in preparation for open pit mining.
- Reserves 700,000 tons to 1.15 million tons at 62% Fe.

1965-66 - Most of magnetite on Main and West Pit Zones that was available to open pit mining, no methods are recorded.
- Mine closed, mill sold.

1966-1983 - No known work on claims.

1983 - airborne Magnetometer by Dickenson Mines Limited followed by geological mapping, extensive sampling and ground magnetometer surveys.

1997 - Area staked by J. L. Paquet of Campbell River, who re-staked and held the claims till 2001.

2001 - Area acquired by staking by J. T. Shearer. Trenching and bulk sampling Jan.-Feb. 2002 and option to Hillsborough Resources Ltd. in August 2002.

2003 - Road construction, bulk sampling, ground magnetometer. Further percussion drilling, Line cutting, geological mapping.

2004 - Proposed diamond drilling.



Figure 9 : Location of the Iron Mike mine

REGIONAL GEOLOGY

Regional geology has been mapped by Muller etal (1974) (92L) and Roddick (1980) (92K) and is published as Geological Survey of Canada Paper 74-8 on the general area to the west of the Iron Ross Project (Muller, Northcote and Carlise, 1974). Northern Vancouver Island and Adjacent Mainland has a complex structural history with frequent rejuvenation of major structures. All Paleozoic rocks are affected by a series of southeast trending, upright to overturned, southwest-verging folds. An inspection of the regional geology map, Figure 5 (Roddick, 1980, O.F. 480), shows several elongate, fault-bounded slices of metasedimentary rocks sandwiched between separate and distinct plutons of the Coast Plutonic Complex.

The rocks underlying the claim group are part of the eastern limb of regional synclinal structure. The oldest rocks are in the area of Late Triassic, pillowed and porphyritic basalt of the Karmutsen Formation. This formation is estimated to be greater than 3000m thick.

The Quatsino Formation conformably overlies the Karmutsen Formation. The formation consists of Limestone up to 900m thick. Granitic intrusives are common within the formation and the limestone has been, in places, converted to marble and skarn.

The early Jurassic Bonanza Formation conformably overlies the Quatsino limestone. The lower part of the formation is composed of carbonaceous shale, calcareous shale and greywacke, occasional tuff units are present. The upper half of the formation is composed of dacitic to andesitic lavas with tuffs and breccias.

The Adams River intrusive intrudes all of the above rock types. In the Adams River area the intrusive is mainly granodiorite in composition with some quartz diorite along the lower contacts. The intrusive is early Jurassic in age. The contact with the lower Quatsino Formation is concordant in most places.





HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS
REGIONAL GEOLOGY

NTS 92K/05W	September 2001	SCALE 1:250,000
WORK BY J. T. Shearer, M.Sc., P. Geo	FIGURE 5	

Homegold Resources Ltd IRON MIKE



Regional Geology

FIG 6

http://webmap.ei.gov.bc.ca/minpot/map/dep_find.mwf

Tuesday, December 19, 2000 10:11 AM

LOCAL GEOLOGY and MINERALIZATION

The area around the Main and West Pit (Iron Mike) areas is underlain by Karmutsen Formation basalt and an intravolcanic band of limestone, which is thought to be part of the Karmutsen Formation rather than the Quatsino Formation. The magnetite occurs on the same horizon as the limestone band and within the basalt (Atherton, 1983).

The volcanics that underlie the limestone and magnetite are pillowed to massive, fine-grained to porphyritic basalts. The pillows indicate tops to be to the west. The volcanics are slightly magnetic to non-magnetic and are generally fine grained. The rocks strike north-south and dip about 25° west. The volcanics are light grey to buff on the weathered surface to dark grey on the fresh surface. The porphyritic rocks contain hornblende phenocryst up to 1 cm long. Slickensides are present along some of the joint planes indicating some movement.

The upper basalt is similar to the lower basalt with more massive porphyritic lava than the pillowed variety. The rock is basically unaltered except in the area of magnetite concentrations. There is a 1-2m band of highly sheared basalt above the magnetite in the Main Pit. The volcanics in the magnetite zone in the West Pit exhibit contact skarn metamorphism. Epidote is common throughout the rock unit.

There is an exposure of limestone along the access road below the Main Pit. The rock is crystalline, granular weathered and pitted. The unit strikes 16° and dips 40° west. Earlier drilling by Orecan indicates the limestone is not continuous (Atherton, 1983).

The ore remnants in the Main Pit are dark black medium crystalline nearly pure magnetite. The magnetite occurs as mainly massive to occasional thin bedded layers. In the West Pit area the magnetite occurs as irregular bands and lenses in a highly altered volcanic. The ratio of magnetite and altered volcanics is variable from section to section. The distribution of magnetite in the pit is shown on the sample sections accompanying this report from the 1983 work by Atherton.

A reference in the Annual Report of the Minister of Mines (ARMM) for 1965 mentions:

> "On the Jim Mineral Claim some 1,400 feet westward from the southwest corner of the Iron Mike Mineral Claim, six holes have been drilled in an area of about 100 by 200 feet. Massive magnetite was cut in core lengths of 27 to 63 feet, all near surface. On the Ken Mineral Claim, about 1,300 feet south-southwest of the same Iron Mike corner, three holes have been drilled, all of which cut magnetite in core lengths up to 10 feet. The Jim and Ken areas are about 1,300 feet apart; a line joining them is sub-parallel to the Iron Mike Zone."

It would appear that this reference is to the currently named Iron Ross and Iron Bethea magnetometer anomalies.

The rocks underlying the west grid #1 area appear to be higher in section than those in the Main Pit area. It is not known if the limestone that occurs on this grid is a second horizon above the Main Pit area or whether the section is repeated by faulting. The geology is shown on Map 7.

The volcanics below the limestone and magnetite are massive porphyritic to fine grained basalts. All of the outcrops are weakly magnetic. The rock strike north and dip 20° to 40° west.



Granite Intrusion

Tuff

Volcanic Rocks

Limestone

Pillowed Basalt

contact

outline of orebody

magnetite outcrop

Figure 10 : Sketch geol
(after Hill and Starck, 1

HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS
LOCAL GEOLOGY

NTS 92K/05W	September 2001	SCALE 1:22,440
WORK BY J. T. Shearer, M.Sc., P. Geo		FIGURE 6

The limestone occurs as a thin band in the volcanics. The rock has granular texture with some mica. The limestone occurs south of the baseline and is continuous for the length of the grid.

The magnetite occurs in two lensitic bodies. The outline of the occurrences has been outlined by the ground magnetic survey. The magnetite is poorly exposed. The Iron Bethea (formerly Iron Mac) occurrence is located between lines 7W and 8W. It is fine grained, massive nearly pure magnetite. One grab sample taken from the outcrop assayed 58% magnetic Fe. The Iron Ross (formerly Iron Dick) occurrence is exposed in magnetite outcrops located between lines 11W and 12W. Grab samples taken from these outcrops assayed 58.1% Fe and 66.6% Mag. Fe.

The magnetite in the Iron Ross (formerly Iron Dick) and Iron Bethea (formerly Iron Mac) occurrences is very similar to the magnetite in the Main Pit Zone indicated by the massive texture and lack of volcanic lenses in the magnetite.

Sampling in 1983 (Atherton, 1983, page 14) from the Iron Ross and Iron Bethea occurrences gave the following results:

	Sample #	% Mg. Fe Satmagan	% Sol. Fe	Description
Iron Bethea	1735	58.1	63.1	Massive magnetite
Iron Ross	1761	58.1	59.0	Massive magnetite
Iron Ross	1762	66.6	69.3	Magnetite and skarn

Tuff is present above the limestone. It consists of silicified tuff bands separated by limestone or other carbonate rich bands. The tuff is exposed on line 62W 1S and L O 1+25S. Abundant pyrite was seen in these two outcrops.

The upper basalts are fine grained and massive. They are mainly non-magnetic but some outcrops were faintly magnetic. This disseminated magnetite and the disseminated magnetite in the porphyritic basalt below the limestone might be the cause of the airborne magnetic high in the southeast part of the grid according to Atherton (1983).

The magnetite outcrop of the Iron Herb II deposit is much different than in the other occurrences. The Iron Herb II occurrence is located between lines 0 and 1E. The occurrence has one outcrop of lower grade magnetite and skarn that gave the following assay (Atherton, 1983):

	Sol. Fe	Mag Fe (Sat)
1758	26%	20.9%

The outcrop is not in the area of the highest magnetic anomaly and might not be representative of the whole occurrence. The magnetite occurs as lumpy concentration up to 1" in diameter in a greenish brown skarn. This showing is on a bench that extends north from the steep hill to the south of the grid. The position of the occurrence in relation to the Iron Herb I occurrence indicates faulting has occurred since the two occurrences have about 50 feet difference in elevation.

The Iron Herb I occurrence is not exposed in outcrop. Several large boulders occur north of the baseline that show the same lumpy appearance as the Iron Herb II showings.

14W

12W

10W

8W

6W

4W

2W

0

IRON DICK

IRON MAC

Pond

GRID #1
MAIN BASELINE

SYMBOLS

- OUTCROP & OUTCROP AREA
- STRIKE & DIP
- JOINT - VERTICAL,INCLINED
- FAULT
- CONTACT - OBSERVED,INFERRED
- CREEK
- ROAD
- LAKE OR RIVER
- CREST OF PIT
- TOE OF PIT

LEGEND

- 5 UPPER BASALT OR UNDETERMINED
- 4 TUFF
- 3 LIMESTONE
- 2 MAGNETITE
- 1 LOWER BASALT

GEOLOGICAL BRANCH
ASSESSMENT REPORT

12,102

PART 1 OF 3

MAP #4

CONTOUR INTERVAL 100 FEET

DICKENSON MINES LIMITED

HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS
PROPERTY GEOLOGY

NTS 92K/05W	September 2001	SCALE 1:5,000
WORK BY J. T. Shearer, M.Sc., P. Geo	FIGURE 7	

12102

TRENCHING PROGRAM COMPLETED in OCTOBER 2002

The work in 2001 to 2003 is outlined below:

1) Sampling & geological mapping

2) Road rehab and trenching

	Line 11W	Trail Building –	100m
Iron Ross	Line 10+75W		75m
	Line 11+25W		90m
	Saw Cuts Trench		31m
	7W		70m
Iron Bethea	7+50W		100m
	8W		60m
		Total Trail -	525m

3) Trenching, 150m of excavating

4) *Excavate 10 tonnes for sandblasting media*
Crush to ½ inch minus
Deliver to OCL in Surrey

5) *Stripping* of the Iron Steve Zone and producing a high grade bulk sample.

The trenching program completed in 2002 was a 75 metre trench along both line 11W and line 10+70W. Solid limestone bedrock was uncovered by this work. A trench was also completed along the 60m perimeter of the massive magnetite outcrop as illustrated in Figure 10 (in pocket).


IRON HERB ZONE I+II
EC100
LIMESTONE
LIMESTONE
IRON STEVE
IRON ROSS
IRON BETHEA
IRON MIKE OPEN PIT
INTRUSIVE
BASELINE
LAKE
old TRAIL
N.W. End Log
W. End Log
Pillow Basalt (Karmutsen Fm)
N
1:20,000
LOCAL Geology
FIGURE 7A
EC 500
A30

DIAMOND DRILLING (Prior to 1965)

Coincident with the development and mining of the Iron Mike deposit prior to 1965-1966, there were a number of X-ray (in 1961) and small diameter core holes completed in the Iron Ross and Iron Bethea Zones, as outlined in Table II and plotted on Figure 10 (in pocket).

TABLE II

DIAMOND DRILLHOLES

IRON BETHEA ZONE

	Hole No.	Northing	Easting	Dip	Length	Azimuth	Remarks
1	X-1			-90		000	Prior to 1961
2	X-2			-90		000	Prior to 1961
3	XX-3			-90		000	Prior to 1961
4	501			-90	10' mag	000	Prior to 1965
5	502			-45	8' mag	050	Prior to 1965
6	503			-90	7' mag		1965
7	504			-45		050	1965
8	505			-45		230	1965

DIAMOND DRILLHOLES

IRON ROSS ZONE

					Estimate Magnetite		
1	X-4			-90	663'	000	Prior to 1961
2	X-5			-90	27'	000	Prior to 1961
3	X-6			-90	35'	000	Prior to 1961
4	401			-90	42'	000	Prior to 1965
5	402			-90	35'	000	1965
6	403			-90	55'	000	1965
7	404			-90	35'	000	1965
8	405			-45	63'	230	1965
9	406			-45	27'	050	1965
10	407			-90		000	1965
11	408			-90		000	1965
12	409			-45		050	1965
13	410			-45		050	1965

The drill logs and assays for this previous diamond drilling have not yet been located. The only reference to the results is contained in the Annual Report of the Minister Mines (ARMM) in 1965 pages 255 and 420:

> "On the Jim Mineral Claim some 1,400 feet westward from the southwest corner of the Iron Mike Mineral Claim, six holes have been drilled in an area of about 100 by 200 feet. Massive magnetite was cut in core lengths of 27 to 63 feet, all near surface. On the Ken Mineral Claim, about 1,300 feet south-southwest of the same Iron Mike corner, three holes have been drilled, all of which cut magnetite in core lengths up to 10 feet. The Jim and Ken areas are about 1,300 feet apart; a line joining them is sub-parallel to the Iron Mike Zone."



HOMEGOLD RESOURCES LTD.

IRON ROSS PROJECT

ROSS CLAIMS

DIAMOND DRILLING on IRON MIKE 1961

and

STRUCTURAL COUNTOURS on HANGING WALL

NTS 92K/05W	September 2001	SCALE as shown
WORK BY J. T. Shearer, M.Sc., P. Geo		FIGURE 8

Figure 12. Diamond-drill intersections on the Iron Mike property. 1961

ARMM. page 92



Figure 30. Orecan magnetite zone. Structural contours on hangingwall. 1965

ARMM. page 226

PERCUSSION DRILLING OCTOBER 2002

Percussion drilling in October 2002 totalled 970 feet (295.66m) in 17 holes mainly around the Iron Ross surface showing and in 2002 trenching as documented in Shearer (2002). (See figure 9 for locations.)

As the holes were drilled, the cuttings blown out of the holes were logged by J. Shearer, M.Sc., P.Geo. and a representative sample was collected in numbered plastic sample bags (refer to Appendix IV for drill logs). These cutting samples are presently stored at the Homegold Office in Port Coquitlam.

Some limitations in using the percussion drill method were apparent. In hole #2002-1, limestone chips were easily recovered down to a depth of 45 feet but the lower contact was wet and the only return to surface was a small amount of yellow mud (gouge) along the contact. The lithology below 45 feet is unknown. A series of holes along Trench 2002-1 is shown on Figure 12 including Holes 2002-1,13,14, 15 and 16. Two lenses of massive magnetite were found completely contained within the limestone unit. The upper lens varied from 2m to 5m thick over a strike length of about 45 metres. From 3m to 5m below the upper lens, the lower lens varied from about 4m to 5m thick over the same strike length of 45 metres. Geological potential from these intersections suggest a range of about 50,000 tonnes of material rich in magnetite with a rough 1.5 to 2.0 stripping ratio. The stripped material would be mainly limestone.

The remaining drill holes (2002-2 to 12) were positioned along the magnetite outcrop on the southside of the access road situated at the contact of the limestone and underlying volcanics. Hole #2002-2 ended at 30 feet still within mostly massive magnetite. The upper trench-drill access is mainly within limestone and an unknown thickness of skarn starting at 50ft. depth. Hole 2002-11 halfway up the eastern trench intersected a magnetite lens between 34' and 45'.

To better understand the Iron Ross magnetite deposit at least two 60 metre long diamond drill core holes are recommended near hole 2002-13 and 16. A core hole below 45 feet near hole 2002-1 may be advantageous to define the sub-surface extent of the magnetite outcrop zone as it dips to the north.

Avg. 15' (4.6 m) magnetite

$300\ m^2 \times 4.6\ m = 1380\ m^3$

$1380\ m^3 \times 5.1\ s.g. = 7038\ tonnes$

(By planimeter)

3 m contour	1710 m^2
5 m contour	830 m^2
7 m contour	410 m^2

4 m avg. thickness = 1710 − 830 = 880 m^2

6 m avg. thickness = 830 − 410 = 420 m^2

8 m avg. thickness = (By difference) = 410 m^2

1) $880 \times 4 = 3520\ m^3 \times 5.1 = 17{,}952$ tonnes

2) $420 \times 6 = 1520\ m^3 \times 5.1 = 12{,}852$ tonnes

3) $410 \times 8 = 3280\ m^3 \times 5.1 = 16{,}728$ tonnes

Total: 47,532 tonnes

Plus exposure ... 7,038 tonnes

Grand Total = 54,570 tonnes

IRON ROSS SHOWING

BOUNDARY, 9,000 T. BULK SAMPLE

HOLE 1

HOLE 2

HOLE 5

HOLE 6

HOLE 10

HOLE 13

HOLE 15

HOLE 16

TRENCH #1

TRENCH #2

OLD GROWTH

IRON ROSS

LOCATION OF 2002 DRILLING

SCALE 1:1,000

SAYWA

IRON ROSS C

COMPLETED V

FIGURE 10

PERCUSSION DRILLING AUGUST-SEPTEMBER 2003

Further percussion drilling was completed in the Fall of 2003 mainly on the Iron Steve Zone and farther east for a total of 31 holes totalling 1,403 feet (427.64m) of drilling.

Drill records are contained in Appendix V. As the holes were being drilled the cuttings were logged by Hillsborough personnel on a visual basis and a representative sample was collected in plastic sample bags every 10 feet or less. These chip samples were each examined by J. T. Shearer, M.Sc., P.Geo. and a suite was assayed both multi-trace element and major elements as shown in Appendix III. The chip samples from the 2003 percussion drilling are presently stored at the Homegold Resources Office in Port Coquitlam.

Most of the holes were drilled in and around the Iron Steve Zone (Holes 2002-1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 24 and 25) as plotted on Cross-Sections 0+20N to 1+20N (Figures 16 to 22) and on Longitudinal Sections 0+30 and 0+00, Figure 14 and 15 (in pocket).

The cross-sections suggest that the massive magnetite zones could dip relatively gently to the east. Much of the known magnetite zones are found between 1+40N to 1+00N, a distance of over 60 metres. The width of the various magnetite zones varies from 20m to 30m. The cross-sectional thickness ranges from about 6 to 10 metres with variable magnetite content. This gives a general resource potential of about 60,000 tonnes of unknown Fe grade. Similarly to the Iron Ross Zone, the Iron Steve Zone, Figure 14, Longitudinal Section 0+30 shows at least 2 main magnetite zones separated by garnet skarn and hosted within the limestone.

On the surface the Iron Steve Zone is mapped as several discontinuous pods of relatively pure massive magnetite separated by garnet-rich skarn. The ground magnetometer data suggests that the magnetite zones dip moderately shallowly to the east. The orientation of the magnetite zone should be further investigated by continued geological mapping.

The only holes west of the magnetite zones are Holes 2003-21, 16, 19 and 20. The main pods of massive magnetite should be further investigated by angle holes on sections 0+40N, 0+55N, 0+60N and 0+80N (perhaps 1+100N). The main access road is located conveniently to the west of these sections, 5 holes to be 15 to 20 metres in length each. Due to the skarn development at the bottom of holes 2003-25, 04, 05, 24, 10 and 15 might indicate a lower buried magnetite zone which is not seen in outcrop. A longer hole should test for this possibility with a length not less than 60 metres.

Additional percussion drill holes were drilled on the other known zones, Iron Herb I and Iron Herb II to the south east of the Iron Steve Zone. Drill Holes 03-22 and 23 were located north of Iron Steve Zone entirely within limestone intrusives.

Holes 03-23 and 29 were spotted near magnetometer line 32 (Iron Herb Zone). Magnetite was encountered in 03-28 from 2.44m – 3.05m and between 3.35m-4.27m. Hole 03-29 intersected magnetite between 0.91m-1.07m and again between 3.96m-4.27m within an extensive skarn zone. The holes appear to have been placed off the more intense part of the magnetometer anomaly.

Near the former producer, West Pit Holes 03-30 and 31 were drilled to investigate the magnetic anomaly and magnetite observed in road cuts. Holes 03-30 encountered an extensive skarn zone but little magnetite. Hole 03-31 intersected magnetite from 1.22m-3.35m with skarn below.



TRENCH 1
IRON ROSS PROJECT
LOOKING WEST
FIGURE 12

SAMPLING in 1983 at IRON MIKE MAIN ZONE

The Main Pit area supplied most of the magnetite ore when the mine and mill were operating. The bulk of the magnetite ore that was amenable to open pit mining was removed during this operation. The 1983 survey by H. E. Neal & Associates Ltd. including chip sampling of the open pit (Atherton, 1983). All samples were sent to Lakefield Research Ltd., Lakefield Ontario. The sampling was done on vertical sections with the following results:

TABLE III

Sampling in 1983 at Iron Mike Main Zone (from Atherton, 1983)

Section	Sample Number	*Interval Relative Height In Metres	Thickness in Metres	Mag. Fe Satmagan%	Grade Sol Fe %
2	1701	437.1-437.5	0.6	53.6	58.5
East Wall	1702	437.5-438.3	0.8	15.8	17.3
	1703	438.3-439.2	0.9	41.6	45.8
	1704	439.2-441.1	1.9	16.3	26.5
	1705	441.1-442.0	0.9	25.9	29.8
3					
East Wall	1706	437.1-441.7	4.6	49.0	52.0
4	1707	437.3-439.0	1.7	37.7	42.7
East Wall	1708	444.6-447.5	2.9	55.6	58.7
5	1709	437.0-439.0	2.0	48.6	53.5
South Wall	1710	440.1-442.2	2.1	44.6	49.2
6	1711	436.6-439.2	2.6	53.3	57.7
South Wall	1712	439.2-441.8	2.6	57.2	60.0
7	1713	437.7-440.2	2.5	53.4	57.3
South Wall	1714	440.2-442.7	2.5	53.4	56.7
8	1715	439.0-442.0	3.0	45.5	49.1
South Wall	1716	442.0-445.0	3.0	48.4	52.7
	1717	446.9-448.5	1.6	56.6	60.3
9	1718	439.7-443.2	2.5	57.6	61.9
South Wall	1719	443.2-446.8	3.6	31.2	36.4
10	1720	437.1-441.1	4.0	39.9	43.3
South Wall	1721	441.1-445.5	4.4	50.9	56.4
12					
West Wall	1722	438.5-439.5	1.0	62.0	65.6
13					
West wall	1723	438.5-440.8	2.3	34.9	38.1
14	1724	437.9-439.9	2.0	45.1	49.1
West Wall	1725	439.9-441.9	2.0	53.2	56.1

*refers to elevation shown on Map #5 only (in Atherton, 1983).

X-S 0+20

W

E

>540.0m

530.0m

520.0m

510.0m

500.0m

ELEVATION 520.0m

DH 02 0/S 2.8m N

CELLAR
518.4m

Limit

3.66m

ROAD

SCALE 1:200

CROSS SECTION 0+20S
IRON STEVE ZONE
scale 1:200

Looking North

FIGURE 16

X-S 0+40

W

E

ELEVATION

550.0m

540.0m

530.0m

520.0m

510.0m

Elevation 520.0m

DH 03-045-3.4m N

COLLAR 520.9m

soft

Lmst

blank

14.63m

DH 25-045-5.8m N

COLLAR 522.8m

white

magnetite

garnet skarn

?

Lmst

magnetite

garnet skarn

?

Lmst + garnet skarn

15.85m

MAIN ROAD

SCALE 1:200

CROSS SECTION 0+40S
IRON STEVE ZONE
SCALE 1:200

LOOKING NORTH

FIGURE 17

X-S 0+55

W

E

E Levation 530.0m

550.0m

540.0m

530.0m

520.0m

510.0m

ELEVATION

DH 24 U/S 1.2m S

COLLAR 528.3m

magnetite

skarn

MAGNETITE PIT 2003

Low mag

MAIN ROAD

gradual drop in mag.

DH 04 U/S 0.2m S

COLLAR 522.3m

white Lmst.

white lmst

brown/buff skarn

thin magnetite

buff/brown skarn

thin magnetite

grey Lmst.

white to brown

grey skarn

15.55m

17.60m

?

?

?

?

SCALE 1:200

0,510

CROSS SECTION 0+55S
IRON STEVE ZONE
Scale 1:200

S Karn ?

LOOKING NORTH
FIGURE 18

X-S 0+60

W

E

ELEVATION

540.0m

530.0m

520.0m

510.0m

SCALE 1:200

DH 24 D/S 3.6m N

DH 10 D/S 7.0m S

COLLAR 529.6m

COLLAR 528.3m

magnetite

SK

magnetite

SK

?

magnetite

garnet SK

magnetite

Lmst

garnet skarn

magnetite

skarn

Lmst.

garnet skarn.

17.68m

Hard skarn

21.34m

MAIN ROAD

DH 04 D/S 4.6m N

COLLAR 522.9

white Lmst.

skarn

white Lmst

skarn

15.55m

?

CROSS SECTION 0+60S
IRON STEVE ZONE
Scale 1:200

LOOKING NORTH

FIGURE 19

X-S 0+80

W

E

550.0m

540.0m

520.0m

510.0m

DH 05 D/S 2.0m S
COLLAR 525.11m
10.98m

DH 15 D/S 8.4m S
COLLAR 528.9m
14.63m

DH 12 D/S 0.6m N
COLLAR 530.1m
14.63m

DH 13 D/S 7.0m S
COLLAR 530.0m
14.63m

DH 11 D/S 1.8m N
COLLAR 530.3m
16.46m

DH 21 D/S 3.7m S
COLLAR 530.2m
14.63m

MAIN ROAD

SCALE 1:200

CROSS SECTION 0+80S
IRON STEVE ZONE
SCALE 1:200

LOOKING NORTH

FIGURE 20

X-S 1+00

W

E

550.0m

540.0m

530.0m

520.0m

510.0m

VATION

DH 14 D/S 5.8m N

DH 16 D/S 2.2m N

DH 06 D/S 0.8m S

COLLAR 527.7m

DH 17 D/S 4.2m S

COLLAR 529.0m

COLLAR 530.2m

COLLAR 530.2m

MAIN ROAD

?

white Lmst

9.15m

gar skarn

mag

grey Lmst

14.63m

garnet skarn

grey Lmst

10.98m

magnetite

garnet skarn

grey Lmst

10.98m

SCALE 1:200

CROSS SECTION 1+100S
IRON STEVE ZONE
Scale 1:200

LOOKING NORTH

FIGURE 21

X-S 1+20

W

E

550.0m

540.0m

520.0m

510.0m

ATION

0.0m

DH 07 O/S 1.6m S
COLLAR 528.9m
Lmst
sk?
Lmst
16.46m

DH 08 O/S 1.8m N
COLLAR 528.9m
Lmst
carbites
Lmst
9.15m

DH 09 O/S 1.0m S
DH 18 O/S 1.6m S
COLLAR 530.1m
COLLAR 529.9m
Magnetite
skarn
garnet sk
greig
Lmst
14.63m
20.12m

DH 20 O/S 4.4m S
DH 19 O/S 1.1m S
COLLAR 530.5m
COLLAR 530.5m
grey
Lmst
12.8m
grey
Lmst
14.63m

MAIN ROAD

SCALE 1:200

CROSS SECTION 1+20S
IRON STEVE ZONE
SCALE 1:200

LOOKING NORTH

FIGURE 22

Section	Sample Number	*Interval Relative Height In Metres	Thickness in Metres	Mag. Fe Satmagan%	Grade Sol Fe %
15	1726	438.6-440.6	2.0	45.2	49.5
West Wall	1727	440.6-442.9	2.3	59.3	62.5
16					
West Wall	1728	439.2-442.8	3.6	53.8	57.4
17					
West Wall	1729	438.8-441.9	2.1	50.0	53.1
18					
West Wall	1730	439.2-441.5	2.3	51.9	55.6
19	1731	437.9-439.9	2.0	48.5	52.1
West Wall	1732	439.9-441.9	2.0	44.8	58.6
20					
West Wall	1733	438.2-441.3	3.1	48.7	54.1
21					
West Wall	1734	439.9-441.9	2.0	28.1	37.0

*refers to elevation shown on Map #5 only (in Atherton, 1983).

The Sample Sections were located at 5m intervals. The geological description of each section is shown by Atherton, 1983 (on Sheet #6).

Sections were chip sampled at 10m intervals in the West Pit. The sections and sample locations are shown on Sheet #7 (in Atherton, 1983). The results are as follows:

Section	Sample Number	*Interval Relative Height In Metres	Thickness in Metres	Mag. Fe Satmagan%	Grade Sol Fe %
22	1736	475.7-478.0	2.3	56.6	59.0
South Wall	1737	478.0-479.7	1.7	33.9	36.1
	1738	479.7-480.9	1.2	54.6	57.0
23	1739	474.7-475.8	1.1	43.5	46.7
South Wall	1740	475.8-479.9	1.6	21.1	23.7
	1741	477.4-479.8	2.4	51.4	54.5
24	1742	474.8-477.3	2.5	54.6	57.4
South Wall	1743	477.3-479.3	2.0	26.6	29.1
25	1744	475.4-477.4	2.0	21.4	23.9
South Wall	1745	477.4-479.4	2.0	37.3	39.3
26	1746	475.1-478.1	3.0	24.8	27.7
South Wall	1747	478.1-481.1	3.0	31.6	34.5
	1748	481.1-483.1	2.0	30.8	33.3
27	1749	476.4-478.9	2.5	31.5	33.4
South Wall	1750	478.9-481.4	2.5	47.5	50.2

*refers to elevation shown on Map #5 only (in Atherton, 1983).

Section	Sample Number	*Interval Relative Height In Metres	Thickness in Metres	Mag. Fe Satmagan%	Grade Sol Fe %
28	1751	477.5-480.0	2.5	18.0	20.1
South Wall	1752	480.0-482.5	2.5	14.7	16.7
29	1753	478.2-480.5	2.3	20.5	22.5
West Wall	1754	480.5-482.5	2.0	33.3	35.4
30	1755	478.2-480.5	2.3	14.5	18.0
West Wall	1756	480.5-482.8	2.3	24.5	26.9

*refers to elevation shown on Map #5 only (in Atherton, 1983).

GEOPHYSICS 1983 AIRBORNE and GROUND MAGNETOMETER 1983

The purpose of the ground magnetic survey in 1983 was to follow up broad magnetic anomalies located by an airborne magnetic survey conducted during April 1983. Two grids, grid #1 and #3, were located along the axis of broad magnetic highs (Atherton, 1983).

The instrument used was a Scintrex MF-1 Fluxgate magnetometer, which has the following accuracy scale ± .5% 100 to 10,000 gammas and ± 1% 100,000 gammas.

The method used for diurnal correction was a progressive adjustment for each survey loop and using a BL 7+00W on grid #1 and BL 3+00E on grid #3 as the base station. The time interval for base station checks was 1 to 2 hours.

The results are presented on map #8 with the unit measured in gammas. The contour interval is 1000 gammas, which is considered adequate for locating magnetite concentrations. The readings were measured at 25m intervals and less over anomalous areas.

The values represent vertical intensity and are relative only to the individual base stations for each grid. The primary base station for both grids was BL 2+00E on grid #3 and all values are relative to that station.

The survey outlined four areas of interest on the two grids. They are designated Iron Bethea (formerly Iron Mac), Iron Ross (formerly Iron Dick), Iron Herb I and Iron Herb II. They are shown on Figure #8, scale 1:5,000.

The Iron Bethea (formerly Iron Mac) anomaly is located between lines 7W and 8+25W south of the baseline on grid #1. Readings up to 15,550 gammas were obtained. The anomaly represents an area 60m by 40m. The shape of the anomaly indicates a shallow SW dip to the magnetite concentration. The anomaly is confirmed by the presence of magnetite occurrence between 7+50W and 7+25W along the logging trail.

The smaller magnetic loop located at line 7W 0+50 MS is likely an extension of the Iron Bethea (formerly Iron Mac) anomaly.

The Iron Ross (formerly the Iron Dick) anomaly is located between 10+75W and 11+50W on grid #1. The anomaly is 100m south of the baseline. Readings up to 11,000 gammas were obtained. The anomaly covers an area 120m by 60m as defined by the 5,000 gamma contour. Outcrop evidence confirms that this anomaly is caused by magnetite.

The Iron Herb I anomaly consists of two magnetic highs with readings up to 18,100 gammas. The magnetic highs are separated by a magnetic low. The south anomaly is from 1+75E to 2+00E on the baseline to 75m north on lines 2E and 2+50W. This anomaly represents an area 85m by 50m. The northern anomaly centred at 100N on line 2+50E and 0+75N on line 3E.

The anomaly covers an area 35m by 95m. No outcrop evidence was found to confirm this anomaly. The presence of large boulders located in the same area as the magnetic low dividing the two anomalies indicates magnetite is the source.

The Iron Herb II anomaly is located from 0+12.5W as the baseline to 0+50E as the baseline to 0+45N on line 0+50E. The anomaly covers an area 120m by 50m by the 5,000 gamma contour.

A smaller anomaly was located at 1+50N on line 3+00W. This was located over an area of slightly magnetic basalt.

GROUND MAGNETOMETER JUNE 2003

SURVEY AREAS

1) Iron Steve Area, Lines 1-10 Map 2

A close-spaced ground magnetometer survey was completed by Hillsborough personnel between June 4 and June 16 on lines cut by chainsaw using an Omni-Plus mobile total field magnetometer. (serial #418141). Diurnal magnetic field variation was corrected using an Omni-Plus stationary base station (serial #634358).

1a) Recce Lines Around Iron Steve Area, Lines 71 & 72 Map 2

The Iron Steve Area is covered by Lines 1, 2, 3, 3a, 4 and 5. The possible southerly extension of the Iron Steve Zone is partially covered by Line 3A and 71.

Lines to the east are lines 6, 7, 8, 9, 10, 11 and 72.

The deposit is exposed on Line 3 and 3a by natural outcrops and old trenches. An irregular siliceous magnetite lens is exposed near the side of the road and was sampled in previous years (1997?) with a channel cut with a diamond saw. Two old packsack holes have been observed.

As shown on map 2, the 5000 gamma and 10,000 gamma contour starts about 42m south on Line 3 and Line 3a at 50m south. Values in the 20,000 gamma range continue south on line 3a from 80m to at least 115m south. High values continue on Line 3a south of Line 71 to 190m south. The total field measurements by the Omni-Plus are limited in absolute accuracy when in areas of very steep magnetic gradient.

The strongly negative readings on Line 4 and 72 suggest that the Iron Steve deposit dips relatively moderately shallowly to the east. Perhaps the deposit has a steeper dip in the southern portion (but the data coverage to the south is not adequate to determine).

Drillhole Recommendation:

A program of 20 drillholes was submitted in a Notice of Work at 15m spacing by S. Gardner, P.Geo. I concur with these 20 holes but would also strongly recommend several more holes be spotted at the intersection of Line 3a and Line 71 and south along Line 3a (a total of at least 5 holes at 15m spacing) refer to Map 1.

The Iron Steve deposit occupies a small low ridge from about 536m elevation to 516m elevation. A general magnitude of possible resource available to an open cut might be on the order of 20m wide x 10m deep x 60m long x 4.5 SG = 54,000 tonnes. Of course, drilling is required to confirm any possible tonnage and the deposit is expected to be irregular in detail. A larger volume of magnetite material may be too deep for open cut extraction.

1a) Recce Lines

Lines 6 through 10, located to the immediate east of the Iron Steve deposit do not appear to indicate any anomalous magnetic values. Line 71 indicates highly anomalous values near its intersection with Line 3a up to 8,170□ with a higher value width of about 30m. Readings on Line 72 starting near the base station location and going around the Iron Steve Zone shows negative values to the northwest of the Iron Steve

Zone (similar to Line 4) with relatively stable background values to the south of the deposit.

2) Iron Mike Mine and West Pit Area, Lines 12-17 Map 3

The Iron Mike Mine produced 168,735 tonnes averaging about 45% Fe to make 112,799 tonnes of concentrate averaging 62.26% Fe.

The present magnetometer survey shows a northwest-southeast magnetic anomaly on Lines 13, 14, 15 and 15 (maximum reading of 13,781gammas) which is just upslope from the southwest corner of the Pit where a decline was collared to follow a large lens of magnetite visible in the pit wall. The present survey confirms that this magnetite lens dips to the south-southwest at a moderate angle. On a cursory examination, it appears that steepness of the slope precludes any large amount of magnetite being available for open cut extraction. The plan in the 1960s was to mine this magnetite by underground methods. A considerable tonnage of magnetite was outlined by diamond drilling in support of the proposed underground operation. This underground operation apparently was not financially viable.

4) West Pit Area, Lines 18-25 Map 3

A small magnetic anomaly is present on Line 18; the 1,000 gamma contour shows an anomaly 30mx50m. Old records suggest that diamond drilling in the 1960s intersected magnetite in this area. Three drillholes are recommended.

The West Pit produced magnetite ore in the 1960s. A weak magnetic anomaly is present on Line 21 to the west of West Pit, having a maximum value of 3,452 gammas. This anomaly is relatively weak suggesting a low grade magnetite zone or a more deeply buried magnetite zone. Two to four holes are warranted.

3) Area Between Iron Mike & Iron Bethea, Lines 11 & 12 Map 3

Line 12 starts southeast of the Iron Mike Pit about 160m. All values on Line 12 are in the background range. Line 11 starts near the start of Line 12 and doglegs about 100m southeast of Line 12. There is a low order anomaly on the south end of the middle hill. The 2,000 gamma contour is 60m in length with the highest reading 4,083 gammas (elevation 510m). Another low order anomaly 50m southwest of the previous anomaly is about 45m long on the 2,000 gamma contour at elevation 498m. Both of these low order anomalies should be checked with prospecting and follow-up magnetic survey lines.

5) & 6) Iron Herb I & II, Lines 27-37 and Lines 38-39, 61-65 Map 4

The Iron Herb I and II areas were covered in the 1983 fluxgate vertical field survey (Alterton, 1983). The Iron Herb I area in the 1983 survey was described as two magnetic anomalies separated by a central low. Values were up to 18,100 gammas (vertical field). The two anomalies were approximately 85m x 50m and 95m x 35m in extent.

In the present (2003) survey the Iron Herb I area extends in an arcuate fashion from beyond Line 37 on the west to beyond Line 27 a distance of at least 290 metres. The central core of the Iron Herb anomaly are mainly well above 10,000 gammas up to 25,034 gammas. The zone appears to dip toward the south.

Drillholes can be positioned relatively easily along the north road beginning from the main road at Line 34 at about 40m to 50m along the branch road. Several holes could be positioned from this locality to test the thickness of the magnetite zone. Excavator trenching is also recommended up the small knoll to the east where a clearing-swamp is shown on the map.

The Iron Herb II anomaly is described from the 1983 survey as a magnetic high 120m x 50m in extent. In the present (2003) survey the Iron Herb II anomaly is about 120m long between Lines 38, 39, 61 and 62 but is somewhat irregular and variable in station values. The highest value is 11,236 gammas. The zone appears to dip to the south-southwest. At least 4 drillholes should be positioned along the main road and north branch to test the subsurface of the zone near Lines 39 and 61.

There is a 75m gap between Line 37 and Line 38. The trend of the Iron Herb I and Iron Herb II anomalies suggest a possible 60 metre right lateral offset between the anomalies due to a possible northwest-southeast fault or that perhaps the zones are separate lenses.

Lines 63, 64 and 65 suggest that the Iron Herb II anomaly does <u>not</u> extend to the southwest.

7) & 8) South of Iron Ross, Lines 41-48 and Iron Bethea, Liens 49-57 <u>Map 5</u>

7) Iron Ross

Line 41 is situated on the trench and drill fence on the south side of the Iron Ross deposit. From percussion drill data, it is known that the Iron Ross magnetite deposit is covered by about 10 to 15 metres of limestone in the vicinity of the 4,000 to 7,000 gamma response. The two stations on Line 42 of 3595 suggest that there may be some extension of the deposit to the south extending from the central cross trench, a distance of about 30 metres. A couple more percussion holes are recommend in this area, likewise 20m west of the start of Line 42 (4,197 gammas).

An area of 4,000 gamma plus readings is present on the west side of Lines 45 and 46 about 120-160m south of the Iron Ross in somewhat steeper terrain. Some detail prospecting is in order to check for magnetite outcrops or float. The steepness of the slope may preclude open cut reserves being present.

Line 48 is entirely background values.

8) Iron Bethea

The "dot" for Iron Bethea appears to be misplotted. The higher magnetic values on Line 11 (6,685 gammas), Line 53 (up to 12,819 gammas) and Line 52 (4,855 gammas) appear to partially reflect the position of the Iron Bethea zone. In the 1983 survey, the Iron Bethea magnetic anomaly (formerly the Iron Mac) was within Lines 7W to 8+25W (old grid) covering an area 60m x 40m with readings up to 15,550 gammas over vertical field. The magnetic pattern suggested a shallow southwest dip.

The present survey (2003) only partially covers the area of interest but might range from 60m to 90m long by 20m to 40m wide. Two additional lines parallel to the southeast of Line 49 would give sufficient coverage. The old road past the Iron Ross deposit would need to be extended about 190m along the old (1950s) logging road, which can be traced to the new logging road corner near the middle of Line 57. Further prospecting and eventually drilling are recommended on the Iron Bethea as access is improved.

Some unknown tonnage, by way of open cut, is potentially available subject to favourable results of future work.

The lines southeast of Iron Bethea (Lines 55, 56, 57 and 58) all exhibit low background values suggesting low magnetic potential.

CONCLUSIONS and RECOMMENDATIONS

The known massive magnetite zones covered by the Ross Mineral Claim have been explored intermittently for some time since discovery in the late 1950's. Assays by previous workers indicate over 62% Fe_2O_3 as relatively coarse crystalline magnetite.

A program of trenching and bulk sampling was completed in early 2002, followed by percussion drilling in later 2002, a ground magnetometer survey in June 2003 and further percussion drilling in September 2003. This report documents the results of all this work but only applies for assessment credit for the work performed in 2003.

Extensive airborne and ground magnetometer surveys were completed in 1983 by Dickenson Mines Limited, which outline 4 additional large massive to skarn and magnetite zones to the west of the Iron Mike main pit.

Hillsborough was successful in producing a high grade bulk sample from the Iron Steve Zone in 2003 which was used in super-heavy concrete applicatons.

Much of the magnetite produced in British Columbia at the present time is from a sophisticated reprocessing of tailings (Craigmont) or hit and miss reprocessing coarse waste dumps (Texada Island). Possible markets for magnetite are: heavy aggregate for high-density concrete, heavy media for coal washing, sandblasting abrasives, high-density filter media and radiation shielding aggregates. Two major construction projects that may start in early 2002 are the expansion of the sub-atomic research TRIUMF facility at the University of British Columbia and the Sumas-Duncan Natural Gas Pipeline (for pipe anchors) by BC Hydro and Williams Pipeline Company. There may also be increasing application to special designed heavy concrete foundations in areas of high hydrostatic ground pressure in areas like Richmond, B.C.

An alternative market may be as a raw material for cement plant use. The current supply from Anyox slag assays 36.4% SiO_2, 5.1% Al_2O_3 but only 45% Fe_2O_3. Anyox slag also assays typically about 3% SO_3 and has a relatively high Bond work index of >23. Bond work index of 10.7 and 15.0 have been obtained for magnetite from other properties on Vancouver Island.

A diamond drill program is recommended for 2004 consisting of a series of short angle holes along the limestone contact at the Iron Steve Zone, two short vertical holes at the Iron Ross Zone to investigate both the limestone hosted magnetite and limestone-basalt contact magnetite. If the logging access roads open up the Iron Bethea area then two angle holes would be warranted at Iron Bethea Zone.

Respectfully submitted,

J. T. Shearer, M.Sc., P.Geo.
Consulting Geologist
January 31, 2004

ESTIMATE of COSTS for FUTURE WORK

Program 2004: Follow-up Geological Mapping and Select Diamond Drilling

(A)	Project Supervision:	
	J. T. Shearer, M.Sc., P.Geo.	
	Room, Board and Transportation and Helper	$ 10,000.00
	Contact Diamond Drilling (1,500 ft. @ $19/ft.)	28,500.00
	Excavator/Bulldozer to move drill	5,000.00
	Consumables @ $5/ft.	7,500.00
	Mob & Demob of Dill & Bulldozer	2,000.00
	Analytical	4,000.00
	Report Preparation, Drafting & Reproduction	3,000.00
	Subtotal	$ 60,000.00
(B)	Additional Bulk Samples, 5,000 tonnes	
	Load & Haul to Crusher & Load Trucks with Excavator @ $2.50/tonne	12,500.00
	Drill/Blast Tank Drill $160/hr.	8,000.00
	Truck to Sayward 30 tonne Trucks, 250 loads, 15 days, $5/tonne approx.	25,000.00
	Barge from Sayward to Mitchell Island, $5/tonne	30,000.00
	Load & Unload, Approx	4,500.00
	Crush at Site, Approx. $5/tonne x 5,000 tonnes to specification	20,000.00
	Mob of Crusher and Tank Drill	5,000.00
	Road Use	5,000.00
	Supervision	5,000.00
	Subtotal	$ 115,000.00
	TOTAL	**$175,500.00**

(C) Program 2005: Mine Permit work, application for 100,000 tonne per year production permit.

Geological Mapping, Drill Supervision:	
J. T. Shearer, M.Sc., P.Geo. & Assistant	$ 10,000.00
Mapping, Survey Control, Lease Survey	9,000.00
Definition Drilling, 1,000 ft @ $16/foot average, percussion and diamond drilling	16,000.00
Mob & Demob and Supplies	4,000.00
Assay – Analytical	3,500.00
Mine Planning & Product Design	16,000.00
Forestry Cutting Plan	3,000.00
Environmental Survey	5,500.00
Acid Rock Drainage Sampling and Report	2,000.00
Permit Application and Reporting	2,000.00
Report Preparation, Word Processing & Reproduction	3,000.00
First Nations Liaison	4,000.00
Public Meetings & Advertising	2,000.00
Total	$ 80,000.00

Program 2004 & 2005 **GRAND TOTAL** **$246,000.00**

REFERENCES

Annual Report of the Minister of Mines:
1961 – pg 92, 1962 – pg 96, 1963 – pg 99, 1964 – pg 152, 1965 – pg 225 & 420.

Atherton, P. G., 1983a:
Report on Geological Survey and Sampling of the Pete #1, Iron Mike, Iron Joe Claims, Sayward Area, Vancouver Island, British Columbia for Dickenson Mines Limited, Dec. 29, 1983 10pp. Assessment Report 12,102 part 1.

1983b:
Report on Ground Magnetic Survey of the Pete #1 Claim Group Sayward Area, Vancouver Island, British Columbia for Dickenson Mines Limited, Dec. 29, 1983 10pp. Assessment Report 12,102 part 2.

Carson, D. J. T., 1973:
The Plutonic Rocks of Vancouver Island, British Columbia: Their Petrography, Chemistry, Age and Emplacement, Geological Survey of Canada, Paper 72-44, Department of Energy Mines and Resources.

Fischl, P., 1992:
Limestone and Dolomite Resources in British Columbia. B.C. Geological Survey, Open File 1992-18, 152 pp.

Goudge, M. F., 1944:
Limestones of Canada, Their Occurrence and Characteristics, Report 811, part 5, pages 163-164, 175-176.

Hancock, K. D., 1988:
Magnetite Occurrences in British Columbia, B.C. Energy and Miens, Open File, 1988 – 28, 154 pp.

Hill, H. and Starck, L., 1963:
Report on the Hartt Iron Property of InterCan Development Ltd. Private Report.

Hill, H., Starck, L. and Associates Ltd., 1964:
Property Report (Iron Mike); BCMEMPR Property File 92K.043, Sept. 29, 1964.

1965a:
Property Report (Iron Mike); BCMEMPR Property File 92K.043, Jan. 6, 1965.

1965b:
Property Report (Iron Mike); BCMEMPR Property File 92K.043, May 15, 1965.

McKechnie, N. D., 1960:
Iron Mike, Mines and Petroleum Resources Report 1960, pp 105, 106.

Muller, J. E., Northcote, K. E. and Carlise, D., 1974:
Geology and Mineral Deposits of Alert-Cape Scott Map Area (92L), Vancouver Island, B.C., Geological Survey of Canada, Paper 74-8, 77pp.

Roddick, J. A., 1980:
Geology of 92K Map Sheet (Bute Inlet) and Notes on the Stratified Rocks of Bute Inlet Map Area, Geological Survey of Canada, Open File 480.

Roddick, J. A. and Hutchison, W. W., 1972:
Plutonic and Associated Rocks of the Coast Mountains of British Columbia. Int. Geol. Confr., Twenty-fourth Session, Canada, Guidebook A04-Cor, 71p.

1974:
Setting of the Coast Plutonic Complex, British Columbia. Pacific Geology, 8, 91-108.

Sangster, D., 1969:
The Contact Metasomatic Magnetite Deposits in Southwestern British Columbia, Geological Survey of Canada, Bulletin 172.

Shearer, J. T., 2001:
Summary Report on the Iron Ross Property, October 1, 2001, 18 pp.

2002:
Geological and Trenching Report on the Iron Ross Project, Filed for Assessment Purposes, March 30, 2002, 21 pp.

Sheldrake, R. F., 1983:
Report on a Helicopter Magnetometer Survey, Pet 1, Pete 2 and White 1 claims, Nanaimo Mining Division, Sayward Area, Vancouver Island, British Columbia for Dickenson Mines Limited.

Woodsworth, G. J. and Roddick, J. A., 1977:
Mineralization in the Cost Plutonic Complex of British Columbia, South of Latitude 55°N. Geological Society of Malaysia, Bulletin 9, Nov. 1977, pg 1-16.

APPENDIX I

STATEMENT of QUALIFICATIONS

January 31, 2004

Appendix I

STATEMENT of QUALIFICATIONS

I, JOHAN T. SHEARER, of 1817 Greenmount Avenue, in the City of Port Coquitlam, in the Province of British Columbia, do hereby certify:

1. I am a graduate of the University of British Columbia (B.Sc., 1973) in Honours Geology, and the University of London, Imperial College (M.Sc., 1977).

2. I have over 30 years experience in exploration for base and precious metals and industrial mineral commodities in the Cordillera of Western North America with such companies as McIntyre Mines Ltd., J. C. Stephen Explorations Ltd., Carolin Mines Ltd. and TRM Engineering Ltd.

3. I am a fellow in good standing of the Geological Association of Canada (Fellow No. F439) and I am a member in good standing with the Association of Professional Engineers and Geoscientists of British Columbia (Member No. 19,279) and a member of the CIMM and a fellow of the Society of Economic Geologists (SEG), Fellow #723766.

4. I am an independent consulting geologist employed since December 1986 by Homegold Resources Ltd. at #5-2330 Tyner St., Port Coquitlam, B.C.

5. I am the author of the present report entitled "Geological, Drilling and Magnetometer Assessment Report on the Iron Ross Project, Nanaimo Mining Division: dated January 31, 2004.

6. I have visited the property on Nov. 29 & 30, 2001, Feb. 6-12, 2002, March 14-17, 2002, October 20-October 29, 2002 and June 2003 and October 2003. I have carried out mapping, percussion drilling and sample collection and am familiar with the regional geology and geology of nearby properties. I have become familiar with the previous work conducted on the Iron Ross Project by examining in detail the available reports and maps and have discussed previous work with persons knowledgeable of the area.

7. I own an interest in the Ross, Iron Ross and Iron Bethea Claims and own Homegold Resources Ltd.

Dated at Port Coquitlam, British Columbia, this 31st day of January, 2004.

J. T. Shearer, M.Sc., F.G.A.C., P.Geo.
Quarry Supervisor #98-3550
January 31, 2004

APPENDIX II

Statement of Costs
2003 & 2004
(current year only)
January 31, 2004

Appendix II

STATEMENT of COSTS 2002 and 2003
IRON ROSS PROJECT, MX-8-216
Geological Mapping, Trenching, Bulk Sampling, Percussion Drilling and Ground Magnetometer Survey

Wages and Benefits		
J. T. Shearer, M.Sc., P.Geo., Quarry Supervisor #98-3550		
Field Supervision, 3 days @ $350/day, June 2003		$ 1,050.00
Data Interpretation, Drill Chip Examination, 6.5 days @ $300 per day, October 2003		1,950.00
Field Assisstant		
3 days @ $200/day, June 2003		600,00
	GST	252.00
	Subtotal Wages	$ 3,.852.00
Transportation		
Truck Rental, Fully equipped 4x4, 3 days @ $65.50/day		196.50
Gas		182.25
Ferries		98.00
Analytical (Chemex Labs)		1,933.51
Equipment Rentals (Chainsaws, etc.)		567.12
Mill Design & Scoping Studies (Industrial Mineral Incorp.)		3,400.00
Line Cutting & Prospecting		13,080.57
Grinding, Specific Gravity, Testing (International Metallurgical)		1,648.00
Living Allowance, R.V. Park, 3 days @ $85/day		255.00
Road Construction (Stripping, Road Repair, Excavator), Douglas Contracting Ltd.		19,510.00
Trenching, Bulk Sampling (Upland Contracting)		13,287.94
Percussion Drilling (Rock Tech Industries)		19,699.70
Crushing Bulk Sample, Upland Contracting		10,139.30
Trucking Bulk Sample to Crusher		2,050.00
Magnetometer & Magnetometer Survey – Rental & Labour		5,285.25
Base Map Production, Eagle Mapping (Detail Photo Map)		11,300.00
Miscellaneous (Road Fee)		2,000.00
AutoCad Drafting (by Hillsborough Personnel)		593.40
Supplies		1,858.46
Baseline Sampling (Nova Pacific Environmental)		7,835.00
Report Preparation		2,500.00
Word Processing and Reproduction		325.00
	Subtotal	$ 117,745.00
	GRAND TOTAL	**$ 121,597.00**

Note: Subdivision of Costs Between 2 Groups

(A) Iron Joe & Iron Mike

Ground Magnetics, 1.5 Line km of Magnetics +	
Line Cutting = 12.5% of Magnetics ($5,285.25)	= $1,635.07
12.5% of Line Cutting & Prospecting ($13,080.57)	= $660.65
Physical 1.65km of Access Road 29.73% of total road work ($19,510)	= $5,800.27
TOTAL	$7,335.07

(B) Work on Iron Ross Group $121,597.00 - $7,335.07 = $114,261.93
(refer to the two filed Statement of Work)

APPENDIX III

ANALYTICAL RESULTS/ASSAY CERTIFICATES 2003 & 2004

January 31, 2004

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

CERTIFICATE VA04004811

Project: Iron Ross

P.O. No.:

This report is for 75 Rock samples submitted to our lab in Vancouver, BC, Canada on 2-FEB-2004.

The following have access to data associated with this certificate:

JOE SHEARER

SAMPLE PREPARATION

ALS CODE	DESCRIPTION
WEI-21	Received Sample Weight
LOG-22	Sample login - Rcd w/o BarCode
CRU-31	Fine crushing - 70% <2mm
SPL-21	Split sample - riffle splitter
PUL-31	Pulverize split to 85% <75 um

ANALYTICAL PROCEDURES

ALS CODE	DESCRIPTION	INSTRUMENT
S-IR08	Total Sulphur (Leco)	LECO
ME-XRF06	Whole Rock Package - XRF	XRF
OA-GRA06	LOI for ME-XRF06	WST-SIM
ME-ICP41	34 Element Aqua Regia ICP-AES	ICP-AES

To: **HOMEGOLD RESOURCES LTD.**
ATTN: JOE SHEARER
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

This is the Final Report and supersedes any preliminary report with this certificate number. Results apply to samples as submitted. All pages of this report have been checked and approved for release.

Signature: 

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method Analyte Units LOR	WEI-21 Recvd Wt kg 0.02	ME-XRF06 SiO2 % 0.01	ME-XRF06 Al2O3 % 0.01	ME-XRF06 Fe2O3 % 0.01	ME-XRF06 CaO % 0.01	ME-XRF06 MgO % 0.01	ME-XRF06 Na2O % 0.01	ME-XRF06 K2O % 0.01	ME-XRF06 Cr2O3 % 0.01	ME-XRF06 TiO2 % 0.01	ME-XRF06 MnO % 0.01	ME-XRF06 P2O5 % 0.01	ME-XRF06 SrO % 0.01	ME-XRF06 BaO % 0.01	ME-XRF06 LOI % 0.01
IS-03-01-1-6		2.86	4.19	0.58	93.24	2.15	0.34	0.15	0.03	<0.01	0.01	0.19	0.02	<0.01	<0.01	-2.60
IS-03-01-6-12		6.20	12.94	1.40	83.11	3.36	0.50	0.11	0.19	0.01	0.03	0.26	0.03	<0.01	0.01	-2.44
IS-03-01-25-30		9.30														
IS-03-01-31-36		7.64														
IS-03-03-0-18		2.96	15.31	4.88	8.53	40.99	0.89	0.13	0.26	<0.01	0.15	0.33	0.05	0.03	<0.01	27.20
IS-03-03-19-24		2.96														
IS-03-03-25-30		2.42														
IS-03-03-31-36		2.62														
IS-03-03-37-48		2.84														
IS-03-03-49-00		2.64														
IS-03-05-0-18		0.24	45.10	15.24	6.16	16.75	2.49	2.48	0.68	<0.01	0.44	0.14	0.21	0.07	0.04	9.63
IS-03-05-19-24		3.10	28.75	10.67	4.30	29.94	1.77	1.67	0.53	<0.01	0.27	0.10	0.14	0.05	0.03	21.60
IS-03-08-0-6		2.24														
IS-03-08-07-12		1.44														
IS-03-08-13-18		1.40														
IS-03-08-19-24		1.24														
IS-03-08-25-30		1.24														
IS-03-09-7-24		8.34	21.33	7.67	55.78	9.56	1.86	0.53	0.16	<0.01	0.33	0.33	0.08	0.01	0.01	0.60
IS-03-10-0-12		7.66	16.99	2.27	75.30	6.05	0.38	0.09	0.29	0.01	0.08	0.31	0.03	<0.01	<0.01	-2.16
IS-03-10-13-18		4.68	10.19	2.20	78.72	8.58	0.34	0.05	0.02	<0.01	0.06	0.38	0.01	<0.01	0.01	-2.05
IS-03-10-19-24		4.44	4.27	0.82	92.42	3.14	0.26	0.10	0.02	<0.01	0.04	0.23	0.02	<0.01	0.01	-2.53
IS-03-10-25-30		3.88	6.49	0.98	86.99	5.30	0.33	0.11	0.02	<0.01	0.02	0.24	0.01	<0.01	<0.01	-2.28
IS-03-10-31-42		4.36														
IS-03-12-0-12		4.96	6.56	1.19	87.59	4.78	0.39	0.09	0.03	<0.01	0.06	0.29	0.01	<0.01	<0.01	-2.03
IS-03-12-13-18		2.94	2.44	0.48	96.36	1.33	0.21	0.14	0.03	0.01	0.01	0.21	0.02	<0.01	0.01	-2.66
IS-03-12-25-30/37-42		6.78														
IS-03-14-0-12		5.44	10.11	2.73	79.46	7.00	0.86	<0.01	0.03	0.01	0.14	0.33	0.04	<0.01	0.01	-1.75
IS-03-IS-0-6.		2.64	19.21	5.40	64.25	8.84	1.03	0.76	0.16	0.01	0.21	0.29	0.08	0.01	0.02	-1.49
IS-03-IS-13-24		6.92	16.50	5.31	69.26	6.93	1.18	0.69	0.16	<0.01	0.23	0.25	0.06	<0.01	<0.01	-1.65
IS-03-17-0-6		2.16	5.53	0.88	90.30	3.63	0.32	0.12	0.02	<0.01	0.04	0.25	0.03	<0.01	0.01	-2.45
IS-03-18-6-12		3.66														
IS-03-18-12-18		5.30	23.97	8.29	50.31	11.72	2.20	0.65	0.26	<0.01	0.40	0.35	0.07	0.01	0.02	0.65
IS-03-22-1-6		1.26														
IS-03-22-6-10		1.08														
IS-03-22-10-IS		2.14														
IS-03-22-IS-20		1.16														
IS-03-22-20-25		1.58														
IS-03-22-25-34		1.00														
IS-03-22-34-46		2.64														
IS-03-22-46-58		4.44														

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method Analyte Units LOR	WEI-21 Recvd Wt kg 0.02	ME-XRF06 SiO2 % 0.01	ME-XRF06 Al2O3 % 0.01	ME-XRF06 Fe2O3 % 0.01	ME-XRF06 CaO % 0.01	ME-XRF06 MgO % 0.01	ME-XRF06 Na2O % 0.01	ME-XRF06 K2O % 0.01	ME-XRF06 Cr2O3 % 0.01	ME-XRF06 TiO2 % 0.01	ME-XRF06 MnO % 0.01	ME-XRF06 P2O5 % 0.01	ME-XRF06 SrO % 0.01	ME-XRF06 BaO % 0.01	ME-XRF06 LOI % 0.01
IS-03-22-58-64		1.46														
IS-03-22-64-70		1.02														
IS-03-23-10-16		0.44														
IS-03-23-16-22		1.08														
IS-03-23-22-28		1.74														
IS-03-23-28-34		1.06														
IS-03-23-34-40		0.34														
IS-03-24-0-6		1.22	12.14	3.19	76.39	6.74	0.67	0.30	0.06	<0.01	0.17	0.29	0.04	0.01	0.01	-1.71
IS-03-24-10-16		2.80														
IS-03-24-16-22		2.18	32.41	10.75	32.15	18.89	2.54	0.50	0.14	0.01	0.51	0.89	0.11	0.02	0.02	0.19
IS-03-25-0-6		1.66														
IS-03-25-6-10		1.24	6.76	1.77	86.85	4.44	0.45	0.19	0.03	<0.01	0.09	0.22	0.03	<0.01	<0.01	-2.32
IS-03-25-28-34		1.98	7.26	0.95	86.21	5.32	0.61	0.10	0.03	<0.01	0.06	0.22	0.02	0.01	<0.01	-2.30
IH-03-27-10-16		1.00	42.70	6.70	26.52	12.73	4.72	0.17	0.10	0.03	0.68	0.35	0.10	0.01	0.01	3.81
IH-03-27-16-22		2.74														
IH-03-27-22-28		2.38														
IH-03-27-28-34		2.94														
IH-03-27-34-40		1.24														
IH-03-27-40-46		2.38														
IH-03-27-46-52		2.32														
IH-03-27-52-55		1.16														
IH-03-28-4-10		3.24														
IH-03-28-10-16		3.40	19.94	5.39	58.99	11.53	2.22	0.21	0.09	0.01	0.30	0.24	0.07	0.01	0.01	-0.10
IH-03-28-16-22		1.60														
IH-03-28-22-34		3.60														
IH-03-28-34-46		2.06														
IH-03-29-3-6		1.44	35.21	12.44	33.05	12.55	3.53	1.02	0.30	0.01	0.66	0.23	0.12	0.04	0.01	0.70
IH-03-29-6-10		1.90														
IH-03-29-10-16		2.02														
IH-03-29-16-22		1.64														
IH-03-29-22-28		3.60														
IH-03-29-28-34		2.56														
WP-03-31-4-10		2.64	11.28	2.26	79.23	5.21	1.52	0.15	0.05	<0.01	0.17	0.18	0.05	<0.01	0.02	-1.51
WP-03-31-10-16		3.96	35.08	11.60	31.24	14.57	3.77	0.68	0.17	0.02	1.25	0.26	0.12	0.03	0.03	0.70

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method	ME-XRF06	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41
	Analyte	Total	Ag	Al	As	B	Ba	Be	Bi	Ca	Cd	Co	Cr	Cu	Fe	Ga
	Units	%	ppm	%	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	%	ppm
	LOR	0.01	0.2	0.01	2	10	10	0.5	2	0.01	0.5	1	1	1	0.01	10
IS-03-01-1-6		98.30														
IS-03-01-6-12		99.50														
IS-03-01-25-30			0.3	0.31	742	<10	<10	<0.5	4	2.11	<0.5	160	5	16	>50	<10
IS-03-01-31-36			<0.2	0.55	256	<10	<10	<0.5	3	2.72	<0.5	49	7	198	>50	<10
IS-03-03-0-18		98.75														
IS-03-03-19-24			<0.2	3.01	151	<10	20	<0.5	<2	13.75	<0.5	28	5	302	4.11	<10
IS-03-03-25-30			<0.2	4.20	56	<10	20	<0.5	2	8.86	<0.5	21	5	85	4.46	10
IS-03-03-31-36			<0.2	2.58	56	<10	10	<0.5	2	6.98	<0.5	24	4	46	27.0	10
IS-03-03-37-48			<0.2	1.82	178	<10	10	<0.5	2	5.26	<0.5	95	7	21	32.8	<10
IS-03-03-49-00			<0.2	1.69	135	<10	<10	<0.5	<2	4.95	<0.5	72	6	23	38.7	<10
IS-03-05-0-18		99.43	<0.2	2.67	9	<10	100	<0.5	<2	9.08	<0.5	7	9	16	2.41	10
IS-03-05-19-24		99.83	<0.2	1.90	9	<10	50	<0.5	<2	20.6	<0.5	4	5	13	1.85	<10
IS-03-08-0-6			<0.2	0.10	3	<10	10	<0.5	<2	>25.0	<0.5	<1	2	7	0.16	<10
IS-03-08-07-12			<0.2	0.12	3	<10	10	<0.5	<2	>25.0	<0.5	<1	2	4	0.16	<10
IS-03-08-13-18			0.2	0.11	4	<10	10	<0.5	<2	>25.0	<0.5	<1	1	7	0.13	<10
IS-03-08-19-24			<0.2	0.14	5	<10	10	<0.5	<2	>25.0	<0.5	<1	2	5	0.16	<10
IS-03-08-25-30			<0.2	0.23	11	<10	10	<0.5	<2	>25.0	<0.5	<1	4	8	1.29	<10
IS-03-09-7-24		98.27														
IS-03-10-0-12		99.64														
IS-03-10-13-18		98.51														
IS-03-10-19-24		98.80														
IS-03-10-25-30		98.21														
IS-03-10-31-42			<0.2	1.04	53	<10	<10	<0.5	2	2.72	<0.5	1	6	41	>50	<10
IS-03-12-0-12		98.95														
IS-03-12-13-18		98.58														
IS-03-12-25-30/37-42			<0.2	2.83	150	<10	20	<0.5	<2	4.08	<0.5	38	19	36	25.6	10
IS-03-14-0-12		98.94														
IS-03-IS-0-6		98.77														
IS-03-IS-13-24		98.92														
IS-03-17-0-6		98.67														
IS-03-18-6-12			<0.2	0.84	421	<10	10	<0.5	3	2.55	<0.5	118	4	18	>50	<10
IS-03-18-12-18		98.89														
IS-03-22-1-6			<0.2	1.37	27	<10	30	<0.5	<2	1.32	0.6	12	32	32	2.05	<10
IS-03-22-6-10			<0.2	1.39	14	<10	40	<0.5	<2	1.18	0.5	8	20	25	1.62	<10
IS-03-22-10-IS			<0.2	1.88	8	<10	30	<0.5	<2	2.12	0.5	5	29	20	1.08	<10
IS-03-22-IS-20			<0.2	6.36	17	10	30	<0.5	<2	5.13	0.5	5	27	14	1.72	10
IS-03-22-20-25			<0.2	3.96	18	<10	30	<0.5	<2	3.28	<0.5	6	28	71	2.34	10
IS-03-22-25-34			<0.2	5.08	20	<10	50	<0.5	2	3.99	<0.5	15	21	89	3.08	10
IS-03-22-34-46			<0.2	4.55	13	<10	60	<0.5	<2	3.13	<0.5	14	19	98	3.26	10
IS-03-22-46-58			<0.2	4.75	12	<10	70	<0.5	<2	3.13	<0.5	17	24	89	3.01	10

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method Analyte Units LOR	ME-XRF06 Total % 0.01	ME-ICP41 Ag ppm 0.2	ME-ICP41 Al % 0.01	ME-ICP41 As ppm 2	ME-ICP41 B ppm 10	ME-ICP41 Ba ppm 10	ME-ICP41 Be ppm 0.5	ME-ICP41 Bi ppm 2	ME-ICP41 Ca % 0.01	ME-ICP41 Cd ppm 0.5	ME-ICP41 Co ppm 1	ME-ICP41 Cr ppm 1	ME-ICP41 Cu ppm 1	ME-ICP41 Fe % 0.01	ME-ICP41 Ga ppm 10
IS-03-22-58-64			<0.2	2.13	13	<10	20	<0.5	<2	2.05	<0.5	12	18	72	1.90	<10
IS-03-22-64-70			<0.2	1.29	9	<10	30	<0.5	<2	1.40	<0.5	9	24	42	1.40	<10
IS-03-23-10-16			<0.2	4.06	12	<10	60	<0.5	<2	17.8	0.5	7	34	34	2.51	<10
IS-03-23-16-22			<0.2	5.36	21	<10	80	<0.5	2	11.60	<0.5	9	24	35	2.90	10
IS-03-23-22-28			<0.2	6.42	21	10	70	<0.5	<2	7.50	<0.5	13	21	59	2.79	10
IS-03-23-28-34			<0.2	4.49	17	10	40	<0.5	<2	5.31	<0.5	11	24	45	2.25	10
IS-03-23-34-40			<0.2	3.56	16	<10	50	<0.5	<2	5.28	<0.5	12	16	40	2.66	10
IS-03-24-0-6		98.30														
IS-03-24-10-16			<0.2	0.53	641	<10	<10	<0.5	5	1.14	<0.5	148	7	10	>50	<10
IS-03-24-16-22		99.13														
IS-03-25-0-6			0.3	2.79	87	<10	10	<0.5	3	2.97	<0.5	28	7	60	41.1	<10
IS-03-25-6-10		98.52														
IS-03-25-28-34		98.51														
IH-03-27-10-16		98.62														
IH-03-27-16-22			<0.2	2.75	15	<10	20	<0.5	2	4.97	<0.5	27	146	17	13.80	10
IH-03-27-22-28			<0.2	2.20	9	<10	10	<0.5	<2	5.56	<0.5	17	128	36	15.2	<10
IH-03-27-28-34			<0.2	2.00	11	<10	10	<0.5	<2	4.83	<0.5	12	97	18	21.9	10
IH-03-27-34-40			<0.2	1.62	5	<10	<10	<0.5	<2	4.20	<0.5	14	52	14	27.1	10
IH-03-27-40-46			<0.2	1.86	7	<10	<10	<0.5	2	4.34	<0.5	14	39	21	28.4	10
IH-03-27-46-52			<0.2	1.78	6	<10	<10	<0.5	2	4.18	<0.5	18	43	53	29.8	<10
IH-03-27-52-55			<0.2	2.07	9	<10	<10	<0.5	<2	4.57	<0.5	18	34	30	28.9	<10
IH-03-28-4-10			<0.2	0.82	50	<10	<10	<0.5	2	22.5	<0.5	11	8	851	33.8	10
IH-03-28-10-16		98.92														
IH-03-28-16-22			<0.2	6.35	14	10	10	<0.5	2	5.76	<0.5	7	18	438	8.28	10
IH-03-28-22-34			<0.2	4.55	9	<10	30	<0.5	<2	3.70	<0.5	12	88	106	3.17	10
IH-03-28-34-46			<0.2	4.66	9	<10	50	<0.5	<2	3.80	<0.5	14	79	357	3.43	10
IH-03-29-3-6		99.88														
IH-03-29-6-10			<0.2	6.75	15	10	30	<0.5	3	5.08	<0.5	12	24	90	9.65	10
IH-03-29-10-16			0.3	0.64	48	<10	<10	<0.5	2	13.50	<0.5	20	5	1200	42.3	10
IH-03-29-16-22			<0.2	4.75	17	<10	10	<0.5	<2	4.13	<0.5	5	21	213	3.67	10
IH-03-29-22-28			<0.2	5.40	5	10	20	<0.5	2	3.69	<0.5	2	22	38	1.19	10
IH-03-29-28-34			<0.2	6.24	5	<10	20	<0.5	<2	4.42	<0.5	6	55	28	1.88	10
WP-03-31-4-10		98.60														
WP-03-31-10-16		99.51														

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41
	Analyte	Hg	K	La	Mg	Mn	Mo	Na	Ni	P	Pb	S	Sb	Sc	Sr	Ti
	Units	ppm	%	ppm	%	ppm	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	%
	LOR	1	0.01	10	0.01	5	1	0.01	1	10	2	0.01	2	1	1	0.01
IS-03-01-1-6																
IS-03-01-6-12																
IS-03-01-25-30		<1	<0.01	<10	0.04	2120	5	0.01	53	70	26	<0.01	<2	1	5	0.01
IS-03-01-31-36		<1	<0.01	<10	0.04	2420	3	<0.01	45	90	24	0.14	<2	1	4	0.03
IS-03-03-0-18																
IS-03-03-19-24		1	0.06	<10	0.38	1180	1	0.11	4	410	4	0.83	<2	2	214	0.07
IS-03-03-25-30		2	0.06	<10	0.75	1490	1	0.11	4	930	5	0.23	<2	3	168	0.08
IS-03-03-31-36		2	0.04	<10	0.34	1250	1	0.07	9	610	11	0.11	<2	2	122	0.06
IS-03-03-37-48		1	0.02	<10	0.21	1470	1	0.03	28	400	17	0.06	<2	2	64	0.05
IS-03-03-49-00		<1	0.02	<10	0.17	1480	2	0.02	29	270	15	0.07	<2	1	47	0.03
IS-03-05-0-18		<1	0.10	<10	0.64	497	1	0.23	2	1000	3	0.06	<2	3	303	0.13
IS-03-05-19-24		2	0.06	<10	0.49	482	<1	0.13	3	720	3	<0.01	<2	2	372	0.09
IS-03-08-0-6		<1	0.01	<10	0.06	406	<1	0.01	2	30	<2	<0.01	<2	<1	450	<0.01
IS-03-08-07-12		1	0.01	<10	0.06	408	<1	0.01	1	40	<2	<0.01	<2	<1	390	<0.01
IS-03-08-13-18		<1	0.01	<10	0.06	460	<1	0.01	1	30	6	<0.01	<2	<1	355	<0.01
IS-03-08-19-24		<1	0.01	<10	0.06	463	<1	0.01	3	40	<2	<0.01	<2	<1	344	<0.01
IS-03-08-25-30		1	0.01	<10	0.07	478	<1	0.01	2	60	<2	<0.01	<2	<1	355	0.01
IS-03-09-7-24																
IS-03-10-0-12																
IS-03-10-13-18																
IS-03-10-19-24																
IS-03-10-25-30																
IS-03-10-31-42		1	0.01	<10	0.07	1320	3	0.01	31	100	26	0.05	<2	1	26	0.03
IS-03-12-0-12																
IS-03-12-13-18																
IS-03-12-25-30/37-42		1	0.04	<10	0.16	1505	2	0.22	41	430	11	0.03	<2	3	112	0.17
IS-03-14-0-12																
IS-03-IS-0-6																
IS-03-IS-13-24																
IS-03-17-0-6																
IS-03-18-6-12		<1	0.01	<10	0.10	1705	3	0.02	15	80	26	0.06	<2	1	26	0.02
IS-03-18-12-18																
IS-03-22-1-6		<1	0.05	10	0.25	328	1	0.12	6	970	8	0.02	<2	2	67	0.16
IS-03-22-6-10		<1	0.07	10	0.37	230	1	0.12	3	1000	7	0.02	<2	2	90	0.15
IS-03-22-10-IS		1	0.06	10	0.27	238	1	0.10	3	1050	6	0.01	<2	2	51	0.13
IS-03-22-IS-20		1	0.05	<10	0.34	391	1	0.58	8	1160	9	0.02	<2	3	353	0.21
IS-03-22-20-25		1	0.06	10	0.56	405	1	0.34	6	1320	13	0.07	<2	4	170	0.19
IS-03-22-25-34		2	0.07	<10	0.99	475	2	0.52	14	980	6	0.35	<2	7	215	0.22
IS-03-22-34-46		1	0.10	<10	0.89	432	1	0.55	10	980	4	0.35	<2	5	237	0.21
IS-03-22-46-58		1	0.12	<10	0.76	358	1	0.50	14	910	7	0.49	<2	4	249	0.21

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

[illegible]OMEGOLD RESOURCES LTD.
[illegible]NIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Total # F [illegible]s: 3 (A - D)
Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41
	Analyte	Hg	K	La	Mg	Mn	Mo	Na	Ni	P	Pb	S	Sb	Sc	Sr	Ti
	Units	ppm	%	ppm	%	ppm	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	%
	LOR	1	0.01	10	0.01	5	1	0.01	1	10	2	0.01	2	1	1	0.01
S-03-22-58-64		1	0.06	<10	0.49	257	2	0.22	6	790	4	0.20	<2	5	85	0.21
IS-03-22-64-70		<1	0.06	<10	0.31	192	2	0.21	7	980	5	0.22	<2	2	74	0.16
IS-03-23-10-16		1	0.03	<10	0.43	1275	1	0.06	19	850	10	<0.01	<2	4	279	0.15
IS-03-23-16-22		<1	0.08	<10	0.72	1090	1	0.26	16	690	8	0.04	<2	6	328	0.17
IS-03-23-22-28		1	0.10	<10	1.06	708	1	0.49	15	540	8	0.04	<2	7	383	0.20
IS-03-23-28-34		<1	0.08	<10	0.81	507	1	0.33	10	520	5	0.04	<2	5	236	0.19
IS-03-23-34-40		1	0.11	<10	0.91	614	1	0.38	10	620	8	0.08	<2	7	176	0.21
IS-03-24-0-6																
IS-03-24-10-16		1	0.01	<10	0.03	1590	4	0.02	6	100	31	0.02	<2	1	18	0.02
IS-03-24-16-22																
IS-03-25-0-6		2	0.03	<10	0.15	1625	2	0.09	11	300	16	0.06	<2	2	89	0.08
IS-03-25-6-10																
IS-03-25-28-34																
IH-03-27-10-16																
IH-03-27-16-22		1	0.10	<10	1.66	1360	2	0.09	63	470	9	0.84	<2	7	78	0.21
IH-03-27-22-28		<1	0.04	<10	1.44	1355	8	0.04	41	420	11	1.04	<2	7	66	0.16
IH-03-27-28-34		<1	0.04	<10	0.89	1880	3	0.05	33	610	8	0.37	<2	5	49	0.14
IH-03-27-34-40		1	0.03	<10	0.59	1245	1	0.03	51	440	12	0.07	<2	4	63	0.11
IH-03-27-40-46		<1	0.03	<10	0.65	1505	2	0.02	53	370	10	0.04	<2	3	66	0.11
IH-03-27-46-52		1	0.03	<10	0.35	1635	2	0.02	44	380	13	0.03	<2	3	56	0.10
IH-03-27-52-55		1	0.02	<10	0.53	1650	2	0.02	32	600	10	0.03	<2	4	67	0.12
IH-03-28-4-10		<1	0.01	<10	0.17	738	1	0.03	81	170	21	<0.01	<2	1	228	0.03
IH-03-28-10-16																
IH-03-28-16-22		1	0.06	<10	0.35	575	<1	0.52	31	620	9	0.07	<2	4	303	0.20
IH-03-28-22-34		1	0.21	<10	1.14	381	2	0.60	39	660	5	0.02	<2	7	202	0.49
IH-03-28-34-46		1	0.31	<10	1.20	370	3	0.64	51	660	6	0.08	<2	6	281	0.51
IH-03-29-3-6																
IH-03-29-6-10		2	0.12	<10	0.68	689	2	0.66	20	660	10	0.01	<2	6	332	0.22
IH-03-29-10-16		<1	0.01	<10	0.10	626	3	0.03	62	110	18	0.18	<2	1	270	0.03
IH-03-29-16-22		1	0.03	<10	0.12	284	1	0.60	13	1030	3	0.03	<2	1	223	0.17
IH-03-29-22-28		<1	0.02	<10	0.09	131	1	0.88	7	1150	7	0.01	<2	1	295	0.19
IH-03-29-28-34		1	0.07	<10	0.60	276	8	0.99	17	800	5	<0.01	<2	6	356	0.37
WP-03-31-4-10																
WP-03-31-10-16																

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method / Analyte / Units / LOR	ME-ICP41 Tl ppm 10	ME-ICP41 U ppm 10	ME-ICP41 V ppm 1	ME-ICP41 W ppm 10	ME-ICP41 Zn ppm 2	S-IR08 S % 0.01
IS-03-01-1-6							
IS-03-01-6-12							
IS-03-01-25-30		10	<10	44	<10	34	
IS-03-01-31-36		<10	<10	59	<10	58	
IS-03-03-0-18							
IS-03-03-19-24		<10	<10	35	<10	32	
IS-03-03-25-30		<10	<10	42	<10	42	
IS-03-03-31-36		<10	<10	30	<10	33	
IS-03-03-37-48		<10	<10	34	<10	25	
IS-03-03-49-00		<10	<10	33	<10	25	
IS-03-05-0-18		<10	<10	60	<10	35	
IS-03-05-19-24		<10	<10	40	<10	37	
IS-03-08-0-6		<10	<10	1	<10	19	
IS-03-08-07-12		<10	<10	1	<10	23	
IS-03-08-13-18		<10	<10	<1	<10	28	
IS-03-08-19-24		<10	<10	1	<10	27	
IS-03-08-25-30		<10	<10	3	<10	24	
IS-03-09-7-24							
IS-03-10-0-12							
IS-03-10-13-18							
IS-03-10-19-24							
IS-03-10-25-30							
IS-03-10-31-42		<10	<10	50	<10	18	
IS-03-12-0-12							
IS-03-12-13-18							
IS-03-12-25-30/37-42		<10	<10	58	<10	31	
IS-03-14-0-12							
IS-03-IS-0-6							
IS-03-IS-13-24							
IS-03-17-0-6							
IS-03-18-6-12		<10	<10	31	<10	64	
IS-03-18-12-18							
IS-03-22-1-6		<10	<10	35	<10	44	
IS-03-22-6-10		<10	<10	42	<10	27	
IS-03-22-10-IS		<10	<10	34	<10	41	
IS-03-22-IS-20		<10	<10	67	<10	60	
IS-03-22-20-25		<10	<10	77	<10	78	
IS-03-22-25-34		<10	<10	115	<10	57	
IS-03-22-34-46		<10	<10	86	<10	31	
IS-03-22-46-58		<10	<10	90	<10	27	

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT 5, 2330 TYNER ST
PORT COQUITLAM BC V3C 2Z1

Date: 9-FEB-2004
Account: MWE

Project: Iron Ross

CERTIFICATE OF ANALYSIS VA04004811

Sample Description	Method Analyte Units LOR	ME-ICP41 Tl ppm 10	ME-ICP41 U ppm 10	ME-ICP41 V ppm 1	ME-ICP41 W ppm 10	ME-ICP41 Zn ppm 2
IS-03-22-58-64		<10	<10	74	<10	29
IS-03-22-64-70		<10	<10	30	<10	54
IS-03-23-10-16		<10	<10	86	<10	164
IS-03-23-16-22		<10	<10	102	<10	88
IS-03-23-22-28		<10	<10	116	<10	62
IS-03-23-28-34		<10	<10	99	<10	58
IS-03-23-34-40		<10	<10	120	<10	70
IS-03-24-0-6						
IS-03-24-10-16		<10	<10	24	<10	26
IS-03-24-16-22						
IS-03-25-0-6		<10	<10	49	<10	45
IS-03-25-6-10						
IS-03-25-28-34						
IH-03-27-10-16						
IH-03-27-16-22		<10	<10	124	<10	91
IH-03-27-22-28		<10	<10	112	<10	85
IH-03-27-28-34		<10	<10	103	<10	46
IH-03-27-34-40		<10	<10	68	<10	27
IH-03-27-40-46		<10	<10	70	<10	29
IH-03-27-46-52		<10	<10	66	<10	21
IH-03-27-52-55		<10	<10	67	<10	35
IH-03-28-4-10		<10	<10	54	<10	26
IH-03-28-10-16						
IH-03-28-16-22		<10	<10	78	<10	26
IH-03-28-22-34		<10	<10	114	<10	28
IH-03-28-34-46		<10	<10	112	<10	31
IH-03-29-3-6						
IH-03-29-6-10		<10	<10	110	<10	33
IH-03-29-10-16		<10	<10	52	<10	23
IH-03-29-16-22		<10	<10	23	<10	21
IH-03-29-22-28		<10	<10	20	<10	17
IH-03-29-28-34		<10	<10	95	<10	17
WP-03-31-4-10						
WP-03-31-10-16						

ALS Chemex

Aurora Laboratory Services Ltd.
Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221 FAX: 604-984-0218

HOMEGOLD RESOURCES LTD.

UNIT #5, 2330 TYNER ST.
PORT COQUITLAM, BC
V3C 2Z1

Project :
Comments: ATTN: JOE SHEARER

Certificate Date: 08-MAR-2002
Invoice No. : I0212447
P.O. Number :
Account : MWE

CERTIFICATE OF ANALYSIS A0212447

SAMPLE	PREP CODE		Weight Kg	Al2O3 %	BaO %	CaO %	Cr2O3 %	Fe2O3 %	K2O %	MgO %	MnO %	Na2O %	P2O5 %	SiO2 %	SrO %	TiO2 %
525N+50E	244	200	2.58	0.46	< 0.01	0.47	< 0.01	98.00	0.85	0.16	0.16	0.29	0.03	2.95	< 0.01	< 0.01
500N+15W	244	200	1.96	0.42	< 0.01	54.02	< 0.01	0.82	0.47	0.14	0.04	0.16	0.05	1.68	0.11	0.01
535N+80F	244	200	2.56	0.80	< 0.01	3.41	< 0.01	84.00	0.79	0.25	0.21	0.30	0.07	5.49	< 0.01	< 0.01
535N+40E	244	200	3.56	0.74	< 0.01	1.82	< 0.01	91.00	0.70	0.18	0.18	0.26	0.11	3.68	< 0.01	< 0.01
535N on Rd	244	200	2.42	0.40	< 0.01	53.30	< 0.01	0.64	0.38	0.17	0.08	0.15	0.06	3.15	0.04	0.02
500N+10E	244	200	1.42	0.29	< 0.01	54.92	< 0.01	0.45	0.39	0.15	0.06	0.17	0.10	3.10	0.07	0.01
535N+20W	244	200	1.86	12.61	0.01	28.33	< 0.01	5.92	0.51	3.08	0.21	0.60	0.15	34.62	0.06	0.71

NOTE: ** UNITS = KILOGRAMS CaCO3 EQUIVALENT PER METRIC TONNE (Kg/MT)

CERTIFICATION:_____

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

To: HOMEGOLD RESOURCES LTD.
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

Date : 10-Jan-2003
Account: MWE

Project : Iron Ross

CERTIFICATE OF ANALYSIS VA02007605

Sample Description	Method Analyte Units LOR	WEI-21 Record Wt kg 0.02	ME-XRF06 SiO2 % 0.01	ME-XRF06 Al2O3 % 0.01	ME-XRF06 Fe2O3 % 0.01	ME-XRF06 CaO % 0.01	ME-XRF06 MgO % 0.01	ME-XRF06 Na2O % 0.01	ME-XRF06 K2O % 0.01	ME-XRF06 Cr2O3 % 0.01	ME-XRF06 TiO2 % 0.01	ME-XRF06 MnO % 0.01	ME-XRF06 P2O5 % 0.01	ME-XRF06 SrO % 0.01	ME-XRF06 BaO % 0.01	ME-XRF06 LOI % 0.01
02-02 10'-20' Magnetite		2.22	10.64	2.31	79.52	5.92	1.37	0.11	0.05	0.02	0.12	0.40	0.04	<0.01	<0.01	-1.25
02-03 0'-10' Magnetite		5.74	7.20	2.07	86.08	4.78	0.60	0.08	0.05	0.02	0.10	0.35	0.03	<0.01	0.01	-1.74
02-03a 10'-20' Magnetite		5.44	10.80	1.87	79.96	7.69	1.34	0.21	0.06	0.01	0.09	0.31	0.03	<0.01	0.01	-2.58
02-04 20'-30' Limestone		2.54	4.52	2.57	1.37	50.03	0.14	0.02	0.28	0.01	0.04	0.05	0.05	0.05	<0.01	40.70
02-05 40'-50' Limestone		1.46	4.40	2.35	1.00	51.20	0.14	0.02	0.22	0.01	0.04	0.06	0.03	0.05	<0.01	40.40
02-12 30'-40' Limestone		1.70	14.10	6.52	10.87	40.42	0.91	0.46	0.37	0.01	0.67	0.11	0.13	0.04	0.02	23.50
02-13 60'-70' Magnetite Pyrite		21.08	26.11	11.90	34.90	10.16	3.68	1.25	0.54	0.01	0.52	0.21	0.11	0.04	0.02	7.92
02-14 20'-30' Limestone		1.20	5.45	1.27	1.46	50.96	0.18	0.05	0.08	0.01	0.04	0.07	0.06	0.05	<0.01	40.20
02-14 30'-40' Limestone		1.74	6.58	1.83	2.49	49.13	0.70	0.06	0.10	0.01	0.08	0.10	0.05	0.05	<0.01	38.60
02-14 50'-60' Magnetite		2.38	10.59	2.85	70.11	12.55	0.38	0.09	0.03	0.02	0.34	0.49	0.06	0.02	0.01	1.45
02-14 60'-70' Magnetite		3.24	20.31	6.41	53.95	13.66	1.91	0.43	0.08	0.01	0.37	0.50	0.08	0.02	<0.01	2.21
02-15 70'-80' Magnetite		4.70	26.25	7.68	42.43	20.12	1.02	0.41	0.07	0.02	0.73	0.86	0.14	0.02	<0.01	0.15
02-16 40'-50' Magnetite		2.42	21.75	7.08	54.88	11.35	1.07	1.10	0.09	0.01	0.31	0.29	0.11	0.05	0.01	1.20
02-16 70'-80' Magnetite		5.08	12.98	6.13	63.58	13.82	1.11	0.24	0.39	0.01	0.26	0.32	0.08	0.02	0.03	3.35
02-16 0'-10' Limestone		0.92	6.65	1.83	1.96	49.64	0.18	0.07	0.20	<0.01	0.05	0.08	0.14	0.05	<0.01	38.60
02-16 20'-30' Limestone		2.16	3.83	0.80	1.09	51.81	0.12	<0.01	0.05	<0.01	0.02	0.05	0.04	0.06	<0.01	41.90
02-17 20'-30' Limestone skarn		0.84	27.54	8.79	31.20	19.53	1.41	0.82	0.99	0.01	0.22	0.49	0.11	0.02	0.06	7.31

ALS Chemex

EXCELLENCE IN ANALYTICAL CHEMISTRY

ALS Canada Ltd
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

To: HOMEGOLD RESOURCES LTD.
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

Project : Iron Ross

CERTIFICATE OF ANALYSIS VA02007604

Sample Description	Method Analyte Units LOR	ME-ICP41 Fe % 0.01	ME-ICP41 Ga ppm 10	ME-ICP41 Hg ppm 1	ME-ICP41 K % 0.01	ME-ICP41 La ppm 10	ME-ICP41 Mg % 0.01	ME-ICP41 Mn ppm 5	ME-ICP41 Mo ppm 1	ME-ICP41 Na % 0.01	ME-ICP41 Ni ppm 1	ME-ICP41 P ppm 10	ME-ICP41 Pb ppm 2	ME-ICP41 S % 0.01	ME-ICP41 Sb ppm 2	ME-ICP41 Sc ppm 1
02-04 50'-60' skarn		1.34	10	<1	0.03	<10	0.16	349	2	0.06	8	800	15	0.68	3	1
02-06 0'-10' intrusive dyke		2.52	10	<1	0.06	<10	0.48	314	<1	0.22	9	1260	6	0.38	5	4
02-07 30'-40' Intrus/skarn		-------														
02-08 10'-20' garnet skarn		4.66	10	<1	0.03	<10	0.14	566	2	0.09	9	240	2	0.14	<2	<1
02-10 10'-20' garnet/green		1.38	10	<1	0.02	<10	0.21	614	<1	0.18	4	1630	<2	0.02	<2	2
02-12 80'-90' green skarn		0.07	10	1	0.07	<10	0.32	184	2	0.42	11	860	5	0.04	2	2
02-12 90'-100' garnet/green sk		2.70	20	<1	0.37	<10	1.10	311	<1	0.35	17	800	<2	0.07	<2	4
02-13 0'-10' skarn/Lst.		0.59	<10	<1	0.02	<10	0.12	347	1	0.20	2	640	17	0.09	<2	1
02-13 30'-40' garnet/garnet sk		7.12	mag 10	<1	0.04	<10	0.37	1210	2	0.22	5	770	2	0.47	<2	3
02-13 40'-50' skarn/minor mag		4.20	10	<1	0.06	<10	0.54	946	1	0.30	11	750	<2	0.12	2	6
02-14 80'-90' skarn green		11.35	10	<1	0.06	<10	0.22	726	1	0.28	8	650	<2	0.06	<2	1
02-14 90'-100' skarn green sk		3.65	10	<1	0.03	<10	0.19	914	3	0.39	6	840	4	0.10	<2	2
02-15 60'-70' garnet/green/mag		>15.0	10	<1	0.02	<10	0.16	1165	2	0.16	19	570	<2	0.25	<2	2
02-15 80'-90' green skarn		2.20	10	<1	0.22	<10	0.29	363	<1	0.52	12	1110	<2	0.05	2	3
02-16 50'-60' gn skarn/Lst		3.65	20	<1	0.17	<10	0.46	349	1	0.61	5	1150	2	0.21	<2	3
02-16 90'-100' gn skarn		3.74	20	<1	0.07	<10	1.71	795	1	0.44	17	660	4	0.10	<2	10
02-17 0'-10' magnetite		>15.0	20	<1	0.01	<10	0.18	1090	5	0.02	15	170	17	0.98	<2	<1

INTERNATIONAL PLASMA LABORATORY LTD.

/anco B.C.
Canada V5Y
Phone (604)b,a-7878
Fax (604)879-7898
Email ipl@direct.ca
[116115:51:31:10101801]

CERTIFICATE OF ANALYSIS
iPL 01J1161

Process Research Associates Ltd
Project : 0100101 M Ron
Shipper : Frank
Shipment: PO#: 2364
Analysis:
ICP(AqR-Metal)30
S(T) by LECO
Comment:

1 **Samples** Out: Oct 17, 2001 In: Oct 16, 2001

CODE	AMOUNT	TYPE	PREPARATION DESCRIPTION	PULP 12M/Dis	REJECT 00M/Dis
B31108	1	CoarsePu	Coarse Pulp-- Sample pulv. & prep.		

NS=No Sample Rep=Replicate M=Month Dis=Discard

Document Distribution

1 Process Research Associates Ltd
9145 Shaughnessy Street
Vancouver
BC V6P 6R9

Att: Frank

EN	RT	CC	IN	FX
1	2	2	2	1
DL	3D	EM	BT	BL
0	0	0	1	0

Ph:604/322-0118
Fx:604/322-0181

Analytical Summary

##	Code	Method	Units	Description	Element	Limit Low	Limit High
01	0135	Leco	%	S(tot) Assay by LECO in %	Sulfur (LECO)	0.01	100.00
02	0701	ICP	ppm	Al ICP (Incomplete Digestion)	Aluminum	100.	50000.
03	0702	ICP	ppm	Sb ICP	Antimony	5.	1000.
04	0703	ICP	ppm	As ICP	Arsenic	5.	10000.
05	0704	ICP	ppm	Ba ICP (Incomplete Digestion)	Barium	2.	10000.
06	0705	ICP	ppm	Bi ICP	Bismuth	2.	10000.
07	0707	ICP	ppm	Cd ICP	Cadmium	0.1	100.0
08	0708	ICP	ppm	Ca ICP (Incomplete Digestion)	Calcium	100.	100000.
09	0709	ICP	ppm	Cr ICP (Incomplete Digestion)	Chromium	1.	10000.
10	0710	ICP	ppm	Co ICP	Cobalt	1.	10000.
11	0711	ICP	ppm	Cu ICP	Copper	1.	20000.
12	0712	ICP	ppm	Fe ICP	Iron	100.	50000.
13	0713	ICP	ppm	La ICP (Incomplete Digestion)	Lanthanum	2.	10000.
14	0714	ICP	ppm	Pb ICP	Lead	2.	20000.
15	0715	ICP	ppm	Mg ICP (Incomplete Digestion)	Magnesium	100.	100000.
16	0716	ICP	ppm	Mn ICP	Manganese	1.	10000.
17	0732	ICP	ppm	Hg ICP	Mercury	3.	10000.
18	0717	ICP	ppm	Mo ICP	Molydenum	1.	1000.
19	0718	ICP	ppm	Ni ICP	Nickel	1.	10000.
20	0719	ICP	ppm	P ICP	Phosphorus	100.	50000.
21	0720	ICP	ppm	K ICP (Incomplete Digestion)	Potassium	100.	100000.
22	0736	ICP	ppm	Sc ICP	Scandium	1.	10000.
23	0721	ICP	ppm	Ag ICP	Silver	0.1	100.0
24	0722	ICP	ppm	Na ICP (Incomplete Digestion)	Sodium	100.	50000.
25	0723	ICP	ppm	Sr ICP (Incomplete Digestion)	Strontium	1.	10000.
26	0747	ICP	ppm	Tl ICP (Incomplete Digestion)	Thallium	10.	1000.
27	0726	ICP	ppm	Ti ICP (Incomplete Digestion)	Titanium	100.	10000.
28	0727	ICP	ppm	W ICP (Incomplete Digestion)	Tungsten	5.	1000.
29	0729	ICP	ppm	V ICP	Vanadium	2.	10000.
30	0730	ICP	ppm	Zn ICP	Zinc	1.	20000.
31	0731	ICP	ppm	Zr ICP	Zirconium	1.	10000.

EN=Envelope # RT=Report Style CC=Copies IN=Invoices Fx=Fax(1=Yes 0=No) Totals: 2=Copy 2=Invoice 0=3½ Disk
DL=Download 3D=3½ Disk EM=E-Mail BT=BBS Type BL=BBS(1=Yes 0=No) ID=C032712
* Our liability is limited solely to the analytical cost of these analyses.

BC Certified Assayer: David Chiu

10/18/01 15:55 IPL

iPL
INTERNATIONAL PLASMA LABORATORY LTD.

CERTIFICATE OF ANALYSIS
iPL 01J1161

2036 Columbia Street
Vancouver, B.C.
Canada V5Y 3E1
Phone (604) 879-7878
Fax (604) 879-7898
Email ipl@direct.ca

Process Research Associates Ltd

Project: 0100101 M Ron

Out: Oct 17, 2001
In : Oct 16, 2001

[116115:51:31:10101B01]

1 Samples 1=CoarsePulp

Symbol	Unit	CoarsePulp Sayward Hd	Limit Low	Limit High
S(tot)	%	0.22	0.01	100.00
Al	ppm	2665.	100.	50000.
Sb	ppm	<5.	5.	1000.
As	ppm	<5.	5.	10000.
Ba	ppm	102.	2.	10000.
Bi	ppm	<2.	2.	10000.
Cd	ppm	<0.1	0.1	100.0
Ca	ppm	6562.	100.	100000.
Cr	ppm	13.	1.	10000.
Co	ppm	128.	1.	10000.
Cu	ppm	216.	1.	20000.
Fe	ppm	64%.	100.	50000.
La	ppm	<2.	2.	10000.
Pb	ppm	32.	2.	20000.
Mg	ppm	642.	100.	100000.
Mn	ppm	957.	1.	10000.
Hg	ppm	<3.	3.	10000.
Mo	ppm	8.	1.	1000.
Ni	ppm	<1.	1.	10000.
P	ppm	209.	100.	50000.
K	ppm	198.	100.	100000.
Sc	ppm	<1.	1.	10000.
Ag	ppm	<0.1	0.1	100.0
Na	ppm	174.	100.	50000.
Sr	ppm	5.	1.	10000.
Tl	ppm	<10.	10.	1000.
Ti	ppm	<100.	100.	10000.
W	ppm	<5.	5.	1000.
V	ppm	53.	2.	10000.
Zn	ppm	90.	1.	20000.
Zr	ppm	18.	1.	10000.

—=No Test Ins=Insufficient Sample Del=Delay Max=No Estimate Rec=ReCheck m=x1000 %=Estimate % NS=No Sample

BC Certified Assayer: David Chiu

CERTIFICAT OF ANALYSIS
iPL 01J1162

INTERNATIONAL PLASMA LABORATORY LTD.
Vancouver, B
Canada V5Y
Phone (604) 879-7878
Fax (604) 879-7898
Email ipl@direct.ca

Client : Process Research Associates Ltd
Project: 0100101 M Ron

1 Samples
1=Pulp

[116215:42:42:10101701]

Out: Oct 17. 2001
In : Oct 16. 2001

Sample Name	Type	Al2O3 %	BaO %	CaO %	Fe2O3 %	K2O %	MgO %	MnO %	Na2O %	P2O5 %	SiO2 %	TiO2 %	LOI %	Total %
Sayward Hd	Pulp	0.87	<0.01	1.49	91.24	<0.01	0.24	0.19	0.20	0.01	3.93	0.02	1.52	99.71
Minimum Detection		0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
Maximum Detection		100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	105.00
Method		WRock	WRock	WRock	WRock	WRock	WRock	WRock	WRock	WRock	WRock	WRock	2000 F	WRock

—=No Test Ins=Insufficient Sample Del=Delay Max=No Estimate Rec=ReCheck m=x1000 %=Estimate % NS=No Sample

10/17/01 15:43 IPL

HOMEGOLD RES.
64 SAMPLES REC'D ON JAN 22 (VA04002884) + 23 SAMPLES REC'D ON JAN 30

1	**15-03-01-1-6'**	Whole Rock			
2	**15-03-01-6-12'**	Whole Rock			
3	**15-03-01-25-30'**	ICP			
4	**15-03-01-31-36'**	ICP			
5	**15-03-03-0-18'**	ICP & Whole Rock			
6	**15-03-03-19-24'**	ICP			
7	**15-03-03-25-30'**	ICP			
8	**15-03-03-31-36'**	ICP			
9	**15-03-03-37-48'**	ICP			
10	**15-03-03-49-00'**	ICP			
11	**15-03-05-0-18'**	ICP & Whole Rock			
12	**15-03-05-19-24'**	ICP & Whole Rock			
13	**15-03-08-0-6'**	ICP			
14	**15-03-08-07-12'**	ICP			
15	**15-03-08-13-18'**	ICP			
16	**15-03-08-19-24'**	ICP			
17	**15-03-08-25-30'**	ICP			
18	**15-03-09-7-12'**	Combine with 19 & 20, Whole Rock			
19	**15-03-09-13-18'**	Combine with 18 & 20, Whole Rock			
20	**15-03-09-19-24'**	Combine with 18 & 19, Whole Rock			
21	**15-03-10-0-6'**	Combine with 22, Whole Rock			
22	**15-03-10-7-12'**	Combine with 21, Whole Rock			
23	**15-03-10-13-18'**	Whole Rock			
24	**15-03-10-19-24'**	Whole Rock			
25	**15-03-10-25-30'**	Whole Rock			
26	**15-03-10-31-36'**	Combine with 27, ICP			
27	**15-03-10-37-42'**	Combine with 26, ICP			
28	**15-03-12-0-6'**	Combine with 29, Whole Rock			
29	**15-03-12-07-12'**	Combine with 28, Whole Rock			
30	**15-03-12-13-18'**	Whole Rock			
31	**15-03-12-25-30'**	Combine with 32, ICP			
32	**15-03-12-37-42'**	Combine with 31, ICP			
33	**15-03-14-0-6'**	Combine with 34, Whole Rock			
34	**15-03-14-7-12'**	Combine with 33, Whole Rock			
35	**15-03-15-0-6'**	Whole Rock			
36	**15-03-15-13-18'**	Combine with 37, Whole Rock			
37	**15-03-15-19-24'**	Combine with 36, Whole Rock			
38	**15-03-17-0-6'**	Whole Rock			
39	**15-03-18-6-12'**	ICP			
40	**15-03-18-12-18'**	Whole Rock			
41	**15-03-22-1-6'**	ICP			
42	**15-03-22-6-10'**	ICP			
43	**15-03-22-10-15'**	ICP			
44	**15-03-22-15-20'**	ICP			
45	**15-03-22-20-25'**	ICP			
46	**15-03-22-25-34'**	ICP			
47	**15-03-22-34-40'**	Combine with 48, ICP			
48	**15-03-22-40-46'**	Combine with 47, ICP			
49	**15-03-22-46-52'**	Combine with 50, ICP			
50	**15-03-22-52-58'**	Combine with 49, ICP			
51	**15-03-22-58-64'**	ICP			

HOMEGOLD RES.
64 SAMPLES REC'D ON JAN 22 (VA04002884) + 23 SAMPLES REC'D ON JAN 30

52	**15-03-22-64-70'**	ICP			
53	**15-03-23-10-16'**	ICP			
54	**15-03-23-16-22'**	ICP			
55	**15-03-23-22-28'**	ICP			
56	**15-03-23-28-34'**	ICP			
57	**15-03-23-34-40'**	ICP			
58	**15-03-24-0-6'**	Whole Rock			
59	**15-03-24-10-16'**	ICP			
60	**15-03-24-16-22'**	Whole Rock			
61	**15-03-25-0-6'**	ICP			
62	**15-03-25-6-10'**	Whole Rock			
63	**15-03-25-28-34'**	Whole Rock			
64	**15-03-27-10-16'**	Whole Rock			
65	**15-03-27-16-22'**	ICP			
66	**15-03-27-22-28'**	ICP			
67	**15-03-27-28-34'**	ICP			
68	**15-03-27-34-40'**	ICP			
69	**15-03-27-40-46'**	ICP			
70	**15-03-27-46-52'**	ICP			
71	**15-03-27-52-55'**	ICP			
72	**15-03-28-4-10'**	ICP			
73	**15-03-28-10-16'**	Whole Rock			
74	**15-03-28-16-22'**	ICP			
75	**15-03-28-22-28'**	Combine with 76, ICP			
76	**15-03-28-28-34'**	Combine with 75, ICP			
77	**15-03-28-34-40'**	Combine with 78, ICP			
78	**15-03-28-40-46'**	Combine with 77, ICP			
79	**15-03-29-3-6'**	Whole Rock			
80	**15-03-29-6-10'**	ICP			
81	**15-03-29-10-16'**	ICP			
82	**15-03-29-16-22'**	ICP			
83	**15-03-29-22-28'**	ICP			
84	**15-03-29-28-34'**	ICP			
85	**15-03-31-4-10'**	Whole Rock			
86	**15-03-31-10-16'**	Whole Rock			
87	**J MAIN**	Whole Rock plus Sulfur			

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

Date : 10-Jan-2003
Account: MWE

CERTIFICATE VA02007604

Project : Iron Ross

P.O. No:

This report is for 17 ROCK samples submitted to our lab in North Vancouver, BC, Canada on 20-Dec-2002.

The following have access to data associated with this certificate:

JOE SHEARER

SAMPLE PREPARATION

ALS CODE	DESCRIPTION
WEI-21	Received Sample Weight
LOG-22	Sample login - Rcd w/o BarCode
CRU-31	Fine crushing - 70% <2mm
SPL-21	Split sample - riffle splitter
PUL-31	Pulverize split to 85% <75 um

ANALYTICAL PROCEDURES

ALS CODE	DESCRIPTION	INSTRUMENT
ME-GRA21	Au Ag 30g FA-GRAV finish	WST-SIM
ME-ICP41	34 Element Aqua Regia ICP-AES	ICP-AES

To: **HOMEGOLD RESOURCES LTD.**
ATTN: JOE SHEARER
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

This is the Final Report and supersedes any preliminary report with this certificate number. Results apply to samples as submitted. All pages of this report have been checked and approved for release.

Signature: 

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

: HOMEGOLD RESOURCES LTD.
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

Date : 10-Jan-2003
Account: MWE

Project : Iron Ross

CERTIFICATE OF ANALYSIS VA02007604

Sample Description	Method Analyte Units LOR	WEI-21 Recvd Wt kg 0.02	ME-GRA21 Au ppm 0.05	ME-GRA21 Ag ppm 5	ME-ICP41 Ag ppm 0.2	ME-ICP41 Al % 0.01	ME-ICP41 As ppm 2	ME-ICP41 B ppm 10	ME-ICP41 Ba ppm 10	ME-ICP41 Be ppm 0.5	ME-ICP41 Bi ppm 2	ME-ICP41 Ca % 0.01	ME-ICP41 Cd ppm 0.5	ME-ICP41 Co ppm 1	ME-ICP41 Cr ppm 1	ME-ICP41 Cu ppm 1
02-04 50'-60'		5.48	0.07	<5	<0.2	1.18	30	<10	30	<0.5	<2	>15.0	1.3	7	8	28
02-06 0'-10'		1.32	0.16	<5	<0.2	1.95	29	<10	30	<0.5	<2	2.29	<0.5	15	16	69
02-07 30'-40'		Not Recvd														
02-08 10'-20		0.44	<0.05	<5	<0.2	1.63	252	<10	20	<0.5	5	>15.0	1.1	31	7	29
02-10 10'-20'		5.18	0.06	<5	<0.2	2.34	40	<10	10	<0.5	3	2.94	0.7	3	18	11
02-12 80'-90'		3.80	0.22	<5	<0.2	2.99	241	<10	30	<0.5	3	3.39	<0.5	6	15	38
02-12 90'-100'		4.96	0.07	<5	<0.2	3.34	68	<10	150	<0.5	4	3.06	0.5	9	15	31
02-13 0'-10'		1.38	0.10	<5	<0.2	0.88	28	<10	10	<0.5	6	>15.0	1.2	4	6	7
02-13 30'-40'		4.62	0.39	<5	<0.2	3.67	734	10	60	<0.5	2	7.48	1.4	39	15	44
02-13 40'-50'		4.42	0.16	<5	<0.2	4.22	529	10	50	<0.5	4	5.74	0.5	50	16	52
02-14 80'-90'		5.78	0.20	<5	<0.2	3.19	178	<10	60	<0.5	3	3.48	2.1	20	15	20
02-14 90'-100'		5.12	0.10	<5	<0.2	2.99	909	<10	60	<0.5	2	4.01	0.6	46	13	55
02-15 60'-70'		4.38	0.14	<5	<0.2	2.46	713	<10	10	<0.5	3	3.49	4.0	104	57	101
02-15 80'-90'		3.54	0.07	<5	<0.2	4.38	112	<10	60	<0.5	3	3.87	0.5	17	39	44
02-16 50'-60'		2.04	0.16	<5	<0.2	6.48	1125	10	90	<0.5	5	4.95	0.7	56	23	59
02-16 90'-100'		4.84	0.19	<5	0.2	6.82	98	<10	140	<0.5	<2	6.60	1.6	19	18	132
02-17 0'-10'		0.80	0.50	<5	<0.2	0.69	584	<10	10	<0.5	21	2.28	15.6	309	14	255

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

HOMEGOLD RESOURCES LTD.
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

Date : 10-Jan-2003
Account: MWE

Project : Iron Ross

CERTIFICATE OF ANALYSIS VA02007604

Sample Description	Method	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41	ME-ICP41
	Analyte	Fe	Ga	Hg	K	La	Mg	Mn	Mo	Na	Ni	P	Pb	S	Sb	Sc
	Units	%	ppm	ppm	%	ppm	%	ppm	ppm	%	ppm	ppm	ppm	%	ppm	ppm
	LOR	0.01	10	1	0.01	10	0.01	5	1	0.01	1	10	2	0.01	2	1
02-04 50'-60'		1.34	10	<1	0.03	<10	0.16	349	2	0.06	8	800	15	0.68	3	1
02-06 0'-10'		2.52	10	<1	0.06	<10	0.48	314	<1	0.22	9	1260	6	0.38	5	4
02-07 30'-40'																
02-08 10'-20		4.66	10	<1	0.03	<10	0.14	566	2	0.09	9	240	2	0.14	<2	<1
02-10 10'-20'		1.38	10	<1	0.02	<10	0.21	614	<1	0.18	4	1630	<2	0.02	<2	2
02-12 80'-90'		0.87	10	1	0.07	<10	0.32	184	2	0.42	11	860	5	0.04	2	2
02-12 90'-100'		2.70	20	<1	0.37	<10	1.10	311	<1	0.35	17	800	<2	0.07	<2	4
02-13 0'-10'		0.59	<10	<1	0.02	<10	0.12	347	1	0.20	2	640	17	0.09	<2	1
02-13 30'-40'		7.12	10	<1	0.04	<10	0.37	1210	2	0.22	5	770	2	0.47	<2	3
02-13 40'-50'		4.26	10	<1	0.06	<10	0.54	946	1	0.30	11	750	<2	0.12	2	6
02-14 80'-90'		11.35	10	<1	0.06	<10	0.22	726	1	0.28	8	650	<2	0.06	<2	1
02-14 90'-100'		3.65	10	<1	0.03	<10	0.19	914	3	0.39	6	840	4	0.10	<2	2
02-15 60'-70'		>15.0	10	<1	0.02	<10	0.16	1165	2	0.16	19	570	<2	0.25	<2	2
02-15 80'-90'		2.20	10	<1	0.22	<10	0.29	363	<1	0.52	12	1110	<2	0.05	2	3
02-16 50'-60'		3.65	20	<1	0.17	<10	0.46	349	1	0.61	5	1150	2	0.21	<2	3
02-16 90'-100'		3.74	20	<1	0.07	<10	1.71	795	1	0.44	17	660	4	0.10	<2	10
02-17 0'-10'		>15.0	20	<1	0.01	<10	0.18	1090	5	0.02	15	170	17	0.98	<2	<1

ALS Chemex
EXCELLENCE IN ANALYTICAL CHEMISTRY
ALS Canada Ltd.
212 Brooksbank Avenue
North Vancouver BC V7J 2C1 Canada
Phone: 604 984 0221 Fax: 604 984 0218

: HOMEGOLD RESOURCES LTD.
UNIT #5, 2330 TYNER ST.
PORT COQUITLAM BC V3C 2Z1

Date : 10-Jan-2003
Account: MWE

Project : Iron Ross

CERTIFICATE OF ANALYSIS VA02007604

Sample Description	Method / Analyte / Units / LOR	ME-ICP41 Sr ppm 1	ME-ICP41 Ti % 0.01	ME-ICP41 Tl ppm 10	ME-ICP41 U ppm 10	ME-ICP41 V ppm 1	ME-ICP41 W ppm 10	ME-ICP41 Zn ppm 2
02-04 50'-60'		323	0.04	<10	<10	18	<10	75
02-06 0'-10'		83	0.10	<10	<10	63	<10	53
02-07 30'-40'								
02-08 10'-20		295	0.03	<10	<10	18	<10	37
02-10 10'-20'		114	0.06	<10	<10	28	<10	30
02-12 80'-90'		172	0.10	<10	<10	27	<10	49
02-12 90'-100'		323	0.22	<10	<10	71	<10	53
02-13 0'-10'		324	0.03	<10	10	8	<10	81
02-13 30'-40'		207	0.06	<10	10	36	<10	46
02-13 40'-50'		197	0.08	<10	10	71	<10	50
02-14 80'-90'		202	0.07	<10	10	31	10	51
02-14 90'-100'		180	0.07	<10	10	21	<10	40
02-15 60'-70'		118	0.09	<10	10	57	10	202
02-15 80'-90'		197	0.11	<10	10	38	<10	39
02-16 50'-60'		207	0.09	<10	10	43	<10	44
02-16 90'-100'		269	0.13	<10	10	135	<10	132
02-17 0'-10'		14	0.02	<10	30	18	10	80

APPENDIX IV

DRILL LOGS, 2002

January 31, 2004

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 25, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #1, Location: Trench #1, South End Near Access Road

Visual Log

0-10	Limestone, White dust & chips
10-20	Limestone, White dust & chips
20-30	Limestone, White dust & chips
30-40	Limestone, Darker dust & chips, Minor skarn
40-50	45 Contact, Limestone
45-50	Wet Yellow Mud, Only material coming to surface,

End Of Hole at 50' (no return)

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 25, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #2, Location: On Magnetite Outcrop -68° Dust & Chips

Visual Log

0-10	0-2' Magnetite (black) 2-6' White Limestone 6-10' Magnetite (black)
10- 20	10-18' Magnetite black 18-19' white limestone 19-20' Magnetite (black)
20-30	20-23' "Lighter black" disseminated magnetite 23-26' White 26-28' Darker lighter black 4" of white 28-30' Magnetite (black)

End Of Hole 30 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 25, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #3, Location: South End of Second Trench in Magnetite

Visual Log

0-10	Magnetite, Mostly very black
10-20	10-12' Magnetite (black) 12-14' Lighter black (disseminated Magnetite 14-20' Magnetite Black mostly
20-30	20-24' Magnetite (black) 24-30' Limestone, Dark grey – light grey
	End Of Hole 30 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 26, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #4, Location: On New Upper Road

Visual Log

0-10	Limestone (White dust)
10-20	Limestone (White dust)
20-30	Limestone (White dust)
30-40	Limestone (White dust)
40-50	Greenish chips starting at 46'-48' (Green Skarn)
50-60	58'-60' Very soft, green skarn Brown garnet Green skarn
60-70	Early 60's brown & wet, take sample at 60'-62' 62' –Yellowish brown mud 64'-67' Very soft 67' Mud
70-80	Yellow mud, No Return
	End Of Hole 80 feet (wet at bottom)

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 26, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #5, Location: -58° Angle Hole Toward 182° at Same Location as 4

Visual Log

0-20	Limestone, white dust
20-40	Limestone, white dust
40-50	Limestone, white dust
40-50	Limestone, white dust
50-60	Limestone, white dust
60-70	Limestone, white dust
70-80	Limestone, white dust

End Of Hole 80 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #6 Location: Halfway Down Access Road at Bend

Visual Log

0-10	Intrusive, Greenish dust
10-20	Intrusive, Greenish dust *Hit Cave at 17' No return*
	No Return Bit in mud/clay

Start New Hole 2m East of 6

End Of Hole 20 feet
(mud seam)

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #6a, Location: 2m East of 6

Visual Log

0-10	Limestone & Garnet, Intrusive
10-20	Hit mud seam
20-30	

End Of Hole 30 feet
(mud seam)

IRON ROSS MAGNETITE
DRILL RECORD

Date: October , 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #6b, Location:

Visual Log

Hit mud seam 20 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #7, Location: On Main Road Near Trench #2

Visual Log

0-10	Dark skarn, Intrusive
10-20	Dark Intrusive, Skarn
20-30	Dark Intrusive, Skarn
30-40	Dark Intrusive, Skarn
40-50	Dark Intrusive, Skarn
50-60	At 53' Magnetite rubble, black dust 53-55: 1½' - 2' Magnetite Garnet
60-70	Limestone Cavity 67'-70'
	End Of Hole 70 feet (cavity)

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 26-27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #8, Location: Trench 2 Near Magnetite Outcrop

Visual Log

0-10	0-8' Broken rock at top (limestone) Limestone, White dust 8-10' Cavity
10-20	Sample red garnet 19-20' Magnetite (black dust) for 1 foot
20-24	Magnetite & red garnet
24-30	Fix drill, No return, Loss of Hole
	End of Hole 30 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #9, Location: Halfway Down First New Trench in Magnetite Subcrop

Visual Log

0-10	Black dust 0-6' Magnetite 6-10' White dust/green, Limestone & skarn
10-20	Greenish dust, some white chips
	End of Hole 20 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #10, Location: On East Side of New Tote Road

Visual Log

0-10	0-5' Green intrusive 5-10' White limestone chips
10-20	10-18' Brown garnet?, minor magnetite 18-20' Whitish, Green chips
20-30	20-26 Magnetite, Black dust 26-28 Garnet 28-30 Green chips
30-40	Lots of Magnetite & garnet in sample Could be caved material Green chips & dust

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 27, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #11, Location: Halfway up Trench, 2nd Feb. Trench

Visual Log

0-10	Broken skarn intrusive at surface Limestone 6 ft down 6-10' Limestone plus significant brown skarn
10-20	Light grey dust Light green chips
20-30	Light grey dust Coarse limestone chips at end
30-40	Darker dust Marked less dust "Seam" contact at about 34" Magnetite 34'-40'
40-50	Magnetite 40'-45' 45'-46' Garnet 46'-50' White dust
50-60	Light grey dust Limestone & Calc-silicates, garnet
	End of Hole 60 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 28, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #12, Location: Vertical Hole at End of Trench

Visual Log

0-10	Limestone powder
10-20	Limestone, dark limestone
20-30	Limestone powder Some dark chips
30-40	Limestone
40-50	Limestone, dark powder (limestone?)
50-60	Light green chips
60-70	White limestone powder
70-80	Greenish chips Contact at 78', garnet
80-90	Light green
90-100	90-95' Red-brown garnet Light green chips Garnet & limestone
	End Of Hole 100 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 28, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #13, Location: Halfway Up First Feb. Trench

Visual Log

0-10	Skarnified intrusive & limestone broken at surface to 8', Green chips 8-10' Then white limestone chips
10-20	Red garnet at 17'
20-30	Darker at 22' Magnetite 22'- Skarn Limestone chips Disseminated magnetite?
30-40	Black at 30' to 36', weak disseminated magnetite? 36' Green skarn & red 38'-40' White & red dust
40-50	Green skarn 40'-45' Magnetite 45'-47' Red dust 47'-50'
50-60	Early 50's green skarn? 55' Red garnet to 56' Green skarn & red 56'-57' 57'-60 Solid magnetite
60-70	Solid magnetite 60'-65' Skarny magnetite 65'-66' Solid Magnetite 66'-69' 69'-70' Green chips, skarn
57-70	13 feet
70-80	Hit water Magnetite chips on board No dust
	End Of Hole 80 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 28, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #14, Location:

Visual Log

0-10	Dyke intrusive, green chips
10-20	11' Start of white limestone
20-30	White Limestone & dark limestone
30-40	Limestone

45 Contact
Wet Yellow Mud

End Of Hole 50 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October 28, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #14A, Location:

Visual Log

0-10	Dyke intrusive, green chips
10-20	14' Start of white limestone
20-30	White Limestone & dark limestone
30-40	Limestone 39' – green skarn?
40-50	Limestone & skarn 40'-44' 44'-45' Magnetite to 50' 43'-50' = 15'
50-60	Solid magnetite 50'-58' massive magnetite 58'-59.6' Limestone skarn 59.5'-60' Magnetite
60-70	60'64' Magnetite 64'-67.5' Green skarn 67.5'-70' Magnetite
70-80	70'-73' Magnetite 73' Green skarn & white limestone
80-90	Green skarn 80'-81.5' Magnetite 81.5'-83' Magnetite 83'-89' Green skarn
90-100	Green skarn
	End Of Hole 100 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October , 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #15 & 15A, Location: End of Trench #1

Visual Log

15A	Struck Limestone above 48' Hit magnetite
50-60	48'-52' Magnetite, Black dust 52'-60' Green skarn
60-70	Green skarn 63'-65' Garnet 65'-66' Magnetite, Black dust 66'-68' Garnet – green skarn 68'-70' Magnetite, Black dust
70-80	70'-74.5' Magnetite, Black dust 74.5'-75' Green skarn 75'-78' Magnetite, Black dust 78'-78.5' Red skarn, garnet 78.5'-80' Magnetite, Black dust
80-90	Skarn, green chips, green dust
	End of Hole 90 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: October , 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged by J.T. Shearer, M.Sc.,P.Geo.

HOLE #16, Location: Halfway Between 15 & 13, 16.8m From 14

Visual Log

0-10	Limestone, white
10-20	Limestone & skarn
20-30	Limestone & skarn
30-40	Massive black magnetite at 34' 34'-50' = 16' of solid magnetite
40-50	14'-47' Solid massive magnetite 47'-50' Skarn & magnetite
50-60	Green & white skarn 50'-55' White limestone 55'-57' Garnet skarn 57'-60' Green skarn & limestone, minor magnetite
60-70	Garnet & green skarn Darker dust at 64', disseminated magnetite 68'-68' Massive magnetite 68-68.5' Skarn 68.5'-70' Massive magnetite
70-80	70'-78' Solid massive magnetite 78'-79 White 79'-79.5' Red garnet & magnetite 79.5'-80' Magnetite
80-90	80'-84' White limestone, red garnet skarn, light green skarn 84'-86' Magnetite 86'-90' Green skarn, disseminated magnetite
90-100	90'-97' Green skarn 97'-98' Garnet skarn 98-200' Green skarn
	End Of Hole 100 feet

IRON ROSS MAGNETITE
DRILL RECORD

Date: November 1, 2002
Project: Iron Ross; Location: Sayward Area
Drill: Rockpro Airtrac
Chip Samples Taken Every 10 Feet, Logged From Cuttings and Drillers
Observations by J.T. Shearer, M.Sc.,P.Geo.

HOLE #17, Location: At Sawcut Showing 500m East of Iron Ross
45° Hole Toward 110°, 30' from Showing

Visual Log

0-10	Magnetite, Black dust?
10-20	Dark Limestone chips, 2 feet of magnetite
20-30	Dark Limestone chips
30-40	
40-50	White Chips, Limestone

APPENDIX IV

DRILL LOGS, 2003

January 31, 2004

Drillhole Summary, Sayward Magnetite Project, Sept/03

Hole #	From ft.	To ft.	Thickness ft.	Remarks	From metres	To metres
1	0	10	10	Dark Grey to Black	0	3.05
	10	20	10	Dark Grey to Black	3.05	6.10
	20	30	10	Variable, dull, some white	6.10	9.15
	30	36	6	Dark Grey	9.15	10.98
	36	41	5	Buff to White	10.98	12.50
	41	46	5	Light Greyish Green	12.50	14.02
2	0	12	12	Lmst; soft, no returns, stuck	0.00	3.66
3	0	12	12	Lmst; soft;	0.00	3.66
	12	15	3	Lmst; soft;	3.66	4.57
	15	18	3	Greenish, soft;	4.57	5.49
	18	22	4	White to grey (lmst?)	5.49	6.71
	22	31	9	Greenish, white; harder	6.71	9.45
	31	32	1	White to grey (lmst?)	9.45	9.76
	32	36	4	Dark grey to black (lmst)	9.76	10.98
	36	48	12	Hole wandering; stopped	10.98	14.63
4	0	6	6	Lmst; white	0.00	1.83
	6	12	6	Lmst; white	1.83	3.66
	12	15	3	White	3.66	4.57
	15	18	3	White	4.57	5.49
	18	24	6	White	5.49	7.32
	24	30	6	Green to light brown	7.32	9.15
	30	35	5	Greenish	9.15	10.67
	35	42	7	White	10.67	12.80
	42	48	6	White; last 2 ft brownish	12.80	14.63
	48	51	3	Greenish grey; hole stopped	14.63	15.55
5	0	12	12	White to light grey	0.00	3.66
	12	18	6	White to light grey;broken	3.66	5.49
	18	24	6	White, 7 ft. void	5.49	7.32
	24	30	6	no returns	7.32	9.15
	30	36	6	abandoned hole	9.15	10.98
6	0	6	6	fill	0.00	1.83
	6	12	6	White	1.83	3.66
	12	18	6	White to light grey;	3.66	5.49
	18	24	6	Hit void; still white showing	5.49	7.32
	24	30	6	Void to 26; no returns;	7.32	9.15
			0	abandoned hole.	0.00	0.00
7	0	6	6	White	0.00	1.83
	6	12	6	White	1.83	3.66
	12	18	6	White to light grey;	3.66	5.49
	18	24	6	Light grey to brownish	5.49	7.32
	24	30	6	White to light grey;	7.32	9.15
	30	36	6	Light grey w\ white	9.15	10.98

	36	42	6	Light grey w\ white	10.98	12.80
	42	48	6	Light grey, 1 to 2 ft void	12.80	14.63
	48	54	6	Light grey, hole wandering	14.63	16.46
				Abandoned hole.		
8	0	6	6	White	0.00	1.83
	6	12	6	White, 2 - 3 ft void	1.83	3.66
	12	18	6	White, 16-18 is void	3.66	5.49
	18	24	6	White, v. soft	5.49	7.32
	24	30	6	White, lost returns; end	7.32	9.15
9	0	7	7	Light grey	0.00	2.13
	7	12	5	Black	2.13	3.66
	12	18	6	Black, small void	3.66	5.49
	18	22	4	Black	5.49	6.71
	22	24	2	Brown	6.71	7.32
	24	30	6	Greyish & brownish	7.32	9.15
	30	36	6	Greyish & brownish	9.15	10.98
	36	42	6	Greyish & brownish	10.98	12.80
	42	48	6	Grey	12.80	14.63
	48	54	6	Grey	14.63	16.46
	54	60	6	Grey	16.46	18.29
	60	66	6	Grey, hole wandering; end	18.29	20.12
10	0	5	5	Black	0.00	1.52
	5	10	5	Black	1.52	3.05
	10	13	3	Black, some grey\white	3.05	3.96
	13	18	5	Brown, grey; 1 ft black	3.96	5.49
	18	22	4	Softer, variable	5.49	6.71
	22	27	5	Mostly magnetite, some waste	6.71	8.23
	27	34	7	Soft; limestone at base	8.23	10.37
	34	37	3	Soft limestone	10.37	11.28
	37	42	5	Orange, then white	11.28	12.80
	42	46	4	White, some greenish	12.80	14.02
	46	52	6	Lmst; soft	14.02	15.85
	52	56	4	Lmst; soft	15.85	17.07
	56	66	10	Skarn; hard	17.07	20.12
	66	70	4	Skarn; hard	20.12	21.34
11	0	5	5	Black	0.00	1.52
	5	10	5	Brown	1.52	3.05
	10	15	5	Black	3.05	4.57
	15	18	3	Brown	4.57	5.49
	18	23	5	Brown	5.49	7.01
	23	24	1	Black	7.01	7.32
	24	30	6	Brown to grey	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
	48	54	6	Grey	14.63	16.46

12	0	6	6	Black	0.00	1.83
	6	12	6	Black	1.83	3.66
	12	18	6	Black, some brown @ 17ft.	3.66	5.49
	18	24	6	Grey	5.49	7.32
	24	26	2	Black	7.32	7.93
	26	30	4	Grey	7.93	9.15
	30	36	6	Grey, (end sampling)	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
13	0	2	2	Black	0.00	0.61
	2	3	1	Brown	0.61	0.91
	3	5	2	Black	0.91	1.52
	5	6	1	Brown	1.52	1.83
	6	12	6	Brown, slight black streaks	1.83	3.66
	12	18	6	Grey	3.66	5.49
	18	24	6	Grey	5.49	7.32
	24	30	6	Grey	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
14	0	6	6	Black	0.00	1.83
	6	10	4	Black	1.83	3.05
	10	18	8	Brown to grey	3.05	5.49
	18	24	6	Grey, some brown	5.49	7.32
	24	30	6	Grey (end sampling)	7.32	9.15
	30	36	6	Grey	9.15	10.98
15	0	2	2	Black	0.00	0.61
	2	4	2	Brown	0.61	1.22
	4	5	1	Black	1.22	1.52
	5	8	3	Brown	1.52	2.44
	8	12	4	Light Brown	2.44	3.66
	12	15	3	Brown	3.66	4.57
	15	18	3	Black	4.57	5.49
	18	22	4	Black	5.49	6.71
	22	30	8	Grey	6.71	9.15
	30	36	6	Grey	9.15	10.98
	36	39	3	Grey	10.98	11.89
	39	42	3	Brown	11.89	12.80
	42	48	6	Light Brown to grey	12.80	14.63
16	0	6	6	Light brown	0.00	1.83
	6	12	6	Light brown to grey	1.83	3.66
	12	18	6	Grey	3.66	5.49
	18	24	6	Grey	5.49	7.32
	24	30	6	Grey	7.32	9.15
	30	36	6	Grey	9.15	10.98

17	0	6	6	Black	0.00	1.83
	6	12	6	Brown	1.83	3.66
	12	18	6	Brown w\1 to 2 ft black streak	3.66	5.49
	18	24	6	Brown to grey	5.49	7.32
	24	30	6	Grey	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
18	0	6	6	Light brown to grey	0.00	1.83
	6	12	6	Light brown to grey	1.83	3.66
	12	20	8	Black	3.66	6.10
	20	24	4	Grey w\ brown streaks	6.10	7.32
	24	30	6	Grey w\ brown streaks	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
19	0	6	6	Till	0.00	1.83
	6	12	6	Grey, slightly brown	1.83	3.66
	12	18	6	Grey	3.66	5.49
	18	24	6	Grey	5.49	7.32
	24	30	6	Grey	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
20	0	6	6	Till	0.00	1.83
	6	12	6	Grey, slightly brown	1.83	3.66
	12	18	6	Grey	3.66	5.49
	18	24	6	Grey	5.49	7.32
	24	30	6	Grey	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
21	0	6	6	Grey	0.00	1.83
	6	12	6	Grey	1.83	3.66
	12	18	6	Grey	3.66	5.49
	18	24	6	Grey	5.49	7.32
	24	30	6	Grey	7.32	9.15
	30	36	6	Grey	9.15	10.98
	36	42	6	Grey	10.98	12.80
	42	48	6	Grey	12.80	14.63
22	0	6	6	Lmst.; soft	0.00	1.83
	6	10	4	Lmst.; soft	1.83	3.05
	10	15	5	Lmst.; soft	3.05	4.57
	15	22	7	Lmst.; soft	4.57	6.71
	22	28	6	Harder; grey to buff	6.71	8.54

	28	34	6	Grey	8.54	10.37
	34	40	6	Greenish grey	10.37	12.20
	40	46	6	Greenish grey	12.20	14.02
	46	52	6	Greenish grey	14.02	15.85
	52	58	6	Greenish grey	15.85	17.68
	58	64	6	Greenish grey	17.68	19.51
	64	70	6	Greenish grey	19.51	21.34
23	0	12	12	Fill : no returns	0.00	3.66
	12	24	12	No returns	3.66	7.32
	24	30	6	Soft; brownish w\white chunks	7.32	9.15
	30	36	6	Greenish grey; harder; last 4 ft.	9.15	10.98
				soft; poor returns		
	36	37	1	Soft lmst.	10.98	11.28
	37	38	1	Dropped into a void; abandon	11.28	11.59
24	0	5	5	Black	0.00	1.52
	5	6	1	White	1.52	1.83
	6	10	4	White	1.83	3.05
	10	18	8	Black	3.05	5.49
	18	22	4	Brown to Buff; hard	5.49	6.71
	22	26	4	Brown to Buff; hard	6.71	7.93
	26	27	1	Black	7.93	8.23
	27	28	1	Buff	8.23	8.54
	28	34	6	Buff, some orange; 1 thin black	8.54	10.37
	34	36	2	Buff	10.37	10.98
	36	36.5	0.5	Black	10.98	11.13
	36.5	40	3.5	Orange	11.13	12.20
	40	46	6	Orange, some grey	12.20	14.02
	46	52	6	Grey, some orange	14.02	15.85
	52	58	6	Grey, some orange	15.85	17.68
25	0	4	4	White lmst.	0.00	1.22
	4	6	2	Black	1.22	1.83
	6	10	4	Black	1.83	3.05
	10	16	6	Orange, some white	3.05	4.88
	16	22	6	White, grey, some orange	4.88	6.71
	22	25	3	White	6.71	7.62
	25	29	4	Black	7.62	8.84
	29	34	5	Black, thin white band	8.84	10.37
	34	37	3	Orange	10.37	11.28
	37	40	3	Greenish grey	11.28	12.20
	40	46	6	Grey	12.20	14.02
	46	52	6	Grey, some orange	14.02	15.85
26	0	6	6	Lmst.	0.00	1.83
	6	10	4	Greenish grey	1.83	3.05
	10	14	4	Greenish grey	3.05	4.27
	14	16	2	Orange bands	4.27	4.88
	16	22	6	Greenish grey	4.88	6.71

27	0	9	9	Road Fill	0.00	2.74
	9	10	1	No returns	2.74	3.05
	10	16	6	Dk Grey w\grn bands;some blk	3.05	4.88
	16	22	6	Dark grey to white	4.88	6.71
	22	28	6	Greenish (wet)	6.71	8.54
	28	34	6	Brownish (wet)	8.54	10.37
	34	40	6	No returns, wet	10.37	12.20
	40	41	1	v. green	12.20	12.50
	41	46	5	Greenish	12.50	14.02
	46	48	2	Greenish	14.02	14.63
	48	49	1	Dark grey	14.63	14.94
	49	52	3	Green & grey mixed	14.94	15.85
	52	55	3	Green & grey; darker	15.85	16.77
28	0	4	4	Fill	0.00	1.22
	4	8	4	White; soft	1.22	2.44
	8	10	2	Magnetite; dirty layers	2.44	3.05
	10	11	1	Green	3.05	3.35
	11	12	1	Black	3.35	3.66
	12	14	2	Black	3.66	4.27
	14	16	2	White	4.27	4.88
	16	22	6	Greenish	4.88	6.71
	22	28	6	Greenish, with grey	6.71	8.54
	28	34	6	Greenish, with grey	8.54	10.37
	34	40	6	Greenish; some white	10.37	12.20
	40	46	6	Greenish; some white	12.20	14.02
29	0	3	3	Fill	0.00	0.91
	3	3.5	0.5	Magnetite	0.91	1.07
	3.5	6	2.5	Soft white lmst.	1.07	1.83
	6	10	4	Greenish wh. W\ blk @9 -10ft.	1.83	3.05
	10	13	3	White	3.05	3.96
	13	14	1	Black	3.96	4.27
	14	15	1	Orange	4.27	4.57
	15	16	1	Green & Black mixed	4.57	4.88
	16	22	6	White; soft; variable;	4.88	6.71
	22	27	5	White; soft; variable;	6.71	8.23
	28	34	6	Green skarn	8.54	10.37
30	0	6	6	Till	0.00	1.83
	6	10	4	Soft; greenish	1.83	3.05
	10	16	6	Greenish; a bit hard	3.05	4.88
	16	22	6	Greenish; a bit hard	4.88	6.71
	22	28	6	Grey and Green	6.71	8.54
	28	34	6	Grey; buff @ 33	8.54	10.37
	34	40	6	Grey and white	10.37	12.20
	40	46	6	Grey and white	12.20	14.02
	46	52	6	Grey and white	14.02	15.85
	52	58	6	Greenish; end of hole	15.85	17.68
31	0	4	4	Road fill	0.00	1.22

	4	10	6	Magnetite; some white particles	1.22	3.05
	10	11	1	Magnetite; dirty; dull	3.05	3.35
	11	16	5	Buff to white	3.35	4.88
	16	22	6	Greenish; end hole	4.88	6.71

Drillhole Summary, Sayward Magnetite Project, Sept/03

Hole #	From ft.	To ft.	Thickness ft.	Remarks	From metres	To metres	Thickness metres	Sample Remarks
1	0	10	10	Dark Grey to Black	0.00	3.05	3.05	Save
	10	20	10	Dark Grey to Black	3.05	6.10	3.05	Save
	20	30	10	Variable, dull, some white	6.10	9.15	3.05	Save
	30	36	6	Dark Grey	9.15	10.98	1.83	Save
	36	41	5	Buff to White	10.98	12.50	1.52	Save
	41	46	5	Light Greyish Green	12.50	14.02	1.52	Save
2	0	12	12	Lmst; soft, no returns, stuck	0.00	3.66	3.66	O.K.
3	0	12	12	Lmst; soft;	0.00	3.66	3.66	O.K.
	12	15	3	Lmst; soft;	3.66	4.57	0.91	O.K.
	15	18	3	Greenish, soft;	4.57	5.49	0.91	O.K.
	18	22	4	White to grey (lmst?)	5.49	6.71	1.22	O.K.
	22	31	9	Greenish, white; harder	6.71	9.45	2.74	O.K.
	31	32	1	White to grey (lmst?)	9.45	9.76	0.30	O.K.
	32	36	4	Dark grey to black (lmst)	9.76	10.98	1.22	O.K.
	36	48	12	Hole wandering; stopped	10.98	14.63	3.66	O.K.
4	0	6	6	Lmst; white	0.00	1.83	1.83	Save
	6	12	6	Lmst; white	1.83	3.66	1.83	Save
	12	15	3	White	3.66	4.57	0.91	Save
	15	18	3	White	4.57	5.49	0.91	Save
	18	24	6	White	5.49	7.32	1.83	Save
	24	30	6	Green to light brown	7.32	9.15	1.83	Save
	30	35	5	Greenish	9.15	10.67	1.52	Save
	35	42	7	White	10.67	12.80	2.13	Save
	42	48	6	White; last 2 ft brownish	12.80	14.63	1.83	Save
	48	51	3	Greenish grey; hole stopped	14.63	15.55	0.91	Save
5	0	12	12	White to light grey	0.00	3.66	3.66	O.K.
	12	18	6	White to light grey;broken	3.66	5.49	1.83	O.K.
	18	24	6	White, 7 ft. void	5.49	7.32	1.83	O.K.
	24	30	6	no returns	7.32	9.15	1.83	O.K.
	30	36	6	abandoned hole	9.15	10.98	1.83	O.K.
6	0	6	6	fill	0.00	1.83	1.83	Save
	6	12	6	White	1.83	3.66	1.83	Save
	12	18	6	White to light grey;	3.66	5.49	1.83	Save
	18	24	6	Hit void; still white showing	5.49	7.32	1.83	Save
	24	30	6	Void to 26; no returns;	7.32	9.15	1.83	Save
			0	abandoned hole.	0.00	0.00	0.00	
7	0	6	6	White	0.00	1.83	1.83	Save
	6	12	6	White	1.83	3.66	1.83	Save
	12	18	6	White to light grey;	3.66	5.49	1.83	Save
	18	24	6	Light grey to brownish	5.49	7.32	1.83	Save
	24	30	6	White to light grey;	7.32	9.15	1.83	Save
	30	36	6	Light grey w\ white	9.15	10.98	1.83	Save
	36	42	6	Light grey w\ white	10.98	12.80	1.83	Save
	42	48	6	Light grey, 1 to 2 ft void	12.80	14.63	1.83	Save
	48	54	6	Light grey, hole wandering	14.63	16.46	1.83	Save
				Abandoned hole.				

Hole #	From ft.	To ft.	Thickness ft.	Remarks	From metres	To metres	Thickness metres	
8	0	6	6	White	0.00	1.83	1.83	O.K.
	6	12	6	White, 2 - 3 ft void	1.83	3.66	1.83	O.K.
	12	18	6	White, 16-18 is void	3.66	5.49	1.83	O.K.
	18	24	6	White, v. soft	5.49	7.32	1.83	O.K.
	24	30	6	White, lost returns; end	7.32	9.15	1.83	O.K.
9	0	7	7	Light grey	0.00	2.13	2.13	Save
	7	12	5	Black	2.13	3.66	1.52	Split 50/50, then
	12	18	6	Black, small void	3.66	5.49	1.83	combine splits
	18	22	4	Black	5.49	6.71	1.22	for assay
	22	24	2	Brown	6.71	7.32	0.61	Save
	24	30	6	Greyish & brownish	7.32	9.15	1.83	Save
	30	36	6	Greyish & brownish	9.15	10.98	1.83	Save
	36	42	6	Greyish & brownish	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
	48	54	6	Grey	14.63	16.46	1.83	Save
	54	60	6	Grey	16.46	18.29	1.83	Save
	60	66	6	Grey, hole wandering; end	18.29	20.12	1.83	Save
10	0	5	5	Black	0.00	1.52	1.52	Split and
	5	10	5	Black	1.52	3.05	1.52	combine
	10	13	3	Black, some grey\white	3.05	3.96	0.91	O.K.
	13	18	5	Brown, grey; 1 ft black	3.96	5.49	1.52	O.K.
	18	22	4	Softer, variable	5.49	6.71	1.22	O.K.
	22	27	5	Mostly magnetite, some waste	6.71	8.23	1.52	O.K.
	27	34	7	Soft; limestone at base	8.23	10.37	2.13	Save
	34	37	3	Soft limestone	10.37	11.28	0.91	Save
	37	42	5	Orange, then white	11.28	12.80	1.52	Save
	42	46	4	White, some greenish	12.80	14.02	1.22	Save
	46	52	6	Lmst; soft	14.02	15.85	1.83	Save
	52	56	4	Lmst; soft	15.85	17.07	1.22	Save
	56	66	10	Skarn; hard	17.07	20.12	3.05	Save
	66	70	4	Skarn; hard	20.12	21.34	1.22	Save
11	0	5	5	Black	0.00	1.52	1.52	Save
	5	10	5	Brown	1.52	3.05	1.52	Save
	10	15	5	Black	3.05	4.57	1.52	Save
	15	18	3	Brown	4.57	5.49	0.91	Save
	18	23	5	Brown	5.49	7.01	1.52	Save
	23	24	1	Black	7.01	7.32	0.30	Save
	24	30	6	Brown to grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
	48	54	6	Grey	14.63	16.46	1.83	Save

Hole #	From ft.	To ft.	Thickness ft.	Remarks	From metres	To metres	Thickness metres	
12	0	6	6	Black	0.00	1.83	1.83	Split and
	6	12	6	Black	1.83	3.66	1.83	combine
	12	18	6	Black, some brown @ 17ft.	3.66	5.49	1.83	O.K.
	18	24	6	Grey	5.49	7.32	1.83	O.K.
	24	26	2	Black	7.32	7.93	0.61	O.K.
	26	30	4	Grey	7.93	9.15	1.22	Save
	30	36	6	Grey, (end sampling)	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
13	0	2	2	Black	0.00	0.61	0.61	Save
	2	3	1	Brown	0.61	0.91	0.30	Save
	3	5	2	Black	0.91	1.52	0.61	Save
	5	6	1	Brown	1.52	1.83	0.30	Save
	6	12	6	Brown, slight black streaks	1.83	3.66	1.83	Save
	12	18	6	Grey	3.66	5.49	1.83	Save
	18	24	6	Grey	5.49	7.32	1.83	Save
	24	30	6	Grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
14	0	6	6	Black	0.00	1.83	1.83	Split and
	6	10	4	Black	1.83	3.05	1.22	combine
	10	18	8	Brown to grey	3.05	5.49	2.44	Save
	18	24	6	Grey, some brown	5.49	7.32	1.83	Save
	24	30	6	Grey (end sampling)	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
15	0	2	2	Black	0.00	0.61	0.61	Split then
	2	4	2	Brown	0.61	1.22	0.61	combine for
	4	5	1	Black	1.22	1.52	0.30	assay
	5	8	3	Brown	1.52	2.44	0.91	Save
	8	12	4	Light Brown	2.44	3.66	1.22	Save
	12	15	3	Brown	3.66	4.57	0.91	Save
	15	18	3	Black	4.57	5.49	0.91	Split and
	18	22	4	Black	5.49	6.71	1.22	combine
	22	30	8	Grey	6.71	9.15	2.44	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	39	3	Grey	10.98	11.89	0.91	Save
	39	42	3	Brown	11.89	12.80	0.91	Save
	42	48	6	Light Brown to grey	12.80	14.63	1.83	Save
16	0	6	6	Light brown	0.00	1.83	1.83	Save
	6	12	6	Light brown to grey	1.83	3.66	1.83	Save
	12	18	6	Grey	3.66	5.49	1.83	Save
	18	24	6	Grey	5.49	7.32	1.83	Save
	24	30	6	Grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
17	0	6	6	Black	0.00	1.83	1.83	O.K.
	6	12	6	Brown	1.83	3.66	1.83	Save
	12	18	6	Brown w\1 to 2 ft black streak	3.66	5.49	1.83	Save
	18	24	6	Brown to grey	5.49	7.32	1.83	Save
	24	30	6	Grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save

Hole #	From ft.	To ft	Thickness ft	Remarks	From metres	To metres	Thickness metres	
18	0	6	6	Light brown to grey	0.00	1.83	1.83	Save
	6	12	6	Light brown to grey	1.83	3.66	1.83	Save
	12	20	8	Black	3.66	6.10	2.44	Save
	20	24	4	Grey wh brown streaks	6.10	7.32	1.22	Save
	24	30	6	Grey wh brown streaks	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
19	0	6	6	Till	0.00	1.83	1.83	Save
	6	12	6	Grey, slightly brown	1.83	3.66	1.83	Save
	12	18	6	Grey	3.66	5.49	1.83	Save
	18	24	6	Grey	5.49	7.32	1.83	Save
	24	30	6	Grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
20	0	6	6	Till	0.00	1.83	1.83	Save
	6	12	6	Grey, slightly brown	1.83	3.66	1.83	Save
	12	18	6	Grey	3.66	5.49	1.83	Save
	18	24	6	Grey	5.49	7.32	1.83	Save
	24	30	6	Grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
21	0	6	6	Grey	0.00	1.83	1.83	Save
	6	12	6	Grey	1.83	3.66	1.83	Save
	12	18	6	Grey	3.66	5.49	1.83	Save
	18	24	6	Grey	5.49	7.32	1.83	Save
	24	30	6	Grey	7.32	9.15	1.83	Save
	30	36	6	Grey	9.15	10.98	1.83	Save
	36	42	6	Grey	10.98	12.80	1.83	Save
	42	48	6	Grey	12.80	14.63	1.83	Save
22	0	6	6	Lmst.; soft	0.00	1.83	1.83	O.K.
	6	10	4	Lmst.; soft	1.83	3.05	1.22	O.K.
	10	15	5	Lmst.; soft	3.05	4.57	1.52	O.K.
	15	22	7	Lmst.; soft	4.57	6.71	2.13	O.K.
	22	28	6	Harder; grey to buff	6.71	8.54	1.83	O.K.
	28	34	6	Grey	8.54	10.37	1.83	O.K.
	34	40	6	Greenish grey	10.37	12.20	1.83	O.K.
	40	46	6	Greenish grey	12.20	14.02	1.83	O.K.
	46	52	6	Greenish grey	14.02	15.85	1.83	O.K.
	52	58	6	Greenish grey	15.85	17.68	1.83	O.K.
	58	64	6	Greenish grey	17.68	19.51	1.83	O.K.
	64	70	6	Greenish grey	19.51	21.34	1.83	O.K
23	0	12	12	Fill : no returns	0.00	3.66	3.66	
	12	24	12	No returns	3.66	7.32	3.66	O.K.
	24	30	6	Soft; brownish white chunks	7.32	9.15	1.83	O.K.
	30	36	6	Greenish grey; harder; last 4 ft.	9.15	10.98	1.83	O.K.
				soft; poor returns				O.K.
	36	37	1	Soft lmst.	10.98	11.28	0.30	O.K.
	37	38	1	Dropped into a void; abandon	11.28	11.58	0.30	O.K.
Hole #	From ft.	To ft	Thickness ft	Remarks	From metres	To metres	Thickness metres	
24	0	5	5	Black	0.00	1.52	1.52	O.K.
	5	6	1	White	1.52	1.83	0.30	Save
	6	10	4	White	1.83	3.05	1.22	Save
	10	18	8	Black	3.05	5.49	2.44	O.K.
	18	22	4	Brown to Buff, hard	5.49	6.71	1.22	Split and
	22	26	4	Brown to Buff, hard	6.71	7.93	1.22	combine
	26	27	1	Black	7.93	8.23	0.30	O.K.
	27	28	1	Buff	8.23	8.54	0.30	Save
	28	34	6	Buff, some orange; 1 thin black	8.54	10.37	1.83	Save
	34	36	2	Buff	10.37	10.98	0.61	Save
	36	36.5	0.5	Black	10.98	11.13	0.15	Save
	36.5	40	3.5	Orange	11.13	12.20	1.07	Save
	40	46	6	Orange, some grey	12.20	14.02	1.83	Save
	46	52	6	Grey, some orange	14.02	15.85	1.83	Save
	52	58	6	Grey, some orange	15.85	17.68	1.83	Save
25	0	4	4	White lmst.	0.00	1.22	1.22	Save
	4	6	2	Black	1.22	1.83	0.61	Split and
	6	10	4	Black	1.83	3.05	1.22	combine
	10	16	6	Orange, some white	3.05	4.88	1.83	Save
	16	22	6	White, grey, some orange	4.88	6.71	1.83	Save
	22	25	3	White	6.71	7.62	0.91	Save
	25	29	4	Black	7.62	8.84	1.22	Split and
	29	34	5	Black, thin white band	8.84	10.37	1.52	combine
	34	37	3	Orange	10.37	11.28	0.91	Save
	37	40	3	Greenish grey	11.28	12.20	0.91	Save
	40	46	6	Grey	12.20	14.02	1.83	Save
	46	52	6	Grey, some orange	14.02	15.85	1.83	Save
26	0	6	6	Lmst.	0.00	1.83	1.83	Save
	6	10	4	Greenish grey	1.83	3.05	1.22	Save
	10	14	4	Greenish grey	3.05	4.27	1.22	Save
	14	16	2	Orange bands	4.27	4.88	0.61	Save
	16	22	6	Greenish grey	4.88	6.71	1.83	Save
27	0	9	9	Road Fill	0.00	2.74	2.74	
	9	10	1	No returns	2.74	3.05	0.30	
	10	16	6	Dk Grey w/grn bands;some blk	3.05	4.88	1.83	O.K
	16	22	6	Dark grey to white	4.88	6.71	1.83	O.K.
	22	28	6	Greenish (wet)	6.71	8.54	1.83	O.K.
	28	34	6	Brownish (wet)	8.54	10.37	1.83	O.K.
	34	40	6	No returns, wet	10.37	12.20	1.83	O.K.
	40	41	1	v. green	12.20	12.50	0.30	O.K.
	41	46	5	Greenish	12.50	14.02	1.52	O.K.
	46	48	2	Greenish	14.02	14.63	0.61	O.K.
	48	49	1	Dark grey	14.63	14.94	0.30	O.K.
	49	52	3	Green & grey mixed	14.94	15.85	0.91	O.K.
	52	55	3	Green & grey; darker	15.85	16.77	0.91	O.K.

Hole #	From ft.	To ft.	Thickness ft.	Remarks	From metres	To metres	Thickness metres	
28	0	4	4	Fill	0.00	1.22	1.22	
	4	8	4	White; soft	1.22	2.44	1.22	
	8	10	2	Magnetite; dirty layers	2.44	3.05	0.61	O.K.
	10	11	1	Green	3.05	3.35	0.30	O.K.
	11	12	1	Black	3.35	3.66	0.30	Split and
	12	14	2	Black	3.66	4.27	0.61	combine
	14	16	2	White	4.27	4.88	0.61	O.K.
	16	22	6	Greenish	4.88	6.71	1.83	O.K.
	22	28	6	Greenish, with grey	6.71	8.54	1.83	O.K.
	28	34	6	Greenish, with grey	8.54	10.37	1.83	O.K.
	34	40	6	Greenish; some white	10.37	12.20	1.83	O.K.
	40	46	6	Greenish; some white	12.20	14.02	1.83	O.K.
29	0	3	3	Fill	0.00	0.91	0.91	O.K.
	3	3.5	0.5	Magnetite	0.91	1.07	0.15	O.K.
	3.5	6	2.5	Soft white lmst.	1.07	1.83	0.76	O.K.
	6	10	4	Greenish wh. W\ blk @9 -10ft.	1.83	3.05	1.22	O.K.
	10	13	3	White	3.05	3.96	0.91	O.K.
	13	14	1	Black	3.96	4.27	0.30	O.K.
	14	15	1	Orange	4.27	4.57	0.30	O.K.
	15	16	1	Green & Black mixed	4.57	4.88	0.30	O.K.
	16	22	6	White; soft; variable;	4.88	6.71	1.83	O.K.
	22	27	5	White; soft; variable;	6.71	8.23	1.52	O.K.
	28	34	6	Green skarn	8.54	10.37	1.83	O.K.
30	0	6	6	Till	0.00	1.83	1.83	
	6	10	4	Soft; greenish	1.83	3.05	1.22	Save
	10	16	6	Greenish; a bit hard	3.05	4.88	1.83	Save
	16	22	6	Greenish; a bit hard	4.88	6.71	1.83	Save
	22	28	6	Grey and Green	6.71	8.54	1.83	Save
	28	34	6	Grey; buff @ 33	8.54	10.37	1.83	Save
	34	40	6	Grey and white	10.37	12.20	1.83	Save
	40	46	6	Grey and white	12.20	14.02	1.83	Save
	46	52	6	Grey and white	14.02	15.85	1.83	Save
	52	58	6	Greenish; end of hole	15.85	17.68	1.83	Save
31	0	4	4	Road fill	0.00	1.22	1.22	
	4	10	6	Magnetite; some white particles	1.22	3.05	1.83	O.K.
	10	11	1	Magnetite; dirty; dull	3.05	3.35	0.30	O.K.
	11	16	5	Buff to white	3.35	4.88	1.52	Save
	16	22	6	Greenish; end hole	4.88	6.71	1.83	Save

APPENDIX VI

RAW FIELD DATA for GROUND MAGNETOMETER SURVEY

January 31, 2004

OMNI-PLUS Tie-line MAG/VLF V12N Ser #418141
TOTAL FIELD DATA (uncorrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 5 JUN 3
Operator: 3000
Records: 27
Bat: 17.2 Volt Lithium: 3.48 Volt
Last time update: 6/05 14:29:00
Start of print: 6/05 16:47:07

Line 1 Date 5 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
2	56467.6	.19	1468 0.0	14:34:23	88	1468
3	56133.8	.04	1134 0.0	14:37:43	88	1134
4	56088.5	.04	1089 0.0	14:39:44	88	1089
5	55960.5	.04	0961 0.0	14:41:06	88	
6	55890.1	.04	890 0.0	14:42:40	88	
7	55882.1	.05	882 0.0	14:43:30	88	
8	55915.4	.04	915 0.0	14:44:33	88	
9	55937.3	.04	937 0.0	14:45:19	88	
10	56018.4	.04	1018 0.0	14:46:34	88	
11	56090.2	.04	1090 0.0	14:47:22	88	

Line 2 Date 5 JUN 3 #11

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
22	55441.2	.04	441 0.0	14:53:08	88	65
33	55258.5	.04	259 0.0	14:59:16	88	
43	56079.0	.05	1079 0.0	15:00:39	88	
53	58360.3	.06	3360 0.0	15:01:54	88	
63	58545.8	.06	3546 0.0	15:02:45	88	65
73	57061.6	.05	2062 0.0	15:03:37	88	
83	56500.4	.06	1500 0.0	15:04:35	88	85
93	56202.3	.05	1202 0.0	15:05:33	88	55
103	55540.0	.06	540 0.0	15:06:10	88	65

Line 3 Date 5 JUN 3 #20

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
113	54533.2	.05	-467 0.0	15:10:23	88	55
123	55164.9	.07	165 0.0	15:12:37	88	65
133	59996.1	.87	4996 0.0	15:13:54	85	55
143	59735.9	.06	4736 0.0	15:15:04	88	66
153	56959.9	.14	1660 0.0	15:16:38	76	
163	69404.2	13.	14,404 0.0	15:17:51	32	68
173	60224.1	.56	5224 0.0	15:18:50	43	56
183	58859.3	.06	3859 0.0	15:19:47	86	

EOF

adjusted values layer adjustment = −55,000

OMNI-IV Tie-line MAG Ser #418141
TOTAL FIELD DATA (Base stn. corrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 6 JUN 3
Operator: 3000
Records: 231
Bat: 17.1 Volt Lithium: 3.48 Volt
Last time update: 6/06 8:18:00
Start of print: 6/06 19:16:25

Base stn. Pos: 1 Line: -1
Last time update: 6/04 13:09:00
Start of print: 6/06 19:17:06

3A.

Line 35 Date 6 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
11	53511.9	.13	755.0	8:49:14	85	
21	53696.7	.10	756.0	8:50:55	88	
31	54647.3	.04	756.0	8:51:48	88	
41	53702.6	.65	755.1	8:53:15	58	
51	57741.7	2.0	754.9	8:54:20	45	
61	68332.9	.86	755.3	8:55:43	53	
71	57181.6	.39	755.5	8:56:58	48	
81	64219.5	14.	756.2	8:58:03	34	
91	73799.6	43.	756.2	8:59:32	32	
101	75835.2	1.5	755.3	9:01:20	46	
111	75970.5	2.0	755.3	9:02:49	36	
121	75697.6	63.	754.5	9:04:52	32	
131	73290.9	85.	749.5	9:14:08	22	
141	75076.4	1.1	749.4	9:16:26	45	
151	72398.3	81.	748.1	9:19:36	22	

3A

LINE 3.5
chainage = 1+70 m
(on plan scales at 194 m)
why is chainage only 160.??)

Line 4 Date 6 JUN 3 #16

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
11	55086.1	.32	746.4	9:26:23	53	
21	54433.4	.04	746.6	9:29:24	88	
31	54380.8	.04	746.8	9:30:08	88	
41	54253.0	.05	747.0	9:31:02	88	
51	53891.7	.05	747.5	9:32:11	88	
61	52938.5	.06	747.1	9:33:28	88	
71	52089.9	.09	746.8	9:34:08	88	
81	48216.9	.20	746.2	9:36:26	86	
91	47079.2	.30	746.4	9:37:50	57	
101	48277.8	.29	746.6	9:38:35	78	
111	51013.1	.14	747.4	9:39:50	78	
121	52386.0	.05	747.4	9:40:28	88	
131	52946.9	.05	746.9	9:41:07	88	
141	55775.2	.36	746.4	9:41:37	68	
151	54100.6	.10	746.1	9:41:58	78	

Line 5 Date 6 JUN 3 #31

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55156.7	.04	746.7	9:47:23	88	
20	55137.0	.04	745.8	9:49:39	88	
30	55165.6	.04	745.9	9:50:36	88	
40	55432.1	.04	745.5	9:51:35	88	
50	55059.4	.04	745.2	9:52:24	88	
60	54693.6	.04	744.6	9:53:29	88	
70	54458.8	.04	744.4	9:54:10	88	
80	54075.6	.04	743.9	9:55:03	88	
90	53217.1	.07	743.8	9:55:38	87	

Line 6 Date 6 JUN 3 #60

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55126.5	.05	741.9	9:58:16	88	
20	55129.3	.04	740.6	10:00:17	88	
30	55093.0	.04	740.2	10:00:52	88	

133	50	55132.5	.04	739.6	10:02:18	88
070	60	55069.6	.05	739.6	10:03:18	88
062	70	55062.1	.05	740.1	10:04:14	88
097	80	55096.9	.05	739.8	10:05:10	88
179	90	55178.9	.04	739.5	10:06:01	88
526	100	55526.1	.04	739.5	10:06:52	88
546	110	55546.0	.04	739.4	10:07:35	88
765	120	55764.7	.04	738.9	10:08:39	88

Line 7 Date 6 JUN 3 #52

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
730 11	55730.3	.03	735.0	10:18:28	88	
790 21	55790.1	.03	733.2	10:21:24	88	
752 31	55751.5	.04	732.3	10:22:30	88	
648 41	55648.0	.06	732.6	10:23:14	88	
531 51	55530.9	.04	732.6	10:24:16	88	
449 61	55448.7	.04	732.3	10:24:57	88	
308 71	55307.6	.05	732.1	10:25:38	88	
793 81	55793.4	.04	732.0	10:26:43	88	
600 91	55599.9	.05	731.2	10:27:26	88	
388 101	55388.3	.05	731.0	10:28:23	88	

Scales @ 110m ??

Line 8 Date 6 JUN 3 #62

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
023 10	55023.0	.05	730.3	10:31:30	88	
2481 20	57481.0	.10	730.4	10:33:28	88	
557 30	55556.5	.06	730.3	10:34:03	86	
193 40	55193.4	.04	730.5	10:35:09	88	
045 50	55044.7	.05	730.6	10:36:01	88	
121 60	55120.7	.04	730.0	10:38:11	88	
027 70	55027.3	.05	730.9	10:39:12	88	
029 80	55028.7	.04	731.6	10:39:56	88	
040 90	55040.2	.05	732.3	10:40:56	88	

Scales at 100m on plan

Line 9 Date 6 JUN 3 #71

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
282 10	55281.7	.04	732.5	10:42:32	88	
340 20	55340.1	.05	731.3	10:45:01	88	
200 30	55199.8	.04	730.9	10:45:46	88	
112 40	55111.9	.04	730.5	10:46:33	88	
077 50	55077.4	.05	730.3	10:47:08	88	
085 60	55084.5	.05	730.4	10:48:05	88	
077 70	55076.9	.04	730.7	10:48:56	88	
176 80	55176.3	.04	730.9	10:49:41	88	
278 90	55277.9	.05	730.6	10:50:50	88	
381 100	55380.8	.04	730.5	10:52:16	88	
365 110	55365.0	.05	730.4	10:52:57	88	
391 120	54608.5	.06	730.0	10:53:52	88	
143 130	55142.7	.04	729.7	10:54:28	88	

Line 10 Date 6 JUN 3 #84

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55181.8	.05	728.1	10:56:54	88	
20	55199.7	.04	728.1	10:59:14	88	
30	55254.2	.04	728.7	11:00:18	88	
40	55295.1	.05	729.1	11:01:18	88	
50	55245.0	.05	728.7	11:02:11	88	
60	55185.1	.04	729.0	11:03:40	88	
70	55170.8	.04	729.6	11:04:38	88	

Reading indicate only 60m

70m on plan

Line 11 Date 6 JUN 3 #91

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55170.2	.04	729.1	11:06:18	88	
20	55172.3	.04	729.4	11:08:18	88	
30	55281.8	.06	729.2	11:09:13	88	

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
	40	55426.3	.04	729.1	11:09:52	88	
	50	55797.5	.03	729.0	11:10:37	88	

Line 52 Date 6 JUN 3 #96

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
4855	10	59854.7	.13	715.7	12:18:21	85	
669	20	55668.9	.08	715.8	12:20:56	84	
03	30	55003.4	.05	717.5	12:22:19	88	
-50	40	54949.6	.04	718.5	12:23:31	88	
50	50	55050.0	.05	717.7	12:24:33	88	
131	60	55130.5	.04	719.5	12:27:08	88	
194	70	55193.8	.04	720.4	12:27:59	88	
254	80	55254.0	.05	720.3	12:28:34	88	
356	90	55355.9	.05	720.6	12:29:12	88	
475	100	55474.9	.04	720.5	12:30:38	88	
627	110	55626.8	.04	720.7	12:33:38	88	
675	120	55674.6	.04	720.4	12:35:00	88	
236	130	55736.4	.04	720.1	12:36:09	88	
359	140	55858.8	.04	719.5	12:37:04	88	
903	150	55902.7	.03	719.7	12:38:01	88	

Line 56 Date 6 JUN 3 #111

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
905	10	55904.9	.04	719.4	12:40:37	88	
970	20	55970.4	.04	719.4	12:43:04	88	
1038	30	56038.1	.04	720.1	12:43:44	88	
1039	40	56038.5	.04	720.4	12:44:40	88	
1032	50	56031.5	.03	720.2	12:45:09	88	
959	60	55959.1	.03	720.7	12:45:59	88	
949	70	55948.8	.04	719.9	12:46:34	88	
286	80	55285.6	.05	719.3	12:47:24	88	
712	90	55711.9	.04	718.8	12:48:03	88	
814	100	55814.2	.04	718.0	12:48:35	88	
1173	110	56172.9	.03	716.1	12:49:30	88	
387	120	55387.2	.04	715.0	12:50:35	88	
185	130	55184.8	.04	715.5	12:51:39	88	
-20	140	54979.5	.04	717.1	12:52:40	88	
-85	150	54914.6	.04	716.9	12:53:25	88	
450	160	55449.8	.04	716.7	12:54:33	88	
550	170	55549.8	.04	716.8	12:55:42	88	
220	180	55220.2	.04	717.2	12:56:21	88	
076	190	55076.3	.05	717.3	12:57:10	88	

Line 57 Date 6 JUN 3 #130

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
802	10	55802.0	.04	715.6	13:01:14	88	
460	20	55460.1	.04	715.5	13:03:49	88	
252	30	55252.4	.05	716.6	13:04:42	88	
114	40	55113.7	.05	716.8	13:05:25	88	
180	50	55179.9	.04	717.6	13:06:10	88	
115	60	55114.9	.04	718.3	13:07:48	88	
072	70	55071.9	.04	718.9	13:08:24	88	
-04	80	54996.3	.05	720.6	13:09:03	88	
-06	90	54994.3	.05	719.4	13:09:32	88	
123	100	55123.4	.04	717.3	13:10:49	88	
085	110	55085.1	.05	717.4	13:11:26	88	
184	120	55183.6	.04	718.0	13:12:09	88	
691	130	55691.2	.05	718.9	13:13:00	88	
712	140	55712.2	.04	719.7	13:13:42	88	
507	150	55506.9	.04	719.5	13:14:58	88	
1455	160	56455.1	.03	720.2	13:15:35	88	
1145	170	56145.2	.05	720.0	13:16:15	88	
857	180	55856.6	.05	720.3	13:16:53	88	
831	190	55830.8	.04	720.8	13:17:26	88	
860	200	55859.7	.03	720.8	13:18:36	88	
865	210	55865.1	.04	721.5	13:19:21	88	
889	220	55888.5	.04	722.3	13:20:36	88	
899	230	55899.1	.04	720.4	13:21:32	88	
885	240	55885.0	.04	720.7	13:22:24	88	

813	250	55812.6	.04	719.0	13:23:52	88	
760	260	55760.4	.05	719.0	13:24:49	88	
690	270	55690.2	.04	720.3	13:25:42	88	
638	280	55638.0	.04	721.1	13:26:45	88	
855	290	55855.0	.04	721.5	13:27:24	88	
679	300	55678.8	.04	721.4	13:28:13	88	
681	310	55680.8	.03	720.1	13:28:59	88	
673	320	55673.3	.05	718.9	13:29:34	88	
565	330	55565.2	.04	719.9	13:30:17	88	
573	340	55573.1	.04	719.4	13:31:12	88	
615	350	55615.1	.04	719.4	13:32:03	88	
582	360	55581.9	.04	720.9	13:32:48	88	
588	370	55588.1	.04	722.8	13:33:30	88	
575	380	55574.7	.05	724.5	13:34:17	88	
521	390	55521.4	.05	725.6	13:35:16	88	
502	400	55501.6	.04	726.2	13:36:01	88	
488	410	55488.3	.04	725.0	13:36:56	88	

Line 58 Date 6 JUN 3 #171

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
334	10	55333.6	.04	721.9	13:41:55	88	
373	20	55372.8	.05	720.4	13:45:17	88	
424	30	55423.8	.04	720.4	13:46:02	88	
432	40	55432.1	.04	720.8	13:46:42	88	
430	50	55430.3	.04	722.5	13:47:25	88	
454	60	55454.0	.04	724.2	13:48:03	88	
412	70	55411.6	.04	724.3	13:48:39	88	
419	80	55418.8	.04	726.0	13:49:08	88	
449	90	55449.1	.04	725.5	13:49:44	88	
466	100	55465.9	.04	725.5	13:50:15	88	
480	110	55479.7	.04	725.8	13:51:10	88	
518	120	55517.8	.04	724.9	13:52:23	88	
572	130	55572.2	.04	724.5	13:53:02	88	
445	140	55445.3	.04	724.4	13:53:56	88	
471	150	55470.9	.04	723.6	13:54:32	88	
515	160	55514.8	.04	723.8	13:55:06	88	
620	170	55620.2	.04	723.5	13:55:48	88	
763	180	55763.1	.04	723.5	13:56:28	88	
784	190	55784.0	.04	723.5	13:57:13	88	

Line 55 Date 6 JUN 3 #190

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
500	10	55500.0	.04	722.6	14:05:27	88	
601	20	55600.9	.04	722.4	14:07:35	88	
792	30	55791.9	.04	722.1	14:08:16	88	
895	40	55895.0	.03	722.3	14:09:03	88	
884	50	55884.4	.03	721.9	14:09:37	88	
731	60	55730.7	.03	722.1	14:10:20	88	
718	70	55718.3	.04	722.2	14:11:04	88	
769	80	55768.7	.04	722.2	14:11:35	88	
087	90	55086.8	.05	722.1	14:12:30	88	
370	100	55370.3	.04	722.3	14:13:10	88	
1093	110	56092.7	.04	722.1	14:13:47	88	
898	120	55898.0	.05	722.6	14:14:26	88	
561	130	55560.6	.04	723.2	14:17:57	88	
1211	140	56210.5	.04	724.1	14:19:10	88	
1494	150	56494.3	.03	724.8	14:20:04	88	
1540	160	56539.9	.04	724.8	14:20:43	88	
1292	170	56292.3	.05	724.9	14:21:26	88	
1118	180	56118.3	.04	725.7	14:22:06	88	
349	190	55349.1	.04	725.2	14:22:53	88	
-123	200	54976.6	.04	725.3	14:23:41	88	
-271	210	54729.4	.06	725.2	14:24:25	88	
135	220	55135.3	.04	725.4	14:25:09	88	
045	230	55045.4	.04	725.5	14:25:51	88	
-191	240	54808.8	.05	725.7	14:26:33	88	

Line 53 Date 6 JUN 3 #214

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT

JUN6CORR.DMP

10	56491.2	.04	722.1	14:58:11	88
20	55435.2	.04	724.3	15:01:30	88
30	54968.3	.05	725.0	15:02:03	88
40	55040.4	.04	725.3	15:02:46	88
50	54922.7	.04	725.8	15:03:49	88
60	55124.5	.04	725.5	15:04:38	88
70	55211.1	.04	726.4	15:05:43	88
80	55389.8	.04	726.2	15:06:34	88
90	56137.9	.08	727.0	15:07:27	88
100	56656.8	.03	728.5	15:08:12	88
110	56289.5	.04	729.9	15:09:18	88
120	55808.7	.05	730.7	15:10:26	88
130	55402.9	.04	731.3	15:11:28	88
140	54117.4	.06	732.3	15:12:18	88
150	52378.7	.11	734.0	15:13:06	88
160	54010.6	.05	735.5	15:16:06	88
170	55981.9	.05	733.8	15:16:40	88
180	57962.3	.06	732.9	15:17:18	88

not inputted July 21/03

Checksum Error! Record #232

Line 0 Date 6 JUN 3 #232

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT	
0	0.0	.00	0.0	0:00:00	0		0.0

EOF

File Name: Jims\Seyward 2003\

Conjugate new (Showing mag lines).

OMNI-PLUS Tie-line MAG/VLF V12N Ser #418141
TOTAL FIELD DATA (uncorrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 7 JUN 3
Operator: 3000
Records: 204
Bat: 17.3 Volt Lithium: 3.48 Volt
Last time update: 6/06 8:18:00
Start of print: 6/07 16:05:41

Line 53 Date 7 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
190	56369.7	.00	0.0	8:33:02	88	

Line (41) ~~40~~ Date 7 JUN 3 #2 ← Should have been L.41

55000 ↓

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
4947 10	59946.5	.38	0.0	8:46:43	78	65
7007 20	62007.1	2.9	0.0	8:48:26	46	55
5321 30	60320.9	1.1	0.0	8:53:17	48	56
4026 40	59026.6	.18	0.0	8:54:48	78	
4034 50	59034.2	.06	0.0	8:55:38	88	
4844 60	59844.2	.08	0.0	8:56:21	78	
7322 70	62321.6	.16	0.0	8:57:00	78	65
7903 80	62902.6	.17	0.0	8:57:47	88	55
5287 90	60286.5	.04	0.0	8:58:33	87	56
4753 100	59753.3	.05	0.0	8:59:18	88	

Line 42 Date 7 JUN 3 #12

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
462 10	55461.7	.05	0.0	9:02:27	87	
1849 20	55848.6	.19	0.0	9:06:08	78	55
4197 40	59197.3	.38	0.0	9:10:03	68	55
1162 50	56162.1	.05	0.0	9:12:12	87	56
1675 60	56674.7	.14	0.0	9:13:11	88	55
2729 70	57727.7	.02	0.0	9:14:03	88	
5 80	58594.6	.06	0.0	9:15:04	88	65
1 90	58595.4	.03	0.0	9:16:26	88	55
2419 100	57419.1	.03	0.0	9:17:22	88	
1958 110	56958.3	.03	0.0	9:18:20	88	
2349 120	57348.7	.03	0.0	9:20:00	88	
2641 130	57641.0	.03	0.0	9:21:47	88	
2764 140	57764.3	.03	0.0	9:22:43	88	
2359 150	57359.2	.02	0.0	9:23:46	88	
2026 160	57026.4	.03	0.0	9:25:04	88	
2097 170	57097.0	.03	0.0	9:26:22	88	
1872 180	56872.4	.03	0.0	9:27:23	88	
1739 190	56738.8	.03	0.0	9:28:15	88	
1697 200	56697.8	.39	0.0	9:29:04	88	

Line 43 Date 7 JUN 3 #31

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
2251 10	57251.0	.04	0.0	9:42:11	88	
2440 20	57439.5	.02	0.0	9:45:54	88	
2575 30	57575.4	.02	0.0	9:47:29	88	
2769 40	57769.4	.04	0.0	9:48:09	88	
2767 50	57767.1	.03	0.0	9:49:40	88	
2503 60	57503.0	.03	0.0	9:50:41	88	
2417 70	57416.5	.03	0.0	9:52:52	88	65
1881 80	56880.6	.03	0.0	9:54:15	88	55
770 90	55769.9	.05	0.0	9:54:57	88	
-240 100	54760.3	.04	0.0	9:55:40	88	
-1297 110	53703.1	.05	0.0	9:56:35	88	
-679 120	54321.4	.03	0.0	9:57:24	88	
-544 130	54456.1	.03	0.0	9:58:05	88	

-164	140	54836.0	.03	0.0	9:58:41	88	
691	150	55690.6	.05	0.0	9:59:37	88	
1093	160	56092.8	.06	0.0	10:00:22	88	
1382	170	56381.7	.05	0.0	10:01:04	88	
778	180	55778.4	.05	0.0	10:01:44	88	
750	190	55750.1	.04	0.0	10:02:23	88	
894	200	55893.9	.07	0.0	10:03:05	88	
1091	210	56091.4	.04	0.0	10:03:44	88	
903	220	55902.8	.03	0.0	10:04:17	88	

Line 44 Date 7 JUN 3 #53

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
1121 10	56121.1	.03	0.0	10:11:50	88	
948 20	55947.9	.04	0.0	10:16:25	88	
1027 30	56026.5	.04	0.0	10:17:17	88	
1173 40	56172.9	.03	0.0	10:17:56	88	
1007 50	56007.4	.03	0.0	10:18:40	88	
847 60	55846.8	.03	0.0	10:19:39	88	
732 70	55731.5	.04	0.0	10:20:24	88	
553 80	55553.4	.03	0.0	10:21:01	88	
-63 90	54937.3	.04	0.0	10:21:24	88	
-43 100	54956.6	.04	0.0	10:22:03	88	
-369 110	54630.7	.03	0.0	10:22:37	88	
54 120	55054.3	.04	0.0	10:23:13	88	
226 130	55226.1	.04	0.0	10:23:42	88	
653 140	55652.7	.03	0.0	10:24:26	88	
2109 150	57108.8	.03	0.0	10:25:06	88	
2669 160	57669.4	.02	0.0	10:26:00	88	
2790 170	57790.2	.03	0.0	10:27:41	88	
3003 180	58002.8	.02	0.0	10:28:54	88	
3288 190	58288.1	.03	0.0	10:29:57	88	
3178 200	58178.2	.03	0.0	10:31:07	88	
3046 210	58045.7	.03	0.0	10:34:22	88	
2880 220	57879.7	.02	0.0	10:35:08	88	
2451 230	57451.3	.03	0.0	10:36:25	88	
2806 240	57805.9	.03	0.0	10:40:21	88	

Line 45 Date 7 JUN 3 #77

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
1294 10	56293.9	.03	0.0	10:58:16	88	
1217 20	56217.3	.03	0.0	11:01:19	88	
1117 30	56116.7	.03	0.0	11:02:16	88	
1057 40	56057.3	.03	0.0	11:04:23	88	
968 50	55967.6	.03	0.0	11:05:07	88	
882 60	55881.7	.03	0.0	11:06:03	88	
785 70	55785.8	.03	0.0	11:06:48	88	
467 80	55461.8	.04	0.0	11:07:45	88	
120 90	55119.9	.03	0.0	11:08:32	88	
608 100	55608.0	.03	0.0	11:09:57	88	
604 110	55603.9	.03	0.0	11:10:49	88	
612 120	55611.8	.04	0.0	11:11:29	88	
1578 130	56578.1	.05	0.0	11:12:32	88	
2409 140	57407.5	.06	0.0	11:13:51	88	
3056 150	58055.6	.02	0.0	11:15:43	88	
3995 160	58995.1	.03	0.0	11:16:54	88	
4253 170	59252.8	.03	0.0	11:17:59	88	
3721 180	58721.2	.03	0.0	11:20:19	88	56
3046 190	58046.3	.03	0.0	11:22:02	88	55

Line 46 Date 7 JUN 3 #96

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
3328 10	58327.9	.03	0.0	11:28:45	88	
4271 20	59270.5	.03	0.0	11:34:55	88	
4902 30	59901.6	.03	0.0	11:36:03	88	56
4074 40	59073.8	.04	0.0	11:37:36	88	
3032 50	58031.8	.04	0.0	11:38:32	88	
1757 60	56757.2	.05	0.0	11:39:51	88	55
898 70	55897.6	.04	0.0	11:41:02	88	
1239 80	56239.4	.03	0.0	11:42:21	88	

451	90	55451.3	.04	0.0	11:43:22	88	
725	100	55725.1	.03	0.0	11:44:15	88	
623	110	55623.3	.04	0.0	11:44:54	88	
695	120	55675.0	.04	0.0	11:45:45	88	
866	130	55866.1	.03	0.0	11:46:19	88	
970	140	55969.6	.03	0.0	11:46:59	88	
1002	150	56001.6	.04	0.0	11:47:38	88	
1057	160	56056.5	.03	0.0	11:48:25	88	
1112	170	56111.9	.03	0.0	11:49:03	88	
1182	180	56182.3	.03	0.0	11:49:48	88	
1328	190	56328.2	.03	0.0	11:50:26	88	
1227	200	56227.7	.03	0.0	11:50:56	88	

Line 47 Date 7 JUN 3 #116

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
1448	10	56448.3	.04	0.0	11:53:54	88	
1311	20	56311.4	.03	0.0	11:58:35	88	
1255	30	56254.7	.04	0.0	11:59:23	88	
1193	40	56193.1	.03	0.0	12:00:12	88	
1113	50	56112.6	.04	0.0	12:00:56	88	
1054	60	56054.4	.04	0.0	12:02:18	88	
1035	70	56034.6	.03	0.0	12:03:04	88	
982	80	55982.1	.03	0.0	12:03:41	88	
970	90	55969.9	.03	0.0	12:04:34	88	
958	100	55957.6	.03	0.0	12:05:23	88	
942	110	55942.2	.03	0.0	12:06:10	88	
923	120	55921.9	.04	0.0	12:06:55	88	
959	130	55958.5	.03	0.0	12:08:39	88	
1102	140	56102.2	.03	0.0	12:09:29	88	
1304	150	56303.6	.03	0.0	12:10:45	88	
1603	160	56603.4	.02	0.0	12:12:30	88	
1875	170	56874.9	.02	0.0	12:13:41	88	
2015	180	57015.3	.03	0.0	12:22:22	88	
2053	190	57053.4	.03	0.0	12:23:33	88	
1951	200	56950.5	.04	0.0	12:24:55	88	
1802	210	56801.6	.03	0.0	12:25:49	88	
1779	220	56778.5	.03	0.0	12:26:55	88	

Line 48 Date 7 JUN 3 #138

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
2016	10	57016.4	.03	0.0	13:11:39	88	
2155	20	57155.0	.03	0.0	13:13:58	88	65
1835	30	56835.1	.04	0.0	13:15:09	88	55
1419	40	56419.0	.03	0.0	13:16:35	88	65
2085	50	57085.3	.04	0.0	13:18:26	88	55
1874	60	56874.3	.04	0.0	13:19:41	88	
1731	70	56731.3	.03	0.0	13:20:28	88	
1511	80	56511.0	.03	0.0	13:21:14	88	
1396	90	56395.9	.03	0.0	13:22:10	88	
1400	100	56400.3	.02	0.0	13:22:53	88	
1375	110	56374.9	.03	0.0	13:23:35	88	85
1656	120	56655.5	.03	0.0	13:25:51	88	55
1402	130	56441.8	.03	0.0	13:27:08	88	
1481	140	56480.6	.03	0.0	13:29:34	88	65
1355	150	56354.9	.03	0.0	13:30:46	88	55
1339	160	56339.2	.03	0.0	13:31:59	88	
1319	170	56319.1	.03	0.0	13:33:13	88	
1314	180	56314.3	.03	0.0	13:34:06	88	
1319	190	56318.6	.03	0.0	13:36:04	88	
1271	200	56271.0	.03	0.0	13:37:26	88	
1252	210	56251.9	.04	0.0	13:38:55	88	
1223	220	56222.8	.03	0.0	13:39:35	88	
1268	230	56267.5	.03	0.0	13:40:25	88	
1205	240	56205.0	.03	0.0	13:41:18	88	65
1275	250	56275.4	.03	0.0	13:42:13	88	55
1256	260	56256.1	.03	0.0	13:42:57	88	
1256	270	56256.2	.03	0.0	13:44:20	88	
1300	280	56300.3	.03	0.0	13:45:26	88	
1268	290	56268.2	.03	0.0	13:46:58	88	

300	56314.8	.03	0.0	13:47:54	88	

Line 49 Date 7 JUN 3 #168

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	60018.6	.05	0.0	14:07:56	88	
20	67818.5	.55	0.0	14:11:18	77	
30	62975.3	2.0	0.0	14:13:04	67	
40	57876.8	.04	0.0	14:14:00	86	56
50	57059.8	.03	0.0	14:15:12	88	55
60	56616.6	.04	0.0	14:15:59	88	
70	56709.2	.03	0.0	14:16:48	88	
80	56394.1	.03	0.0	14:17:48	88	
90	56297.6	.02	0.0	14:18:47	88	
100	56322.2	.04	0.0	14:19:47	88	
110	56260.3	.02	0.0	14:20:29	88	
120	56226.5	.03	0.0	14:21:14	88	
130	56179.5	.03	0.0	14:21:55	88	
140	56140.4	.04	0.0	14:22:37	88	
150	56047.9	.03	0.0	14:23:38	88	
160	55861.3	.03	0.0	14:24:08	88	
170	55519.1	.04	0.0	14:24:58	88	
180	56350.1	.04	0.0	14:25:54	88	65

Line 50 Date 7 JUN 3 #186

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55187.9	.05	0.0	14:36:16	88	
20	55733.8	.03	0.0	14:38:45	88	
30	55918.6	.03	0.0	14:39:26	88	
40	56025.2	.03	0.0	14:40:03	88	
50	56111.5	.03	0.0	14:40:48	88	
60	56149.0	.03	0.0	14:41:24	88	
70	56171.3	.03	0.0	14:42:07	88	
80	56133.7	.04	0.0	14:42:37	88	
90	56278.6	.03	0.0	14:43:15	88	
100	55957.5	.04	0.0	14:43:50	88	
110	55944.9	.04	0.0	14:44:30	88	
120	55930.9	.04	0.0	14:45:04	88	
130	55895.9	.03	0.0	14:45:49	88	
140	55842.3	.03	0.0	14:46:42	88	
150	55722.6	.03	0.0	14:48:19	88	
160	55706.5	.03	0.0	14:48:56	88	65
170	55267.2	.04	0.0	14:49:26	88	55
180	55293.5	.03	0.0	14:50:10	88	
190	55723.1	.03	0.0	14:50:59	88	

EOF

OMNI-IV Tie-line MAG Ser #418141
TOTAL FIELD DATA (Base stn. corrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 9 JUN 3
Operator: 3000
Records: 169
Bat: 17.2 Volt Lithium: 3.48 Volt
Last time update: 6/09 8:51:00
Start of print: 6/09 18:04:14

Base stn. Pos: 1 Line: -1
Last time update: 6/09 8:23:00
Start of print: 6/09 18:04:27

Line 19 Date 9 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	54721.8	.03	788.1	9:09:19	88	
20	54568.4	.03	787.1	9:16:46	88	
30	54373.4	.03	787.4	9:17:37	88	
40	54156.4	.03	787.8	9:18:05	88	
50	53504.1	.03	789.6	9:20:25	88	
60	52926.5	.04	789.8	9:21:07	88	
70	50668.5	.13	789.8	9:21:51	78	
80	47136.1	1.2	790.4	9:22:27	45	
90	39646.4	1.3	791.2	9:23:20	68	

Line 20 Date 9 JUN 3 #10

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	53176.6	.21	790.9	9:27:46	73	
20	54310.6	.05	791.0	9:29:39	88	
30	54299.6	.05	790.9	9:30:03	88	
40	54396.1	.03	790.9	9:30:28	88	

Line 21 Date 9 JUN 3 #14

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	52223.6	.05	789.7	9:43:24	88	
20	51870.8	.28	789.5	9:46:59	88	
30	55666.7	2.2	789.8	9:47:39	68	
40	58451.5	.07	790.0	9:48:18	88	
50	58001.9	.04	790.1	9:49:09	88	
60	57866.0	.05	789.8	9:49:50	88	
70	57605.8	.03	789.6	9:50:17	88	
80	57005.6	.03	789.3	9:50:53	88	
90	56513.1	.03	789.7	9:53:50	88	
100	56043.0	.03	790.0	9:54:23	88	
110	55892.0	.03	790.4	9:55:24	88	
120	55837.6	.02	790.5	9:56:07	88	
130	54829.5	.48	789.5	9:58:12	78	
140	56333.7	.02	789.6	9:58:53	88	
150	55976.5	.02	789.7	9:59:28	88	
160	55933.1	.03	789.0	10:01:15	88	
170	55930.6	.12	788.9	10:02:01	88	
180	55891.9	.03	788.7	10:02:42	88	
190	55897.6	.03	788.6	10:03:15	88	
200	56305.7	.08	788.9	10:04:02	88	
210	55757.1	.03	787.8	10:05:04	88	
220	55727.9	.02	787.0	10:05:40	88	
230	55689.3	.02	786.5	10:06:22	88	
240	55708.6	.07	786.7	10:07:07	88	
250	55677.7	.02	786.8	10:08:00	88	
260	55689.1	.02	787.2	10:09:09	88	
270	55482.7	.02	787.5	10:09:59	88	
280	55348.0	.03	787.6	10:10:29	88	
290	55625.8	.02	787.1	10:11:31	88	← last rdg does not fit on line.

Line 22 Date 9 JUN 3 #43

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55687.3	.02	784.9	10:17:24	88	
20	55694.6	.02	783.4	10:19:45	88	
30	55728.2	.02	783.1	10:20:21	88	
40	55791.1	.03	782.9	10:21:02	88	
50	55679.5	.02	782.7	10:21:33	88	
60	55397.7	.03	782.2	10:22:20	88	
70	55224.2	.03	781.8	10:23:05	88	
80	54832.5	.03	781.5	10:23:38	88	
90	54262.2	.03	781.0	10:24:12	88	
100	53706.9	.03	778.9	10:26:18	88	
110	53442.3	.03	778.2	10:27:01	88	
120	53694.0	.02	777.5	10:28:32	88	
130	53832.0	.05	777.3	10:29:04	88	
140	51102.7	.50	776.9	10:29:36	68	
150	53476.2	.03	776.5	10:30:12	88	
160	54347.6	.02	776.1	10:30:50	88	
170	54721.9	.03	775.7	10:31:21	88	

Line 23 Date 9 JUN 3 #60

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	54239.6	.03	769.4	10:38:40	88	
20	53752.1	.03	767.7	10:41:21	88	
30	50776.4	.18	767.1	10:41:51	78	
40	52053.2	.05	767.5	10:42:53	88	
50	54301.6	.04	767.3	10:43:23	88	
60	54571.0	.03	766.6	10:44:00	88	
70	55066.3	.03	765.8	10:44:48	88	
80	54892.2	.03	765.1	10:45:24	88	
90	54884.7	.03	766.6	10:47:29	88	
100	55123.2	.03	764.8	10:48:57	88	
110	55318.7	.03	763.9	10:50:05	88	
120	55532.6	.03	765.1	10:51:07	88	

Line 24 Date 9 JUN 3 #72

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	53637.1	.09	768.2	10:59:47	88	
20	53885.7	.03	765.7	11:07:50	88	
30	53927.7	.03	765.8	11:08:24	88	
40	53309.8	.08	765.7	11:09:18	88	
50	53284.9	.04	765.8	11:09:54	88	
60	52679.7	.04	765.9	11:10:33	88	
70	52243.6	.04	765.9	11:11:26	88	
80	52463.6	.03	765.4	11:12:12	88	
90	53433.4	.03	764.1	11:13:22	88	
100	54144.2	.03	764.4	11:14:36	88	
110	54792.6	.03	764.8	11:15:39	88	
120	55307.1	.03	763.7	11:16:37	88	
130	55597.9	.03	762.7	11:17:36	88	

Line 25 Date 9 JUN 3 #85

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	54189.3	.04	764.8	11:20:59	88	
20	53683.4	.04	765.0	11:23:41	88	
30	51995.0	.06	764.8	11:24:56	88	
40	52574.2	.03	765.1	11:25:32	88	
50	52966.7	.02	765.5	11:26:10	88	
60	53846.8	.03	765.7	11:26:49	88	
70	54404.5	.03	765.9	11:27:26	88	
80	54432.4	.04	766.2	11:28:00	88	
90	53861.3	.03	764.9	11:28:27	88	
100	54963.7	.04	763.7	11:28:50	88	
110	54635.0	.03	763.4	11:29:14	88	

Line 26 Date 9 JUN 3 #96

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55341.6	.42	762.5	11:40:27	88	

JUN9CORR

- 5	20	54994.7	.07	761.4	11:42:43	88
277	30	55276.7	.05	761.1	11:43:06	88
732	40	55751.6	.05	761.0	11:43:30	88
2199	50	57199.1	.32	761.0	11:43:53	88
1490	60	56490.1	.46	760.7	11:44:15	58
107	70	55107.1	.05	760.4	11:44:38	88
299	80	55299.3	.03	760.0	11:45:01	88
180	90	55179.8	.03	759.8	11:45:22	88
190	100	55189.5	.03	759.2	11:46:18	88
345	110	55344.7	.03	758.9	11:46:44	88
207	120	55207.0	.03	758.5	11:47:08	88
196	130	55195.7	.03	757.9	11:47:36	88
244	140	55243.9	.03	756.5	11:48:56	88
282	150	55282.2	.03	756.6	11:49:23	88
211	160	55211.0	.05	757.0	11:50:00	88
220	170	55220.3	.03	756.6	11:50:27	88
782	180	55781.9	.04	756.1	11:50:58	88
445	190	55445.4	.04	755.8	11:51:33	88

Line 27 Date 9 JUN 3 #115

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
30	10	55030.4	.03	749.3	12:44:45	88
119	20	55119.0	.03	749.9	12:47:14	88
101	30	55101.4	.03	749.6	12:47:53	88
11	40	55011.2	.03	750.0	12:48:24	88
- 42	50	54957.5	.03	750.7	12:48:58	88
8	60	55007.8	.05	749.0	12:49:59	88
- 477	70	54523.0	.04	748.7	12:50:38	88
151	80	55151.1	.03	748.7	12:51:24	88
- 25	90	54975.4	.04	749.5	12:52:31	88
68	100	55068.1	.03	749.9	12:52:57	88
118	110	55118.1	.03	750.0	12:53:26	88
261	120	55261.0	.03	749.9	12:53:56	88
163	130	55163.4	.22	749.7	12:54:30	78
177	140	55177.3	.03	749.6	12:55:02	88
562	150	55562.1	.03	751.2	12:56:15	88
865	160	55865.4	.03	751.7	12:56:54	88
3346	170	58348.0	.19	752.1	12:57:22	88
- 1935	180	53064.8	.09	752.7	12:58:23	85
9493	190	64492.8	20.	752.6	12:58:51	32
1298	200	56298.2	1.1	752.4	13:00:06	44
990	210	55989.9	.05	752.9	13:00:34	88
390	220	55390.2	.03	753.5	13:01:02	88
72	230	55072.3	.03	753.5	13:01:30	88

Line 28 Date 9 JUN 3 #138

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
- 131	10	54869.2	.03	751.4	13:12:59	88
- 738	20	54262.3	.04	757.7	13:16:11	88
- 3386	30	51614.1	.20	757.8	13:17:29	78
- 2403	40	52596.5	.04	757.6	13:19:49	88
- 591	50	54403.0	.07	756.5	13:21:47	88
- 954	60	54045.5	.04	756.7	13:22:25	88
- 1804	70	53196.3	.21	756.8	13:23:00	88
- 15	80	54984.9	.07	756.4	13:23:30	88
- 9357	90	45642.5	4.4	756.1	13:23:55	32
- 8823	100	46116.9	1.2	755.4	13:24:34	68
78	110	55058.2	3.2	754.1	13:25:45	34
9273	120	63272.7	2.5	753.5	13:26:20	42
- 3466	130	52533.7	.41	752.4	13:27:09	54
3506	140	58505.5	.18	751.2	13:27:38	87
796	150	55796.3	.98	749.6	13:28:37	46
64	160	55063.5	.15	747.5	13:33:17	88
- 367	170	54633.2	.04	747.9	13:33:52	88
- 1068	180	53932.0	.08	748.0	13:35:01	88
670	190	55669.5	.04	748.0	13:35:39	88

Line 29 Date 9 JUN 3 #157

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT

```
                                        JUN9CORR
    10    54959.0 .03    752.5 13:43:57 88
    20    55020.0 .04    757.8 13:47:00 88
    30    58805.7 .52    758.9 13:47:41 58
    40    64464.9 69.    762.9 13:49:24 32
    50    50928.3 3.7    771.0 13:52:54 33
    60    53514.7 62.    772.5 13:58:38 32
    70    53996.9 .04    772.3 13:59:31 88
    80    52916.2 3.6    772.2 14:00:22 57
    90    61556.6 16.    773.1 14:02:18 23
   100    76922.3 5.0    772.7 14:02:56 33
   110    75091.2 88.    772.9 14:06:09 32
   120    74247.9 83.    773.1 14:08:10 22
   130    80335.7 91.    774.7 14:09:26 22

Checksum Error! Record   #170

Line     0    Date  9 JUN  3         #170
POSITION  FIELD  ERR   DRIFT   TIME    DS CULT
     0      0.0 .00     0.0  0:00:00  0            0.0

EOF


OO
```

not entered (faulty readings).

OMNI-IV Tie-line MAG Ser #634358
TOTAL FIELD DATA (Tieline corrected)

Reference field: 55000.0
Datum subtracted: 50000.0Date 10 JUN 3
Operator: 3000
Records: 196
Bat: 17.5 Volt Lithium: 3.48 Volt
Last time update: 6/09 8:23:00
Start of print: 6/10 17:30:55

(-) in front of number (only day this was registered - settings are different in Test Mode)

subtract another 5000

Line -30 Date 10 JUN 3 #1

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
624	-20	5624.2	.05	0.0	9:04:40	88	
1168	-30	6167.6	.07	0.0	9:06:01	88	
1281	-40	6281.4	.05	0.0	9:06:54	88	
1392	-50	6391.6	.05	0.0	9:07:37	87	
1381	-60	6381.4	.05	0.0	9:08:28	88	
1022	-70	6022.2	.05	0.0	9:09:12	88	
972	-80	5972.7	.05	0.0	9:10:13	88	

-5000 Line -31 Date 10 JUN 3 #8

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
-316	-10	4684.4	.08	0.0	9:19:48	88	
-1963	-20	3036.6	.13	0.0	9:22:57	87	
4105	-30	5404.7	1.7	0.0	9:23:33	46	
4661	-40	5466.1	17.	0.0	9:24:35	32	
13504	-50	18504.0	2.6	0.0	9:25:07	43	
13676	-60	18626.2	9.2	0.0	9:25:42	43	
13646	-70	18646.1	6.1	0.0	9:26:19	42	
1695	-80	6696.3	.21	0.0	9:29:07	73	
-702	-90	4297.5	.35	0.0	9:29:40	86	
1901	-100	6800.5	.13	0.0	9:30:08	88	=
1207	-110	6206.9	.05	0.0	9:30:39	88	=
-970	-120	4030.1	.72	0.0	9:31:13	76	=
-298	-130	4702.0	.06	0.0	9:31:47	88	=

} disregard these readings - location of stations questionable

Line -32 Date 10 JUN 3 #21

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
724	-10	5723.7	.05	0.0	9:37:14	88	
773	-20	5773.1	.05	0.0	9:41:07	88	
2898	-30	7897.9	.13	0.0	9:42:06	88	
2205	-40	7204.5	19.	0.0	9:42:52	32	
1310	-50	6309.8	9.5	0.0	9:43:34	46	
-4339	-60	661.6	39.	0.0	9:44:09	43	
12512	-70	17512.3	28.	0.0	9:44:54	32	
12895	-80	17895.7	28.	0.0	9:46:28	42	

Line -33 Date 10 JUN 3 #29

	POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
-1439	-10	3560.9	.43	0.0	9:50:23	53	
3291	-20	8290.8	32.	0.0	9:53:00	44	
-4165	-30	834.6	12.	0.0	9:53:24	53	
1492	-40	6491.5	9.4	0.0	9:53:47	55	
1196	-50	6185.9	2.4	0.0	9:54:44	36	
3507	-60	8506.9	.06	0.0	9:55:13	88	
146	-70	4854.3	.76	0.0	9:55:36	75	
-2013	-80	2987.3	.09	0.0	9:56:23	86	
-1145	-90	3855.1	.04	0.0	9:56:56	88	
947	-100	5947.1	.05	0.0	9:57:22	88	
796	-110	5796.1	.06	0.0	10:01:07	88	
756	-120	5755.8	.05	0.0	10:01:53	88	
946	-130	5946.3	.05	0.0	10:02:29	88	
971	-140	5888.3	.05	0.0	10:03:06	88	

JU10REMR

Line -34 Date 10 JUN 3 #43

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
634 -10	5633.9	.05	0.0	10:09:15	88	
522 -20	5522.2	.07	0.0	10:12:26	88	
623 -30	5623.8	.05	0.0	10:12:57	88	
1787 -40	6787.4	.19	0.0	10:13:40	78	
761 -50	5760.6	.21	0.0	10:14:46	78	
2794 -60	7793.6	.05	0.0	10:15:18	88	
5981 -70	10980.5	.07	0.0	10:16:07	86	
11356 -80	16356.3	.94	0.0	10:16:40	54	
5754 -90	10754.2	.33	0.0	10:17:10	63	
2274 -100	7273.8	.13	0.0	10:17:39	76	
-561 -110	4438.6	.12	0.0	10:18:13	85	
-297 -120	4703.2	.05	0.0	10:19:16	88	
172 -130	5172.1	.05	0.0	10:19:41	88	
694 -140	5694.3	.04	0.0	10:21:01	88	
911 -150	5910.6	.04	0.0	10:21:36	88	
900 -160	5899.7	.04	0.0	10:22:11	88	

Line -35 Date 10 JUN 3 #59

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
896 -10	5896.1	.05	0.0	10:41:58	88	
935 -20	5935.4	.05	0.0	10:44:05	88	
1014 -30	6014.1	.05	0.0	10:44:37	88	
1634 -40	6634.4	.06	0.0	10:45:12	88	
889 -50	5889.0	.05	0.0	10:47:10	88	
914 -60	5913.9	.05	0.0	10:47:47	88	
1210 -70	6209.5	.05	0.0	10:48:09	88	
12244 -80	17243.6	59.	0.0	10:48:30	32	
12473 -90	18473.4	26.	0.0	10:49:28	42	
13584 -100	18584.2	8.8	0.0	10:50:30	53	
-636 -110	4374.4	.30	0.0	10:51:17	63	
530 -120	5529.9	.04	0.0	10:51:50	88	
816 -130	5815.8	.05	0.0	10:52:38	88	
934 -140	5933.8	.04	0.0	10:53:17	88	
910 -150	5907.8	.04	0.0	10:54:29	88	
826 -160	5825.5	.05	0.0	10:54:59	88	
727 -170	5727.4	.04	0.0	10:55:37	88	
809 -180	5808.6	.04	0.0	10:56:31	88	

Line -36 Date 10 JUN 3 #77

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
885 -10	5884.6	.05	0.0	11:12:21	88	
1564 -20	6564.1	.05	0.0	11:14:38	88	
41219 -30	9217.6	.08	0.0	11:15:06	88	
11395 -40	16395.1	12.	0.0	11:15:54	55	
10144 -50	15144.0	21.	0.0	11:16:41	45	
-2852 -60	2147.7	3.2	0.0	11:17:44	32	
-674 -70	4326.0	.05	0.0	11:18:19	88	
5070 -80	10070.2	4.8	0.0	11:18:49	54	
-371 -90	4629.2	.15	0.0	11:19:16	74	
853 -100	5853.2	.04	0.0	11:19:42	88	
742 -110	5741.5	.05	0.0	11:20:14	88	
715 -120	5715.3	.05	0.0	11:21:08	88	
731 -130	5730.7	.04	0.0	11:21:47	88	
844 -140	5844.1	.05	0.0	11:22:39	88	
783 -150	5783.3	.04	0.0	11:23:24	88	

Line -37 Date 10 JUN 3 #92

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
1264 -10	6264.2	.04	0.0	11:31:56	88	
659 -20	5658.8	.06	0.0	11:35:27	88	
3329 -30	8329.0	.15	0.0	11:37:24	88	
6544 -40	11544.1	.19	0.0	11:38:04	77	
2245 -50	7245.0	.15	0.0	11:38:51	74	
-1681 -60	3319.2	.85	0.0	11:39:27	85	
32 -70	5031.7	.05	0.0	11:41:35	88	
-19 -80	4981.4	.05	0.0	11:42:09	88	
409 -90	5409.1	.04	0.0	11:42:48	88	

-5000

JU10REMR

605	-100	5604.6	.05	0.0	11:43:32	88
674	-110	5673.8	.04	0.0	11:43:57	88
559	-120	5559.2	.05	0.0	11:44:25	88
543	-130	5542.7	.04	0.0	11:45:00	88
757	-140	5757.4	.04	0.0	11:46:26	88

Line -38 Date 10 JUN 3 #106

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
665 -10	5665.0	.05	0.0	12:32:14	88	
500 -20	5499.8	.05	0.0	12:35:20	88	
197 -30	5197.2	.04	0.0	12:35:53	88	
137 -40	5137.4	.05	0.0	12:36:30	88	
190 -50	5189.7	.05	0.0	12:37:21	88	
422 -60	5421.8	.04	0.0	12:37:40	88	
161 -70	5160.7	.05	0.0	12:38:01	88	
435 -80	5434.7	.04	0.0	12:38:23	88	
1531 -90	6530.6	.05	0.0	12:39:03	88	
8 -100	5007.9	.18	0.0	12:39:34	87	
-777 -110	4223.3	.07	0.0	12:40:15	87	
-86 -120	4913.9	.04	0.0	12:40:59	88	
272 -130	5272.0	.04	0.0	12:41:40	88	
545 -140	5545.0	.04	0.0	12:43:17	88	
541 -150	5540.6	.05	0.0	12:44:02	88	
549 -160	5549.2	.06	0.0	12:44:35	88	
622 -170	5621.7	.05	0.0	12:44:59	88	

Line -39 Date 10 JUN 3 #123

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
634 -10	5634.1	.05	0.0	12:52:03	88	
598 -20	5598.3	.05	0.0	12:55:49	88	
1685 -30	6685.2	.05	0.0	12:56:36	88	
3021 -40	8021.0	.04	0.0	12:57:15	88	
6028 -50	11028.0	3.5	0.0	12:57:40	77	
2305 -60	7305.4	.16	0.0	12:59:49	85	
-114 -70	4885.5	.11	0.0	13:00:28	86	
476 -80	5476.3	.07	0.0	13:00:59	88	
125 -90	5124.9	.09	0.0	13:01:40	88	
-4712 -100	287.9	7.6	0.0	13:03:12	74	
-520 -110	4479.5	.10	0.0	13:03:56	86	
37 -120	5037.2	.04	0.0	13:05:09	88	
490 -130	5489.7	.05	0.0	13:05:50	88	
500 -140	5500.3	.04	0.0	13:06:30	88	
650 -150	5650.2	.05	0.0	13:07:06	88	
799 -160	5798.5	.05	0.0	13:07:36	88	
958 -170	5957.5	.04	0.0	13:08:27	88	
924 -180	5924.2	.05	0.0	13:09:13	88	

Line -61 Date 10 JUN 3 #141

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
1183 -10	6182.8	.04	0.0	13:22:52	88	
1248 -20	6248.2	.05	0.0	13:23:53	88	
1376 -30	6375.7	.04	0.0	13:25:41	88	
1488 -40	6487.9	.05	0.0	13:26:15	88	
1860 -50	6859.7	.05	0.0	13:26:51	88	
3357 -60	8357.4	.08	0.0	13:27:22	88	
10093 -70	15093.2	.35	0.0	13:27:51	74	
8593 -80	13582.7	.08	0.0	13:30:13	88	
2823 -90	7823.0	.31	0.0	13:31:16	74	
559 -100	5559.2	.08	0.0	13:32:18	87	
55 -110	5055.2	.07	0.0	13:32:55	88	
431 -120	5431.3	.05	0.0	13:34:12	88	
-487 -130	4513.1	.06	0.0	13:34:45	88	
-753 -140	4246.6	.06	0.0	13:35:16	88	
-47 -150	4952.8	.05	0.0	13:35:55	88	
341 -160	5340.9	.08	0.0	13:36:49	88	

Line -62 Date 10 JUN 3 #157

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
7741 -10	7741.4	.05	0.0	13:54:58	88	

-5000

JU10REMR

3633	-20	8633.2	.04	0.0	13:59:56	88
3259	-30	8258.7	.13	0.0	14:00:52	88
1493	-40	6493.1	.07	0.0	14:01:58	86
824	-50	5823.5	.05	0.0	14:03:56	88
710	-60	5709.6	.21	0.0	14:04:38	78
34	-70	5033.8	.06	0.0	14:05:17	87
242	-80	5242.2	.05	0.0	14:05:52	88
-60	-90	4940.1	.05	0.0	14:06:32	88
-120	-100	4880.1	.05	0.0	14:07:08	88
54	-110	5053.9	.05	0.0	14:07:44	88

Line -63 Date 10 JUN 3 #168

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
1141	-10	6140.5	.04	0.0	14:29:44	88	
1192	-20	6191.7	.04	0.0	14:35:28	88	
1460	-30	6460.2	.05	0.0	14:35:59	88	
1383	-40	6383.4	.05	0.0	14:36:33	88	
1182	-50	6181.6	.04	0.0	14:37:23	88	
1228	-60	6227.7	.05	0.0	14:38:02	88	
1185	-70	6184.5	.04	0.0	14:38:40	88	
1339	-80	6339.2	.04	0.0	14:39:27	88	
1431	-90	6431.1	.04	0.0	14:40:08	88	
1565	-100	6565.1	.05	0.0	14:40:46	88	
1996	-110	6996.1	.04	0.0	14:41:33	88	
1945	-120	6945.2	.03	0.0	14:42:12	88	
1057	-130	6057.3	.05	0.0	14:44:27	88	
716	-140	5715.5	.06	0.0	14:45:09	88	
413	-150	5413.0	.06	0.0	14:47:44	88	
-51	-160	4949.2	.06	0.0	14:49:51	88	

Line -64 Date 10 JUN 3 #184

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
1342	-10	6341.9	.05	0.0	14:54:35	88	
1139	-20	6139.3	.05	0.0	14:56:46	88	
831	-30	5830.7	.05	0.0	14:57:20	88	
692	-40	5692.2	.05	0.0	14:58:02	88	
568	-50	5568.1	.05	0.0	14:58:38	88	
553	-60	5553.3	.06	0.0	14:59:02	88	

Line -65 Date 10 JUN 3 #190

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
959	-10	5958.9	.05	0.0	15:04:19	88	
1004	-20	6004.0	.05	0.0	15:06:43	88	
1022	-30	6021.9	.05	0.0	15:07:19	88	
1161	-40	6161.0	.05	0.0	15:08:08	88	
867	-50	5866.5	.05	0.0	15:08:41	87	
1195	-60	6194.9	.04	0.0	15:11:19	88	
1491	-70	6490.9	.04	0.0	15:12:01	88	

EOF

DD

OMNI-PLUS Tie-line MAG/VLF V12N Ser #418141
TOTAL FIELD DATA (uncorrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 12 JUN 3
Operator: 3000
Records: 186
Bat: 17.0 Volt Lithium: 3.48 Volt
Last time update: 6/11 13:24:00
Start of print: 6/12 16:17:42

Line 65 Date 12 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55983.5	.07	0.0	8:18:41	88	
20	56023.5	.03	0.0	8:20:36	88	
30	56051.0	.03	0.0	8:21:19	88	
40	56255.8	.03	0.0	8:22:08	88	
50	55999.4	.03	0.0	8:22:44	88	
60	56185.5	.03	0.0	8:23:20	88	
70	56505.0	.03	0.0	8:24:09	88	

Line 64 Date 12 JUN 3 #8

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	56374.1	.03	0.0	8:29:24	88	
20	56053.2	.03	0.0	8:31:04	88	
30	55784.6	.03	0.0	8:31:34	88	
40	55649.5	.03	0.0	8:32:12	88	
50	55475.5	.03	0.0	8:32:50	88	

Line 63 Date 12 JUN 3 #13

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	56160.8	.03	0.0	8:42:51	88	
20	56238.0	.02	0.0	8:44:30	88	
30	56620.0	.03	0.0	8:45:13	88	
40	56399.0	.03	0.0	8:45:47	88	
50	56203.8	.03	0.0	8:46:20	88	
60	56254.7	.03	0.0	8:46:53	88	
70	56212.7	.03	0.0	8:47:29	88	
80	56329.4	.03	0.0	8:48:08	88	
90	56405.5	.03	0.0	8:48:54	88	
100	56535.5	.02	0.0	8:49:28	88	
110	56825.2	.03	0.0	8:50:22	88	
120	57079.7	.02	0.0	8:50:58	88	
130	56034.5	.04	0.0	8:51:52	88	
140	55943.3	.03	0.0	8:52:36	88	
150	55725.4	.04	0.0	8:53:08	88	
160	55458.5	.03	0.0	8:54:05	88	

Line 62 Date 12 JUN 3 #29

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	57771.7	.03	0.0	8:57:53	88	65
20	58839.1	.03	0.0	9:00:04	88	55
30	58186.5	.03	0.0	9:00:59	88	
40	56581.0	.04	0.0	9:01:39	88	
50	55836.3	.03	0.0	9:02:19	88	
60	54895.1	.28	0.0	9:03:00	88	
70	55087.9	.04	0.0	9:03:37	88	
80	55265.1	.03	0.0	9:04:11	88	
90	54937.3	.03	0.0	9:04:49	88	
100	54917.1	.02	0.0	9:05:26	88	
110	55098.2	.03	0.0	9:06:01	88	
120	55271.6	.04	0.0	9:06:44	88	

Line 61 Date 12 JUN 3 #41

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT

JUN12REM

1229	10	56229.3	.03	0.0	9:19:07	88	
1272	20	56272.4	.03	0.0	9:22:04	88	
1369	30	56369.2	.02	0.0	9:23:00	88	
1466	40	56466.0	.03	0.0	9:23:42	88	85
1631	50	56630.6	.04	0.0	9:24:16	88	65
3892	60	58892.2	.08	0.0	9:25:01	88	55
11236	70	66235.7	1.0	0.0	9:26:05	65	58
8338	80	63337.9	.20	0.0	9:27:19	77	55
5652	90	60652.4	.22	0.0	9:28:19	66	56
583	100	55583.0	.10	0.0	9:29:10	86	86
119	110	55119.1	.04	0.0	9:29:58	88	
461	120	55460.8	.03	0.0	9:30:33	88	
0	130	54499.9	.04	0.0	9:31:06	88	65
-640	140	54359.7	.03	0.0	9:31:40	88	55
-79	150	54921.2	.03	0.0	9:32:15	88	
362	160	55362.4	.03	0.0	9:33:16	88	

Line 39 Date 12 JUN 3 #57

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
668	55667.5	.05	0.0	9:40:59	85	66
707	55707.0	.03	0.0	9:42:46	88	55
2071	57078.6	.03	0.0	9:43:18	88	
3068	58068.2	.04	0.0	9:43:55	88	
6448	61447.5	.61	0.0	9:44:28	88	58
1223	56223.0	.27	0.0	9:44:51	55	56
319	55318.7	.04	0.0	9:45:25	88	55
670	55671.1	.05	0.0	9:46:09	88	65
-1341	53658.7	.31	0.0	9:46:46	68	55
-5038	49962.4	.49	0.0	9:47:20	66	
-434	54566.3	.06	0.0	9:47:55	88	
162	55162.2	.02	0.0	9:48:40	88	
538	55537.6	.03	0.0	9:49:21	88	85
541	55540.9	.03	0.0	9:49:48	88	
663	55663.1	.03	0.0	9:50:18	88	55
826	55826.0	.03	0.0	9:50:56	88	
988	55988.8	.04	0.0	9:51:28	88	
968	55968.4	.04	0.0	9:52:06	88	

Line 38 Date 12 JUN 3 #75

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
691	55690.8	.03	0.0	10:05:39	88	
525	55525.0	.03	0.0	10:07:28	88	
214	55213.7	.04	0.0	10:08:15	88	
049	55049.3	.03	0.0	10:08:52	88	
215	55214.5	.03	0.0	10:09:21	88	
320	55320.1	.03	0.0	10:09:46	88	
203	55202.5	.03	0.0	10:10:08	88	65
459	55457.9	.04	0.0	10:10:36	88	55
1560	56559.7	.04	0.0	10:11:13	88	
-439	54560.5	.08	0.0	10:11:43	88	85
-478	54522.0	.04	0.0	10:12:16	88	65
63	55062.6	.03	0.0	10:13:12	88	55
361	55360.9	.03	0.0	10:13:46	88	
598	55597.6	.03	0.0	10:14:20	88	65
587	55586.8	.03	0.0	10:14:57	88	55
571	55570.6	.03	0.0	10:15:28	88	
638	55637.9	.03	0.0	10:15:50	88	

Line 37 Date 12 JUN 3 #92

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
1304	56304.0	.03	0.0	10:29:07	88	
755	55755.2	.04	0.0	10:30:47	88	
566	57565.6	.10	0.0	10:31:21	88	
7256	62256.2	.20	0.0	10:31:53	68	58
4633	59632.8	.05	0.0	10:32:24	88	56
-1019	53982.2	.39	0.0	10:32:57	55	
-838	54162.1	.04	0.0	10:33:18	88	55
11	54988.7	.03	0.0	10:34:29	88	
37	55037.4	.03	0.0	10:35:09	88	65

JUN12REM

500	100	55499.9	.04	0.0	10:35:39	88	55
637	110	55637.4	.03	0.0	10:36:06	88	
701	120	55701.3	.03	0.0	10:36:36	88	
489	130	55488.5	.04	0.0	10:37:14	88	
643	140	55642.7	.03	0.0	10:38:15	88	65
759	150	55758.6	.03	0.0	10:38:54	88	

Line 36 Date 12 JUN 3 #107

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
860	10	55859.5	.03	0.0	10:51:37	88	
1602	20	56602.4	.03	0.0	10:53:21	88	
4076	30	59075.5	.06	0.0	10:53:51	88	
2985	40	63984.7	.53	0.0	10:54:18	58	
19174	50	74174.1	39.	0.0	10:54:52	32	
25034	60	80033.7	90.	0.0	10:57:41	22	
8190	90	63190.2	3.0	0.0	11:02:34	43	58
-115	100	54884.8	.08	0.0	11:03:48	85	56
901	110	55901.3	.03	0.0	11:04:31	88	55
741	120	55741.1	.03	0.0	11:05:02	88	
709	130	55709.4	.03	0.0	11:05:35	88	
753	140	55753.2	.03	0.0	11:06:14	88	65
854	150	55854.6	.03	0.0	11:07:06	88	
783	160	55782.7	.03	0.0	11:07:55	88	55

Line 35 Date 12 JUN 3 #121

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
892	10	55881.7	.19	0.0	11:21:15	53	56
935	20	55935.0	.03	0.0	11:24:26	88	55
1030	30	55999.9	.03	0.0	11:25:01	88	65
1556	40	56556.1	.04	0.0	11:25:32	88	
927	50	55927.2	.04	0.0	11:26:06	88	
973	60	55922.5	.03	0.0	11:26:33	88	55
1039	70	56039.3	.04	0.0	11:26:56	88	
9898	80	64898.1	2.4	0.0	11:27:20	34	88
10447	90	65446.8	76.	0.0	11:28:32	32	55
13284	100	68284.1	80.	0.0	11:29:48	22	55
-3025	110	51974.7	.59	0.0	11:30:41	43	56
143	120	55142.8	.03	0.0	11:31:25	88	85
678	130	55678.3	.03	0.0	11:31:55	88	65
855	140	55855.2	.03	0.0	11:32:22	88	55
924	150	55924.2	.04	0.0	11:32:55	88	
870	160	55870.3	.03	0.0	11:33:43	88	
766	170	55765.8	.04	0.0	11:34:26	88	85
705	180	55705.3	.04	0.0	11:35:01	88	65
705	190	55804.8	.04	0.0	11:35:43	88	55

Line 34 Date 12 JUN 3 #140

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
604	10	55603.9	.04	0.0	11:46:34	88	
492	20	55491.7	.03	0.0	11:49:52	88	
812	30	55811.9	.04	0.0	11:50:22	88	
1050	40	56049.8	.16	0.0	11:50:50	88	
1283	50	56282.6	.09	0.0	11:51:14	88	
2672	60	57672.4	.04	0.0	11:51:47	88	
6204	70	61203.9	.22	0.0	11:52:14	68	58
10819	80	65819.3	.98	0.0	11:52:47	68	55
5329	90	60329.1	.18	0.0	11:53:27	65	56
1024	100	56023.8	.13	0.0	11:53:53	86	
-589	110	54411.2	.06	0.0	11:54:17	88	65
-230	120	54770.0	.04	0.0	11:54:38	88	
280	130	55279.8	.03	0.0	11:55:00	88	
671	140	55670.8	.03	0.0	11:55:24	88	85
877	150	55876.6	.03	0.0	11:55:50	88	55

Reran line but used previous day's data. (See June 10/03)

Line 33 Date 12 JUN 3 #155

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
876	10	55875.7	.03	0.0	12:02:05	88	
929	20	55928.8	.03	0.0	12:04:54	88	
740	30	55740.3	.04	0.0	12:05:25	88	

JUN12REM

779	40	55778.7	.03	0.0	12:06:03	88		
1151	50	56151.3	.12	0.0	12:06:32	88		
-1245	60	53754.8	.10	0.0	12:06:57	88	65	
-1873	70	53126.6	.07	0.0	12:07:39	88	55	
295	80	54704.9	.18	0.0	12:08:36	88	85	
1917	90	56917.1	.11	0.0	12:09:38	88	55	
1181	100	56181.1	2.2	0.0	12:10:26	38		
-4428	110	50571.8	11.	0.0	12:11:00	34		
-7611	120	47388.6	2.8	0.0	12:11:31	33	86	
-366	130	54633.8	59.	0.0	12:13:33	22	58	
2452	140	57451.7	5.4	0.0	12:14:10	48	55	
8636	150	63635.9	2.9	0.0	12:14:59	33	58	
7427	160	62427.2	9.0	0.0	12:15:28	34	55	
2617	170	57617.4	.57	0.0	12:16:34	56	56	
781	180	55780.9	.04	0.0	12:17:09	88	85	
686	190	55685.7	.04	0.0	12:17:40	88	55	

Line 32 Date 12 JUN 3 #174

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
-533	10	54466.8	.06	0.0	12:24:52	88	
792	20	55791.6	.12	0.0	12:27:06	88	65
1567	30	56567.3	.33	0.0	12:27:34	88	
-449	40	54550.7	.07	0.0	12:28:00	88	55
1722	50	56722.0	.14	0.0	12:28:28	88	
-1490	60	53510.3	2.1	0.0	12:28:59	45	
1994	70	56994.4	18.	0.0	12:30:33	36	55
19094	80	74094.2	75.	0.0	12:31:05	32	58
26781	90	81780.9	90.	0.0	12:32:22	22	

11. e.) Line 32

entered

→ then used previous day's data to continue...

Line 70 Date 12 JUN 3 #183

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
236	10	55236.0	.04	0.0	12:43:46	88	
-336	20	54664.3	.04	0.0	12:44:45	88	
-1598	30	53401.8	.11	0.0	12:45:14	88	65
-483	40	54516.7	1.4	0.0	12:45:44	48	55

Continuation Line 32 (heading S.)

EOF

OMNI-PLUS Tie-line MAG/VLF V12N Ser #418141
TOTAL FIELD DATA (uncorrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 8 JUN 3
Operator: 3000
Records: 229
Bat: 17.0 Volt Lithium: 3.48 Volt
Last time update: 6/06 8:18:00
Start of print: 6/08 17:53:07

Line 50 Date 8 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
200	56369.7	.00	0.0	8:24:22	88	
210	56369.7	.00	0.0	8:25:19	88	

Line 857 Date 8 JUN 3 #3

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55207.4	.03	0.0	8:53:55	88	
20	55546.2	.03	0.0	8:55:59	88	
30	55828.2	.04	0.0	8:56:39	88	
40	55986.2	.03	0.0	8:57:18	88	
50	56072.3	.03	0.0	8:57:56	88	
60	56146.3	.02	0.0	8:58:25	88	
70	56193.2	.03	0.0	8:58:49	88	
80	56199.4	.03	0.0	8:59:24	88	
90	56183.6	.02	0.0	8:59:59	88	
100	56236.1	.03	0.0	9:00:37	88	
110	56228.0	.03	0.0	9:01:18	88	
120	56187.0	.03	0.0	9:01:56	88	
130	56119.9	.03	0.0	9:02:50	88	
140	56196.9	.02	0.0	9:03:29	88	
150	56158.6	.02	0.0	9:04:07	88	
160	55868.9	.03	0.0	9:04:30	88	
170	55467.3	.03	0.0	9:04:59	88	
180	54590.2	.11	0.0	9:05:33	88	
190	55254.6	.20	0.0	9:06:10	88	
200	61684.5	.30	0.0	9:06:30	56	58
210	57479.5	.11	0.0	9:07:05	87	56
220	55045.8	.06	0.0	9:07:42	88	55
230	51221.5	.49	0.0	9:08:32	67	
240	54732.9	.14	0.0	9:09:20	88	
250	54912.4	.48	0.0	9:19:06	58	
260	55914.4	.03	0.0	9:19:33	88	
270	56021.0	.02	0.0	9:20:02	88	
280	56012.5	.02	0.0	9:20:29	88	
290	55891.2	.02	0.0	9:20:55	88	
300	55673.6	.04	0.0	9:21:42	88	
310	55583.7	.03	0.0	9:22:46	88	
320	55674.9	.03	0.0	9:26:17	88	
330	55898.0	.08	0.0	9:27:55	88	
340	56433.3	.03	0.0	9:28:51	88	
350	57584.3	.10	0.0	9:29:26	88	
360	58896.0	.26	0.0	9:29:52	88	
370	58589.5	.28	0.0	9:30:33	88	
380	58226.0	.06	0.0	9:31:09	88	
390	56608.0	.04	0.0	9:32:08	88	
400	56357.6	.03	0.0	9:32:42	88	
410	56607.3	.03	0.0	9:33:40	88	
420	56028.9	.07	0.0	9:34:27	88	
430	56437.7	.03	0.0	9:35:00	88	
440	57088.2	.02	0.0	9:35:35	88	
450	57268.3	.03	0.0	9:36:07	88	
460	59082.8	.21	0.0	9:36:37	88	
470	58427.8	.20	0.0	9:37:10	88	56

JUN8REMR

300							
2551	480	57551.3	.03	0.0	9:37:42	88	55
2444	490	57444.1	.03	0.0	9:38:13	88	
2421	500	57421.0	.03	0.0	9:38:46	88	
313	510	55313.0	.41	0.0	9:39:33	68	
1251	520	56250.8	.02	0.0	9:40:15	88	
1258	530	56258.2	.03	0.0	9:40:57	88	
939	540	55939.1	.04	0.0	9:41:44	88	
940	550	55940.3	.02	0.0	9:42:57	88	
692	560	55691.9	.04	0.0	9:43:39	88	
0	570	54999.5	.03	0.0	9:44:23	88	
223	580	55223.0	.03	0.0	9:45:01	88	
1143	590	56142.7	.03	0.0	9:45:51	88	
1436	600	56435.8	.03	0.0	9:48:37	88	
1265	610	56265.7	.03	0.0	9:49:15	88	
989	620	55989.1	.03	0.0	9:49:47	88	
888	630	55888.3	.05	0.0	9:50:29	88	
1141	640	56140.7	.03	0.0	9:51:05	88	
2014	650	57013.9	.03	0.0	9:51:40	88	
1299	660	56299.2	.03	0.0	9:52:14	88	
1330	670	56330.0	.09	0.0	9:52:47	78	
496	680	55495.9	.04	0.0	9:53:16	88	
175	690	55175.2	.03	0.0	9:54:04	88	
-549	700	54451.3	.04	0.0	9:54:56	88	
-334	710	54666.2	.06	0.0	9:55:52	88	
-37	720	54962.5	.03	0.0	9:56:40	88	
210	730	55209.7	.04	0.0	9:57:35	88	
270	740	55270.0	.03	0.0	9:58:27	88	
236	750	55235.7	.03	0.0	9:59:07	88	
347	760	55346.7	.03	0.0	9:59:50	88	
231	770	55231.4	.03	0.0	10:00:29	88	
444	780	55444.2	.04	0.0	10:01:01	88	65
585	790	55584.9	.77	0.0	10:01:32	88	
357	800	55356.5	.04	0.0	10:02:05	88	
505	810	55505.2	.03	0.0	10:02:51	88	
425	820	55425.1	.04	0.0	10:03:39	88	55
459	830	55459.2	.03	0.0	10:04:29	88	
523	840	55523.0	.03	0.0	10:05:03	88	
678	850	55678.2	.03	0.0	10:07:16	88	
771	860	55771.4	.04	0.0	10:08:02	88	
812	870	55812.2	.03	0.0	10:08:45	88	
610	880	55610.1	.03	0.0	10:09:37	88	
312	890	55311.9	.08	0.0	10:10:22	88	
134	900	55133.6	.04	0.0	10:11:15	88	
398	910	55397.8	.03	0.0	10:12:07	88	
568	920	55567.8	.03	0.0	10:12:59	88	
634	930	55633.5	.03	0.0	10:13:30	88	
514	940	55514.4	.04	0.0	10:14:58	88	
561	950	55561.0	.03	0.0	10:15:40	88	
421	960	55421.3	.07	0.0	10:16:38	88	
643	970	55643.2	.03	0.0	10:17:07	88	

no room for these values at end of line (these stations double counted some on this line).

Line 12 Date 8 JUN 3 #100

POSITION		FIELD	ERR	DRIFT	TIME	DS	CULT
422	10	55422.4	.03	0.0	10:35:52	88	
243	20	55244.7	.04	0.0	10:38:47	88	
263	30	55263.2	.03	0.0	10:40:20	88	
554	40	55554.3	.04	0.0	10:41:22	88	
937	50	55937.3	.07	0.0	10:42:21	88	
928	60	55927.7	.03	0.0	10:43:34	88	
790	70	55789.5	.03	0.0	10:44:49	88	
539	80	55539.3	.04	0.0	10:45:40	88	
210	90	55209.6	.05	0.0	10:47:59	88	
548	100	55547.9	.03	0.0	10:49:35	88	
242	110	55241.9	.05	0.0	10:50:44	88	
232	120	55232.4	.04	0.0	10:52:07	88	
140	130	55139.6	.03	0.0	10:54:00	88	
515	140	55515.4	.03	0.0	10:55:45	88	
282	150	55281.9	.04	0.0	10:58:17	88	
201	160	55201.1	.04	0.0	11:00:03	88	

drawn on the plan at 150m.
readings indicate 270m.??
↓
Corrected line length on plan Jul. 22/03)

170	55052.2	.03	0.0	11:01:42	88		
180	55343.9	.03	0.0	11:04:48	88		
190	56255.0	.03	0.0	11:08:20	88		
200	56041.1	.04	0.0	11:09:13	88		
210	56111.6	.03	0.0	11:10:33	88		
220	55941.6	.03	0.0	11:12:07	88		
230	55894.8	.03	0.0	11:13:20	88		
240	56124.0	.03	0.0	11:13:55	88		
250	56484.5	.22	0.0	11:14:44	88		
260	55998.4	.04	0.0	11:15:45	88		
270	55538.7	.03	0.0	11:16:32	88		
280	55374.9	.04	0.0	11:18:13	88		

Line 13 Date 8 JUN 3 #128

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	51332.3	.25	0.0	12:16:39	76	
20	54976.3	63.	0.0	12:18:11	32	
30	53742.8	.29	0.0	12:19:42	68	
40	61264.8	.15	0.0	12:20:46	76	58
50	61762.4	.21	0.0	12:21:40	88	55
60	58281.0	.06	0.0	12:22:45	86	56
70	57697.4	.04	0.0	12:23:18	88	55
80	57805.7	.04	0.0	12:23:54	88	
90	57263.2	.04	0.0	12:24:34	88	
100	56731.7	.03	0.0	12:25:17	88	
110	56261.2	.04	0.0	12:26:47	88	
120	56117.9	.03	0.0	12:28:11	88	
130	55956.9	.04	0.0	12:29:11	88	
140	56105.6	.03	0.0	12:30:10	88	
150	55962.1	.03	0.0	12:31:21	88	

Line 14 Date 8 JUN 3 #143

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55999.8	.03	0.0	12:38:27	88	65
20	56145.9	.06	0.0	12:41:18	88	55
30	56190.1	.03	0.0	12:41:59	88	
40	56301.2	.02	0.0	12:42:52	88	
50	56485.1	.07	0.0	12:44:15	88	
60	56847.2	.03	0.0	12:44:58	88	
70	57296.9	.11	0.0	12:45:31	88	
80	58018.8	.03	0.0	12:46:01	88	
90	58259.9	.03	0.0	12:46:42	88	
100	58010.8	.05	0.0	12:47:14	88	
110	59734.1	.03	0.0	12:47:39	88	
120	64104.9	.80	0.0	12:48:07	58	
130	65729.1	1.5	0.0	12:48:59	68	
140	48965.0	6.6	0.0	12:49:34	32	56
150	44383.6	.35	0.0	12:50:25	55	
160	47607.2	1.1	0.0	12:51:04	48	55
170	56015.8	.13	0.0	12:51:28	75	58
180	50809.8	11.	0.0	12:51:57	43	55
190	54539.3	.05	0.0	12:52:22	88	

Line 15 Date 8 JUN 3 #162

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	50290.0	31.	0.0	12:57:53	42	
20	64935.5	33.	0.0	12:59:43	22	58
30	57328.1	.50	0.0	13:00:12	44	56
40	54093.8	.13	0.0	13:00:32	76	55
50	53650.6	.42	0.0	13:00:52	58	
60	50458.9	1.7	0.0	13:01:17	87	
70	45316.7	.51	0.0	13:02:59	45	56
80	47969.1	48.	0.0	13:05:34	22	
90	61402.5	65.	0.0	13:06:31	32	58
100	68780.6	1.4	0.0	13:07:32	55	55
110	59503.9	.06	0.0	13:08:09	84	56
120	58207.2	.03	0.0	13:08:51	88	
130	58296.3	.02	0.0	13:09:38	88	55
140	58029.9	.03	0.0	13:10:26	88	

150	57352.7	.03	0.0	13:11:05	88	
160	56922.9	.03	0.0	13:12:08	88	
170	56657.3	.03	0.0	13:13:15	88	
180	56418.6	.03	0.0	13:14:06	88	
190	56245.3	.03	0.0	13:15:52	88	
200	56128.1	.03	0.0	13:16:56	88	
210	55965.7	.03	0.0	13:18:12	88	
220	56146.4	.03	0.0	13:19:33	88	

Line 16 Date 8 JUN 3 #184

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55953.3	.07	0.0	13:28:56	88	
20	56099.2	.04	0.0	13:31:20	88	
30	56214.9	.03	0.0	13:31:55	88	
40	56264.7	.03	0.0	13:32:37	88	
50	56164.1	.03	0.0	13:33:06	88	
60	56537.7	.03	0.0	13:33:47	88	
70	56796.0	.03	0.0	13:34:33	88	
80	57123.5	.02	0.0	13:35:05	88	
90	57604.4	.03	0.0	13:35:38	88	
100	58099.9	.02	0.0	13:36:32	88	
110	58857.2	.02	0.0	13:37:10	88	
120	59382.4	.06	0.0	13:37:44	88	
130	59893.4	.05	0.0	13:39:05	88	56
140	55694.9	2.8	0.0	13:40:05	35	
150	54698.1	.21	0.0	13:43:17	78	55
160	56197.6	.92	0.0	13:57:28	48	65
170	49189.7	23.	0.0	13:58:37	44	55
180	52495.1	.21	0.0	14:00:18	78	

Line 17 Date 8 JUN 3 #202

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55347.5	.15	0.0	14:09:21	88	
20	55076.8	.03	0.0	14:12:12	88	
30	54818.4	.03	0.0	14:12:43	88	
40	54455.3	.03	0.0	14:14:02	88	
50	54387.8	.03	0.0	14:14:24	88	
60	54505.1	.04	0.0	14:15:06	88	
70	53288.9	.05	0.0	14:16:08	88	
80	48427.0	.14	0.0	14:16:52	65	56
90	57403.5	.07	0.0	14:29:36	85	58
100	57279.2	.81	0.0	14:30:18	88	55
110	57141.1	.03	0.0	14:32:34	88	
120	57063.8	.03	0.0	14:34:09	88	
130	56904.3	.03	0.0	14:35:07	88	
140	56506.3	.03	0.0	14:36:02	88	
150	56766.2	.03	0.0	14:37:26	88	
160	56904.2	.03	0.0	14:39:39	88	

Line 18 Date 8 JUN 3 #218

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	56091.7	.04	0.0	14:43:47	88	
20	56213.5	.06	0.0	14:53:56	88	
30	56332.1	.03	0.0	14:55:37	88	
40	55976.6	.03	0.0	14:57:16	88	
50	55678.4	.03	0.0	14:57:57	88	
60	55164.2	.04	0.0	14:58:44	88	
70	53728.2	.06	0.0	14:59:33	88	
80	50196.5	1.8	0.0	15:00:27	76	
90	51532.9	.04	0.0	15:01:48	88	
100	53787.3	.02	0.0	15:02:37	88	
110	54513.8	.03	0.0	15:03:12	88	
120	54942.2	.03	0.0	15:03:39	88	

EOF

OMNI-PLUS Tie-line MAG/VLF V12N Ser #418141
TOTAL FIELD DATA (uncorrected)

Reference field: 55000.0
Datum subtracted: 0.0Date 13 JUN 3
Operator: 3000
Records: 159
Bat: 17.0 Volt Lithium: 3.48 Volt
Last time update: 6/13 8:33:00
Start of print: 6/13 17:00:50

Line 70 Date 13 JUN 3 #1

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
60	56369.7	.00	0.0	8:21:12	88	

Line 71 Date 13 JUN 3 #2

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55536.0	.07	0.0	8:24:48	88	55
20	55279.0	.05	0.0	8:26:15	88	
30	54662.3	.22	0.0	8:27:20	88	
40	62733.9	2.9	0.0	8:28:20	34	58
80	63170.1	78.	0.0	8:36:12	22	
90	50792.5	58.	0.0	8:38:12	22	56
100	51809.2	.07	0.0	8:40:13	88	58
110	54524.2	.03	0.0	8:42:04	88	55
120	55217.7	.03	0.0	8:43:24	88	
130	55670.1	.03	0.0	8:44:37	88	
140	56026.1	.03	0.0	8:46:47	88	
150	56084.8	.04	0.0	8:48:09	88	
160	56188.3	.02	0.0	8:49:35	88	
170	56581.2	.07	0.0	8:50:27	88	
180	56268.0	.03	0.0	8:51:29	88	65
190	56449.3	.03	0.0	8:52:17	88	55
200	56530.9	.03	0.0	8:53:03	88	
210	56560.9	.02	0.0	8:54:03	88	
220	56633.1	.03	0.0	8:54:56	88	
230	56692.5	.03	0.0	8:55:59	88	
240	56844.4	.03	0.0	8:56:53	88	
250	56857.5	.03	0.0	8:58:19	88	
260	56863.2	.03	0.0	8:59:27	88	
270	56908.4	.02	0.0	9:00:17	88	85
280	56966.8	.03	0.0	9:01:05	88	65
290	56890.2	.03	0.0	9:02:06	88	
300	56805.0	.03	0.0	9:02:55	88	55
310	56698.4	.02	0.0	9:03:42	88	85
320	56640.4	.03	0.0	9:04:32	88	55
330	56534.0	.14	0.0	9:05:13	88	85
340	56442.9	.03	0.0	9:06:02	88	55
350	56299.8	.03	0.0	9:07:07	88	65
360	56526.6	.03	0.0	9:07:35	88	85

Line 72 Date 13 JUN 3 #35

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	56656.6	.03	0.0	9:09:50	88	55
20	57170.3	.19	0.0	9:10:43	88	65
30	56641.5	.04	0.0	9:11:16	88	55
40	57095.9	.16	0.0	9:11:37	78	
50	56818.2	.03	0.0	9:11:59	88	
60	56736.0	.03	0.0	9:12:19	88	
70	56516.4	.03	0.0	9:12:39	88	
80	56554.6	.04	0.0	9:12:59	88	
90	56477.4	.02	0.0	9:13:18	88	
100	56825.1	.05	0.0	9:13:38	88	
110	56762.9	.03	0.0	9:13:57	88	
120	56876.5	.04	0.0	9:14:14	88	

1746	130	56745.5	.03	0.0	9:14:33	88		
1671	140	56670.5	.03	0.0	9:14:53	88		
1437	150	56437.6	.03	0.0	9:15:11	88		
1408	160	56407.8	.03	0.0	9:15:30	88		
881	170	55881.0	.03	0.0	9:15:50	88		
506	180	55505.8	.04	0.0	9:16:10	88		
-169	190	54830.9	.04	0.0	9:16:29	88		
-898	200	54102.2	.04	0.0	9:16:48	88		
-1604	210	53395.9	.06	0.0	9:17:07	88		
-2777	220	52223.0	.08	0.0	9:17:27	88	65	
-9485	230	45515.2	26.	0.0	9:17:47	22	56	
-226	240	54773.9	.52	0.0	9:18:25	55	58	
-424	250	54576.1	.04	0.0	9:18:46	88	55	← road intersection of rock saw cut. (as per notes).
-37	260	54963.3	.03	0.0	9:19:27	88		
33	270	55033.1	.04	0.0	9:19:48	88	65	
-597	280	54413.3	.82	0.0	9:20:08	78	55	
-1478	290	53522.1	.04	0.0	9:20:25	88		
-1602	300	53398.4	.04	0.0	9:20:43	88		
-1211	310	53739.4	.03	0.0	9:21:02	88		
-1002	320	53998.0	.03	0.0	9:21:21	88		
-627	330	54377.6	.03	0.0	9:21:39	88		
-404	340	54596.3	.04	0.0	9:21:57	88		
-101	350	54898.5	.04	0.0	9:22:16	88	65	
81	360	55087.5	.03	0.0	9:22:36	88	55	
250	370	55249.7	.04	0.0	9:22:55	88		← by intersection at Ec 600 (See notes)
-1129	380	53870.9	.62	0.0	9:23:28	78		
1099	390	56098.5	.05	0.0	9:32:52	88		
1369	400	56369.1	.03	0.0	9:33:14	88		
1584	410	56583.9	.03	0.0	9:33:35	88		
1426	420	56426.3	.02	0.0	9:33:57	88		
1162	430	56162.3	.03	0.0	9:34:20	88		
1392	440	56391.6	.03	0.0	9:34:41	88		
1266	450	56266.1	.02	0.0	9:35:03	88		
1232	460	56231.7	.03	0.0	9:35:24	88		
1138	470	56837.7	.21	0.0	9:35:44	78	65	
1356	480	56356.1	.03	0.0	9:36:05	88	55	
1329	490	56329.3	.03	0.0	9:36:24	88	65	
1606	500	56605.5	.04	0.0	9:36:45	88	55	
1997	510	56996.9	.11	0.0	9:37:06	88	85	
1963	520	56962.7	.09	0.0	9:37:27	78	55	
1588	530	56587.8	.03	0.0	9:37:47	88		
2095	540	57095.2	.19	0.0	9:38:07	78		
1361	550	56361.3	.03	0.0	9:38:28	88		
1304	560	56304.1	.03	0.0	9:38:49	88		
1344	570	56344.4	.03	0.0	9:39:12	88		
1217	580	56217.8	.03	0.0	9:39:37	88		
1259	590	56259.7	.03	0.0	9:40:00	88	65	
1182	600	56181.7	.03	0.0	9:40:21	88	85	
1156	610	56156.3	.03	0.0	9:40:47	88	55	← end of road (took Right fork into trees) See notes
1154	620	56153.6	.03	0.0	9:42:47	88		
1122	630	56122.2	.04	0.0	9:43:43	88		
1151	640	56151.2	.04	0.0	9:44:38	88		
1030	650	56030.3	.04	0.0	9:46:16	88		
1026	660	56026.0	.04	0.0	9:47:46	88		
1046	670	56043.1	.03	0.0	9:48:52	88		
1065	680	56065.3	.04	0.0	9:49:52	88		
1048	690	56048.4	.03	0.0	9:51:01	88		
1081	700	56081.2	.04	0.0	9:51:57	88		
1085	710	56085.1	.06	0.0	9:53:15	88		
1083	720	56083.1	.04	0.0	9:54:04	88		
1130	730	56130.2	.04	0.0	9:54:42	88		
1041	740	55640.9	.11	0.0	9:55:28	78		
1108	750	56108.1	.04	0.0	9:56:01	88		
1040	760	56039.5	.04	0.0	9:57:40	88		
1083	770	56082.9	.03	0.0	9:58:37	88		
963	780	55962.8	.03	0.0	9:59:27	88		
966	790	55966.0	.04	0.0	10:00:11	88		
900	800	55900.4	.04	0.0	10:01:05	88		
860	810	55860.3	.03	0.0	10:02:09	88		

JUN13REM

820	55858.7	.03	0.0	10:03:17	88	
830	56400.6	.07	0.0	10:03:57	88	
840	55896.4	.05	0.0	10:05:22	88	
850	55705.6	.04	0.0	10:05:50	88	
860	55534.8	.04	0.0	10:06:16	88	
870	55507.9	.03	0.0	10:06:43	88	
880	55444.5	.03	0.0	10:07:10	88	
890	55448.5	.02	0.0	10:07:36	88	
900	55458.3	.02	0.0	10:08:02	88	
910	55493.7	.02	0.0	10:08:29	88	

end of line does not match map (spread out stations over line length).

Line 73 Date 13 JUN 3 #126

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	55724.7	.02	0.0	11:42:59	88	
20	55535.0	.04	0.0	11:45:46	88	
30	55582.1	.03	0.0	11:46:46	88	
40	55571.3	.04	0.0	11:47:24	88	
50	55431.4	.04	0.0	11:48:13	88	
60	55227.2	.03	0.0	11:48:54	88	Jake Claims
70	55320.7	.04	0.0	11:49:47	88	
80	55259.7	.03	0.0	11:50:09	88	
90	55178.7	.03	0.0	11:50:33	88	
100	55210.0	.03	0.0	11:51:31	88	
110	55424.8	.03	0.0	11:53:11	88	

Line 74 Date 13 JUN 3 #137

POSITION	FIELD	ERR	DRIFT	TIME	DS	CULT
10	56215.5	.03	0.0	13:15:05	88	
20	56378.0	.03	0.0	13:16:56	88	
30	56990.5	.03	0.0	13:17:18	88	
40	56279.9	.03	0.0	13:17:51	88	
50	55484.3	.03	0.0	13:18:23	88	
60	55407.2	.03	0.0	13:18:52	88	
70	55654.1	.03	0.0	13:20:45	88	Jake Claims
80	56096.6	.03	0.0	13:21:04	88	
90	56030.5	.04	0.0	13:21:27	88	
100	55509.5	.03	0.0	13:21:54	88	
110	55776.8	.03	0.0	13:22:14	88	
120	56275.4	.03	0.0	13:22:34	88	
130	56203.8	.03	0.0	13:22:55	88	
140	56617.7	.04	0.0	13:23:15	88	
150	56110.2	.03	0.0	13:23:35	88	
160	56222.3	.03	0.0	13:24:04	88	
170	56169.1	.03	0.0	13:24:24	88	
180	54979.1	2.8	0.0	13:24:58	55	
190	55928.5	.03	0.0	13:25:19	88	
200	55948.7	.03	0.0	13:25:49	88	
210	56024.6	.03	0.0	13:26:25	88	
220	55969.8	.14	0.0	13:26:42	88	
230	55967.1	.03	0.0	13:27:01	88	

EOF

APPENDIX VII

INTERNATIONAL METALLURGICAL TESTING

January 31, 2004

INTERNATIONAL METALLURGICAL AND ENVIRONMENTAL INC.
13-2550 Acland Road, Kelowna, B.C., CANADA, V1X 7L4, Telephone (250) 491-1722, Facsimile (250) 491-1723

PRELIMINARY REPORT

ICP & WHOLE ROCK ANALYSES OF MAGNETITE OUTCROP DRILL - EXPECTED WEEK OF JAN 23rd, 2003

JAN 17, 2003

January 6, 2003

Mr Steve Gardner
Hillsborough Resources Limited
PO Box 5000
Campbell River, B.C.
V9W 5C5

Dear Steve Gardner

A bulk sample of magnetite ore was submitted to International Metallurgical and Environmental Inc. for metallurgical testing and to evaluate the magnetite concentrate produced as a heavy media product for use in coal cleaning circuits.

The magnetite produced in this particular test program exceeds the specific gravity and percentage magnetics specifications but was marginally coarser than the magnetite generally supplied to coal cleaning operations.

Sample	Specific Gravity g/cc	Percent Magnetics (900 Gauss)	Passing 45 micron %	Passing 38 micron %	Passing 10 micron %
Magnetite Conc.	5.04	99.7	87.5	74.9	17.0
Magnetite specifications	>4.7	>95	>90	>75	<30

Approximately 10 kilograms of magnetite concentrate was produced and has been prepared for use in marketing surveys.

Test Procedure

A series of test grinds were conducted in a stainless steel laboratory rod mill to determine the grind size in relation to grind time. A batch of approximately 20 kilograms of material was ground to a size of 80% passing 174 microns and this was pumped as a slurry with water to a single stage magnetic drum separator. The process flowsheet is given in Diagram 1.

INTERNATIONAL METALLURGICAL AND ENVIRONMENTAL INC.
13-2550 Acland Road, Kelowna, B.C., CANADA, V1X 7L4, Telephone (250) 491-1722, Facsimile (250) 491-1723

The rougher magnetic concentrate produced was reground in a laboratory rod mill to a sizing of 80% passing 41 microns. This rougher concentrate was then processed using the single magnetic drum separator, circulating the slurry to simulate a multi-stage cleaning operation and the cleaner concentrate collected as the final magnetite product.

The magnetite concentrate was submitted for sizing analysis, percentage magnetics (Davis Tube at 900 gauss) and specific gravity determinations.



Diagram 1 – Magnetite testwork flowsheet

Results and Discussion

The bulk magnetite ore sample submitted to International Metallurgical and Environmental Inc. for testing contained approximately 80 percent magnetics.

At a primary grind size of 80 percent passing 174µm, the magnetic rougher concentrate contained 91.2% magnetics with a magnetics recovery of 99.0%. The rougher tails were analysed at 5.4% magnetics. (See Appendix 1). The primary grind size used for this testwork (80% passing 174µm) is approximately the grind size used in similar test programs conducted by International Metallurgical and Environmental Inc. on other magnetite ores.

The final cleaner concentrate produced was 99.7% magnetics and a cleaner tails sample analysed at 20.2% magnetics. As the cleaning circuit was operated in an open circuit configuration, no mass balance and recovery data was prepared. In a closed circuit configuration the cleaner tails would be re-circulated within the process circuit.

INTERNATIONAL METALLURGICAL AND ENVIRONMENTAL INC.
13-2550 Acland Road, Kelowna, B.C., CANADA, V1X 7L4, Telephone (250) 491-1722, Facsimile (250) 491-1723

The magnetite product had a sizing of 87.5% passing 45 micron and 17.0% passing 10 micron, marginally coarser than that typically supplied to coal cleaning operations. (See appendix 2). The fineness of the magnetite product was limited by the operating characteristics of the laboratory rod mill as the secondary grinding stage. The magnetite concentrate produced in a large scale operation is expected to be finer with the use of a ball mill for secondary grinding, operating in closed circuit with hydro-cyclones.

The specific gravity of the ground magnetite product was 5.04 g/cc.

The Bond Work Index of the bulk sample submitted for testing was determined to be 15.3kWhr/tonne. (Appendix 3)

A whole rock analysis and ICP multi-element analysis are given in Appendices 4 and 5. These results are in line with magnetite produced for use in coal processing plants.

RESULTS AWAITED BUT EXPECTED TO BE TYPICAL OF OTHER MAGNETITE PRODUCTS

Overall magnetite recovery from this material in a production scale operation is anticipated to be at least 95% and this testwork has indicated that the product will meet the specifications required by coal processing plants.

The optimum grind size for the Hillsborough magnetite ore must be established in relation to particle liberation size to determine the primary grinding power requirements and maximize magnetite recovery.

Please call with any questions

Yours truly

Jeff Austin, P.Eng., - President
International Metallurgical and Environmental Inc.

Appendix 1

International Metallurgical and Environmental Inc.
Magnetic Separation Test Summary

Project: Hillsborough
Mag Sep Test No. 100
Test Sample: Magnetite ore

Primary Grind: 7 min, P_{80} = 174um

Metallurgical Balance

Sample	Weight %	Magnetics %	Distribution Magnetics %
Rougher Conc	85.2	91.2	99.0
Final Tail	14.8	5.4	1.0
Calculated Head	100.0	78.5	100.0
Sampled Head		82.8	
Cleaner Concentrate		99.7	n/a
Cleaner Tails		20.2	n/a

International Metallurgical and Environmental Inc.
Summary of Magnetite Analysis

Project : Hillsborough
Sample: Magnetite Concentrate
Reporting Date: December 31, 2002

Sample	Specific Gravity	Percent Magnetics (900 Gauss)	Passing 45 micron %	Passing 38 micron %	Passing 10 micron %
Magnetite Conc.	5.04	99.7	87.5	74.9	17.0

Jeffrey B. Austin, P. Eng.- President
International Metallurgical and Environmental Inc.

International Metallurgical and Environmental Inc.
Bond Ball Mill Work Index Determination

Project: Hillsborough Magnetite
Sample: Magnetite Composite
Mesh Size used in test: 200 mesh (75 µm)

Weight of 700 cc of fresh feed : 1730.5g

Cycle	Revolutions	Product Oversize g	Product Undersize g	Circulating Load %	Product per Rev. g/rev
1	200	1,396.0	328.3	425.2	1.51
2	301	1,361.7	363.5	374.7	1.11
3	410	1,264.7	464.0	272.5	1.04
4	436	1,244.4	477.9	260.4	1.01
5	451	1,235.4	495.0	249.6	1.01
6	451	1,232.8	499.8	246.7	1.02

80 percent passing size for test feed :	4075	microns	see attached
80 percent passing size for product :	56	microns	screen analysis
Average grindability of last 3 cycles :	1.013	grams/rev	
Calculated Bond Work Index :	15.3	kWhr/tonne	
	13.9	kWhr/st	

International Metallurgical and Environmental Inc.
Screen Analysis

Project: Hillsborough Magnetite
Sample: Magnetite Composite

Bond Work Index - Feed

Screen Size		% Retained		Cumulative
Mesh	Micron	Individual	Cumulative	% Passing
4	4750	9.5	9.5	90.5
6	3350	22.1	31.7	68.3
8	2360	11.4	43.1	56.9
10	1700	9.2	52.3	47.7
14	1180	7.8	60.0	40.0
20	850	6.1	66.2	33.8
28	600	5.5	71.6	28.4
35	425	4.2	75.9	24.1
48	300	4.2	80.1	19.9
65	212	3.8	83.9	16.1
100	150	3.1	87.0	13.0
150	106	2.5	89.4	10.6
200	75	2.7	92.1	7.9
270	53	1.6	93.7	6.3
400	38	1.7	95.4	4.6
Minus 400	-38	4.6	100.0	

Bond Work Index - Product

Screen Size		% Retained		Cumulative
Mesh	Micron	Individual	Cumulative	% Passing
65	212	0.0	0.0	100.0
100	150	0.1	0.1	99.9
150	106	0.2	0.3	99.7
200	75	2.7	3.0	97.0
270	53	20.4	23.4	76.6
400	38	21.0	44.4	55.6
Minus 400	-38	55.7	100.0	

80 Percent passing size for feed	4075	microns
80 Percent passing size for product	56	microns

International Metallurgical and Environmental Inc.
Screen Analysis Summary

Project: Hillsborough - Sayward Project
Sample: Magnetite Feed - Grind #10 - 7 minute
Date: December 16, 2002
80 % passing **174 µm**

Mesh Size	Micron Size	% Retained		Cum. % Passing
		Individual	Cumulative	
20	850	0.2	0.2	99.8
28	600	0.1	0.3	99.7
35	425	0.0	0.3	99.7
48	300	0.7	1.0	99.0
65	212	8.2	9.2	90.8
100	150	17.9	27.1	72.9
150	106	16.0	43.1	56.9
200	75	17.0	60.1	39.9
270	53	9.9	70.0	30.0
400	38	8.6	78.6	21.4
-400	-38	21.5	91.6	8.4



Hillsborough Magnetite - Primary Test Grind Sizes



International Metallurgical and Environmental Inc.
Screen Analysis Summary

Project: Hillsborough
Sample: Test 100 - Ro Conc 22 min. re-grind
Date: December 19, 2002
80 % passing **41** **µm**

Mesh Size	Micron Size	% Retained		Cum. % Passing
		Individual	Cumulative	
28	600	0.0	0.0	100.0
35	425	0.0	0.0	100.0
48	300	0.0	0.0	100.0
65	212	0.0	0.0	100.0
100	150	0.0	0.0	100.0
150	106	0.0	0.0	100.0
200	75	0.6	0.7	99.3
270	53	5.6	6.3	93.7
325	45	7.8	14.1	85.9
400	38	11.5	25.6	74.4
-400	-38	74.4	100.0	



International Metallurgical and Environmental Inc.
Screen Analysis Summary

Project: Hillsborough
Sample: Test 100 - Cleaner Conc
Date: December 31, 2002
80 % passing **41** **µm**

Mesh Size	Micron Size	% Retained		Cum. % Passing
		Individual	Cumulative	
28	600	0.0	0.0	100.0
35	425	0.0	0.0	100.0
48	300	0.0	0.0	100.0
65	212	0.0	0.0	100.0
100	150	0.0	0.0	100.0
150	106	0.0	0.0	100.0
200	75	0.6	0.6	99.4
270	53	5.9	6.5	93.5
325	45	6.0	12.5	87.5
400	38	12.6	25.1	74.9
-400	-38	74.9	100.0	



International Metallurgical and Environmental Inc.
Cyclosizing Analysis Summary

Project: Hillsborough
Test No.: T100
Sample: Cleaner Concentrate
Reporting Date December 31, 2002
% Passing 10 µm: 17.0

Sieve Size			% Retained		
Mesh Size	Cyclone Size (µm)	Wt grams	Individual	Cumulative	Cumulative % Passing
Cyclone 1	34	6.24	12.5	12.5	87.5
Cyclone 2	25	15.52	31.0	43.5	56.5
Cyclone 3	18	10.82	21.6	65.2	34.8
Cyclone 4	11	6.38	12.8	77.9	22.1
Cyclone 5	8	3.35	6.7	84.6	15.4
Minus Cyclone 5	minus 8	7.69	15.4	100.0	
		50.0027			



Date 3/5 Pages 2
From Sandvik
Co. Jerry Akurst
Phone 920 734 7600
Fax 7151
Post-it® Fax Note 7671
To PRA
Co./Dept. Attn: Peter Tse
Phone
Fax 604-322-0181

SANDVIK

Sandvik Rock Processing

Feb. 5th, 2002

Process Research Associates Ltd.
9145 Shaughnessy Street
Vancouver, B.C. Canada V6P 6R9

Attention: Peter Tse

Enclosed are the results of testing the material received in a 5 gal. Bucket. on Jan 22, 2002. The material appeared to be a Magnetite Ore. The container received was not marked with any thing else.

The abrasion index of the samples was tested by the use of the Pennsylvania Abrasion index device, in which a 76-mm by 25-mm- by 6-mm (3-in by 1-in by 1/4-in.) piece of 500 Brielle SAE 4130 chrome-nickel-molybdenum steel rotates in a falling stream of ore under standard conditions and the weight loss is measured. The abrasion index (*Ai*) is then used to empirically predict wear rates of crusher liners,

During operation the single paddle strikes a column of falling rock or ore particles. The sampling size is four 400 gram samples of broken rock, mineral or ore, (assuming that the solid density is 160 pounds per cubic foot),which are sized to pass Tyler screen 0.742 and to be held upon screen 0.50. A complete test consists of 1,600 grams run as four batches of 400 grams each. Each 400 gram portion is run exactly 15 minutes by stop watch; then the drum is opened and cleaned out, a fresh lot of material is added and the test is continued. Before this test this paddle is demagnetized, and is accurately weighed on a balance, to a tenth of a milligram. After the completed run of 1,600 grams the paddle is removed and washed clean of all rock particles, dried, demagnetized and reweigh. The loss of weight recorded in tenths of a milligram represents the abrasive index for the particular rock, mineral or ore.

Sample Number	Abrasion Index	Sandvik Test #
	0.0846	A02105

For comparison purposes the test appeared to have characteristics that would generally indicate less than normal wear when crushed in a compression type crusher. As a general observation it should be noted that during the test the

Sandvik Rock Processing
1051 N. Lindale Drive
Appleton Wi. 54914

Phone 920-734-7600 Fax. 920-734-7151

material did breakdown fairly quickly in the impact testing device. This may result in a slightly misleading index for crushing.

As a quick reference, the abrasion test values for tested limestone obtained in the Sandvik rock lab for the last two years, together with the corresponding high energy work index values, are displayed in the table below. The line across the high energy work index values represents the mean of the values, whereas the line across the abrasion values represents the median of all tests. The mean work index for limestone is 9.41 kwh/st, while the median abrasion index for limestone is 0.0152.



Regards:
Jerry Heckert
Supervisor Application Eng. & Laboratory Testing

Sandvik Rock Processing
1051 N. Lindale Drive
Appleton WI. 54914

Phone: 920-734-7600 Fax. 920-734-7131

BOND MILL GRINDABILITY TEST* REPORT

Client: Tilbury Cement
Test: BI-1
Sample: Magnetite-Sayward

Date: 2-Oct-01
Project: 0100101

TEST CONDITIONS

Cycle	Oversize Wt. (grams)	Product Wt. (grams)	Feed Undersize (grams)	Net Product (grams)	Product per Rev. (grams/rev.)	Required Rev. (rev.)
1	1,393	1,935	889	145	1.45	100
2	1,767	661	379	282	1.30	216
3	1,748	680	242	437	1.26	346
4	1,743	685	249	436	1.24	351
5	1,737	691		440	1.24	356
6	1,735	693	252	439	1.23	356

SIZE ANALYSIS

Sieve Size		% Passing	
Tyler mesh	µm	Feed	Product
8	2,380	98.3	
10	1,680	92.7	
14	1,190	84.8	
20	841	79.8	
28	595	74.6	
35	420	69.4	
48	297	64.1	
65	210	57.8	
100	149	51.2	
150	105	43.5	
200	74	36.6	100.0
270	53	25.9	66.6
325	44	23.2	56.5
400	37	22.0	49.4

TEST RESULTS

Material Charge Wt.-700 mL(g) = 2,428
Test Screen (µm) = 74
Undersize in Feed (%)= 36.64
Circulating Load (%) = 251
Gbg (ave.) = 1.24
Product P_{80} (µm) = 61.6
Feed F_{80} (µm) = 856
W (kWh/ton) = 14.9
W (kWh/tonne) = 16.4

* Bond, F.C. Crushing and Grinding Calculations. Part I and II. British Chemical Engineering 6: 378-391, 543-548, 1960.



IRON
Hill

IRON
Hill

IRON
Ross

IRON
Bella

IRON
Mike

OLD
MINE
SITE

N

0 50 100

1:2000

MAP 11

FIGURE 11
IRON ROSS PROJECT
LOCATION of Magnetometer Lines

FIGURE 11

Line 1
Line 2
Line 3
Line 4
Line 5
Line 6
Start
Start
Start
Start
Start
Start
Start line
N
SCALE
1 : 200
0 5 10m
IRON STEVE ZONE
Location of DRILL HOLES + SECTION LINES
FIGURE 13



LONGITUDINAL SECTION 0+30E
IRON STEVE ZONE.
SCALE 1:200
LOOKING EAST

FIGURE 14



GEOLOGICAL SURVEY
ASSESSMENT

27,438

LONGITUDINAL SECTION 0+00 E
IRON STEVE ZONE
SCALE 1:200
LOOKING EAST

FIGURE 15



N
530
530.8
BROKEN LIMESTONE
SKARN DYKE/SILL
SKARN 318deg/vert to irreg
45 deg cont with magnetite
magnetite
DYKE WITH GARNET CAP
pebbly dyke
garnet skarn
BLAST OVERSIZE
MAGNETITE BLAST
MAGNETITE
toe
GARNET SKARN + SKARNIFIED INTERVAL
X-S 0+00
X-S 0+20
X-S 0+40
X-S 0+55
X-S 0+60
X-S 0+80
518.4385
521.2866
520.8618
522.8181
522.3016
525.1058
527.6794
528.7628
528.3274
529.5775
530.2496
530.6144
530.0213
528.8612
530.1545
528.9522
530.4675
529.9546
530.1298
529.9085
528.8571
529.6444
532.0900
SCALE 1:200
SAYWARD PROJECT
IRON STEVE CLAIM
COMPLETED WORK PROGRAM 2003
HOMEGOLD RESOURCES LIMITED
HILLSBOROUGH RESOURCES LIMITED
DATE: 12/03
DRAWN BY: L.L.
FIGURE 23
27,738



GEOLOGICAL SURVEY BRANCH
ASSESSMENT REPORT

SCALE 1: 2000

27,150

MAGNETOMETER
LINES
Values

IRON ROSS PROJECT

FIGURE 24



GEOLOGICAL SURVEY BRANCH

27,438

IRON STEVE ZONE

MAGNETOMETER

FIGURE 25


Start
Line 25
Start
Line 22
Line 23
Line 18
Line 20
Start
Start
Start
Line 24
Line 19
Line 16
Start
Start
Start
Line 14
Line 21
Line 17
Start
Start
Start
Line 15
Line 13
Line 11
Start
1000
2000
3000
5000
SCALE 1:1000
IRON MIKE + WEST PIT AREA
27-438
FIGURE 26



SCALE 1:1,000

IRON HERB ZONES
MAGNETOMETER

FIGURE 27



scale 1:1000

GEOLOGICAL SURVEY BRANCH

27 438

IRON ROSS
+
IRON BETHEA

MAGNETOMETER

FIGURE 28