

RECEIVED

AUG 14 2007

Gold Commissioner's Office
VANCOUVER, B.C.

**DIAMOND DRILLING
ASSESSMENT REPORT**

on the

**LANG BAY (DUCK LAKE) KAOLINITE DEPOSIT
Tenure # 514350, 514352, 514363, 514264,
514349, 514353-355, 514357, 514362**

Longitude 124°24'29"/Latitude 49°48'48"

NTS: 92F/16W (92F.088)

Vancouver M.D.

Prepared for

Electra Gold Ltd.

Unit 5 - 2330 Tyne St.,

Port Coquitlam, B.C.,

V3C 2Z1

Phone: 604-970-6402 / Fax: 604-944-6102

Web Site: www.ElectraGoldLtd.com

Prepared by

J. T. SHEARER, M.Sc., P.Geo.

GEOLOGIST

May 15, 2007

Fieldwork completed between November 15, 2006 and December 20, 2006

**2007-2009
GEOLOGICAL SURVEY BRANCH
ASSESSMENT REPORT**

TABLE OF CONTENTS

	<u>Page</u>
LIST OF ILLUSTRATIONS and TABLES.....	ii
SUMMARY	iii
INTRODUCTION.....	1
LOCATION and ACCESS.....	2
CLAIM STATUS.....	3
HISTORY.....	4
REGIONAL GEOLOGY	6
LOCAL GEOLOGY	7
2006 DIAMOND DRILLING.....	8
GEOPHYSICS.....	10
CONCLUSIONS and RECOMMENDATIONS	11
COST ESTIMATE for FUTURE WORK	12
REFERENCES.....	13
APPENDICES	
Appendix I Statement of Qualifications.....	15
Appendix II Statement of Costs	16
Appendix III Drill Hole Logs.....	17
Appendix IV Assay Certificates.....	18
Appendix V Drill Contract	19

LIST of ILLUSTRATIONS and TABLES

ILLUSTRATIONS and TABLES

	<u>Following Page</u>
FIGURE 1 Location Map,	1
FIGURE 2 Topography Map, 1:50,000,	2
FIGURE 3 Claim Map, 1:50,000.....	3
FIGURE 4 Surface Tenure Map, 1:20,000	4
FIGURE 5 Regional Geology	5
FIGURE 6 Local Geology and Stratigraphy	7
FIGURE 7 Trim Map of Duck Lake Area and Drillhole Locations, 1:20,000.....	8
FIGURE 8 Geological Model of Basin Development	9
FIGURE 9 Overburden Thickness Contours	10


TABLES

	<u>Page</u>
TABLE I List of Claims	3
TABLE II Diamond Drill Hole Data 1999	5
TABLE III Diamond Drill Hole Data 2006	9

SUMMARY

- 1) The Lang Bay (Duck Lake) Property consists of the 17 cell mineral claims totalling 2,148 ha.
- 2) The claims are located 3 km north of Highway 101 at Myrtle Point. Access is via the Duck Lake Forest Service Road or along the powerline from Zilinski Road.
- 3) The claims cover the western and eastern margins of an Upper Cretaceous sedimentary basin containing shale, sandstone and minor coal.
- 4) Work on the sedimentary basin originally (1940's to 1960's) focussed on germanium in the ash of the coal beds exposed in Lang Creek. Subsequently the kaolinite potential was realized in 1986.
- 5) A previous owner entered into a joint-venture agreement with Brenda Mines Ltd., a Noranda Group company, in September 1987. An extensive exploration program was initiated in September 1987, which continued until February 1989. Work completed during that time consisted of 6,700 metres of seismic refraction survey, 10,500 metres of magnetometer survey, 11,000 metres of Dipole-Dipole resistivity survey, 4 Schlumberger electrical soundings and 2,100 metres of reverse circulation and diamond drilling.
- 6) In February 1992 Fletcher Challenge Canada carried out a trial at Elk Falls paper mill near Campbell River. The trial produced 60 tonnes of newsprint containing up to 5% load of kaolin from the eastern margin of the Duck Lake area. This test was apparently favourable.
- 7) Overburden consisting of bouldery gravels, sand, till and clay-rich glaciofluvial units, is highly variable in thickness.
- 8) In 1999, a program was completed of 4 diamond drill holes (198.88m) and 4.3 km of seismic refraction geophysics and metallurgical work was done in 2006.
- 9) Current work as documented in this report documents a 5 hole diamond drill program completed in December 2006 for a total footage of 293.53m (963 ft.).
- 10) The 2006 drill program intersected a series of interbedded kaolinized sandstone and shale beds in 5 holes, however the overburden was relatively deep, up to 27m deep.
- 11) Placing the resulting filler products with industrial end users is recommended to obtain feedback on optimizing product specifications.

Respectfully submitted,



J.T. (Jo) Shearer, M.Sc., P.Geo.
Geologist
May 15, 2007



INTRODUCTION

In 1999, the Duck Lake Mineral Claims were staked covering the western margin of the Cretaceous Sedimentary Basin near Powell River, British Columbia. Subsequently, the eastern portion was acquired in 2001. These claims cover a basin, which contains a large inferred resource of kaolin. Additionally, the property is known to contain highly anomalous values of germanium and gallium in some of the more carbonaceous horizons of the deposit.

Basement granitoid rocks, which in places are extensively altered to kaolin, are overlain by shales containing kaolin clays. Work in 1999 consisted of 4 diamond drillholes and 4.3 km of seismic refraction surveys. In the late 1980's and early 1990's an effort was made to evaluate the eastern margin of the basin. In February 1992 Fletcher Challenge Canada carried out a trial at Elk Falls paper mill near Campbell River. The trial produced 60 tonnes of newsprint containing up to 5% load of kaolin from the eastern margin of the Duck Lake area. This test was apparently favourable.

A calcining test was carried out on a sample of Lang Bay kaolin by Nord Kaolin Company of Jeffersonville, Georgia. The sample was first beneficiated by Magnetic separation and ozone bleaching and this improved the brightness to that of a standard performance filler. The sample was then calcined and brightness values equivalent to those of imported calcined grades were achieved. This is significant because calcined kaolin produces a superior performance and sells for up to four times the price of filler grade. The calcined grade requires heating by natural gas, which only recently has been made available for industrial users in the Powell River area.

The current 2006 program consisted of continued organizing of the core logging facility, continuing assessing the previously drilled core and reverse circulation samples and completing a 293.53m (963 ft.) diamond drill program in 5 holes during December 2006.



NOTE:

This map is a segment of the NTS map sheet 92 F/16, "HASLAM LAKE".

LANG BAY SHALE/SANDSTONE PROSPECT, POWELL RIVER AREA, B.C.		
SEISMIC REFRACTION SURVEY		
LOCATION PLAN		
DATE: SEPTEMBER 1999	SCALE 1:50,000	FIG. 1

LOCATION and ACCESS

The Duck Lake Claims are northeast of Myrtle Point near the town of Powell River. Highway 101 follows the coast from Saltery Bay to Powell River and passes 2 km south of the southern border of the Duck Lake claim group. A good paved secondary road (Zilinski Road) connecting to Highway 101 between Lang Creek and Kelly Creek extends north end then west where a tote road along the power line in useable condition, gives access to the area where the drilling was undertaken. The drill area is also accessible by driving north along the Duck Lake Forest Service Road to the power line area.

The claim group lies 15 km southeast of the town of Powell River, British Columbia and centred on Kelly Creek. General physiographic boundaries are Malaspina Strait between Lang Bay and Myrtle Point to the south, Myrtle Creek and Hammil Lake to the west and northwest, Lang Creek to the north and Whitall Creek to the east. The approximate co-ordinates are 49°48'N and 124°25'W. The NTS map reference for the area is 92F/16W.

The moderately undulating terrain has a maximum elevation of approximately one hundred and eighty metres above sea level near the northeast corner of the property. The ground slopes gently to the southeast. Kelly Creek has cut its valley about 10 metres below the general level of the surrounding area.


The area is covered with a mixed second growth forest consisting mainly of fir, hemlock, cedar and alder. The area was first logged around 1920.

The water supply is plentiful due to the many streams and creeks on the property, the main ones being centrally located, Lang Creek and Kelly Creek, both flowing southeasterly and to the west, Deighton Creek flowing southerly into Malaspina Strait.

The climate is mild with an annual rainfall from 40 to 50 inches (100 - 125mm) and minimal snowfall in the winter.

Dissecting the property in a northwest to southeast line is a high voltage power line to the town of Powell River and the pulp mill.

The 2006 drill sites were accessed by the old road which continues north on crownland from the core logging facility.




1999 Drilling Area

Primary Kaolinite Deposit outlined in 1987-1988




2006 Drilling Area

TOPOGRAPHIC MAP

FIG 2



KEY

-  Claim boundary
-  Paved highway
-  Inferred boundary of Sedimentary Basin

LOCATION MAP
LANG BAY KAOLIN PROSPECT

FIG. 1

CLAIM STATUS

The Duck Lake Property consists of the 17 claims totalling 103 cells of 2,273.13 ha as tabulated in Table I and shown on Figure 3.

TABLE I
List of Claims

Claim Name	Tenure #	Cells	Area (ha)	Registered Owner	Issue Date	Current Good To Date*
	514363	5	104.260	J. T. Shearer	June 11/05	Sept. 11, 2011
	515264	5	104.275	Electra Gold Ltd	June 11/05	Sept. 11, 2011
	515267	2	41.701	Electra Gold Ltd	June 11/05	Sept. 11, 2011
	514359	5	104.240	J. T. Shearer	June 11/05	Sept. 11, 2011
	515265	8	166.840	J. T. Shearer	June 25/05	Sept. 11, 2011
Duck Lake Southwest	514362	10	208.590	J. T. Shearer	June 11/05	June 11, 2011
Duck Lake South	514365	12	250.370	J. T. Shearer	June 11/05	June 11, 2011
Duck Lake S.	514357	20	417.150	J. T. Shearer	June 11/05	June 11, 2011
	514379	1	20.850	J. T. Shearer	June 11/05	Sept. 11, 2011
Duck Lake	514349	1	20.850	J. T. Shearer	June 11/05	June 11, 2011
Lang Bay Pick up	517151	2	41.700	J. T. Shearer	July 12/05	July 12, 2011
	514350	3	62.550	J. T. Shearer	June 11/05	Sept. 11, 2011
	514355	12	250.160	J. T. Shearer	June 11/05	Sept. 11, 2011
	514352	4	83.395	J. T. Shearer	June 11/05	Sept. 11, 2011
	514353	4	83.400	J. T. Shearer	June 11/05	Sept. 11, 2011
Duck Lake Southwest	514354	9	187.680	J. T. Shearer	June 11/05	Sept. 11, 2011
Duck Lake Fill	556422		125.1245		April 15/07	April 8, 2008

17 Claims 103 cells 2,273.1355 ha

* with application of assessment work documented in this report.











Under the present status of mineral claims in British Columbia, the consideration of industrial minerals requires careful designation of the product end use. An industrial mineral is a rock or naturally occurring substance that can be mined and processed for its unique qualities and used for industrial purposes (as defined in the *Mineral Tenure Act*). It does not include "Quarry Resources". Quarry Resources includes earth, soil, marl, peat, sand and gravel, and rock, rip-rap and stone products that are used for construction purposes (as defined in the *Land Act*). Construction means the use of rock or other natural substances for roads, buildings, berms, breakwaters, runways, rip-rap and fills and includes crushed rock. Dimension stone means any rock or stone product that is cut or split on two or more sides, but does not include crushed rock.

The apparent expected end use of the Alumina resource (that of supporting a cement plant raw materials) from Duck Lake Mineral Claim comes within the Industrial Use definition and therefore can be considered under the *Mineral Tenure Act*. Claims require \$4 of assessment work per ha (or cash-in-lieu) each of the first three years and \$8 per ha each year after.





Claim 532098 lapsed (April 14, 2007, 125.124 ha (6 cells) was owned by J. M. Owen but has now been added to the claim package.

Lang Bay Project---Duck Lake Claims

MTO Mineral Titles Layers

-  MTO Mineral Titles Online Labels <200K
 -  Coal
 -  Placer
 -  Mineral
 -  Other
-  MTO Mineral Titles Online Polygons
 -  Coal
 -  Placer
 -  Mineral
 -  Other

Topographic Layers

-  Roads 1:20K undefined
-  Lakes 1:20K (<100K)
-  Rivers 1:20K (<100K)
-  Border line 1:250K (<2M)

Grid Layers



SCALE 1 : 70,765



N



HISTORY

In 1948 a spectrographic research study on the coals of British Columbia discovered high values of germanium in the carbonaceous shales and sandstones found in the Lang Creek area. In 1957 the mineral rights to the area were acquired by the now defunct Taiga Mines Ltd. who carried out a bulldozer trenching and a churn and diamond drilling program throughout 1958 and 1959.

In 1981 the property was acquired by Fargo Resources Limited, who conducted a number of trenching and sampling programs between August 1981 and April 1984. Work in 1985 consisted of research on methods of recovering germanium from the arkosic sandstone formation.

In 1986-1987, a drilling program of 9 holes was carried out for a more detailed exploration of germanium bearing brown beds. Tests on clay/shale horizons contained within the brown beds determined that they contain a high quality kaolin.

In May 1987, a hole drilled a distance of 1 km to the northwest of the previous area of sampling also contained kaolin, indicating a potentially large resource of this commodity at Lang Bay.

Starting in May 1987, most of the work at Lang Bay centred on evaluating the property as a kaolin deposit. It was envisaged that if a mine were to ever come into production, the primary product would be kaolin clay with germanium and gallium being valuable by-products.

The 1987 Program


The 1987 drilling program confirmed the presence of a significant thickness of kaolin clay within the prospect. However, the reverse circulation drilling method destroyed the texture of the Insitu clay structure and confused any distinction between:

- a) primary kaolins derived from Insitu alteration (weathering or basement granitoid rocks; or
- b) secondary kaolins within the basin sediments.

The geophysical surveys included seismic profiling, ground magnetic surveys, dipole-dipole resistivity surveys and Schlumberger vertical electric soundings. The seismic surveys were undertaken to define the profile of the basement rocks across the basin. The magnetic surveys were carried out to locate near surface basement rocks, which were found to have strong magnetic signatures. The electrical resistivity surveys were used to locate conductive clay horizons in the subsurface.

The magnetic surveys successfully modelled the shallowing of the basement rocks towards the edge of the basin, although significant 'geologic noise' was encountered due to the presence of large altered granitic boulders in the glacial till. Interpretation of the seismic profiling was constrained by the complexity of the sedimentary units in the basin and the lack of contrast in seismic velocity between certain of these units and the basement. The electrical resistivity surveys successfully delineated conductive clay horizons although it was not possible to distinguish between the primary and secondary kaolins.

Beneficiation studies and laboratory testing of selected samples from the 1987 reverse circulation drilling were carried out by Sutton (1987) who confirmed that certain of the clay horizons were suitable for processing to paper filler clay specifications.



1:20,000 FIG 4

SURFACE TENURE

Mineralogical investigations of borehole samples from the 1987 drilling by Mak (1987) demonstrated that the kaolin content of the primary kaolin (weathered granitoid rocks) decreases with increasing depth below the surface.

Preliminary testing and examination of cores of the secondary kaolin indicates that the quality and composition of these clays may be highly variable. A test sample of 6 tonnes was shipped to the Elk Falls paper mill near Campbell River in 1992 with apparently favourable results. Other samples were sent to pulp and paper concerns to be mill tested for linerboard and filler in the manufacture of adhesives.

A calcining test was carried out on a sample of Lang Bay kaolin by Nord Kaolin Company of Jeffersonville, Georgia. The sample was first beneficiated by Magnetic separation and ozone bleaching and this improved the brightness to that of a standard performance filler. The sample was then calcined and brightness values equivalent to those of imported calcined grades were achieved. This is significant because calcined kaolin produces a superior performance and sells for up to four times the price of filler grade. The calcined grade requires heating by natural gas, which only recently has been made available for industrial users in the Powell River area.

1999 DIAMOND DRILLING

In May 1999 a program of 4 diamond drill holes were completed as summarized in Table II.

Hole #	Location		Elevation	Azimuth	Dip	Length	Comments
	Northing	Easting					
DL-99-01	2600N	2400E	154m	000	-90	56.24m (184.5ft)	92 ft overburden
DL-99-02	0600N	2200W	135m	000	-90	50.29m (165ft)	15 ft overburden
DL-99-03	3800N	6000W	142m	000	-90	47.85m (153ft)	115 ft overburden
DL-99-00	9200N	1600W	156m	000	-90	(150ft)	>150' of overburden
Total						198.88m (652.5ft)	

Grid centre was at the intersection of the Duck Lake Road and the Powerline Road.

The drill used was a unitized Boyles 37A which was required to penetrate the variable thickness of boulder gravel, sand and till.

Hole #DL-99-01, located 260m north of the powerline encountered 92 feet (28.04m) of coarse gravel and till. The Cretaceous section consists of dark green shale which grades to shaly sandstone. Well altered green pebble conglomerate occurs between 152'2" to 156'5". Green to brown sandstone was found below the pebble conglomerate horizon which contain minor slickensides at 30° to core axis. A well altered, friable pebble conglomerate occurs at the bottom of the hole. This pebble conglomerate is characterized by matrix supported granite clasts. More whitish matrix is found at the bottom of the hole.


Diamond drill hole #DL-99-02 was located west of Duck Lake Road on the north side of the powerline. Overburden was only 16.5fr (4.72m) and consists of boulders,

LANG BAY Geology

First Nations Layers


 Indian Reserves

Parks Layers

 BC Parks (July 2004) outline (<1M)

Mineral Titles Layers

 MTO Mineral Titles Online Labels <200K

 Placer
 Mineral

 MTO Mineral Titles Online Polygons

 Placer
 Mineral


Topographic Layers

 Roads 1:20K undefined


 Coast 1:20K (<1M)

 Lakes 1:50K (<300K)

 Rivers 1:50K (<300K)


 Border line 1:250K (<2M)

Grid Layers

 Grid 1:20K maps - labels

 Grid 1:20K maps - outline

 Grid 1:250K maps - outline



SCALE 1 : 62,010






Figure 5 Regional setting of the Georgia Basin (modified from Monger, 1990). Letters indicate localities discussed in this study. A. Lang Bay outlier; B. Mouet Creek outlier; C. Lasqueti Island outlier; D. Blue Mountain outlier; E. Richfield-Pure Sunnyside exploration well.

REGIONAL GEOLOGY

Figure 5

glaciomarine stony clay over 1 foot of granitic boulders. The Cretaceous sequence was similar to Hole #1 which was alternating green-brown shale and coarse green speckled sandstone. Minor wispy coal partings were noted in the sandstone between 50.3m to 51.4m. The layering bedding is at 82° to core axis. The sequence appears to be a prograding deltaic depositional environment in which minor coal is forming elsewhere in lagoonal portions in the immediate vicinity and being eroded and redeposited in the outer delta turbiditic sequence. Near the bottom of Hole #2 an intense brown shale was encountered. Some sections are a dark red brown. Slickensides at 55° to core axis were noted between 137.10 ft to 139.5ft.

Hole #DL-99-03 was drilled close to the west edge of the basin west of hole #2 along the powerline. There was over 115 feet of coarse gravel and sand overburden. Strong water inflow at 52' and again at 80' made driving of the casing difficult. The Cretaceous sequence is characterized by dark brown shale. The bottom of the hole encountered grey-green conglomerate composed of matrix supported rounded to angular fragments of mostly lighter grey shale. Numerous narrow lamphrophic dykes were noted. Some sections (approx 15%) are heavily oxidized and leached particularly at the bottom of the hole.

Hole #DL-99-04 was located on the Duck Lake Road, however over 150 feet of sand and gravel was encountered without hitting bedrock.

REGIONAL GEOLOGY

The sedimentary rocks underlying the Duck Lake Claims are a small outlier of the extensive Georgia Basin, which is well known in the Nanaimo-Comox area due to large scale coal mining.

The Georgia Basin overlies three different basement entities: Wrangellia terrane on Vancouver Island; the Coast Belt on the mainland of British Columbia; and Cascade terranes in northwest Washington State. The main structural control on the sub-Georgia Basin rocks and the Georgia Basin itself is underthrusting of the Farallon/Kula oceanic plates beneath the North American Plate (Mustard and Rouse, 1991). A mid to late Cretaceous west-vergent thrust system is preserved at the southern margin of the Georgia Basin and in the eastern Coast Belt, mainly east of Harrison Lake. Dextral strike-slip faults influenced both basin formation and depositional patterns during the Tertiary. The basin has also been affected by early Tertiary compression, which resulted in southwest directed thrusting in the Nanaimo Group and possibly caused northwest plunging folds in the Chuckanut Formation. Younger (Miocene?) northeast trending faults and folds are evident on gravity and seismic profiles of the Fraser River lowlands. These are probably the subsurface expression of Tertiary structures preserved in the Coast and Cascade Mountains to the east and north (Mustard and Rouse, 1991).

The Nanaimo Group constitutes up to 4 km of Santonian (locally Turonian) to Maastrichtian age sedimentary rocks. The strata are commonly subdivided into nine formations comprising conglomerate, sandstone and mudstone with coal in lower units. The basal, coal-bearing formations appear to have formed in coastal plain, deltatic and shallow marine environments. Most recent interpretations of the other formations emphasize submarine fan models. Interpretations of the tectonic controls on basin sedimentation include forearc, strike-slip and foreland models (Mustard and Rouse, 1991).

Except for an isolated occurrence of Paleocene rocks on Lasqueti Island, the Tertiary rocks of the Georgia Basin are only exposed in the lower Fraser Valley and northwestern Washington. The main stratigraphic components are non-marine clastics of the Paleocene-Eocene Chuckanut Formation of Washington State, the partly equivalent upper Burrard and Kitsilano Formations of the Vancouver area, the late Eocene to Oligocene age Huntingdon Formation and younger (mostly Miocene) sedimentary rocks known from a few surface exposures and subsurface drilling. Upper Cretaceous rocks occur disconformably beneath the Tertiary strata at Burrard Inlet in Vancouver (Rouse et al., 1975) and in the western Fraser River delta subsurface.

LOCAL GEOLOGY

A sedimentary outlier of about 35 km is preserved at Lang Bay, about 13 km southeast of Powell River. Outcrop is limited to discontinuous exposures in Lang Creek (Mustard and Rouse, 1991). Conglomerate, sandstone and mudstone dip 10-15° to the southwest. The sequence unconformably overlies granodiorite and, in the northwest, part of the outlier, mafic volcanics. Crickmay and Pocock (1963) and Bradley (1972) reported late Cretaceous palynomorphs from this outlier and suggested correlation with the lower Nanaimo Group (Comox or Extension Formations). White (1986) reviewed the exploration history of the area, which most recently was evaluated for industrial kaolin. More than 50 drillholes were emplaced during 1987-89 by Fargo Resources Ltd. and Brenda Mines Ltd. to evaluate the kaolin deposits. The thickest drill intersection of Upper Cretaceous strata is about 70m, with Quaternary alluvium directly overlying the Cretaceous strata.

Two of the core logs from the 1987 work are shown in Figure 7 (Mustard and Rouse, 1991). Fining and thinning upward trends are apparent, both on the scale of the preserved sequence (tens of metres) and as smaller cycles (a few metres or less). Conglomerates are clast-supported and moderately sorted with subround pebbles and rare cobbles in an arkosic matrix. Conglomerate clasts are predominantly granitic or mafic volcanic in composition, compatible with local derivation. Sandstones are arkosic or lithic arenites. Mudstones are brown or grey-green and massive, rarely laminated. Normal grading is common in both conglomerate and sandstone beds. Many sandstones display planar or (less common) trough crossbedding. The few well-exposed crossbeds in Lang Creek indicate paleoflow towards the southwest. The small scale fining upward cycles display gradational upward change from coarse, graded sandstone with abundant mudstone ripups to trough crossbedded medium grained sandstone, to rippled or wavy bedded fine grained sandstone and siltstone, to massive mudstone. Many mudstones are carbonaceous and contain abundant plant debris. Rare coal lenses are present in Lang Creek and in one place; in situ root systems are preserved (Mustard and Rouse, 1991).

The metre-scale cycles display features of fluvial channel and point-bar deposits. The isolated graded sandstone beds in mudstones are interpreted as crevasse-splay deposits. These features, plus the presence of coal lenses, and in situ rootlets support a fluvial-floodplain depositional model.

Palynomorph assemblages have been obtained from about 6 surface samples along Lang Creek and 6 mudstone layers in drillcore (Table 1). Most palynomorphs range from the Santonian to Campanian, but a few range to Albian-Cenomanian, and others into the Maastrichtian. The Santonian-Campanian range agrees with the invertebrate-based range given for the Comox through Extension Formations.

At Lang Bay, several palynomorph species appear restricted to the upper beds, viz. *Proteacidites thalmani*, *P. marginus*, *Tricolpopollenites divergens*, and *Tricolporopollinites punctatus* (Mustard and Rouse, 1991). These are also found in the Extension-Protection Formations of Vancouver Island, and the Lions Gate Formation at Vancouver (Rouse et al., 1975, p. 469, Table 1), but appear absent from Comox and older equivalents. Hence, preliminary results suggest that there is a contact between younger and older segments of the Santonian-Campanian series near the top of the Lang Bay sequence.






Figure 2. Lang Bay outlier with logs from two drillholes. Outlier boundary is modified from White (1986). (after Mustard + Rousee).

2006 DIAMOND DRILLING

A short program of diamond drilling was completed in December 2006.

Hole locations are plotted on Figure 7 and drill logs are contained in Appendix III. The core was split and assayed at Chemex Labs Ltd. Assay certificates are contained in Appendix IV. The drillcore is stored in our locked core shed located on private property just south of the 2006 drilled area located at N49°47.881 + W124°23.253

TABLE III
Diamond Drill Hole Data 2006

Hole #	Location		Elevation	Azimuth	Dip	Length
	Northing	Easting				
LB-06-01	49°48.320	124°23.490	125m	Vertical	-90	92.97m (305 ft)
LB-06-02	49°48.370	124°23.533	125m	Vertical	-90	71.62m (235 ft)
LB-06-03	49°48.410	124°23.609	125m	Vertical	-90	51.21m (168 ft)
LB-06-04	49°48.457	124°23.645	125m	Vertical	-90	48.77m (160 ft)
LB-06-05	49°48.501	124°23.692	125m	Vertical	-90	28.96m (95 ft)
Total						293.53m (963 ft)

The sequence of sandstone and shale encountered in the 2006 program consisted of lesser shale and more abundant kaolinized sandstone.


Chemical analysis by Chemex Labs was by MEXRF06 protocol for high precision results plus loss on ignition. All elements were by lithium meta or tetra borate fusion.

Discussions have been held with major cement producers as to the suitability of the sandstone-shale sequence for cement raw materials as a source of SiO₂ and Al₂O₃.

Average chemistry of the drillholes is as follows:

	Weighted average SiO ₂	Weighted average Al ₂ O ₃	Weighted average Alkali (Na ₂ O + K ₂ O)
Hole LB-06-1	62.15%	16.01%	2.49%
Hole LB-06-2	59.63%	15.88%	2.38%
Hole LB-06-3	63.03%	14.35%	2.42%
Hole LB-06-04	62.03%	16.16%	2.44%

These averages are within the specifications of the cement producers and further work will be done by the Cement Plant in house XRF and pulps have been delivered to the Cement Plant.



DRILL HOLE LOCATIONS
2006

FIGURE 7


GEOPHYSICS

A large amount of geophysical testing was completed in the period 1986 to 1989 including ground magnetometer, seismic refraction, electrical conductivity, dipole-dipole resistivity and some down-the-hole electrical soundings.


Seismic refraction work in 1999 was carried out primarily to give some indication on the areas of thinner overburden but unfortunately the velocities of the compacted clay-rich till and glacial-fluvial stony clays give very similar values to the velocities encountered in the Cretaceous shales which form the bedrock.

POWELL RIVER BASIN.

West East




Emplacement and subsequent erosion of Granitoid
Basement Rocks
Jurassic-Cretaceous
(180-100 million years ago)




Primary Kaolin developed as weathering profile preserved on basin margin
Cretaceous
(100-70 million years ago)


Fissure Zone deep weathering
basal conglomerate




Infilling of basin by cyclothem sediments
Late Cretaceous
(70 million years ago)



Faulted basin surface
Uplift and erosion
Tertiary
(< 60 million years ago)



Glacial action and deposits of glacial till
Quaternary
(< 1.5 million years ago)



Recent erosion to produce the present Landform

Considerable elevation contrast to top of Cretaceous sediments "paleo surface"


100m

Approx. 8Km

(Vertical Exaggeration 5x)

Topographic surface

GEOLOGICAL MAP



CONCLUSIONS and RECOMMENDATIONS

The Duck Lake Property (Lang Bay Project) consists of 16 cell claims located about 15 km southeast of Powell River Townsite. The claims are 3 km north of Highway 101 at Myrtle Point. Access is via the Duck Lake Forestry Road or alternatively along the Powerline of Zilinsky Road.

The area is underlain by Upper Cretaceous shale-sandstone and minor coal, which can be correlated with the Nanaimo Group.

Previous work on the eastern margin of the outlier basin in the 1980's and early 1990's suggest that there is good potential to define primary and secondary low alkali kaolin deposits.


A 1999 program consisted of 4 diamond drillholes (totalling 198.88m) and 4.3 km of seismic refraction geophysics. The drilling encountered dark green shale, shaly sandstone and green pebble conglomerate. In some holes a distinct alternating sequence of green to very brown shale. The interval appears to be a prograding detatic depositional environment in which minor coal is forming in lagoonal portions in the immediate vicinity and then being eroded and redeposited in the outer delta-turbiditic sequence.

The five holes drilled in the current 2006 program intersected a series of interbedded green and brown sandstone and shale.

A major problem in the economic evaluation the area is the variable thickness of till and clay-rich overburden which ranges from <15 feet to >150 feet within relatively short distances.

The seismic refraction survey gave ambiguous results since the velocities of the compacted till are very similar to the velocities in the Cretaceous shale. It is recommended that a resistivity survey be done over the seismic lines to differentiate between overburden and altered bedrock. The resistivity data will provide location and depth distribution of shallow, electrically conductive materials that may be correlated with alteration zones. Based on previous experience in the area, the sedimentary bedrock where the alteration occurs has seismic velocities of the order of 2500 m/s to 3100 m/s. In order to clarify that the conductive anomalies are in the sedimentary rock sequence and not within the overburden, seismic refraction surveying should be carried out in the target areas. This seismic information together with the resistivity data would be used to select drillhole locations and would serve as the basis for additional exploration in the area.

Respectfully submitted,



J.T. (Jo) Shearer, M.Sc., P.Ge.
Consulting Geologist
May 15, 2007

COST ESTIMATE for FUTURE WORK

The Duck Lake Claims require continued geological mapping and hand trenching in certain areas. A small diamond drill program is recommended. The nature of industrial minerals suggests that a bulk sample would be useful to conduct test work for specific markets.

Drill Supervision

Senior Geologist, 12 days @ \$500	\$ 6,000.00
Assistant, 12 days @ \$250	3,000.00
GST	<u>540.00</u>
Subtotal	\$ 9,540.00

Diamond Drilling of 10 Holes @ 100m Depth Each:

Footage price \$21 x 1,500 (NQ)	\$31,500.00
Mob/demob	2,500.00
Standby/machine time (if required) Field costs	5,500.00
Moving Field costs	3,000.00
Meals/Accommodations	At Contractor's Expense
Set up Field costs	<u>3,000.00</u>
Subtotal	\$45,500.00

Dozer time in moves/road access

Road - 15 hrs @ \$85	\$ 1,275.00
Moves - 15 hrs @ \$85	<u>1,275.00</u>
Subtotal	42,550.00

GST 2,883.00

Diamond Drilling Subtotal \$50,933.00

Metallurgical Ongoing Work

Samples out to end users & Followup	\$ 6,000.00
Calcining Followup	2,500.00
Magnetic Separation to Address Iron Content	2,500.00
Classification of Undersize Thickener & Hydrocycloning	10,000.00
Market & Customer Study, Update of 1989 Study	<u>19,000.00</u>
Subtotal	\$ 40,000.00

Bulk Sample

Environmental Survey & Report	\$ 8,000.00
Application & Preparation of required reports & documents for Bulk Sample Permit	6,000.00
Tote Road Preparation	10,000.00
Bulk Sample Mining & Crushing 10,000 tons + Loadout	45,000.00
Trucking Sample to Loadout	35,000.00
Final Report Preparation	<u>6,000.00</u>
Subtotal	\$110,000.00

TOTAL \$200,933.00

REFERENCES

- Bacon, W. R., 1957:
Geology of the Lower Jervis Inlet, British Columbia; Bulletin 39, pages 17, 37.
- Bradley, R. K., 1972:
Upper Cretaceous Plant Fossils from Mainland Coastal Deposits North of Vancouver, British Columbia, Canada; Canadian Journal of Earth Sciences, v. 10, p. 1841-1843.
- Bustin, R. M., 1990:
Stratigraphy, Sedimentology and Petroleum Source Rock Potential of the Georgia Basin, Southwest British Columbia and Northwest Washington State; in Current Research, part F, Geological Survey of Canada, Paper 90-1F, p. 103-108.
- Crickmay, C. E. and Pocock, S. A. J., 1963:
Cretaceous at Vancouver, British Columbia, Canada; American Association of Petroleum Geologists Bulletin, v. 47, p. 1928-1942.
- Currie, J. A., 1988A:
Assessment Report on the Kelly 1-5 and Trish 1-2 Mineral Claims, Fargo Resources Assessment Report 16734, 225 pp.
- 1988B:
Same Report # Assessment Report 17616, 225 pp.
- England, T. D. J., 1989:
Lithostratigraphy of the Nanaimo Group, Georgia Basin, South-western British Columbia; in Current Research, Part E, Geological Survey of Canada, Paper 89-1E, p.103-108.
- 1990:
Late Cretaceous to Paleogene Evolution of the Georgia Basin, South-western British Columbia; unpublished Ph.D. theses, Memorial University of Newfoundland, St. John's, 481 p.
- Foundex Geophysics, 1987a:
Seismic Refraction Investigation, Lang Bay Kaolin Prospect, October 1987.
- 1987b:
Report on an Electrical Resistivity and Magnetometer Survey, Lang Bay Kaolin Prospect, December 1987.
- Hilchey, G. R., 1986:
1986 Assessment Report Kelly, Trish Claims.
- 1985:
1985 Assessment Report Kelly, Trish Claims.
- Lobdell, D., 1988:
Report on February 1988 Core Drilling, Lang Bay Kaolin Prospect.
- Mak, S.:
Investigation on the Kaolin at the Lang Bay Prospect, Department of Metals and Material Engineering, University of British Columbia (NRC sponsored study).

- Mak, S., and Chaklader, A. C. D., 1987:
University of British Columbia – Department of Metals and Materials Engineering, October 1987 – “Investigation on the Kaolin at the Lang Bay Deposit”.
- Muller, J. E., and Jeletzky, J. A., 1970:
Geology of the Upper Cretaceous Nanaimo Group, Vancouver Island and Gulf Islands, British Columbia; Geological Survey of Canada, Paper 69-25, 77 p.
- Mustard, P. S., and Rouse G. E.,
Sedimentary Outliers of the Eastern Georgia Basin Margin in Current Research, Part A, Geological Survey of Canada, Paper 91-1A p. 229-240.
- Pilon, C. G., 1987:
Drilling Report on the Lang Bay Kaolin Prospect, November, 1987.
- Read, P. B., 1994:
Kaolin Potential of the Comox Sub-Basin, B.C. Ministry of Energy, Mines and Petroleum Resources, Open File 1996-16 57 pp.
- Roddick, J. A. and Hutchinson, W. W., 1967:
Coast Mountains Project, British Columbia; in Report of Activities, Paper 1968-1A, pages 37-40.
- Roddick, J. A., Woodsworth, G. J. and Hutchinson, W. W., 1979:
Geology of Vancouver West Half and Mainland Part of Alberni, Open file 611.
- Rouse, G. E., Mathews, W. H., and Blunden, R. H., 1975:
The Lions Gate Member: a New Late Cretaceous Sedimentary Division in the Vancouver Area of British Columbia; Canadian Journal of Earth Sciences, v. 12, p.464-471.
- Rouse, G. E., Lesack, K. A., and White, J. M., 1990:
Palynology of Cretaceous and Tertiary Strata of Georgia Basin, Southwestern British Columbia; in Current Research. Part F. Geological Survey of Canada, Paper 90-1F, p. 109-113.
- Shearer, J. T., 1998:
Mining Permit Application Summary on the South Slesse Limestone Quarry, Mx7-114, for I.G. Machine & Fibers Ltd., Dated January 10, 1998, 23 pages.
- 1999:
Diamond Drilling Report on the Duck Lake Claims, Assessment Report, 18 pp.
- 2006:
Geological and Metallurgical Assessment Report on the Lang Bay (Duck Lake) Kaolinite Deposit for Electra Gold Ltd., dated August 15, 2006.
- White, G. V., 1986:
Preliminary Report. Lang Bay Germanium Prospect (92F/1610). Paper 1986-1, Geological Field Work (1985), Ministry EMPR of British Columbia

APPENDIX I

STATEMENT OF QUALIFICATIONS

J. T. SHEARER, M.Sc., F.G.A.C., P.Geo.

May 15, 2007

Appendix I


STATEMENT OF QUALIFICATIONS

I, Johan T. Shearer of 3572 Hamilton Street, in the City of Port Coquitlam, in the Province of British Columbia, do hereby certify:

1. I graduated in Honours Geology (B.Sc., 1973) from the University of British Columbia and the University of London, Imperial College, (M.Sc. 1977).
2. I have practiced my profession as an Exploration Geologist continuously since graduation and have been employed by such mining companies as McIntyre Mines Ltd., J.C. Stephen Explorations Ltd., Carolin Mines Ltd. and TRM Engineering Ltd. I am presently employed by Homegold Resources Ltd.
3. I am a fellow of the Geological Association of Canada (Fellow No. F439). I am also a member of the Canadian Institute of Mining and Metallurgy, and the Geological Society of London. I am a member in good standing of the Association of Professional Engineers and Geoscientists of British Columbia (P.Geo., Member Number 19,279).
4. I am an independent consulting geologist employed since December 1986 by Homegold Resources Ltd. at Unit #5 2330 Tyner Street, Port Coquitlam, British Columbia.
5. I am the author of the report entitled "Diamond Drilling Assessment Report on the Lang Bay (Duck Lake) Kaolinite Deposit, May 15, 2007".
6. I visited the property in May, June, July and August 1999. I supervised and logged the diamond drill core. I worked on drillcore and reverse circulation samples on January 5 to 7 and 10 to 12, 2006. I supervised the diamond drilling completed between November 15, 2006 and December 14, 2006. I am familiar with the regional geology and geology of nearby properties. I have become familiar with the previous work conducted on the Duck Lake Property by examining in detail the available reports, plans and sections, and have discussed previous work with persons knowledgeable of the area.

Dated at Port Coquitlam, British Columbia, this 15th day of ~~August~~^{May}, 2007.

Respectfully Submitted



J.T. Shearer, M.Sc., F.G.A.C., P.Geo.
May 15, 2007

APPENDIX II

STATEMENT OF COSTS

May 15, 2007

Appendix II

STATEMENT of COSTS 2006 and 2007
LANG BAY PROJECT (DUCK LAKE CLAIMS)
Diamond Drilling Assessment Report

Wages and Benefits

J.T. Shearer, M.Sc., P.Geo., Senior Geologist, Quarry Supervisor 98-3550 15.5 days @ \$500/day, Nov. 25 - 27/Dec. 3-7, 10-14, 2006, Jan. 12-14, 2007	\$ 7,750.00
Jon Stewart Experienced Prospector 14 days @ \$400.00/day, Nov. 25-27/Dec. 3-7, 10-14, 2006	\$5,600.00
B. Berchty, Core Splitter, Chainsaw 7 days @ \$200/day Dec. 6-12, 2006	<u>1,400.00</u>
	\$ 14,750.00
	GST <u>885.00</u>
	Subtotal Wages \$ 15,635.00

Expenses

Transportation Truck Rental, Fully equipped 4x4 20 days @ \$75/day	3,000.00
Gas	650.00
Motel, Meals	3,500.00
Contract Diamond Drilling (Neil Mining)	38,000.00
Analytical (Chemex Labs)	8,000.00
Core Shack Rental	4,000.00
Genset Rental for Core Shack	525.00
Core Splitter Rental	400.00
Report Preparation	1,500.00
Drafting	600.00
Word Processing and Reproduction	<u>250.00</u>
	Subtotal Expenses \$ 60,425.00

Total  **\$ 76,060.00**

APPENDIX III

Drill Hole Logs

May 15, 2007

ELECTRA GOLD LTD.

LANG BAY 2006 Program

SECTION: Lang Bay South

Diamond Drill Log

DDH#: LB-06-01

Northing: 49°48.032
 Easting: 124°23.318
 Elevation: 125
 Azimuth: Vertical
 Inclination: -90
 Grid: No Grid
 Length (m): 92.97m (305 ft.)
 Core size: LBW Thin Wall
 Contractor: McNeill
 Drill Type: Hydrocore 28

Drill Hole survey		
Method: <u>Brunton</u>		
Azimuth	Dip	Depth
-	-90	Collar

Property: Lang Bay
 NTS: 92F/16W
 Claim: Duck Lake 4
 Date Started: Dec. 5, 2006
 Date Completed: Dec. 6, 2006
 Logged by: J.T. Shearer,
M.Sc., P.Geo.

Samples Split:

Samples 1-38 refer to Page 3

Purpose: Follow up core drilling to check kaolinitic section and depth of overburden

from (m)	to (m)	Description	from/to	width (m)	CaO %
0.00	25.91	OVERBURDEN: with granite boulders, Casing to 25.91m			
25.91	27.13	SHALE: Dark green very soft Dark green-grey Shale - very soft, friable. Minor slickensides on natural breaks throughout at 86° to core axis. Desiccation cracks common. Traces of micaceous minerals Fault at 90° to core axis, minor crushed shale			
27.13	47.24	INTERBEDDED SHALE and SANDSTONE: 27.13m to 28.96m - shale and sandstone, 28.96m-30.12m - 5 cm black banding, 30.12m-32.31m - sandstone, 32.31m-33.22m - hematite staining, 33.22m-35.15m - sandstone 35.15m-35.26m - Kaolinitic fine sandstone, 35.26m- 37.19m - Kaolinitic coarse sandstone			
47.24	38.23	Coarse sandstone to PEBBLE CONGLOMERATE - well altered, pronounced green colour, matrix supported mainly, well rounded clasts average 1-2 cm in diameter, traces of pyrite along clast edges, rarely rimming small clasts; some brown interclast matrix			
38.23	47.24	38.23m-39.68m - Sandstone with 2" black banding, 39.73m-40.84m- sandstone, 40.84m-40.94m - sandstone with some coal 40.94m-41.76m - sandstone, 41.76m-41.86m - black banding with hematite, 41.86m-43.89m - sandstone with few little bands kaolin, 43.89m-44.20m - sandstone with bands of hematite Coarse sandstone			
47.24	53.80	SANDSTONE: 47.24m-48.26m - sandstone mainly kaolin, 48.26m-48.77m - sandstone, 48.77m-50.37m - sandstone with hematite staining, Very kaolinitic sandstone Sandstone, Kaolinized, intense kaolinized feldspars			
53.80	60.01	GREEN to BROWN SANDSTONE: well altered, wispy brown partins at 83° to core axis, sharp lower contact, soft, highly fractured, minor silty intervals, micaceous component, 53.80m-53.95m - Sandstone, 53.95m-54.05m - Sandstone with black banding, 54.05m-56.08 - Sandstone 50.28m-58.52m - very kaolinitic sandstone, 58.52m-60.66m - Sandstone with small bands kaolin			


ELECTRA GOLD LTD.
LANG BAY 2006 Program

Page 3 of 3
Hole #1

Sample No.	From/To (ft.)
No. 1	85 - 90
No. 2	90 - 95
No. 3	95 - 100
No. 4	100 - 105
No. 5	105 - 110
No. 6	110 - 115
No. 7	115 - 120
No. 8	120 - 125
No. 9	125 - 130
No. 10	130 - 135
No. 11	135 - 140
No. 12	140 - 145
No. 13	145 - 150
No. 14	150 - 155
No. 15	155 - 160
No. 16	160 - 165
No. 17	165 - 170
No. 18	170 - 175
No. 19	175 - 180

Sample No.	From/To (ft.)
No. 20	180 - 185
No. 21	185 - 190
No. 22	190 - 195
No. 23	195 - 200
No. 24	200 - 205
No. 25	205 - 210
No. 26	210 - 215
No. 27	215 - 220
No. 28	220 - 225
No. 29	225 - 230
No. 30	230 - 235
No. 31	235 - 240
No. 32	240 - 245
No. 33	245 - 250
No. 34	250 - 255
No. 35	255 - 260
No. 36	260 - 265
No. 37	256 - 270
No. 38	270 - 275

see
Appendix IV
for Results



ELECTRA GOLD LTD. LANG BAY

SECTION: Lang Bay South

Diamond Drill Log

DDH#: LB-06-02

Northing: 49°48.370
 Easting: 124°23.533
 Elevation: 125m
 Azimuth: Vertical
 Inclination: -90
 Grid: No Grid
 Length (m): 71.63m (235 ft.)
 Core size: BW Thin Wall
 Contractor: McNeill
 Drill Type: Hydrocore 28

Drill Hole survey		
Method: <u>Brunton</u>		
Azimuth	Dip	Depth
Vertical	-90	Collar

Property: Lang Bay
 NTS: 92F/16W
 Claim: Duck Lake 4
 Date Started: Dec. 7, 2006
 Date Completed: Dec. 8, 2006
 Logged by: J.T. Shearer,
 M.Sc., P.Geo.

Samples Split:

 16 samples split see Page 2

Purpose: Follow up core drilling to check kaolinitic section and depth of overburden

from <small>(m)</small>	to <small>(m)</small>	Description	from/to	width <small>(m)</small>	CaO <small>%</small>
0.00	27.43	OVERBURDEN: till, granitic boulders, casing to 27.43m			
27.43	32.31	Kaolinitic sandstone COARSE GREEN SANDSTONE: slightly more altered than above, floating pebbles common, very minor carbonaceous partings, speckled texture throughout, slightly finer grained toward lower contact, sharp, slickensided lower contact - fault at 24° to core axis.			
32.31	33.22	COARSE GREEN SPECKLED SANDSTONE: moderately altered, floating pebbles to 1.5 cm in diameter common throughout section, larger pebbles common in top 0.15m, coarsening slightly in lower part of interval			
33.22	33.83	Kaolinitic sandstone			
33.83	36.58	COARSE GREEN SANDSTONE with interbeds of WISPY BROWN CARBONACEOUS MATERIAL: entire interval has a brownish hue, carbonaceous zones 5-2=10cm wide, black coaly partings, coal fragment at 33.04m which is 4cm wide by 5cm across, this fragment (clast) is forming elsewhere in the immediate vicinity and being eroded and redeposited in the outer delta turbidic sequences, traces of crystalline pyrite around the coaly areas. 33.83m-35.05m - sandstone, coal fragments and kaolin, 35.05m-36.58m - sandstone, kaolin, coal fragments 36.42m, large amount of pyrite			
		Coarse Green Sandstone: speckled texture floating pebbles common especially between 86.85m to 87.7m, somewhat speckled appearance, pebbles up to 2cm across			
36.58	41.45	36.58m-37.44m - coarse sandstone 37.44m-37.59m hematite, 37.59m-37.80m - coarse sandstone 37.80m-38.10m massive hematite, 38.10m-41.45m - coarse sandstone with hematite			
41.45	42.06	Kaolinitic sandstone			
42.06	50.90	42.06m-45.72m - coarse sandstone, black banding, 45.72m-47.24m - coarse sandstone fine, 47.24m-50.90 - coarse sandstone, large fragments of silica			
50.90	71.62	QUARTZ DIORITE - light grey, medium crystalline, hypidiomorphic granular			
		End of Hole 71.62m (235 feet)			

ELECTRA GOLD LTD.
LANG BAY

Hole # 2

Sample No.	From/To (ft.)
No. 1	90 - 95
No. 2	95 - 100
No. 3	100 - 105
No. 4	105 - 110
No. 5	110 - 115
No. 6	115 - 120
No. 7	120 - 125
No. 8	125 - 130
No. 9	130 - 135
No. 10	135 - 140
No. 11	140 - 145
No. 12	145 - 150
No. 13	150 - 155
No. 14	155 - 160
No. 15	160 - 165
No. 16	165 - 168

ELECTRA GOLD LTD. LANG BAY

SECTION: Lang Bay South

Diamond Drill Log

DDH#: LB-06-03

Northing: 49°48.410
 Easting: 124°23.609
 Elevation: 125m
 Azimuth: Vertical
 Inclination: -90
 Grid: No Grid
 Length (m): 51.21m (168 ft.)
 Core size: LBW Thin Wall
 Contractor: McNeill
 Drill Type: Hydrocore 28

Drill Hole survey		
Method: <u>Brunton</u>		
Azimuth	Dip	Depth
Vertical	-90	Collar

Property: Lang Bay
 NTS: 92F/16W
 Claim: Duck Lake 4
 Date Started: Dec. 8, 2006
 Date Completed: Dec. 9, 2006
 Logged by: J.T. Shearer,
 M.Sc., P.Geo.

Samples Split:
 16 samples split see Page 2

Purpose: Follow up core drilling to check kaolinitic section and depth of overburden

from	to	Description	from/to	width (m)	CaO %
0.00	27.89	OVERBURDEN: till, more sandy sections, boulders, casing to 27.43m			
27.89	31.55	SHALY SANDSTONE: mainly green in colour due to dominate clast type is a green "volcanic", gradational coarsening, matrix whitish-kaolinized, coarser sandstone at bottom of interval			
		92'-96' - kaolin, 96'-97' sandstone, 97'-100' - kaolin, 100'-103'6" - kaolin			
31.55	32.00	GREEN SANDSTONE: with wispy black to brown partings, wispy layers mainly at 85° to core axis, well altered, carbonaceous material on some parting surfaces, lower part of interval gradually becomes coarser grained to sharp contact with pebble conglomerate, minor pebble layers			
32.00	35.66	Coarse sandstone, some hematitic banding, small band kaolin			
35.66	37.49	GREEN to BROWN SANDSTONE: well altered, wispy brown partings at 83° to core axis, sharp lower contact, soft, highly fractured, minor silty intervals, micaceous component			
		Sandstone with bands of coal			
37.49	39.62	37.49m-38.10m - coarse sandstone, hematite, 38.10m-39.62m - coarse sandstone with black banding, hematite			
39.62	40.23	Kaolin			
40.23	42.67	27.49m-41.15m - sandstone coarse, some hematite stain with black band, little bit of shell, 41.15m-42.67m - coarse sandstone			
42.67	44.20	Sandstone with a lot of mica, coarse sandstone grey in colour			
44.20	45.72	sandstone			
45.72	51.21	45.72m-47.24m - sandstone with large fragments of rock, shale fragments, a little of kaolin banding and hematite banding, 47.24m-48.77m - coarse sandstone with kaolin, 45.72m-46.63m - sandstone with large fragments, 50.29m-51.21m - sandstone with very large fragments of other type rock			
		End of Hole 51.21m (168 feet)			

ELECTRA GOLD LTD. LANG BAY

SECTION: Lang Bay South

Diamond Drill Log

DDH#: LB-06-04

Northing: 49°48.417
 Easting: 124°23.645
 Elevation: 125
 Azimuth: Vertical
 Inclination: -90
 Grid: No Grid
 Length (m): 48.77m (160 ft.)
 Core size: LBW Thin Wall
 Contractor: McNeill
 Drill Type: Hydrocore 28

Drill Hole survey		
Method: <u>Brunton</u>		
Azimuth	Dip	Depth
Vertical	-90	Collar

Property: Lang Bay
 NTS: 92F/16W
 Claim: Duck Lake 4
 Date Started: Dec. 9, 2006
 Date Completed: Dec. 10, 2006
 Logged by: J.T. Shearer,
 M.Sc., P.Geol.

Samples Split:

 16 samples split see Page 2

Purpose: Follow up core drilling to check kaolinitic section and depth of overburden

from (ft)	to (ft)	Description	from/to	width (m)	CaO %
0.00	20.42	OVERBURDEN: No Core, till, minor sand, boulders, casing to 21.34m			
20.42	22.86	Kaolinitic Sandstone COARSE GREEN SANDSTONE: slightly more altered, floating pebbles common, very minor carbonaceous partings, speckled texture throughout, slightly finer grained toward lower contact, sharp, slickensided lower contact - fault at 24° to core axis. Sandstone with banding of kaolinized feldspars			
22.86	24.38	Kaolinitic sandstone			
24.38	30.48	Sandstone with band of kaolin and hematite COARSE GREEN SPECKLED SANDSTONE: alteration of the white feldspars moderate, minor small floating pebbles			
30.48	32.00	Coarse sandstone with hematite, bands of coal COARSE GREEN SANDSTONE with interbeds of WISPY BROWN CARBONACEOUS MATERIAL: entire interval has a brownish hue, carbonaceous zones 5-2=10cm wide, black coaly partings, coal fragment at 33.04m which is 4cm wide by 5cm across, this fragment (clast) is forming elsewhere in the immediate vicinity and being eroded and redeposited in the outer delta turbidic sequences, traces of crystalline pyrite around the coaly areas.			
32.00	32.91	Sandstone fragments of coal and hematite stains			
32.91	33.53	Kaolinized sandstone			
33.53	35.05	Sandstone with hematite			
35.05	36.58	Sandstone with black banding (coal)			
36.58	41.15	Sandstone			
41.15	42.67	Sandstone, fair amount of mica CLOSE PACKED PEBBLE CONGLOMERATE: altered rims on mainly fine grained green pebbles averaging less than 1 cm in diameter, probably the course member of the overlying sandstone			
42.67	43.89	Sandstone			
43.89	48.77	Hornblende - biotite diorite, medium crystalline			
		End of Hole 48.77m (160 feet)			

ELECTRA GOLD LTD.
LANG BAY

Hole #4

Sample No.	From/To (ft.)
No. 1	67 - 70
No. 2	70 - 75
No. 3	75 - 80
No. 4	80 - 85
No. 5	85 - 90
No. 6	90 - 95
No. 7	95 - 100
No. 8	100 - 105
No. 9	105 - 110
No. 10	110 - 115
No. 11	115 - 120
No. 12	120 - 125
No. 13	125 - 130
No. 14	130 - 135
No. 15	135 - 140
No. 16	140 - 145
No. 17.	145 - 150

APPENDIX IV

Assay Certificates

May 15, 2007

VA06128216 - Finalized

CLIENT : "ELEGOL - Electra Gold Ltd"

of SAMPLES : 87

DATE RECEIVED : 2006-12-14 DATE FINALIZED : 2007-02-01

PROJECT : "Lang Bay"

CERTIFICATE COMMENTS : ""

PO NUMBER : ""

Hole # 1

Hole # 2

SAMPLE	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06
DESCRIPTION	SiO2	Al2O3	Fe2O3	CaO	MgO	Na2O	K2O	Cr2O3
%	%	%	%	%	%	%	%	%
LB-06-01-1 <i>85-90</i>	57.29	17.13	4.94	3.34	1.66	1.15	1.47	<0.01
LB-06-01-2 <i>90-95</i>	60.32	19.39	4.49	1.27	1.4	0.88	1.52	<0.01
LB-06-01-3 <i>95-100</i>	62.51	17.1	4.57	1.61	1.6	1.13	1.55	<0.01
LB-06-01-4 <i>100-105</i>	64.54	15.97	4.37	1.61	1.53	1.2	1.57	<0.01
LB-06-01-5 <i>105-110</i>	62.19	13.34	5.76	2.75	1.92	1.38	1.54	<0.01
LB-06-01-6 <i>110-115</i>	65.8	15.6	3.95	1.76	1.3	1.26	1.64	<0.01
LB-06-01-7 <i>115-120</i>	53.16	22.89	5.44	1.19	1.64	1.11	1.43	<0.01
LB-06-01-8 <i>120-125</i>	58.68	17.04	4.51	2.6	1.92	1.22	1.47	<0.01
LB-06-01-9 <i>125-130</i>	72.37	10.23	4.09	2.55	1.07	1.8	1.42	<0.01
LB-06-01-10 <i>130-135</i>	65.03	15.6	4.15	2.16	1.37	1.37	1.72	<0.01
LB-06-01-11 <i>135-140</i>	61.93	15.18	5.14	2.24	1.64	1.3	1.59	<0.01
LB-06-01-12 <i>140-145</i>	66.73	13.4	4.85	1.68	1.36	1.41	1.42	<0.01
LB-06-01-13 <i>145-150</i>	70.55	12.14	3.64	2.03	1.16	1.74	1.57	<0.01
LB-06-01-14 <i>150-155</i>	74.38	9.72	3.77	2.27	1.01	1.65	1.42	<0.01
LB-06-01-15 <i>155-160</i>	61.94	17.33	5.15	1.77	1.47	1.38	1.54	<0.01
LB-06-01-16 <i>160-165</i>	62.63	15.03	6.19	2.11	1.23	1.34	1.38	<0.01
LB-06-01-17 <i>165-170</i>	64.48	13.22	3.45	3.54	1.99	1.48	1.67	<0.01
LB-06-01-18 <i>170-175</i>	54.59	21.58	4.59	1.73	1.31	1.06	1.32	<0.01
LB-06-01-19 <i>175-180</i>	64.83	13.95	4.11	2.37	1.54	1.07	1.71	<0.01
LB-06-01-20 <i>180-185</i>	58.72	17.68	5.49	2.59	1.66	1.25	1.49	<0.01
LB-06-01-21 <i>185-190</i>	56.36	18.21	3.8	5.05	1.17	1.34	1.49	<0.01
LB-06-01-22 <i>190-195</i>	58.19	18.31	5.91	1.79	1.37	1.06	1.38	<0.01
LB-06-01-23 <i>195-200</i>	75.71	7.19	4.18	3.24	0.78	1.02	1.24	<0.01
LB-06-01-24 <i>200-205</i>	50.81	22.04	7.95	1.66	1.49	1.13	1.36	<0.01
LB-06-01-25 <i>205-210</i>	61.94	13.99	7.05	2.63	1.07	1.38	1.43	<0.01
LB-06-01-26 <i>210-215</i>	51.02	23.75	6.22	2.14	1.21	0.84	1.35	<0.01
LB-06-01-27 <i>215-220</i>	58.54	18.94	5.83	1.29	0.92	0.54	1.34	<0.01
LB-06-01-28 <i>220-225</i>	59.72	20.07	5.6	0.57	0.67	0.39	0.8	<0.01
LB-06-01-29 <i>225-230</i>	63.87	15.7	8.69	0.36	0.75	0.14	0.59	<0.01
LB-06-01-30 <i>230-235</i>	60.68	15.95	9.35	0.48	0.77	0.17	1.02	<0.01
LB-06-01-31 <i>235-240</i>	70.61	13.43	5.37	0.41	0.58	0.17	1.74	<0.01
LB-06-01-32 <i>240-245</i>	63.9	15.27	7.18	0.79	0.89	0.19	1.79	<0.01
LB-06-01-33 <i>245-250</i>	61.89	14.01	8.55	1.86	0.85	0.41	1.65	<0.01
LB-06-01-34 <i>250-255</i>	57.27	13.85	9.83	3.53	0.99	0.66	1.44	<0.01
LB-06-01-35 <i>255-260</i>	55.11	13.54	11.24	5.91	1.94	1.15	1.24	<0.01
LB-06-01-36 <i>260-265</i>	51.42	14.36	13.05	6.55	3.61	1.69	0.79	0.01
LB-06-01-37 <i>265-270</i>	52.28	14.37	12.57	7.33	4.54	1.82	0.74	0.01
LB-06-01-38 <i>270-275</i>	56.97	16.28	9.89	4.01	3.28	2	1.24	<0.01
LB-06-02-1 <i>90-95</i>	49	26.06	6.2	1.19	1.37	0.76	1.2	<0.01
LB-06-02-2 <i>95-100</i>	49.2	23.87	6.46	2.39	1.33	0.76	1.13	<0.01
LB-06-02-3 <i>100-105</i>	48.78	26.42	5.82	0.97	1.23	0.71	1.2	<0.01
LB-06-02-4 <i>105-110</i>	56.32	18.72	6.84	2.58	1.22	1.08	1.34	<0.01

Hole # 2

LB-06-02-5 110-115	54.82	16.7	4.21	6.1	0.99	1.17	1.49	<0.01
LB-06-02-6 115-120	58.68	20.32	4.3	1.51	0.95	0.84	1.16	<0.01
LB-06-02-7 120-125	73.65	9.67	4.13	2.74	0.65	1.4	1.12	<0.01
LB-06-02-8 125-130	64.82	15.19	4.75	2.03	1.09	1.16	1.46	<0.01
LB-06-02-9 130-135	73.08	9.95	3.81	2.58	0.7	1.27	1.16	<0.01
LB-06-02-10 135-140	61.95	15.76	7.23	1.5	1.09	0.76	1.54	<0.01
LB-06-02-11 140-145	66.03	10.92	5.87	3.35	0.94	1.22	1.5	<0.01
LB-06-02-12 145-150	68.98	9.78	6.31	2.57	1.03	0.9	1.42	<0.01
LB-06-02-13 150-155	64.29	13.21	6.81	2.16	1.14	1.49	1.45	<0.01
LB-06-02-14 155-160	57.51	11.24	10.93	3.91	1.52	1.51	1.25	<0.01
LB-06-02-15 160-165	53.49	12.32	11.26	4.62	1.92	1.14	1.02	<0.01
LB-06-02-16 165-168	53.5	13.99	8.11	6.19	1.93	1.11	1.3	<0.01

Hole # 3

LB-06-03-1 115-120	48.31	24.05	6.7	1.55	1.36	0.66	1.09	<0.01
LB-06-03-2 120-125	55.62	19.51	5.92	2.19	1.26	0.85	1.13	<0.01
LB-06-03-3 125-130	57.66	21.14	4.73	1.85	0.94	0.99	1.27	<0.01
LB-06-03-4 130-135	66.81	11.83	4.25	4.33	0.77	1.52	1.68	<0.01
LB-06-03-5 135-140	71.95	10.18	4.48	2.55	0.62	1.69	1.42	<0.01
LB-06-03-6 140-145	66.84	13.17	4.5	3.35	0.78	1.25	1.31	<0.01
LB-06-03-7 145-150	74.95	9.61	3.39	2.3	0.55	1.3	1.15	0.01
LB-06-03-8 150-155	72.47	9.51	4.76	2.98	0.69	1.34	1.15	<0.01
LB-06-03-9 155-160	63.52	15.66	5.48	2.16	0.95	0.99	1.33	<0.01
LB-06-03-10 160-165	67.08	14.76	5.67	0.69	0.84	0.25	1.13	<0.01
LB-06-03-11 165-170	70.84	10.53	5.72	1.45	0.78	0.33	1.57	<0.01
LB-06-03-12 170-175	61.58	12.82	10.17	1.73	1.01	0.65	1.54	<0.01
LB-06-03-13 175-180	63.17	12.47	9.35	1.58	1.04	0.86	1.4	0.01
LB-06-03-14 180-185	54.61	15.9	9.69	3.16	1.44	0.91	1.44	<0.01
LB-06-03-15 185-190	61.03	12.94	7.58	2.59	1.6	0.93	1.43	<0.01
LB-06-03-16 190-195	52.07	15.45	7.34	5.71	1.62	1.49	1.45	0.01

Hole # 4

LB-06-04-1 170-175	51.39	24.63	6.08	1.26	1.36	0.72	0.93	<0.01
LB-06-04-2 175-180	61.92	14.64	4.42	4.26	1.12	1.37	1.55	<0.01
LB-06-04-3 180-185	59	16.98	5.49	2.21	1.3	1.13	1.41	<0.01
LB-06-04-4 185-190	56.94	18.29	6.17	2.17	1.3	0.85	1.37	<0.01
LB-06-04-5 190-195	55.73	20.88	5.19	2.17	1.16	0.94	1.19	<0.01
LB-06-04-6 195-200	55.47	20.26	5.27	2.11	1.16	0.85	1.11	0.02
LB-06-04-7 200-205	49.69	24.77	6.34	1.52	1.29	0.9	1.24	<0.01
LB-06-04-8 205-210	70.77	10.12	6.28	2.07	0.74	1.54	1.48	<0.01
LB-06-04-9 210-215	62.38	15.48	5.07	2.78	0.93	1.21	1.35	<0.01
LB-06-04-10 215-220	66.7	13.49	4.2	2.7	0.74	1.45	1.37	<0.01
LB-06-04-11 220-225	71.65	9.32	4.11	3.5	0.66	1.21	1.2	<0.01
LB-06-04-12 225-230	62.59	16.53	5.06	2.18	1.01	1.19	1.46	<0.01
LB-06-04-13 230-235	69.24	14.38	4.35	0.77	0.73	0.36	1.16	<0.01
LB-06-04-14 235-240	64.1	13.71	7.52	1.88	0.95	0.59	1.43	<0.01
LB-06-04-15 240-245	69.37	9.82	6.3	3.05	0.71	1.07	1.44	<0.01
LB-06-04-16 245-250	65.62	14.23	5.36	2.23	0.93	1.03	1.77	<0.01
LB-06-04-17 250-255	61.87	17.13	4.51	1.93	1.25	1.32	2.26	<0.01

ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06	ME-XRF06
TiO2	MnO	P2O5	SrO	BaO	LOI	Total
%	%	%	%	%	%	%
0.58	0.1	0.05	0.02	0.05	10.9	98.68
0.61	0.05	0.04	0.02	0.06	9.84	99.89
0.51	0.06	0.03	0.02	0.06	9.28	100.05
0.48	0.06	0.03	0.02	0.06	8.3	99.75
0.53	0.12	0.03	0.03	0.05	8.72	98.36
0.47	0.06	0.03	0.02	0.06	7.65	99.6
0.71	0.07	0.03	0.02	0.05	11.65	99.39
0.57	0.07	0.03	0.03	0.06	10.05	98.24
0.3	0.06	0.04	0.03	0.06	5.05	99.06
0.5	0.09	0.03	0.02	0.06	7.64	99.73
0.47	0.08	0.03	0.02	0.06	8.65	98.33
0.41	0.07	0.02	0.02	0.06	7.07	98.49
0.37	0.07	0.03	0.02	0.06	5.62	99
0.26	0.05	0.03	0.02	0.05	4.52	99.15
0.51	0.08	0.03	0.02	0.06	8.77	100.05
0.53	0.07	0.04	0.02	0.05	8.03	98.65
0.41	0.07	0.03	0.03	0.06	8.32	98.75
0.7	0.07	0.03	0.02	0.05	11.35	98.39
0.48	0.08	0.03	0.02	0.06	8.33	98.57
0.54	0.09	0.03	0.02	0.06	10.05	99.66
0.54	0.11	0.04	0.02	0.06	11.15	99.34
0.56	0.09	0.03	0.02	0.05	10.1	98.85
0.27	0.07	0.03	0.01	0.05	5.39	99.17
0.73	0.1	0.04	0.02	0.05	11.85	99.23
0.49	0.1	0.04	0.02	0.06	8.27	98.46
0.69	0.1	0.04	0.01	0.05	12.45	99.88
0.59	0.08	0.03	0.01	0.05	10.35	98.5
0.76	0.04	0.05	0.01	0.03	9.53	98.24
0.65	0.06	0.05	0.01	0.02	9.19	100.05
0.69	0.04	0.03	0.01	0.04	9.24	98.47
0.47	0.03	0.03	0.01	0.06	6.53	99.42
0.59	0.08	0.02	0.01	0.06	8.1	98.86
0.56	0.1	0.03	0.01	0.05	8.64	98.61
0.71	0.13	0.03	0.02	0.05	9.63	98.14
0.8	0.19	0.05	0.02	0.04	7.51	98.74
1.27	0.18	0.09	0.03	0.04	5.32	98.41
1.45	0.2	0.09	0.03	0.02	3.87	99.32
0.96	0.14	0.06	0.03	0.05	5.22	99.13
0.8	0.07	0.04	0.02	0.04	12.9	99.65
0.7	0.09	0.05	0.02	0.05	13.1	99.14
0.79	0.06	0.04	0.02	0.04	13.2	99.28
0.62	0.1	0.04	0.02	0.06	10.8	99.73

0.54	0.15	0.04	0.02	0.06	11.85	98.13
0.6	0.06	0.03	0.02	0.05	10.4	98.92
0.32	0.08	0.03	0.02	0.05	5.29	99.15
0.48	0.09	0.03	0.02	0.06	7.74	98.92
0.28	0.07	0.02	0.02	0.05	5.54	98.52
0.55	0.09	0.03	0.02	0.05	8.81	99.38
0.38	0.09	0.06	0.02	0.05	7.72	98.15
0.38	0.09	0.02	0.02	0.05	7.33	98.87
0.43	0.1	0.04	0.03	0.05	8.32	99.51
0.69	0.15	0.07	0.04	0.04	9.7	98.56
0.82	0.17	0.07	0.04	0.03	11.55	98.45
0.77	0.15	0.06	0.04	0.06	11.95	99.16
0.75	0.08	0.05	0.02	0.04	13.9	98.56
0.6	0.08	0.05	0.02	0.05	11.7	98.97
0.59	0.06	0.03	0.02	0.05	10.45	99.78
0.37	0.09	0.04	0.02	0.06	7.33	99.11
0.33	0.06	0.05	0.03	0.06	4.84	98.24
0.42	0.07	0.04	0.02	0.05	7.24	99.04
0.3	0.04	0.04	0.02	0.05	4.72	98.43
0.32	0.07	0.09	0.02	0.05	5.53	98.97
0.5	0.08	0.05	0.02	0.05	8.44	99.23
0.55	0.06	0.03	0.01	0.04	8.19	99.3
0.32	0.08	0.02	0.01	0.05	6.93	98.62
0.5	0.11	0.07	0.02	0.05	9.18	99.42
0.48	0.11	0.06	0.03	0.04	8.5	99.1
0.86	0.15	0.06	0.04	0.05	10.75	99.05
0.53	0.13	0.03	0.04	0.05	10.2	99.07
0.89	0.17	0.09	0.12	0.06	12.65	99.11
0.69	0.06	0.06	0.02	0.03	11.8	99.04
0.41	0.14	0.05	0.02	0.06	9.13	99.09
0.56	0.08	0.04	0.02	0.05	10.05	98.32
0.64	0.08	0.04	0.02	0.05	10.8	98.71
0.61	0.07	0.05	0.02	0.04	11.55	99.61
0.62	0.07	0.06	0.02	0.05	11.55	98.62
0.73	0.09	0.04	0.03	0.05	12.8	99.47
0.43	0.08	0.04	0.02	0.06	5.14	98.77
0.53	0.08	0.03	0.02	0.05	8.85	98.76
0.57	0.07	0.06	0.03	0.06	6.92	98.34
0.35	0.08	0.05	0.02	0.04	6.15	98.34
0.57	0.08	0.04	0.02	0.06	8.64	99.43
0.48	0.05	0.03	0.01	0.04	7.55	99.14
0.42	0.09	0.03	0.01	0.05	8.69	99.48
0.41	0.1	0.02	0.02	0.05	6.72	99.07
0.47	0.11	0.1	0.02	0.06	7.57	99.5
0.53	0.11	0.04	0.02	0.08	7.29	98.32

APPENDIX V

Drill Contract

May 15, 2007

CONTRACT
NEILL'S MINING LTD.

Unit 84 - 2911 Sooke Lake Road
Victoria, BC
V9B 4F4

Phone: (250) 488-1807

Contract contains (2) two pages:

604 944 6102

1/2

To Jamie
from Jo

Between ELECTRA GOLD LTD (The Company)

UNIT 5 - 2330 TYNER ST. PORT COQUITLAM

BC
(Province/State)

V3C 2Z2
(Postal/Zip)

(Country)

And: Neill's Mining Ltd., (The Contractor) to Diamond Drill on the Company's Property.

CONTRACTOR'S AGREEMENT:

- To conduct all work within regulations, with minimum impact on the environment.
- Will supply Diamond Drills, rods, tools, etc., to drill to desired depth.
- Will drill to provide maximum core recovery. Core to be placed in core boxes and marked as to depth.
- Will provide all water pumps, hoses, etc., to deliver water to drill site within a reasonable distance.
- Will provide Compensation and Insurance for contractors crew and equipment.

COMPANY'S AGREEMENT:

- The company agrees to bare the cost of any permits necessary to do the job.
- To bare all costs pertaining to heating of the water, from the source to the drilling sites, if necessary.
- Should weather conditions (deep snow or extreme temperatures) make further drilling impracticable, all footage drilled shall be paid at the rates agreed upon.
- An advance payment of \$ 15,000 shall be made to the Contractor before commencement. This advance will be deducted from the last invoice.
- Final payments to be made to the Contractor 15 days after invoice date.
- This agreement is for a minimum of 1500 feet of core drilling.

RATES:

2/2

- Rate for 7.8 mm Core will be \$ 2.8 per foot.
- Casing will be \$ 2.5 per foot.
- Moving from site to site (which includes: breakdown, move, set-up, waterline) at a rate of \$ 3.0 per man hr.
- Site preparation at a rate of \$ 3.0 per man hr.
- Core boxes to be supplied by CONTRACTOR
- Helicopter costs, if necessary, will be paid by COMPANY.
- All Camp costs will be paid by CONTRACTOR
- A flat rate of \$ 3000 will be charged for Mobilization and demobilization.

ADDITIONAL COSTS TO THE COMPANY:

ROAD BUILDING, STANDBY RATE \$100 HR

[Signature] _____ NOV 23 06
 Signature of Company's Authorized Rep. Date

[Signature] M.Sc., P. Geo. NOV 24 06
 Signature of Contractor's Authorized Rep. Date
President